

ETSI TS 124 501 V15.4.0 (2019-07)



5G;
Non-Access-Stratum (NAS) protocol for 5G System (5GS);
Stage 3
(3GPP TS 24.501 version 15.4.0 Release 15)



ReferenceRTS/TSGC-0124501vF40

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	18
1 Scope	19
2 References	19
3 Definitions and abbreviations.....	21
3.1 Definitions	21
3.2 Abbreviations	25
4 General	27
4.1 Overview	27
4.2 Coordination between the protocols for 5GS mobility management and 5GS session management	27
4.3 UE domain selection	28
4.3.1 UE's usage setting	28
4.3.2 Domain selection for UE originating sessions / calls.....	28
4.3.3 Change of UE's usage setting.....	30
4.3.4 Change or determination of IMS voice availability	30
4.4 NAS security	31
4.4.1 General.....	31
4.4.2 Handling of 5G NAS security contexts.....	31
4.4.2.1 General	31
4.4.2.2 Establishment of a mapped 5G NAS security context during inter-system change from S1 mode to N1 mode in 5GMM-CONNECTED mode.....	33
4.4.2.3 Establishment of a 5G NAS security context during N1 mode to N1 mode handover	34
4.4.2.4 Establishment of an EPS security context during inter-system change from N1 mode to S1 mode in 5GMM-CONNECTED mode	35
4.4.2.5 Establishment of secure exchange of NAS messages	35
4.4.2.6 Change of security keys	37
4.4.3 Handling of NAS COUNT and NAS sequence number	37
4.4.3.1 General	37
4.4.3.2 Replay protection	38
4.4.3.3 Integrity protection and verification.....	38
4.4.3.4 Ciphering and deciphering	38
4.4.3.5 NAS COUNT wrap around	38
4.4.4 Integrity protection of NAS signalling messages.....	39
4.4.4.1 General	39
4.4.4.2 Integrity checking of NAS signalling messages in the UE	39
4.4.4.3 Integrity checking of NAS signalling messages in the AMF	40
4.4.5 Ciphering of NAS signalling messages	42
4.4.6 Protection of initial NAS signalling messages.....	42
4.5 Unified access control	43
4.5.1 General.....	43
4.5.2 Determination of the access identities and access category associated with a request for access.....	45
4.5.3 Operator-defined access categories.....	49
4.5.4 Access control and checking.....	50
4.5.4.1 Access control and checking in 5GMM-IDLE mode.....	50
4.5.4.2 Access control and checking in 5GMM-CONNECTED mode and in 5GMM-CONNECTED mode with RRC inactive indication	51
4.5.5 Exception handling and avoiding double barring	53
4.5.6 Mapping between access categories/access identities and RRC establishment cause	56
4.6 Network slicing	57
4.6.1 General.....	57
4.6.2 Mobility management aspects.....	57
4.6.2.1 General	57

4.6.2.2	NSSAI storage.....	58
4.6.2.3	Provision of NSSAI to lower layers in 5GMM-IDLE mode.....	59
4.6.3	Session management aspects	61
4.7	NAS over non-3GPP access	61
4.7.1	General.....	61
4.7.2	5GS mobility management aspects.....	61
4.7.2.1	General	61
4.7.2.2	Establishment cause for non-3GPP access.....	62
4.7.3	5GS session management aspects.....	62
4.7.4	Limited service state over non-3GPP access	62
4.8	Interworking with E-UTRAN connected to EPC	63
4.8.1	General.....	63
4.8.2	Single-registration mode.....	63
4.8.2.1	General	63
4.8.2.2	Single-registration mode with N26 interface	63
4.8.2.3	Single-registration mode without N26 interface	63
4.8.2.3.1	Interworking between NG-RAN and E-UTRAN	63
4.8.2.3.2	Interworking between N3IWF connected to 5GCN and E-UTRAN	64
4.8.3	Dual-registration mode	65
4.8.4	Core Network selection	66
4.9	Disabling and re-enabling of UE's N1 mode capability	66
4.9.1	General.....	66
4.9.2	Disabling and re-enabling of UE's N1 mode capability for 3GPP access.....	67
4.9.3	Disabling and re-enabling of UE's N1 mode capability for non-3GPP access.....	67
4.10	Interworking with ePDG connected to EPC.....	68
4.11	UE configuration parameter updates	68
5	Elementary procedures for 5GS mobility management	68
5.1	Overview	68
5.1.1	General.....	68
5.1.2	Types of 5GMM procedures.....	68
5.1.3	5GMM sublayer states	70
5.1.3.1	General	70
5.1.3.2	5GMM sublayer states	70
5.1.3.2.1	5GMM sublayer states in the UE.....	70
5.1.3.2.1.1	General.....	70
5.1.3.2.1.2	Main states	70
5.1.3.2.1.2.1	5GMM-NUL	70
5.1.3.2.1.2.2	5GMM-DEREGISTERED.....	70
5.1.3.2.1.2.3	5GMM-REGISTERED-INITIATED	71
5.1.3.2.1.2.4	5GMM-REGISTERED	71
5.1.3.2.1.2.5	5GMM-DEREGISTERED-INITIATED.....	71
5.1.3.2.1.2.6	5GMM-SERVICE-REQUEST-INITIATED.....	71
5.1.3.2.1.3	Substates of state 5GMM-DEREGISTERED.....	71
5.1.3.2.1.3.1	General	71
5.1.3.2.1.3.2	5GMM-DEREGISTERED.NORMAL-SERVICE.....	71
5.1.3.2.1.3.3	5GMM-DEREGISTERED.LIMITED-SERVICE.....	71
5.1.3.2.1.3.4	5GMM-DEREGISTERED.ATTEMPTING-REGISTRATION	71
5.1.3.2.1.3.5	5GMM-DEREGISTERED.PLMN-SEARCH	71
5.1.3.2.1.3.6	5GMM-DEREGISTERED.NO-SUPI	72
5.1.3.2.1.3.7	5GMM-DEREGISTERED.NO-CELL-AVAILABLE.....	72
5.1.3.2.1.3.8	5GMM-DEREGISTERED.eCALL-INACTIVE.....	72
5.1.3.2.1.3.9	5GMM-DEREGISTERED.INITIAL-REGISTRATION-NEEDED	72
5.1.3.2.1.4	Substates of state 5GMM-REGISTERED	72
5.1.3.2.1.4.1	General	72
5.1.3.2.1.4.2	5GMM-REGISTERED.NORMAL-SERVICE	72
5.1.3.2.1.4.3	5GMM-REGISTERED.NON-ALLOWED-SERVICE.....	72
5.1.3.2.1.4.4	5GMM-REGISTERED.ATTEMPTING-REGISTRATION-UPDATE.....	73
5.1.3.2.1.4.5	5GMM-REGISTERED.LIMITED-SERVICE	73
5.1.3.2.1.4.6	5GMM-REGISTERED.PLMN-SEARCH	73
5.1.3.2.1.4.7	5GMM-REGISTERED.NO-CELL-AVAILABLE	73
5.1.3.2.1.4.8	5GMM-REGISTERED.UPDATE-NEEDED	73

5.1.3.2.2	5GS update status in the UE	73
5.1.3.2.3	5GMM sublayer states in the network side	74
5.1.3.2.3.1	General.....	74
5.1.3.2.3.2	5GMM-DEREGISTERED	74
5.1.3.2.3.3	5GMM-COMMON-PROCEDURE-INITIATED.....	74
5.1.3.2.3.4	5GMM-REGISTERED.....	74
5.1.3.2.3.5	5GMM-DEREGISTERED-INITIATED	74
5.1.4	Coordination between 5GMM and EMM.....	75
5.1.4.1	General	75
5.1.4.2	Coordination between 5GMM and EMM with N26 interface	75
5.1.4.3	Coordination between 5GMM and EMM without N26 interface	75
5.2	Behaviour of the UE in state 5GMM-DEREGISTERED and state 5GMM-REGISTERED	76
5.2.1	General.....	76
5.2.2	UE behaviour in state 5GMM-DEREGISTERED	76
5.2.2.1	General.....	76
5.2.2.2	Primary substate selection.....	76
5.2.2.2.1	Selection of the substate after power on.....	76
5.2.2.3	Detailed description of UE behaviour in state 5GMM-DEREGISTERED.....	76
5.2.2.3.1	NORMAL-SERVICE.....	76
5.2.2.3.2	LIMITED-SERVICE.....	77
5.2.2.3.3	ATTEMPTING-REGISTRATION	77
5.2.2.3.4	PLMN-SEARCH.....	77
5.2.2.3.5	NO-SUPI	77
5.2.2.3.6	NO-CELL-AVAILABLE	77
5.2.2.3.7	eCALL-INACTIVE.....	77
5.2.2.4	Substate when back to state 5GMM-DEREGISTERED from another 5GMM state	78
5.2.3	UE behaviour in state 5GMM-REGISTERED	78
5.2.3.1	General	78
5.2.3.2	Detailed description of UE behaviour in state 5GMM-REGISTERED	78
5.2.3.2.1	NORMAL-SERVICE.....	78
5.2.3.2.2	NON-ALLOWED-SERVICE.....	79
5.2.3.2.3	ATTEMPTING-REGISTRATION-UPDATE	79
5.2.3.2.4	LIMITED-SERVICE.....	80
5.2.3.2.5	PLMN-SEARCH.....	80
5.2.3.2.6	NO-CELL-AVAILABLE	80
5.3	General on elementary 5GMM procedures	80
5.3.1	5GMM modes and N1 NAS signalling connection	80
5.3.1.1	Establishment of the N1 NAS signalling connection.....	80
5.3.1.2	Re-establishment of the N1 NAS signalling connection.....	81
5.3.1.3	Release of the N1 NAS signalling connection	82
5.3.1.4	5GMM-CONNECTED mode with RRC inactive indication	85
5.3.2	Permanent identifiers	87
5.3.3	Temporary identities	87
5.3.4	Registration areas.....	88
5.3.5	Service area restrictions	89
5.3.6	Mobile initiated connection only mode	90
5.3.7	Handling of the periodic registration update timer and mobile reachable timer	91
5.3.8	Handling of timer T3502	93
5.3.9	Handling of NAS level mobility management congestion control	93
5.3.10	Handling of DNN based congestion control	94
5.3.11	Handling of S-NSSAI based congestion control.....	94
5.3.12	Handling of local emergency numbers	94
5.3.12A	Handling of local emergency numbers received via 3GPP access and non-3GPP access	95
5.3.12A.1	General	95
5.3.12A.2	Receiving a REGISTRATION ACCEPT message via non-3GPP access.....	96
5.3.13	Lists of 5GS forbidden tracking areas.....	96
5.3.14	List of equivalent PLMNs.....	97
5.3.15	Transmission failure abnormal case in the UE	97
5.4	5GMM common procedures.....	97
5.4.1	Primary authentication and key agreement procedure	97
5.4.1.1	General	97
5.4.1.2	EAP based primary authentication and key agreement procedure	97

5.4.1.2.1	General	97
5.4.1.2.2	EAP-AKA' related procedures.....	100
5.4.1.2.2.1	General.....	100
5.4.1.2.2.2	Initiation.....	100
5.4.1.2.2.3	UE successfully authenticates network.....	100
5.4.1.2.2.4	Errors when handling EAP-request/AKA'-challenge message	101
5.4.1.2.2.5	Network successfully authenticates UE	101
5.4.1.2.2.6	UE handling EAP-AKA' notification message	101
5.4.1.2.2.6A	EAP based Identification initiation by the network	101
5.4.1.2.2.6B	EAP based Identification response by the UE	101
5.4.1.2.2.7	Network sending EAP-success message.....	102
5.4.1.2.2.8	UE handling EAP-success message.....	102
5.4.1.2.2.9	Network not successfully authenticates UE	102
5.4.1.2.2.10	Network sending EAP-failure message	102
5.4.1.2.2.11	UE handling EAP-failure message	103
5.4.1.2.2.12	Abnormal cases in the UE.....	103
5.4.1.2.3	EAP-TLS related procedures.....	103
5.4.1.2.3.1	General.....	103
5.4.1.2.4	EAP message reliable transport procedure	105
5.4.1.2.4.1	General.....	105
5.4.1.2.4.2	EAP message reliable transport procedure initiation by the network	105
5.4.1.2.4.3	EAP message reliable transport procedure accepted by the UE.....	105
5.4.1.2.4.4	Abnormal cases on the network side.....	106
5.4.1.2.4.5	Abnormal cases in the UE.....	106
5.4.1.2.5	EAP result message transport procedure	108
5.4.1.2.5.1	General.....	108
5.4.1.2.5.2	EAP result message transport procedure initiation by the network	108
5.4.1.3	5G AKA based primary authentication and key agreement procedure	109
5.4.1.3.1	General	109
5.4.1.3.2	Authentication initiation by the network	109
5.4.1.3.3	Authentication response by the UE	110
5.4.1.3.4	Authentication completion by the network.....	110
5.4.1.3.5	Authentication not accepted by the network.....	111
5.4.1.3.6	Authentication not accepted by the UE	111
5.4.1.3.7	Abnormal cases	112
5.4.2	Security mode control procedure	116
5.4.2.1	General	116
5.4.2.2	NAS security mode control initiation by the network.....	116
5.4.2.3	NAS security mode command accepted by the UE.....	118
5.4.2.4	NAS security mode control completion by the network	120
5.4.2.5	NAS security mode command not accepted by the UE.....	120
5.4.2.6	Abnormal cases in the UE	121
5.4.2.7	Abnormal cases on the network side.....	121
5.4.3	Identification procedure	121
5.4.3.1	General	121
5.4.3.2	Identification initiation by the network	122
5.4.3.3	Identification response by the UE	122
5.4.3.4	Identification completion by the network	122
5.4.3.5	Abnormal cases in the UE.....	122
5.4.3.6	Abnormal cases on the network side.....	122
5.4.4	Generic UE configuration update procedure.....	123
5.4.4.1	General	123
5.4.4.2	Generic UE configuration update procedure initiated by the network	125
5.4.4.3	Generic UE configuration update accepted by the UE.....	126
5.4.4.4	Generic UE configuration update completion by the network	127
5.4.4.5	Abnormal cases in the UE.....	128
5.4.4.6	Abnormal cases on the network side.....	128
5.4.5	NAS transport procedure(s).....	129
5.4.5.1	General	129
5.4.5.2	UE-initiated NAS transport procedure	130
5.4.5.2.1	General	130
5.4.5.2.2	UE-initiated NAS transport procedure initiation	130

5.4.5.2.3	UE-initiated NAS transport of messages accepted by the network	132
5.4.5.2.4	UE-initiated NAS transport of messages not accepted by the network	135
5.4.5.2.5	Abnormal cases on the network side	135
5.4.5.2.6	Abnormal cases in the UE	138
5.4.5.3	Network-initiated NAS transport procedure	139
5.4.5.3.1	General	139
5.4.5.3.2	Network-initiated NAS transport procedure initiation	139
5.4.5.3.3	Network-initiated NAS transport of messages	142
5.4.6	5GMM status procedure	144
5.4.6.1	General	144
5.4.6.2	5GMM status received in the UE	144
5.4.6.3	5GMM status received in the network	145
5.5	5GMM specific procedures	145
5.5.1	Registration procedure	145
5.5.1.1	General	145
5.5.1.2	Registration procedure for initial registration	146
5.5.1.2.1	General	146
5.5.1.2.2	Initial registration initiation	146
5.5.1.2.3	5GMM common procedure initiation	149
5.5.1.2.4	Initial registration accepted by the network	149
5.5.1.2.5	Initial registration not accepted by the network	155
5.5.1.2.6	Initial registration for emergency services not accepted by the network	158
5.5.1.2.6A	Initial registration for initiating a PDU session for emergency services not accepted by the network	158
5.5.1.2.7	Abnormal cases in the UE	159
5.5.1.2.8	Abnormal cases on the network side	161
5.5.1.3	Registration procedure for mobility and periodic registration update	162
5.5.1.3.1	General	162
5.5.1.3.2	Mobility and periodic registration update initiation	162
5.5.1.3.3	5GMM common procedure initiation	167
5.5.1.3.4	Mobility and periodic registration update accepted by the network	168
5.5.1.3.5	Mobility and periodic registration update not accepted by the network	177
5.5.1.3.6	Mobility and periodic registration update for initiating an emergency PDU session not accepted by the network	180
5.5.1.3.7	Abnormal cases in the UE	180
5.5.1.3.8	Abnormal cases on the network side	183
5.5.2	De-registration procedure	184
5.5.2.1	General	184
5.5.2.2	UE-initiated de-registration procedure	185
5.5.2.2.1	UE-initiated de-registration procedure initiation	185
5.5.2.2.2	UE-initiated de-registration procedure completion	186
5.5.2.2.3	UE-initiated de-registration procedure completion for 5GS services over 3GPP access	186
5.5.2.2.4	UE-initiated de-registration procedure completion for 5GS services non-3GPP access	187
5.5.2.2.5	UE-initiated de-registration procedure completion for 5GS services over both 3GPP access and non-3GPP access	187
5.5.2.2.6	Abnormal cases in the UE	187
5.5.2.2.7	Abnormal cases in the network side	189
5.5.2.3	Network-initiated de-registration procedure	189
5.5.2.3.1	Network-initiated de-registration procedure initiation	189
5.5.2.3.2	Network-initiated de-registration procedure completion by the UE	189
5.5.2.3.3	Network-initiated de-registration procedure completion by the network	192
5.5.2.3.4	Abnormal cases in the UE	192
5.5.2.3.5	Abnormal cases in the network side	193
5.5.3	eCall inactivity procedure	193
5.6	5GMM connection management procedures	194
5.6.1	Service request procedure	194
5.6.1.1	General	194
5.6.1.2	Service request procedure initiation	196
5.6.1.3	Common procedure initiation	198
5.6.1.4	Service request procedure accepted by the network	198
5.6.1.5	Service request procedure not accepted by the network	200
5.6.1.6	Service request procedure for initiating an emergency PDU session not accepted by the network	203

5.6.1.7	Abnormal cases in the UE	204
5.6.1.8	Abnormal cases on the network side	206
5.6.2	Paging procedure	207
5.6.2.1	General	207
5.6.2.2	Paging for 5GS services	207
5.6.2.2.1	General	207
5.6.2.2.2	Abnormal cases on the network side	208
5.6.2.2.3	Abnormal cases in the UE	208
5.6.3	Notification procedure	208
5.6.3.1	General	208
5.6.3.2	Notification procedure initiation	208
5.6.3.3	Notification procedure completion.....	209
5.6.3.4	Abnormal cases on the network side	210
5.6.3.5	Abnormal cases on the UE side.....	210
6	Elementary procedures for 5GS session management	210
6.1	Overview	210
6.1.1	General.....	210
6.1.2	Types of 5GSM procedures	211
6.1.3	5GSM sublayer states	211
6.1.3.1	General	211
6.1.3.2	5GSM sublayer states in the UE	211
6.1.3.2.1	Overview	211
6.1.3.2.2	PDU SESSION INACTIVE	212
6.1.3.2.3	PDU SESSION ACTIVE PENDING	212
6.1.3.2.4	PDU SESSION ACTIVE	212
6.1.3.2.5	PDU SESSION INACTIVE PENDING.....	212
6.1.3.2.6	PDU SESSION MODIFICATION PENDING	212
6.1.3.2.7	PROCEDURE TRANSACTION INACTIVE.....	212
6.1.3.2.8	PROCEDURE TRANSACTION PENDING.....	212
6.1.3.3	5GSM sublayer states in the network side	213
6.1.3.3.1	Overview	213
6.1.3.3.2	PDU SESSION INACTIVE	213
6.1.3.3.3	PDU SESSION ACTIVE	213
6.1.3.3.4	PDU SESSION INACTIVE PENDING.....	213
6.1.3.3.5	PDU SESSION MODIFICATION PENDING	214
6.1.3.3.6	PROCEDURE TRANSACTION INACTIVE.....	214
6.1.3.3.7	PROCEDURE TRANSACTION PENDING.....	214
6.1.4	Coordination between 5GSM and ESM.....	214
6.1.4.1	Coordination between 5GSM and ESM with N26 interface	214
6.1.4.2	Coordination between 5GSM and ESM without N26 interface	221
6.2	General on elementary 5GSM procedures.....	223
6.2.1	Principles of PTI handling for 5GSM procedures.....	223
6.2.2	PDU session types	225
6.2.3	PDU session management	225
6.2.4	IP address allocation	225
6.2.4.1	General	225
6.2.4.2	IP address allocation via NAS signalling	226
6.2.5	Quality of service.....	227
6.2.5.1	General	227
6.2.5.1.1	QoS rules	227
6.2.5.1.1.1	General.....	227
6.2.5.1.1.2	Signalled QoS rules	227
6.2.5.1.1.3	Derived QoS rules.....	228
6.2.5.1.1.4	QoS flow descriptions.....	228
6.2.5.1.2	Session-AMBR.....	229
6.2.5.1.3	UL user data packet matching	229
6.2.5.1.4	Reflective QoS.....	229
6.2.5.1.4.1	General.....	229
6.2.5.1.4.2	Derivation of packet filter for UL direction from DL user data packet	229
6.2.5.1.4.3	Creating a derived QoS rule by reflective QoS in the UE.....	231
6.2.5.1.4.4	Updating a derived QoS rule by reflective QoS in the UE	232

6.2.5.1.4.5	Deleting a derived QoS rule in the UE	232
6.2.5.1.4.6	Ignoring RQI in the UE.....	232
6.2.6	Local area data network (LADN)	232
6.2.7	Handling of DNN based congestion control	233
6.2.8	Handling of S-NSSAI based congestion control.....	233
6.2.9	Interaction with upper layers	234
6.2.9.1	General	234
6.2.9.2	URSP.....	234
6.2.10	Handling of 3GPP PS data off	235
6.2.11	Multi-homed IPv6 PDU session	236
6.3	Network-requested 5GSM procedures	236
6.3.1	PDU session authentication and authorization procedure	236
6.3.1.1	General	236
6.3.1.2	PDU EAP message reliable transport procedure.....	238
6.3.1.2.1	PDU EAP message reliable transport procedure initiation.....	238
6.3.1.2.2	PDU EAP message reliable transport procedure accepted by the UE	239
6.3.1.2.3	Abnormal cases on the network side	239
6.3.1.2.4	Abnormal cases in the UE	239
6.3.1.3	PDU EAP result message transport procedure	239
6.3.1.3.1	PDU EAP result message transport procedure initiation	239
6.3.2	Network-requested PDU session modification procedure	240
6.3.2.1	General	240
6.3.2.2	Network-requested PDU session modification procedure initiation	240
6.3.2.3	Network-requested PDU session modification procedure accepted by the UE.....	242
6.3.2.4	Network-requested PDU session modification procedure not accepted by the UE.....	247
6.3.2.5	Abnormal cases on the network side	250
6.3.2.6	Abnormal cases in the UE	250
6.3.3	Network-requested PDU session release procedure	251
6.3.3.1	General	251
6.3.3.2	Network-requested PDU session release procedure initiation	251
6.3.3.3	Network-requested PDU session release procedure accepted by the UE	252
6.3.3.4	N1 SM delivery skipped.....	258
6.3.3.5	Abnormal cases on the network side	258
6.3.3.6	Abnormal cases in the UE	258
6.4	UE-requested 5GSM procedures.....	258
6.4.1	UE-requested PDU session establishment procedure	258
6.4.1.1	General	258
6.4.1.2	UE-requested PDU session establishment procedure initiation	259
6.4.1.3	UE-requested PDU session establishment procedure accepted by the network	262
6.4.1.4	UE requested PDU session establishment procedure not accepted by the network	269
6.4.1.5	Handling the maximum number of established PDU sessions.....	277
6.4.1.6	Abnormal cases in the UE	278
6.4.1.7	Abnormal cases on the network side	278
6.4.2	UE-requested PDU session modification procedure.....	279
6.4.2.1	General	279
6.4.2.2	UE-requested PDU session modification procedure initiation.....	280
6.4.2.3	UE-requested PDU session modification procedure accepted by the network	282
6.4.2.4	UE-requested PDU session modification procedure not accepted by the network	282
6.4.2.5	Abnormal cases in the UE	289
6.4.2.6	Abnormal cases on the network side	289
6.4.3	UE-requested PDU session release procedure	290
6.4.3.1	General	290
6.4.3.2	UE-requested PDU session release procedure initiation	290
6.4.3.3	UE-requested PDU session release procedure accepted by the network.....	291
6.4.3.4	UE-requested PDU session release procedure not accepted by the network.....	291
6.4.3.5	Abnormal cases in the UE	291
6.4.3.6	Abnormal cases on the network side	292
6.5	5GSM status procedure	292
6.5.1	General.....	292
6.5.2	5GSM status received in the UE	293
6.5.3	5GSM status received in the SMF	293
6.6	Miscellaneous procedures	293

6.6.1	Exchange of extended protocol configuration options.....	293
7	Handling of unknown, unforeseen, and erroneous protocol data	294
7.1	General	294
7.2	Message too short or too long	294
7.2.1	Message too short	294
7.2.2	Message too long	294
7.3	Unknown or unforeseen procedure transaction identity or PDU Session identity.....	294
7.3.1	Procedure transaction identity.....	294
7.3.2	PDU Session identity.....	295
7.4	Unknown or unforeseen message type	295
7.5	Non-semantic mandatory information element errors	296
7.5.1	Common procedures	296
7.5.2	5GS mobility management	296
7.5.3	5GS session management	296
7.6	Unknown and unforeseen IEs in the non-imperative message part.....	297
7.6.1	IEs unknown in the message	297
7.6.2	Out of sequence IEs	297
7.6.3	Repeated IEs	297
7.7	Non-imperative message part errors.....	297
7.7.1	Syntactically incorrect optional IEs	298
7.7.2	Conditional IE errors	298
7.8	Messages with semantically incorrect contents.....	298
8	Message functional definitions and contents.....	298
8.1	Overview	298
8.2	5GS mobility management messages.....	298
8.2.1	Authentication request	298
8.2.1.1	Message definition	298
8.2.1.2	Authentication parameter RAND	299
8.2.1.3	Authentication parameter AUTN	299
8.2.1.4	Void.....	299
8.2.1.5	EAP message.....	299
8.2.2	Authentication response.....	299
8.2.2.1	Message definition	299
8.2.2.2	Authentication response parameter	300
8.2.2.3	EAP message.....	300
8.2.3	Authentication result.....	300
8.2.3.1	Message definition	300
8.2.3.2	ABBA	300
8.2.4	Authentication failure	301
8.2.4.1	Message definition	301
8.2.4.2	Authentication failure parameter.....	301
8.2.5	Authentication reject.....	301
8.2.5.1	Message definition	301
8.2.5.2	EAP message.....	302
8.2.6	Registration request	302
8.2.6.1	Message definition	302
8.2.6.2	Non-current native NAS key set identifier.....	304
8.2.6.3	5GMM capability.....	304
8.2.6.4	UE security capability.....	304
8.2.6.5	Requested NSSAI	304
8.2.6.6	Last visited registered TAI.....	304
8.2.6.7	S1 UE network capability	304
8.2.6.8	Uplink data status.....	304
8.2.6.9	PDU session status	304
8.2.6.10	MICO indication	304
8.2.6.11	UE status	304
8.2.6.12	Additional GUTI.....	304
8.2.6.13	Allowed PDU session status	305
8.2.6.14	UE's usage setting	305
8.2.6.15	Requested DRX parameters	305

8.2.6.16	EPS NAS message container.....	305
8.2.6.17	LADN indication.....	305
8.2.6.17A	Payload container type	305
8.2.6.18	Payload container.....	305
8.2.6.19	Network slicing indication	305
8.2.6.20	5GS update type	305
8.2.6.21	NAS message container	305
8.2.6.22	EPS bearer context status	306
8.2.7	Registration accept.....	306
8.2.7.1	Message definition	306
8.2.7.2	5G-GUTI.....	309
8.2.7.3	Equivalent PLMNs.....	309
8.2.7.4	TAI list	309
8.2.7.5	Allowed NSSAI	309
8.2.7.6	Rejected NSSAI	309
8.2.7.7	Configured NSSAI.....	309
8.2.7.8	5GS network feature support.....	309
8.2.7.9	PDU session status	309
8.2.7.10	PDU session reactivation result.....	309
8.2.7.11	PDU session reactivation result error cause	309
8.2.7.12	LADN information.....	310
8.2.7.13	MICO indication	310
8.2.7.14	Network slicing indication	310
8.2.7.15	Service area list	310
8.2.7.16	T3512 value.....	310
8.2.7.17	Non-3GPP de-registration timer value	310
8.2.7.18	T3502 value.....	310
8.2.7.19	Emergency number list	310
8.2.7.20	Extended emergency number list	310
8.2.7.21	SOR transparent container	310
8.2.7.22	EAP message.....	310
8.2.7.23	NSSAI inclusion mode	311
8.2.7.24	Operator-defined access category definitions	311
8.2.7.25	Negotiated DRX parameters	311
8.2.7.26	Non-3GPP NW provided policies	311
8.2.7.27	EPS bearer context status	311
8.2.8	Registration complete	311
8.2.8.1	Message definition	311
8.2.8.2	SOR transparent container	311
8.2.9	Registration reject.....	312
8.2.9.1	Message definition	312
8.2.9.2	T3346 value.....	312
8.2.9.3	T3502 value.....	312
8.2.9.4	EAP message.....	312
8.2.10	UL NAS transport.....	312
8.2.10.1	Message definition	312
8.2.10.2	PDU session ID	313
8.2.10.3	Old PDU session ID	313
8.2.10.4	Request type	313
8.2.10.5	S-NSSAI	313
8.2.10.6	DNN.....	313
8.2.10.7	Additional information.....	313
8.2.11	DL NAS transport.....	314
8.2.11.1	Message definition	314
8.2.11.2	PDU session ID	314
8.2.11.3	Additional information.....	314
8.2.11.4	5GMM cause.....	314
8.2.11.5	Back-off timer value	314
8.2.12	De-registration request (UE originating de-registration)	315
8.2.12.1	Message definition	315
8.2.13	De-registration accept (UE originating de-registration).....	315
8.2.13.1	Message definition	315

8.2.14	De-registration request (UE terminated de-registration).....	315
8.2.14.1	Message definition	315
8.2.14.2	5GMM cause.....	316
8.2.14.3	T3346 value.....	316
8.2.15	De-registration accept (UE terminated de-registration)	316
8.2.15.1	Message definition	316
8.2.16	Service request.....	317
8.2.16.1	Message definition	317
8.2.16.2	Uplink data status.....	317
8.2.16.3	PDU session status	317
8.2.16.4	Allowed PDU session status	317
8.2.16.5	NAS message container	317
8.2.17	Service accept	318
8.2.17.1	Message definition	318
8.2.17.2	PDU session status	318
8.2.17.3	PDU session reactivation result.....	318
8.2.17.4	PDU session reactivation result error cause	318
8.2.17.5	EAP message.....	318
8.2.18	Service reject	319
8.2.18.1	Message definition	319
8.2.18.2	PDU session status	319
8.2.18.3	T3346 value.....	319
8.2.18.4	EAP message.....	319
8.2.19	Configuration update command.....	319
8.2.19.1	Message definition	319
8.2.19.2	Configuration update indication.....	320
8.2.19.3	5G-GUTI.....	320
8.2.19.4	TAI list	320
8.2.19.5	Allowed NSSAI	320
8.2.19.6	Service area list	321
8.2.19.7	Full name for network.....	321
8.2.19.8	Short name for network.....	321
8.2.19.9	Local time zone	321
8.2.19.10	Universal time and local time zone	321
8.2.19.11	Network daylight saving time	321
8.2.19.12	LADN information.....	321
8.2.19.13	MICO indication	321
8.2.19.14	Network slicing indication.....	321
8.2.19.15	Configured NSSAI.....	321
8.2.19.16	Rejected NSSAI	321
8.2.19.17	Operator-defined access category definitions	321
8.2.19.18	SMS indication.....	321
8.2.20	Configuration update complete.....	322
8.2.20.1	Message definition	322
8.2.21	Identity request	322
8.2.21.1	Message definition	322
8.2.22	Identity response.....	322
8.2.22.1	Message definition	322
8.2.23	Notification	323
8.2.23.1	Message definition	323
8.2.24	Notification response	323
8.2.24.1	Message definition	323
8.2.24.2	PDU session status	324
8.2.25	Security mode command	324
8.2.25.1	Message definition	324
8.2.25.2	IMEISV request	325
8.2.25.3	Void.....	325
8.2.25.4	Selected EPS NAS security algorithms.....	325
8.2.25.5	Additional 5G security information	325
8.2.25.6	EAP message.....	325
8.2.25.7	ABBA	325
8.2.25.8	Replayed S1 UE security capabilities	326