



LTE;
**Evolved Universal Terrestrial Radio Access (E-UTRA);
Physical channels and modulation
(3GPP TS 36.211 version 14.11.0 Release 14)**

iTeh 3GPP Standard PREVIEW
Full Standard
<https://standards.iteh.ai/catalog/3gpp/standards/etsi-ts-136-211-v14.11.0-2019-07-411c-9023-3b9d99a0591a/etsi-ts-136-211-v14.11.0-2019-07>



Reference

RTS/TSGR-0136211veb0

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and LTE™ are trademarks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and
of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal notice

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal notice	2
Modal verbs terminology.....	2
Foreword.....	8
1 Scope	9
2 References	9
3 Symbols and abbreviations.....	9
3.1 Symbols.....	9
3.2 Abbreviations	13
4 Frame structure.....	14
4.1 Frame structure type 1	14
4.2 Frame structure type 2.....	15
4.3 Frame structure type 3	16
5 Uplink.....	18
5.1 Overview	18
5.1.1 Physical channels.....	18
5.1.2 Physical signals.....	18
5.2 Slot structure and physical resources.....	18
5.2.1 Resource grid	18
5.2.2 Resource elements	20
5.2.3 Resource blocks	20
5.2.4 Narrowbands and widebands	20
5.2.5 Guard period for narrowband and wideband retuning.....	21
5.3 Physical uplink shared channel.....	23
5.3.1 Scrambling.....	23
5.3.2 Modulation.....	24
5.3.2A Layer mapping	25
5.3.2A.1 Layer mapping for transmission on a single antenna port.....	25
5.3.2A.2 Layer mapping for spatial multiplexing	25
5.3.3 Transform precoding.....	26
5.3.3A Precoding	26
5.3.3A.1 Precoding for transmission on a single antenna port.....	26
5.3.3A.2 Precoding for spatial multiplexing	26
5.3.4 Mapping to physical resources.....	29
5.4 Physical uplink control channel.....	32
5.4.1 PUCCH formats 1, 1a and 1b	33
5.4.2 PUCCH formats 2, 2a and 2b	36
5.4.2A PUCCH format 3	37
5.4.2B PUCCH format 4	39
5.4.2C PUCCH format 5	39
5.4.3 Mapping to physical resources.....	40
5.5 Reference signals.....	43
5.5.1 Generation of the reference signal sequence.....	43
5.5.1.1 Base sequences of length $3N_{sc}^{RB}$ or larger	43
5.5.1.2 Base sequences of length less than $3N_{sc}^{RB}$	44
5.5.1.3 Group hopping	47
5.5.1.4 Sequence hopping	48
5.5.1.5 Determining virtual cell identity for sequence generation	48
5.5.2 Demodulation reference signal	49
5.5.2.1 Demodulation reference signal for PUSCH	49
5.5.2.1.1 Reference signal sequence.....	49
5.5.2.1.2 Mapping to physical resources	52
5.5.2.2 Demodulation reference signal for PUCCH.....	52

5.5.2.2.1	Reference signal sequence.....	52
5.5.2.2.2	Mapping to physical resources	54
5.5.3	Sounding reference signal.....	55
5.5.3.1	Sequence generation.....	55
5.5.3.2	Mapping to physical resources.....	55
5.5.3.3	Sounding reference signal subframe configuration.....	58
5.6	SC-FDMA baseband signal generation	59
5.7	Physical random access channel.....	60
5.7.1	Time and frequency structure	60
5.7.2	Preamble sequence generation.....	67
5.7.3	Baseband signal generation.....	72
5.8	Modulation and upconversion	73
6	Downlink	74
6.1	Overview	74
6.1.1	Physical channels.....	74
6.1.2	Physical signals.....	74
6.2	Slot structure and physical resource elements	75
6.2.1	Resource grid	75
6.2.2	Resource elements	76
6.2.3	Resource blocks	77
6.2.3.1	Virtual resource blocks of localized type	77
6.2.3.2	Virtual resource blocks of distributed type	77
6.2.4	Resource-element groups.....	79
6.2.4A	Enhanced Resource-Element Groups (EREGs).....	79
6.2.5	Guard period for half-duplex FDD operation	80
6.2.6	Guard Period for TDD Operation	80
6.2.7	Narrowbands and widebands	80
6.2.8	Guard period for narrowband and wideband retuning	81
6.3	General structure for downlink physical channels.....	81
6.3.1	Scrambling	82
6.3.2	Modulation.....	83
6.3.3	Layer mapping	83
6.3.3.1	Layer mapping for transmission on a single antenna port.....	83
6.3.3.2	Layer mapping for spatial multiplexing.....	83
6.3.3.3	Layer mapping for transmit diversity.....	86
6.3.4	Precoding	86
6.3.4.1	Precoding for transmission on a single antenna port.....	86
6.3.4.2	Precoding for spatial multiplexing using antenna ports with cell-specific reference signals	86
6.3.4.2.1	Precoding without CDD	86
6.3.4.2.2	Precoding for large delay CDD	87
6.3.4.2.3	Codebook for precoding and CSI reporting.....	88
6.3.4.3	Precoding for transmit diversity	89
6.3.4.4	Precoding for spatial multiplexing using antenna ports with UE-specific reference signals.....	90
6.3.5	Mapping to resource elements	91
6.4	Physical downlink shared channel.....	91
6.4.1	Physical downlink shared channel for BL/CE UEs	93
6.5	Physical multicast channel	95
6.6	Physical broadcast channel.....	95
6.6.1	Scrambling	96
6.6.2	Modulation.....	96
6.6.3	Layer mapping and precoding	96
6.6.4	Mapping to resource elements	96
6.7	Physical control format indicator channel	97
6.7.1	Scrambling	98
6.7.2	Modulation.....	98
6.7.3	Layer mapping and precoding	98
6.7.4	Mapping to resource elements	98
6.8	Physical downlink control channel.....	99
6.8.1	PDCCH formats	99
6.8.2	PDCCH multiplexing and scrambling	99
6.8.3	Modulation.....	100

6.8.4	Layer mapping and precoding	100
6.8.5	Mapping to resource elements	100
6.8A	Enhanced physical downlink control channel	101
6.8A.1	EPDCCH formats	101
6.8A.2	Scrambling	103
6.8A.3	Modulation	103
6.8A.4	Layer mapping and precoding	103
6.8A.5	Mapping to resource elements	103
6.8B	MTC physical downlink control channel	104
6.8B.1	MPDCCH formats	104
6.8B.2	Scrambling	105
6.8B.3	Modulation	106
6.8B.4	Layer mapping and precoding	106
6.8B.5	Mapping to resource elements	106
6.9	Physical hybrid ARQ indicator channel	108
6.9.1	Modulation	109
6.9.2	Resource group alignment, layer mapping and precoding	110
6.9.3	Mapping to resource elements	111
6.10	Reference signals	113
6.10.1	Cell-specific Reference Signal (CRS)	113
6.10.1.1	Sequence generation	114
6.10.1.2	Mapping to resource elements	114
6.10.2	MBSFN reference signals	116
6.10.2.1	Sequence generation	116
6.10.2.1.1	Sequence generation for 15 kHz and 7.5 kHz subcarrier spacing	116
6.10.2.1.2	Sequence generation for 1.25 kHz subcarrier spacing	116
6.10.2.2	Mapping to resource elements	117
6.10.2.2.1	Mapping to resource elements for 15 kHz and 7.5 kHz subcarrier spacing	117
6.10.2.2.2	Mapping to resource elements for 1.25 kHz	118
6.10.3	UE-specific reference signals associated with PDSCH	118
6.10.3.1	Sequence generation	119
6.10.3.2	Mapping to resource elements	120
6.10.3A	Demodulation reference signals associated with EPDCCH or MPDCCH	125
6.10.3A.1	Sequence generation	125
6.10.3A.2	Mapping to resource elements	126
6.10.4	Positioning reference signals	127
6.10.4.1	Sequence generation	128
6.10.4.2	Mapping to resource elements	128
6.10.4.3	Positioning reference signal subframe configuration	130
6.10.5	CSI reference signals	131
6.10.5.1	Sequence generation	132
6.10.5.2	Mapping to resource elements	132
6.10.5.3	CSI reference signal subframe configuration	140
6.11	Synchronization signals	140
6.11.1	Primary synchronization signal (PSS)	140
6.11.1.1	Sequence generation	140
6.11.1.2	Mapping to resource elements	141
6.11.2	Secondary synchronization signal (SSS)	142
6.11.2.1	Sequence generation	142
6.11.2.2	Mapping to resource elements	143
6.11A	Discovery signal	144
6.12	OFDM baseband signal generation	145
6.13	Modulation and upconversion	145
7	Generic functions	147
7.1	Modulation mapper	147
7.1.1	BPSK	147
7.1.2	QPSK	147
7.1.3	16QAM	147
7.1.4	64QAM	148
7.1.5	256QAM	150
7.2	Pseudo-random sequence generation	153

8	Timing	153
8.1	Uplink-downlink frame timing.....	153
9	Sidelink.....	154
9.1	Overview	154
9.1.1	Physical channels.....	154
9.1.2	Physical signals.....	154
9.1.3	Handling of simultaneous sidelink and uplink/downlink transmissions	154
9.2	Slot structure and physical resources.....	155
9.2.1	Resource grid.....	155
9.2.2	Resource elements	155
9.2.3	Resource blocks	156
9.2.4	Resource pool	156
9.2.5	Guard period.....	156
9.3	Physical Sidelink Shared Channel.....	156
9.3.1	Scrambling.....	156
9.3.2	Modulation.....	157
9.3.3	Layer mapping.....	157
9.3.4	Transform precoding.....	157
9.3.5	Precoding	157
9.3.6	Mapping to physical resources.....	157
9.4	Physical Sidelink Control Channel.....	158
9.4.1	Scrambling.....	158
9.4.2	Modulation.....	158
9.4.3	Layer mapping.....	158
9.4.4	Transform precoding.....	158
9.4.5	Precoding	158
9.4.6	Mapping to physical resources.....	158
9.5	Physical Sidelink Discovery Channel.....	159
9.5.1	Scrambling.....	159
9.5.2	Modulation.....	159
9.5.3	Layer mapping.....	159
9.5.4	Transform precoding.....	159
9.5.5	Precoding	159
9.5.6	Mapping to physical resources.....	159
9.6	Physical Sidelink Broadcast Channel.....	159
9.6.1	Scrambling.....	159
9.6.2	Modulation.....	159
9.6.3	Layer mapping.....	160
9.6.4	Transform precoding.....	160
9.6.5	Precoding	160
9.6.6	Mapping to physical resources.....	160
9.7	Sidelink Synchronization Signals.....	160
9.7.1	Primary sidelink synchronization signal	160
9.7.1.1	Sequence generation.....	160
9.7.1.2	Mapping to resource elements.....	160
9.7.2	Secondary sidelink synchronization signal	161
9.7.2.1	Sequence generation.....	161
9.7.2.2	Mapping to resource elements.....	161
9.8	Demodulation reference signals	161
9.9	SC-FDMA baseband signal generation	163
9.10	Timing	163
10	Narrowband IoT	164
10.1	Uplink.....	164
10.1.1	Overview	164
10.1.1.1	Physical channels	164
10.1.1.2	Physical signals	164
10.1.2	Slot structure and physical resources	164
10.1.2.1	Resource grid	164
10.1.2.2	Resource elements.....	165
10.1.2.3	Resource unit.....	165

10.1.3	Narrowband physical uplink shared channel	166
10.1.3.1	Scrambling	166
10.1.3.2	Modulation	166
10.1.3.3	Layer mapping	166
10.1.3.4	Transform precoding	166
10.1.3.5	Precoding	166
10.1.3.6	Mapping to physical resources	166
10.1.4	Demodulation reference signal	167
10.1.4.1	Reference signal sequence	167
10.1.4.1.1	Reference signal sequence for $N_{sc}^{RU} = 1$	167
10.1.4.1.2	Reference signal sequence for $N_{sc}^{RU} > 1$	168
10.1.4.1.3	Group hopping	169
10.1.4.2	Mapping to physical resources	170
10.1.5	SC-FDMA baseband signal generation	170
10.1.6	Narrowband physical random access channel	171
10.1.6.1	Time and frequency structure	171
10.1.6.2	Baseband signal generation	173
10.1.7	Modulation and upconversion	173
10.2	Downlink	173
10.2.1	Overview	173
10.2.1.1	Physical channels	173
10.2.1.2	Physical signals	174
10.2.2	Slot structure and physical resource elements	174
10.2.2.1	Resource grid	174
10.2.2.2	Resource elements	174
10.2.2.3	Guard period for half-duplex FDD operation	174
10.2.3	Narrowband physical downlink shared channel	174
10.2.3.1	Scrambling	174
10.2.3.2	Modulation	174
10.2.3.3	Layer mapping and precoding	175
10.2.3.4	Mapping to resource elements	175
10.2.4	Narrowband physical broadcast channel	176
10.2.4.1	Scrambling	176
10.2.4.2	Modulation	176
10.2.4.3	Layer mapping and precoding	176
10.2.4.4	Mapping to resource elements	176
10.2.5	Narrowband physical downlink control channel	177
10.2.5.1	NPDCCH formats	177
10.2.5.2	Scrambling	177
10.2.5.3	Modulation	177
10.2.5.4	Layer mapping and precoding	177
10.2.5.5	Mapping to resource elements	177
10.2.6	Narrowband reference signal (NRS)	178
10.2.6.1	Sequence generation	180
10.2.6.2	Mapping to resource elements	180
10.2.6A	Narrowband positioning reference signal (NPRS)	181
10.2.6A.1	Sequence generation	181
10.2.6A.2	Mapping to resource elements	182
10.2.6A.3	NPRS subframe configuration	183
10.2.7	Synchronization signals	184
10.2.7.1	Narrowband primary synchronization signal (NPSS)	184
10.2.7.1.1	Sequence generation	184
10.2.7.1.2	Mapping to resource elements	184
10.2.7.2	Narrowband secondary synchronization signal (NSSS)	184
10.2.7.2.1	Sequence generation	184
10.2.7.2.2	Mapping to resource elements	185
10.2.8	OFDM baseband signal generation	186
10.2.9	Modulation and upconversion	186
Annex A (informative):	Change history	187
History	197	

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

iTeh STANDARD PREVIEW
(Standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/ea79de28-a204-411c-9023-3b9d99a0591a/etsi-ts-1.36-211-v14.11.0-2019-07>

1 Scope

The present document describes the physical channels for evolved UTRA.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 36.201: "Evolved Universal Terrestrial Radio Access (E-UTRA); LTE physical layer; General description".
- [3] 3GPP TS 36.212: "Evolved Universal Terrestrial Radio Access (E-UTRA); Multiplexing and channel coding".
- [4] 3GPP TS 36.213: "Evolved Universal Terrestrial Radio Access (E-UTRA); Physical layer procedures".
- [5] 3GPP TS 36.214: "Evolved Universal Terrestrial Radio Access (E-UTRA); Physical layer; Measurements".
- [6] 3GPP TS 36.104: "Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) radio transmission and reception".
- [7] 3GPP TS 36.101: "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) radio transmission and reception".
- [8] 3GPP TS 36.321, "Evolved Universal Terrestrial Radio Access (E-UTRA); Medium Access Control (MAC) protocol specification".
- [9] 3GPP TS 36.331, "Evolved Universal Terrestrial Radio Access (E-UTRA); Radio Resource Control (RRC) Protocol specification"
- [10] 3GPP TS 36.304, "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) procedures in idle mode"

3 Symbols and abbreviations

3.1 Symbols

For the purposes of the present document, the following symbols apply:

- | | |
|-----------------|--|
| (k, l) | Resource element with frequency-domain index k and time-domain index l |
| $a_{k,l}^{(p)}$ | Value of resource element (k, l) [for antenna port p] |
| D | Matrix for supporting cyclic delay diversity |

D_{RA}	Density of random access opportunities per radio frame
f_0	Carrier frequency
f_{RA}	PRACH resource frequency index within the considered time-domain location
$f_{\text{PRACH,hop}}$	PRACH frequency hopping offset, expressed as a number of resource blocks
$l_{\text{NPDCCHStart}}$	Start symbol in slot 0 for NPDCCH
$l_{\text{NPDSCHStart}}$	Start symbol in slot 0 for NPDSCH
$M_{\text{sc}}^{\text{PSBCH}}$	Bandwidth for PSBCH transmission, expressed as a number of subcarriers
$M_{\text{RB}}^{\text{PSBCH}}$	Bandwidth for PSBCH transmission, expressed as a number of resource blocks
$M_{\text{sc}}^{\text{PSCCH}}$	Bandwidth for PSCCH transmission, expressed as a number of subcarriers
$M_{\text{RB}}^{\text{PSCCH}}$	Bandwidth for PSCCH transmission, expressed as a number of resource blocks
$M_{\text{sc}}^{\text{PSDCH}}$	Bandwidth for PSDCH transmission, expressed as a number of subcarriers
$M_{\text{RB}}^{\text{PSDCH}}$	Bandwidth for PSDCH transmission, expressed as a number of resource blocks
$M_{\text{sc}}^{\text{PSSCH}}$	Scheduled bandwidth for PSSCH transmission, expressed as a number of subcarriers
$M_{\text{RB}}^{\text{PSSCH}}$	Scheduled bandwidth for PSSCH transmission, expressed as a number of resource blocks
$M_{\text{sc}}^{\text{PUSCH}}$	Scheduled bandwidth for uplink transmission, expressed as a number of subcarriers
$M_{\text{RB}}^{\text{PUSCH}}$	Scheduled bandwidth for uplink transmission, expressed as a number of resource blocks
$M_{\text{rep}}^{\text{NPUSCH}}$	Scheduled number of repetitions of a NPUSCH transmission
$M_{\text{rep}}^{\text{NPDSCH}}$	Scheduled number of repetitions of a NPDSCH transmission
$M_{\text{sc}}^{\text{NPUSCH}}$	Scheduled bandwidth for uplink NPUSCH transmission, expressed as a number of subcarriers
$M_{\text{identical}}^{\text{NPUSCH}}$	Number of repetitions of identical slots for NPUSCH
$M_{\text{bit}}^{(q)}$	Number of coded bits to transmit on a physical channel [for codeword q]
$M_{\text{symb}}^{(q)}$	Number of modulation symbols to transmit on a physical channel [for codeword q]
$M_{\text{symb}}^{\text{layer}}$	Number of modulation symbols to transmit per layer for a physical channel
$M_{\text{symb}}^{\text{ap}}$	Number of modulation symbols to transmit per antenna port for a physical channel
N	A constant equal to 2048 for $\Delta f = 15 \text{ kHz}$, 4096 for $\Delta f = 7.5 \text{ kHz}$ and 8192 for $\Delta f = 3.75 \text{ kHz}$
$N_{\text{CP},l}$	Downlink cyclic prefix length for OFDM symbol l in a slot
N_{CS}	Cyclic shift value used for random access preamble generation
$N_{\text{cs}}^{(1)}$	Number of cyclic shifts used for PUCCH formats 1/1a/1b in a resource block with a mix of formats 1/1a/1b and 2/2a/2b
$N_{\text{RB}}^{(2)}$	Bandwidth available for use by PUCCH formats 2/2a/2b, expressed in multiples of $N_{\text{sc}}^{\text{RB}}$
$N_{\text{RB}}^{\text{HO}}$	The offset used for PUSCH frequency hopping, expressed in number of resource blocks (set by higher layers)
$N_{\text{ID}}^{\text{cell}}$	Physical layer cell identity
$N_{\text{ID}}^{\text{Ncell}}$	Narrowband physical layer cell identity
$N_{\text{ID}}^{\text{MBSFN}}$	MBSFN area identity
$N_{\text{ID}}^{\text{SL}}$	Physical layer sidelink synchronization identity
$N_{\text{ID}}^{\text{PRS}}$	Positioning reference signal identity
$N_{\text{RB}}^{\text{DL}}$	Downlink bandwidth configuration, expressed in multiples of $N_{\text{sc}}^{\text{RB}}$
$N_{\text{RB}}^{\text{min, DL}}$	Smallest downlink bandwidth configuration, expressed in multiples of $N_{\text{sc}}^{\text{RB}}$
$N_{\text{RB}}^{\text{max, DL}}$	Largest downlink bandwidth configuration, expressed in multiples of $N_{\text{sc}}^{\text{RB}}$
$N_{\text{RB}}^{\text{UL}}$	Uplink bandwidth configuration, expressed in multiples of $N_{\text{sc}}^{\text{RB}}$
$N_{\text{RB}}^{\text{min, UL}}$	Smallest uplink bandwidth configuration, expressed in multiples of $N_{\text{sc}}^{\text{RB}}$

$N_{\text{RB}}^{\max, \text{UL}}$	Largest uplink bandwidth configuration, expressed in multiples of $N_{\text{sc}}^{\text{RB}}$
$N_{\text{RB}}^{\text{SL}}$	Sidelink bandwidth configuration, expressed in multiples of $N_{\text{sc}}^{\text{RB}}$
N_{SF}	Number of scheduled subframes for NPDSCH transmission
$N_{\text{symb}}^{\text{NPSS}}$	Number of symbols for NPSS in a subframe
$N_{\text{symb}}^{\text{NSSS}}$	Number of symbols for NSSS in a subframe
$N_{\text{sc}}^{\text{RU}}$	Number of consecutive subcarriers in an UL resource unit for NB-IoT
$N_{\text{seq}}^{\text{RU}}$	Number of reference signal sequences available for the UL resource unit size
N_{RU}	Number of scheduled UL resource units for NB-IoT
$N_{\text{NB}}^{\text{UL}}$	Total number of uplink narrowbands
$N_{\text{WB}}^{\text{UL}}$	Total number of uplink widebands
$N_{\text{sc}}^{\text{UL}}$	Number of subcarriers in the frequency domain for NB-IoT
N_{acc}	Number of consecutive absolute subframes over which the scrambling sequence stays the same
$N_{\text{abs}}^{\text{PUSCH}}$	Total number of absolute subframes a PUSCH with repetition spans , expressed as a number of absolute subframes
$N_{\text{rep}}^{\text{PUSCH}}$	Number of repetitions of a PUSCH transmission
$N_{\text{NB}}^{\text{sh,UL}}$	Number of consecutive absolute subframes over which PUCCH or PUSCH stays at the same narrowband before hopping to another narrowband, expressed as a number of absolute subframes
$f_{\text{NB,hop}}^{\text{PUSCH}}$	Narrowband offset between one narrowband and the next narrowband a PUSCH hops to, expressed as a number of uplink narrowbands
$N_{\text{abs}}^{\text{PUCCH}}$	Total number of absolute subframes a PUCCH with repetition spans, expressed as a number of absolute subframes
$N_{\text{rep}}^{\text{PUCCH}}$	Number of repetitions of a PUCCH transmission
$N_{\text{rep}}^{\text{PRACH}}$	Number of PRACH repetitions per preamble transmission attempt
$N_{\text{sf}}^{\text{RA}}$	Number of subframes allowed for preamble transmission within a 1024-frame interval
$N_{\text{start}}^{\text{PRACH}}$	PRACH starting subframe periodicity
$N_{\text{rep}}^{\text{NPRACH}}$	Number of NPRACH repetitions per preamble transmission attempt
$N_{\text{period}}^{\text{NPRACH}}$	NPRACH resource periodicity
$N_{\text{scffset}}^{\text{NPRACH}}$	Frequency location of the first sub-carrier allocated to NPRACH
$N_{\text{sc}}^{\text{NPRACH}}$	Number of sub-carriers allocated to NPRACH
$N_{\text{sc_cont}}^{\text{NPRACH}}$	Number of starting sub-carriers allocated for UE initiated random access
$N_{\text{start}}^{\text{NPRACH}}$	NPRACH starting subframe
$N_{\text{MSG3}}^{\text{NPRACH}}$	Fraction for starting subcarrier index for UE support for multi-tone msg3 transmission
$N_{\text{gap,period}}$	Periodicity for NPDSCH/NPDCCH gaps
$N_{\text{gap,duration}}$	Duration for NPDSCH/NPDCCH gaps
$N_{\text{gap,threshold}}$	Threshold for applying NPDDCH/NPDCCH gaps
$N_{\text{NB}}^{\text{DL}}$	Total number of downlink narrowbands
$N_{\text{WB}}^{\text{DL}}$	Total number of downlink widebands
$N_{\text{abs}}^{\text{PDSCH}}$	Total number of absolute subframes a PDSCH with repetition spans, expressed as a number of absolute subframes
$N_{\text{rep}}^{\text{PDSCH}}$	Number of repetitions of a PDSCH transmission
$N_{\text{NB}}^{\text{sh,DL}}$	Number of consecutive absolute subframes over which MPDCCH or PDSCH stays at the same narrowband before hopping to another narrowband, expressed as a number of absolute subframes

$N_{\text{NB,hop}}^{\text{ch,DL}}$	Number of narrowbands over which MPDCCH or PDSCH frequency hops
$f_{\text{NB,hop}}^{\text{DL}}$	Narrowband offset between one narrowband and the next narrowband an MPDCCH or PDSCH hops to, expressed as a number of downlink narrowbands
$N_{\text{PDSCH}}^{\text{SIB1-BR}}$	Number of times a PDSCH carrying SIB1-BR is transmitted over 8 radio frames
$N_{\text{abs}}^{\text{MPDCCH}}$	Total number of absolute subframes a MPDCCH with repetition spans , expressed as a number of absolute subframes
$N_{\text{rep}}^{\text{MPDCCH}}$	Number of repetitions of a MPDCCH transmission
$N_{\text{abs,ss}}^{\text{MPDCCH}}$	Total number of absolute subframes a MPDCCH search space with maximum repetition level spans, expressed as a number of absolute subframes
$N_{\text{rep,ss}}^{\text{MPDCCH}}$	Maximum repetition level of a MPDCCH search space
$N_{\text{ECCE}}^{\text{MPDCCH}}$	Number of ECCEs in a subframe for one MPDCCH
$N_{\text{symb}}^{\text{DL}}$	Number of OFDM symbols in a downlink slot
$N_{\text{symb}}^{\text{UL}}$	Number of SC-FDMA symbols in an uplink slot
$N_{\text{symb}}^{\text{retune}}$	Number of symbols in a guard period for narrowband or wideband retuning
$N_{\text{slots}}^{\text{UL}}$	Number of consecutive slots in an UL resource unit for NB-IoT
$N_{\text{symb}}^{\text{SL}}$	Number of SC-FDMA symbols in a sidelink slot
$N_{\text{sc}}^{\text{RB}}$	Resource block size in the frequency domain, expressed as a number of subcarriers
N_{sb}	Number of sub-bands for PUSCH frequency-hopping with predefined hopping pattern
$N_{\text{RB}}^{\text{sb}}$	Size of each sub-band for PUSCH frequency-hopping with predefined hopping pattern, expressed as a number of resource blocks
$N_{\text{sc}}^{\text{RA}}$	Size of narrow-band random-access resource in number of subcarriers
N_{SP}	Number of downlink to uplink switch points within the radio frame
$N_{\text{RS}}^{\text{PUCCH}}$	Number of reference symbols per slot for PUCCH
N_{TA}	Timing offset between uplink and downlink radio frames at the UE, expressed in units of T_s
$N_{\text{TA offset}}$	Fixed timing advance offset, expressed in units of T_s
$N_{\text{TA,SL}}$	Timing offset between sidelink and timing reference frames at the UE, expressed in units of T_s
$n_{\text{PUCCH}}^{(1,\tilde{p})}$	Resource index for PUCCH formats 1/1a/1b
$n_{\text{PUCCH}}^{(2,\tilde{p})}$	Resource index for PUCCH formats 2/2a/2b
$n_{\text{PUCCH}}^{(3,\tilde{p})}$	Resource index for PUCCH formats 3
n_{PDCCH}	Number of PDCCHs present in a subframe
n_{PRB}	Physical resource block number
$n_{\text{PRB}}^{\text{RA}}$	First physical resource block occupied by PRACH resource considered
$n_{\text{PRB offset}}^{\text{RA}}$	First physical resource block available for PRACH
$n_{\text{SC}}^{\text{RA}}$	Subcarrier occupied by NPRACH resource considered
n_{VRB}	Virtual resource block number
n_{RNTI}	Radio network temporary identifier
$n_{\text{ID}}^{\text{SA}}$	Sidelink group destination identity
n_f	System frame number
n_s	Slot number within a radio frame
$n_{\text{sf}}^{\text{abs}}$	Absolute subframe number
$n_{\text{sf}}^{\text{RA}}$	Index for subframes allowed for preamble transmission
P	Number of antenna ports used for transmission of a channel
p	Antenna port number