



**Smart Cards;
UICC-Terminal interface;
Physical and logical characteristics
(Release 14)**

*iTeh STANDARD PREVIEW
(see https://standards.iteh.ai/catalog/standards/sls/1244bb9eb-b71c-40c3-a747-ed2f9c3f194b/etsi-ts-102-221-v14-2-0-2019-07)*

ReferenceRTS/SCP-T102221ve20

Keywordssmart card

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	12
Foreword.....	12
Modal verbs terminology.....	12
Introduction	13
1 Scope	14
2 References	14
2.1 Normative references	14
2.2 Informative references.....	16
3 Definition of terms, symbols, abbreviations and coding conventions.....	16
3.1 Terms.....	16
3.2 Symbols.....	18
3.3 Abbreviations	19
3.4 Coding conventions	21
4 Physical characteristics.....	21
4.0 UICC Form Factors	21
4.0.0 Generic requirements.....	21
4.0.1 ID-1 UICC	21
4.0.2 Plug-in UICC.....	21
4.0.3 Mini-UICC.....	22
4.0.4 4FF.....	23
4.1 ID-1 UICC.....	24
4.2 Plug-in UICC.....	24
4.3 Mini-UICC	24
4.4 Environmental conditions for card operation and storage.....	24
4.4.0 Standard UICC environmental conditions.....	24
4.4.1 Specific UICC environmental conditions	24
4.4.1.0 Specific UICC environmental conditions indication.....	24
4.4.1.1 Temperature range for specific UICC environmental conditions.....	25
4.4.1.2 High humidity	25
4.5 Contacts.....	25
4.5.1 Provision of contacts.....	25
4.5.1.1 Terminal.....	25
4.5.1.2 UICC.....	25
4.5.2 Contact activation and deactivation	26
4.5.2.1 Contacts assigned by the present document	26
4.5.2.2 Optional contacts.....	26
4.5.3 Inactive contacts	26
4.5.4 Contact pressure.....	26
5 Electrical specifications of the UICC - Terminal interface	26
5.0 General requirements	26
5.1 Class A operating conditions.....	27
5.1.1 Supply voltage Vcc (contact C1)	27
5.1.2 Reset (RST) (contact C2).....	27
5.1.3 Programming voltage Vpp (contact C6)	28
5.1.4 Clock CLK (contact C3).....	28
5.1.5 I/O (contact C7)	28
5.2 Class B operating conditions	29
5.2.1 Supply voltage Vcc (contact C1)	29
5.2.2 Reset (RST) (contact C2).....	29
5.2.3 Clock CLK (contact C3).....	29
5.2.4 I/O (contact C7)	30
5.3 Class C operating conditions	30
5.3.1 Supply voltage Vcc (contact C1)	30

5.3.2	Reset (RST) (contact C2).....	31
5.3.3	Clock CLK (contact C3).....	31
5.3.4	I/O (contact C7).....	31
6	Initial communication establishment procedures.....	32
6.1	UICC activation and deactivation.....	32
6.2	Supply voltage switching.....	32
6.2.0	UICC activation voltage.....	32
6.2.1	Supply voltage classes.....	32
6.2.2	Power consumption of the UICC during ATR.....	32
6.2.3	Application related electrical parameters.....	33
6.3	Answer To Reset content.....	33
6.3.0	Introduction.....	33
6.3.1	Coding of historical bytes.....	34
6.3.2	Speed enhancement.....	34
6.3.3	Global Interface bytes.....	34
6.4	PPS procedure.....	35
6.5	Reset procedures.....	35
6.5.1	Cold reset.....	35
6.5.2	Warm reset.....	35
6.5.3	Reaction to resets.....	36
6.6	Clock stop mode.....	36
6.7	Bit/character duration and sampling time.....	36
6.8	Error handling.....	36
6.9	Compatibility.....	37
7	Transmission protocols.....	37
7.0	Introduction.....	37
7.1	Physical layer.....	38
7.2	Data link layer.....	38
7.2.0	Introduction.....	38
7.2.1	Character frame.....	38
7.2.1.0	Structure, coding and timing.....	38
7.2.1.1	Low impedance I/O line behaviour.....	39
7.2.2	Transmission protocol T = 0.....	39
7.2.2.0	Introduction.....	39
7.2.2.1	Timing and specific options for characters in T = 0.....	39
7.2.2.2	Command header.....	40
7.2.2.3	Command processing.....	40
7.2.2.3.0	General description.....	40
7.2.2.3.1	Procedure bytes.....	40
7.2.2.3.2	Status bytes.....	40
7.2.2.4	Error detection and correction.....	41
7.2.3	Transmission protocol T = 1.....	41
7.2.3.0	Introduction.....	41
7.2.3.1	Timing and specific options for blocks sent with T = 1.....	41
7.2.3.1.0	Introduction.....	41
7.2.3.1.1	Information field size.....	41
7.2.3.1.2	Character waiting integer.....	41
7.2.3.1.3	Character waiting time.....	41
7.2.3.1.4	Block waiting time.....	42
7.2.3.1.5	Block guard time.....	42
7.2.3.1.6	Waiting time extension.....	42
7.2.3.1.7	Error detection code.....	42
7.2.3.2	Block frame structure.....	42
7.2.3.2.0	Overall structure.....	42
7.2.3.2.1	Prologue field.....	43
7.2.3.2.2	Epilogue field.....	44
7.2.3.2.3	Block notations.....	45
7.2.3.3	Error free operation.....	45
7.2.3.4	Error handling for T = 1.....	46
7.2.3.4.0	General description.....	46

7.2.3.4.1	Protocol initialization	46
7.2.3.4.2	Block dependent errors.....	46
7.2.3.5	Chaining.....	47
7.2.3.5.0	Chaining Mechanism.....	47
7.2.3.5.1	Rules for chaining.....	47
7.3	Transport layer	47
7.3.0	Introduction.....	47
7.3.1	Transportation of an APDU using T = 0.....	47
7.3.1.0	Introduction.....	47
7.3.1.1	Mapping of APDUs to TPDUs.....	48
7.3.1.1.0	General behaviour	48
7.3.1.1.1	Case 1	48
7.3.1.1.2	Case 2	49
7.3.1.1.3	Case 3	49
7.3.1.1.4	Case 4	50
7.3.1.1.5	Use of procedure bytes '61xx' and '6Cxx'	51
7.3.2	Transportation of a APDU using T = 1.....	52
7.3.2.0	General mechanism.....	52
7.3.2.1	Case 1.....	52
7.3.2.2	Case 2.....	52
7.3.2.3	Case 3.....	53
7.3.2.4	Case 4.....	53
7.4	Application layer	53
7.4.0	Overall description.....	53
7.4.1	Exchange of APDUs.....	54
7.4.2	CAT layer	54
7.4.2.0	Overview.....	54
7.4.2.1	Proactive command.....	54
7.4.2.2	ENVELOPE Commands.....	55
7.4.3	Application execution.....	55
8	Application and file structure	56
8.1	UICC application structure.....	56
8.2	File types	56
8.2.0	Introduction.....	56
8.2.1	Dedicated files	57
8.2.2	Elementary files	57
8.2.2.1	Transparent EF.....	57
8.2.2.2	Linear fixed EF	57
8.2.2.3	Cyclic EF	57
8.2.2.4	BER-TLV structure EF	58
8.3	File referencing	58
8.4	Methods for selecting a file	58
8.4.0	Default state after UICC activation and ATR.....	58
8.4.1	SELECT by File Identifier referencing.....	59
8.4.2	SELECT by path referencing.....	60
8.4.3	Short File Identifier (SFI)	61
8.5	Application characteristics	61
8.5.0	Application selection types.....	61
8.5.1	Explicit application selection.....	61
8.5.1.1	SELECT by DF name	61
8.5.1.2	SELECT by partial DF name	62
8.5.2	Application session activation	62
8.5.3	Application session termination.....	62
8.5.4	Application session reset	63
8.5.5	Void.....	63
8.6	Reservation of file Ids	63
8.7	Logical channels.....	64
8.8	Shareable versus not-shareable files.....	65
8.9	Secure channels	65
9	Security features.....	66

9.0	Introduction	66
9.1	Supported security features	66
9.2	Security architecture.....	66
9.2.0	Overview and basic rules	66
9.2.1	Security attributes	67
9.2.2	Access mode	67
9.2.3	Security condition.....	67
9.2.4	Access rules	67
9.2.5	Compact format	68
9.2.6	Expanded format.....	68
9.2.7	Access rule referencing.....	68
9.3	Security environment	69
9.3.0	Description.....	69
9.3.1	Definition of the security environment	70
9.3.2	Logical Channels and Security Environment.....	70
9.4	PIN definitions	71
9.4.0	Introduction.....	71
9.4.1	Universal PIN	71
9.4.2	Application PIN	71
9.4.3	Local PIN.....	71
9.4.4	PINs and logical channels.....	71
9.5	PIN and key reference relationship	72
9.5.0	Introduction.....	72
9.5.1	Access condition mapping	72
9.5.2	PIN status indication.....	73
10	Structure of commands and responses	74
10.1	Command APDU	74
10.1.0	Structure and case	74
10.1.1	Coding of Class Byte	75
10.1.2	Coding of Instruction Byte	76
10.1.3	Coding of parameter bytes	77
10.1.4	Coding of Lc byte	77
10.1.5	Coding of data part	77
10.1.6	Coding of Le byte	77
10.2	Response APDU.....	77
10.2.0	Structure.....	77
10.2.1	Status conditions returned by the UICC	77
10.2.1.0	Introduction.....	77
10.2.1.1	Normal processing	78
10.2.1.2	Postponed processing	78
10.2.1.3	Warnings	78
10.2.1.4	Execution errors	78
10.2.1.5	Checking errors	79
10.2.1.5.0	Base checking errors.....	79
10.2.1.5.1	Functions in CLA not supported	79
10.2.1.5.2	Command not allowed.....	79
10.2.1.5.3	Wrong parameters	79
10.2.1.6	Application errors	80
10.2.2	Status words of the commands	81
10.3	Logical channels.....	83
11	Commands.....	83
11.1	Generic commands	83
11.1.0	Introduction.....	83
11.1.1	SELECT.....	83
11.1.1.1	Functional description.....	83
11.1.1.2	Command parameters and data	83
11.1.1.3	Response Data.....	84
11.1.1.3.0	Base coding	84
11.1.1.3.1	Response for MF, DF or ADF	85
11.1.1.3.2	Response for an EF.....	85

11.1.1.4	File control parameters.....	85
11.1.1.4.1	File size.....	85
11.1.1.4.2	Total file size	86
11.1.1.4.3	File Descriptor.....	86
11.1.1.4.4	File identifier	87
11.1.1.4.5	DF name	87
11.1.1.4.6	Proprietary information	87
11.1.1.4.7	Security attributes.....	91
11.1.1.4.8	Short file identifier	93
11.1.1.4.9	Life cycle status integer.....	93
11.1.1.4.10	PIN status template DO	93
11.1.2	STATUS	94
11.1.2.1	Functional description.....	94
11.1.2.2	Command parameters.....	94
11.1.3	READ BINARY	95
11.1.3.1	Functional description.....	95
11.1.3.2	Command parameters.....	95
11.1.4	UPDATE BINARY	95
11.1.4.1	Functional parameters	95
11.1.4.2	Command parameters and data	96
11.1.5	READ RECORD	96
11.1.5.1	Functional description.....	96
11.1.5.2	Command parameters.....	97
11.1.6	UPDATE RECORD	97
11.1.6.1	Functional description.....	97
11.1.6.2	Command parameters and data	98
11.1.7	SEARCH RECORD	98
11.1.7.1	Functional description.....	98
11.1.7.2	Command parameters and data	99
11.1.8	INCREASE.....	100
11.1.8.1	Functional description.....	100
11.1.8.2	Command parameters and data	100
11.1.9	VERIFY PIN	101
11.1.9.1	Functional description.....	101
11.1.9.1.1	PIN verification	101
11.1.9.1.2	PIN retry counter	101
11.1.9.2	Void.....	102
11.1.9.3	Command parameters.....	102
11.1.10	CHANGE PIN	102
11.1.10.1	Functional description.....	102
11.1.10.2	Command parameters.....	103
11.1.11	DISABLE PIN	103
11.1.11.1	Functional description.....	103
11.1.11.2	Command parameters.....	104
11.1.12	ENABLE PIN	104
11.1.12.1	Functional description.....	104
11.1.12.2	Command parameters.....	105
11.1.13	UNBLOCK PIN.....	105
11.1.13.1	Functional description.....	105
11.1.13.1.1	PIN unblocking.....	105
11.1.13.1.2	UNBLOCK PIN retry counter	106
11.1.13.2	Void.....	106
11.1.13.3	Command parameters.....	106
11.1.14	DEACTIVATE FILE.....	106
11.1.14.1	Functional description.....	106
11.1.14.2	Command parameters.....	107
11.1.15	ACTIVATE FILE.....	107
11.1.15.1	Functional description.....	107
11.1.15.2	Command parameters.....	107
11.1.16	AUTHENTICATE.....	108
11.1.16.1	Functional description.....	108
11.1.16.2	Command parameters and data	109

11.1.17	MANAGE CHANNEL.....	111
11.1.17.1	Functional description.....	111
11.1.17.2	Command parameters and data	111
11.1.18	GET CHALLENGE.....	112
11.1.18.1	Functional description.....	112
11.1.18.2	Command parameters and data	112
11.1.19	TERMINAL CAPABILITY	112
11.1.19.1	Functional description.....	112
11.1.19.2	Command parameters and data	113
11.1.19.2.0	Base coding	113
11.1.19.2.1	Terminal power supply.....	113
11.1.19.2.2	Extended logical channels terminal support.....	113
11.1.19.2.3	Additional interfaces support.....	114
11.1.19.2.4	Additional Terminal capability indications related to eUICC	114
11.1.20	MANAGE SECURE CHANNEL.....	115
11.1.20.1	General functional description	115
11.1.20.2	Retrieve UICC Endpoints	116
11.1.20.2.0	Introduction	116
11.1.20.2.1	Functional description	116
11.1.20.2.2	Command parameters and data.....	116
11.1.20.3	Establish SA - Master SA	118
11.1.20.3.0	Introduction	118
11.1.20.3.1	Functional description	118
11.1.20.3.2	Command parameters and data.....	118
11.1.20.4	Establish SA - Connection SA	120
11.1.20.4.0	Introduction	120
11.1.20.4.1	Functional description	120
11.1.20.4.2	Command parameters and data.....	120
11.1.20.5	Establish SA - Start Secure Channel	122
11.1.20.5.0	Introduction	122
11.1.20.5.1	Functional description	122
11.1.20.5.2	Command parameters and data.....	122
11.1.20.6	Terminate Secure Channel SA	124
11.1.20.6.0	Introduction	124
11.1.20.6.1	Functional description	124
11.1.20.6.2	Command parameters and data.....	124
11.1.21	TRANSACT DATA	125
11.1.21.1	General functional description.....	125
11.1.21.2	Command parameters and data	126
11.1.22	SUSPEND UICC	128
11.1.22.1	Functional description.....	128
11.1.22.2	UICC suspension.....	129
11.1.22.2.1	Introduction	129
11.1.22.2.2	Functional description	129
11.1.22.2.3	Command parameters and data.....	129
11.1.22.3	UICC resume.....	130
11.1.22.3.1	Introduction	130
11.1.22.3.2	Functional description	130
11.1.22.3.3	Command parameters and data.....	131
11.2	CAT commands.....	131
11.2.1	TERMINAL PROFILE.....	131
11.2.1.1	Functional description.....	131
11.2.1.2	Command parameters and data	131
11.2.2	ENVELOPE.....	131
11.2.2.1	Functional description.....	131
11.2.2.2	Command parameters and data	132
11.2.3	FETCH.....	132
11.2.3.1	Functional description.....	132
11.2.3.2	Command parameters and data	132
11.2.4	TERMINAL RESPONSE.....	132
11.2.4.1	Functional description.....	132
11.2.4.2	Command parameters and data	133

11.3	Data Oriented commands	133
11.3.0	Overview and generic mechanism	133
11.3.1	RETRIEVE DATA	134
11.3.1.1	Functional description	134
11.3.1.2	Command parameters and data	135
11.3.2	SET DATA	136
11.3.2.1	Functional description	136
11.3.2.2	Command parameters and data	137
12	Transmission oriented commands	137
12.1	T = 0 specific commands	137
12.1.1	GET RESPONSE	137
12.1.1.1	Functional description	137
12.1.1.2	Command parameters	138
13	Application independent files	138
13.1	EF _{DIR}	138
13.2	EF _{ICCID} (ICC Identification)	139
13.3	EF _{PL} (Preferred Languages)	140
13.4	EF _{ARR} (Access Rule Reference)	140
13.5	DF _{CD} (Configuration Data)	141
13.5.0	Introduction	141
13.5.1	EF _{LAUNCH PAD}	141
13.5.2	EF _{ICON}	144
13.6	EF _{UMPC} (UICC Maximum Power Consumption)	145
14	Application independent protocol	146
14.1	File related procedures	146
14.1.1	Reading an EF	146
14.1.2	Updating an EF	146
14.1.3	Increasing an EF	146
14.2	PIN related procedures	147
14.2.0	Overview	147
14.2.1	PIN verification	147
14.2.2	PIN value substitution	147
14.2.3	PIN disabling	148
14.2.4	PIN enabling	148
14.2.5	PIN unblocking	148
14.3	Application selection procedures	148
14.3.1	Application selection by use of the EF _{DIR} file	148
14.3.2	Direct application selection	149
14.3.3	Direct application selection with partial AID	149
14.4	General application related procedures	149
14.4.1	Application session activation	149
14.4.2	UICC application interrogation	149
14.4.3	UICC application session termination	149
14.5	Miscellaneous procedures	149
14.5.1	UICC activation	149
14.5.2	UICC presence detection	149
14.5.3	UICC preferred language request	150
14.5.4	UICC logical channels	150
14.5.5	Power negotiation	150
14.5.6	UICC suspension	150
14.6	CAT related procedures	150
14.6.0	Scope of CAT related procedures	150
14.6.1	CAT Initialization procedure	150
14.6.2	Proactive polling	151
14.6.3	Support of commands	151
14.6.4	Support of response codes	151
14.6.5	Independence of applications and CAT tasks	151
14.6.6	Use of BUSY status response	151
14.6.7	Additional processing time	151

15	Support of APDU-based UICC applications over USB	151
Annex A (normative):	UCS2 coding of Alpha fields for files residing on the UICC	153
Annex B (informative):	Main states of a UICC	155
Annex C (informative):	APDU protocol transmission examples.....	156
C.1	Exchanges Using T = 0	156
C.1.0	Overview	156
C.1.1	Case 1 command	156
C.1.2	Case 2 command	156
C.1.3	Case 3 command	157
C.1.4	Case 4 command	157
C.1.5	Case 2 commands Using the '61' and '6C' procedure bytes	157
C.1.6	Case 4 command Using the '61' procedure byte	158
C.1.7	Case 4 command with warning condition	158
Annex D (informative):	ATR examples	159
Annex E (informative):	Security attributes mechanisms and examples.....	161
E.1	Coding	161
E.2	Compact format	161
E.2.0	Coding	161
E.2.1	AM byte	161
E.2.2	SC byte	161
E.2.3	Examples	162
E.3	Expanded format	162
E.3.0	Coding	162
E.3.1	AM_DO	162
E.3.2	SC_DO	162
E.3.3	Access rule referencing	163
E.3.4	Examples	163
Annex F (informative):	Example of contents of EF_{ARR} '2F06'	164
F.1	Sample content of the EF _{ARR}	164
Annex G (informative):	Access Rules Referencing (ARR).....	165
G.1	Sample content of EF _{ARR}	165
G.2	Example of access rule referencing with SE ID	168
Annex H (normative):	List of SFI Values assigned in ETSI TS 102 221	169
H.1	List of SFI Values at the MF Level	169
Annex I (informative):	Resets and modes of operation	170
Annex J (informative):	Example of the use of PINs	171
J.1	Application having several ADFs	171
J.2	Two applications with two different security contexts.....	171
Annex K (informative):	Examples of the PIN state transition on multi verification capable UICC	172
K.0	Context	172
K.1	PIN state transition on the single logical channel	172
K.2	PIN state transition between logical channels	174

Annex L (informative):	Examples of SET DATA and RETRIEVE DATA usage.....	178
L.1	Examples of SET DATA and RETRIEVE DATA usage	178
L.2	Examples of RETRIEVE DATA usage with transport protocol T = 0	179
Annex M (informative):	Examples of ODD AUTHENTICATE instruction code usage	182
M.1	Examples of ODD AUTHENTICATE instruction code usage at applicative level.....	182
M.2	Examples of ODD AUTHENTICATE instruction code usage with transport protocol T = 0.....	183
Annex N (informative):	Change history	186
History		192

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/1a4bb9eb-b71c-40c3-a747-ed2f9c3f194b/etsi-ts-102-221-v14.2.0-2019-07>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Smart Card Platform (SCP).

It is based on work originally done in the 3GPP in TSG-terminals WG3.

The contents of the present document are subject to continuing work within TC SCP and may change following formal TC SCP approval. If TC SCP modifies the contents of the present document, it will then be republished by ETSI with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 0 early working draft;
 - 1 presented to TC SCP for information;
 - 2 presented to TC SCP for approval;
 - 3 or greater indicates TC SCP approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document defines a generic Terminal/Integrated Circuit Card (ICC) interface.

The aim of the present document is to ensure interoperability between an ICC and a terminal independently of the respective manufacturer, card issuer or operator. The present document does not define any aspects related to the administrative management phase of the ICC. Any internal technical realization of either the ICC or the terminal is only specified where these are reflected over the interface.

Application specific details for applications residing on an ICC are specified in the respective application specific documents. The Universal Subscriber Identity Module (USIM)-application for 3G telecommunication networks is specified in ETSI TS 131 102 [2].

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/1a4bb9eb-b71c-40c3-a747-ed2f9c3f194b/etsi-ts-102-221-v14.2.0-2019-07>