

ETSI TS 136 306 V14.11.0 (2019-07)



LTE;
Evolved Universal Terrestrial Radio Access (E-UTRA);
User Equipment (UE) radio access capabilities
(3GPP TS 36.306 version 14.11.0 Release 14)

Standard PREVIEW
Full standard available at: <https://standards.iteh.ai/catalog/standards/si/9310bf5-79bd-4c85-b9b0-316cb2b45c7b/etsi-ts-136-306-v14-11-0-2019-07>



ReferenceRTS/TSGR-0236306veb0

KeywordsLTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	12
1 Scope	13
2 References	13
3 Definitions, symbols and abbreviations	14
3.1 Definitions	14
3.2 Symbols.....	15
3.3 Abbreviations	15
4 UE radio access capability parameters.....	16
4.1 <i>ue-Category</i>	17
4.1A <i>ue-CategoryDL</i> and <i>ue-CategoryUL</i>	20
4.1B <i>ue-CategorySL-C</i> and <i>ue-CategorySL-D</i>	36
4.1C <i>ue-Category-NB</i>	37
4.2 Parameters set by the field <i>ue-Category</i> and <i>ue-CategoryDL / ue-CategoryUL</i>	38
4.2.1 Transport channel parameters in downlink.....	38
4.2.1.1 Maximum number of DL-SCH transport block bits received within a TTI	38
4.2.1.2 Maximum number of bits of a DL-SCH transport block received within a TTI.....	38
4.2.1.3 Total number of DL-SCH soft channel bits	38
4.2.1.4 Maximum number of bits of a MCH transport block received within a TTI	38
4.2.2 Transport channel parameters in uplink.....	38
4.2.2.1 Maximum number of bits of an UL-SCH transport block transmitted within a TTI.....	38
4.2.2.2 Maximum number of UL-SCH transport block bits transmitted within a TTI.....	38
4.2.3 Physical channel parameters in downlink (DL).....	39
4.2.3.1 Maximum number of supported layers for spatial multiplexing in DL.....	39
4.2.4 Physical channel parameters in uplink (UL).....	39
4.2.4.1 Support for 64QAM in UL.....	39
4.2.5 Total layer 2 buffer size	39
4.2.6 Half-duplex FDD operation type.....	39
4.2.7 RF parameters	39
4.2.7.1 Maximum UE channel bandwidth.....	39
4.2A Parameters set by <i>ue-CategorySL-C / ue-CategorySL-D</i>	39
4.2A.1 Transport channel parameters in sidelink (SL)	39
4.2A.1.1 Maximum number of SL-SCH transport block bits received within a TTI.....	39
4.2A.1.2 Maximum number of bits of a SL-SCH transport block received within a TTI.....	39
4.2A.1.3 Maximum number of SL-DCH transport block bits received within a TTI.....	39
4.2A.1.4 Maximum number of bits of a SL-DCH transport block received within a TTI.....	40
4.2A.1.5 Maximum number of bits of a SL-SCH transport block transmitted within a TTI	40
4.2A.1.6 Maximum number of SL-SCH transport block bits transmitted within a TTI	40
4.2A.1.7 Maximum number of bits of a SL-DCH transport block transmitted within a TTI.....	40
4.2A.1.8 Maximum number of SL-DCH transport block bits transmitted within a TTI.....	40
4.2A.2 Physical channel parameters in sidelink (SL)	40
4.2A.2.1 Maximum number of supported layers for spatial multiplexing in SL-C	40
4.2A.2.2 Maximum number of supported layers for spatial multiplexing in SL-D	40
4.3 Parameters independent of the field <i>ue-Category</i> and <i>ue-CategoryDL / ue-CategoryUL</i>	40
4.3.1 PDCP Parameters.....	40
4.3.1.1 <i>supportedROHC-Profiles</i>	40
4.3.1.1A <i>supportedROHC-Profiles-r13</i>	41
4.3.1.2 <i>maxNumberROHC-ContextSessions</i>	41
4.3.1.2A <i>maxNumberROHC-ContextSessions-r13</i>	41
4.3.1.3 <i>pdcp-SN-Extension</i>	41
4.3.1.4 <i>supportRohcContextContinue</i>	41
4.3.1.5 <i>pdcp-SN-Extension-18bits-r13</i>	42

4.3.1.6	<i>supportedUplinkOnlyROHC-Profiles</i>	42
4.3.2	RLC parameters	42
4.3.2.1	Void.....	42
4.3.2.2	<i>extended-RLC-LI-Field-r12</i>	42
4.3.2.3	<i>extendedRLC-SN-SO-Field-r13</i>	42
4.3.2.4	<i>extendedPollByte-r14</i>	42
4.3.3	Void	42
4.3.4	Physical layer parameters	42
4.3.4.1	<i>ue-TxAntennaSelectionSupported</i>	42
4.3.4.2	<i>ue-SpecificRefSigsSupported</i>	42
4.3.4.3	Void.....	42
4.3.4.4	<i>enhancedDualLayerFDD</i>	42
4.3.4.5	<i>enhancedDualLayerTDD</i>	42
4.3.4.6	<i>supportedMIMO-CapabilityUL-r10</i>	43
4.3.4.7	<i>supportedMIMO-CapabilityDL-r10</i>	43
4.3.4.8	<i>two-AntennaPortsForPUCCH-r10</i>	43
4.3.4.9	<i>tm9-With-8Tx-FDD-r10</i>	43
4.3.4.10	<i>pmi-Disabling-r10</i>	43
4.3.4.11	<i>crossCarrierScheduling-r10</i>	43
4.3.4.12	<i>simultaneousPUCCH-PUSCH-r10</i>	43
4.3.4.13	<i>multiClusterPUSCH-WithinCC-r10</i>	43
4.3.4.14	<i>nonContiguousUL-RA-WithinCC-Info-r10</i>	44
4.3.4.15	<i>crs-InterfHandl-r11</i>	44
4.3.4.16	Void.....	44
4.3.4.17	Void.....	44
4.3.4.18	<i>ePDCCH-r11</i>	44
4.3.4.19	<i>multiACK-CSI-Reporting-r11</i>	44
4.3.4.20	<i>ss-CCH-InterfHandl-r11</i>	44
4.3.4.21	<i>tdd-SpecialSubframe-r11</i>	44
4.3.4.21A	<i>tdd-SpecialSubframe-r14</i>	44
4.3.4.21B	<i>ssp10-TDD-Only-r14</i>	44
4.3.4.22	<i>txDiv-PUCCH1b-ChSelect-r11</i>	45
4.3.4.23	<i>ul-CoMP-r11</i>	45
4.3.4.24	<i>tm5-FDD</i>	45
4.3.4.25	<i>tm5-TDD</i>	45
4.3.4.26	<i>interBandTDD-CA-WithDifferentConfig-r11</i>	45
4.3.4.27	<i>e-HARQ-Pattern-FDD-r12</i>	45
4.3.4.28	<i>tdd-FDD-CA-PCellDuplex-r12</i>	45
4.3.4.29	<i>csi-SubframeSet-r12</i>	45
4.3.4.30	<i>phy-TDD-ReConfig-FDD-PCell-r12</i>	45
4.3.4.31	<i>phy-TDD-ReConfig-TDD-PCell-r12</i>	45
4.3.4.32	<i>pusch-SRS-PowerControl-SubframeSet-r12</i>	46
4.3.4.33	<i>enhanced-4TxCodebook-r12</i>	46
4.3.4.34	<i>pusch-FeedbackMode-r12</i>	46
4.3.4.35	<i>naics-Capability-List-r12</i>	46
4.3.4.36	<i>noResourceRestrictionForTTIBundling-r12</i>	46
4.3.4.37	Void.....	46
4.3.4.38	<i>discoverySignalsInDeactSCell-r12</i>	46
4.3.4.39	<i>ul-64QAM-r12</i>	46
4.3.4.40	<i>supportedMIMO-CapabilityDL-r12</i>	46
4.3.4.41	<i>alternativeTBS-Indices-r12</i>	46
4.3.4.42	<i>codebook-HARQ-ACK-r13</i>	46
4.3.4.43	<i>fdd-HARQ-TimingTDD-r13</i>	47
4.3.4.44	<i>maxNumberUpdatedCSI-Proc-r13</i>	47
4.3.4.45	<i>pucch-Format4-r13</i>	47
4.3.4.46	<i>pucch-Format5-r13</i>	47
4.3.4.47	<i>pucch-SCell-r13</i>	47
4.3.4.48	<i>supportedBlindDecoding-r13</i>	47
4.3.4.48.1	<i>maxNumberDecoding-r13</i>	47
4.3.4.48.2	<i>pdccch-CandidateReductions-r13</i>	47
4.3.4.48.3	<i>skipMonitoringDCI-Format0-1A-r13</i>	47
4.3.4.49	<i>crs-InterfMitigationTM10-r13</i>	47

4.3.4.49a	<i>crs-InterfMitigationTM1toTM9-r13</i>	47
4.3.4.50	<i>pdsch-CollisionHandling-r13</i>	48
4.3.4.51	<i>aperiodicCSI-Reporting-r13</i>	48
4.3.4.52	<i>crossCarrierScheduling-B5C-r13</i>	48
4.3.4.53	<i>spatialBundling-HARQ-ACK-r13</i>	48
4.3.4.54	<i>uci-PUSCH-Ext-r13</i>	48
4.3.4.55	<i>multiTone-r13</i>	48
4.3.4.56	<i>multiCarrier-r13</i>	48
4.3.4.57	<i>cch-InterfMitigation-RefRecTypeA-r13</i>	48
4.3.4.58	<i>cch-InterfMitigation-RefRecTypeB-r13</i>	49
4.3.4.59	<i>cch-InterfMitigation-MaxNumCCs-r13</i>	49
4.3.4.60	<i>tdd-TTI-Bundling-r14</i>	49
4.3.4.61	<i>dmrs-LessUpPTS-r14</i>	49
4.3.4.62	<i>twoHARQ-Processes-r14</i>	49
4.3.4.63	<i>ce-PUSCH-NB-MaxTBS-r14</i>	49
4.3.4.64	<i>ce-PDSCH-PUSCH-MaxBandwidth-r14</i>	49
4.3.4.65	<i>ce-HARQ-AckBundling-r14</i>	49
4.3.4.66	<i>ce-PDSCH-TenProcesses-r14</i>	50
4.3.4.67	<i>ce-RetuningSymbols-r14</i>	50
4.3.4.68	<i>ce-PDSCH-PUSCH-Enhancement-r14</i>	50
4.3.4.69	<i>ce-SchedulingEnhancement-r14</i>	50
4.3.4.70	<i>ce-SRS-Enhancement-r14</i>	50
4.3.4.70A	<i>ce-SRS-EnhancementWithoutComb4-r14</i>	50
4.3.4.71	<i>ce-PUCCH-Enhancement-r14</i>	50
4.3.4.72	<i>ce-ClosedLoopTxAntennaSelection-r14</i>	50
4.3.4.73	<i>ul-256QAM-r14</i>	50
4.3.4.74	<i>alternativeTBS-Index-r14</i>	50
4.3.4.75	<i>multiCarrier-NPRACH-r14</i>	51
4.3.4.76	<i>multiCarrierPaging-r14</i>	51
4.3.4.77	<i>ul-256QAM-perCC-InfoList-r14</i>	51
4.3.4.78	<i>unicast-fembmsMixedSCell-r14</i>	51
4.3.4.79	<i>emptyUnicastRegion-r14</i>	51
4.3.4.80	<i>interferenceRandomisation-r14</i>	51
4.3.4.81	<i>must-CapabilityPerBand-r14</i>	51
4.3.4.81.1	<i>must-TM234-UpTo2Tx-r14</i>	51
4.3.4.81.2	<i>must-TM89-UpToOneInterferingLayer-r14</i>	51
4.3.4.81.3	<i>must-TM10-UpToOneInterferingLayer-r14</i>	51
4.3.4.81.4	<i>must-TM89-UpToThreeInterferingLayers-r14</i>	51
4.3.4.81.5	<i>must-TM10-UpToThreeInterferingLayers-r14</i>	52
4.3.4.82	<i>crs-LessDwPTS-r14</i>	52
4.3.4.83	<i>srs-UpPTS-6sym-r14</i>	52
4.3.5	RF parameters.....	52
4.3.5.1	<i>supportedBandListEUTRA</i>	52
4.3.5.1.1	<i>ue-PowerClass-N-r13, ue-PowerClass-5-r13</i>	52
4.3.5.1.2	<i>intraFreq-CE-NeedForGaps-r13</i>	52
4.3.5.1.3	<i>ue-CA-PowerClass-N</i>	52
4.3.5.1A	<i>supportedBandList-r13</i>	52
4.3.5.1A.1	<i>powerClassNB-20dBm-r13</i>	52
4.3.5.1A.2	<i>powerClassNB-14dBm-r14</i>	52
4.3.5.2	<i>supportedBandCombination</i>	52
4.3.5.2.1	<i>supportedBandCombinationReduced-r13</i>	53
4.3.5.3	<i>multipleTimingAdvance</i>	54
4.3.5.4	<i>simultaneousRx-Tx</i>	54
4.3.5.5	<i>supportedCSI-Proc-r11</i>	54
4.3.5.6	<i>freqBandRetrieval-r11</i>	54
4.3.5.7	<i>dl-256QAM-r12</i>	54
4.3.5.8	<i>supportedNAICS-2CRS-AP-r12</i>	54
4.3.5.9	<i>dc-Support-r12</i>	54
4.3.5.9.1	<i>asynchronous-r12</i>	54
4.3.5.9.2	<i>supportedCellGrouping-r12</i>	55
4.3.5.10	<i>modifiedMPR-Behavior-r10</i>	55
4.3.5.11	<i>freqBandPriorityAdjustment-r12</i>	55

4.3.5.12	<i>commSupportedBandsPerBC-r12</i>	55
4.3.5.13	<i>supportedCSI-Proc-r12</i>	55
4.3.5.14	<i>fourLayerTM3-TM4-r10</i>	55
4.3.5.15	<i>fourLayerTM3-TM4-perCC-r12</i>	55
4.3.5.16	<i>multiNS-Pmax-r10</i>	55
4.3.5.16A	<i>multiNS-Pmax-r13</i>	55
4.3.5.17	<i>differentFallbackSupported-r13</i>	55
4.3.5.18	<i>maximumCCsRetrieval-r13</i>	55
4.3.5.19	<i>skipFallbackCombinations-r13</i>	56
4.3.5.20	Void	56
4.3.5.21	<i>reducedIntNonContComb-r13</i>	56
4.3.5.22	<i>additionalRx-Tx-PerformanceReq-r13</i>	56
4.3.5.23	<i>maxLayersMIMO-Indication-r12</i>	56
4.3.5.24	<i>rf-RetuningTimeDL-r14</i>	56
4.3.5.25	<i>rf-RetuningTimeUL-r14</i>	56
4.3.5.26	<i>diffFallbackCombReport-r14</i>	56
4.3.5.27	<i>v2x-SupportedTxBandCombListPerBC-r14, v2x-SupportedRxBandCombListPerBC-r14</i>	57
4.3.5.28	<i>txAntennaSwitchDL-r13</i>	57
4.3.5.29	<i>txAntennaSwitchUL-r13</i>	57
4.3.5.30	Void	57
4.3.5.31	Void	57
4.3.5.32	<i>srs-MaxSimultaneousCCs-r14</i>	57
4.3.5.33	Void	57
4.3.5.34	Void	57
4.3.5.35	<i>srs-FlexibleTiming-r14</i>	57
4.3.5.36	<i>srs-HARQ-ReferenceConfig-r14</i>	57
4.3.6	Measurement parameters	57
4.3.6.1	<i>interFreqNeedForGaps and interRAT-NeedForGaps</i>	57
4.3.6.2	<i>rsrqMeasWideband</i>	58
4.3.6.3	<i>timerT312-r12</i>	58
4.3.6.4	<i>alternativeTimeToTrigger-r12</i>	58
4.3.6.5	<i>benefitsFromInterruption-r11</i>	58
4.3.6.6	<i>incMonEUTRA-r12</i>	58
4.3.6.7	<i>incMonUTRA-r12</i>	58
4.3.6.8	<i>extendedMaxMeasId-r12</i>	58
4.3.6.9	<i>crs-DiscoverySignalsMeas-r12</i>	58
4.3.6.10	<i>csi-RS-DiscoverySignalsMeas-r12</i>	58
4.3.6.11	<i>extendedRSRQ-LowerRange-r12</i>	58
4.3.6.12	<i>rsrq-OnAllSymbols-r12</i>	59
4.3.6.13	<i>rs-SINR-Meas-r13</i>	59
4.3.6.14	<i>whiteCellList-r13</i>	59
4.3.6.15	<i>extendedFreqPriorities-r13</i>	59
4.3.6.16	<i>extendedMaxObjectId-r13</i>	59
4.3.6.17	<i>ul-PDCP-Delay-r13</i>	59
4.3.6.18	Void	59
4.3.6.19	<i>rsqi-AndChannelOccupancyReporting-r13</i>	59
4.3.6.20	<i>multiBandInfoReport-r13</i>	59
4.3.6.21	Void	59
4.3.6.22	Void	59
4.3.6.23	<i>ceMeasurements-r14</i>	59
4.3.6.24	<i>ncsg-r14</i>	60
4.3.6.25	<i>perServingCellMeasurementGap-r14</i>	60
4.3.6.26	<i>shortMeasurementGap-r14</i>	60
4.3.6.27	<i>nonUniformGap-r14</i>	60
4.3.6.28	<i>rlm-ReportSupport-r14</i>	60
4.3.6.29	nonCSG-SI-Reporting	60
4.3.7	Inter-RAT parameters	60
4.3.7.1	<i>utraFDD</i>	60
4.3.7.2	<i>supportedBandListUTRA-FDD</i>	60
4.3.7.3	<i>utraTDD128</i>	60
4.3.7.4	<i>supportedBandListUTRA-TDD128</i>	60
4.3.7.5	<i>utraTDD384</i>	60

4.3.7.6	<i>supportedBandListUTRA-TDD384</i>	61
4.3.7.7	<i>utraTDD768</i>	61
4.3.7.8	<i>supportedBandListUTRA-TDD768</i>	61
4.3.7.9	<i>geran</i>	61
4.3.7.10	<i>supportedBandListGERAN</i>	61
4.3.7.11	<i>interRAT-PS-HO-ToGERAN</i>	61
4.3.7.12	<i>cdma2000-HRPD</i>	61
4.3.7.13	<i>supportedBandListHRPD</i>	61
4.3.7.14	<i>tx-ConfigHRPD</i>	61
4.3.7.15	<i>rx-ConfigHRPD</i>	61
4.3.7.16	<i>cdma2000-1xRTT</i>	61
4.3.7.17	<i>supportedBandList1XRTT</i>	61
4.3.7.18	<i>tx-Config1XRTT</i>	62
4.3.7.19	<i>rx-Config1XRTT</i>	62
4.3.7.20	<i>e-CSFB-1XRTT</i>	62
4.3.7.21	<i>e-CSFB-ConcPS-Mob1XRTT</i>	62
4.3.7.22	<i>e-RedirectionUTRA</i>	62
4.3.7.23	<i>e-RedirectionGERAN</i>	62
4.3.7.24	<i>dtm</i>	62
4.3.7.25	<i>e-CSFB-dual-1XRTT</i>	62
4.3.7.26	<i>e-RedirectionUTRA-TDD</i>	62
4.3.7.27	<i>cdma2000-NW-Sharing-r11</i>	62
4.3.7.28	<i>mfb1-UTRA</i>	62
4.3.7.29	<i>supportedBandListWLAN</i>	63
4.3.8	General parameters	63
4.3.8.1	<i>accessStratumRelease</i>	63
4.3.8.1A	<i>accessStratumRelease-r13</i>	63
4.3.8.2	<i>deviceType</i>	63
4.3.8.3	Void	63
4.3.8.4	Void	63
4.3.8.5	<i>multipleDRB-r13</i>	63
4.3.8.6	Void	63
4.3.9	Void	63
4.3.10	CSG Proximity Indication parameters	63
4.3.10.1	<i>intraFreqProximityIndication</i>	63
4.3.10.2	<i>interFreqProximityIndication</i>	63
4.3.10.3	<i>utran-ProximityIndication</i>	63
4.3.11	Neighbour cell SI acquisition parameters	64
4.3.11.1	<i>intraFreqSI-AcquisitionForHO</i>	64
4.3.11.2	<i>interFreqSI-AcquisitionForHO</i>	64
4.3.11.3	<i>utran-SI-AcquisitionForHO</i>	64
4.3.12	SON parameters	64
4.3.12.1	<i>rach-Report</i>	64
4.3.13	UE-based network performance measurement parameters	64
4.3.13.1	<i>loggedMeasurementsIdle</i>	64
4.3.13.2	<i>standaloneGNSS-Location</i>	64
4.3.13.3	Void	64
4.3.13.4	<i>loggedMBSFNMeasurements-r12</i>	64
4.3.13.5	<i>locationReport-r14</i>	64
4.3.14	IMS Voice parameters	65
4.3.14.1	<i>voiceOver-PS-HS-UTRA-FDD</i>	65
4.3.14.2	<i>voiceOver-PS-HS-UTRA-TDD128</i>	65
4.3.14.3	<i>srvc-FromUTRA-FDD-ToGERAN</i>	65
4.3.14.4	<i>srvc-FromUTRA-FDD-ToUTRA-FDD</i>	65
4.3.14.5	<i>srvc-FromUTRA-TDD128-ToGERAN</i>	65
4.3.14.6	<i>srvc-FromUTRA-TDD128-ToUTRA-TDD128</i>	65
4.3.15	Other parameters	65
4.3.15.1	Void	65
4.3.15.2	<i>inDeviceCoexInd-r11</i>	65
4.3.15.3	<i>powerPrefInd-r11</i>	65
4.3.15.4	<i>ue-Rx-TxTimeDiffMeasurements-r11</i>	65
4.3.15.5	Void	66

4.3.15.6	Void.....	66
4.3.15.7	Void.....	66
4.3.15.8	<i>inDeviceCoexInd-UL-CA-r11</i>	66
4.3.15.9	<i>bwPrefInd-r14</i>	66
4.3.15.10	<i>inDeviceCoexInd-HardwareSharingInd-r13</i>	66
4.3.15.11	<i>overheatingInd-r14</i>	66
4.3.16	Positioning parameters.....	66
4.3.16.1	<i>otdoa-UE-assisted</i>	66
4.3.16.2	<i>interFreqRSTDmeasurement</i>	66
4.3.17	MBMS parameters.....	66
4.3.17.1	<i>mbms-SCell-r11</i>	66
4.3.17.2	<i>mbms-NonServingCell-r11</i>	66
4.3.17.3	<i>mbms-AsyncDC-r12</i>	67
4.3.17.4	<i>fembmsMixedCell-r14</i>	67
4.3.17.5	<i>fembmsDedicatedCell-r14</i>	67
4.3.17.6	<i>subcarrierSpacingMBMS-khz1dot25-r14, subcarrierSpacingMBMS-khz7dot5-r14</i>	67
4.3.17.7	<i>mbms-MaxBW-r14</i>	67
4.3.17.8	<i>mbms-ScalingFactor1dot25-r14, mbms-ScalingFactor7dot5-r14</i>	67
4.3.18	RAN-assisted WLAN interworking parameters	67
4.3.18.1	<i>wlan-IW-RAN-Rules-r12</i>	67
4.3.18.2	<i>wlan-IW-ANDSF-Policies-r12</i>	67
4.3.18.3	<i>rclwi-r13</i>	68
4.3.19	MAC parameters.....	68
4.3.19.1	<i>longDRX-Command-r12</i>	68
4.3.19.2	<i>logicalChannelSR-ProhibitTimer-r12</i>	68
4.3.19.3	<i>extendedMAC-LengthField-r13</i>	68
4.3.19.4	<i>extendedLongDRX-r13</i>	68
4.3.19.5	<i>shortSPS-IntervalFDD-r14</i>	68
4.3.19.6	<i>shortSPS-IntervalTDD-r14</i>	68
4.3.19.7	<i>skipUplinkDynamic-r14</i>	68
4.3.19.8	<i>skipUplinkSPS-r14</i>	68
4.3.19.9	<i>dataInactMon-r14</i>	68
4.3.19.10	<i>rai-Support-r14</i>	68
4.3.19.11	<i>multipleUplinkSPS-r14</i>	69
4.3.19.12	<i>earlyContentionResolution-r14</i>	69
4.3.20	Dual Connectivity parameters.....	69
4.3.20.1	<i>drb-TypeSplit-r12</i>	69
4.3.20.2	<i>drb-TypeSCG-r12</i>	69
4.3.20.3	<i>pdcp-TransferSplitUL-r13</i>	69
4.3.20.4	<i>ue-SSTD-Meas-r13</i>	69
4.3.21	Sidelink parameters.....	69
4.3.21.1	<i>commSupportedBands-r12</i>	69
4.3.21.2	<i>commSimultaneousTx-r12</i>	69
4.3.21.3	<i>discSupportedBands-r12</i>	69
4.3.21.4	<i>discScheduledResourceAlloc-r12</i>	69
4.3.21.5	<i>disc-UE-SelectedResourceAlloc-r12</i>	70
4.3.21.6	<i>disc-SLSS-r12</i>	70
4.3.21.7	<i>discSupportedProc-r12</i>	70
4.3.21.8	<i>commMultipleTx-r13</i>	70
4.3.21.9	<i>discInterFreqTx-r13</i>	70
4.3.21.10	<i>discPeriodicSLSS-r13</i>	70
4.3.21.11	<i>discSysInfoReporting-r13</i>	70
4.3.21.12	<i>zoneBasedPoolSelection-r14</i>	70
4.3.21.13	<i>v2x-HighReception-r14</i>	70
4.3.21.14	<i>v2x-eNB-Scheduled-r14</i>	70
4.3.21.15	<i>ue-AutonomousWithFullSensing-r14</i>	71
4.3.21.16	<i>ue-AutonomousWithPartialSensing-r14</i>	71
4.3.21.17	<i>slss-TxRx-r14</i>	71
4.3.21.18	<i>sl-CongestionControl-r14</i>	71
4.3.21.19	<i>v2x-TxWithShortResvInterval-r14</i>	71
4.3.21.20	<i>v2x-numberTxRxTiming-r14</i>	71
4.3.21.21	<i>v2x-nonAdjacentPSCCH-PSSCH-r14</i>	71

4.3.21.22	<i>v2x-HighPower-r14</i>	71
4.3.21.23	<i>v2x-SupportedBandCombinationList-r14</i>	71
4.3.22	SC-PTM parameters	71
4.3.22.1	<i>scptm-ParallelReception-r13</i>	71
4.3.22.2	Void.....	72
4.3.22.3	<i>scptm-SCell-r13</i>	72
4.3.22.4	<i>scptm-NonServingCell-r13</i>	72
4.3.22.5	<i>scptm-AsyncDC-r13</i>	72
4.3.23	LAA parameters.....	72
4.3.23.1	<i>downlinkLAA-r13</i>	72
4.3.23.2	<i>crossCarrierSchedulingLAA-DL-r13</i>	72
4.3.23.3	<i>csi-RS-DRS-RRM-MeasurementsLAA-r13</i>	72
4.3.23.4	<i>endingDwPTS-r13</i>	72
4.3.23.5	<i>secondSlotStartingPosition-r13</i>	73
4.3.23.6	<i>tm9-LAA-r13</i>	73
4.3.23.7	<i>tm10-LAA-r13</i>	73
4.3.23.8	<i>uplinkLAA-r14</i>	73
4.3.23.9	<i>crossCarrierSchedulingLAA-UL-r14</i>	73
4.3.23.10	<i>twoStepSchedulingTimingInfo-r14</i>	73
4.3.23.11	<i>uss-BlindDecodingAdjustment-r14</i>	73
4.3.23.12	<i>uss-BlindDecodingReduction-r14</i>	73
4.3.23.13	<i>outOfSequenceGrantHandling-r14</i>	73
4.3.24	LWIP parameters	73
4.3.24.1	<i>lwip-r13</i>	73
4.3.24.2	<i>lwip-Aggregation-UL-r14</i>	74
4.3.24.3	<i>lwip-Aggregation-DL-r14</i>	74
4.3.25	LWA parameters.....	74
4.3.25.1	<i>lwa-r13</i>	74
4.3.25.2	<i>lwa-SplitBearer-r13</i>	74
4.3.25.3	<i>lwa-BufferSize-r13</i>	74
4.3.25.4	<i>wlan-MAC-Address-r13</i>	74
4.3.25.5	<i>lwa-HO-WithoutWT-Change-r14</i>	74
4.3.25.6	<i>lwa-UL-r14</i>	74
4.3.25.7	Void	74
4.3.25.8	<i>wlan-SupportedDataRate-r14</i>	74
4.3.25.9	<i>lwa-RLC-UM-r14</i>	74
4.3.26	Void	75
4.3.26.1	Void.....	75
4.3.27	Inter-RAT parameters WLAN	75
4.3.27.1	<i>supportedBandListWLAN-r13</i>	75
4.3.28	EBF FD-MIMO parameters	75
4.3.28.1	<i>beamformed-r13</i>	75
4.3.28.2	<i>channelMeasRestriction-r13</i>	75
4.3.28.3	<i>csi-RS-EnhancementsTDD-r13</i>	75
4.3.28.4	<i>dmrs-Enhancements-r13</i>	75
4.3.28.5	<i>interferenceMeasRestriction-r13</i>	75
4.3.28.6	<i>nonPrecoded-r13</i>	75
4.3.28.7	<i>srs-Enhancements-r13</i>	76
4.3.28.8	<i>srs-EnhancementsTDD-r13</i>	76
4.3.28.9	<i>csi-ReportingAdvanced-r14, csi-ReportingAdvancedMaxPorts-r14</i>	76
4.3.28.10	Void	76
4.3.28.11	<i>csi-ReportingNP-r14</i>	76
4.3.28.12	<i>relWeightTwoLayers-r13, relWeightFourLayers-r13, relWeightEightLayers-r13</i>	76
4.3.28.13	<i>totalWeightedLayers-r13</i>	76
4.3.28.14	<i>zp-CSI-RS-AperiodicInfo-r14</i>	77
4.3.28.15	<i>ul-dmrs-Enhancements-r14</i>	77
4.3.28.16	<i>densityReductionNP-r14, densityReductionBF-r14</i>	77
4.3.28.17	<i>hybridCSI-r14</i>	77
4.3.28.18	<i>semiOL-r14</i>	77
4.3.29	CE parameters.....	77
4.3.29.1	<i>ce-ModeA-r13</i>	77
4.3.29.2	<i>ce-ModeB-r13</i>	77

4.3.29.3	<i>intraFreqA3-CE-ModeA-r13</i>	77
4.3.29.4	<i>intraFreqA3-CE-ModeB-r13</i>	77
4.3.29.5	<i>intraFreqHO-CE-ModeA-r13</i>	78
4.3.29.6	<i>intraFreqHO-CE-ModeB-r13</i>	78
4.3.29.7	<i>ue-CE-NeedULGaps-r13</i>	78
4.3.29.8	<i>unicastFrequencyHopping-r13</i>	78
4.3.29.9	<i>ce-SwitchWithoutHO-r14</i>	78
4.3.29.10	<i>tm9-CE-ModeA-r13</i>	78
4.3.29.11	<i>tm9-CE-ModeB-r13</i>	78
4.3.29.12	<i>tm6-CE-ModeA-r13</i>	78
4.3.30	Mobility enhancement parameters	78
4.3.30.1	<i>makeBeforeBreak-r14</i>	78
4.3.30.2	<i>rach-Less-r14</i>	78
4.3.31	Void	79
4.3.31.1	Void.....	79
4.3.31.2	Void.....	79
4.3.32	MMTEL parameters	79
4.3.32.1	<i>delayBudgetReporting-r14</i>	79
4.3.32.2	<i>pusch-Enhancements-r14</i>	79
4.3.32.3	<i>recommendedBitRate-r14</i>	79
4.3.33	High speed enhancement parameters.....	79
4.3.33.1	<i>measurementEnhancements-r14</i>	79
4.3.33.2	<i>demodulationEnhancements-r14</i>	79
4.3.33.3	<i>prach-Enhancements-r14</i>	79
5	Void.....	79
6	Optional features without UE radio access capability parameters	79
6.1	CSG features	80
6.2	PWS features	80
6.2.1	ETWS	80
6.2.2	CMAS	80
6.2.3	KPAS	80
6.2.4	EU-Alert	80
6.3	MBMS features	80
6.3.1	MBMS Service Continuity	80
6.3.2	MBMS reception with 256QAM	80
6.4	Void.....	81
6.5	Positioning features	81
6.5.0	Void	81
6.5.1	Void	81
6.6	UE receiver features	81
6.6.1	MMSE with IRC receiver	81
6.6.2	MMSE with IRC receiver for PDSCH transmission mode 9.....	81
6.6.3	Single-user MIMO interference mitigation advanced receiver for UEs with 2 receiver antenna ports	81
6.6.4	Single-user MIMO interference mitigation advanced receiver for UEs with 4 receiver antenna ports	81
6.6.5	MMSE-IRC DL Control Channel interference mitigation receiver for UEs with 4 receiver antenna ports	81
6.7	RRC Connection	81
6.7.1	RRC Connection Reject with deprioritisation.....	81
6.7.2	RRC Connection Establishment Failure Temporary Qoffset.....	81
6.7.3	<i>mo-VoiceCall</i> establishment cause for mobile originating MMTEL video	82
6.7.4	<i>mo-VoiceCall</i> establishment cause for mobile originating MMTEL voice.....	82
6.7.5	RRC Connection Re-establishment for the Control Plane CIoT EPS Optimization.....	82
6.8	Other features	82
6.8.1	System Information Block Type 16.....	82
6.8.2	QCI1 indication in Radio Link Failure Report	82
6.8.3	Enhanced random access power control	82
6.9	Void.....	82
6.10	SON features	82
6.10.1	Radio Link Failure Report for inter-RAT MRO	82
6.11	Mobility state features	82

6.11.1	Mobility history information storage	82
6.12	Void	83
6.13	Sidelink features	83
6.13.1	Sidelink Relay UE operation	83
6.13.2	Sidelink Remote UE operation	83
6.13.3	Sidelink discovery gap	83
6.14	DRX features	83
6.14.1	Extended DRX in RRC_IDLE	83
6.15	Load balancing features	83
6.15.1	Redistribution in RRC_IDLE	83
6.16	SC-PTM features	83
6.16.1	SC-PTM in Idle mode	83
6.17	Idle mode measurements	83
6.17.1	Relaxed monitoring	83
6.17.2	Serving cell idle mode measurements reporting	83
6.17.3	DL channel quality reporting	84
7	Conditionally Mandatory features	84
7.1	Access control features	84
7.1.1	SSAC	84
7.1.2	CSFB Access Barring Control	84
7.1.3	Extended Access Barring	84
7.1.4	ACDC	84
7.2	Emergency call features	84
7.2.1	IMS emergency call	84
7.3	MAC features	84
7.3.1	SR mask	84
7.3.2	Power Management Indicator in PHR	84
7.4	Inter-RAT Mobility features	85
7.4.1	High Priority CSFB redirection	85
7.4.2	GERAN A/Gb mode to E-UTRAN Inter RAT handover (PS Handover)	85
7.4.3	SRVCC to E-UTRAN from GERAN	85
7.5	Delay Tolerant Access Features	85
7.5.1	extendedWaitTime	85
7.6	RRC Connection	85
7.6.1	Void	85
7.7	Physical layer features	85
7.7.1	Different UL/ DL configuration for TDD inter-band carrier aggregation	85
7.7.2	Full duplex for TDD and FDD carrier aggregation	85
7.7.3	Simultaneous transmission of PUCCH and PUSCH across PUCCH groups	85
7.7.4	Simultaneous transmission of PUCCH in licensed spectrum and PUSCH in LAA SCells	86
7.8	Positioning features	86
7.8.1	OTDOA Inter-frequency RSTD measurement indication	86
7.9	Void	86
7.9.1	Void	86
7.10	Other features	86
7.10.1	Logged MDT measurement suspension due to IDC interference	86
7.10.2	Support of extended reporting of WLAN measurements	86
7.10.3	wlan-ReportAnyWLAN-r14	86
7.10.4	wlan-PeriodicMeas-r14	86
Annex A (informative):	Guideline on maximum number of DL PDCP SDUs per TTI	87
Annex B (informative):	Change history	88
History		93

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/f9310bf5-79bd-4c85-b9b0-316eb2b45c7b/etsi-ts-136-306-v14.11.0-2019-07>