

ETSI TS 136 331 V14.11.0 (2019-07)



**LTE;
Evolved Universal Terrestrial Radio Access (E-UTRA);
Radio Resource Control (RRC);
Protocol specification
(3GPP TS 36.331 version 14.11.0 Release 14)**



ReferenceRTS/TSGR-0236331veb0

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	20
1 Scope	21
2 References	21
3 Definitions, symbols and abbreviations	24
3.1 Definitions	24
3.2 Abbreviations	26
4 General	29
4.1 Introduction	29
4.2 Architecture	30
4.2.1 UE states and state transitions including inter RAT	30
4.2.2 Signalling radio bearers	32
4.3 Services	33
4.3.1 Services provided to upper layers.....	33
4.3.2 Services expected from lower layers	33
4.4 Functions	33
4.5 Data available for transmission for NB-IoT	34
5 Procedures	35
5.1 General	35
5.1.1 Introduction.....	35
5.1.2 General requirements.....	35
5.2 System information	36
5.2.1 Introduction.....	36
5.2.1.1 General	36
5.2.1.2 Scheduling.....	37
5.2.1.2a Scheduling for NB-IoT	38
5.2.1.3 System information validity and notification of changes	38
5.2.1.4 Indication of ETWS notification	40
5.2.1.5 Indication of CMAS notification.....	40
5.2.1.6 Notification of EAB parameters change	41
5.2.1.7 Access Barring parameters change in NB-IoT	41
5.2.2 System information acquisition	41
5.2.2.1 General	41
5.2.2.2 Initiation.....	41
5.2.2.3 System information required by the UE.....	42
5.2.2.4 System information acquisition by the UE.....	42
5.2.2.5 Essential system information missing	46
5.2.2.6 Actions upon reception of the <i>MasterInformationBlock</i> message.....	46
5.2.2.7 Actions upon reception of the <i>SystemInformationBlockType1</i> message	47
5.2.2.8 Actions upon reception of <i>SystemInformation</i> messages	48
5.2.2.9 Actions upon reception of <i>SystemInformationBlockType2</i>	49
5.2.2.10 Actions upon reception of <i>SystemInformationBlockType3</i>	50
5.2.2.11 Actions upon reception of <i>SystemInformationBlockType4</i>	51
5.2.2.12 Actions upon reception of <i>SystemInformationBlockType5</i>	51
5.2.2.13 Actions upon reception of <i>SystemInformationBlockType6</i>	52
5.2.2.14 Actions upon reception of <i>SystemInformationBlockType7</i>	52
5.2.2.15 Actions upon reception of <i>SystemInformationBlockType8</i>	52
5.2.2.16 Actions upon reception of <i>SystemInformationBlockType9</i>	53
5.2.2.17 Actions upon reception of <i>SystemInformationBlockType10</i>	53
5.2.2.18 Actions upon reception of <i>SystemInformationBlockType11</i>	53
5.2.2.19 Actions upon reception of <i>SystemInformationBlockType12</i>	54

5.2.2.20	Actions upon reception of <i>SystemInformationBlockType13</i>	54
5.2.2.21	Actions upon reception of <i>SystemInformationBlockType14</i>	54
5.2.2.22	Actions upon reception of <i>SystemInformationBlockType15</i>	55
5.2.2.23	Actions upon reception of <i>SystemInformationBlockType16</i>	55
5.2.2.24	Actions upon reception of <i>SystemInformationBlockType17</i>	55
5.2.2.25	Actions upon reception of <i>SystemInformationBlockType18</i>	55
5.2.2.26	Actions upon reception of <i>SystemInformationBlockType19</i>	55
5.2.2.27	Actions upon reception of <i>SystemInformationBlockType20</i>	56
5.2.2.28	Actions upon reception of <i>SystemInformationBlockType21</i>	56
5.2.2.29	Actions upon reception of <i>SystemInformationBlockType22-NB</i>	56
5.2.3	Acquisition of an SI message	56
5.2.3a	Acquisition of an SI message by BL UE or UE in CE or a NB-IoT UE	57
5.2.3b	Acquisition of an SI message from MBMS-dedicated cell	57
5.3	Connection control	58
5.3.1	Introduction	58
5.3.1.1	RRC connection control	58
5.3.1.2	Security	59
5.3.1.2a	RN security	60
5.3.1.3	Connected mode mobility	60
5.3.1.4	Connection control in NB-IoT	61
5.3.2	Paging	62
5.3.2.1	General	62
5.3.2.2	Initiation	62
5.3.2.3	Reception of the <i>Paging</i> message by the UE	63
5.3.3	RRC connection establishment	64
5.3.3.1	General	64
5.3.3.1a	Conditions for establishing RRC Connection for sidelink communication/ discovery/ V2X sidelink communication	65
5.3.3.2	Initiation	67
5.3.3.3	Actions related to transmission of <i>RRCConnectionRequest</i> message	71
5.3.3.3a	Actions related to transmission of <i>RRCConnectionResumeRequest</i> message	72
5.3.3.4	Reception of the <i>RRCConnectionSetup</i> by the UE	73
5.3.3.4a	Reception of the <i>RRCConnectionResume</i> by the UE	75
5.3.3.5	Cell re-selection while T300, T302, T303, T305, T306, or T308 is running	77
5.3.3.6	T300 expiry	78
5.3.3.7	T302, T303, T305, T306, or T308 expiry or stop	79
5.3.3.8	Reception of the <i>RRCConnectionReject</i> by the UE	80
5.3.3.9	Abortion of RRC connection establishment	81
5.3.3.10	Handling of SSAC related parameters	81
5.3.3.11	Access barring check	82
5.3.3.12	EAB check	82
5.3.3.13	Access barring check for ACDC	83
5.3.3.14	Access Barring check for NB-IoT	84
5.3.3.15	Failure to deliver NAS information in <i>RRCConnectionSetupComplete</i> message	85
5.3.4	Initial security activation	85
5.3.4.1	General	85
5.3.4.2	Initiation	86
5.3.4.3	Reception of the <i>SecurityModeCommand</i> by the UE	86
5.3.5	RRC connection reconfiguration	87
5.3.5.1	General	87
5.3.5.2	Initiation	87
5.3.5.3	Reception of an <i>RRCConnectionReconfiguration</i> not including the <i>mobilityControlInfo</i> by the UE	88
5.3.5.4	Reception of an <i>RRCConnectionReconfiguration</i> including the <i>mobilityControlInfo</i> by the UE (handover)	89
5.3.5.5	Reconfiguration failure	94
5.3.5.6	T304 expiry (handover failure)	94
5.3.5.7	Void	95
5.3.5.7a	T307 expiry (SCG change failure)	95
5.3.5.8	Radio Configuration involving full configuration option	96
5.3.6	Counter check	97
5.3.6.1	General	97

5.3.6.2	Initiation.....	97
5.3.6.3	Reception of the <i>CounterCheck</i> message by the UE.....	97
5.3.7	RRC connection re-establishment.....	98
5.3.7.1	General.....	98
5.3.7.2	Initiation.....	99
5.3.7.3	Actions following cell selection while T311 is running.....	100
5.3.7.4	Actions related to transmission of <i>RRCCConnectionReestablishmentRequest</i> message.....	100
5.3.7.5	Reception of the <i>RRCCConnectionReestablishment</i> by the UE.....	101
5.3.7.6	T311 expiry.....	104
5.3.7.7	T301 expiry or selected cell no longer suitable.....	104
5.3.7.8	Reception of <i>RRCCConnectionReestablishmentReject</i> by the UE.....	104
5.3.8	RRC connection release.....	104
5.3.8.1	General.....	104
5.3.8.2	Initiation.....	105
5.3.8.3	Reception of the <i>RRCCConnectionRelease</i> by the UE.....	105
5.3.8.4	T320 expiry.....	106
5.3.8.5	T322 expiry.....	106
5.3.8.6	UE actions upon receiving the expiry of <i>DataInactivityTimer</i>	106
5.3.9	RRC connection release requested by upper layers.....	106
5.3.9.1	General.....	106
5.3.9.2	Initiation.....	106
5.3.10	Radio resource configuration.....	107
5.3.10.0	General.....	107
5.3.10.1	SRB addition/ modification.....	107
5.3.10.2	DRB release.....	108
5.3.10.3	DRB addition/ modification.....	108
5.3.10.3a1	DC specific DRB addition or reconfiguration.....	109
5.3.10.3a2	LWA specific DRB addition or reconfiguration.....	111
5.3.10.3a3	LWIP specific DRB addition or reconfiguration.....	112
5.3.10.3a	SCell release.....	113
5.3.10.3b	SCell addition/ modification.....	113
5.3.10.3c	PSCell addition or modification.....	113
5.3.10.4	MAC main reconfiguration.....	114
5.3.10.5	Semi-persistent scheduling reconfiguration.....	114
5.3.10.6	Physical channel reconfiguration.....	114
5.3.10.7	Radio Link Failure Timers and Constants reconfiguration.....	115
5.3.10.8	Time domain measurement resource restriction for serving cell.....	116
5.3.10.9	Other configuration.....	116
5.3.10.10	SCG reconfiguration.....	118
5.3.10.11	SCG dedicated resource configuration.....	120
5.3.10.12	Reconfiguration SCG or split DRB by <i>drb-ToAddModList</i>	120
5.3.10.13	Neighbour cell information reconfiguration.....	120
5.3.10.14	Void.....	121
5.3.10.15	Sidelink dedicated configuration.....	121
5.3.10.15a	V2X sidelink Communication dedicated configuration.....	122
5.3.10.16	T370 expiry.....	123
5.3.11	Radio link failure related actions.....	123
5.3.11.1	Detection of physical layer problems in RRC_CONNECTED.....	123
5.3.11.1a	Early detection of physical layer problems in RRC_CONNECTED.....	123
5.3.11.1b	Detection of physical layer improvements in RRC_CONNECTED.....	123
5.3.11.2	Recovery of physical layer problems.....	123
5.3.11.2a	Recovery of early detection of physical layer problems.....	124
5.3.11.2b	Cancellation of physical layer improvements in RRC_CONNECTED.....	124
5.3.11.3	Detection of radio link failure.....	124
5.3.11.3a	Detection of early-out-of-sync event.....	126
5.3.11.3b	Detection of early-in-sync event.....	126
5.3.12	UE actions upon leaving RRC_CONNECTED.....	126
5.3.13	UE actions upon PUCCH/ SRS release request.....	127
5.3.14	Proximity indication.....	128
5.3.14.1	General.....	128
5.3.14.2	Initiation.....	128
5.3.14.3	Actions related to transmission of <i>ProximityIndication</i> message.....	128

5.3.15	Void	129
5.4	Inter-RAT mobility.....	129
5.4.1	Introduction.....	129
5.4.2	Handover to E-UTRA.....	129
5.4.2.1	General	129
5.4.2.2	Initiation.....	129
5.4.2.3	Reception of the <i>RRCConnectionReconfiguration</i> by the UE.....	130
5.4.2.4	Reconfiguration failure	131
5.4.2.5	T304 expiry (handover to E-UTRA failure).....	132
5.4.3	Mobility from E-UTRA	132
5.4.3.1	General	132
5.4.3.2	Initiation.....	133
5.4.3.3	Reception of the <i>MobilityFromEUTRACommand</i> by the UE	133
5.4.3.4	Successful completion of the mobility from E-UTRA.....	134
5.4.3.5	Mobility from E-UTRA failure	134
5.4.4	Handover from E-UTRA preparation request (CDMA2000)	135
5.4.4.1	General	135
5.4.4.2	Initiation.....	135
5.4.4.3	Reception of the <i>HandoverFromEUTRAPreparationRequest</i> by the UE	135
5.4.5	UL handover preparation transfer (CDMA2000)	136
5.4.5.1	General	136
5.4.5.2	Initiation.....	136
5.4.5.3	Actions related to transmission of the <i>ULHandoverPreparationTransfer</i> message.....	136
5.4.5.4	Failure to deliver the <i>ULHandoverPreparationTransfer</i> message.....	136
5.4.6	Inter-RAT cell change order to E-UTRAN.....	136
5.4.6.1	General	136
5.4.6.2	Initiation.....	137
5.4.6.3	UE fails to complete an inter-RAT cell change order	137
5.5	Measurements.....	137
5.5.1	Introduction.....	137
5.5.2	Measurement configuration	139
5.5.2.1	General	139
5.5.2.2	Measurement identity removal.....	140
5.5.2.2a	Measurement identity autonomous removal	140
5.5.2.3	Measurement identity addition/ modification	141
5.5.2.4	Measurement object removal	141
5.5.2.5	Measurement object addition/ modification.....	142
5.5.2.6	Reporting configuration removal	144
5.5.2.7	Reporting configuration addition/ modification.....	145
5.5.2.8	Quantity configuration	145
5.5.2.9	Measurement gap configuration.....	145
5.5.2.10	Discovery signals measurement timing configuration	147
5.5.2.11	RSSI measurement timing configuration	147
5.5.2.12	Measurement gap sharing configuration	147
5.5.3	Performing measurements	147
5.5.3.1	General	147
5.5.3.2	Layer 3 filtering	151
5.5.4	Measurement report triggering	151
5.5.4.1	General	151
5.5.4.2	Event A1 (Serving becomes better than threshold)	156
5.5.4.3	Event A2 (Serving becomes worse than threshold)	157
5.5.4.4	Event A3 (Neighbour becomes offset better than PCell/ PSCell).....	157
5.5.4.5	Event A4 (Neighbour becomes better than threshold)	158
5.5.4.6	Event A5 (PCell/ PSCell becomes worse than threshold1 and neighbour becomes better than threshold2)	159
5.5.4.6a	Event A6 (Neighbour becomes offset better than SCell)	160
5.5.4.7	Event B1 (Inter RAT neighbour becomes better than threshold).....	160
5.5.4.8	Event B2 (PCell becomes worse than threshold1 and inter RAT neighbour becomes better than threshold2)	161
5.5.4.9	Event C1 (CSI-RS resource becomes better than threshold).....	162
5.5.4.10	Event C2 (CSI-RS resource becomes offset better than reference CSI-RS resource).....	162
5.5.4.11	Event W1 (WLAN becomes better than a threshold).....	163

5.5.4.12	Event W2 (All WLAN inside WLAN mobility set becomes worse than threshold1 and a WLAN outside WLAN mobility set becomes better than threshold2)	164
5.5.4.13	Event W3 (All WLAN inside WLAN mobility set becomes worse than a threshold)	164
5.5.4.14	Event V1 (The channel busy ratio is above a threshold)	165
5.5.4.15	Event V2 (The channel busy ratio is below a threshold)	165
5.5.5	Measurement reporting	166
5.5.6	Measurement related actions	171
5.5.6.1	Actions upon handover and re-establishment	171
5.5.6.2	Speed dependant scaling of measurement related parameters	172
5.5.7	Inter-frequency RSTD measurement indication	172
5.5.7.1	General	172
5.5.7.2	Initiation	173
5.5.7.3	Actions related to transmission of <i>InterFreqRSTDMeasurementIndication</i> message	173
5.6	Other	173
5.6.0	General	173
5.6.1	DL information transfer	174
5.6.1.1	General	174
5.6.1.2	Initiation	174
5.6.1.3	Reception of the <i>DLInformationTransfer</i> by the UE	174
5.6.2	UL information transfer	174
5.6.2.1	General	174
5.6.2.2	Initiation	175
5.6.2.3	Actions related to transmission of <i>ULInformationTransfer</i> message	175
5.6.2.4	Failure to deliver <i>ULInformationTransfer</i> message	175
5.6.3	UE capability transfer	176
5.6.3.1	General	176
5.6.3.2	Initiation	176
5.6.3.3	Reception of the <i>UECapabilityEnquiry</i> by the UE	176
5.6.4	CSFB to 1x Parameter transfer	180
5.6.4.1	General	180
5.6.4.2	Initiation	180
5.6.4.3	Actions related to transmission of <i>CSFBParametersRequestCDMA2000</i> message	180
5.6.4.4	Reception of the <i>CSFBParametersResponseCDMA2000</i> message	180
5.6.5	UE Information	180
5.6.5.1	General	180
5.6.5.2	Initiation	181
5.6.5.3	Reception of the <i>UEInformationRequest</i> message	181
5.6.6	Logged Measurement Configuration	182
5.6.6.1	General	182
5.6.6.2	Initiation	182
5.6.6.3	Reception of the <i>LoggedMeasurementConfiguration</i> by the UE	182
5.6.6.4	T330 expiry	183
5.6.7	Release of Logged Measurement Configuration	183
5.6.7.1	General	183
5.6.7.2	Initiation	183
5.6.8	Measurements logging	183
5.6.8.1	General	183
5.6.8.2	Initiation	183
5.6.9	In-device coexistence indication	186
5.6.9.1	General	186
5.6.9.2	Initiation	186
5.6.9.3	Actions related to transmission of <i>InDeviceCoexIndication</i> message	187
5.6.10	UE Assistance Information	188
5.6.10.1	General	188
5.6.10.2	Initiation	188
5.6.10.3	Actions related to transmission of <i>UEAssistanceInformation</i> message	190
5.6.11	Mobility history information	191
5.6.11.1	General	191
5.6.11.2	Initiation	191
5.6.12	RAN-assisted WLAN interworking	192
5.6.12.1	General	192
5.6.12.2	Dedicated WLAN offload configuration	192

5.6.12.3	WLAN offload RAN evaluation	192
5.6.12.4	T350 expiry or stop	192
5.6.12.5	Cell selection/ re-selection while T350 is running	193
5.6.13	SCG failure information	193
5.6.13.1	General	193
5.6.13.2	Initiation	193
5.6.13.3	Actions related to transmission of <i>SCGFailureInformation</i> message	194
5.6.14	LTE-WLAN Aggregation	194
5.6.14.1	Introduction	194
5.6.14.2	Reception of LWA configuration	194
5.6.14.3	Release of LWA configuration	195
5.6.15	WLAN connection management	195
5.6.15.1	Introduction	195
5.6.15.2	WLAN connection status reporting	196
5.6.15.2.1	General	196
5.6.15.2.2	Initiation	196
5.6.15.2.3	Actions related to transmission of <i>WLANConnectionStatusReport</i> message	196
5.6.15.3	T351 Expiry (WLAN connection attempt timeout)	196
5.6.15.4	WLAN status monitoring	197
5.6.16	RAN controlled LTE-WLAN interworking	198
5.6.16.1	General	198
5.6.16.2	WLAN traffic steering command	198
5.6.17	LTE-WLAN aggregation with IPsec tunnel	198
5.6.17.1	General	198
5.6.17.2	LWIP reconfiguration	198
5.6.17.3	LWIP release	199
5.6.18	Void	199
5.7	Generic error handling	199
5.7.1	General	199
5.7.2	ASN.1 violation or encoding error	200
5.7.3	Field set to a not comprehended value	200
5.7.4	Mandatory field missing	200
5.7.5	Not comprehended field	201
5.8	MBMS	202
5.8.1	Introduction	202
5.8.1.1	General	202
5.8.1.2	Scheduling	202
5.8.1.3	MCCH information validity and notification of changes	202
5.8.2	MCCH information acquisition	203
5.8.2.1	General	203
5.8.2.2	Initiation	204
5.8.2.3	MCCH information acquisition by the UE	204
5.8.2.4	Actions upon reception of the <i>MBSFNAreaConfiguration</i> message	204
5.8.2.5	Actions upon reception of the <i>MBMScountingRequest</i> message	204
5.8.3	MBMS PTM radio bearer configuration	204
5.8.3.1	General	204
5.8.3.2	Initiation	205
5.8.3.3	MRB establishment	205
5.8.3.4	MRB release	205
5.8.4	MBMS Counting Procedure	205
5.8.4.1	General	205
5.8.4.2	Initiation	205
5.8.4.3	Reception of the <i>MBMScountingRequest</i> message by the UE	206
5.8.5	MBMS interest indication	206
5.8.5.1	General	206
5.8.5.2	Initiation	207
5.8.5.3	Determine MBMS frequencies of interest	207
5.8.5.4	Actions related to transmission of <i>MBMSInterestIndication</i> message	208
5.8a	SC-PTM	209
5.8a.1	Introduction	209
5.8a.1.1	General	209
5.8a.1.2	SC-MCCH scheduling	209

5.8a.1.3	SC-MCCH information validity and notification of changes.....	209
5.8a.1.4	Procedures.....	210
5.8a.2	SC-MCCH information acquisition	210
5.8a.2.1	General.....	210
5.8a.2.2	Initiation.....	210
5.8a.2.3	SC-MCCH information acquisition by the UE	210
5.8a.2.4	Actions upon reception of the <i>SCPTMConfiguration</i> message.....	211
5.8a.3	SC-PTM radio bearer configuration	211
5.8a.3.1	General.....	211
5.8a.3.2	Initiation.....	211
5.8a.3.3	SC-MRB establishment.....	211
5.8a.3.4	SC-MRB release	212
5.9	RN procedures.....	212
5.9.1	RN reconfiguration	212
5.9.1.1	General.....	212
5.9.1.2	Initiation.....	212
5.9.1.3	Reception of the <i>RNReconfiguration</i> by the RN	212
5.10	Sidelink	213
5.10.1	Introduction.....	213
5.10.1a	Conditions for sidelink communication operation.....	213
5.10.1d	Conditions for V2X sidelink communication operation	214
5.10.2	Sidelink UE information.....	215
5.10.2.1	General.....	215
5.10.2.2	Initiation.....	216
5.10.2.3	Actions related to transmission of <i>SidelinkUEInformation</i> message	221
5.10.3	Sidelink communication monitoring.....	223
5.10.4	Sidelink communication transmission	225
5.10.5	Sidelink discovery monitoring.....	226
5.10.6	Sidelink discovery announcement	227
5.10.6a	Sidelink discovery announcement pool selection	230
5.10.6b	Sidelink discovery announcement reference carrier selection	230
5.10.7	Sidelink synchronisation information transmission	231
5.10.7.1	General.....	231
5.10.7.2	Initiation.....	232
5.10.7.3	Transmission of SLSS.....	233
5.10.7.4	Transmission of <i>MasterInformationBlock-SL</i> or <i>MasterInformationBlock-SL-V2X</i> message	236
5.10.7.5	Void.....	237
5.10.8	Sidelink synchronisation reference.....	237
5.10.8.1	General.....	237
5.10.8.2	Selection and reselection of synchronisation reference.....	237
5.10.9	Sidelink common control information	239
5.10.9.1	General.....	239
5.10.9.2	Actions related to reception of <i>MasterInformationBlock-SL/ MasterInformationBlock-SL-V2X</i> message	240
5.10.10	Sidelink relay UE operation.....	240
5.10.10.1	General.....	240
5.10.10.2	AS-conditions for relay related sidelink communication transmission by sidelink relay UE	240
5.10.10.3	AS-conditions for relay PS related sidelink discovery transmission by sidelink relay UE	240
5.10.10.4	Sidelink relay UE threshold conditions.....	241
5.10.11	Sidelink remote UE operation.....	241
5.10.11.1	General.....	241
5.10.11.2	AS-conditions for relay related sidelink communication transmission by sidelink remote UE	241
5.10.11.3	AS-conditions for relay PS related sidelink discovery transmission by sidelink remote UE	242
5.10.11.4	Selection and reselection of sidelink relay UE.....	242
5.10.11.5	Sidelink remote UE threshold conditions.....	242
5.10.12	V2X sidelink communication monitoring.....	243
5.10.13	V2X sidelink communication transmission	243
5.10.13.1	Transmission of V2X sidelink communication.....	243
5.10.13.1a	Transmission of P2X related V2X sidelink communication	246
5.10.13.2	V2X sidelink communication transmission pool selection	246
5.10.13.3	V2X sidelink communication transmission reference cell selection.....	248
5.10.14	DFN derivation from GNSS	248

6	Protocol data units, formats and parameters (tabular & ASN.1)	249
6.1	General	249
6.2	RRC messages	250
6.2.1	General message structure	251
–	EUTRA-RRC-Definitions	251
–	BCCH-BCH-Message	251
–	BCCH-BCH-Message-MBMS	251
–	BCCH-DL-SCH-Message	251
–	BCCH-DL-SCH-Message-BR	252
–	BCCH-DL-SCH-Message-MBMS	252
–	MCCH-Message	252
–	PCCH-Message	253
–	DL-CCCH-Message	253
–	DL-DCCH-Message	253
–	UL-CCCH-Message	254
–	UL-DCCH-Message	254
–	SC-MCCH-Message	255
6.2.2	Message definitions	255
–	CounterCheck	255
–	CounterCheckResponse	256
–	CSFBParametersRequestCDMA2000	257
–	CSFBParametersResponseCDMA2000	257
–	DLInformationTransfer	258
–	HandoverFromEUTRAPreparationRequest (CDMA2000)	258
–	InDeviceCoexIndication	260
–	InterFreqRSTDMeasurementIndication	262
–	LoggedMeasurementConfiguration	264
–	MasterInformationBlock	265
–	MasterInformationBlock-MBMS	266
–	MBMSCountingRequest	266
–	MBMSCountingResponse	267
–	MBMSInterestIndication	268
–	MBSFNAreaConfiguration	268
–	MeasurementReport	269
–	MobilityFromEUTRACommand	270
–	Paging	273
–	ProximityIndication	274
–	RNReconfiguration	275
–	RNReconfigurationComplete	275
–	RRCCConnectionReconfiguration	276
–	RRCCConnectionReconfigurationComplete	282
–	RRCCConnectionReestablishment	283
–	RRCCConnectionReestablishmentComplete	284
–	RRCCConnectionReestablishmentReject	285
–	RRCCConnectionReestablishmentRequest	285
–	RRCCConnectionReject	286
–	RRCCConnectionRelease	287
–	RRCCConnectionRequest	291
–	RRCCConnectionResume	291
–	RRCCConnectionResumeComplete	292
–	RRCCConnectionResumeRequest	293
–	RRCCConnectionSetup	293
–	RRCCConnectionSetupComplete	294
–	SCGFailureInformation	296
–	SCPTMConfiguration	297
–	SCPTMConfiguration-BR	298
–	SecurityModeCommand	298
–	SecurityModeComplete	299
–	SecurityModeFailure	299
–	SidelinkUEInformation	300
–	SystemInformation	303
–	SystemInformationBlockType1	303

–	SystemInformationBlockType1-MBMS	310
–	UEAssistanceInformation	312
–	UECapabilityEnquiry	314
–	UECapabilityInformation	316
–	UEInformationRequest	317
–	UEInformationResponse	317
–	ULHandoverPreparationTransfer (CDMA2000)	323
–	ULInformationTransfer	324
–	WLANConnectionStatusReport	324
6.3	RRC information elements	325
6.3.1	System information blocks	325
–	SystemInformationBlockType2	325
–	SystemInformationBlockType3	329
–	SystemInformationBlockType4	333
–	SystemInformationBlockType5	334
–	SystemInformationBlockType6	339
–	SystemInformationBlockType7	342
–	SystemInformationBlockType8	343
–	SystemInformationBlockType9	347
–	SystemInformationBlockType10	347
–	SystemInformationBlockType11	348
–	SystemInformationBlockType12	349
–	SystemInformationBlockType13	349
–	SystemInformationBlockType14	350
–	SystemInformationBlockType15	350
–	SystemInformationBlockType16	352
–	SystemInformationBlockType17	352
–	SystemInformationBlockType18	353
–	SystemInformationBlockType19	354
–	SystemInformationBlockType20	357
–	SystemInformationBlockType21	360
6.3.2	Radio resource control information elements	361
–	AntennaInfo	361
–	AntennaInfoUL	363
–	CQI-ReportAperiodic	364
–	CQI-ReportBoth	367
–	CQI-ReportConfig	368
–	CQI-ReportPeriodic	370
–	CQI-ReportPeriodicProcExtId	373
–	CrossCarrierSchedulingConfig	373
–	CSI-IM-Config	374
–	CSI-IM-ConfigId	375
–	CSI-Process	375
–	CSI-ProcessId	376
–	CSI-RS-Config	377
–	CSI-RS-ConfigBeamformed	378
–	CSI-RS-ConfigEMIMO	379
–	CSI-RS-ConfigNonPrecoded	380
–	CSI-RS-ConfigNZP	381
–	CSI-RS-ConfigNZPId	382
–	CSI-RS-ConfigZP	383
–	CSI-RS-ConfigZPId	383
–	DataInactivityTimer	383
–	DMRS-Config	384
–	DRB-Identity	384
–	EPDCCH-Config	384
–	EIMTA-MainConfig	386
–	LogicalChannelConfig	387
–	LWA-Configuration	388
–	LWIP-Configuration	389
–	MAC-MainConfig	389
–	P-C-AndCBSR	395

–	PDCCH-ConfigSCell	396
–	PDCH-Config	397
–	PDSCH-Config	400
–	PDSCH-RE-MappingQCL-ConfigId	402
–	PerCC-GapIndicationList	403
–	PHICH-Config	403
–	PhysicalConfigDedicated	403
–	P-Max	411
–	PRACH-Config	412
–	PresenceAntennaPort1	415
–	PUCCH-Config	415
–	PUSCH-Config	420
–	RACH-ConfigCommon	426
–	RACH-ConfigDedicated	428
–	RadioResourceConfigCommon	428
–	RadioResourceConfigDedicated	433
–	RCLWI-Configuration	439
–	RLC-Config	440
–	RLF-TimersAndConstants	442
–	RN-SubframeConfig	443
–	SchedulingRequestConfig	444
–	SoundingRS-UL-Config	445
–	SPS-Config	448
–	SRS-TPC-PDCCH-Config	452
–	TDD-Config	453
–	TimeAlignmentTimer	454
–	TPC-PDCCH-Config	454
–	TunnelConfigLWIP	455
–	UplinkPowerControl	455
–	WLAN-Id-List	459
–	WLAN-MobilityConfig	459
6.3.3	Security control information elements	460
–	NextHopChainingCount	460
–	SecurityAlgorithmConfig	460
–	ShortMAC-I	460
6.3.4	Mobility control information elements	461
–	AdditionalSpectrumEmission	461
–	ARFCN-ValueCDMA2000	461
–	ARFCN-ValueEUTRA	461
–	ARFCN-ValueGERAN	462
–	ARFCN-ValueUTRA	462
–	BandclassCDMA2000	462
–	BandIndicatorGERAN	462
–	CarrierFreqCDMA2000	462
–	CarrierFreqGERAN	463
–	CarrierFreqsGERAN	463
–	CarrierFreqListMBMS	464
–	CDMA2000-Type	464
–	CellIdentity	464
–	CellIndexList	464
–	CellReselectionPriority	465
–	CellSelectionInfoCE	465
–	CellSelectionInfoCE1	465
–	CellReselectionSubPriority	466
–	CSFB-RegistrationParam1XRTT	466
–	CellGlobalIdEUTRA	467
–	CellGlobalIdUTRA	467
–	CellGlobalIdGERAN	468
–	CellGlobalIdCDMA2000	468
–	CellSelectionInfoNFreq	469
–	CSG-Identity	469
–	FreqBandIndicator	469