



**5G;
NR;
Base Station (BS) conformance testing Part 2: Radiated
conformance testing
(3GPP TS 38.141-2 version 15.2.0 Release 15)**



ReferenceRTS/TSGR-0438141-2v120

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	14
1 Scope	15
2 References	15
3 Definitions, symbols and abbreviations	17
3.1 Definitions	17
3.2 Symbols.....	20
3.3 Abbreviations	22
4 General radiated test conditions and declarations	24
4.1 Measurement uncertainties and test requirements	24
4.1.1 General.....	24
4.1.2 Acceptable uncertainty of OTA Test System	26
4.1.2.1 General	26
4.1.2.2 Measurement of transmitter	27
4.1.2.3 Measurement of receiver	30
4.1.2.4 Measurement of performance requirement	31
4.1.3 Interpretation of measurement results	32
4.2 Radiated requirement reference points	33
4.3 Base station classes	34
4.4 Regional requirements.....	34
4.5 BS configurations	35
4.5.1 Transmit configurations	35
4.5.2 Receive configurations	36
4.5.3 Power supply options.....	37
4.5.4 BS with integrated Iuant BS modem	37
4.6 Manufacturer's declarations	37
4.7 Test configurations	45
4.7.1 General.....	45
4.7.2 Test signal configurations	46
4.7.2.1 Test signal used to build Test Configurations	46
4.7.2.2 NRTC1: Contiguous spectrum operation	46
4.7.2.2.1 NRTC1 generation.....	46
4.7.2.2.2 NRTC1 power allocation.....	47
4.7.2.3 NRTC2: Contiguous CA occupied bandwidth	47
4.7.2.3.1 NRTC2 generation.....	47
4.7.2.3.2 NRTC2 power allocation.....	47
4.7.2.4 NRTC3: Non-contiguous spectrum operation.....	48
4.7.2.4.1 NRTC3 generation.....	48
4.7.2.4.2 NRTC3 power allocation.....	48
4.7.2.5 NRTC4: Multi-band test configuration for full carrier allocation	48
4.7.2.5.1 NRTC4 generation.....	48
4.7.2.5.2 NRTC4 power allocation.....	49
4.7.2.6 NRTC5: Multi-band test configuration with high PSD per carrier	49
4.7.2.6.1 NRTC5 generation.....	49
4.7.2.6.2 NRTC5 power allocation.....	50
4.8 Applicability of requirements.....	50
4.8.1 Requirement set applicability	50
4.8.2 Applicability of test configurations for <i>single-band RIB</i>	50
4.8.3 Applicability of test configurations for <i>multi-band RIB</i>	51
4.9 RF channels and test models	52
4.9.1 RF channels	52
4.9.2 Test models	53

4.9.2.1	General	53
4.9.2.2	NR FR2 test models	53
4.9.2.2.1	NR FR2 test model 1.1 (NR-FR2-TM1.1).....	55
4.9.2.2.2	NR FR2 test model 2 (NR-FR2-TM2).....	55
4.9.2.2.3	NR FR2 test model 3.1 (NR-FR2-TM3.1).....	56
4.9.2.3	Data content of physical channels and signals for NR-FR2-TM.....	56
4.9.2.3.1	PDCCH.....	56
4.9.2.3.2	PDSCH	57
4.10	Requirements for contiguous and non-contiguous spectrum.....	57
4.11	Requirements for BS capable of multi-band operation	58
4.12	Co-location requirements	58
4.12.1	General.....	58
4.12.2	Co-location test antenna.....	59
4.12.2.1	General	59
4.12.2.2	Co-location test antenna characteristics	59
4.12.2.3	Co-location test antenna alignment	59
4.13	Format and interpretation of tests.....	60
4.14	Reference coordinate system.....	61
5	Operating bands and channel arrangement.....	63
6	Radiated transmitter characteristics.....	64
6.1	General	64
6.2	Radiated transmit power.....	64
6.2.1	Definition and applicability	64
6.2.2	Minimum requirement	64
6.2.3	Test purpose.....	65
6.2.4	Method of test	65
6.2.4.1	Initial conditions	65
6.2.4.2	Procedure	65
6.2.5	Test requirement	66
6.3	OTA base station output power.....	66
6.3.1	Definition and applicability.....	66
6.3.2	Minimum requirement	66
6.3.3	Test purpose.....	67
6.3.4	Method of test	67
6.3.4.1	Initial conditions	67
6.3.4.2	Procedure	67
6.3.5	Test requirement	68
6.3.5.1	BS type 1-O	68
6.3.5.2	BS type 2-O	68
6.4	OTA output power dynamics	68
6.4.1	General.....	68
6.4.2	OTA RE power control dynamic range	68
6.4.2.1	Definition and applicability.....	68
6.4.2.2	Minimum requirement	68
6.4.2.3	Method of test	68
6.4.3	OTA total power dynamic range.....	69
6.4.3.1	Definition and applicability.....	69
6.4.3.2	Minimum requirement	69
6.4.3.3	Test purpose	69
6.4.3.4	Method of test	69
6.4.3.4.1	Initial conditions.....	69
6.4.3.4.2	Procedure.....	69
6.4.3.5	Test requirement	70
6.4.3.5.1	BS type 1-O.....	70
6.4.3.5.2	BS type 2-O.....	71
6.5	OTA transmit ON/OFF power.....	71
6.5.1	OTA transmitter OFF power.....	71
6.5.1.1	Definition and applicability.....	71
6.5.1.2	Minimum requirement	72
6.5.1.3	Test purpose	72

6.5.1.4	Method of test	72
6.5.1.5	Test requirements	72
6.5.2	OTA transmitter transient period	72
6.5.2.1	Definition and applicability	72
6.5.2.2	Minimum requirement	72
6.5.2.3	Test purpose	73
6.5.2.4	Method of test	73
6.5.2.4.1	Initial conditions	73
6.5.2.4.2	Procedure	73
6.5.2.4.2.1	General procedure	73
6.5.2.4.2.2	BS type 1-O	73
6.5.2.4.2.3	BS type 2-O	74
6.5.2.5	Test requirements	74
6.5.2.5.1	BS type 1-O	74
6.5.2.5.2	BS type 2-O	74
6.6	OTA transmitted signal quality	75
6.6.1	General	75
6.6.2	OTA frequency error	75
6.6.2.1	Definition and applicability	75
6.6.2.2	Minimum Requirement	75
6.6.2.3	Test purpose	75
6.6.2.4	Method of test	75
6.6.2.4.1	Initial conditions	75
6.6.2.5	Test Requirements	75
6.6.3	OTA modulation quality	75
6.6.3.1	Definition and applicability	75
6.6.3.2	Minimum Requirement	76
6.6.3.3	Test purpose	76
6.6.3.4	Method of test	76
6.6.3.4.1	Initial conditions	76
6.6.3.4.2	Procedure	76
6.6.3.5	Test requirements	77
6.6.3.5.1	BS type 1-O	77
6.6.3.5.2	BS type 2-O	79
6.6.4	OTA time alignment error	80
6.6.4.1	Definition and applicability	80
6.6.4.2	Minimum requirement	80
6.6.4.3	Test purpose	80
6.6.4.4	Method of test	80
6.6.4.4.1	Initial conditions	80
6.6.4.4.2	Procedure	81
6.6.4.5	Test Requirement	81
6.6.4.5.1	BS type 1-O	81
6.6.4.5.2	BS type 2-O	81
6.7	OTA unwanted emissions	82
6.7.1	General	82
6.7.2	OTA occupied bandwidth	82
6.7.2.1	Definition and applicability	82
6.7.2.2	Minimum requirement	82
6.7.2.3	Test purpose	83
6.7.2.4	Method of test	83
6.7.2.4.1	Initial conditions	83
6.7.2.4.2	Procedure	83
6.7.2.5	Test requirement	84
6.7.2.5.1	BS type 1-O	84
6.7.2.5.2	BS type 2-O	85
6.7.3	OTA Adjacent Channel Leakage Power Ratio (ACLR)	85
6.7.3.1	Definition and applicability	85
6.7.3.2	Minimum requirement	85
6.7.3.3	Test purpose	85
6.7.3.4	Method of test	85
6.7.3.4.1	Initial conditions	85

6.7.3.4.2	Procedure.....	85
6.7.3.5	Test requirements.....	86
6.7.3.5.1	BS type 1-O.....	86
6.7.3.5.2	BS type 2-O.....	89
6.7.4	OTA operating band unwanted emissions	92
6.7.4.1	Definition and applicability.....	92
6.7.4.2	Minimum requirement	92
6.7.4.3	Test purpose	92
6.7.4.4	Method of test	92
6.7.4.4.1	Initial conditions.....	92
6.7.4.4.2	Procedure.....	92
6.7.4.5	Test requirements.....	93
6.7.4.5.1	BS type 1-O.....	93
6.7.4.5.1.1	Wide Area BS (Category A).....	94
6.7.4.5.1.2	Wide Area BS Category B (Option 1)	96
6.7.4.5.1.3	Wide Area BS Category B (Option 2)	98
6.7.4.5.1.4	Medium Range BS (Category A and Category B).....	98
6.7.4.5.1.5	Local Area BS (Category A and Category B).....	101
6.7.4.5.1.6	Additional requirements.....	103
6.7.4.5.1.6.1	Limits in FCC Title 47	103
6.7.4.5.1.6.2	Protection of DTT	103
6.7.4.5.2	BS type 2-O.....	104
6.7.4.5.2.1	General.....	104
6.7.4.5.2.2	OTA operating band unwanted emission limits (Category A).....	104
6.7.4.5.2.3	OTA operating band unwanted emission limits (Category B).....	105
6.7.5	OTA transmitter spurious emissions.....	105
6.7.5.1	General	105
6.7.5.2	General OTA transmitter spurious emissions requirements.....	106
6.7.5.2.1	Definition and applicability	106
6.7.5.2.2	Minimum requirement	106
6.7.5.2.3	Test purpose	106
6.7.5.2.4	Method of test.....	106
6.7.5.2.4.1	Initial conditions	106
6.7.5.2.4.2	Procedure	107
6.7.5.2.5	Test requirement.....	108
6.7.5.2.5.1	Test requirement for BS type 1-O	108
6.7.5.2.5.2	Test requirement for BS type 2-O	108
6.7.5.2.5.2.1	General.....	108
6.7.5.2.5.2.2	OTA transmitter spurious emissions (Category A).....	109
6.7.5.2.5.2.3	OTA transmitter spurious emissions (Category B).....	109
6.7.5.3	Protection of the BS receiver of own or different BS	109
6.7.5.3.1	Definition and applicability	109
6.7.5.3.2	Minimum requirements	110
6.7.5.3.3	Test purpose	110
6.7.5.3.4	Method of test.....	110
6.7.5.3.4.1	Initial conditions	110
6.7.5.3.4.2	Procedure	110
6.7.5.3.5	Test requirements	111
6.7.5.3.5.1	Test requirement for BS type 1-O	111
6.7.5.4	Additional spurious emissions requirements.....	111
6.7.5.4.1	Definition and applicability.....	111
6.7.5.4.2	Minimum Requirement	111
6.7.5.4.3	Test purpose	112
6.7.5.4.4	Method of test.....	112
6.7.5.4.4.1	Initial conditions	112
6.7.5.4.4.2	Procedure	112
6.7.5.4.5	Test requirement.....	113
6.7.5.4.5.1	Test requirement for BS type 1-O	113
6.7.5.5	Co-location requirements.....	118
6.7.5.5.1	Definition and applicability.....	118
6.7.5.5.2	Minimum requirements	118
6.7.5.5.3	Test purpose	118

6.7.5.5.4	Method of test.....	118
6.7.5.5.4.1	Initial conditions	118
6.7.5.5.4.2	Procedure	119
6.7.5.5.5	Test requirements	119
6.7.5.5.5.1	Test requirement for <i>BS type 1-O</i>	119
6.8	OTA transmitter intermodulation	124
6.8.1	Definition and applicability	124
6.8.2	Minimum requirement	125
6.8.3	Test purpose.....	125
6.8.4	Method of test	125
6.8.4.1	Initial conditions	125
6.8.4.2	Procedure	125
6.8.5	Test requirements.....	127
6.8.5.1	Requirement for <i>BS type 1-O</i>	127
7	Radiated receiver characteristics	128
7.1	General	128
7.2	OTA sensitivity	128
7.2.1	Definition and applicability	128
7.2.2	Minimum requirement	129
7.2.3	Test Purpose.....	129
7.2.4	Method of test	129
7.2.4.1	Initial conditions	129
7.2.4.2	Procedure	129
7.2.5	Test requirements.....	130
7.2.5.1	General	130
7.2.5.2	Test requirements for <i>BS type 1-H</i> and <i>BS type 1-O</i>	130
7.2.5.3	Test requirements for <i>BS type 2-O</i>	130
7.3	OTA reference sensitivity level.....	130
7.3.1	Definition and applicability	130
7.3.2	Minimum requirement	131
7.3.3	Test Purpose.....	131
7.3.4	Method of test	131
7.3.4.1	Initial conditions	131
7.3.4.2	Procedure	131
7.3.5	Test requirements.....	132
7.3.5.1	General	132
7.3.5.2	Test requirements for <i>BS type 1-O</i>	132
7.3.5.3	Test requirements for <i>BS type 2-O</i>	133
7.4	OTA dynamic range	134
7.4.1	Definition and applicability	134
7.4.2	Minimum requirement	134
7.4.3	Test purpose.....	134
7.4.4	Method of test	134
7.4.4.1	Initial conditions	134
7.4.4.2	Procedure	135
7.4.5	Test requirement	135
7.4.5.1	General	135
7.4.5.2	Test requirements for <i>BS type 1-O</i>	135
7.5	OTA in-band selectivity and blocking.....	144
7.5.1	OTA adjacent channel selectivity.....	144
7.5.1.1	Definition and applicability.....	144
7.5.1.2	Minimum requirement	144
7.5.1.3	Test purpose	144
7.5.1.4	Method of test	144
7.5.1.4.1	Initial conditions	144
7.5.1.4.2	Procedure.....	144
7.5.1.5	Test requirement	145
7.5.1.5.1	General	145
7.5.1.5.2	Test requirements for <i>BS type 1-O</i>	145
7.5.1.5.3	Test requirements for <i>BS type 2-O</i>	146
7.5.2	OTA in-band blocking.....	147

7.5.2.1	Definition and applicability	147
7.5.2.2	Minimum requirement	147
7.5.2.3	Test purpose	147
7.5.2.4	Method of test	147
7.5.2.4.1	Initial conditions	147
7.5.2.4.2	Procedure	148
7.5.2.5	Test requirement	148
7.5.2.5.1	General	148
7.5.2.5.2	Test requirements for <i>BS type 1-O</i>	149
7.5.2.5.3	Test requirements for <i>BS type 2-O</i>	152
7.6	OTA out-of-band blocking	153
7.6.1	Definition and applicability	153
7.6.2	Minimum requirement	153
7.6.3	Test purpose	153
7.6.4	Method of test	153
7.6.4.1	Initial conditions	153
7.6.4.2	Procedure	154
7.6.4.2.1	<i>BS type 1-O</i> procedure for out-of-band blocking	154
7.6.4.2.2	<i>BS type 1-O</i> procedure for co-location blocking	154
7.6.4.2.3	<i>BS type 2-O</i> procedure for out-of-band blocking	155
7.6.5	Test requirements	156
7.6.5.1	Requirement for <i>BS type 1-O</i>	156
7.6.5.1.1	General	156
7.6.5.1.2	Co-location requirement	156
7.6.5.2	Requirement for <i>BS type 2-O</i>	157
7.6.5.2.1	General requirement	157
7.7	OTA receiver spurious emissions	157
7.7.1	Definition and applicability	157
7.7.2	Minimum requirement	158
7.7.3	Test purpose	158
7.7.4	Method of test	158
7.7.4.1	Initial conditions	158
7.7.4.2	Procedure	159
7.7.5	Test requirement	159
7.7.5.1	Test requirement for <i>BS type 1-O</i>	159
7.7.5.2	Test requirement for <i>BS type 2-O</i>	160
7.8	OTA receiver intermodulation	160
7.8.1	Definition and applicability	160
7.8.2	Minimum requirement	160
7.8.3	Test purpose	161
7.8.4	Method of test	161
7.8.4.1	Initial conditions	161
7.8.4.2	Procedure	161
7.8.5	Test requirement	162
7.8.5.1	<i>BS type 1-O</i>	162
7.8.5.2	<i>BS type 2-O</i>	166
7.9	OTA in-channel selectivity	166
7.9.1	Definition and applicability	166
7.9.2	Minimum requirement	166
7.9.3	Test purpose	167
7.9.4	Method of test	167
7.9.4.1	Initial conditions	167
7.9.4.2	Procedure	167
7.9.5	Test requirement	168
7.9.5.1	<i>BS type 1-O</i>	168
7.9.5.2	<i>BS type 2-O</i>	170
8	Radiated performance requirements	171
8.1	General	171
8.1.0	Scope and definitions	171
8.1.1	OTA demodulation branches	171
8.1.2	Applicability rule	172

8.1.2.0	General	172
8.1.2.1	Applicability of PUSCH performance requirements	172
8.1.2.1.1	Applicability of requirements for different subcarrier spacings	172
8.1.2.1.2	Applicability of requirements for different channel bandwidths	172
8.1.2.1.3	Applicability of requirements for different configurations	172
8.1.2.2	Applicability of PUCCH performance requirements	172
8.1.2.2.1	Applicability of requirements for different formats	172
8.1.2.2.2	Applicability of requirements for different subcarrier spacings	172
8.1.2.2.3	Applicability of requirements for different channel bandwidths	172
8.1.2.2.4	Applicability of requirements for different configurations	173
8.1.2.2.5	Applicability of requirements for multi-slot PUCCH	173
8.1.2.3	Applicability of PRACH performance requirements	173
8.1.2.3.1	Applicability of requirements for different formats	173
8.1.2.3.2	Applicability of requirements for different subcarrier spacings	173
8.1.2.3.3	Applicability of requirements for different channel bandwidths	173
8.2	OTA performance requirements for PUSCH	173
8.2.1	Performance requirements for PUSCH with transform precoding disabled	173
8.2.1.1	Definition and applicability	173
8.2.1.2	Minimum Requirement	173
8.2.1.3	Test purpose	173
8.2.1.4	Method of test	174
8.2.1.4.1	Initial conditions	174
8.2.1.4.2	Procedure	174
8.2.1.5	Test Requirement	175
8.2.1.5.1	Test requirement for BS type 1-O	175
8.2.1.5.2	Test requirement for BS type 2-O	178
8.2.2	Performance requirements for PUSCH with transform precoding enabled	182
8.2.2.1	Definition and applicability	182
8.2.2.2	Minimum Requirement	182
8.2.2.3	Test Purpose	182
8.2.2.4	Method of test	182
8.2.2.4.1	Initial Conditions	182
8.2.2.4.2	Procedure	182
8.2.2.5	Test Requirement	184
8.2.2.5.1	Test requirement for BS type 1-O	184
8.2.2.5.2	Test requirement for BS type 2-O	184
8.2.3	Performance requirements for UCI multiplexed on PUSCH	185
8.2.3.1	Definition and applicability	185
8.2.3.2	Minimum Requirement	185
8.2.3.3	Test purpose	186
8.2.3.4	Method of test	186
8.2.3.4.1	Initial conditions	186
8.2.3.4.2	Procedure	186
8.2.3.5	Test Requirement	188
8.2.3.5.1	Test requirement for BS type 1-O	188
8.2.3.5.2	Test requirement for BS type 2-O	189
8.3	OTA performance requirements for PUCCH	190
8.3.1	Performance requirements for PUCCH format 0	190
8.3.1.1	Definition and applicability	190
8.3.1.2	Minimum Requirement	190
8.3.1.3	Test purpose	191
8.3.1.4	Method of test	191
8.3.1.4.1	Initial conditions	191
8.3.1.4.2	Procedure	191
8.3.1.5	Test Requirement	192
8.3.1.5.1	Test requirement for BS type 1-O	192
8.3.1.5.2	Test requirement for BS type 2-O	192
8.3.2	Performance requirements for PUCCH format 1	193
8.3.2.1	NACK to ACK detection	193
8.3.2.1.1	Definition and applicability	193
8.3.2.1.2	Minimum Requirement	193
8.3.2.1.3	Test purpose	193

8.3.2.1.4	Method of test.....	193
8.3.2.1.4.1	Initial Conditions	193
8.3.2.1.4.2	Procedure	194
8.3.2.1.5	Test Requirement.....	195
8.3.2.1.5.1	Test Requirement for <i>BS type 1-O</i>	195
8.3.2.1.5.2	Test Requirement for <i>BS type 2-O</i>	195
8.3.2.2	ACK missed detection.....	196
8.3.2.2.1	Definition and applicability	196
8.3.2.2.2	Minimum Requirement	196
8.3.2.2.3	Test purpose	196
8.3.2.2.4	Method of test.....	196
8.3.2.2.4.1	Initial Conditions	196
8.3.2.2.4.2	Procedure	196
8.3.2.2.5	Test Requirement.....	198
8.3.2.1.5.1	Test Requirement for <i>BS type 1-O</i>	198
8.3.2.2.5.2	Test Requirement for <i>BS type 2-O</i>	198
8.3.3	Performance requirements for PUCCH format 2.....	198
8.3.3.1	ACK missed detection performance requirements.....	198
8.3.3.1.1	Definition and applicability	198
8.3.3.1.2	Minimum Requirement	199
8.3.3.1.3	Test Purpose	199
8.3.3.1.4	Method of test.....	199
8.3.3.1.4.1	Initial conditions	199
8.3.3.1.4.2	Procedure	199
8.3.3.1.5	Test requirement.....	200
8.3.3.1.5.1	Requirements for <i>BS type 1-O</i>	200
8.3.3.1.5.2	Requirements for <i>BS type 2-O</i>	201
8.3.3.2	UCI BLER performance requirements.....	201
8.3.3.2.1	Definition and applicability	201
8.3.3.2.2	Minimum Requirement	201
8.3.3.2.3	Test Purpose	201
8.3.3.2.4	Method of test.....	201
8.3.3.2.4.1	Initial conditions	201
8.3.3.2.4.2	Procedure	202
8.3.3.2.5	Test requirement.....	203
8.3.3.2.5.1	Requirements for <i>BS type 1-O</i>	203
8.3.3.2.5.2	Requirements for <i>BS type 2-O</i>	203
8.3.4	Performance requirements for PUCCH format 3.....	204
8.3.4.1	Definition and applicability.....	204
8.3.4.2	Minimum requirement	204
8.3.4.3	Test purpose	204
8.3.4.4	Method of test	204
8.3.4.4.1	Initial conditions.....	204
8.3.4.4.2	Procedure.....	205
8.3.4.5	Test requirement	206
8.3.4.5.1	Test requirement for <i>BS type 1-O</i>	206
8.3.4.5.2	Test requirement for <i>BS type 2-O</i>	206
8.3.5	Performance requirements for PUCCH format 4.....	207
8.3.5.1	Definition and applicability.....	207
8.3.5.2	Minimum requirement	207
8.3.5.3	Test purpose	207
8.3.5.4	Method of test	207
8.3.5.4.1	Initial conditions.....	207
8.3.5.4.2	Procedure.....	207
8.3.5.5	Test requirement	209
8.3.5.5.1	Test requirement for <i>BS type 1-O</i>	209
8.3.5.5.2	Test requirement for <i>BS type 2-O</i>	209
8.4	OTA performance requirements for PRACH.....	210
8.4.1	PRACH false alarm probability and missed detection.....	210
8.4.1.1	Definition and applicability.....	210
8.4.1.2	Minimum requirement	210
8.4.1.3	Test purpose	210

8.4.1.4	Method of test	210
8.4.1.4.1	Initial conditions	210
8.4.1.4.2	Procedure	211
8.4.1.5	Test requirement	212
8.4.1.5.1	Test requirement for <i>BS type 1-O</i>	212
8.4.1.5.2	Test requirement for <i>BS type 2-O</i>	213
Annex A (normative):	Reference measurement channels	214
A.1	Fixed Reference Channels for OTA sensitivity, OTA reference sensitivity level, OTA ACS, OTA in-band blocking, OTA out-of-band blocking, OTA receiver intermodulation and OTA in-channel selectivity (QPSK, R=1/3)	214
A.2	Fixed Reference Channels for OTA dynamic range (16QAM, R=2/3)	215
A.3	Fixed Reference Channels for performance requirements (QPSK, R=193/1024)	216
A.4	Fixed Reference Channels for performance requirements (16QAM, R=658/1024)	221
A.5	Fixed Reference Channels for performance requirements (64QAM, R=567/1024)	224
A.6	PRACH Test preambles	226
Annex B (normative):	Environmental requirements for the BS equipment	227
B.1	General	227
B.2	Normal test environment	227
B.3	Extreme test environment	227
B.3.1	Extreme temperature	227
B.4	Vibration	228
B.5	Power supply	228
B.6	Measurement of test environments	228
B.7	OTA extreme test methods	229
B.7.1	Direct far field method	229
B.7.2	Relative method	229
Annex C (informative):	Test tolerances and derivation of test requirements	231
C.1	Measurement of transmitter	232
C.2	Measurement of receiver	235
C.3	Measurement of performance requirements	237
Annex D (normative):	Calibration	238
Annex E (informative):	OTA measurement system set-up	239
E.1	Transmitter	239
E.1.1	Radiated transmit power, OTA output power dynamics, OTA transmitted signal quality, OTA occupied bandwidth, and OTA transmit ON/OFF power (<i>BS type 2-O</i>)	239
E.1.2	OTA base station output power, OTA ACLR, OTA operating band unwanted emissions	240
E.1.3	OTA spurious emissions	240
E.1.4	OTA co-location emissions, OTA transmit ON/OFF power (<i>BS type 1-O</i>)	241
E.1.5	OTA transmitter intermodulation	242
E.2	Receiver	243
E.2.1	OTA sensitivity and OTA reference sensitivity level	243
E.2.2	OTA dynamic range	243
E.2.3	OTA adjacent channel selectivity, general OTA blocking, and OTA narrowband blocking	244
E.2.4	OTA blocking	245
E.2.4.1	General OTA out-of-band blocking	245
E.2.4.2	OTA co-location blocking	246

E.2.5	OTA receiver spurious emissions.....	246
E.2.6	OTA receiver intermodulation	247
E.2.7	OTA in-channel selectivity.....	247
E.3	Performance requirements.....	248
Annex F (normative):	Void	249
Annex G (informative):	Transmitter spatial emissions declaration.....	250
G.1	General	250
G.2	Declarations.....	250
Annex H (normative):	Characteristics of the interfering signals.....	252
Annex I (normative):	TRP measurement procedures	253
I.1	General	253
I.2	Spherical equal angle grid	253
I.2.1	General	253
I.2.2	Reference angular step criteria	253
I.3	Spherical equal area grid	255
I.4	Spherical Fibonacci grid.....	255
I.5	Orthogonal cut grid	256
I.6	Wave vector space grid	257
I.7	Orthogonal 2 cuts with pattern multiplication.....	257
I.8	Orthogonal 2 or 3 cut with dense sampling.....	258
I.8.1	Operating band unwanted emissions.....	258
I.8.2	Spurious unwanted emissions.....	258
I.9	Full sphere with sparse sampling	258
I.10	Beam-based directions	259
I.11	Peak method	259
I.12	Equal sector with peak average.....	259
I.13	Pre-scan	259
Annex J (normative):	Propagation conditions.....	261
J.1	Static propagation condition.....	261
J.2	Multi-path fading propagation conditions	261
J.2.1	Delay profiles	261
J.2.1.1	Delay profiles for FR1	262
J.2.1.2	Delay profiles for FR2	263
J.2.2	Combinations of channel model parameters	264
J.2.3	MIMO channel correlation matrices.....	264
J.2.3.1	MIMO correlation matrices using Uniform Linear Array	264
J.2.3.1.1	Definition of MIMO correlation matrices	264
J.2.3.1.2	MIMO correlation matrices at high, medium and low level	266
J.2.3.2	Multi-antenna channel models using cross polarized antennas.....	268
J.2.3.2.1	Definition of MIMO correlation matrices using cross polarized antennas.....	268
J.2.3.2.2	Spatial correlation matrices at UE and gNB sides.....	269
J.2.3.2.2.1	Spatial correlation matrices at UE side.....	269
J.2.3.2.2.2	Spatial correlation matrices at gNB side	269
J.2.3.2.3	MIMO correlation matrices using cross polarized antennas	269
Annex K (informative):	Measuring noise close to noise-floor.....	271