



**Publicly Available Specification (PAS);  
Intelligent Transport Systems (ITS);  
MirrorLink®;  
Part 7: GPS Data Service**

**CAUTION**

The present document has been submitted to ETSI as a PAS produced by CCC and approved by the ETSI Technical Committee Intelligent Transport Systems (ITS).

CCC is owner of the copyright of the document CCC-TS-020 and/or had all relevant rights and had assigned said rights to ETSI on an "as is basis". Consequently, to the fullest extent permitted by law, ETSI disclaims all warranties whether express, implied, statutory or otherwise including but not limited to merchantability, non-infringement of any intellectual property rights of third parties. No warranty is given about the accuracy and the completeness of the content of the present document.

## Reference

RTS/ITS-98-7

## Keywords

interface, ITS, PAS, smartphone

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

**Important notice**

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

©ETSI 2019.

© Car Connectivity Consortium 2011-2019.

All rights reserved.

ETSI logo is a Trade Mark of ETSI registered for the benefit of its Members.

MirrorLink® is a registered trademark of Car Connectivity Consortium LLC.

RFB® and VNC® are registered trademarks of RealVNC Ltd.

UPnP® is a registered trademark of Open Connectivity Foundation, Inc.

Other names or abbreviations used in the present document may be trademarks of their respective owners.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

**3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

**GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

# Contents

Intellectual Property Rights .....	4
Foreword.....	4
Modal verbs terminology.....	4
1 Scope .....	5
2 References .....	5
2.1 Normative references .....	5
2.2 Informative references.....	5
3 Definition of terms, symbols and abbreviations.....	5
3.1 Terms.....	5
3.2 Symbols.....	5
3.3 Abbreviations .....	6
4 Data Service Definition.....	6
4.1 GPS Data Service Version 1.0.....	6
4.2 GPS Data Service Version 2.0.....	7
5 SBP Binding.....	8
<b>Annex A (informative): Authors and Contributors.....</b>	<b>9</b>
History .....	10

**ITeH STANDARD PREVIEW**  
 (standards.iteh.ai)  
 Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/6a44aa163-4a04-acbc-c5c172544ca2/etsi-ts-103-544-7-v1.3.1-2019-10>

---

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

---

# Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Intelligent Transport Systems (ITS).

The present document is part 7 of a multi-part deliverable. Full details of the entire series can be found in part 1 [i.1].

---

# Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

# 1 Scope

The present document is part of the MirrorLink® specification which specifies an interface for enabling remote user interaction of a mobile device via another device. The present document is written having a vehicle head-unit to interact with the mobile device in mind, but it will similarly apply for other devices, which provide a colour display, audio input/output and user input mechanisms.

The present document specifies GPS service based on SBP (Service Binary Protocol) framework. The service is used to provide better GPS data in car environments. The present document is based on NMEA specification 0183 [1] as bearer of GPS.

---

## 2 References

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

[1] NMEA 0183 version 3.01 (January 2002): "Standard For Interfacing Marine Electronic Devices".

NOTE: Available at <http://www.plaisance-pratique.com/IMG/pdf/NMEA0183-2.pdf>.

### 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

[i.1] ETSI TS 103 544-1 (V1.3.1): "Publicly Available Specification (PAS); Intelligent Transport Systems (ITS); MirrorLink®; Part 1: Connectivity".

---

## 3 Definition of terms, symbols and abbreviations

### 3.1 Terms

Void.

### 3.2 Symbols

Void.

### 3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

GPS	Global Positioning System
NMEA	National Marine Electronics Association
SBP	Service Binary Protocol

## 4 Data Service Definition

### 4.1 GPS Data Service Version 1.0

```

/** The purpose of GPS service is to provide better GPS data in car
 * environments. The specification relies on NMEA as bearer of GPS
 * data.
 * @version 1.0
 */
SERVICE com.mirrorlink.GPS {
  /** SUPPORTED_SENTENCES
   */
  ENUM<INT> SUPPORTED_SENTENCES {
    /** SUPPORT_GGA
     */
    SUPPORT_GGA = 0x01,
    /** SUPPORT_GLL
     */
    SUPPORT_GLL = 0x02,
    /** SUPPORT_GSA
     */
    SUPPORT_GSA = 0x04,
    /** SUPPORT_GSV
     */
    SUPPORT_GSV = 0x08,
    /** SUPPORT_RMC
     */
    SUPPORT_RMC = 0x10,
    /** SUPPORT_VTG
     */
    SUPPORT_VTG = 0x20,
    /** SUPPORT_GST
     */
    SUPPORT_GST = 0x40
  };
  /** NMEA object carrying NMEA sentence
   * This Object delivers NMEA-0183 v3.0 [1] compatible NMEA strings
   * included in the "data" member variable. Among all NMEA messages,
   * only following 7 messages are supported.
   * - GGA: Global Positioning System Fixed Data
   * - GLL: Geographic Position - Latitude/Longitude
   * - GSA: GNSS DOP and Active Satellites
   * - GSV: GNSS Satellites in View
   * - RMC: Recommended Minimum Specific GNSS Data
   * - VTG: Course Over Ground and Ground Speed
   * - GST: GPS Pseudo Range Noise (PRN) statistics
   * As some NMEA sentences are delivering the same information
   * redundantly, it is not necessary to support all NMEA sentences.
   * It is up to the server implementation to decide necessary
   * combinations. As the Object can be used even for non-GPS-based
   * positioning method, minimum set of messages can be, for example, GLL
   * only. The client for the service can Get NMEA_description object to
   * check which sentences are supported.
   * NMEA object shall support the subscription type of regular interval.
   * The minimum subscription interval of NMEA Object supported by the
   * service server shall be less than or equal to 1 second. In some server
   * implementation, server may decide to send each NMEA sentence as
   * separate SBP message rather than combining them into one message.
   * In that case, subscription interval is not the interval between
   * each sentence, but it should be the interval where the same sentence
   * is repeated. And depending on the situation, some NMEA sentences may
   * NOT be available for some time. For example, if location fix-up is
   * not available yet, server may send only GSV sentence.

```

```

* Note that getting NMEA object may return just one NMEA sentence
* which does not necessarily include positioning data. NMEA object
* is intended for being used with Subscribe command, and sequences
* of NMEA sentences should be monitored to get meaningful information.
* @mandatory, @readable, @version 1.0, @uid 0x0aac4540
*/
Object NMEA {
  /** NMEA sentences
   * NMEA messages as byte array. Multiple NMEA sentences can be
   * combined into single array.
   * @mandatory, @uid 0x144a776f
   */
  BYTES data;
  /** UTC time of data
   * Time stamp of the NMEA data embedded. It is a UTC time associated
   * with the NMEA sentences contained.
   * In case UTC time associated with the NMEA sentence is unknown, the
   * GPS Data Source shall set the timestamp value to zero (0).
   * @mandatory, @uid 0x59413fd1
   */
  TIME timeStamp;
};
/** Provides configuration information of NMEA object
 * The NMEA_description should be accessed before NMEA object is
 * subscribed. Accessing NMEA_description object while NMEA object is
 * accessed may fail depending on server's resource status.
 * @mandatory, @readable, @version: 1.0, @uid 0x9d08b19d
*/
Object NMEA_description {
  /** bit wise OR of supported sentences, as defined in the enumeration
   * ENUM<SUPPORTED_SENTENCES>.
   * The data source implementation shall support at least one active
   * command.
   * @mandatory, @uid 0x6e72b167
   */
  INT supportedSentences;
};
};

```

## 4.2 GPS Data Service Version 2.0

```

SERVICE com.mirrorlink.GPS : @version 1.0 {
  ENUM<INT> definedCoordinateSystem {
    /** WGS-84 coordinate system
     * @mandatory
     */
    CS_WGS84 = 0x00000001;
    /** GCJ-02 coordinate system
     * @optional
     */
    CS_GCJ02 = 0x00000002;
    /** GCJ-02 coordinate system
     * @optional
     */
    CS_Proprietary = 0x80000000;
  };
  /** This object returns bit flags of supported coordinate systems
   * from the Location Data source.
   * @mandatory, @readable, @version 2.0, @uid 0x6f1c2428
  */
  Object availableCoordinateSystems {
    /** Bit wise OR of all supported coordinate systems by the data
     * source. Possible coordinate systems are defined in the
     * definedCoordinateSystem enumeration.
     * This object should be accessed before accessing any of the other
     * objects. A location data source shall support WGS-84, unless the
     * device is operating in China.
     * @mandatory, @uid 0x0885cf07
     */
    int coordinateSystems;
  };
  /** This object contains the currently used coordinate system from the
   * Location Data source. The object can be set from data sink to
   * change the coordinate system.
   * It should be accessed before subscribing to the NMEA
   * object. The object's default value should be cs_WGS-84, unless the

```

```

* device is operating in China, where it may be cs_GCJ02.
* If the object is set to a coordinate system, unknown or not
* supported, the location data source shall indicate the location
* as not being available.
* The coordinate system shall not be changed, after subscription
* to the NMEA object. The location data sink may change the
* coordinate system if it has not subscribed to the NMEA
* object.
* The data source shall honor the selected coordinate system.
* @mandatory, @configurable, @version 2.0, @uid 0x17ab51db
*/
Object currentCoordinateSystem {
/** Provide coordinate system, the source is currently using
* @mandatory, @uid 0xd2394c6c
*/
ENUM<definedCoordinateSystem> coordinateSystem;
};
};

```

## 5 SBP Binding

The GPS Data Services uses the following objects and their access capabilities:

Object Name	Access Type	Subscription Type
NMEA	READABLE	ON_CHANGE, REGULAR, or AUTO
NMEA_description	READABLE	NONE
availableCoordinateSystems	READABLE	NONE
currentCoordinateSystem	CONFIGURABLE	NONE

If the SBP Source endpoint's geolocation sensor is temporarily not available, the SBP Source endpoint shall show the following behaviour within the SBP protocol:

- The SBP Source endpoint shall return an SBP *response* message with a "Not available" SBP error code in response to a SBP *Get* command to the *GeoLocation* object.
- The SBP Source endpoint shall send an SBP *response* message with a "Not available" SBP error code when the SBP Sink endpoint has subscribed to the *GeoLocation* object, either once in case of on-change subscription, or in regular intervals in case of interval subscription. The SBP Source shall provide a valid *GeoLocation* object, as soon as the geolocation sensor becomes available again.
- The SBP Source endpoint shall send an SBP *response* message with a "Not available" SBP error code in response to a SBP *Subscribe* command to the *GeoLocation* object. The SBP Sink endpoint should then send a new *Subscribe* command again not earlier than 5 s and not later than 30 s to receive notifications again.

If the GPS receiver has only lost satellite reception, it should encode this into to NMEA sentences and should not return a "Not available" error code.

The GPS data service shall not be offered and/or advertised, if the GPS receiver is permanently unavailable, e.g. use of GPS receiver is disabled or GPS antenna is missing.

The MirrorLink Client should not provide map-matched coordinates. If available, the MirrorLink Client should use a dead-reckoned position.

The version 2.0 of the GPS service adds a set of new objects, which are not available in version 1.0 version of the service. The SBP protocol can handle this. The following items describe the possible behaviour:

- A version 2.0 sink may try to subscribe or access a version 2.0 object from a version 1.0 source. The version 1.0 source shall always respond with a recoverable SBP Error ("Unknown Object UID").
- A version 1.0 sink may subscribe or access to the NMEA object of a version 2.0 source. In case that source operates in a region, where it cannot provide WGS-84, it shall make the NMEA object "Not available" for the sink.



---

## Annex A (informative): Authors and Contributors

The following people have contributed to the present document:

Rapporteur:	Dr. Jörg Brakensiek, E-Qualus (for Car Connectivity Consortium LLC)
Other contributors:	Keun-Young Park, Nokia Corporation
	Matthias Benesch, Daimler
	Chaminda Basnayake, General Motors
	Robert Hrabak, General Motors
	Kenji Nishimura, Panasonic
	Alfred Tom, General Motors

**ITeH STANDARD PREVIEW**  
(standards.iteh.ai)

Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/cfd26a4a-a163-4a04-acbc-c5c172544ca2/etsi-ts-103-544-7-v1.3.1-2019-10>