



**Smart Cards;
Test specification for the Host Controller Interface (HCI);
Part 2: UICC features
(Release 11)**

iTeh STANDARDS PREVIEW
Full standard
<https://standards.iteh.ai/catalogs/40e9-b921-308d7a9fa568/etsi-ts-102-695-2-v11.0.0-2019-08>

Reference
RTS/SCP-00HClUvb00

Keywords
smart card, terminal

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88.

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and
of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	10
Foreword.....	10
Modal verbs terminology.....	11
Introduction	11
1 Scope	12
2 References	12
2.1 Normative references	12
2.2 Informative references.....	13
3 Definition of terms, symbols and abbreviations.....	13
3.1 Terms.....	13
3.2 Symbols	13
3.3 Abbreviations	13
3.4 Void.....	14
3A Formats.....	14
3A.1 Format of the table of optional features.....	14
3A.2 Format of the applicability table.....	15
3A.3 Status and Notations.....	15
3A.4 Format of the conformance requirements tables.....	16
4 Test environment.....	16
4.1 Table of optional features.....	16
4.2 Applicability table	17
4.3 Information to be provided by the device supplier.....	21
4.4 Test equipment	21
4.4.0 Base Requirements	21
4.4.1 Measurement/setting uncertainties.....	21
4.4.2 Default conditions for DUT operation.....	22
4.4.2.1 General	22
4.4.2.2 Status of UICC interfaces.....	22
4.4.3 Minimum/maximum conditions for DUT operation.....	22
4.4.4 Conventions	22
4.5 Test execution	22
4.5.1 Parameter variations	22
4.5.2 Execution requirements	22
4.6 Pass criterion	23
4.6.0 Principle	23
4.6.1 Unanticipated behaviour from the DUT	23
5 Test cases.....	23
5.1 HCI architecture	23
5.1.1 Overview	23
5.1.2 Hosts	24
5.1.2.1 Conformance requirements	24
5.1.2.2 Test case 1: processing of RFU host identifier.....	24
5.1.2.2.1 Test execution.....	24
5.1.2.2.2 Initial conditions.....	24
5.1.2.2.3 Test procedure	24
5.1.3 Gates	24
5.1.3.1 Conformance requirements	24
5.1.3.2 Test case 1: existence of gates.....	24
5.1.3.2.1 Test execution.....	24
5.1.3.2.2 Initial conditions.....	24
5.1.3.2.3 Test procedure	25
5.1.3.3 Void.....	25

5.1.4	Pipes.....	25
5.1.4.1	Conformance requirements	25
5.1.4.2	Test case 1: static pipe deletion - administration gate	25
5.1.4.2.1	Test execution.....	25
5.1.4.2.2	Initial conditions.....	25
5.1.4.2.3	Test procedure	26
5.1.4.3	Test case 2: static pipe deletion - link management gate	26
5.1.4.3.1	Test execution.....	26
5.1.4.3.2	Initial conditions.....	26
5.1.4.3.3	Test procedure	26
5.1.4.4	Test case 3: persistence of pipe state.....	26
5.1.4.4.1	Test execution.....	26
5.1.4.4.2	Initial conditions.....	26
5.1.4.4.3	Test procedure	26
5.1.4.5	Test case 4: initial pipe state	27
5.1.4.5.1	Test execution.....	27
5.1.4.5.2	Initial conditions.....	27
5.1.4.5.3	Test procedure	27
5.1.5	Registries	27
5.1.5.1	Conformance requirements	27
5.1.5.2	Void.....	27
5.1.5.3	Void.....	27
5.2	HCP.....	28
5.2.1	HCP packets.....	28
5.2.1.1	Conformance requirements	28
5.2.2	HCP message structure	28
5.2.2.1	Conformance requirements	28
5.2.2.2	Test case 1: commands/events on pipe which is not open	28
5.2.2.2.1	Test execution.....	28
5.2.2.2.2	Initial conditions.....	28
5.2.2.2.3	Test procedure	29
5.2.3	Message fragmentation	29
5.2.3.1	Conformance requirements	29
5.3	Instructions	30
5.3.1	Commands	30
5.3.1.1	Overview.....	30
5.3.1.1.1	Conformance requirements	30
5.3.1.2	Generic commands.....	30
5.3.1.2.1	ANY_SET_PARAMETER	30
5.3.1.2.2	ANY_GET_PARAMETER.....	31
5.3.1.2.3	ANY_OPEN_PIPE.....	32
5.3.1.2.4	ANY_CLOSE_PIPE.....	33
5.3.1.3	Administration commands	34
5.3.1.3.1	ADM_CREATE_PIPE	34
5.3.1.3.2	ADM_NOTIFY_PIPE_CREATED.....	34
5.3.1.3.3	ADM_DELETE_PIPE	34
5.3.1.3.4	ADM_NOTIFY_PIPE_DELETED	34
5.3.1.3.5	ADM_CLEAR_ALL_PIPE	35
5.3.1.3.6	ADM_NOTIFY_ALL_PIPE_CLEARED	35
5.3.2	Responses	35
5.3.2.1	Conformance requirements	35
5.3.2.2	Test case 1: response to unknown command	35
5.3.2.2.1	Test execution.....	35
5.3.2.2.2	Initial conditions.....	35
5.3.2.2.3	Test procedure	35
5.3.2.3	Test case 2: responses received out of order, previous command sent by host controller	36
5.3.2.3.1	Test execution.....	36
5.3.2.3.2	Initial conditions.....	36
5.3.2.3.3	Test procedure	36
5.3.2.4	Void.....	36
5.3.3	Events	36
5.3.3.1	Conformance requirements	36

5.3.3.2	Test case 1: reception of unknown events.....	36
5.3.3.2.1	Test execution.....	36
5.3.3.2.2	Initial conditions.....	37
5.3.3.2.3	Test procedure	37
5.4	GATES and subclauses	37
5.4.1	GATES	37
5.4.1.1	Conformance requirements	37
5.4.1.2	Test case 1: command and event support for link management gate	37
5.4.1.2.1	Test execution.....	37
5.4.1.2.2	Initial conditions.....	37
5.4.1.2.3	Test procedure	37
5.4.1.3	Test case 2: command and event support for management gates except link management gate	38
5.4.1.3.1	Test execution.....	38
5.4.1.3.2	Initial conditions.....	38
5.4.1.3.3	Test procedure	38
5.4.2	Management gates	38
5.4.2.1	Administration gates	38
5.4.2.1.1	Host controller administration gate	38
5.4.2.1.2	Host administration gate.....	39
5.4.2.2	Link management gate	39
5.4.2.2.1	Host controller link management gate	39
5.4.2.2.2	Host link management gate	40
5.4.2.3	Identity management gate	40
5.4.2.3.1	Local registry.....	40
5.4.2.3.2	Remote registry	42
5.4.2.4	Loop back gate	42
5.4.2.4.1	Conformance requirements.....	42
5.4.3	Generic gates	42
5.5	HCI procedures	43
5.5.1	Pipe management.....	43
5.5.1.1	Pipe creation.....	43
5.5.1.1.1	Conformance requirements.....	43
5.5.1.1.2	Void.....	43
5.5.1.1.3	Test case 2: ADM_NOTIFY_PIPE_CREATED from host controller	43
5.5.1.1.4	Test case 3: ADM_NOTIFY_PIPE_CREATED from other host	43
5.5.1.1.5	Test case 4: ADM_NOTIFY_PIPE_CREATED with incorrect destination H _{ID}	44
5.5.1.1.6	Test case 5: unsuccessful ADM_NOTIFY_PIPE_CREATED.....	44
5.5.1.2	Pipe deletion.....	45
5.5.1.2.1	Conformance requirements.....	45
5.5.1.2.2	Void.....	45
5.5.1.2.3	Test case 2: receiving ADM_NOTIFY_PIPE_DELETED.....	45
5.5.1.3	Clear all Pipes	45
5.5.1.3.1	Conformance requirements.....	45
5.5.1.3.2	Test case 1: ADM_CLEAR_ALL_PIPE for data link layer specified in ETSI TS 102 613	46
5.5.1.3.3	Test case 2: ADM_CLEAR_ALL_PIPE - static pipes, dynamic pipes to host controller.....	47
5.5.1.3.4	Test case 3: ADM_CLEAR_ALL_PIPE - dynamic pipes to other host	47
5.5.1.3.5	Void.....	48
5.5.2	Registry access.....	48
5.5.3	Host and Gate discovery	48
5.5.4	Session initialization	48
5.5.4.1	Conformance requirements	48
5.5.4.2	Test case 1: SESSION_IDENTITY not changed.....	49
5.5.4.2.1	Test execution.....	49
5.5.4.2.2	Initial conditions.....	49
5.5.4.2.3	Test procedure	49
5.5.4.3	Test case 2: SESSION_IDENTITY changed.....	49
5.5.4.3.1	Test execution.....	49
5.5.4.3.2	Initial conditions.....	49
5.5.4.3.3	Test procedure	49
5.5.4.4	Test case 3: activation in low power mode, no session initialization.....	50
5.5.4.4.1	Test execution.....	50
5.5.4.4.2	Initial conditions.....	50

5.5.4.4.3	Test procedure	50
5.5.4.5	Test case 4: subsequent activation, no session initialization	50
5.5.4.5.1	Test execution.....	50
5.5.4.5.2	Initial conditions.....	50
5.5.4.5.3	Test procedure	50
5.5.4.6	Test case 5: activation in low power mode, ACT_POWER_MODE with FR=1, no session initialization	50
5.5.4.6.1	Test execution.....	50
5.5.4.6.2	Initial conditions.....	50
5.5.4.6.3	Test procedure	51
5.5.4.7	Test case 6: subsequent activation, ACT_POWER_MODE with FR=1, no session initialization	51
5.5.4.7.1	Test execution.....	51
5.5.4.7.2	Initial conditions.....	51
5.5.4.7.3	Test procedure	51
5.5.5	Loop back testing.....	51
5.5.5.1	Conformance requirements	51
5.5.5.2	Test case 1: pipe creation from host controller	51
5.5.5.2.1	Test execution.....	51
5.5.5.2.2	Initial conditions.....	52
5.5.5.2.3	Test procedure	52
5.5.5.3	Test case 2: pipe creation from another host	52
5.5.5.3.1	Test execution.....	52
5.5.5.3.2	Initial conditions.....	52
5.5.5.3.3	Test procedure	52
5.5.5.4	Test case 3: processing of EVT_POST_DATA	52
5.5.5.4.1	Test execution.....	52
5.5.5.4.2	Initial conditions.....	52
5.5.5.4.3	Test procedure	52
5.6	Contactless card emulation	53
5.6.1	Overview	53
5.6.1.1	Conformance requirements.....	53
5.6.2	Void	53
5.6.3	Gates	53
5.6.3.1	Void.....	53
5.6.3.2	Identity management gate	53
5.6.3.2.1	Conformance requirements.....	53
5.6.3.3	Card RF gates.....	53
5.6.3.3.1	Overview	53
5.6.3.3.2	Commands.....	53
5.6.3.3.3	Events and subclauses	54
5.6.3.3.4	Registry and subclauses.....	54
5.6.3.4	Card application gates	56
5.6.3.4.1	Overview	56
5.6.3.4.2	Commands.....	56
5.6.3.4.3	Events and subclauses	57
5.6.3.4.4	Registry	58
5.6.3.4.4.1	Conformance requirements	58
5.6.4	Procedures.....	58
5.6.4.1	Use of contactless card application	58
5.6.4.1.1	Conformance requirements.....	58
5.6.4.1.2	Test case 1: full power mode	58
5.6.4.1.3	Test case 2: full power mode, no EVT_CARD_ACTIVATED and EVT_CARD_DEACTIVATED	59
5.6.4.1.4	Test case 3: sequence from DEACTIVATED state	60
5.6.4.1.5	Test case 4: sequence from DEACTIVATED state, no EVT_CARD_ACTIVATED or EVT_CARD_DEACTIVATED	60
5.6.4.1.6	Test case 5: low power, power down instead of EVT_FIELD_OFF	61
5.6.4.1.7	Test case 6: EVT_FIELD_OFF after EVT_FIELD_ON / SWP interface activation	62
5.6.4.1.8	Test case 7: EVT_FIELD_OFF after EVT_CARD_ACTIVATED	63
5.6.4.1.9	Test case 8: EVT_FIELD_OFF after EVT_SEND_DATA.....	63
5.6.4.1.10	Test case 9: multiple open card gates	64
5.6.4.1.11	Test case 10: empty C-APDU	65

5.6.4.2	Non ISO/IEC 14443-4 type A.....	66
5.6.4.2.1	Conformance requirements.....	66
5.6.4.2.2	Test case 1: full power mode	66
5.6.4.2.3	Test case 2: sequence from DEACTIVATED state	67
5.6.4.2.4	Test case 3: low power mode, power down instead EVT_FIELD_OFF	68
5.6.4.2.5	Test case 4: EVT_FIELD_OFF after EVT_FIELD_ON / SWP interface activation	68
5.6.4.2.6	Test case 5: EVT_FIELD_OFF during CLT frames exchange	69
5.6.4.2.7	Test case 6: multiple open card gates	69
5.6.4.3	Type B' RF technology	70
5.6.4.3.1	Conformance requirements.....	70
5.6.4.4	Type F RF technology.....	71
5.6.4.4.1	Conformance requirements.....	71
5.6.4.4.2	Test case 1: RF error indicator	71
5.6.4.4.3	Test case 2: full power mode	72
5.6.4.4.4	Test case 3: sequence from DEACTIVATED state	73
5.6.4.4.5	Test case 4: low power, power down instead of EVT_FIELD_OFF	74
5.6.4.4.6	Test case 5: EVT_FIELD_OFF after EVT_FIELD_ON / SWP interface activation	75
5.6.4.4.7	Test case 6: EVT_FIELD_OFF after EVT_SEND_DATA.....	76
5.6.4.4.8	Test case 7: multiple open card gates	77
5.6.4.4.9	Test case 8: EVT_FIELD_OFF during CLT frames exchange	78
5.6.4.5	Update RF technology settings	79
5.6.4.5.1	Conformance requirements.....	79
5.6.4.6	Identity check	79
5.6.4.6.1	Conformance requirements.....	79
5.7	Contactless reader.....	80
5.7.1	Overview	80
5.7.1.1	Conformance requirements	80
5.7.2	Reader RF gates	80
5.7.2.1	Overview	80
5.7.2.2	Command	80
5.7.2.2.1	WR_XCHG_DATA	80
5.7.2.3	Registries.....	80
5.7.2.3.1	Type A reader RF gate	80
5.7.2.3.2	Type B reader RF gate	81
5.7.2.4	Events and subclauses	81
5.7.2.4.1	Events	81
5.7.2.4.2	EVT_READER_REQUESTED	81
5.7.2.4.3	EVT_END_OPERATION	81
5.7.2.5	Responses.....	82
5.7.2.5.1	Conformance requirements.....	82
5.7.3	Reader application gates	82
5.7.3.1	Overview.....	82
5.7.3.2	Command	82
5.7.3.2.1	Conformance requirements.....	82
5.7.3.3	Registry	82
5.7.3.3.1	Conformance requirements.....	82
5.7.3.4	Events and subclauses	82
5.7.3.4.1	Events	82
5.7.3.4.2	EVT_TARGET_DISCOVERED	82
5.7.3.4.3	EVT_READER_STATUS	83
5.7.4	Procedures.....	83
5.7.4.1	Use of contactless reader application	83
5.7.4.1.1	Conformance requirements.....	83
5.7.4.2	Contactless reader not available	83
5.7.4.2.1	Conformance requirements.....	83
5.7.4.3	Error management	83
5.7.4.3.1	Conformance requirements.....	83
5.8	Connectivity	83
5.8.1	Overview	83
5.8.2	Connectivity gate and subclauses	84
5.8.2.1	Connectivity gate	84
5.8.2.2	Commands	84

5.8.2.2.1	PRO_HOST_REQUEST	84
5.8.2.3	Events and subclauses	84
5.8.2.3.1	Events	84
5.8.2.3.2	EVT_CONNECTIVITY	84
5.8.2.3.3	Void	84
5.8.2.3.4	EVT_OPERATION_ENDED	84
5.8.2.3.5	EVT_TRANSACTION	85
5.8.2.4	Registry	85
5.8.2.4.1	Conformance requirements	85
5.8.3	Connectivity application gate and subclauses	85
5.8.3.1	Connectivity application gate	85
5.8.3.1.1	Conformance requirements	85
5.8.3.2	Commands	85
5.8.3.2.1	Conformance requirements	85
5.8.3.3	Events and subclauses	85
5.8.3.3.1	Events	85
5.8.3.3.2	EVT_STANDBY	86
5.8.3.4	Registry	86
5.8.3.4.1	Conformance requirements	86
5.8.4	Procedures	86
5.8.4.1	Use of connectivity gate	86

Annex A (normative): Additional test cases..........**87**

A.1	Overview	87
A.2	Applicability table	87
A.3	Conformance requirements	88
A.4	Test cases	89
A.4.1	Test case 1: registry creation	89
A.4.1.1	Test execution	89
A.4.1.2	Initial conditions	89
A.4.1.3	Test procedure	89
A.4.2	Test case 2: registry deletion	89
A.4.2.1	Test execution	89
A.4.2.2	Initial conditions	89
A.4.2.3	Test procedure	90
A.4.3	Test case 3: ANY_GET_PARAMETER reception - WO registry parameter	90
A.4.3.1	Test execution	90
A.4.3.2	Initial conditions	90
A.4.3.3	Test procedure	90
A.4.4	Test case 4: ANY_OPEN_PIPE transmission	90
A.4.4.1	Test execution	90
A.4.4.2	Initial conditions	90
A.4.4.3	Test procedure	91
A.4.5	Test case 5: ANY_CLOSE_PIPE transmission	91
A.4.5.1	Test execution	91
A.4.5.2	Initial conditions	91
A.4.5.3	Test procedure	91
A.4.6	Test case 6: responses received out of order, previous command sent by host	91
A.4.6.1	Test execution	91
A.4.6.2	Initial conditions	91
A.4.6.3	Test procedure	92
A.4.7	Test case 7: WHITELIST	92
A.4.7.1	Test execution	92
A.4.7.2	Initial conditions	92
A.4.7.3	Test procedure	92
A.4.8	Test case 8: REC_ERROR	92
A.4.8.1	Test execution	92
A.4.8.2	Initial conditions	92
A.4.8.3	Test procedure	92

A.4.9	Test case 9: REC_ERROR after HCI session initialization	93
A.4.9.1	Test execution	93
A.4.9.2	Initial conditions	93
A.4.9.3	Test procedure	93
A.4.10	Test case 10: ADM_CREATE_PIPE	93
A.4.10.1	Test execution	93
A.4.10.2	Initial conditions	93
A.4.10.3	Test procedure	93
A.4.11	Test case 11: sending ADM_DELETE_PIPE	94
A.4.11.1	Test execution	94
A.4.11.2	Initial conditions	94
A.4.11.3	Test procedure	94
A.4.12	Test case 12: ADM_CLEAR_ALL_PIPE - registry parameters	94
A.4.12.1	Test execution	94
A.4.12.2	Initial conditions	94
A.4.12.3	Test procedure	95
Annex B (informative):	Core specification version information.....	96
Annex C (informative):	Change history	97
History	98

iTeh STANDARD PREVIEW
(Standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/47e0d118-017b-40e9-b921-308d7a9fa568/etsi-ts-102-695-2-v11.0.0-2019-08>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Smart Card Platform (SCP).

The contents of the present document are subject to continuing work within TC SCP and may change following formal TC SCP approval. If TC SCP modifies the contents of the present document, it will then be republished by ETSI with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 0 early working draft;
 - 1 presented to TC SCP for information;
 - 2 presented to TC SCP for approval;
 - 3 or greater indicates TC SCP approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

The present document is part 2 of a multi-part deliverable covering the Test specification for the Host Controller Interface (HCI), as identified below:

Part 1: "Terminal features";

Part 2: "UICC features";

Part 3: "Host Controller features".

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

The present document defines test cases for the UICC relating to the Host Controller Interface (HCI) as specified in ETSI TS 102 622 [1].

The aim of the present document is to ensure interoperability between the terminal and the UICC independently of the respective manufacturer, card issuer or operator.

iTeh STANDARD PREVIEW
(Standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/47e0d118-017b-40c9-b921-308d7a9fa568/etsi-ts-102-695-2-v11.0.0-2019-08>

1 Scope

The present document covers the minimum characteristics which are considered necessary for the UICC in order to provide compliance to ETSI TS 102 622 [1].

The present document specifies the test cases for:

- the HCI core as described in the first part of ETSI TS 102 622 [1];
- the contactless platform as described in the second part of ETSI TS 102 622 [1].

Test cases for the terminal relating to ETSI TS 102 622 [1] and test cases for the Single Wire Protocol (SWP) covering both terminal and UICC are out of scope of the present document.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

- In the case of a reference to a TC SCP document, a non specific reference implicitly refers to the latest version of that document in the same Release as the present document.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TS 102 622: "Smart Cards; UICC - Contactless Front-end (CLF) Interface; Host Controller Interface (HCI)".
- [2] ETSI TS 102 613: "Smart Cards; UICC - Contactless Front-end (CLF) Interface; Part 1: Physical and data link layer characteristics".
- [3] ISO/IEC 18092: "Information technology - Telecommunications and information exchange between systems - Near Field Communication - Interface and Protocol (NFCIP-1)".
- [4] ISO/IEC 14443-3: "Cards and security devices for personal identification -- Contactless proximity objects -- Part 3: Initialization and anticollision".
- [5] ISO/IEC 14443-4: "Cards and security devices for personal identification -- Contactless proximity objects -- Part 4: Transmission protocol".
- [6] ISO/IEC 9646-7: "Information technology -- Open Systems Interconnection -- Conformance testing methodology and framework -- Part 7: Implementation Conformance Statements".
- [7] ETSI TS 102 221: "Smart Cards; UICC-Terminal interface; Physical and logical characteristics".
- [8] ETSI TS 102 600: "Smart Cards; UICC-Terminal interface; Characteristics of the USB interface".
- [9] ISO/IEC 7816-4: "Identification cards - Integrated circuit cards - Part 4: Organization, security and commands for interchange".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

- In the case of a reference to a TC SCP document, a non specific reference implicitly refers to the latest version of that document in the same Release as the present document.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

Not applicable.

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the terms given in ETSI TS 102 622 [1] and the following apply:

allowed error response code: response code which is not ANY, OK and which is allowed for the referenced command as specified in ETSI TS 102 622 [1]

non-occurrence RQ: RQ which has been extracted from ETSI TS 102 622 [1], but which indicates a situation which should never occur

NOTE: The consequence is that such RQs cannot be explicitly tested.

user: any logical or physical entity which controls the test equipment in a way that it is able to trigger activities of the DUT

3.2 Symbols

For the purposes of the present document, the symbols given in ETSI TS 102 622 [1] and the following apply:

PIPE ₀	the static pipe connected to the link management gate of the device under test
PIPE ₁	the static pipe connected to the administration gate of the device under test

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in ETSI TS 102 622 [1] and the following apply:

ATQA	Answer To reQuest of type A
ATQB	Answer To reQuest of type B
CLT	ContactLess Tunnelling
DUT	Device Under Test
EOF	End of Frame
FFS	For Further Study
FWI	Frame Waiting time Integer
HCI	Host Controller Interface
HCS	Host Controller Simulator
HUT	Host Under Test
ICRx	Initial Condition Requirement (where x is a number)

NOTE: As used in the applicability table; see clauses 4.2 and 4.5.2.