

ETSI TS 124 196 V15.1.0 (2019-10)



**Universal Mobile Telecommunications System (UMTS);
LTE;
5G;
Enhanced Calling Name (eCNAM)
(3GPP TS 24.196 version 15.1.0 Release 15)**

STANDARD PREVIEW
https://standards.iteh.ai/standards/sist/2020-148-7839-49e9-b46b-38e772b45c51-24-196-v15.1.0-201910



ReferenceRTS/TSGC-0124196vf10

Keywords5G,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	4
1 Scope	5
2 References	5
3 Definitions and abbreviations.....	5
3.1 Definitions	5
3.2 Abbreviations	6
4 Enhanced Calling Name (eCNAM)	7
4.1 Introduction	7
4.2 Service Description	7
4.2.1 General Description	7
4.3 Operational Requirements	7
4.3.1 Provision/withdrawal	7
4.3.2 Requirements on the Originating Network	7
4.3.3 Requirements on the Terminating Network.....	8
4.3.3.1 Data Sources	8
4.5 Signalling Procedures.....	8
4.5.1 General.....	8
4.5.2 Activation/Deactivation	8
4.5.3 Invocation and Operation.....	8
4.5.3.1 Actions at the Originating UE.....	8
4.5.3.2 Actions at the AS serving the Originating UE	8
4.5.3.3 Actions at the AS serving the Terminating UE.....	9
4.5.3.3.1 Identity not available	9
4.5.3.3.2 Identity available, presentation not allowed	9
4.5.3.3.3 Identity available, originating user identity verified and passed, presentation allowed.....	9
4.5.3.3.4 Identity available, verification failed.....	10
4.5.3.4 Actions at the Terminating UE.....	10
4.6 Interaction with other Services.....	11
4.6.1 Originating Identification Presentation (OIP).....	11
4.6.2 Originating Identification Restriction (OIR).....	11
4.6.3 Terminating Identification Presentation / Terminating Identification Restriction (TIP/TIR).....	11
4.6.4 Advice of Charge	11
4.6.5 Communication Waiting (CW).....	11
4.6.6 Communication Hold.....	11
4.6.7 Explicit Communication Transfer (ECT)	11
4.6.8 Closed User Group (CUG)	11
4.6.9 Completion of Communications to Busy Subscriber (CCBS)	11
4.6.10 Communication Diversion (CDIV).....	11
4.6.11 Malicious Communication Identification (MCID)	12
4.6.12 Anonymous Communication Rejection (ACR) and Incoming Communications Barring (ICB).....	12
4.6.13 Message Waiting Indication (MWI)	12
4.6.14 Flexible Alerting (FA)	12
4.6.15 Personal Network Management (PNM).....	12
4.7 Parameter values (timers).....	12
Annex A (informative): Change history	13
History	14

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/20cb5d48-7839-49e9-b46b-38e772b45c97/etsi-ts-124-196-v15.1.0-2019-10>

1 Scope

The present document specifies the stage three (protocol description) of the Enhanced Calling Name (eCNAM) supplementary service based on stage one description in 3GPP TS 22.173 [1]. It provides the protocol details in the IP Multimedia (IM) Core Network (CN) subsystem (see 3GPP TS 24.229 [2]) based on the Session Initiation Protocol (SIP) (see RFC 3261 [3]) where the eCNAM data is retrieved by the terminating network from trusted data sources.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 22.173: "IP Multimedia Core Network Subsystem (IMS) Multimedia Telephony Service and supplementary services".
- [2] 3GPP TS 24.229: "IP Multimedia call control protocol based on Session Initiation Protocol (SIP) and Session Description Protocol (SDP); Stage 3".
- [3] IETF RFC 3261: "SIP: Session Initiation Protocol".
- [4] 3GPP TS 23.003: "Numbering, addressing and identification".
- [5] IETF RFC 3325: "Private Extensions to the Session Initiation Protocol (SIP) for Network Asserted Identity within Trusted Networks".
- [6] IETF RFC 3323: "A Privacy Mechanism for the Session Initiation Protocol (SIP)".
- [7] IETF RFC 3966: "The tel URI for Telephone Numbers".
- [8] 3GPP TS 24.604: "Communication Diversion (CDIV) using IP Multimedia (IM) Core Network (CN) subsystem".
- [9] IETF RFC 8224: "Authenticated Identity Management in the Session Initiation Protocol (SIP)".
- [10] ITU-T Recommendation E.164 (11/2010): "The international public telecommunication numbering plan".
- [11] ITU-T Recommendation I.210 (03/1993): "Principles of telecommunication services supported by an ISDN and the means to describe them".

3 Definitions and abbreviations

For the purposes of the present document, the following definitions and abbreviations apply.

3.1 Definitions

For the purposes of the present document, the following definitions and abbreviations apply:

Identity information: all the information identifying a user, including trusted (network generated) and/or untrusted (user generated) addresses.

NOTE: Identity information takes the form of either a SIP URI (see RFC 3261 [3]) or a tel URI (see RFC 3966 [7]).

Originating UE: sender of a SIP request intended to initiate either a dialog (e.g. INVITE, SUBSCRIBE), or a standalone transaction.

Private information: information that according to RFC 3323 [6] and RFC 3325 [5] is not permitted to be delivered to the remote end.

Searchkey: a user identity employed to retrieve the eCNAM data associated with that identity from the appropriate data sources.

terminating UE: recipient of a SIP request intended either to initiate a dialog or to initiate either a dialog or a standalone transaction

trusted identity information: network generated user public identity information

For the purposes of the present document, the following definitions given in RFC 3261 [3] apply.

header
header field
request
response
session
(SIP) transaction

For the purposes of the present document, the following definitions given in ITU-T Recommendation I.210 [11] apply:

supplementary service
E.164 telephone number: telephone number formatted according to ITU-T.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply.

3GPP	3 rd Generation Partnership Project
ACR	Anonymous Communication Rejection
AS	Application Server
CCBS	Completion of Communication to Busy Subscriber
CDIV	Communication DIVersion
CN	Core Network
CUG	Closed User Group
CW	Communication Waiting
eCNAM	Enhanced Calling Name
ECT	Explicit Communication Transfer
FA	Flexible Alerting
HOLD	Communication Hold
ICB	Incoming Communications Barring
IETF	Internet Engineering Task Force
IM	IP Multimedia
IMS	IP Multimedia Subsystem
IP	Internet Protocol
MCID	Malicious Communication Identification
MWI	Message Waiting Indication
OIP	Originating Identification Presentation
OIR	Originating Identification Restriction
PNM	Personal Network Management
SDP	Session Description Protocol
SIP	Session Initiation Protocol
TIP	Terminating Identification Presentation
TIR	Terminating Identification Restriction
TN	Telephone Number

UE	User Equipment
URI	Universal Resource Identifier

4 Enhanced Calling Name (eCNAM)

4.1 Introduction

The eCNAM service provides the terminating user with the name associated with the originating user and optionally delivers metadata about that originating user. While eCNAM is a terminating service, the eCNAM operations rely on information received from the originating network, such as the originating user's E.164 telephone number (TN) to retrieve eCNAM data from trusted data sources (via methods outside the scope of this specification).

4.2 Service Description

4.2.1 General Description

The eCNAM service provides the terminating user with a name that identifies the originating user, and metadata about that originating user (e.g., address, language).

NOTE: The terminating service provider retrieves the name and metadata from pre-selected data sources. The terminating service provider can also partner with analytics providers that offer risk indicators about the incoming call (e.g., known perpetrators of scams) as part of the metadata eCNAM delivers.

To retrieve eCNAM data, the service provider formulates queries using a searchkey to retrieve the name and metadata. The searchkey is a user identity obtained from the incoming SIP INVITE. Most commonly, the service provider uses an E.164 TN as that searchkey. Other identities could be used to retrieve the eCNAM data.

If the terminating network determines that the telephone number's (or other identity's) presentation is restricted (i.e., not to be presented to the end user), the eCNAM data will also be restricted.

If the terminating network determines that the telephone number (or other identity's) presentation is not restricted (i.e., to be presented to the end user), the eCNAM data will also be presented to the end user with no restriction.

4.3 Operational Requirements

4.3.1 Provision/withdrawal

The eCNAM service can be provided after prior arrangement with the service provider.

The eCNAM service can be withdrawn at the subscriber's request or for administrative reasons.

4.3.2 Requirements on the Originating Network

eCNAM is a terminating service, however, the eCNAM operations rely on information received from the originating network.

If the originating user identity, such as the originating user's E.164 TN, is not delivered by the originating network to the terminating network, the terminating service provider will not be able to retrieve eCNAM data from the relevant data sources.

NOTE: The searchkey element necessary for retrieving eCNAM data from the relevant data source is, in most cases, restricted to the originating user's E.164 TN for most databases. However, other user identities can be used as searchkey elements.

The originating network can support a verification capability, such as the number verification capability described in 3GPP TS 24.229 [2]. Without a verification capability at the originating network, the integrity of the eCNAM data retrieved could be impacted.

4.3.3 Requirements on the Terminating Network

4.3.3.1 Data Sources

The eCNAM service involves the retrieval of the name data and the additional caller information from data sources that the terminating service provider has access to, based on service provider policy.

The special arrangements and interfaces between the terminating service provider and the data sources are outside the scope of this document and are subject to operator procedures.

NOTE 1: The accuracy of the name information and the metadata about the caller varies among sources; therefore, the terminating service provider exercises a choice of which source to use. The interfaces and protocols used to retrieve the data are typically negotiated between the terminating service provider and the data source.

NOTE 2: The terminating service provider pre-determines the elements of metadata that will be delivered on each call to eCNAM subscribers. The set of metadata varies from one service provider to another.

4.4 Syntax Requirements

The syntax for the header fields are normatively described in 3GPP TS 24.229 [2]. The relevant headers are:

- The P-Asserted-Identity header field which shall conform to the specifications in RFC 3325 [5] and RFC 3966 [7].
- The Identity header field which shall conform to the specifications in RFC 8224 [9].
- The Call-Info header field which shall conform to the specifications in RFC 3261 [3].
- The Privacy header field which shall conform to the specifications in RFC 3323 [6] and RFC 3325 [5].

NOTE: The privacy level "session" and "critical" are not used in this specification.

- The From header field which shall conform to the specifications in RFC 3261 [3] and RFC 3966 [7].

4.5 Signalling Procedures

4.5.1 General

Configuration of the eCNAM is performed by the service provider.

4.5.2 Activation/Deactivation

The service provider activates the eCNAM service at provisioning, upon the user's request.

The service provider deactivates the service at withdrawal upon the user's request.

No user configuration is defined in this release.

4.5.3 Invocation and Operation

4.5.3.1 Actions at the Originating UE

No actions at the originating UE.

4.5.3.2 Actions at the AS serving the Originating UE

No actions at the AS serving the originating UE.