

ETSI TS 129 336 V14.8.0 (2019-10)



**Universal Mobile Telecommunications System (UMTS);
LTE;
Home Subscriber Server (HSS) diameter interfaces for
interworking with packet data networks and applications
(3GPP TS 29.336 version 14.8.0 Release 14)**

REVIEW
47a5-91c3-bb3a084845d0tsi-14.8.0-2019-10



Reference

RTS/TSGC-0429336ve80

Keywords

LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and
of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Contents

| | |
|---|----|
| Intellectual Property Rights | 2 |
| Legal Notice | 2 |
| Modal verbs terminology..... | 2 |
| Foreword..... | 7 |
| 1 Scope | 8 |
| 2 References | 8 |
| 3 Abbreviations | 9 |
| 3.1 Abbreviations | 9 |
| 4 General Description..... | 9 |
| 4.1 Introduction | 9 |
| 5 Diameter-based S6m/S6n Interface..... | 11 |
| 5.1 Introduction | 11 |
| 5.2 Procedure Descriptions..... | 11 |
| 5.2.1 Subscriber Information Retrieval..... | 11 |
| 5.2.1.1 General | 11 |
| 5.2.1.2 Detailed Behaviour of the HSS | 13 |
| 5.2.1.3 Detailed Behaviour of the MTC-IWF | 14 |
| 5.2.1.4 Detailed Behaviour of the MTC-AAA | 14 |
| 6 Protocol Specification | 15 |
| 6.1 Introduction | 15 |
| 6.1.1 Use of Diameter Base Protocol..... | 15 |
| 6.1.2 Securing Diameter Messages..... | 15 |
| 6.1.3 Accounting Functionality | 15 |
| 6.1.4 Use of Sessions | 15 |
| 6.1.5 Transport Protocol | 15 |
| 6.1.6 Routing Considerations..... | 15 |
| 6.1.7 Advertising Application Support | 16 |
| 6.1.8 Diameter Application Identifier..... | 16 |
| 6.1.9 Use of the Supported-Features AVP | 16 |
| 6.1.10 User Identity to HSS resolution..... | 16 |
| 6.2 Commands..... | 17 |
| 6.2.1 Introduction..... | 17 |
| 6.2.2 Command-Code values..... | 17 |
| 6.2.3 Subscriber-Information-Request (SIR) Command | 17 |
| 6.2.4 Subscriber-Information-Answer (SIA) Command | 18 |
| 6.3 Result-Code AVP and Experimental-Result AVP Values | 18 |
| 6.3.1 General..... | 18 |
| 6.3.2 Success..... | 18 |
| 6.3.3 Permanent Failures | 18 |
| 6.3.3.1 DIAMETER_ERROR_USER_UNKNOWN (5001) | 18 |
| 6.3.3.2 DIAMETER_ERROR_UNAUTHORIZED_REQUESTING_ENTITY (5510) | 18 |
| 6.3.3.3 DIAMETER_ERROR_UNAUTHORIZED_SERVICE (5511) | 19 |
| 6.4 AVPs | 19 |
| 6.4.1 General..... | 19 |
| 6.4.2 User-Identifier..... | 20 |
| 6.4.3 Service-ID..... | 20 |
| 6.4.4 SCS-Identity | 20 |
| 6.4.5 Service-Parameters | 21 |
| 6.4.6 T4-Parameters | 21 |
| 6.4.7 Service-Data | 21 |
| 6.4.8 T4-Data | 21 |
| 6.4.9 HSS-Cause | 22 |

| | | |
|---------|---|----|
| 6.4.10 | SIR-Flags | 22 |
| 6.4.11 | External-Identifier..... | 22 |
| 6.4.12 | Serving-Node..... | 22 |
| 6.4.13 | Additional-Serving-Node..... | 23 |
| 6.4.14 | IP-SM-GW-Number | 24 |
| 6.4.15 | IP-SM-GW-Name | 24 |
| 6.4.16 | OC-Supported-Features | 24 |
| 6.4.17 | OC-OLR | 24 |
| 6.4.18 | IP-SM-GW-Realm..... | 24 |
| 6.4.19 | DRMP | 24 |
| 6.4.20 | Load | 24 |
| 7 | Diameter-based S6t Interface | 24 |
| 7.1 | Introduction | 24 |
| 7.2 | Procedure Descriptions..... | 25 |
| 7.2.1 | Configuration Information on S6t..... | 25 |
| 7.2.1.1 | General | 25 |
| 7.2.1.2 | Detailed Behaviour of the HSS | 27 |
| 7.2.1.3 | Detailed Behaviour of the SCEF..... | 29 |
| 7.2.2 | Reporting on S6t | 30 |
| 7.2.2.1 | General | 30 |
| 7.2.2.2 | Detailed Behaviour of the HSS | 31 |
| 7.2.2.3 | Detailed Behaviour of the SCEF..... | 32 |
| 7.2.3 | NIDD Information on S6t | 32 |
| 7.2.3.1 | General | 32 |
| 7.2.3.2 | Detailed Behaviour of the HSS | 33 |
| 7.2.3.3 | Detailed Behaviour of the SCEF..... | 34 |
| 8 | Protocol Specification for S6t | 34 |
| 8.1 | Introduction | 34 |
| 8.1.1 | Use of Diameter Base Protocol..... | 34 |
| 8.1.2 | Securing Diameter Messages..... | 35 |
| 8.1.3 | Accounting Functionality | 35 |
| 8.1.4 | Use of Sessions | 35 |
| 8.1.5 | Transport Protocol | 35 |
| 8.1.6 | Routing Considerations..... | 35 |
| 8.1.7 | Advertising Application Support | 35 |
| 8.1.8 | Diameter Application Identifier..... | 35 |
| 8.1.9 | Use of the Supported-Features AVP | 36 |
| 8.1.10 | User Identity to HSS resolution..... | 36 |
| 8.2 | Commands..... | 36 |
| 8.2.1 | Introduction..... | 36 |
| 8.2.2 | Command-Code values..... | 36 |
| 8.2.3 | Configuration Information Request (CIR) Command | 37 |
| 8.2.4 | Configuration-Information-Answer (CIA) Command | 37 |
| 8.2.5 | Reporting-Information-Request (RIR) Command | 38 |
| 8.2.6 | Reporting-Information-Answer (RIA) Command | 38 |
| 8.2.7 | NIDD Information Request (NIR) Command..... | 38 |
| 8.2.8 | NIDD-Information-Answer (NIA) Command | 39 |
| 8.3 | Result-Code AVP and Experimental-Result AVP Values | 39 |
| 8.3.1 | General..... | 39 |
| 8.3.2 | Success..... | 39 |
| 8.3.3 | Permanent Failures | 40 |
| 8.3.3.1 | DIAMETER_ERROR_USER_UNKNOWN (5001) | 40 |
| 8.3.3.2 | DIAMETER_ERROR_UNAUTHORIZED_REQUESTING_ENTITY (5510)..... | 40 |
| 8.3.3.3 | DIAMETER_ERROR_UNAUTHORIZED_SERVICE (5511) | 40 |
| 8.3.3.4 | DIAMETER_ERROR_REQUESTED_RANGE_IS_NOT_ALLOWED (5512) | 40 |
| 8.3.3.5 | DIAMETER_ERROR_CONFIGURATION_EVENT_STORAGE_NOT_SUCCESSFUL (5513)..... | 40 |
| 8.3.3.6 | DIAMETER_ERROR_CONFIGURATION_EVENT_NON_EXISTANT (5514)..... | 40 |
| 8.3.3.7 | DIAMETER_ERROR_USER_NO_APN_SUBSCRIPTION (5451) | 40 |
| 8.4 | AVPs | 40 |

| | | |
|----------|--|----|
| 8.4.1 | General..... | 40 |
| 8.4.2 | Monitoring-Event-Configuration..... | 44 |
| 8.4.3 | Monitoring-Event-Report | 45 |
| 8.4.4 | SCEF-Reference-ID..... | 45 |
| 8.4.5 | SCEF-ID | 45 |
| 8.4.6 | SCEF-Reference-ID-for-Deletion..... | 46 |
| 8.4.7 | Monitoring-Type..... | 46 |
| 8.4.8 | Maximum-Number-of-Reports | 46 |
| 8.4.9 | UE-Reachability-Configuration..... | 46 |
| 8.4.10 | Monitoring-Duration..... | 46 |
| 8.4.11 | Maximum-Detection-Time | 46 |
| 8.4.12 | Reachability-Type..... | 46 |
| 8.4.13 | Maximum-Latency..... | 47 |
| 8.4.14 | Maximum-Response-Time | 47 |
| 8.4.15 | Location-Information-Configuration | 47 |
| 8.4.16 | MONTE-Location-Type | 47 |
| 8.4.17 | Accuracy | 47 |
| 8.4.18 | Association-Type | 47 |
| 8.4.19 | Roaming-Information | 48 |
| 8.4.20 | Reachability-Information..... | 48 |
| 8.4.21 | EPS-Location-Information..... | 48 |
| 8.4.22 | IMEI-Change | 48 |
| 8.4.23 | Feature-List AVP..... | 48 |
| 8.4.23.1 | Feature-List AVP for the S6t application..... | 48 |
| 8.4.24 | Monitoring-Event-Config-Status | 49 |
| 8.4.25 | AESE-Communication-Pattern..... | 49 |
| 8.4.26 | Communication-Pattern-Set..... | 50 |
| 8.4.27 | Periodic-Communication-Indicator | 50 |
| 8.4.28 | Communication-duration-time..... | 50 |
| 8.4.29 | Periodic-time..... | 50 |
| 8.4.30 | Scheduled-communication-time | 51 |
| 8.4.31 | Stationary indication | 51 |
| 8.4.32 | AESE-Communication-Pattern-Config-Status | 51 |
| 8.4.33 | AESE-Error-Report | 51 |
| 8.4.34 | MME-Location-Information | 52 |
| 8.4.35 | SGSN-Location-Information | 52 |
| 8.4.36 | User-Identifier..... | 52 |
| 8.4.37 | Service-Result..... | 53 |
| 8.4.38 | Service-Result-Code | 53 |
| 8.4.39 | CIR-Flags..... | 53 |
| 8.4.40 | Supported-Services | 53 |
| 8.4.41 | Supported-Monitoring-Events | 54 |
| 8.4.42 | Reference-ID-Validity-Time..... | 54 |
| 8.4.43 | Event-Handling | 54 |
| 8.4.44 | NIDD-Authorization-Request | 54 |
| 8.4.45 | NIDD-Authorization-Response | 55 |
| 8.4.46 | DRMP | 55 |
| 8.4.47 | Service-Report | 55 |
| 8.4.48 | Node-Type | 55 |
| 8.4.49 | Service-Selection | 55 |
| 8.4.50 | S6t-HSS-Cause | 56 |
| 8.4.51 | Enhanced-Coverage-Restriction | 56 |
| 8.4.52 | Enhanced-Coverage-Restriction-Data | 56 |
| 8.4.53 | Restricted-PLMN-List | 56 |
| 8.4.54 | Allowed-PLMN-List..... | 57 |
| 8.4.55 | Requested-Validity-Time..... | 57 |
| 8.4.56 | Granted-Validity-Time | 57 |
| 8.4.57 | NIDD-Authorization-Update | 57 |
| 8.4.58 | Loss-Of-Connectivity-Reason | 57 |
| 8.4.59 | Group-Reporting-Guard-Timer..... | 58 |
| 8.4.60 | CIA-Flags | 58 |
| 8.4.61 | Group-Monitoring-Event-Report..... | 58 |

| | | |
|--------|--|----|
| 8.4.62 | Group-Monitoring-Event-Report-Item | 58 |
| 8.4.63 | RIR-Flags..... | 59 |
| 8.4.64 | Type-Of-External-Identifier..... | 59 |
| 8.4.65 | APN-Validity-Time | 59 |

Annex A (normative): Diameter overload control mechanism60

| | | |
|-------|-------------------------|----|
| A.1 | General | 60 |
| A.2 | S6m interface..... | 60 |
| A.2.1 | General..... | 60 |
| A.2.2 | HSS behaviour | 60 |
| A.2.3 | MTC-IWF behaviour | 60 |
| A.3 | S6t interface..... | 60 |
| A.3.1 | General..... | 60 |
| A.3.2 | HSS behaviour | 61 |
| A.3.3 | SCEF behaviour..... | 61 |

Annex B (Informative): Diameter overload control node behaviour62

| | | |
|-----|---------------------------------------|----|
| B.1 | Introduction | 62 |
| B.2 | Message prioritisation over S6m | 62 |
| B.3 | Message prioritisation over S6t | 62 |

Annex C (normative): Diameter message priority mechanism.....63

| | | |
|-----|-------------------------------|----|
| C.1 | General | 63 |
| C.2 | S6m, S6n, S6t interfaces..... | 63 |

Annex D (normative): Diameter load control mechanism.....64

| | | |
|-------|-------------------------|----|
| D.1 | General | 64 |
| D.2 | S6m interface..... | 64 |
| D.2.1 | General..... | 64 |
| D.2.2 | HSS behaviour | 64 |
| D.2.3 | MTC-IWF behaviour | 64 |
| D.3 | S6t interface..... | 64 |
| D.3.1 | General..... | 64 |
| D.3.2 | HSS behaviour | 64 |
| D.3.3 | SCEF behaviour..... | 65 |

Annex E (informative): Change history.....66

| | |
|---------------|----|
| History | 69 |
|---------------|----|

*ITI Standard Review
47a521c3-b3a08a845ab/etsi-ts-129-336-v14.8.0-2019-10*

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standard/sist/33991da5-1303-47a5-91c3-bb3a084845db/etsi-ts-129-336-v14.8.0-2019-10>

1 Scope

The present document describes the Diameter-based interfaces between the HSS and other network elements involved in the architecture for interworking with packet data networks and applications, such as Machine-Type Communications (MTC).

In particular, this document specifies the S6m interface between the Home Subscriber Server (HSS) and the MTC Interworking Function (MTC-IWF), the S6n interface between the HSS and the MTC-AAA and the S6t interface between the HSS and the Service Capability Exposure Function (SCEF). The procedures over those interfaces are defined in 3GPP TS 23.682 [2].

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 23.682: "Architecture enhancements to facilitate communications with packet data networks and applications".
- [3] Void.
- [4] 3GPP TS 33.210: "3G security; Network Domain Security (NDS); IP network layer security".
- [5] IETF RFC 4960: "Stream Control Transport Protocol".
- [6] 3GPP TS 29.228: "IP multimedia (IM) Subsystem Cx Interface; Signalling flows and Message Elements".
- [7] 3GPP TS 29.229: "Cx and Dx interfaces based on the Diameter protocol; protocol details".
- [8] 3GPP TS 29.173: "Diameter-based SLh interface for Control Plane LCS".
- [9] IETF RFC 5234: "Augmented BNF for Syntax Specifications: ABNF".
- [10] 3GPP TS 29.329: "Sh Interface based on the Diameter protocol".
- [11] 3GPP TS 23.003: "Numbering, addressing and identification".
- [12] 3GPP TS 29.338: "Diameter based protocols to support SMS capable MMEs".
- [13] 3GPP TS 29.368: "Tsp interface protocol between the MTC Interworking Function (MTC-IWF) and Service Capability Server (SCS)".
- [14] 3GPP TS 29.272: "Mobility Management Entity (MME) and Serving GPRS Support Node (SGSN) related interfaces based on Diameter protocol".
- [15] IETF RFC 7683 : "Diameter Overload Indication Conveyance".
- [16] 3GPP TS 32.299: "Telecommunication management; Charging management; Diameter charging applications".
- [17] 3GPP TS 29.217: "Congestion Reporting Over Np Reference Point".

- [18] IETF RFC 5777: "Traffic Classification and Quality of Service (QoS) Attributes for Diameter".
- [19] 3GPP TS 23.007: "Restoration procedures".
- [20] IETF RFC 7944: "Diameter Routing Message Priority".
- [21] IETF RFC 5778: "Diameter Mobile IPv6: Support for Home Agent to Diameter Server Interaction".
- [22] IETF RFC 8583: "Diameter Load Information Conveyance".

Editor's note: The above document cannot be formally referenced until it is published as an RFC.

- [23] IETF RFC 6733: "Diameter Base Protocol".
- [24] Void.
- [25] 3GPP TS 29.154: "Service capability exposure functionality over Nt Reference point".

3 Abbreviations

3.1 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [1].

| | |
|---------|--|
| AAA | Authentication, Authorization and Accounting |
| ABNF | Augmented Backus-Naur Form |
| AVP | Attribute-Value Pair |
| DRMP | Diameter Routing Message Priority |
| DSCP | Differentiated Services Code Point |
| IANA | Internet Assigned Numbers Authority |
| MTC | Machine-Type Communications |
| MTC-IWF | MTC Interworking Function |
| NIDD | Non-IP Data Delivery |
| SCS | Services Capability Server |
| SCEF | Service Capability Exposure Function |

4 General Description

4.1 Introduction

The S6m reference point between the MTC-IWF and the HSS, the S6n reference point between the MTC-AAA and the HSS, and the S6t reference point between the SCEF and the HSS, are defined in the 3GPP TS 23.682 [2].

This document describes the Diameter-based S6m, S6n and S6t related procedures, message parameters and protocol specification.

An excerpt of the architecture for Machine-Type Communication, as defined in 3GPP TS 23.682 [2] is shown in Figure 4.1-1, where the relevant interfaces towards the HSS are highlighted.




Figure 4.1-1: 3GPP Architecture for Machine-Type Communication

In this architecture, the S6m reference point connects the MTC-IWF with the HSS, where the subscription information of the UE (e.g., an MTC device) is stored. This reference point allows the MTC-IWF to retrieve subscription data and to do any necessary mapping between different identities associated to the UE.

The S6m interface shall allow the MTC-IWF to:

- retrieve subscription information of the UE from the HSS;
- request routing information from the HSS, i.e. the address of the UE's serving nodes supporting SMS for the UE ; in this context serving nodes of the UE are the MSC or MME but not both, the SGSN, and the IP-SM-GW,
- retrieve the IMSI of the UE,
- retrieve the External Identifier of the UE associated to an Application Port Identifier,
- perform authorization of the Service Capability Server that is requesting to send a device trigger to the UE.

Additionally, the S6n reference point connects the MTC-AAA with the HSS, and it allows the MTC-AAA to do the mapping of the UE IMSI to the external identifier(s) of the UE.

The S6t reference point connects the SCEF with the HSS to perform configuration and reporting of Monitoring events, and configuration of AESE Communication Pattern.

The S6t interface shall allow the SCEF to:

- configure UE related Monitoring events
- receive reporting of the configured Monitoring events from the HSS
- configure UE related AESE Communication Pattern
- Authorize the UE for NIDD.

5 Diameter-based S6m/S6n Interface

5.1 Introduction

This section describes the Diameter-based S6m and S6n interface related procedures and Information elements exchanged between functional entities.

In the tables that describe the Information Elements transported by each Diameter command, each Information Element is marked as (M) Mandatory, (C) Conditional or (O) Optional in the "Cat." column. For the correct handling of the Information Element according to the category type, see the description detailed in section 6 of the 3GPP TS 29.228 [6].

5.2 Procedure Descriptions

5.2.1 Subscriber Information Retrieval

5.2.1.1 General

This procedure is used between the MTC-IWF and the HSS and between the MTC-AAA and the HSS.

When the procedure is invoked by the MTC-IWF, it is used:

- To translate an external identifier, or MSISDN, to the IMSI of the user,
- To retrieve information about the serving entities currently serving a certain user,
- To authorize a certain SCS to request a specific service (e.g. device triggering),
- To retrieve subscription data of the user, associated to the specific service requested by the SCS,
- To retrieve an External Identifier based on IMSI and application port identifier.

When the procedure is invoked by the MTC-AAA, it is used:

- To translate an IMSI to one or more external identifiers of the user.

This procedure is mapped to the commands Subscriber-Information-Request/Answer in the Diameter application specified in chapter 6. Tables 5.2.1.1/1 and 5.2.1.1/2 detail the involved information elements.

Table 5.2.1.1/1: Subscriber Information Retrieval (Request)

| Information Element Name | Mapping to Diameter AVP | Cat. | Description |
|--|--------------------------------|-------------|--|
| User Identity (see 6.4.2) | User-Identifier | M | This Information Element shall contain the identity of the UE. This is a grouped AVP containing either an External Identifier, an MSISDN or an IMSI (exactly one, and only one, of those identifiers shall be included in the request). |
| Requested Service (see 6.4.3) | Service-ID | O | This Information Element shall contain the service requested by the SCS. In this release, only the Device Triggering and SMS_MO services are supported. |
| SCS Identity (see 6.4.4) | SCS-Identity | O | This Information Element shall contain the identity of the Service Capability Server that is requesting a service to be applied to a certain UE. When the Service-ID indicates DEVICE_TRIGGER (0) or SMS_MO (1), the SCS-Identity shall be formatted as an E.164 address as described in section 6.4.4. |
| Service Parameters (see 6.4.5) | Service-Parameters | O | This Information Element shall contain the parameters associated to the requested service by the SCS (identified by the Service-ID AVP). In this release, only parameters associated to Device Triggering via SMS-MT (T4) and parameters associated to SMS_MO are supported. For Device Triggering via SMS-MT, this AVP may contain: Priority-Indication, SM-RP-SMEA... For SMS_MO, this parameter may contain: Application-Port Identifier. |
| SIR Flags (see 6.4.10) | SIR-Flags | M | This Information Element shall contain a bit mask. See section 6.4.10 for the meaning of the bits. |
| Supported Features (See 3GPP TS 29.229 [7]) | Supported-Features | O | If present, this Information Element shall contain the list of features supported by the origin host. |

iTeh STANDARDS Full standard 47a5-91c3-bb3a084845db/etsi ts 129-336 v14.8.0