

# ETSI TS 123 501 V15.7.0 (2019-10)



## 5G; System architecture for the 5G System (5GS) (3GPP TS 23.501 version 15.7.0 Release 15)

*ITeH STANDARD PREVIEW  
(standards.it-eh.com)  
Full standard available at  
<https://standards.iteh.ai/catalog/standards/sist/42ff-adb4-1a8568015a76/etsi-ts-123-501-15-7-2019-10>*



---

Reference

RTS/TSGS-0223501vf70

---

Keywords

5G

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

**GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

---

# Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

---

# Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

Intellectual Property Rights .....	2
Legal Notice .....	2
Modal verbs terminology.....	2
Foreword.....	12
1 Scope .....	13
2 References .....	13
3 Definitions and abbreviations.....	16
3.1 Definitions .....	16
3.2 Abbreviations .....	18
4 Architecture model and concepts .....	20
4.1 General concepts .....	20
4.2 Architecture reference model .....	20
4.2.1 General.....	20
4.2.2 Network Functions and entities .....	21
4.2.3 Non-roaming reference architecture .....	21
4.2.4 Roaming reference architectures.....	25
4.2.5 Data Storage architectures .....	27
4.2.6 Service-based interfaces .....	29
4.2.7 Reference points .....	29
4.2.8 Support of non-3GPP access.....	31
4.2.8.1 General Concepts to Support Non-3GPP Access .....	31
4.2.8.2 Architecture Reference Model for Non-3GPP Accesses.....	32
4.2.8.2.1 Non-roaming Architecture for Non-3GPP Accesses .....	32
4.2.8.2.2 LBO Roaming Architecture for Non-3GPP Accesses, N3IWF in same PLMN as 3GPP access.....	32
4.2.8.2.3 Home-routed Roaming Architecture for Non-3GPP Accesses, N3IWF in same PLMN as 3GPP access .....	33
4.2.8.2.4 LBO Roaming Architecture for Non-3GPP Accesses, N3IWF in different PLMN from 3GPP access.....	34
4.2.8.2.5 Home-routed Roaming Architecture for Non-3GPP Accesses, N3IWF in different PLMN from 3GPP access.....	35
4.2.8.3 Non-3GPP Access Reference Points .....	36
4.2.9 Network Analytics architecture .....	36
4.3 Interworking with EPC.....	37
4.3.1 Non-roaming architecture .....	37
4.3.2 Roaming architecture.....	38
4.3.3 Interworking between 5GC via non-3GPP access and E-UTRAN connected to EPC.....	39
4.3.3.1 Non-roaming architecture .....	39
4.3.3.2 Roaming architecture .....	40
4.3.4 Interworking between ePDG connected to EPC and 5GS .....	42
4.3.4.1 Non-roaming architecture .....	42
4.3.4.2 Roaming architectures.....	43
4.4 Specific services .....	45
4.4.1 Public Warning System .....	45
4.4.2 SMS over NAS .....	45
4.4.2.1 Architecture to support SMS over NAS.....	45
4.4.2.2 Reference point to support SMS over NAS .....	47
4.4.2.3 Service based interface to support SMS over NAS .....	47
4.4.3 IMS support .....	47
4.4.4 Location services .....	48
4.4.4.1 Architecture to support Location Services .....	48
4.4.4.2 Reference point to support Location Services.....	48
4.4.4.3 Service Based Interfaces to support Location Services.....	49
4.4.5 Application Triggering Services .....	49

5	High level features.....	49
5.1	General .....	49
5.2	Network Access Control .....	49
5.2.1	General.....	49
5.2.2	Network selection .....	49
5.2.3	Identification and authentication.....	50
5.2.4	Authorisation .....	50
5.2.5	Access control and barring .....	50
5.2.6	Policy control.....	51
5.2.7	Lawful Interception.....	51
5.3	Registration and Connection Management.....	51
5.3.1	General.....	51
5.3.2	Registration Management .....	51
5.3.2.1	General .....	51
5.3.2.2	5GS Registration Management states.....	51
5.3.2.2.1	General .....	51
5.3.2.2.2	RM-DEREGISTERED state.....	51
5.3.2.2.3	RM-REGISTERED state .....	52
5.3.2.2.4	5GS Registration Management State models .....	52
5.3.2.3	Registration Area management .....	53
5.3.2.4	Support of a UE registered over both 3GPP and Non-3GPP access .....	53
5.3.3	Connection Management .....	55
5.3.3.1	General .....	55
5.3.3.2	5GS Connection Management states.....	55
5.3.3.2.1	General .....	55
5.3.3.2.2	CM-IDLE state .....	55
5.3.3.2.3	CM-CONNECTED state .....	56
5.3.3.2.4	5GS Connection Management State models .....	56
5.3.3.2.5	CM-CONNECTED with RRC Inactive state .....	57
5.3.3.3	NAS signalling connection management .....	59
5.3.3.3.1	General .....	59
5.3.3.3.2	NAS signalling connection establishment .....	59
5.3.3.3.3	NAS signalling connection Release.....	59
5.3.3.4	Support of a UE connected over both 3GPP and Non-3GPP access.....	59
5.3.4	UE Mobility .....	60
5.3.4.1	Mobility Restrictions.....	60
5.3.4.1.1	General .....	60
5.3.4.1.2	Management of Service Area Restrictions .....	61
5.3.4.2	Mobility Pattern .....	62
5.3.4.3	Radio Resource Management functions.....	62
5.3.4.4	UE mobility event notification.....	63
5.4	3GPP access specific aspects.....	64
5.4.1	UE reachability in CM-IDLE.....	64
5.4.1.1	General .....	64
5.4.1.2	UE reachability allowing mobile terminated data while the UE is CM-IDLE.....	65
5.4.1.3	Mobile Initiated Connection Only (MICO) mode.....	65
5.4.2	UE reachability in CM-CONNECTED.....	66
5.4.3	Paging strategy handling.....	66
5.4.3.1	General .....	66
5.4.3.2	Paging Policy Differentiation.....	66
5.4.3.3	Paging Priority .....	67
5.4.4	UE Radio Capability handling.....	67
5.4.4.1	UE radio capability information storage in the AMF.....	67
5.4.4.2	Void.....	68
5.4.4.2a	UE Radio Capability Match Request .....	68
5.4.4.3	Paging assistance information.....	68
5.4.4a	UE MM Core Network Capability handling.....	68
5.4.4b	UE 5GSM Core Network Capability handling .....	69
5.4.5	DRX (Discontinuous Reception) framework.....	69
5.4.6	Core Network assistance information for RAN optimization .....	70
5.4.6.1	General .....	70
5.4.6.2	Core Network assisted RAN parameters tuning.....	70

5.4.6.3	Core Network assisted RAN paging information.....	70
5.4.7	NG-RAN location reporting .....	71
5.5	Non-3GPP access specific aspects .....	71
5.5.1	Registration Management .....	71
5.5.2	Connection Management .....	71
5.5.3	UE Reachability .....	72
5.5.3.1	UE reachability in CM-IDLE .....	72
5.5.3.2	UE reachability in CM-CONNECTED .....	73
5.6	Session Management .....	73
5.6.1	Overview .....	73
5.6.2	Interaction between AMF and SMF .....	75
5.6.3	Roaming.....	76
5.6.4	Single PDU Session with multiple PDU Session Anchors .....	77
5.6.4.1	General .....	77
5.6.4.2	Usage of an UL Classifier for a PDU Session.....	77
5.6.4.3	Usage of IPv6 multi-homing for a PDU Session.....	78
5.6.5	Support for Local Area Data Network.....	79
5.6.6	Secondary authentication/authorization by a DN-AAA server during the establishment of a PDU Session .....	82
5.6.7	Application Function influence on traffic routing .....	83
5.6.8	Selective activation and deactivation of UP connection of existing PDU Session .....	88
5.6.9	Session and Service Continuity .....	89
5.6.9.1	General .....	89
5.6.9.2	SSC mode.....	89
5.6.9.2.1	SSC Mode 1.....	89
5.6.9.2.2	SSC Mode 2.....	89
5.6.9.2.3	SSC Mode 3.....	89
5.6.9.3	SSC mode selection.....	90
5.6.10	Specific aspects of different PDU Session types .....	90
5.6.10.1	Support of IP PDU Session type .....	90
5.6.10.2	Support of Ethernet PDU Session type .....	91
5.6.10.3	Support of Unstructured PDU Session type .....	92
5.6.11	UE presence in Area of Interest reporting usage by SMF.....	93
5.6.12	Use of Network Instance.....	94
5.6.13	Always-on PDU session .....	94
5.6.14	Support of Framed Routing .....	95
5.7	QoS model.....	95
5.7.1	General Overview .....	95
5.7.1.1	QoS Flow .....	95
5.7.1.2	QoS Profile.....	96
5.7.1.3	Control of QoS Flows .....	96
5.7.1.4	QoS Rules .....	97
5.7.1.5	QoS Flow mapping .....	97
5.7.1.6	DL traffic.....	99
5.7.1.7	UL Traffic .....	99
5.7.1.8	AMBR/MFBR enforcement and rate limitation.....	100
5.7.1.9	Precedence Value .....	100
5.7.2	5G QoS Parameters.....	100
5.7.2.1	5QI .....	100
5.7.2.2	ARP.....	101
5.7.2.3	RQA .....	101
5.7.2.4	Notification control .....	101
5.7.2.5	Flow Bit Rates.....	102
5.7.2.6	Aggregate Bit Rates .....	102
5.7.2.7	Default values .....	103
5.7.2.8	Maximum Packet Loss Rate.....	103
5.7.3	5G QoS characteristics.....	103
5.7.3.1	General .....	103
5.7.3.2	Resource Type.....	104
5.7.3.3	Priority Level .....	104
5.7.3.4	Packet Delay Budget .....	104
5.7.3.5	Packet Error Rate .....	105



5.7.3.6	Averaging Window .....	105
5.7.3.7	Maximum Data Burst Volume .....	105
5.7.4	Standardized 5QI to QoS characteristics mapping.....	106
5.7.5	Reflective QoS .....	109
5.7.5.1	General .....	109
5.7.5.2	UE Derived QoS Rule .....	110
5.7.5.3	Reflective QoS Control .....	111
5.7.6	Packet Filter Set .....	112
5.7.6.1	General .....	112
5.7.6.2	IP Packet Filter Set.....	112
5.7.6.3	Ethernet Packet Filter Set.....	112
5.8	User Plane Management.....	113
5.8.1	General.....	113
5.8.2	Functional Description.....	113
5.8.2.1	General .....	113
5.8.2.2	UE IP Address Management .....	113
5.8.2.2.1	General .....	113
5.8.2.2.2	Routing rules configuration .....	115
5.8.2.2.3	The procedure of Stateless IPv6 Address Autoconfiguration .....	115
5.8.2.3	Management of CN Tunnel Info .....	116
5.8.2.3.1	General .....	116
5.8.2.3.2	Management of CN Tunnel Info in the SMF.....	116
5.8.2.3.3	Management of CN Tunnel Info in the UPF .....	116
5.8.2.4	Traffic Detection .....	116
5.8.2.4.1	General .....	116
5.8.2.4.2	Traffic Detection Information .....	116
5.8.2.5	Control of User Plane Forwarding .....	117
5.8.2.6	Charging and Usage Monitoring Handling .....	118
5.8.2.6.1	General .....	118
5.8.2.6.2	Activation of Usage Reporting in UPF.....	118
5.8.2.6.3	Reporting of Usage Information towards SMF.....	119
5.8.2.7	PDU Session and QoS Flow Policing .....	119
5.8.2.8	PCC Related Functions.....	120
5.8.2.8.1	Activation/Deactivation of predefined PCC rules .....	120
5.8.2.8.2	Enforcement of Dynamic PCC Rules .....	120
5.8.2.8.3	Redirection .....	121
5.8.2.8.4	Support of PFD Management.....	121
5.8.2.9	Functionality of Sending of "End marker" .....	121
5.8.2.9.0	Introduction .....	121
5.8.2.9.1	UPF Constructing the "End marker" Packets .....	122
5.8.2.9.2	SMF Constructing the "End marker" Packets.....	122
5.8.2.10	UP Tunnel Management .....	122
5.8.2.11	Parameters for N4 session management.....	123
5.8.2.11.1	General .....	123
5.8.2.11.2	N4 Session Context .....	123
5.8.2.11.3	Packet Detection Rule .....	123
5.8.2.11.4	QoS Enforcement Rule.....	124
5.8.2.11.5	Usage Reporting Rule.....	126
5.8.2.11.6	Forwarding Action Rule .....	128
5.8.2.11.7	Usage Report generated by UPF .....	131
5.8.2.12	Reporting of the UE MAC addresses used in a PDU Session.....	131
5.8.3	Explicit Buffer Management.....	132
5.8.3.1	General .....	132
5.8.3.2	Buffering at UPF .....	132
5.8.3.3	Buffering at SMF .....	132
5.8.4	SMF Pause of Charging .....	132
5.9	Identifiers .....	133
5.9.1	General.....	133
5.9.2	Subscription Permanent Identifier .....	133
5.9.2a	Subscription Concealed Identifier.....	133
5.9.3	Permanent Equipment Identifier .....	133
5.9.4	5G Globally Unique Temporary Identifier .....	133

5.9.5	AMF Name .....	134
5.9.6	Data Network Name (DNN) .....	134
5.9.7	Internal-Group Identifier .....	135
5.9.8	Generic Public Subscription Identifier .....	135
5.9.9	AMF UE NGAP ID .....	135
5.10	Security aspects .....	135
5.10.1	General .....	135
5.10.2	Security Model for non-3GPP access .....	136
5.10.2.1	Signalling Security .....	136
5.10.3	PDU Session User Plane Security .....	136
5.11	Support for Dual Connectivity, Multi-Connectivity .....	137
5.11.1	Support for Dual Connectivity .....	137
5.12	Charging .....	138
5.12.1	General .....	138
5.12.2	Usage Data Reporting for Secondary RAT .....	138
5.12.3	Secondary RAT Periodic Usage Data Reporting Procedure .....	139
5.13	Support for Edge Computing .....	139
5.14	Policy Control .....	139
5.15	Network slicing .....	140
5.15.1	General .....	140
5.15.2	Identification and selection of a Network Slice: the S-NSSAI and the NSSAI .....	140
5.15.2.1	General .....	140
5.15.2.2	Standardised SST values .....	141
5.15.3	Subscription aspects .....	142
5.15.4	UE NSSAI configuration and NSSAI storage aspects .....	142
5.15.4.1	General .....	142
5.15.4.1.1	UE Network Slice configuration .....	142
5.15.4.1.2	Mapping of S-NSSAIs values in the Allowed NSSAI and in the Requested NSSAI to the S-NSSAIs values used in the HPLMN .....	144
5.15.4.2	Update of UE Network Slice configuration .....	144
5.15.5	Detailed Operation Overview .....	145
5.15.5.1	General .....	145
5.15.5.2	Selection of a Serving AMF supporting the Network Slices .....	145
5.15.5.2.1	Registration to a set of Network Slices .....	145
5.15.5.2.2	Modification of the Set of Network Slice(s) for a UE .....	148
5.15.5.2.3	AMF Re-allocation due to Network Slice(s) Support .....	150
5.15.5.3	Establishing a PDU Session in a Network Slice .....	150
5.15.6	Network Slicing Support for Roaming .....	151
5.15.7	Network slicing and Interworking with EPS .....	152
5.15.7.1	General .....	152
5.15.7.2	Idle mode aspects .....	152
5.15.7.3	Connected mode aspects .....	153
5.15.8	Configuration of Network Slice availability in a PLMN .....	153
5.16	Support for specific services .....	154
5.16.1	Public Warning System .....	154
5.16.2	SMS over NAS .....	154
5.16.2.1	General .....	154
5.16.2.2	SMS over NAS transport .....	155
5.16.3	IMS support .....	155
5.16.3.1	General .....	155
5.16.3.2	IMS voice over PS Session Supported Indication over 3GPP access .....	155
5.16.3.2a	IMS voice over PS Session Supported Indication over non-3GPP access .....	156
5.16.3.3	Homogeneous support for IMS voice over PS Session supported indication .....	156
5.16.3.4	P-CSCF address delivery .....	156
5.16.3.5	Domain selection for UE originating sessions / calls .....	156
5.16.3.6	Terminating domain selection for IMS voice .....	157
5.16.3.7	UE's usage setting .....	157
5.16.3.8	Domain and Access Selection for UE originating SMS .....	157
5.16.3.8.1	UE originating SMS for IMS Capable UEs supporting SMS over IP .....	157
5.16.3.8.2	Access Selection for SMS over NAS .....	158
5.16.3.9	SMF support for P-CSCF restoration procedure .....	158
5.16.3.10	IMS Voice Service via EPS Fallback or RAT fallback in 5GS .....	158



5.16.4	Emergency Services.....	158
5.16.4.1	Introduction.....	158
5.16.4.2	Architecture Reference Model for Emergency Services.....	161
5.16.4.3	Mobility Restrictions and Access Restrictions for Emergency Services.....	161
5.16.4.4	Reachability Management.....	161
5.16.4.5	SMF and UPF selection function for Emergency Services.....	161
5.16.4.6	QoS for Emergency Services.....	162
5.16.4.7	PCC for Emergency Services.....	162
5.16.4.8	IP Address Allocation.....	162
5.16.4.9	Handling of PDU Sessions for Emergency Services.....	162
5.16.4.9a	Handling of PDU Sessions for normal services for Emergency Registered UEs.....	162
5.16.4.10	Support of eCall Only Mode.....	162
5.16.4.11	Emergency Services Fallback.....	163
5.16.5	Multimedia Priority Services.....	163
5.16.6	Mission Critical Services.....	165
5.17	Interworking and Migration.....	166
5.17.1	Support for Migration from EPC to 5GC.....	166
5.17.1.1	General.....	166
5.17.1.2	User Plane management to support interworking with EPS.....	167
5.17.2	Interworking with EPC.....	167
5.17.2.1	General.....	167
5.17.2.2	Interworking Procedures with N26 interface.....	169
5.17.2.2.1	General.....	169
5.17.2.2.2	Mobility for UEs in single-registration mode.....	170
5.17.2.3	Interworking Procedures without N26 interface.....	171
5.17.2.3.1	General.....	171
5.17.2.3.2	Mobility for UEs in single-registration mode.....	172
5.17.2.3.3	Mobility for UEs in dual-registration mode.....	173
5.17.2.3.4	Redirection for UEs in connected state.....	174
5.17.2.4	Mobility between 5GS and GERAN/UTRAN.....	174
5.17.3	Interworking with EPC in presence of Non-3GPP PDU Sessions.....	174
5.17.4	Network sharing support and interworking between EPS and 5GS.....	174
5.17.5	Configuration Transfer Procedure between NG-RAN and E-UTRAN.....	175
5.17.5.1	Architecture Principles for Configuration Transfer between NG-RAN and E-UTRAN.....	175
5.17.5.2	Addressing, routing and relaying.....	176
5.17.5.2.1	Addressing.....	176
5.17.5.2.2	Routing.....	176
5.17.5.2.3	Relaying.....	176
5.18	Network Sharing.....	176
5.18.1	General concepts.....	176
5.18.2	Broadcast system information for network sharing.....	177
5.18.2a	PLMN list handling for network sharing.....	177
5.18.3	Network selection by the UE.....	177
5.18.4	Network selection by the network.....	178
5.18.5	Network Sharing and Network Slicing.....	178
5.19	Control Plane Load Control, Congestion and Overload Control.....	178
5.19.1	General.....	178
5.19.2	TNLA Load Balancing and TNLA Load Re-Balancing.....	178
5.19.3	AMF Load Balancing.....	179
5.19.4	AMF Load Re-Balancing.....	179
5.19.5	AMF Control Of Overload.....	180
5.19.5.1	General.....	180
5.19.5.2	AMF Overload Control.....	180
5.19.6	SMF Overload Control.....	181
5.19.7	NAS level congestion control.....	181
5.19.7.1	General.....	181
5.19.7.2	General NAS level congestion control.....	181
5.19.7.3	DNN based congestion control.....	182
5.19.7.4	S-NSSAI based congestion control.....	184
5.19.7.5	Group specific NAS level congestion control.....	185
5.20	External Exposure of Network Capability.....	185
5.21	Architectural support for virtualized deployments.....	186

5.21.0	General.....	186
5.21.1	Architectural support for N2.....	186
5.21.1.1	TNL associations.....	186
5.21.1.2	NGAP UE-TNLA-binding.....	186
5.21.1.3	N2 TNL association selection.....	187
5.21.2	AMF Management.....	187
5.21.2.1	AMF Addition/Update.....	187
5.21.2.2	AMF planned removal procedure.....	187
5.21.2.2.1	AMF planned removal procedure with UDSF deployed.....	187
5.21.2.2.2	AMF planned removal procedure without UDSF.....	189
5.21.2.3	Procedure for AMF Auto-recovery.....	191
5.22	System Enablers for priority mechanism.....	192
5.22.1	General.....	192
5.22.2	Subscription-related Priority Mechanisms.....	192
5.22.3	Invocation-related Priority Mechanisms.....	193
5.22.4	QoS Mechanisms applied to established QoS Flows.....	194
5.23	Supporting for Asynchronous Type Communication.....	195
5.24	3GPP PS Data Off.....	195
5.25	Support of OAM Features.....	196
5.25.1	Support of Tracing: Signalling Based Activation/Deactivation of Tracing.....	196
5.26	Configuration Transfer Procedure.....	196
5.26.1	Architecture Principles for Configuration Transfer.....	196
5.26.2	Addressing, routing and relaying.....	197
5.26.2.1	Addressing.....	197
5.26.2.2	Routing.....	197
5.26.2.3	Relaying.....	197
6	Network Functions.....	198
6.1	General.....	198
6.2	Network Function Functional description.....	198
6.2.1	AMF.....	198
6.2.2	SMF.....	199
6.2.3	UPF.....	200
6.2.4	PCF.....	200
6.2.5	NEF.....	200
6.2.5.1	Support for CAPIF.....	201
6.2.6	NRF.....	201
6.2.7	UDM.....	202
6.2.8	AUSF.....	203
6.2.9	N3IWF.....	203
6.2.10	AF.....	204
6.2.11	UDR.....	204
6.2.12	UDSF.....	204
6.2.13	SMSF.....	204
6.2.14	NSSF.....	205
6.2.15	5G-EIR.....	205
6.2.16	LMF.....	205
6.2.17	SEPP.....	205
6.2.18	Network Data Analytics Function (NWDAF).....	205
6.3	Principles for Network Function and Network Function Service discovery and selection.....	206
6.3.1	General.....	206
6.3.2	SMF discovery and selection.....	207
6.3.3	User Plane Function Selection.....	208
6.3.3.1	Overview.....	208
6.3.3.2	SMF Provisioning of available UPF(s).....	208
6.3.3.3	Selection of an UPF for a particular PDU Session.....	208
6.3.4	AUSF discovery and selection.....	209
6.3.5	AMF discovery and selection.....	210
6.3.6	N3IWF selection.....	211
6.3.6.1	General.....	211
6.3.6.2	Stand-alone N3IWF selection.....	212
6.3.6.3	Combined N3IWF/ePDG Selection.....	212

6.3.6.4	PLMN Selection for emergency services .....	213
6.3.7	PCF discovery and selection .....	213
6.3.7.0	General principles .....	213
6.3.7.1	PCF discovery and selection for a UE or a PDU Session .....	214
6.3.7.2	Providing policy requirements that apply to multiple UE and hence to multiple PCF.....	215
6.3.7.3	Binding an AF request targeting an IP address to the relevant PCF .....	215
6.3.8	UDM discovery and selection.....	215
6.3.9	UDR discovery and selection.....	216
6.3.10	SMSF discovery and selection.....	216
6.3.11	CHF discovery and selection .....	217
7	Network Function Services and descriptions .....	217
7.1	Network Function Service Framework.....	217
7.1.1	General.....	217
7.1.2	NF Service Consumer - NF Service Producer interactions.....	217
7.1.3	Network Function Service discovery .....	218
7.1.4	Network Function Service Authorization .....	219
7.1.5	Network Function and Network Function Service registration and de-registration.....	219
7.2	Network Function Services .....	220
7.2.1	General.....	220
7.2.2	AMF Services .....	221
7.2.3	SMF Services.....	221
7.2.4	PCF Services.....	222
7.2.5	UDM Services .....	222
7.2.6	NRF Services.....	223
7.2.7	AUSF Services.....	223
7.2.8	NEF Services .....	224
7.2.9	SMSF Services.....	224
7.2.10	UDR Services .....	224
7.2.11	5G-EIR Services .....	225
7.2.12	NWDAF Services .....	225
7.2.13	UDSF Services.....	225
7.2.14	NSSF Services .....	225
7.2.15	BSF Services.....	226
7.2.16	LMF Services.....	226
7.2.17	CHF Services .....	226
7.3	Exposure.....	226
8	Control and User Plane Protocol Stacks.....	227
8.1	General .....	227
8.2	Control Plane Protocol Stacks.....	227
8.2.1	Control Plane Protocol Stacks between the 5G-AN and the 5G Core: N2 .....	227
8.2.1.1	General .....	227
8.2.1.2	AN - AMF.....	228
8.2.1.3	AN - SMF .....	228
8.2.2	Control Plane Protocol Stacks between the UE and the 5GC .....	228
8.2.2.1	General .....	228
8.2.2.2	UE - AMF .....	230
8.2.2.3	UE - SMF .....	230
8.2.3	Control Plane Protocol Stacks between the network functions in 5GC .....	231
8.2.3.1	The Control Plane Protocol Stack for the service based interface.....	231
8.2.3.2	The Control Plane protocol stack for the N4 interface between SMF and UPF.....	231
8.2.4	Control Plane for untrusted non 3GPP Access .....	232
8.3	User Plane Protocol Stacks.....	232
8.3.1	User Plane Protocol Stack for a PDU Session .....	232
8.3.2	User Plane for untrusted non 3GPP Access.....	234
<b>Annex A (informative):</b>	<b>Relationship between Service-Based Interfaces and Reference Points...235</b>	
<b>Annex B (normative):</b>	<b>Mapping between temporary identities .....</b>	<b>237</b>
<b>Annex C (informative):</b>	<b>Guidelines and Principles for Compute-Storage Separation.....</b>	<b>238</b>

**Annex D (informative):**    **Change history** .....239  
History .....249

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/fa727b21-1259-42ff-adb4-1a8568015a76/etsi-ts-123-501-v15.7.0-2019-10>

---

# Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

**PREVIEW**  
iTech STANDARD  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/fa727b21-1259-42ff-adb4-1a8568015a76/etsi-ts-123-501-v15.7.0-2019-10>