

ETSI TS 132 426 V11.5.0 (2019-10)



LTE;
Telecommunication management;
Performance Management (PM);
Performance measurements Evolved Packet Core (EPC)
network
(3GPP TS 32.426 version 11.5.0 Release 11)



ReferenceRTS/TSGS-0532426vb50

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
1 Scope	11
2 References	11
3 Measurement family and abbreviations.....	12
3.1 Measurement family.....	12
3.2 Abbreviations	12
4 Measurements related to the MME	13
4.1 Mobility Management	13
4.1.1 EPS attach procedures	13
4.1.1.0 General	13
4.1.1.1 Attempted EPS attach procedures	13
4.1.1.2 Successful EPS attach procedures.....	13
4.1.1.3 Failed EPS attach procedures	14
4.1.1.4 Combined EPS/IMSI attach	14
4.1.1.4.0 General	14
4.1.1.4.1 Attempted combined attach procedures.....	14
4.1.1.4.2 Successful combined attach procedures.....	14
4.1.1.4.3 Failed combined attach procedures	15
4.1.1.5 EPS emergency attach procedures	15
4.1.1.5.0 General	15
4.1.1.5.1 Attempted emergency attach procedures.....	15
4.1.1.5.2 Successful emergency attach procedures.....	16
4.1.1.5.3 Failed emergency attach procedures.....	16
4.1.2 UE-initiated EPS Detach procedure.....	17
4.1.2.1 Attempted EPS detach procedures by UE.....	17
4.1.2.2 Successful EPS detach procedures by UE.....	17
4.1.3 MME-initiated EPS Detach procedure.....	17
4.1.3.1 Attempted EPS detach procedures by MME.....	17
4.1.3.2 Successful EPS detach procedures by MME	18
4.1.4 HSS-initiated EPS Detach procedure.....	18
4.1.4.1 Attempted EPS detach procedures by HSS.....	18
4.1.4.2 Successful EPS detach procedures by HSS.....	18
4.1.5 Tracking area update procedure with Serving GW change.....	19
4.1.5.0 General	19
4.1.5.1 Attempted tracking area update procedure with Serving GW change	19
4.1.5.2 Successful tracking area update procedure with Serving GW change	19
4.1.5.3 Failed tracking area update procedure with Serving GW change	19
4.1.6 Tracking area update procedure without Serving GW change.....	20
4.1.6.0 General	20
4.1.6.1 Attempted tracking area update procedure without Serving GW change	20
4.1.6.2 Successful tracking area update procedure without Serving GW change	20
4.1.6.3 Failed tracking area update procedure without Serving GW change	21
4.1.7 EPS paging procedures	21
4.1.7.0 General	21
4.1.7.1 Attempted EPS paging procedures.....	21
4.1.7.2 Successful EPS paging procedures	22
4.1.7.3 Failed EPS paging procedures.....	22
4.1.8 MME control of overload related measurements for EPC.....	22
4.1.8.1 Attempted Overload Start procedure.....	22
4.1.8.2 Attempted Overload Stop procedure.....	23
4.1.9 EMM-Registered subscribers.....	23
4.1.9.1 Mean number of EMM-Registered subscribers	23

4.1.9.2	Maximum number of EMM-Registered subscribers	23
4.1.10	Handover related measurements	24
4.1.10.1	Inter RAT handover	24
4.1.10.1.1	Incoming inter RAT handover	24
4.1.10.1.1.1	Attempted incoming inter RAT handover	24
4.1.10.1.1.2	Successful incoming inter RAT handover	24
4.1.10.1.2	Outgoing inter RAT handover	24
4.1.10.1.2.1	Attempted outgoing inter RAT handover	24
4.1.10.1.2.2	Successful outgoing inter RAT handover	25
4.1.11	Routing area update with MME interaction	25
4.1.11.0	General	25
4.1.11.1	Attempted routing area update with MME interaction	25
4.1.11.2	Successful routing area update with MME interaction and without S-GW change	26
4.1.11.3	Failed routing area update with MME interaction and without S-GW change	26
4.1.11.4	Successful routing area update with MME interaction and with S-GW change	26
4.1.11.5	Failed routing area update with MME interaction and with S-GW change	27
4.1.12	Combined TA/LA update procedure	27
4.1.12.0	General	27
4.1.12.1	Attempted Combined TA/LA update	27
4.1.12.2	Successful Combined TA/LA update	28
4.1.12.3	Failed Combined TA/LA update	28
4.1.13	Number of implicit detach related measurements	28
4.2	Session Management	29
4.2.1	Number of dedicated EPS bearers in active mode (Mean)	29
4.2.2	Number of dedicated EPS bearers in active mode (Maximum)	29
4.2.3	Dedicated bearer set-up time by MME (Mean)	29
4.2.4	MME initiated dedicated bearer activation	30
4.2.4.1	Attempted dedicated bearer activation procedures by MME	30
4.2.4.2	Successful dedicated bearer activation procedures by MME	30
4.2.4.3	Failed dedicated bearer activation procedures by MME	30
4.2.5	MME initiated dedicated bearer deactivation	31
4.2.5.1	Attempted dedicated bearer deactivation procedures by MME	31
4.2.5.2	Successful dedicated bearer deactivation procedures by MME	31
4.2.6	MME initiated EPS bearer modification	31
4.2.6.1	Attempted EPS bearer modification procedures by MME	31
4.2.6.2	Successful EPS bearer modification procedures by MME	32
4.2.6.3	Failed EPS bearer modification procedures by MME	32
4.2.7	Total EPS Service Request	32
4.2.7.0	General	32
4.2.7.1	Total Attempted EPS Service Request procedures.	32
4.2.7.2	Total Successful EPS Service Request procedures.	33
4.2.7.3	Total failed EPS Service Request procedures.	33
4.3	Subscriber management for MME	33
4.3.1	Attempted insert subscriber data requests received from a HSS	33
4.3.2	Attempted delete subscriber data requests received from a HSS	34
4.3.3	Number of subscribers in ECM-IDLE state	34
4.3.4	Number of subscribers in ECM-CONNECTED state	34
4.4	S1-MME data volume related measurements	35
4.4.1	Number of incoming IP data packets on the S1-MME interface from eNodeB to MME	35
4.4.2	Number of outgoing IP data packets on the S1-MME interface from MME to eNodeB	35
4.4.3	Number of octets of incoming IP data packets on the S1-MME interface from eNodeB to MME	35
4.4.4	Number of octets of outgoing IP data packets on the S1-MME interface from MME to eNodeB	36
4.5	Equipment resource	36
4.5.1	MME Processor usage	36
4.5.1.1	Mean Processor Usage	36
4.5.1.2	Peak processor usage	36
4.6	S6a related measurements	38
4.6.1	Update location related measurements	38
4.6.1.1	General	38
4.6.1.2	Attempted update location procedure	38
4.6.1.3	Successful update location procedure	38
4.6.1.4	Failed update location procedure	38

4.7	S6a related measurements	40
4.7.1	Authentication related measurements	40
4.7.1.1	General	40
4.7.1.2	Attempted authentication information retrieval procedure	40
4.7.1.3	Successful authentication information retrieval procedure	40
4.7.1.4	Failed authentication information retrieval procedure	40
5	Measurements related to the PDN-GW for a GTP based S5/S8	42
5.1	Session Management	42
5.1.1	PDN-GW initiated Dedicated Bearer Creation	42
5.1.1.0	General	42
5.1.1.1	Attempted number of PDN-GW initiated Dedicated Bearer Creation	42
5.1.1.2	Successful number of PDN-GW initiated Dedicated Bearer Creation	42
5.1.1.3	Failed number of PDN-GW initiated Dedicated Bearer Creation	42
5.1.2	PDN-GW initiated Dedicated Bearer Deletion	43
5.1.2.0	General	43
5.1.2.1	Attempted number of PDN-GW initiated Dedicated Bearer Deletion	43
5.1.2.2	Successful number of PDN-GW initiated Dedicated Bearer Deletion	43
5.1.2.3	Failed number of PDN-GW initiated Dedicated Bearer Deletion	44
5.1.3	PDN-GW initiated Dedicated Bearer Modification with QoS update procedure	44
5.1.3.0	General	44
5.1.3.1	Attempted number of PDN-GW initiated Dedicated Bearer Modification with QoS update	44
5.1.3.2	Successful PDN-GW initiated Dedicated Bearer Modification with QoS update	44
5.1.3.3	Failed PDN-GW initiated Dedicated Bearer Modification with QoS update	45
5.1.4	PDN-GW initiated Dedicated Bearer Modification without QoS update procedure	45
5.1.4.0	General	45
5.1.4.1	Attempted number of PDN-GW initiated Dedicated Bearer Modification without QoS update	45
5.1.4.2	Successful number of PDN-GW initiated Dedicated Bearer Modification without QoS update	46
5.1.4.3	Failed number of PDN-GW initiated Dedicated Bearer Modification without QoS update	46
5.1.5	Active EPS Bearers related measurements for EPC	46
5.1.5.1	Mean Number of Active EPS Bearers	46
5.1.5.2	Max Number of Active EPS Bearers	47
5.1.6	UE requested bearer resource modification related measurements for EPC	47
5.1.6.0	General	47
5.1.6.1	Attempted UE requested bearer resource modification procedure	47
5.1.6.2	Successful UE requested bearer resource modification procedure	47
5.1.6.3	Failed UE requested bearer resource modification procedure	48
5.1.7	PDN Connections related measurements for EPC	48
5.1.7.1	Mean Number of PDN Connections, per APN	48
5.1.7.2	Max Number of PDN Connections, per APN	49
5.1.8	Number of EPS bearer	49
5.1.8.1	Mean number of EPS bearers	49
5.1.8.2	Maximum number of EPS bearers	49
5.2	SGi related measurements	50
5.2.1	SGi incoming link usage	50
5.2.2	SGi outgoing link usage	50
6	Measurements related to the S-GW	51
6.1	GTP related measurements	51
6.1.1	GTP S5/S8	51
6.1.1.1	Number of outgoing GTP data packets on the S5/S8 interface, from S-GW to PDN-GW	51
6.1.1.2	Number of incoming GTP data packets on the S5/S8 interface, from PDN-GW to S-GW	51
6.1.1.3	Number of octets of outgoing GTP data packets on the S5/S8 interface, from S-GW to PDN-GW	51
6.1.1.4	Number of octets of incoming GTP data packets on the S5/S8 interface, from PDN-GW to S-GW	52
6.1.1.5	Number of outgoing GTP signalling packets on the S5/S8 interface, from S-GW to PDN-GW	52
6.1.1.6	Number of incoming GTP signalling packets on the S5/S8 interface, from PDN-GW to S-GW	52
6.1.1.7	Number of octets of outgoing GTP signalling packets on the S5/S8 interface, from S-GW to PDN-GW	53
6.1.1.8	Number of octets of incoming GTP signalling packets on the S5/S8 interface, from PDN-GW to S-GW	53
6.1.2	GTP S4 data volume related measurements	53

6.1.2.1	Number of octets of outgoing GTP packets on the S4 interface, from S-GW to SGSN	53
6.1.2.2	Number of octets of incoming GTP packets on the S4 interface, from SGSN to S-GW	54
6.1.3	GTP S12 data volume related measurements	54
6.1.3.1	Number of octets of outgoing GTP data packets on the S12 interface, from S-GW to UTRAN	54
6.1.3.2	Number of octets of incoming GTP data packets on the S12 interface, from UTRAN to S-GW	54
6.2	S1-U data volume related measurements	56
6.2.1	Number of outgoing GTP data packets on the S1-U interface, from S-GW to eNodeB.....	56
6.2.2	Number of incoming GTP data packets on the S1-U interface, from eNodeB to S-GW	56
6.2.3	Number of octets of outgoing GTP data packets on the S1-U interface, from S-GW to eNodeB	56
6.2.4	Number of octets of incoming GTP data packets on the S1-U interface, from eNodeB to S-GW	57
6.3	Session Management	57
6.3.1	Related to S4/S11	57
6.3.1.1	EPS bearer creation related measurements	57
6.3.1.1.1	Attempted number of default bearer creation	57
6.3.1.1.2	Successful number of default bearer creation.....	57
6.3.1.1.3	Attempted number of dedicated bearer creation.....	58
6.3.1.1.4	Successful number of dedicated bearer creation.....	58
6.3.1.2	EPS bearer modification related measurements	58
6.3.1.2.1	Attempted number of bearer modification.....	58
6.3.1.2.2	Successful number of bearer modification	59
6.3.2	Related to S5/S8	59
6.3.2.1	EPS bearer creation related measurements	59
6.3.2.1.1	Attempted number of default bearer creation	59
6.3.2.1.2	Successful number of default bearer creation	59
6.3.2.1.3	Attempted number of dedicated bearer creation.....	60
6.3.2.1.4	Successful number of dedicated bearer creation.....	60
6.3.2.2	EPS bearer modification related measurements.....	60
6.3.2.2.1	Attempted number of bearer modification.....	60
6.3.2.2.2	Successful number of bearer modification	61
6.3.3	EPS bearer deletion related measurements	61
6.3.3.0	General	61
6.3.3.1	Attempted number of bearer deletion.....	61
6.3.3.2	Successful number of bearer deletion	61
6.3.3.3	Failed number of bearer deletion	62
6.3.4	Bearer resource Usage related measurements.....	62
6.3.4.1	Max number of Active EPS bearers.....	62
6.3.4.2	Mean number of Active EPS bearers	62
7	Measurements related to the MBMS GW	64
7.1	Session Management	64
7.1.1	MBMS session creation related measurements.....	64
7.1.1.1	Measurement types	64
7.1.1.2	Attempted number of session creation	64
7.1.1.3	Successful number of session creation	64
7.1.1.4	Failed number of session creation	64
7.2	M1 data volume related measurements	65
7.2.1	Number of octets of outgoing GTP data packets on the M1 interface	65
7.2.2	Number of octets of incoming GTP data packets on the M1 interface	65
8	Measurements related to PCRF	66
8.1	IP-CAN session establishment related measurements.....	66
8.1.0	General.....	66
8.1.1	Attempted IP-CAN session establishment.....	66
8.1.2	Successful IP-CAN session establishment.....	66
8.1.3	Failed IP-CAN session establishment.....	66
8.2	IP-CAN session modification related measurements	68
8.2.1	General.....	68
8.2.2	Attempted IP-CAN session modification	68
8.2.3	Successful IP-CAN session modification	68
8.2.3	Failed IP-CAN session modification	68
8.3	Authorization of QoS resources related measurements.....	70
8.3.1	General.....	70

8.3.2	Overview	70
8.3.3	Attempted resource authorization procedures at session establishment	70
8.3.4	Attempted resource authorization procedures at session modification	71
8.3.5	Successful resource authorization procedures at session establishment	71
8.3.6	Successful resource authorization procedures at session modification	71
8.3.7	Failed resource authorization procedures	72
8.4	Gateway Control session establishment related measurements	73
8.4.1	General	73
8.4.2	Attempted Gateway Control session establishment	73
8.4.3	Successful Gateway Control session establishment	73
8.4.4	Failed Gateway Control session establishment	73
8.5	Credit re-authorization procedure related measurements	75
8.5.1	General	75
8.5.2	Attempted credit re-authorization procedure	75
8.5.3	Successful credit re-authorization procedure	75
8.5.4	Failed credit re-authorization procedure	75
8.6	IP-CAN session termination related measurements	77
8.6.1	Attempted IP-CAN session termination	77
8.6.2	Successful IP-CAN session termination	77
Annex A (informative):	Use case for measurements	78
A.1	Use case for mobility management related measurements	78
A.2	Use case for detach related measurements	78
A.3	Use case for tracking and routing area update related measurements	78
A.4	Use case for session related measurements	79
A.5	Use case for EPS paging procedures	79
A.6	Use case of PDN-GW initiated Dedicated Bearer Creation related measurements for EPC	79
A.7	Use case of PDN-GW initiated Dedicated Bearer Deletion related measurements for EPC	79
A.8	Use case of PDN-GW initiated Dedicated Bearer Modification with QoS Update related measurements for EPC	80
A.9	Use case of PDN-GW initiated Dedicated Bearer Modification without QoS Update related measurements for EPC	80
A.10	Use case of GTP S5/S8 data volume related measurements	80
A.11	Use case of S1-U data volume related measurements	80
A.12	Use case of SGi related measurements for EPC	80
A.13	Use case of subscriber management for MME related measurements	81
A.14	Use case of S1-MME data volume related measurements	81
A.15	Use case of Active EPS Bearers related measurements for EPC	81
A.16	Use case of MME control of overload related measurements for EPC	81
A.17	Use case of UE requested bearer resource modification related measurements for EPC	82
A.18	Use case for registered subscribers related measurements for EPC	82
A.19	Use case of PDN Connections related measurements for EPC	82
A.20	Use case of MME processor usage	82
A.21	Use case for EPS Service Request related Measurements	82
A.22	Use case for session management based on SGW related Measurements	83
A.23	Use case for MBMS session related measurements	83
A.24	Use case of SGW bearer deletion related measurements	83

A.25	Use case of bearer resource usage related measurements	83
A.26	Use case for M1 data volume related measurements	83
A.27	Use case for combined TA/LA update procedure related measurements.....	84
A.28	Use case of S4 data volume related measurements	84
A.29	Use case of S12 data volume related measurements	84
A.30	Use case of implicit detach related measurements	84
A.31	Use case for IP-CAN session establishment related measurements.....	84
A.32	Use case for credit re-authorization procedure related measurements	85
A.33	Use case for IP-CAN session related measurements.....	85
A.34	Use case for update location related measurements	85
A.35	Use case for authentication information retrieval related measurements.....	85
A.36	Use case for Number of EPS bearer in PGW related measurements	86
Annex B (informative):	Change history	87
History		89

iTeh STANDARD PREVIEW
 (standards.iteh.ai)
 Full standard:
<https://standards.iteh.ai/catalog/standards/sist/dd5083b1-8209-4b01-8f76-e0658b3d46e5/etsi-ts-132-426-v11.5.0-2019-10>

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management; as identified below:

32.401	Performance Management (PM); Concept and requirements
52.402	Performance Management (PM); Performance measurements - GSM
32.404	Performance Management (PM); Performance measurements - Definitions and template
32.405	Performance Management (PM); Performance measurements Universal Terrestrial Radio Access Network (UTRAN)
32.406	Performance Management (PM); Performance measurements Core Network (CN) Packet Switched (PS) domain
32.407	Performance Management (PM); Performance measurements Core Network (CN) Circuit Switched (CS) domain
32.408	Performance Management (PM); Performance measurements Teleservice
32.409	Performance Management (PM); Performance measurements IP Multimedia Subsystem (IMS)
32.425	Performance Management (PM); Performance measurements Evolved Universal Terrestrial Radio Access Network (E-UTRAN)
32.426	Performance Management (PM); Performance measurements Evolved Packet Core network (EPC)

The present document is part of a set of specifications, which describe the requirements and information model necessary for the standardised Operation, Administration and Maintenance (OA&M) of a multi-vendor LTE SAE-system.

During the lifetime of a LTE SAE network, its logical and physical configuration will undergo changes of varying degrees and frequencies in order to optimise the utilisation of the network resources. These changes will be executed through network configuration management activities and/or network engineering, see TS 32.600 [2].

Many of the activities involved in the daily operation and future network planning of a LTE SAE network require data on which to base decisions. This data refers to the load carried by the network and the grade of service offered. In order to produce this data performance measurements are executed in the NEs, which comprise the network. The data can then be transferred to an external system, e.g. an Operations System (OS) in TMN terminology, for further evaluation.

The purpose of the present document is to describe the mechanisms involved in the collection of the data and the definition of the data itself.

Annex B of TS 32.404 helps in the definition of new performance measurements that can be submitted to 3GPP for potential adoption and inclusion in the present document. Annex B of TS 32.404 discusses a top-down performance measurement definition methodology that focuses on how the end-user of performance measurements can use the measurements.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/dd5083b1-8209-4b01-8f76-e0658b3d46e5/etsi-ts-132-426-v11.5.0-2019-10>

1 Scope

The present document describes the measurements for EPC and combined EPC/UMTS/GSM.

TS 32.401 [1] describes Performance Management concepts and requirements.

The present document is valid for all measurement types provided by an implementation of an EPC network and combined EPC/UMTS/GSM network. Only measurement types that are specific to EPC or combined EPC/UMTS/GSM networks are defined within the present documents.

Vendor specific measurement types used in EPC and combined EPC/UMTS/GSM networks are not covered. Instead, these could be applied according to manufacturer's documentation.

Measurements related to "external" technologies (such as IP) as described by "external" standards bodies (e.g. IETF) shall only be referenced within this specification, wherever there is a need identified for the existence of such a reference.

The definition of the standard measurements is intended to result in comparability of measurement data produced in a multi-vendor network, for those measurement types that can be standardised across all vendors' implementations.

The structure of the present document is as follows:

- Header 1: Network Element (e.g. MME related measurements);
- Header 2: Measurement function;
- Header 3: Measurements.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 32.401: "Telecommunication management; Performance Management (PM); Concept and requirements".
- [2] 3GPP TS 32.600: "Telecommunication management; Configuration Management (CM); Concept and high-level requirements".
- [3] 3GPP TS 24.301: "Technical Specification Group Core Network and Terminals; Non-Access-Stratum (NAS) protocol for Evolved Packet System (EPS); Stage 3".
- [4] 3GPP TS 29.274: "Evolved General Packet Radio Service (GPRS); Tunnelling Protocol for Control plane (GTPv2-C); Stage 3".
- [5] 3GPP TS 23.401: "General Packet Radio Service (GPRS) enhancements for Evolved Universal Terrestrial Radio Access Network (E-UTRAN) access (Release 8)".
- [6] 3GPP TS 29.274: "Tunnelling Protocol for Control plane (GTPv2-C)".
- [7] 3GPP TS 29.281: "GPRS Tunnelling Protocol User Plane (GTPv1-U)".
- [8] 3GPP TS 36.414: "Evolved Universal Terrestrial Access Network (E-UTRAN); S1 data transport".
- [9] 3GPP TS 29.272: "Mobility Management Entity (MME) and Serving GPRS Support Node (SGSN) related interfaces based on Diameter protocol".

- [10] 3GPP TS 23.203: "Policy and charging control architecture".
- [11] 3GPP TS 36.413: "Evolved Universal Terrestrial Radio Access Network (E-UTRAN); S1 Application Protocol (S1AP)".
- [12] 3GPP TS 36.412: "Evolved Universal Terrestrial Access Network (E-UTRAN); S1 signaling transport".
- [13] 3GPP TS 23.402: "Architecture enhancements for non-3GPP accesses".
- [14] IETF RFC 5136: "Defining Network Capacity".
- [15] 3GPP TS 23.246: "Multimedia Broadcast Multicast Service (MBMS); Architecture and functional description".
- [16] 3GPP TS 36.445: "Evolved Universal Terrestrial Radio Access Network (E-UTRAN); M1 data transport".
- [17] 3GPP TS 23.272: Circuit Switched (CS) fallback in Evolved Packet System (EPS); Stage 2.
- [18] 3GPP TS 29.212: "Policy and charging control over Gx reference point".
- [19] 3GPP TS 29.213: "Policy and charging control signalling flows and Quality of Service (QoS) parameter mapping".
- [20] IETF RFC 3588: "Diameter Base Protocol"

3 Measurement family and abbreviations

3.1 Measurement family

The measurement names defined in the present document are all beginning with a prefix containing the measurement family name. This family name identifies all measurements which relate to a given functionality and it may be used for measurement administration (see TS 32.401 [1]).

The list of families currently used in the present document is as follows:

- EQPT (measurements related to Equipment)
- MM (measurements related to Mobility Management)
- GTP (measurements related to GTP Management)
- IP (measurements related to IP Management)
- IRATHO (measurements related to Inter-Radio Access Technology Handover)
- QOS (measurements related to Quality Of Service)
- SEC (measurements related to Security)
- SM (measurements related to Session Management)
- SUB (measurements related to Subscriber Management)

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

EQPT	Equipment
EPC	Evolved Packet Core
GTP	GPRS Tunnelling Protocol