

# ETSI TS 132 661 V15.1.0 (2019-10)



**Digital cellular telecommunications system (Phase 2+) (GSM);  
Universal Mobile Telecommunications System (UMTS);  
LTE;  
Telecommunication management;  
Configuration Management (CM);  
Kernel CM Requirements  
(3GPP TS 32.661 version 15.1.0 Release 15)**



---

**Reference**

RTS/TSGS-0532661vf10

---

**Keywords**

GSM,LTE,UMTS

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

**GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

## Intellectual Property Rights

### Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

### Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

---

## Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

Intellectual Property Rights .....	2
Legal Notice .....	2
Modal verbs terminology.....	2
Foreword.....	4
Introduction .....	4
1 Scope .....	5
2 References .....	5
3 Definitions and abbreviations.....	5
3.1 Definitions .....	5
3.3 Abbreviations .....	6
4 Requirements.....	7
4.1 General Requirements .....	7
4.2 Kernel CM Requirements.....	7
<b>Annex A (informative): Change history .....</b>	<b>8</b>
History .....	9

**iTeh STANDARD PREVIEW**  
 (standards.iteh.ai)  
 Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/b783a521-4492-4b61-8aa7-86ceb9a6e3e/etsi-ts-132-661-v15.1.0-2019-10>

---

## Foreword

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

---

## Introduction

The present document is part of a TS-family covering the 3<sup>rd</sup> Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management; as identified below:

### **32.661 Configuration Management (CM); Kernel CM Requirements**

32.662 Configuration Management (CM); Kernel CM Information Service (IS)

32.666: Configuration Management (CM); Kernel CM Integration Reference Point (IRP); Solution Set (SS) definitions

Configuration Management (CM), in general, provides the operator with the ability to assure correct and effective operation of the 3G network as it evolves. CM actions have the objective to control and monitor the actual configuration on the Network Elements (NEs) and network resources, and they may be initiated by the operator or by functions in the Operations Systems (OSs) or NEs.

CM actions may be requested as part of an implementation programme (e.g. additions and deletions), as part of an optimisation programme (e.g. modifications), and to maintain the overall Quality of Service (QoS). The CM actions are initiated either as single actions on single NEs of the 3G network, or as part of a complex procedure involving actions on many resources/objects in one or several NEs.

---

# 1 Scope

The present document defines, in addition to the requirements defined in 3GPP TS 32.101 [1], 3GPP TS 32.102 [2] and 3GPP TS 32.600 [3], the requirements for the present IRP: Kernel Configuration Management IRP. It is the intent of Kernel Configuration Management to provide an IRP that contains the configuration management functionality that is basic and minimal. It is the functionality that is common to and required by both Basic CM and Bulk CM. While neither the Basic CM IRP nor Bulk CM IRP requires the other, they each require the Kernel CM IRP.

---

# 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
- [2] 3GPP TS 32.102: "Telecommunication management; Architecture".
- [3] 3GPP TS 32.600: "Telecommunication management; Configuration Management (CM); Concept and high-level requirements".
- [4] 3GPP TS 32.622: "Telecommunication management; Configuration Management (CM); Generic network resources Integration Reference Point (IRP): Network Resource Model (NRM)".
- [5] 3GPP TS 32.632: "Telecommunication management; Configuration Management (CM); Core Network Resources Integration Reference Point (IRP): Network Resource Model (NRM)".
- [6] 3GPP TS 32.642: "Telecommunication management; Configuration Management (CM); UTRAN network resources Integration Reference Point (IRP): Network Resource Model (NRM)".
- [7] 3GPP TS 32.652: "Telecommunication management; Configuration Management (CM); GERAN network resources Integration Reference Point (IRP): Network Resource Model (NRM)".
- [8] 3GPP TS 32.662: "Telecommunication management; Configuration Management (CM); Kernel CM Information Service (IS)".
- [9] Void
- [10] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [11] 3GPP TS 28.622: "Telecommunication management; Generic Network Resource Model (NRM) Integration Reference Point (IRP); Information Service (IS)".

---

# 3 Definitions and abbreviations

## 3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [10], 3GPP TS 32.101 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [10] and 3GPP TS 32.101 [1].

**Element Manager (EM):** provides a package of end-user functions for management of a set of closely related types of Network Elements (NEs). These functions can be divided into two main categories:

*Element Management Functions* for management of NEs on an individual basis. These are basically the same functions as supported by the corresponding local terminals.

*Sub-Network Management Functions* that are related to a network model for a set of NEs constituting a clearly defined sub-network, which may include relations between the NEs. This model enables additional functions on the sub-network level (typically in the areas of network topology presentation, alarm correlation, service impact analysis and circuit provisioning).

**IRP:** See 3GPP TS 32.101 [1].

**IRP Information Model:** See 3GPP TS 32.101 [1].

**IRP Information Service:** See 3GPP TS 32.101 [1].

**IRP Solution Set:** See 3GPP TS 32.101 [1].

**Managed Object (MO):** abstract entity, which may be accessed through an open interface between two or more systems, and representing a network resource for the purpose of management.

NOTE 1: The Managed Object (MO) is an instance of a Managed Object Class (MOC) as defined in a Management Information Model (MIM). The MIM does not define how the MO or network resource is implemented; only what can be seen in the interface.

**Managed Object Class (MOC):** description of all the common characteristics for a number of MOs, such as their attributes, operations, notifications and behaviour

**Managed Object Instance (MOI):** instance of a MOC, which is the same as a MO as described above

**Management Information Base (MIB):** set of existing managed objects in a management domain, together with their attributes, constitutes that management domain's MIB. The MIB may be distributed over several OS/NEs.

**Management Information Model (MIM):** also referred to as NRM – see the definition below.

NOTE 2: There is a slight difference between the meaning of MIM and NRM – the term MIM is generic and can be used to denote any type of management model, while NRM denotes the model of the actual managed telecommunications Network Resources (NRs).

**Network Manager (NM):** provides a package of end-user functions with the responsibility for the management of a network, mainly as supported by the EM(s) but it may also involve direct access to the NEs.

NOTE 3: All communication with the network is based on open and well-standardised interfaces supporting management of multi-vendor and multi-technology NEs.

**Network resource:** See definition in 3GPP TS 3GPP 28.622 [11].

**Network Resource Model (NRM):** See definition in 3GPP TS 3GPP 28.622 [11].

**Operations System (OS):** indicates a generic management system, independent of its location level within the management hierarchy

### 3.3 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [10] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [10].

CM Configuration Management

## 4 Requirements

### 4.1 General Requirements

This requirements specification defines requirements for the IS for this IRP. As such, capabilities specified here as being required in the IS are not necessarily required in the product implementation. That which is required in the product implementation will be specified in the IS itself.

The following general and high-level requirements apply for the present IRP:

- A. IRP-related requirements in 3GPP TS 32.101 [1].
- B. IRP-related requirements in 3GPP TS 32.102 [2].
- C. IRP-related requirements in 3GPP TS 32.600 [3].

In addition to the above, the following more specific requirements apply:

1. The IS defined by this IRP shall enable an NM to operate on (access) any NRMs defined in any NRM IRPs, such as those defined in [4], [5], [6], [7] and [8].
2. The IS defined by this IRP shall as far as possible be independent of any specific definitions of MOCs, attributes etc. in the NRMs referred to in item 1.

### 4.2 Kernel CM Requirements

The IS defined by this IRP shall include the following operations that may be invoked by the IRP Manager to retrieve management information from the IRP Agent:

- An operation to retrieve the Network Resource IRP SS document versions (IRP Versions) of the NRM Solution Sets that are supported by each Network Resource IRP present in the subject implementation.

The IS defined by this IRP shall include a notification capability by which the IRP Agent sends management information to the IRP Manager whenever an event of a specific type occurs. Whether these notifications are mandatory or optional is specified in the Information Service (3GPP TS 32.662 [8]). Specifically, the following types of notifications shall be supported:

- A notification that identifies the instance of a managed object that was created.
- A notification that identifies one or more instances of a managed object that were deleted.
- A notification that identifies the values of one or more attributes of a managed object instance that were changed.
- A notification that enables reporting of state and status changes of a managed object instance.
- A notification which identifies that part of or the whole configuration information of managed system should be synchronized.



## Annex A (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
Mar 2002	S_15	SP-020034	--	--	Submitted to TSG SA #15 for Information	1.0.0	
Sep 2002	S_17	SP-020464	--	--	Submitted to TSG SA #17 for Approval	2.0.0	5.0.0
Dec 2002	S_18	SP-020750	001	--	Clarification regarding optionality of notifications	5.0.0	5.1.0
Mar 2003	S_19	SP-030145	002	--	Add requirement for the emission of notifyCMSynchronizationRecommended notification	5.1.0	6.0.0
Jun 2004	S_24	SP-040260	003	--	Add State Management Support to Kernel CM IRP Requirements	6.0.0	6.1.0
Dec 2004	S_26	SP-040812	004	--	Add Signalling Transport Network (STN) NRM IRP in KernelCM IRP Requirements	6.1.0	6.2.0
Feb 2005	--	--	--	--	History box clean-up to show only the 32661 Dec 2004 CRs	6.2.0	6.2.1
Jun 2007	SA_36	--	--	--	Automatic upgrade to Rel-7 (no CR) at freeze of Rel-7. Deleted reference to CMIP SS, discontinued from R7 onwards.	6.2.1	7.0.0
Dec 2008	SA_42	--	--	--	Upgrade to Release 8	7.0.0	8.0.0
Sep 2009	SA_45	SP-090534	005	--	Add missing NRMs into scope of Kernel CM IRP	8.0.0	8.1.0
Dec 2009	--	--	--	--	Change history correction	8.1.0	8.1.1
Dec 2009	-	-	-	-	Update to Rel-9 version	8.1.1	9.0.0
2011-03	-	-	-	-	Update to Rel-10 version (MCC)	9.0.0	10.0.0
2012-09	-	-	-	-	Update to Rel-11 version (MCC)	10.0.0	11.0.0
2014-10	-	-	-	-	Update to Rel-12 version (MCC)	11.0.0	12.0.0
2016-01	-	-	-	-	Update to Rel-13 version (MCC)	12.0.0	13.0.0
2017-04	SA#75	-	-	-	Promotion to Release 14 without technical change	13.0.0	14.0.0
2018-06	-	-	-	-	Update to Rel-15 version (MCC)	14.0.0	15.0.0

Change history							
Date	Meeting	TDoc	CR	Rev	Cat	Subject/Comment	New version
2019-09	SA#85	SP-190752	0006	-	F	Correction of NR definition to avoid misalignment with SA2	15.1.0