

ETSI TS 129 163 V14.13.0 (2019-10)



**Digital cellular telecommunications system (Phase 2+) (GSM);
Universal Mobile Telecommunications System (UMTS);
LTE;
Interworking between the IP Multimedia (IM) Core Network (CN)
subsystem and Circuit Switched (CS) networks
(3GPP TS 29.163 version 14.13.0 Release 14)**



Reference

RTS/TSGC-0329163ved0

Keywords

GSM,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	17
1 Scope	18
2 References	18
3 Definitions and abbreviations.....	24
3.1 Definitions	24
3.2 Abbreviations	25
4 General	27
4.1 General interworking overview	27
5 Network characteristics	27
5.1 Key characteristics of ISUP/BICC based CS networks	27
5.2 Key characteristics of IM CN subsystem	27
6 Interworking with CS networks	27
6.1 Interworking reference model	27
6.1.1 Interworking reference points and interfaces	28
6.1.2 Interworking functional entities	28
6.1.2.1 Signalling Gateway Function (SGW)	28
6.1.2.2 Media Gateway Control Function (MGCF)	28
6.1.2.3 IP Multimedia - Media Gateway Function (IM-MGW)	28
6.2 Control plane interworking model	29
6.3 User plane interworking model	29
7 Control plane interworking	29
7.1 General	29
7.2 Interworking between CS networks supporting ISUP and the IM CN subsystem	30
7.2.1 Services performed by network entities in the control plane	30
7.2.1.1 Services performed by the SS7 signalling function	30
7.2.1.2 Services of the SGW	30
7.2.1.3 Services of the MGCF	31
7.2.1.4 Services of the SIP signalling function	31
7.2.2 Signalling interactions between network entities in the control plane	31
7.2.2.1 Signalling between the SS7 signalling function and MGCF	31
7.2.2.1.1 Signalling from MGCF to SS7 signalling function	31
7.2.2.1.2 Signalling from SS7 signalling function to MGCF	31
7.2.2.1.3 Services offered by SCTP and M3UA	31
7.2.2.1.3.1 Services offered by SCTP	31
7.2.2.1.3.2 Services offered by M3UA	31
7.2.2.2 Signalling between the MGCF and SIP signalling function	32
7.2.3 SIP-ISUP protocol interworking	32
7.2.3.1 Incoming call interworking from SIP to ISUP at I-MGCF	32
7.2.3.1.1 Sending of IAM	32
7.2.3.1.2 Coding of the IAM	33
7.2.3.1.2.0 General	33
7.2.3.1.2.1 Called party number	33
7.2.3.1.2.2 Nature of connection indicators	34
7.2.3.1.2.3 Forward call indicators	35
7.2.3.1.2.4 Calling party's category	36
7.2.3.1.2.4A Originating Line Information	36
7.2.3.1.2.5 Transmission medium requirement	36
7.2.3.1.2.5a Transmission medium requirement prime and USI prime (optional)	38
7.2.3.1.2.6 Calling party number	40

7.2.3.1.2.7	Generic number.....	45
7.2.3.1.2.8	User service information.....	45
7.2.3.1.2.9	Hop Counter (National option)	45
7.2.3.1.2.10	Progress Indicator	46
7.2.3.1.2.11	Location Number	46
7.2.3.1.2.12	Support of ICS call	48
7.2.3.1.2.13	UID capability indicators (National option)	48
7.2.3.1.2.14	Called IN number and original called IN number (optional)	49
7.2.3.1.2A	Coding of the IAM when Number Portability is supported.....	49
7.2.3.1.2A.1	Coding of the IAM when a Number Portability Routing Number is available.....	49
7.2.3.1.2A.1.1	Separate Directory Number Addressing Method	50
7.2.3.1.2A.1.2	Concatenated Addressing Method.....	51
7.2.3.1.2A.1.3	Separate Network Routing Number Addressing Method	51
7.2.3.1.2A.2	Number Portability Forward Information	52
7.2.3.1.2B	Coding of the IAM for Carrier Routeing.....	52
7.2.3.1.2B.1	Coding of the IAM when a Carrier Identification Code (CIC) is present	52
7.2.3.1.2B.2	Void	52
7.2.3.1.3	Sending of COT.....	52
7.2.3.1.3A	Sending of SAM	53
7.2.3.1.3A.1	General.....	53
7.2.3.1.3A.2	Additional digits received in in-dialog SIP INFO requests.....	53
7.2.3.1.3A.3	Additional digits received in SIP INVITE requests	53
7.2.3.1.4	Sending of 180 ringing	54
7.2.3.1.4.0	General.....	54
7.2.3.1.4.0a	PSTN XML body.....	55
7.2.3.1.4.0b	Fallback by I-MGCF.....	56
7.2.3.1.4.1	Fallback in a succeeding network: Transmission Medium Used parameter (TMU) received.....	57
7.2.3.1.4A	Sending of 183 Session Progress for early media scenarios	57
7.2.3.1.4B	Sending of 181Call is being forwarded	60
7.2.3.1.4C	Sending of 183 Session Progress for overlap signalling using the in-dialog method	61
7.2.3.1.4D	Sending of 183 Session Progress to carry ISUP Cause	61
7.2.3.1.4E	Sending of 183 Session Progress for ICS call	61
7.2.3.1.5	Sending of the 200 OK (INVITE)	62
7.2.3.1.6	Sending of the Release message (REL).....	64
7.2.3.1.7	Coding of the REL.....	64
7.2.3.1.8	Receipt of the Release Message	66
7.2.3.1.9	Receipt of RSC, GRS or CGB (H/W oriented)	70
7.2.3.1.9a	Receipt of REFER	70
7.2.3.1.10	Autonomous Release at I-MGCF	71
7.2.3.1.11	Internal through connection of the bearer path.....	71
7.2.3.2	Outgoing Call Interworking from ISUP to SIP at O-MGCF.....	71
7.2.3.2.1	Sending of INVITE	71
7.2.3.2.1.1	General.....	71
7.2.3.2.1.2	Interaction with continuity check.....	72
7.2.3.2.1.3	IAM without calling party number	72
7.2.3.2.1.4	Terminating overlap signalling at MGCF.....	73
7.2.3.2.1.5	Fallback (optional)	73
7.2.3.2.1a	Sending of INVITE without determining the end of address signalling.....	74
7.2.3.2.1a.1	General.....	74
7.2.3.2.1a.2	Additional digits sent with in-dialog overlap method.....	74
7.2.3.2.1a.3	Additional digits sent using the multiple INVITEs overlap method.....	75
7.2.3.2.2	Coding of the INVITE.....	76
7.2.3.2.2.0	Overview.....	76
7.2.3.2.2.1	Request-URI and To header field	76
7.2.3.2.2.2	SDP Media Description	77
7.2.3.2.2.3	P-Asserted-Identity, From and Privacy header fields	81
7.2.3.2.2.3A	"cp" URI Parameter in P-Asserted-Identity Header	86
7.2.3.2.2.3B	"oli" URI Parameter in P-Asserted-Identity Header	86
7.2.3.2.2.4	Max Forwards header	87
7.2.3.2.2.5	IMS Communication Service Identifier	87
7.2.3.2.2.6	P-Early-Media header field.....	87

7.2.3.2.2.7	PSTN XML elements.....	87
7.2.3.2.2.8	Progress indicator	88
7.2.3.2.2.9	P-Access-Network-Info	89
7.2.3.2.2A	Coding of the INVITE when Number Portability is supported	89
7.2.3.2.2A.1	Request-URI and To header field	89
7.2.3.2.2A.1.1	Separate Directory Number Addressing Method	90
7.2.3.2.2A.1.2	Concatenated Addressing Method.....	90
7.2.3.2.2A.1.3	Separate Network Routing Number Addressing Method	91
7.2.3.2.2B	Coding of the INVITE for Carrier Routeing	91
7.2.3.2.2B.1	Mapping of "cic" in Request-URI.....	91
7.2.3.2.2B.2	Void	91
7.2.3.2.2C	Coding of INVITE with instance-id in form of IMEI URN	91
7.2.3.2.2.10	PSAP Call-back indication	92
7.2.3.2.2.11	History-Info header field (optional)	92
7.2.3.2.3	Receipt of CONTINUITY.....	92
7.2.3.2.4	Sending of ACM and awaiting answer indication	93
7.2.3.2.5	Coding of the ACM	95
7.2.3.2.5.0	General.....	95
7.2.3.2.5.1	Backward call indicators.....	95
7.2.3.2.5.2	Optional Backward call indicators	97
7.2.3.2.5.3	Access Transport Parameter, Transmission medium used parameter	97
7.2.3.2.5.4	Progress indicator	98
7.2.3.2.5.5	Cause Value	98
7.2.3.2.6	Sending of the Call Progress message (CPG).....	98
7.2.3.2.6.0	General.....	98
7.2.3.2.6.1	Handling of the progress indicator.....	100
7.2.3.2.7	Coding of the CPG	100
7.2.3.2.7.0	General.....	100
7.2.3.2.7.1	Event information	101
7.2.3.2.7.2	Access Transport Parameter.....	101
7.2.3.2.7.3	Void	101
7.2.3.2.7.4	Handling of Backward Call indicators.....	101
7.2.3.2.7.5	Optional Backward call indicators.....	101
7.2.3.2.7.6	Cause Value	101
7.2.3.2.7a	Receipt of 200 OK(INVITE).....	102
7.2.3.2.7b	Internal through connection of the bearer path.....	102
7.2.3.2.8	Sending of the Answer Message (ANM).....	102
7.2.3.2.9	Coding of the ANM.....	102
7.2.3.2.9.1	Backwards Call Indicators	102
7.2.3.2.9.2	Access Transport Parameter.....	102
7.2.3.2.9.3	Transmission Medium Used parameter (TMU).....	103
7.2.3.2.10	Sending of the Connect message (CON).....	104
7.2.3.2.11	Coding of the CON.....	104
7.2.3.2.11.0	General.....	104
7.2.3.2.11.1	Backward call indicators.....	104
7.2.3.2.11.2	Access Transport Parameter.....	104
7.2.3.2.11.3	Transmission medium used parameter.....	104
7.2.3.2.11A	Receipt of a reINVITE request.....	104
7.2.3.2.12	Receipt of Status Codes 4xx, 5xx or 6xx.....	104
7.2.3.2.12.1	Special handling of 404 Not Found and 484 Address Incomplete responses after sending of INVITE without determining the end of address signalling	107
7.2.3.2.13	Receipt of a BYE.....	107
7.2.3.2.14	Receipt of the Release Message	107
7.2.3.2.15	Receipt of RSC, GRS or CGB (H/W oriented)	107
7.2.3.2.16	Autonomous Release at O-MGCF.....	108
7.2.3.2.17	Special handling of 580 precondition failure received in response to either an INVITE or UPDATE	108
7.2.3.2.17.1	580 Precondition failure response to an INVITE.....	108
7.2.3.2.17.2	580 Precondition failure response to an UPDATE within an early dialog.....	108
7.2.3.2.18	Sending of CANCEL.....	109
7.2.3.2.19	Receipt of SIP redirect (3xx) response	109
7.2.3.2.20	Sending of INFO for overlap signalling using the in-dialog method	109

7.2.3.2.20.1	General.....	109
7.2.3.2.20.2	Encoding of the INFO.....	109
7.2.3.3	Timers	110
7.3	Interworking between CS networks supporting BICC and the IM CN subsystem.....	110
7.3.1	Services performed by network entities in the control plane.....	111
7.3.2	Signalling interactions between network entities in the control plane.....	111
7.3.2.1	Signalling between the SS7 signalling function and MGCF.....	111
7.3.2.1.1	Signalling from MGCF to SS7 signalling function	111
7.3.2.1.2	Signalling from SS7 signalling function to MGCF	111
7.3.2.1.3	Services offered by STC, SCTP and M3UA	112
7.3.2.1.3.1	Services offer by SCTP.....	112
7.3.2.1.3.2	Services offered by M3UA	112
7.3.2.1.3.3	Services offered by STC	112
7.3.2.2	Signalling between the MGCF and SIP signalling function.....	112
7.3.3	SIP-BICC protocol interworking	112
7.3.3.1	Incoming call interworking from SIP to BICC at I-MGCF.....	112
7.3.3.1.1	Sending of IAM.....	112
7.3.3.1.2	Coding of IAM	112
7.3.3.1.2.1	Called party number.....	112
7.3.3.1.2.2	Nature of connection indicators	112
7.3.3.1.2.3	Forward call indicators	113
7.3.3.1.2.4	Calling party's category	113
7.3.3.1.2.4A	Originating Line Information.....	113
7.3.3.1.2.5	Transmission medium requirement.....	113
7.3.3.1.2.6	Calling party number	113
7.3.3.1.2.7	Generic number.....	113
7.3.3.1.2.8	User service information.....	113
7.3.3.1.2.9	Hop counter (National option)	113
7.3.3.1.2.10	Location Number	113
7.3.3.1.2.11	Support of ICS call	113
7.3.3.1.2.12	UID capability indicators (National option)	113
7.3.3.1.2A	Coding of the IAM when Number Portability is supported.....	113
7.3.3.1.2B	Coding of the IAM for Carrier Routing.....	113
7.3.3.1.2.13	Called IN number and original called IN number (optional)	113
7.3.3.1.3	Sending of COT.....	114
7.3.3.1.3A	Sending of SAM.....	114
7.3.3.1.4	Sending of 180 Ringing.....	114
7.3.3.1.4A	Sending of 183 Session Progress for early media scenarios.....	114
7.3.3.1.4B	Sending of 181 Call is being forwarded.....	114
7.3.3.1.4C	Sending of 183 Session Progress for overlap signalling using the in-dialog method	114
7.3.3.1.4D	Sending of 183 Session Progress to carry ISUP Cause	114
7.3.3.1.4E	Sending of 183 Session Progress for ICS call	114
7.3.3.1.5	Sending of the 200 OK (INVITE).....	115
7.3.3.1.6	Sending of the Release message (REL).....	115
7.3.3.1.7	Coding of the REL.....	115
7.3.3.1.8	Receipt of the Release Message	115
7.3.3.1.9	Receipt of RSC, GRS or CGB (H/W oriented)	115
7.3.3.1.9a	Receipt of REFER	115
7.3.3.1.9b	Autonomous Release at I-MGCF	115
7.3.3.1.10	Internal through connection of the bearer path.....	115
7.3.3.1.11	Out of Band DTMF	115
7.3.3.2	Outgoing Call Interworking from BICC to SIP at O-MGCF	115
7.3.3.2.1	Sending of INVITE	115
7.3.3.2.1a	Sending of INVITE without determining the end of address signalling.....	116
7.3.3.2.2	Coding of the INVITE.....	116
7.3.3.2.2.1	Request-URI and To header field	116
7.3.3.2.2.2	SDP Media Description	116
7.3.3.2.2.3	P-Asserted-Identity and privacy header fields	116
7.3.3.2.2.3A	"cpc" URI Parameter in P-Asserted-Identity Header	116
7.3.3.2.2.3B	"oli" URI Parameter in P-Asserted-Identity Header	116
7.3.3.2.2.4	Max Forwards header	116
7.3.3.2.2.5	IMS Communication Service Identifier.....	117

7.3.3.2.2.6	P-Access-Network-Info	117
7.3.3.2.2A	Coding of the INVITE when number portability is supported	117
7.3.3.2.2B	Coding of the INVITE for Carrier Routing	117
7.3.3.2.2C	Coding of INVITE with instance-id in form of IMEI URN	117
7.3.3.2.2.7	PSAP Call-back indication	117
7.3.3.2.2.8	History-Info header field (optional)	117
7.3.3.2.3	Sending of UPDATE	117
7.3.3.2.4	Sending of ACM and Awaiting Answer indication	118
7.3.3.2.5	Coding of the ACM	118
7.3.3.2.5.1	Backward call indicators	118
7.3.3.2.6	Sending of the Call Progress message (CPG)	118
7.3.3.2.7	Coding of the CPG	118
7.3.3.2.7.1	Event information	118
7.3.3.2.7.2	Optional Backward call indicators	118
7.3.3.2.7a	Receipt of 200 OK (INVITE)	118
7.3.3.2.7b	Internal through connection of the bearer path	118
7.3.3.2.8	Sending of the Answer Message (ANM)	118
7.3.3.2.9	Coding of the ANM	118
7.3.3.2.10	Sending of the Connect message (CON)	118
7.3.3.2.11	Coding of the CON	118
7.3.3.2.11.1	Void	119
7.3.3.2.11A	Receipt of re-INVITE requests	119
7.3.3.2.12	Receipt of Status Codes 4xx, 5xx or 6xx	119
7.3.3.2.13	Receipt of a BYE	119
7.3.3.2.14	Receipt of the Release Message	119
7.3.3.2.15	Receipt of RSC, GRS or CGB (H/W oriented)	119
7.3.3.2.16	Out of Band DTMF	119
7.3.3.2.17	Sending of CANCEL	119
7.3.3.2.18	Autonomous Release at O-MGCF	119
7.3.3.2.19	Special handling of 580 precondition failure received in response to either an INVITE or UPDATE	119
7.3.3.2.20	Receipt of SIP redirect (3xx) response	119
7.3.3.2.21	Sending of INFO for overlap signalling using the in-dialog method	119
7.3.3.3	Timers	120
7.4	Supplementary Services	120
7.4.1	Calling line identification presentation/restriction (CLIP/CLIR)	120
7.4.2	Connected line presentation and restriction (COLP/COLR)	120
7.4.2.0	General	120
7.4.2.1	Incoming Call Interworking from SIP to BICC/ISUP at the I-MGCF	120
7.4.2.1.1	INVITE to IAM interworking (SIP to ISUP/BICC calls)	120
7.4.2.1.2	ANM/CON to 200 OK (INVITE)	120
7.4.2.2	Outgoing Call Interworking from BICC/ISUP to SIP at O-MGCF	121
7.4.2.2.1	IAM to INVITE interworking (ISUP to SIP calls)	121
7.4.2.2.2	1XX to ANM or CON interworking	122
7.4.2.2.3	200 OK (INVITE) to ANM/CON interworking	122
7.4.3	Direct Dialling In (DDI)	123
7.4.4	Malicious call identification	123
7.4.5	Subaddressing (SUB)	123
7.4.5.1	General	123
7.4.5.2	Interworking at I-MGCF	124
7.4.5.3	Interworking at O-MGCF	125
7.4.6	Call Forwarding Busy (CFB)/ Call Forwarding No Reply (CFNR) / Call Forwarding Unconditional (CFU) / Call Deflection (CD)	126
7.4.6.1	General	126
7.4.6.2	Interworking at the O-MGCF	126
7.4.6.2.1	General	126
7.4.6.2.2	Interworking SIP to ISUP	126
7.4.6.2.3	Interworking ISUP to SIP	130
7.4.6.3	Interworking at the I-MGCF	133
7.4.6.3.1	General	133
7.4.6.3.2	Interworking from SIP to ISUP	134
7.4.6.3.3	Interworking from ISUP to SIP	136

7.4.7	Void	142
7.4.8	Explicit Call Transfer (ECT)	142
7.4.9	Call Waiting	142
7.4.10	Call Hold.....	142
7.4.10.1	Session hold initiated from the IM CN subsystem side.....	142
7.4.10.2	Session hold initiated from the CS network side.....	143
7.4.11	Call Completion on busy subscriber	146
7.4.12	Completion of Calls on No Reply (CCNR)	146
7.4.13	Terminal Portability (TP).....	146
7.4.14	Conference calling (CONF) / Three-Party Service (3PTY).....	146
7.4.15	Void	147
7.4.16	Closed User Group (CUG)	147
7.4.17	Multi-Level Precedence and Pre-emption (MLPP).....	147
7.4.18	Global Virtual Network Service (GVNS).....	147
7.4.19	International telecommunication charge card (ITCC)	147
7.4.20	Reverse charging (REV).....	147
7.4.21	User-to-User Signalling (UUS).....	147
7.4.21.0	General	147
7.4.21.1	User-to-User Signalling (UUS) service 1 (implicit).....	147
7.4.21.1.0	General	147
7.4.21.1.1	Void	148
7.4.21.1.2	User-to-user information Interworking from SIP to ISUP	148
7.4.21.1.3	User-to-user information Interworking from ISUP to SIP	148
7.4.21.2	User-to-User Signalling (UUS) service 1 (explicit).....	148
7.4.21.3	User-to-User Signalling (UUS) service 2 (explicit)	148
7.4.21.4	User-to-User Signalling (UUS) service 3 (explicit)	148
7.4.22	Multiple Subscriber Number (MSN)	149
7.4.23	Anonymous Call rejection	149
7.4.23.0	General	149
7.4.23.1	ISUP-SIP protocol interworking at the I-MGCF	149
7.4.23.2	SIP-ISUP protocol interworking at the O-MGCF	149
7.4.24	Customized Alerting Tones (CAT) in the 3GPP CS domain.....	149
7.5	IMS Supplementary Services.....	149
7.5.1	Originating Identification Presentation (OIP) and Originating Identification Restriction (OIR).....	149
7.5.2	Terminating Identification Presentation (TIP) and Terminating Identification Restriction (TIR).....	149
7.5.2.1	General	149
7.5.2.2	Interworking at the O-MGCF.....	149
7.5.2.3	Interworking at the I-MGCF	151
7.5.2.4	Timer.....	152
7.5.3	void	152
7.5.4	Communication Diversion (CDIV).....	152
7.5.4.1	General	152
7.5.4.2	Interworking at the O-MGCF.....	153
7.5.4.2.1	General	153
7.5.4.2.2	Call Diversion within the ISUP Network appeared.....	158
7.5.4.3	Interworking at the I-MGCF	161
7.5.5	Communication Hold (HOLD).....	169
7.5.6	Conference call (CONF).....	169
7.5.6.1	General	169
7.5.6.2	Subscribing for the conference event package	169
7.5.6.3	Interworking the notification.....	170
7.5.7	Anonymous Communication Rejection (ACR) and Communication Barring (CB).....	170
7.5.8	Message Waiting Indication (MWI)	171
7.5.9	Malicious Communication Identification (MCID)	171
7.5.9.0	General	171
7.5.9.1	Interworking at the O-MGCF.....	171
7.5.9.1.0	General	171
7.5.9.1.1	Interworking of the MCID XML Request schema with the ISUP MCID request indicators	171
7.5.9.1.2	Interworking of the ISUP MCID response indicators with the MCID XML Response schema ...	172
7.5.9.1.3	Interworking of the ISUP Calling Party Number in an Identification Response with the OrigPartyIdentity within the MCID XML Response schema.....	172

7.5.9.1.4	Interworking of the ISUP Generic Number in an Identification Response with the GenericNumber within the MCID XML Response schema	172
7.5.9.2	Interworking at the I-MGCF	172
7.5.9.2.1	General	172
7.5.9.2.2	Interworking of identification Request	172
7.5.9.2.3	Interworking of identification Response.....	173
7.5.10	Closed User Group (CUG)	173
7.5.10.0	General	173
7.5.10.1	Interworking at the I-MGCF	173
7.5.10.2	Interworking at the O-MGCF.....	174
7.5.11	CCBS/CCNR	175
7.5.11.0	General	175
7.5.11.1	Interworking at the I-MGCF	175
7.5.11.2	Interworking at the O-MGCF.....	177
7.5.12	Communication Waiting (CW).....	179
7.5.12.0	General	179
7.5.12.1	Interworking at the I-MGCF	179
7.5.12.2	Interworking at the O-MGCF.....	179
7.5.13	Customized Alerting Tones (CAT).....	179
7.5.13.1	General	179
7.5.13.2	Early session model.....	179
7.5.13.2.1	Interworking at the O-MGCF	179
7.5.13.2.2	MGCF - IM-MGW Interaction for CAT service.....	180
7.5.13.2.2.1	General.....	180
7.5.13.2.2.2	IM CN subsystem side Early Session establishment	180
7.5.13.2.2.3	IM CN subsystem side normal Session establishment.....	180
7.5.13.2.2.4	Called party alerting.....	181
7.5.13.2.2.5	Message sequence chart.....	181
7.5.13.3	Forking model.....	184
7.5.13.4	Gateway model	184
8	User plane interworking	184
8.1	Interworking between IM CN subsystem and bearer independent CS network	184
8.1.1	Transcoder-less Mb to Nb Interworking	185
8.1.1.1	Initialisation	185
8.1.1.2	Time alignment	185
8.1.1.3	Rate control	185
8.1.1.3.1	General	185
8.1.1.3.2	Rate control for AMR and AMR-WB codecs	185
8.1.1.3.3	Rate and Mode control for the EVS codec	186
8.1.1.3.4	Interworking of rate control between compatible AMR-WB and EVS codec configurations.....	187
8.1.1.3.5	Interworking between rate control and RTCP-APP-CMR messages for MTSI	187
8.1.1.4	Frame quality indication	188
8.1.1.5	Framing	188
8.1.1.6	Transcoding.....	188
8.1.1.7	Discontinuous transmission	188
8.1.1.8	Timing and sequence information.....	188
8.2	Interworking between IM CN subsystem and TDM-based CS network	189
8.3	Transcoding requirements	189
8.4	Diffserv code point requirements	189
8.5	DTMF handling.....	190
9	MGCF - IM-MGW Interaction.....	190
9.1	Overview	190
9.2	Mn signalling interactions	190
9.2.1	Network model	190
9.2.2	Basic IM CN subsystem originated session.....	191
9.2.2.1	BICC forward bearer establishment.....	191
9.2.2.1.1	IM-MGW selection	191
9.2.2.1.2	CS network side bearer establishment.....	191
9.2.2.1.3	IM CN subsystem side termination reservation.....	191
9.2.2.1.4	IM CN subsystem side session establishment	192

9.2.2.1.5	Through-connection	192
9.2.2.1.6	Codec handling.....	192
9.2.2.1.7	Failure handling in MGCF	193
9.2.2.1.8	Message sequence chart.....	193
9.2.2.2	BICC backward bearer establishment	194
9.2.2.2.1	IM-MGW selection	194
9.2.2.2.2	IM CN subsystem side termination reservation.....	195
9.2.2.2.3	IM CN subsystem side session establishment	195
9.2.2.2.4	CS network side bearer establishment.....	195
9.2.2.2.5	Through-connection	196
9.2.2.2.6	Codec handling.....	196
9.2.2.2.7	Failure handling in MGCF	196
9.2.2.2.8	Message sequence chart.....	196
9.2.2.3	ISUP	197
9.2.2.3.1	IM-MGW selection	197
9.2.2.3.2	IM CN subsystem side termination reservation.....	197
9.2.2.3.3	IM CN subsystem side session establishment	198
9.2.2.3.4	CS network side circuit reservation.....	198
9.2.2.3.5	Through-connection	198
9.2.2.3.6	Continuity check.....	199
9.2.2.3.7	Codec handling.....	199
9.2.2.3.8	Voice processing function	199
9.2.2.3.9	Failure handling in MGCF	199
9.2.2.3.10	Message sequence chart.....	199
9.2.3	Basic CS network originated session	201
9.2.3.1	BICC forward bearer establishment.....	201
9.2.3.1.1	IM-MGW selection	201
9.2.3.1.2	IM CN subsystem side termination reservation.....	201
9.2.3.1.3	IM CN subsystem side session establishment	201
9.2.3.1.4	CS network side bearer establishment	201
9.2.3.1.5	Called party alerting	202
9.2.3.1.6	Called party answer	202
9.2.3.1.7	Through-Connection.....	202
9.2.3.1.8	Codec handling.....	202
9.2.3.1.9	Failure handling in MGCF	202
9.2.3.1.10	Message sequence chart.....	202
9.2.3.2	BICC Backward bearer establishment	204
9.2.3.2.1	IM-MGW selection	204
9.2.3.2.2	CS network side bearer establishment.....	204
9.2.3.2.3	IM CN subsystem side termination reservation.....	204
9.2.3.2.4	IM CN subsystem side session establishment	205
9.2.3.2.5	Called party alerting	205
9.2.3.2.6	Called party answer	205
9.2.3.2.7	Through-Connection.....	205
9.2.3.2.8	Codec handling.....	205
9.2.3.2.9	Failure handling in MGCF	206
9.2.3.2.10	Message sequence chart.....	206
9.2.3.3	ISUP	208
9.2.3.3.1	IM-MGW selection	208
9.2.3.3.2	CS network side circuit reservation.....	208
9.2.3.3.3	IM CN subsystem side termination reservation.....	208
9.2.3.3.4	IM CN subsystem side session establishment	208
9.2.3.3.5	Called party alerting	209
9.2.3.3.6	Called party answer	209
9.2.3.3.7	Through-Connection.....	209
9.2.3.3.8	Continuity Check.....	209
9.2.3.3.9	Codec handling.....	209
9.2.3.3.10	Voice Processing function.....	210
9.2.3.3.11	Failure handling in MGCF	210
9.2.3.3.12	Message sequence chart.....	210
9.2.3.4	Handling of Forking	212
9.2.3.4.1	Detection of Forking.....	212

9.2.3.4.2	IM CN subsystem side session establishment	212
9.2.3.4.3	IM CN subsystem side session establishment completion	214
9.2.3.4.4	Message sequence chart.....	215
9.2.4	Session release initiated from IM CN subsystem side	218
9.2.4.1	BICC	218
9.2.4.1.1	Session release in the IM CN subsystem side.....	218
9.2.4.1.2	Session release in the CS network side.....	218
9.2.4.1.3	Message sequence chart.....	218
9.2.4.2	ISUP	219
9.2.4.2.1	Session release in the IM CN subsystem side.....	219
9.2.4.2.2	Session release in the CS network side.....	219
9.2.4.2.3	Message sequence chart.....	219
9.2.5	Session release initiated from CS network side	219
9.2.5.1	BICC	219
9.2.5.1.1	Session release in the CS network side.....	219
9.2.5.1.2	Session release in the IM CN subsystem side.....	220
9.2.5.1.3	Message sequence chart.....	220
9.2.5.2	ISUP	220
9.2.5.2.1	Session release in the CS network side.....	220
9.2.5.2.2	Session release in the IM CN subsystem side.....	220
9.2.5.2.3	Message sequence chart.....	221
9.2.6	Session release initiated by MGCF.....	221
9.2.6.1	BICC	221
9.2.6.1.1	Session release in the CS network side.....	221
9.2.6.1.2	Session release in the IM CN subsystem side.....	221
9.2.6.1.3	Message sequence chart.....	221
9.2.6.2	ISUP	222
9.2.6.2.1	Session release in the CS network side.....	222
9.2.6.2.2	Session release in the IM CN subsystem side.....	222
9.2.6.2.3	Message sequence chart.....	222
9.2.7	Session release initiated by IM-MGW.....	223
9.2.7.1	BICC	223
9.2.7.1.1	Session release in the CS network side.....	223
9.2.7.1.2	Session release in the IM CN subsystem side.....	223
9.2.7.1.3	Message sequence chart.....	223
9.2.7.2	ISUP	224
9.2.7.2.1	Session release in the CS network side.....	224
9.2.7.2.2	Session release in the IM CN subsystem side.....	224
9.2.7.2.3	Message sequence chart.....	225
9.2.8	Handling of RTP telephone events	225
9.2.8.1	Sending DTMF digits out-of-band to CS CN (BICC).....	226
9.2.8.2	Sending and receiving DTMF digits inband to/from CS CN (ISUP or BICC)	228
9.2.8.3	Receiving DTMF digits out-of-band from CS CN (BICC).....	229
9.2.9	Session hold initiated from IM CN subsystem	230
9.2.10	Session hold initiated from CS network	232
9.2.11	Explicit Congestion Notification Support.....	234
9.2.11.1	General	234
9.2.11.1a	Incoming Call Interworking from SIP to ISUP/BICC at I-MGCF.....	234
9.2.11.1b	Outgoing Call Interworking from ISUP/BICC to SIP at O-MGCF	235
9.2.11.1c	Detection of ECN failures by IM-MGW.....	235
9.2.11.2	Message sequence chart	235
9.2.12	Interactive Connectivity Establishment Support.....	236
9.2.12.1	General	236
9.2.12.2	ICE lite	236
9.2.12.3	Full ICE.....	237
9.2.12.4	Procedures for Interactive Connectivity Establishment (ICE)	239
9.2.12.4.1	ICE lite	239
9.2.12.4.2	Full ICE	240
9.2.12.4.3	Connectivity check result notification (full ICE)	241
9.2.12.4.4	New peer reflexive candidate notification (full ICE)	241
9.2.13	Codec Parameters Handling.....	242
9.2.13.1	Handling of common codec parameters.....	242

9.2.13.2	Handling of EVS speech codec parameters when interworking with a different codec.....	243
9.2.13.3	Handling of EVS speech codec parameters when the EVS codec is used end-to-end	255
9.2.14	SDP Capability Negotiation (SDPCapNeg).....	265
9.2.15	Rate adaptation for media endpoints.....	265
9.3	Mn Signalling procedures	265
9.3.1	Procedures related to terminations towards the IM CN Subsystem	265
9.3.1.1	Reserve IMS connection point	266
9.3.1.2	Configure IMS resources	269
9.3.1.3	Reserve IMS Connection point and configure remote resources	271
9.3.1.4	Release IMS termination.....	274
9.3.1.5	Detect IMS RTP Tel event.....	274
9.3.1.6	Notify IMS RTP Tel event.....	274
9.3.1.7	Void.....	274
9.3.1.8	Send IMS RTP Tel event	274
9.3.1.9	Stop IMS RTP Tel event.....	274
9.3.1.10	Termination heartbeat indication	275
9.3.1.11	IMS Bearer Released.....	275
9.3.1.12	End IMS RTP Tel event.....	275
9.3.1.13	IMS Send Tone	275
9.3.1.14	IMS Stop Tone	275
9.3.1.15	IMS Tone Completed.....	275
9.3.1.16	ECN Failure Indication	276
9.3.1.17	ICE Connectivity Check Result Notification	276
9.3.1.18	ICE New Peer Reflexive Candidate Notification.....	277
9.3.2	Procedures related to a termination towards an ISUP network.....	277
9.3.2.1	Reserve TDM circuit.....	277
9.3.2.2	Change TDM through-connection	278
9.3.2.3	Activate TDM voice-processing function	278
9.3.2.4	Send TDM tone.....	278
9.3.2.5	Stop TDM tone.....	278
9.3.2.6	Play TDM announcement	278
9.3.2.7	TDM announcement completed.....	278
9.3.2.8	Stop TDM announcement.....	278
9.3.2.9	Continuity check	278
9.3.2.10	Continuity check verify.....	279
9.3.2.11	Continuity check response	279
9.3.2.12	Release TDM termination.....	279
9.3.2.13	Termination Out-of-Service.....	280
9.3.2.14	Termination heartbeat indication	280
9.3.2.15	Bearer Released.....	280
9.3.2.16	TDM tone completed	280
9.3.3	Procedures related to a termination towards a BICC network.....	280
9.3.4	Non-call related procedures	281
9.3.5	Multiple IP Realms	282
9.4	Multimedia Priority Service (MPS) Support.....	283
9.4.1	General.....	283
9.4.2	IM-MGW Resource Congestion in ADD response, request is queued.....	283
9.4.3	IM-MGW Resource Congestion in ADD response, MGCF seizes new IM-MGW	284
9.4.4	IM-MGW Priority Resource Allocation	284
9.4.5	IM-MGW Priority User Data marking.....	285
Annex A (informative):	Void	286
Annex B (normative):	Codec Negotiation between a BICC CS network and the IM CN subsystem.....	287
B.1	Introduction	287
B.2	Control plane interworking	287
B.2.1	Incoming call interworking from SIP to BICC at I-MGCF.....	287
B.2.1.1	Sending of IAM	287
B.2.1.2	Sending of SDP answer	287
B.2.2	Outgoing call interworking from BICC to SIP at O-MGCF	287