

ETSI TS 129 163 V13.13.0 (2019-10)



**Digital cellular telecommunications system (Phase 2+) (GSM);
Universal Mobile Telecommunications System (UMTS);**

LTE;

**Interworking between the IP Multimedia (IM) Core Network (CN)
subsystem and Circuit Switched (CS) networks
(3GPP TS 29.163 version 13.13.0 Release 13)**



ReferenceRTS/TSGC-0329163vdd0

Keywords

GSM,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	17
1 Scope	18
2 References	18
3 Definitions and abbreviations.....	24
3.1 Definitions	24
3.2 Abbreviations	25
4 General	26
4.1 General interworking overview	26
5 Network characteristics	27
5.1 Key characteristics of ISUP/BICC based CS networks	27
5.2 Key characteristics of IM CN subsystem	27
6 Interworking with CS networks	27
6.1 Interworking reference model	27
6.1.1 Interworking reference points and interfaces	28
6.1.2 Interworking functional entities	28
6.1.2.1 Signalling Gateway Function (SGW)	28
6.1.2.2 Media Gateway Control Function (MGCF)	28
6.1.2.3 IP Multimedia - Media Gateway Function (IM-MGW)	28
6.2 Control plane interworking model	29
6.3 User plane interworking model	29
7 Control plane interworking	29
7.1 General	29
7.2 Interworking between CS networks supporting ISUP and the IM CN subsystem	30
7.2.1 Services performed by network entities in the control plane	30
7.2.1.1 Services performed by the SS7 signalling function	30
7.2.1.2 Services of the SGW	30
7.2.1.3 Services of the MGCF	31
7.2.1.4 Services of the SIP signalling function	31
7.2.2 Signalling interactions between network entities in the control plane	31
7.2.2.1 Signalling between the SS7 signalling function and MGCF	31
7.2.2.1.1 Signalling from MGCF to SS7 signalling function	31
7.2.2.1.2 Signalling from SS7 signalling function to MGCF	31
7.2.2.1.3 Services offered by SCTP and M3UA	31
7.2.2.1.3.1 Services offered by SCTP	31
7.2.2.1.3.2 Services offered by M3UA	31
7.2.2.2 Signalling between the MGCF and SIP signalling function	32
7.2.3 SIP-ISUP protocol interworking	32
7.2.3.1 Incoming call interworking from SIP to ISUP at I-MGCF	32
7.2.3.1.1 Sending of IAM	32
7.2.3.1.2 Coding of the IAM	33
7.2.3.1.2.0 General	33
7.2.3.1.2.1 Called party number	33
7.2.3.1.2.2 Nature of connection indicators	34
7.2.3.1.2.3 Forward call indicators	35
7.2.3.1.2.4 Calling party's category	36
7.2.3.1.2.4A Originating Line Information	36
7.2.3.1.2.5 Transmission medium requirement	36
7.2.3.1.2.5a Transmission medium requirement prime and USI prime (optional)	38
7.2.3.1.2.6 Calling party number	40

7.2.3.1.2.7	Generic number.....	44
7.2.3.1.2.8	User service information.....	44
7.2.3.1.2.9	Hop Counter (National option)	44
7.2.3.1.2.10	Progress Indicator	45
7.2.3.1.2.11	Location Number	45
7.2.3.1.2.12	Support of ICS call	47
7.2.3.1.2.13	UID capability indicators (National option)	47
7.2.3.1.2.14	Called IN number and original called IN number (optional)	48
7.2.3.1.2A	Coding of the IAM when Number Portability is supported.....	48
7.2.3.1.2A.1	Coding of the IAM when a Number Portability Routing Number is available.....	48
7.2.3.1.2A.1.1	Separate Directory Number Addressing Method	49
7.2.3.1.2A.1.2	Concatenated Addressing Method.....	50
7.2.3.1.2A.1.3	Separate Network Routing Number Addressing Method.....	50
7.2.3.1.2A.2	Number Portability Forward Information	51
7.2.3.1.2B	Coding of the IAM for Carrier Routeing.....	51
7.2.3.1.2B.1	Coding of the IAM when a Carrier Identification Code (CIC) is present	51
7.2.3.1.2B.2	Void	51
7.2.3.1.3	Sending of COT.....	51
7.2.3.1.3A	Sending of SAM.....	52
7.2.3.1.3A.1	General.....	52
7.2.3.1.3A.2	Additional digits received in in-dialog SIP INFO requests.....	52
7.2.3.1.3A.3	Additional digits received in SIP INVITE requests	52
7.2.3.1.4	Sending of 180 ringing	53
7.2.3.1.4.0	General.....	53
7.2.3.1.4.0a	PSTN XML body.....	54
7.2.3.1.4.0b	Fallback by I-MGCF.....	55
7.2.3.1.4.1	Fallback in a succeeding network: Transmission Medium Used parameter (TMU) received.....	56
7.2.3.1.4A	Sending of 183 Session Progress for early media scenarios.....	56
7.2.3.1.4B	Sending of 181Call is being forwarded	59
7.2.3.1.4C	Sending of 183 Session Progress for overlap signalling using the in-dialog method	60
7.2.3.1.4D	Sending of 183 Session Progress to carry ISUP Cause	60
7.2.3.1.4E	Sending of 183 Session Progress for ICS call	60
7.2.3.1.5	Sending of the 200 OK (INVITE)	61
7.2.3.1.6	Sending of the Release message (REL).....	63
7.2.3.1.7	Coding of the REL.....	63
7.2.3.1.8	Receipt of the Release Message	64
7.2.3.1.9	Receipt of RSC, GRS or CGB (H/W oriented)	67
7.2.3.1.9a	Receipt of REFER.....	68
7.2.3.1.10	Autonomous Release at I-MGCF	68
7.2.3.1.11	Internal through connection of the bearer path.....	69
7.2.3.2	Outgoing Call Interworking from ISUP to SIP at O-MGCF.....	69
7.2.3.2.1	Sending of INVITE	69
7.2.3.2.1.1	General.....	69
7.2.3.2.1.2	Interaction with continuity check.....	69
7.2.3.2.1.3	IAM without calling party number	70
7.2.3.2.1.4	Terminating overlap signalling at MGCF	71
7.2.3.2.1.5	Fallback (optional)	71
7.2.3.2.1a	Sending of INVITE without determining the end of address signalling.....	72
7.2.3.2.1a.1	General.....	72
7.2.3.2.1a.2	Additional digits sent with in-dialog overlap method.....	72
7.2.3.2.1a.3	Additional digits sent using the multiple INVITEs overlap method.....	73
7.2.3.2.2	Coding of the INVITE.....	74
7.2.3.2.2.0	Overview.....	74
7.2.3.2.2.1	Request-URI and To header field	74
7.2.3.2.2.2	SDP Media Description	75
7.2.3.2.2.3	P-Asserted-Identity, From and Privacy header fields	79
7.2.3.2.2.3A	"cpc" URI Parameter in P-Asserted-Identity Header	84
7.2.3.2.2.3B	"oli" URI Parameter in P-Asserted-Identity Header	84
7.2.3.2.2.4	Max Forwards header	85
7.2.3.2.2.5	IMS Communication Service Identifier.....	85
7.2.3.2.2.6	P-Early-Media header field.....	85

7.2.3.2.2.7	PSTN XML elements.....	85
7.2.3.2.2.8	Progress indicator	86
7.2.3.2.2.9	P-Access-Network-Info	87
7.2.3.2.2A	Coding of the INVITE when Number Portability is supported	87
7.2.3.2.2A.1	Request-URI and To header field	87
7.2.3.2.2A.1.1	Separate Directory Number Addressing Method	88
7.2.3.2.2A.1.2	Concatenated Addressing Method.....	88
7.2.3.2.2A.1.3	Separate Network Routing Number Addressing Method	89
7.2.3.2.2B	Coding of the INVITE for Carrier Routeing	89
7.2.3.2.2B.1	Mapping of "cic" in Request-URI.....	89
7.2.3.2.2B.2	Void	89
7.2.3.2.2C	Coding of INVITE with instance-id in form of IMEI URN	89
7.2.3.2.2.10	PSAP Call-back indication	90
7.2.3.2.2.11	History-Info header field (optional)	90
7.2.3.2.3	Receipt of CONTINUITY.....	90
7.2.3.2.4	Sending of ACM and awaiting answer indication	91
7.2.3.2.5	Coding of the ACM	93
7.2.3.2.5.0	General.....	93
7.2.3.2.5.1	Backward call indicators.....	93
7.2.3.2.5.2	Optional Backward call indicators.....	95
7.2.3.2.5.3	Access Transport Parameter, Transmission medium used parameter	95
7.2.3.2.5.4	Progress indicator	96
7.2.3.2.5.5	Cause Value	96
7.2.3.2.6	Sending of the Call Progress message (CPG).....	96
7.2.3.2.6.0	General.....	96
7.2.3.2.6.1	Handling of the progress indicator.....	98
7.2.3.2.7	Coding of the CPG	98
7.2.3.2.7.0	General.....	98
7.2.3.2.7.1	Event information	99
7.2.3.2.7.2	Access Transport Parameter.....	99
7.2.3.2.7.3	Void	99
7.2.3.2.7.4	Handling of Backward Call indicators.....	99
7.2.3.2.7.5	Optional Backward call indicators.....	99
7.2.3.2.7.6	Cause Value	99
7.2.3.2.7a	Receipt of 200 OK(INVITE).....	100
7.2.3.2.7b	Internal through connection of the bearer path.....	100
7.2.3.2.8	Sending of the Answer Message (ANM).....	100
7.2.3.2.9	Coding of the ANM.....	100
7.2.3.2.9.1	Backwards Call Indicators	100
7.2.3.2.9.2	Access Transport Parameter.....	100
7.2.3.2.9.3	Transmission Medium Used parameter (TMU).....	101
7.2.3.2.10	Sending of the Connect message (CON)	102
7.2.3.2.11	Coding of the CON.....	102
7.2.3.2.11.0	General.....	102
7.2.3.2.11.1	Backward call indicators.....	102
7.2.3.2.11.2	Access Transport Parameter.....	102
7.2.3.2.11.3	Transmission medium used parameter.....	102
7.2.3.2.11A	Receipt of a reINVITE request.....	102
7.2.3.2.12	Receipt of Status Codes 4xx, 5xx or 6xx.....	102
7.2.3.2.12.1	Special handling of 404 Not Found and 484 Address Incomplete responses after sending of INVITE without determining the end of address signalling.....	104
7.2.3.2.13	Receipt of a BYE.....	105
7.2.3.2.14	Receipt of the Release Message	105
7.2.3.2.15	Receipt of RSC, GRS or CGB (H/W oriented)	105
7.2.3.2.16	Autonomous Release at O-MGCF	105
7.2.3.2.17	Special handling of 580 precondition failure received in response to either an INVITE or UPDATE	106
7.2.3.2.17.1	580 Precondition failure response to an INVITE.....	106
7.2.3.2.17.2	580 Precondition failure response to an UPDATE within an early dialog.....	106
7.2.3.2.18	Sending of CANCEL.....	106
7.2.3.2.19	Receipt of SIP redirect (3xx) response	107
7.2.3.2.20	Sending of INFO for overlap signalling using the in-dialog method	107

7.2.3.2.20.1	General.....	107
7.2.3.2.20.2	Encoding of the INFO.....	107
7.2.3.3	Timers	108
7.3	Interworking between CS networks supporting BICC and the IM CN subsystem.....	108
7.3.1	Services performed by network entities in the control plane	109
7.3.2	Signalling interactions between network entities in the control plane	109
7.3.2.1	Signalling between the SS7 signalling function and MGCF	109
7.3.2.1.1	Signalling from MGCF to SS7 signalling function	109
7.3.2.1.2	Signalling from SS7 signalling function to MGCF	109
7.3.2.1.3	Services offered by STC, SCTP and M3UA	110
7.3.2.1.3.1	Services offer by SCTP.....	110
7.3.2.1.3.2	Services offered by M3UA	110
7.3.2.1.3.3	Services offered by STC	110
7.3.2.2	Signalling between the MGCF and SIP signalling function.....	110
7.3.3	SIP-BICC protocol interworking	110
7.3.3.1	Incoming call interworking from SIP to BICC at I-MGCF.....	110
7.3.3.1.1	Sending of IAM.....	110
7.3.3.1.2	Coding of IAM	110
7.3.3.1.2.1	Called party number.....	110
7.3.3.1.2.2	Nature of connection indicators	110
7.3.3.1.2.3	Forward call indicators	111
7.3.3.1.2.4	Calling party's category	111
7.3.3.1.2.4A	Originating Line Information.....	111
7.3.3.1.2.5	Transmission medium requirement.....	111
7.3.3.1.2.6	Calling party number	111
7.3.3.1.2.7	Generic number.....	111
7.3.3.1.2.8	User service information.....	111
7.3.3.1.2.9	Hop counter (National option)	111
7.3.3.1.2.10	Location Number	111
7.3.3.1.2.11	Support of ICS call	111
7.3.3.1.2.12	UID capability indicators (National option)	111
7.3.3.1.2A	Coding of the IAM when Number Portability is supported.....	111
7.3.3.1.2B	Coding of the IAM for Carrier Routing.....	111
7.3.3.1.2.13	Called IN number and original called IN number (optional)	111
7.3.3.1.3	Sending of COT.....	112
7.3.3.1.3A	Sending of SAM.....	112
7.3.3.1.4	Sending of 180 Ringing.....	112
7.3.3.1.4A	Sending of 183 Session Progress for early media scenarios.....	112
7.3.3.1.4B	Sending of 181 Call is being forwarded	112
7.3.3.1.4C	Sending of 183 Session Progress for overlap signalling using the in-dialog method	112
7.3.3.1.4D	Sending of 183 Session Progress to carry ISUP Cause	112
7.3.3.1.4E	Sending of 183 Session Progress for ICS call	112
7.3.3.1.5	Sending of the 200 OK (INVITE)	113
7.3.3.1.6	Sending of the Release message (REL).....	113
7.3.3.1.7	Coding of the REL.....	113
7.3.3.1.8	Receipt of the Release Message	113
7.3.3.1.9	Receipt of RSC, GRS or CGB (H/W oriented)	113
7.3.3.1.9a	Receipt of REFER	113
7.3.3.1.9b	Autonomous Release at I-MGCF	113
7.3.3.1.10	Internal through connection of the bearer path.....	113
7.3.3.1.11	Out of Band DTMF	113
7.3.3.2	Outgoing Call Interworking from BICC to SIP at O-MGCF	113
7.3.3.2.1	Sending of INVITE	113
7.3.3.2.1a	Sending of INVITE without determining the end of address signalling.....	114
7.3.3.2.2	Coding of the INVITE.....	114
7.3.3.2.2.1	Request-URI and To header field	114
7.3.3.2.2.2	SDP Media Description	114
7.3.3.2.2.3	P-Asserted-Identity and privacy header fields	114
7.3.3.2.2.3A	"cpc" URI Parameter in P-Asserted-Identity Header	114
7.3.3.2.2.3B	"oli" URI Parameter in P-Asserted-Identity Header	114
7.3.3.2.2.4	Max Forwards header	114
7.3.3.2.2.5	IMS Communication Service Identifier	115

7.3.3.2.2.6	P-Access-Network-Info	115
7.3.3.2.2A	Coding of the INVITE when number portability is supported	115
7.3.3.2.2B	Coding of the INVITE for Carrier Routeing	115
7.3.3.2.2C	Coding of INVITE with instance-id in form of IMEI URN	115
7.3.3.2.2.7	PSAP Call-back indication	115
7.3.3.2.2.8	History-Info header field (optional)	115
7.3.3.2.3	Sending of UPDATE	115
7.3.3.2.4	Sending of ACM and Awaiting Answer indication	116
7.3.3.2.5	Coding of the ACM	116
7.3.3.2.5.1	Backward call indicators	116
7.3.3.2.6	Sending of the Call Progress message (CPG)	116
7.3.3.2.7	Coding of the CPG	116
7.3.3.2.7.1	Event information	116
7.3.3.2.7.2	Optional Backward call indicators	116
7.3.3.2.7a	Receipt of 200 OK (INVITE)	116
7.3.3.2.7b	Internal through connection of the bearer path	116
7.3.3.2.8	Sending of the Answer Message (ANM)	116
7.3.3.2.9	Coding of the ANM	116
7.3.3.2.10	Sending of the Connect message (CON)	116
7.3.3.2.11	Coding of the CON	116
7.3.3.2.11.1	Void	117
7.3.3.2.11A	Receipt of re-INVITE requests	117
7.3.3.2.12	Receipt of Status Codes 4xx, 5xx or 6xx	117
7.3.3.2.13	Receipt of a BYE	117
7.3.3.2.14	Receipt of the Release Message	117
7.3.3.2.15	Receipt of RSC, GRS or CGB (H/W oriented)	117
7.3.3.2.16	Out of Band DTMF	117
7.3.3.2.17	Sending of CANCEL	117
7.3.3.2.18	Autonomous Release at O-MGCF	117
7.3.3.2.19	Special handling of 580 precondition failure received in response to either an INVITE or UPDATE	117
7.3.3.2.20	Receipt of SIP redirect (3xx) response	117
7.3.3.2.21	Sending of INFO for overlap signalling using the in-dialog method	117
7.3.3.3	Timers	118
7.4	Supplementary Services	118
7.4.1	Calling line identification presentation/restriction (CLIP/CLIR)	118
7.4.2	Connected line presentation and restriction (COLP/COLR)	118
7.4.2.0	General	118
7.4.2.1	Incoming Call Interworking from SIP to BICC/ISUP at the I-MGCF	118
7.4.2.1.1	INVITE to IAM interworking (SIP to ISUP/BICC calls)	118
7.4.2.1.2	ANM/CON to 200 OK (INVITE)	118
7.4.2.2	Outgoing Call Interworking from BICC/ISUP to SIP at O-MGCF	119
7.4.2.2.1	IAM to INVITE interworking (ISUP to SIP calls)	119
7.4.2.2.2	1XX to ANM or CON interworking	120
7.4.2.2.3	200 OK (INVITE) to ANM/CON interworking	120
7.4.3	Direct Dialling In (DDI)	121
7.4.4	Malicious call identification	121
7.4.5	Subaddressing (SUB)	121
7.4.5.1	General	121
7.4.5.2	Interworking at I-MGCF	122
7.4.5.3	Interworking at O-MGCF	123
7.4.6	Call Forwarding Busy (CFB)/ Call Forwarding No Reply (CFNR) / Call Forwarding Unconditional (CFU) / Call Deflection (CD)	124
7.4.6.1	General	124
7.4.6.2	Interworking at the O-MGCF	124
7.4.6.2.1	General	124
7.4.6.2.2	Interworking SIP to ISUP	124
7.4.6.2.3	Interworking ISUP to SIP	128
7.4.6.3	Interworking at the I-MGCF	131
7.4.6.3.1	General	131
7.4.6.3.2	Interworking from SIP to ISUP	132
7.4.6.3.3	Interworking from ISUP to SIP	134

7.4.7	Void	138
7.4.8	Explicit Call Transfer (ECT)	138
7.4.9	Call Waiting	138
7.4.10	Call Hold	138
7.4.10.1	Session hold initiated from the IM CN subsystem side	138
7.4.10.2	Session hold initiated from the CS network side	139
7.4.11	Call Completion on busy subscriber	142
7.4.12	Completion of Calls on No Reply (CCNR)	142
7.4.13	Terminal Portability (TP)	142
7.4.14	Conference calling (CONF) / Three-Party Service (3PTY)	142
7.4.15	Void	143
7.4.16	Closed User Group (CUG)	143
7.4.17	Multi-Level Precedence and Pre-emption (MLPP)	143
7.4.18	Global Virtual Network Service (GVNS)	143
7.4.19	International telecommunication charge card (ITCC)	143
7.4.20	Reverse charging (REV)	143
7.4.21	User-to-User Signalling (UUS)	143
7.4.21.0	General	143
7.4.21.1	User-to-User Signalling (UUS) service 1 (implicit)	143
7.4.21.1.0	General	143
7.4.21.1.1	Void	144
7.4.21.1.2	User-to-user information Interworking from SIP to ISUP	144
7.4.21.1.3	User-to-user information Interworking from ISUP to SIP	144
7.4.21.2	User-to-User Signalling (UUS) service 1 (explicit)	144
7.4.21.3	User-to-User Signalling (UUS) service 2 (explicit)	144
7.4.21.4	User-to-User Signalling (UUS) service 3 (explicit)	144
7.4.22	Multiple Subscriber Number (MSN)	145
7.4.23	Anonymous Call rejection	145
7.4.23.0	General	145
7.4.23.1	ISUP-SIP protocol interworking at the I-MGCF	145
7.4.23.2	SIP-ISUP protocol interworking at the O-MGCF	145
7.4.24	Customized Alerting Tones (CAT) in the 3GPP CS domain	145
7.5	IMS Supplementary Services	145
7.5.1	Originating Identification Presentation (OIP) and Originating Identification Restriction (OIR)	145
7.5.2	Terminating Identification Presentation (TIP) and Terminating Identification Restriction (TIR)	145
7.5.2.1	General	145
7.5.2.2	Interworking at the O-MGCF	145
7.5.2.3	Interworking at the I-MGCF	147
7.5.2.4	Timer	148
7.5.3	void	148
7.5.4	Communication Diversion (CDIV)	148
7.5.4.1	General	148
7.5.4.2	Interworking at the O-MGCF	149
7.5.4.2.1	General	149
7.5.4.2.2	Call Diversion within the ISUP Network appeared	154
7.5.4.3	Interworking at the I-MGCF	157
7.5.5	Communication Hold (HOLD)	165
7.5.6	Conference call (CONF)	165
7.5.6.1	General	165
7.5.6.2	Subscribing for the conference event package	165
7.5.6.3	Interworking the notification	166
7.5.7	Anonymous Communication Rejection (ACR) and Communication Barring (CB)	166
7.5.8	Message Waiting Indication (MWI)	167
7.5.9	Malicious Communication Identification (MCID)	167
7.5.9.0	General	167
7.5.9.1	Interworking at the O-MGCF	167
7.5.9.1.0	General	167
7.5.9.1.1	Interworking of the MCID XML Request schema with the ISUP MCID request indicators	167
7.5.9.1.2	Interworking of the ISUP MCID response indicators with the MCID XML Response schema	168
7.5.9.1.3	Interworking of the ISUP Calling Party Number in an Identification Response with the OrigPartyIdentity within the MCID XML Response schema	168

7.5.9.1.4	Interworking of the ISUP Generic Number in an Identification Response with the GenericNumber within the MCID XML Response schema	168
7.5.9.2	Interworking at the I-MGCF	168
7.5.9.2.1	General	168
7.5.9.2.2	Interworking of identification Request	168
7.5.9.2.3	Interworking of identification Response	169
7.5.10	Closed User Group (CUG)	169
7.5.10.0	General	169
7.5.10.1	Interworking at the I-MGCF	169
7.5.10.2	Interworking at the O-MGCF	170
7.5.11	CCBS/CCNR	171
7.5.11.0	General	171
7.5.11.1	Interworking at the I-MGCF	171
7.5.11.2	Interworking at the O-MGCF	173
7.5.12	Communication Waiting (CW)	175
7.5.12.0	General	175
7.5.12.1	Interworking at the I-MGCF	175
7.5.12.2	Interworking at the O-MGCF	175
7.5.13	Customized Alerting Tones (CAT)	175
7.5.13.1	General	175
7.5.13.2	Early session model	175
7.5.13.2.1	Interworking at the O-MGCF	175
7.5.13.2.2	MGCF - IM-MGW Interaction for CAT service	176
7.5.13.2.2.1	General	176
7.5.13.2.2.2	IM CN subsystem side Early Session establishment	176
7.5.13.2.2.3	IM CN subsystem side normal Session establishment	176
7.5.13.2.2.4	Called party alerting	177
7.5.13.2.2.5	Message sequence chart	177
7.5.13.3	Forking model	180
7.5.13.4	Gateway model	180
8	User plane interworking	180
8.1	Interworking between IM CN subsystem and bearer independent CS network	180
8.1.1	Transcoder-less Mb to Nb Interworking	181
8.1.1.1	Initialisation	181
8.1.1.2	Time alignment	181
8.1.1.3	Rate control	182
8.1.1.3.1	General	182
8.1.1.3.2	Rate control for AMR and AMR-WB codecs	182
8.1.1.3.3	Rate and Mode control for the EVS codec	182
8.1.1.3.4	Interworking of rate control between compatible AMR-WB and EVS codec configurations	183
8.1.1.3.5	Interworking between rate control and RTCP-APP-CMR messages for MTSI	184
8.1.1.4	Frame quality indication	184
8.1.1.5	Framing	184
8.1.1.6	Transcoding	185
8.1.1.7	Discontinuous transmission	185
8.1.1.8	Timing and sequence information	185
8.2	Interworking between IM CN subsystem and TDM-based CS network	185
8.3	Transcoding requirements	186
8.4	Diffserv code point requirements	186
8.5	DTMF handling	186
9	MGCF - IM-MGW Interaction	186
9.1	Overview	186
9.2	Mn signalling interactions	187
9.2.1	Network model	187
9.2.2	Basic IM CN subsystem originated session	187
9.2.2.1	BICC forward bearer establishment	187
9.2.2.1.1	IM-MGW selection	187
9.2.2.1.2	CS network side bearer establishment	187
9.2.2.1.3	IM CN subsystem side termination reservation	187
9.2.2.1.4	IM CN subsystem side session establishment	188

9.2.2.1.5	Through-connection	188
9.2.2.1.6	Codec handling.....	189
9.2.2.1.7	Failure handling in MGCF	189
9.2.2.1.8	Message sequence chart.....	189
9.2.2.2	BICC backward bearer establishment	190
9.2.2.2.1	IM-MGW selection	190
9.2.2.2.2	IM CN subsystem side termination reservation.....	191
9.2.2.2.3	IM CN subsystem side session establishment	191
9.2.2.2.4	CS network side bearer establishment.....	191
9.2.2.2.5	Through-connection	192
9.2.2.2.6	Codec handling.....	192
9.2.2.2.7	Failure handling in MGCF	192
9.2.2.2.8	Message sequence chart.....	192
9.2.2.3	ISUP	193
9.2.2.3.1	IM-MGW selection	193
9.2.2.3.2	IM CN subsystem side termination reservation.....	193
9.2.2.3.3	IM CN subsystem side session establishment	194
9.2.2.3.4	CS network side circuit reservation.....	194
9.2.2.3.5	Through-connection	194
9.2.2.3.6	Continuity check.....	195
9.2.2.3.7	Codec handling.....	195
9.2.2.3.8	Voice processing function	195
9.2.2.3.9	Failure handling in MGCF	195
9.2.2.3.10	Message sequence chart.....	195
9.2.3	Basic CS network originated session	197
9.2.3.1	BICC forward bearer establishment.....	197
9.2.3.1.1	IM-MGW selection	197
9.2.3.1.2	IM CN subsystem side termination reservation.....	197
9.2.3.1.3	IM CN subsystem side session establishment	197
9.2.3.1.4	CS network side bearer establishment.....	197
9.2.3.1.5	Called party alerting	198
9.2.3.1.6	Called party answer	198
9.2.3.1.7	Through-Connection.....	198
9.2.3.1.8	Codec handling.....	198
9.2.3.1.9	Failure handling in MGCF	198
9.2.3.1.10	Message sequence chart.....	198
9.2.3.2	BICC Backward bearer establishment	200
9.2.3.2.1	IM-MGW selection	200
9.2.3.2.2	CS network side bearer establishment.....	200
9.2.3.2.3	IM CN subsystem side termination reservation.....	200
9.2.3.2.4	IM CN subsystem side session establishment	201
9.2.3.2.5	Called party alerting	201
9.2.3.2.6	Called party answer	201
9.2.3.2.7	Through-Connection.....	201
9.2.3.2.8	Codec handling.....	201
9.2.3.2.9	Failure handling in MGCF	202
9.2.3.2.10	Message sequence chart.....	202
9.2.3.3	ISUP	204
9.2.3.3.1	IM-MGW selection	204
9.2.3.3.2	CS network side circuit reservation.....	204
9.2.3.3.3	IM CN subsystem side termination reservation.....	204
9.2.3.3.4	IM CN subsystem side session establishment	204
9.2.3.3.5	Called party alerting	205
9.2.3.3.6	Called party answer	205
9.2.3.3.7	Through-Connection.....	205
9.2.3.3.8	Continuity Check.....	205
9.2.3.3.9	Codec handling.....	205
9.2.3.3.10	Voice Processing function.....	206
9.2.3.3.11	Failure handling in MGCF	206
9.2.3.3.12	Message sequence chart.....	206
9.2.3.4	Handling of Forking	208
9.2.3.4.1	Detection of Forking.....	208

9.2.3.4.2	IM CN subsystem side session establishment	208
9.2.3.4.3	IM CN subsystem side session establishment completion	209
9.2.3.4.4	Message sequence chart.....	209
9.2.4	Session release initiated from IM CN subsystem side	212
9.2.4.1	BICC	212
9.2.4.1.1	Session release in the IM CN subsystem side.....	212
9.2.4.1.2	Session release in the CS network side.....	212
9.2.4.1.3	Message sequence chart.....	212
9.2.4.2	ISUP	213
9.2.4.2.1	Session release in the IM CN subsystem side.....	213
9.2.4.2.2	Session release in the CS network side.....	213
9.2.4.2.3	Message sequence chart.....	213
9.2.5	Session release initiated from CS network side	213
9.2.5.1	BICC	213
9.2.5.1.1	Session release in the CS network side.....	213
9.2.5.1.2	Session release in the IM CN subsystem side.....	214
9.2.5.1.3	Message sequence chart.....	214
9.2.5.2	ISUP	214
9.2.5.2.1	Session release in the CS network side.....	214
9.2.5.2.2	Session release in the IM CN subsystem side.....	214
9.2.5.2.3	Message sequence chart.....	215
9.2.6	Session release initiated by MGCF.....	215
9.2.6.1	BICC	215
9.2.6.1.1	Session release in the CS network side.....	215
9.2.6.1.2	Session release in the IM CN subsystem side.....	215
9.2.6.1.3	Message sequence chart.....	215
9.2.6.2	ISUP	216
9.2.6.2.1	Session release in the CS network side.....	216
9.2.6.2.2	Session release in the IM CN subsystem side.....	216
9.2.6.2.3	Message sequence chart.....	216
9.2.7	Session release initiated by IM-MGW.....	217
9.2.7.1	BICC	217
9.2.7.1.1	Session release in the CS network side.....	217
9.2.7.1.2	Session release in the IM CN subsystem side.....	217
9.2.7.1.3	Message sequence chart.....	217
9.2.7.2	ISUP	218
9.2.7.2.1	Session release in the CS network side.....	218
9.2.7.2.2	Session release in the IM CN subsystem side.....	218
9.2.7.2.3	Message sequence chart.....	219
9.2.8	Handling of RTP telephone events	219
9.2.8.1	Sending DTMF digits out-of-band to CS CN (BICC).....	220
9.2.8.2	Sending and receiving DTMF digits inband to/from CS CN (ISUP or BICC)	222
9.2.8.3	Receiving DTMF digits out-of-band from CS CN (BICC).....	223
9.2.9	Session hold initiated from IM CN subsystem	224
9.2.10	Session hold initiated from CS network	226
9.2.11	Explicit Congestion Notification Support.....	228
9.2.11.1	General	228
9.2.11.1a	Incoming Call Interworking from SIP to ISUP/BICC at I-MGCF	228
9.2.11.1b	Outgoing Call Interworking from ISUP/BICC to SIP at O-MGCF	229
9.2.11.1c	Detection of ECN failures by IM-MGW.....	229
9.2.11.2	Message sequence chart	229
9.2.12	Interactive Connectivity Establishment Support.....	230
9.2.12.1	General	230
9.2.12.2	ICE lite	230
9.2.12.3	Full ICE.....	231
9.2.12.4	Procedures for Interactive Connectivity Establishment (ICE)	233
9.2.12.4.1	ICE lite	233
9.2.12.4.2	Full ICE	234
9.2.12.4.3	Connectivity check result notification (full ICE)	235
9.2.12.4.4	New peer reflexive candidate notification (full ICE)	235
9.2.13	Codec Parameters Handling.....	236
9.2.13.1	Handling of common codec parameters.....	236

9.2.13.2	Handling of EVS speech codec parameters when interworking with a different codec.....	237
9.2.13.3	Handling of EVS speech codec parameters when the EVS codec is used end-to-end	249
9.2.14	SDP Capability Negotiation (SDPCapNeg).....	259
9.2.15	Rate adaptation for media endpoints.....	259
9.3	Mn Signalling procedures	259
9.3.1	Procedures related to terminations towards the IM CN Subsystem	259
9.3.1.1	Reserve IMS connection point	260
9.3.1.2	Configure IMS resources	263
9.3.1.3	Reserve IMS Connection point and configure remote resources	265
9.3.1.4	Release IMS termination.....	268
9.3.1.5	Detect IMS RTP Tel event.....	268
9.3.1.6	Notify IMS RTP Tel event.....	268
9.3.1.7	Void.....	268
9.3.1.8	Send IMS RTP Tel event	268
9.3.1.9	Stop IMS RTP Tel event	268
9.3.1.10	Termination heartbeat indication	269
9.3.1.11	IMS Bearer Released.....	269
9.3.1.12	End IMS RTP Tel event.....	269
9.3.1.13	IMS Send Tone	269
9.3.1.14	IMS Stop Tone	269
9.3.1.15	IMS Tone Completed.....	269
9.3.1.16	ECN Failure Indication	270
9.3.1.17	ICE Connectivity Check Result Notification	270
9.3.1.18	ICE New Peer Reflexive Candidate Notification.....	271
9.3.2	Procedures related to a termination towards an ISUP network.....	271
9.3.2.1	Reserve TDM circuit.....	271
9.3.2.2	Change TDM through-connection	272
9.3.2.3	Activate TDM voice-processing function	272
9.3.2.4	Send TDM tone.....	272
9.3.2.5	Stop TDM tone.....	272
9.3.2.6	Play TDM announcement	272
9.3.2.7	TDM announcement completed	272
9.3.2.8	Stop TDM announcement	272
9.3.2.9	Continuity check	272
9.3.2.10	Continuity check verify.....	273
9.3.2.11	Continuity check response	273
9.3.2.12	Release TDM termination.....	273
9.3.2.13	Termination Out-of-Service	274
9.3.2.14	Termination heartbeat indication	274
9.3.2.15	Bearer Released.....	274
9.3.2.16	TDM tone completed	274
9.3.3	Procedures related to a termination towards a BICC network	274
9.3.4	Non-call related procedures	275
9.3.5	Multiple IP Realms	276
9.4	Multimedia Priority Service (MPS) Support.....	277
9.4.1	General.....	277
9.4.2	IM-MGW Resource Congestion in ADD response, request is queued.....	277
9.4.3	IM-MGW Resource Congestion in ADD response, MGCF seizes new IM-MGW	278
9.4.4	IM-MGW Priority Resource Allocation	278
9.4.5	IM-MGW Priority User Data marking.....	279

Annex A (informative):	Void	280
-------------------------------	-------------------	------------

Annex B (normative):	Codec Negotiation between a BICC CS network and the IM CN subsystem.....	281
-----------------------------	---	------------

B.1	Introduction	281
B.2	Control plane interworking	281
B.2.1	Incoming call interworking from SIP to BICC at I-MGCF.....	281
B.2.1.1	Sending of IAM	281
B.2.1.2	Sending of SDP answer	281
B.2.2	Outgoing call interworking from BICC to SIP at O-MGCF	281