

# ETSI TS 129 154 V15.3.0 (2019-10)



TECHNICAL SPECIFICATION

**Universal Mobile Telecommunications System (UMTS);  
LTE;  
Service capability exposure functionality over Nt reference  
point  
(3GPP TS 29.154 version 15.3.0 Release 15)**



## Reference

---

RTS/TSGC-0329154vf30

## Keywords

---

LTE,UMTS

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

---

The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

---

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

**GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

---

# Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

---

# Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

Intellectual Property Rights .....	2
Legal Notice .....	2
Modal verbs terminology.....	2
Foreword.....	5
1 Scope .....	6
2 References .....	6
3 Definitions and abbreviations.....	7
3.1 Definitions .....	7
3.2 Abbreviations .....	7
4 Nt application .....	7
4.1 Overview .....	7
4.2 Nt Reference Model .....	8
4.3 Functional elements.....	8
4.3.1 PCRF .....	8
4.3.2 SCEF.....	8
4.4 Procedures over the Nt reference point .....	8
4.4.1 Negotiation for future background data transfer.....	8
4.5 PCRF selection.....	9
5 Nt protocol.....	9
5.1 Protocol support .....	9
5.2 Initialization, maintenance and termination of connection and session.....	9
5.3 Nt specific AVPs.....	10
5.3.1 General.....	10
5.3.2 Network-Area-Info-List AVP.....	10
5.3.3 Reference-Id AVP.....	10
5.3.4 Transfer-Request-Type AVP.....	10
5.3.5 Time-Window AVP.....	11
5.3.6 Transfer-End-Time AVP.....	11
5.3.7 Transfer-Start-Time AVP.....	11
5.3.8 Transfer-Policy AVP.....	11
5.3.9 Transfer-Policy-Id AVP.....	11
5.3.10 Number-Of-UEs AVP.....	11
5.4 Nt re-used AVPs.....	11
5.4.1 General.....	11
5.4.2 Use of the Supported-Features AVP for the Nt application.....	12
5.5 Nt specific Experimental-Result-Code AVP values.....	13
5.5.1 General.....	13
5.5.2 Success.....	13
5.5.3 Permanent Failures .....	13
5.5.4 Transient Failures .....	13
5.6 Nt messages.....	13
5.6.1 Command-Code Values.....	13
5.6.2 Background-Data-Transfer-Request (BTR) command .....	14
5.6.3 Background-Data-Transfer-Answer (BTA) command .....	14
<b>Annex A (normative): Nta application .....</b>	<b>15</b>
A.1 Overview .....	15
A.2 Reference Model .....	15
A.3 Functional elements.....	15
A.3.1 PCRF .....	15
A.3.2 SCEF .....	16

A.4	Procedures over the Nta application.....	16
A.4.1	Event Monitoring Configuration.....	16
A.4.2	Event Monitoring Reporting.....	16
A.5	PCRF selection.....	17
A.6	Nta protocol.....	17
A.6.1	Protocol support.....	17
A.6.2	Initialization, maintenance and termination of connection and session.....	17
A.6.3	Nta specific AVPs.....	17
A.6.3.1	General.....	17
A.6.3.2	Access-Network-Reports AVP.....	18
A.6.3.3	Event-Configuration.....	18
A.6.3.4	Event-Configuration-State AVP.....	18
A.6.3.5	Event-Configuration-Status AVP.....	18
A.6.3.6	Event-Reporting-Results AVP.....	19
A.6.3.7	Event-Reports AVP.....	19
A.6.3.8	Extended-SCEF-Reference-ID.....	19
A.6.4	Nta re-used AVPs.....	19
A.6.4.1	General.....	19
A.6.4.2	Use of the Supported-Features AVP for the Nt application.....	21
A.6.5	Nta specific Experimental-Result-Code AVP values.....	21
A.6.6	Nta messages.....	21
A.6.6.1	Command-Code Values.....	21
A.6.6.2	Event-Configuration-Request (ECR) command.....	22
A.6.6.3	Event-Configuration-Answer (ECA) command.....	22
A.6.6.4	Event-Reporting-Request (ERR) command.....	22
A.6.6.5	Event-Reporting-Answer (ERA) command.....	23
<b>Annex B (informative):</b>	<b>Change history.....</b>	<b>24</b>
History.....		25

iTech STANDARD PREVIEW  
 (standards.iteh.ai)  
 Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/0ca2388c-80e3-4aeb-8145-3ed65e0c095a/etsi-ts-129-154-v15.3.0-2019-10>

---

# Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- Y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

**PREVIEW**  
**STANDARD**  
**ETSI**  
**(standards.iteh.ai)**  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/0c9a388c-80e3-4aeb-8145-3ed65e0c095a/etsi-ts-129-154-v15.3.0-2019-10>

---

# 1 Scope

This document defines the protocol for Nt reference point. The Nt reference point includes Nt application and Nta application.

The functional requirements and the stage 2 specifications of the Nt application are contained in 3GPP TS 23.203 [2]. The Nt application of Nt reference point lies between Service Capability Exposure Function (SCEF) and Policy and Charging Rules Function (PCRF), it supports the negotiation of background data transfer policy and is documented in the main body of this document.

The functional requirements and the stage 2 specifications of the Nta application are contained in subclause 5.6.4.1a of 3GPP TS 23.682 [x5]. The Nta application of Nt reference point lies between SCEF and PCRF, it supports the event monitoring configuration for a group of UEs and the corresponding event reporting. The Nta application is documented in Annex A.

NOTE: Nta is a stage 3 name of Diameter Application due to extensibility rule mentioned in IETF RFC 6733 [15].

---

# 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 23.203: "Policy and charging control architecture".
- [3] IETF RFC 3588: "Diameter Base Protocol".
- [4] IETF RFC 4006: "Diameter Credit Control Application".
- [5] 3GPP TS 29.214: "Policy and Charging Control over Rx reference point".
- [6] 3GPP TS 29.274: "3GPP Evolved Packet System. Evolved GPRS Tunnelling Protocol for EPS (GTPv2)".
- [7] IETF RFC 5719: "Updated IANA Considerations for Diameter Command Code Allocations".
- [8] IETF RFC 2234: "Augmented BNF for syntax specifications".
- [9] 3GPP TS 29.213: "Policy and charging control signalling flows and Quality of Service (QoS) parameter mapping".
- [10] IETF RFC 7683: "Diameter Overload Indication Conveyance".
- [11] 3GPP TS 29.229: "Cx and Dx interfaces based on Diameter protocol; Protocol details".
- [12] IETF RFC 7944: "Diameter Routing Message Priority".
- [13] 3GPP TS 29.215: "Policy and Charging Control (PCC) over S9 reference point; Stage 3".
- [14] IETF RFC 8583: "Diameter Load Information Conveyance".
- [15] IETF RFC 6733: "Diameter Base Protocol".

- [16] 3GPP TS 29.329: "Sh Interface based on the Diameter protocol".
- [17] 3GPP TS 29.336: "Home Subscriber Server (HSS) diameter interfaces for interworking with packet data networks and applications".
- [18] 3GPP TS 29.061: "Interworking between the Public Land Mobile Network (PLMN) supporting packet based services and Packet Data Networks (PDN)".
- [19] 3GPP TS 29.212: "Policy and Charging Control (PCC); Reference points".
- [20] 3GPP TS 23.682: "Architecture enhancements to facilitate communications with packet data networks and applications".

---

## 3 Definitions and abbreviations

### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

### 3.2 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

ASP	Application Service Provider
BBERF	Bearer Binding and Event Reporting Function
BTA	Background Data Transfer Answer
BTR	Background Data Transfer Request
ECA	Event Configuration Answer
ECR	Event Configuration Request
ERA	Event Reporting Answer
ERR	Event Reporting Request
DRA	Diameter Routing Agent
DRMP	Diameter Routing Message Priority
PCEF	Policy and Charging Enforcement Function
PCRF	Policy and Charging Rules Function
SCEF	Service Capability Exposure Function
SPR	Subscription Profile Repository

---

## 4 Nt application

### 4.1 Overview

The Nt application of Nt reference point is located between the PCRF and the SCEF. It is used for reporting the transfer policies from the PCRF to the SCEF.

The stage 2 requirements for Nt application are defined in TS 23.203 [2].

Refer to Annex G of 3GPP TS 29.213 [9] for Diameter overload control procedures for the Nt application.


Refer to Annex J of 3GPP TS 29.213 [9] for Diameter message priority mechanism procedures for the Nt application.

Refer to Annex K of 3GPP TS 29.213 [9] for Diameter load control procedures for the Nt application.



## 4.2 Nt Reference Model

The Nt application of Nt reference point resides between the SCEF and PCRF. The relationship between the two functional entities is depicted in figure 4.2-1. The overall PCC architecture is depicted in subclause 3a of 3GPP TS 29.213 [9].



**Figure 4.2-1: Reference model for Nt application of Nt interface**

NOTE: For roaming case, the SCEF is always in the H-PLMN and always contact the H-PCRF.

## 4.3 Functional elements

### 4.3.1 PCRF

The PCRF is a functional element that encompasses policy control decision and flow based charging control functionalities.

The PCRF uses the information received from SCEF and other available information to determine one or more transfer policies for background data to the application service provider. The PCRF provides the selected transfer policies with a reference ID to the SPR for storage.

### 4.3.2 SCEF

The SCEF is a functional element which provides a means to securely expose the services and capabilities provided by 3GPP network interfaces.

The SCEF is triggered by an SCS/AS which requests for the negotiation with the PCRF for providing necessary policy to transfer background data.

## 4.4 Procedures over the Nt reference point

### 4.4.1 Negotiation for future background data transfer

Based on the SCS/AS request, the SCEF shall send the Background-Data-Transfer-Request (BTR) command to the PCRF including the Transfer-Request-Type AVP with the value TRANSFER\_POLICY\_REQUEST(0), it shall also include the ASP identifier within the Application-Service-Provider-Identity AVP, volume of data per UE within the CC-Output-Octets AVP for downlink volume and/or the CC-Input-Octets AVP for uplink volume, or the CC-Total-Octets AVP for total volume regardless direction, expected number of UEs within the Number-Of-UEs AVP and desired time window within the Time-Window AVP.

The Time-Window AVP shall include desired start time within the Transfer-Start-Time AVP and desired end time within the Transfer-End-Time AVP.

The SCEF may also provide network area information within Network-Area-Info-List AVP.

Once the PCRF receives the BTR command, the PCRF shall retrieve all existing transfer policies stored for any ASP from the SPR.

When all existing transfer policies are retrieved, the PCRF shall determine one or more transfer policies based on the information received from the SCEF and other available information (e.g. network policy, congestion level (if available), load status estimation for the required time window and network area, existing transfer policies) and respond with a Background-Data-Transfer-Answer (BTA) command including the possible transfer policies within Transfer-Policy AVP (s) and a reference ID within Reference-Id AVP.

The Transfer-Policy AVP(s) shall include the Transfer-Policy-Id AVP, the Time-Window AVP, the Rating-Group AVP, and may also include an Max-Requested-Bandwidth-DL AVP and/or an Max-Requested-Bandwidth-UL AVP.

If more than one transfer policies are included in the BTA command, the PCRF shall also include the PCRF Id within the PCRF-Address AVP in the BTA command.

NOTE 1: If only one Transfer-Policy AVP is included in the BTA command, the PCRF sends a request to the SPR to store the reference ID together with the transfer policy and corresponding network area information (if available).

If there is more than one Transfer-Policy AVP included in the BTA command, the PCRF waits for the transfer policy selected by the SCS/AS before communicating with the SPR.

If there is more than one transfer policy provided from the PCRF to the SCEF in the BTA command, when the SCEF receives the selected transfer policy from the SCS/AS, the SCEF shall send Background-Data-Transfer-Request (BTR) command to the PCRF including the Transfer-Request-Type AVP set to the value TRANSFER\_POLICY\_NOTIFICATION (1). The SCEF shall also include the reference ID in the Reference-Id AVP, the identity of the selected transfer policy within the Transfer-Policy-Id AVP and the destination PCRF Id within the Destination-Host AVP.

NOTE 2: When receiving the BTA command from the PCRF, if there is only one transfer policy included, the SCEF forwards the transfer policy to SCS/AS.

If there is more than the one transfer policy included, the SCEF forwards these transfer policies to the SCS/AS and waits for the answer including the identity of the transfer policy selected by the SCS/AS.

The PCRF shall acknowledge the BTR command by sending Background-Data-Transfer-Answer (BTA) command.

NOTE 3: The PCRF sends a request to the SPR to store the reference ID together with the transfer policy and corresponding network area information (if available).

## 4.5 PCRF selection

The SCEF or DRA (if deployed) may select a PCRF in the HPLMN based on operator policy (e.g. pre-configured PCRF identities or routing strategy, etc).

---

# 5 Nt protocol

## 5.1 Protocol support

The Diameter Base Protocol as specified in IETF RFC 6733 [15] shall apply except as modified by the defined support of the methods and the defined support of the commands and AVPs, result and error codes as specified in this specification. Unless otherwise specified, the procedures specified in IETF RFC 6733 [15] (including error handling and unrecognised information handling) shall be used unmodified.

The Nt application is defined as vendor specific Diameter application, where the vendor is 3GPP and the Application-ID for the Nt application in the present release is 16777348. The vendor identifier assigned by IANA to 3GPP (<http://www.iana.org/assignments/enterprise-numbers>) is 10415.

With regard to the Diameter protocol defined for the Nt application, the PCRF acts as a Diameter server, in the sense that it is the network element that handles background data transfer request. The SCEF acts as the Diameter client, in the sense that it is the network element requesting background data transfer.

## 5.2 Initialization, maintenance and termination of connection and session

The initialization and maintenance of the connection between each SCEF and PCRF pair is defined by the underlying protocol. Establishment and maintenance of connections between Diameter nodes is described in IETF RFC 6733 [15]. After establishing the transport connection, the SCEF and the PCRF shall advertise the support of the Nt specific Application by including the value of the application identifier in the Auth-Application-Id AVP and the