



**Universal Mobile Telecommunications System (UMTS);
LTE;
Terminal acoustic characteristics for telephony;
Requirements
(3GPP TS 26.131 version 15.2.0 Release 15)**

STANDARD PREVIEW
<https://standards.iteh.ai/catalog/standards/sist/8e5e5f1c-d2e1-46cb-b068-81663d1c1e35/etsi-ts-126-131-v15-2-0-2019-10>



Reference

RTS/TSGS-0426131vf20

Keywords

LTE,UMTS**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	7
Introduction	7
1 Scope	8
2 References	8
3 Definitions, symbols and abbreviations	9
3.1 Definitions	9
3.2 Abbreviations	9
4 Interfaces	10
5 Narrowband telephony transmission performance	11
5.1 Applicability.....	11
5.2 Overall loss/loudness ratings	11
5.2.1 General.....	11
5.2.2 Connections with handset UE.....	11
5.2.2a Connections with handset UE in the presence of background noise.....	11
5.2.3 Connections with desktop and vehicle-mounted hands-free UE.....	11
5.2.4 Connections with hand-held hands-free UE.....	12
5.2.5 Connections with headset UE.....	12
5.2.5a Connections with headset UE in the presence of background noise.....	12
5.3 Idle channel noise (handset and headset UE)	13
5.3.1 Sending	13
5.3.2 Receiving	13
5.4 Sensitivity/frequency characteristics	13
5.4.1 Handset and headset UE sending	13
5.4.2 Handset and headset UE receiving	14
5.4.3 Desktop and vehicle-mounted hands-free UE sending	15
5.4.4 Desktop and vehicle-mounted hands-free UE receiving.....	16
5.4.5 Hand-held hands-free UE sending	17
5.4.6 Hand-held hands-free UE receiving.....	18
5.5 Sidetone characteristics (handset and headset UE)	19
5.5.1 Sidetone loss	19
5.5.2 Sidetone delay.....	19
5.6 Stability loss	20
5.7 Acoustic echo control.....	20
5.7.1 General.....	20
5.7.2 Acoustic echo control in desktop and vehicle-mounted hands-free UE	20
5.7.3 Acoustic echo control in hand-held hands-free UE	21
5.7.4 Acoustic echo control in a handset UE.....	21
5.7.5 Acoustic echo control in a headset UE	21
5.8 Distortion.....	21
5.8.1 Sending distortion	21
5.8.2 Receiving	22
5.9 Void.....	23
5.10 Information on other parameters (not normative)	23
5.11 Sending performance in the presence of ambient noise	23
5.11.1 General.....	23
5.11.2 Connections with handset UE.....	23
5.11.3 Connections with Handheld hands-free UE.....	23
5.12 Delay	24
5.12.0 UE delay definition	24

5.12.1	Handset UE	24
5.12.2	Headset UE	25
5.12.2.1	Wired headset	25
5.12.2.2	Wireless headset	26
5.13	Echo control characteristics	26
5.13.1	Handset	27
5.13.2	Headset	27
5.13.3	Handheld hands-free	27
5.13.4	Desktop and vehicle mounted hands-free	27
5.14	Clock accuracy	27
5.15	Jitter buffer management behaviour	28
6	Wideband telephony transmission performance	28
6.1	Applicability	28
6.2	Overall loss/loudness ratings	28
6.2.1	General	28
6.2.2	Connections with handset UE	28
6.2.2a	Connections with handset UE in the presence of background noise	29
6.2.3	Connections with desktop and vehicle-mounted hands-free UE	29
6.2.4	Connections with hand-held hands-free UE	29
6.2.5	Connections with headset UE	30
6.2.5a	Connections with headset UE in the presence of background noise	30
6.3	Idle channel noise (handset and headset UE)	30
6.3.1	Sending	30
6.3.2	Receiving	30
6.4	Sensitivity/frequency characteristics	31
6.4.1	Handset and headset UE sending	31
6.4.2	Handset and headset UE receiving	31
6.4.3	Desktop and vehicle-mounted hands-free UE sending	32
6.4.4	Desktop and vehicle-mounted hands-free UE receiving	33
6.4.5	Hand-held hands-free UE sending	34
6.4.6	Hand-held hands-free UE receiving	35
6.5	Sidetone characteristics (handset and headset UE)	37
6.5.1	Sidetone loss	37
6.5.2	Sidetone delay	37
6.6	Stability loss	37
6.7	Acoustic echo control	38
6.7.1	General	38
6.7.2	Acoustic echo control in desktop and vehicle-mounted hands-free UE	38
6.7.3	Acoustic echo control in hand-held hands-free UE	38
6.7.4	Acoustic echo control in a handset UE	38
6.7.5	Acoustic echo control in a headset UE	39
6.8	Distortion	39
6.8.1	Sending distortion	39
6.8.2	Receiving	40
6.9	Void	40
6.10	Sending performance in the presence of ambient noise	41
6.10.1	General	41
6.10.2	Connections with handset UE	41
6.10.3	Connections with Handheld hands-free UE	41
6.11	Delay	41
6.11.0	UE delay definition	41
6.11.1	Handset UE	42
6.11.2	Headset UE	43
6.11.2.1	Wired headset	43
6.11.2.2	Wireless headset	44
6.12	Echo control characteristics	44
6.12.1	Handset	45
6.12.2	Headset	45
6.12.3	Handheld hands-free	45
6.12.4	Desktop and vehicle mounted hands-free	45
6.13	Clock accuracy	45

6.14	Jitter buffer management behaviour	46
7	Super-wideband telephony transmission performance	46
7.1	Applicability	46
7.2	Overall loss/loudness ratings	46
7.2.1	General	46
7.2.2	Connections with handset UE	46
7.2.2a	Connections with handset UE in the presence of background noise	47
7.2.3	Connections with desktop and vehicle-mounted hands-free UE	47
7.2.4	Connections with hand-held hands-free UE	47
7.2.5	Connections with headset UE	48
7.2.5a	Connections with headset UE in the presence of background noise	48
7.3	Idle channel noise (handset and headset UE)	48
7.3.1	Sending	48
7.3.2	Receiving	48
7.4	Sensitivity/frequency characteristics	49
7.4.0	General	49
7.4.1	Handset and headset UE sending	49
7.4.2	Handset and headset UE receiving	50
7.4.2.1	Handset UE receiving	50
7.4.2.2	Headset UE receiving	51
7.4.3	Desktop and vehicle-mounted hands-free UE sending	52
7.4.4	Desktop and vehicle-mounted hands-free UE receiving	53
7.4.5	Hand-held hands-free UE sending	54
7.4.6	Hand-held hands-free UE receiving	54
7.5	Sidetone characteristics (handset and headset UE)	55
7.5.1	Sidetone loss	55
7.5.2	Sidetone delay	56
7.6	Stability loss	56
7.7	Acoustic echo control	56
7.7.1	General	56
7.7.2	Acoustic echo control in desktop and vehicle-mounted hands-free UE	56
7.7.3	Acoustic echo control in hand-held hands-free UE	57
7.7.4	Acoustic echo control in a handset UE	57
7.7.5	Acoustic echo control in a headset UE	57
7.8	Distortion	58
7.8.1	Sending distortion	58
7.8.2	Receiving	58
7.9	Void	59
7.10	Sending performance in the presence of ambient noise	59
7.10.1	General	59
7.10.2	Connections with handset UE	59
7.10.3	Connections with Handheld hands-free UE	60
7.11	Delay	60
7.11.0	UE delay definition	60
7.11.1	Handset UE	60
7.11.2	Headset UE	61
7.11.2.1	Wired headset	61
7.11.2.2	Wireless headset	63
7.12	Echo control characteristics	63
7.12.1	Handset	64
7.12.2	Headset	64
7.12.3	Handheld hands-free	64
7.12.4	Desktop and vehicle mounted hands-free	64
7.13	Clock accuracy	64
7.14	Jitter buffer management behaviour	65
8	Fullband telephony transmission performance	65
8.1	Applicability	65
8.2	Overall loss/loudness ratings	65
8.2.1	General	65
8.2.2	Connections with handset UE	65

8.2.2a	Connections with handset UE in the presence of background noise.....	65
8.2.3	Connections with desktop and vehicle-mounted hands-free UE.....	65
8.2.4	Connections with hand-held hands-free UE	66
8.2.5	Connections with headset UE	66
8.2.5a	Connections with headset UE in the presence of background noise.....	66
8.3	Idle channel noise (handset and headset UE)	66
8.3.1	Sending	66
8.3.2	Receiving.....	66
8.4	Sensitivity/frequency characteristics	66
7.4.0	General.....	66
8.4.1	Handset and headset UE sending.....	66
8.4.2	Handset and headset UE receiving	66
8.4.2.1	Handset UE receiving	66
8.4.2.2	Headset UE receiving.....	67
8.4.3	Desktop and vehicle-mounted hands-free UE sending	67
8.4.4	Desktop and vehicle-mounted hands-free UE receiving.....	67
8.4.5	Hand-held hands-free UE sending	67
8.4.6	Hand-held hands-free UE receiving.....	67
8.5	Sidetone characteristics (handset and headset UE)	67
8.5.1	Sidetone loss	67
8.5.2	Sidetone delay.....	67
8.6	Stability loss	67
8.7	Acoustic echo control.....	67
8.7.1	General.....	67
8.7.2	Acoustic echo control in desktop and vehicle-mounted hands-free UE.....	68
8.7.3	Acoustic echo control in hand-held hands-free UE.....	68
8.7.4	Acoustic echo control in a handset UE	68
8.7.5	Acoustic echo control in a headset UE	68
8.8	Distortion.....	68
8.8.1	Sending distortion	68
8.8.2	Receiving.....	68
8.9	Void.....	68
8.10	Sending performance in the presence of ambient noise	68
8.10.1	General.....	68
8.10.2	Connections with handset UE.....	68
8.10.3	Connections with Handheld hands-free UE.....	68
8.11	Delay	69
8.11.0	UE delay definition.....	69
8.11.1	Handset UE.....	69
8.11.2	Headset UE	70
8.11.2.1	Wired headset.....	70
8.11.2.2	Wireless headset.....	71
8.12	Echo control characteristics.....	71
8.12.1	Handset	71
8.12.2	Headset	71
8.12.3	Handheld hands-free	71
8.12.4	Desktop and vehicle mounted hands-free	71
8.13	Clock accuracy	71
8.14	Jitter buffer management behaviour	72
Annex A (informative): Change history		73
History		76

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document specifies minimum performance requirements for the acoustic characteristics of 3G, LTE, and WLAN terminals when used to provide narrowband, wideband, super-wideband or fullband telephony.

The objective for narrowband services is to reach a quality as close as possible to ITU-T standards for PSTN circuits. However, due to technical and economic factors, there cannot be full compliance with the general characteristics of international telephone connections and circuits recommended by the ITU-T.

The performance requirements are specified in the main body of the text; the test methods and considerations are described in TS 26.132.

1 Scope

The present document is applicable to any terminal capable of supporting narrowband, wideband, super-wideband or fullband telephony, either as a stand-alone service or as the telephony component of a multimedia service. The present document specifies minimum performance requirements for the acoustic characteristics of 3G, LTE and WLAN terminals when used to provide narrowband, wideband, super-wideband or fullband telephony.

The set of minimum performance requirements enables a guaranteed level of speech quality while taking possible physical limits of the terminal design into account. Some performance objectives are also defined, if such design limits can be overcome. Care must be taken in applying performance objectives in isolation, not to degrade overall end-user speech quality.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 26.132: "Speech and video telephony terminal acoustic test specification".
- [2] ITU-T Recommendation B.12 (1988): "Use of the decibel and the neper in telecommunications"
- [3] ITU-T Recommendation G.103 (1998): "Hypothetical reference connections".
- [4] ITU-T Recommendation G.111 (1993): "Loudness ratings (LRs) in an international connection".
- [5] ITU-T Recommendation G.121 (1993): "Loudness ratings (LRs) of national systems".
- [6] ITU-T Recommendation G.122 (1993): "Influence of national systems on stability and talker echo in international connections".
- [7] Void
- [8] ITU-T Recommendation P.11 (1993): "Effect of transmission impairments".
- [9] ITU-T Recommendation P. 380 (2003): "Electro-acoustic measurements on headsets".
- [10] ITU-T Recommendation P.50 (1993): "Artificial voices".
- [11] ITU-T Recommendation P.79 (11/07) with Annex G (2001): "Calculation of loudness ratings for telephone sets".
- [12] ITU-T Recommendation G.223 (11/88): "Assumptions for the calculation of noise on hypothetical reference circuits for telephony".
- [13] ITU-T Recommendation P.340 (05/00): "Transmission characteristics and speech quality parameters of hands-free terminals".
- [14] ITU-T Recommendation P.501 (01/12): "Test signals for use in telephonometry".
- [15] ITU-T Recommendation P.502 (05/00): "Objective test methods for speech communication systems using complex test signals".

- [16] 3GPP TS 06.77 (R99): "Minimum Performance Requirements for Noise Suppressor Application to the AMR Speech Encoder".
- [17] 3GPP TS 26.114: "IP Multimedia Subsystem (IMS); Multimedia Telephony; Media handling and interaction".
- [18] 3GPP TS 23.203: "Policy and charging control architecture".
- [19] 3GPP TS 23.402: "Architecture enhancements for non-3GPP accesses".
- [20] 3GPP TS 24.302: "Access to the 3GPP Evolved Packet Core (EPC) via non-3GPP access networks; Stage 3".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document the terms *narrowband*, *wideband*, *super-wideband* and *fullband* refer to signals associated with the corresponding operating modes of the speech codecs specified in TS 26.132.

For the purposes of the present document, the terms dB, dBr, dBm0, dBm0p and dBA, shall be interpreted as defined in ITU-T Recommendation B.12 [2]; the term dBPa shall be interpreted as the sound pressure level relative to 1 pascal expressed in dB (0 dBPa is equivalent to 94 dB SPL).

The overload point (maximum load capacity) is for the purposes of this document defined as the RMS level of a digital representation of a full-scale pure tone at the input of the speech encoder. The overload point is defined at 3,14 dBm0 for AMR, AMR-WB and EVS speech codecs.

A 3GPP softphone is a telephony system running on a general purpose computer or PDA complying with the 3GPP terminal acoustic requirements (TS 26.131 and 26.132).

For the purposes of the present document the term *clock skew* is defined as the difference between the clock of the device under test (C_{DUT}) and the clock of the reference client (C_{REF}). The skew of C_{DUT} relative to C_{REF} is defined in parts per million (PPM) as: $(C_{DUT} - C_{REF}) \cdot 10^6 / C_{REF}$.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ADC	Analogue to Digital Converter
AMR	Adaptive Multi Rate
DAC	Digital to Analogue Converter
DAI	Digital Audio Interface
DRP	Eardrum Reference Point
DTX	Discontinuous Transmission
EEC	Electrical Echo Control
EL	Echo LossERP Ear Reference Point
EVS	Enhanced Voice ServicesHATS Head and Torso Simulator
G-MOS-LQO _n	Global (Overall) Mean Opinion Score - Listening Quality Objective - Narrowband
G-MOS-LQO _w	Global (Overall) Mean Opinion Score - Listening Quality Objective - Wideband
G-MOS-LQO _{fb}	Global (Overall) Mean Opinion Score - Listening Quality Objective - Fullband
IMS	IP Multimedia Subsystem
LSTR	Listener Sidetone Rating
LTE	Long Term Evolution
MRP	Mouth Reference Point
MTSI	Multimedia Telephony Service for IMSOLR Overall Loudness Rating
N-MOS-LQO _n	Noise (Background) Mean Opinion Score - Listening Quality Objective - Narrowband
N-MOS-LQO _w	Noise (Background) Mean Opinion Score - Listening Quality Objective - Wideband
N-MOS-LQO _{fb}	Noise (Background) Mean Opinion Score - Listening Quality Objective - Fullband
PCM	Pulse Code Modulation

PDA	Personal Digital Assistant
POI	Point of Interconnection (with PSTN)
PSTN	Public Switched Telephone Network
RRL	Receive Loudness Rating
S-MOS-LQO _n	Speech Signal Quality Mean Opinion Score - Listening Quality Objective - Narrowband
S-MOS-LQO _w	Speech Signal Quality Mean Opinion Score - Listening Quality Objective - Wideband
S-MOS-LQO _{fb}	Speech Signal Quality Mean Opinion Score - Listening Quality Objective - Fullband
SLR	Send Loudness Rating
STMR	Sidetone Masking Rating
SS	System Simulator
TX	Transmission
UE	User Equipment
UMTS	Universal Mobile Telecommunications System
UPCMI	13-bit Uniform PCM Interface
WLAN	Wireless Local Area Network

4 Interfaces

The interfaces required to define terminal acoustic characteristics are shown in TS 26.132. These are the air interface and the point of interconnect (POI). The interfaces are shown for one-channel (mono) operation, interfaces for two-channel (stereo) operation is for further study.

The Air Interfaces for GSM, 3G and LTE are specified by GSM 05, 3GPP 45, 3GPP 25 and 3GPP 36 series specifications, and the Air Interface for WLAN access to EPC is specified by WLAN access to EPC as defined in 3GPP TS 23.402 [19] and TS 24.302 [20]. MTSI speech aspects are specified by TS 26.114 [17].

Measurements can be made using the system simulator (SS) described in TS 26.132.

The POI with the public switched telephone network (PSTN) is considered to have a relative level of 0 dB.

Five classes of acoustic interface are considered in this specification:

- Handset UE including softphone UE used as a handset;
- Headset UE including softphone UE used with headset;
- Desktop-mounted hands-free UE including softphone UE with external loudspeaker(s) used in hands-free mode;
- Vehicle-mounted hands-free UE including softphone UE mounted in a vehicle;
- Hand-held hands-free UE including softphone UE with internal loudspeaker(s) used in hands-free mode.

(See definition of softphone in Clause 3.1)

NOTE: The requirements and performance objectives for a softphone UE shall be derived according to the following rules:

- When using a softphone UE as a handset: requirements and performance objectives shall correspond to handset mode.
- When using a softphone UE with headset: requirements and performance objectives shall correspond to headset mode.
- When a softphone UE is mounted in a vehicle: requirements and performance objectives shall correspond to vehicle-mounted handsfree mode.
- When using a softphone UE in hands-free mode:
 - When using internal loudspeaker(s), requirements and performance objectives shall correspond to hand-held hands-free.
 - When using external loudspeaker(s), requirements and performance objectives shall correspond to desktop-mounted hands-free.

5 Narrowband telephony transmission performance

5.1 Applicability

The performance requirements in this sub-clause shall apply when UE is used to provide narrowband telephony, either as a stand-alone service, or as part of a multimedia service.

5.2 Overall loss/loudness ratings

5.2.1 General

An international connection involving a 3G, LTE or WLAN network and the PSTN should meet the overall loudness rating (OLR) limits in ITU-T Recommendation G.111 [4]. The national parts of the connection should therefore meet the send and receive loudness rating (SLR, RLR) limits in ITU-T Recommendation G.121 [5].

For the case where digital routings are used to connect the 3G, LTE or WLAN network to the international chain of circuits, the SLR and RLR of the national extension will be largely determined by the SLR and RLR of the 3G, LTE or WLAN network. The limits given below are consistent with the national extension limits and long term objectives in ITU-T Recommendation G.121 [5].

The SLR and RLR values for the 3G, LTE or WLAN network apply up to the POI. However, the main determining factors are the characteristics of the UE, including the analogue to digital conversion (ADC) and digital to analogue conversion (DAC). In practice, it is convenient to specify loudness ratings to the Air Interface. For the normal case, where the 3G, LTE or WLAN network introduces no additional loss between the Air Interface and the POI, the loudness ratings to the PSTN boundary (POI) will be the same as the loudness ratings measured at the Air Interface. However, in some cases loss adjustment may be needed for interworking situations in individual countries.

5.2.2 Connections with handset UE

The nominal values of SLR/RLR to the POI shall be:

$$\text{SLR} = 8 \pm 3 \text{ dB};$$

$$\text{RLR} = 2 \pm 3 \text{ dB}.$$

Where a user-controlled receiving volume control is provided, the RLR shall meet the nominal value for at least one setting of the control. When the control is set to maximum, the RLR shall not be \leq (equal or louder than) -13 dB.

With the volume control set to the minimum position the RLR shall not be \geq (equal or quieter than) 18 dB.

Compliance shall be checked by the relevant tests described in TS 26.132.

5.2.2a Connections with handset UE in the presence of background noise

In the presence of background noise, the RLR at maximum volume control shall not be \leq (equal or louder than) -13 dB.

Compliance shall be checked by the relevant tests described in TS 26.132.

5.2.3 Connections with desktop and vehicle-mounted hands-free UE

The nominal values of SLR/RLR to/from the POI shall be:

$$\text{SLR} = 13 \pm 4 \text{ dB};$$

$$\text{RLR} = 2 \pm 4 \text{ dB (for vehicle-mounted hands-free UE);}$$

$$\text{RLR} = 5 \pm 4 \text{ dB (for desktop hands-free UE).}$$

1. For a vehicle-mounted hands-free UE:

Where a user-controlled volume control is provided, the RLR shall meet the nominal value for at least one setting of the control. It is recommended that a volume control giving at least 15 dB increase from the nominal RLR (louder) is provided for hands-free units intended to work in the vehicle environment. This is to allow for the increased acoustic noise level in a moving vehicle.

RLR at the maximum volume control setting should be \leq (equal or louder than) -2 dB.

2. For a desktop hands-free UE:

Where a user-controlled volume control is provided, the RLR shall meet the nominal value for at least one setting of the control. It is recommended that a volume control giving at least 15 dB increase from the nominal RLR (louder) is provided for hands-free units. This is to allow for the increased acoustic noise level in the usage environment.

RLR at the maximum volume control setting should be \leq (equal or louder than) 1 dB.

Compliance shall be checked by the relevant tests described in TS 26.132.

NOTE: The target value for nominal RLR, as recommended in ITU-T G.111 Annex B – Table B.1 [4], lies between 1 and 3 dB. The higher RLR requirement of 5 dB for desktop hands-free is appreciative of the limitations in transducer output with current typical form factors.

5.2.4 Connections with hand-held hands-free UE

The nominal values of SLR/RLR to/from the POI shall be:

SLR = 13 ± 4 dB;

RLR = $9 + 9 / - 7$ dB.

As a performance objective it is recommended that the RLR at the maximum volume control setting is \leq (equal or louder than) 2 dB.

Where a user-controlled volume control is provided, the RLR shall meet the nominal value for at least one setting of the control. It is recommended that a volume control range ≥ 15 dB be provided. Compliance shall be checked by the relevant tests described in TS 26.132.

NOTE: The target value for nominal RLR, as recommended in ITU-T G.111 Annex B – Table B.1 [4], lies between 1 and 3 dB. The higher RLR requirement of 9 dB for hand-held hands-free is appreciative of the limitations in transducer output with typical form factors.

5.2.5 Connections with headset UE

The nominal values of SLR/RLR to/from the POI shall be:

SLR = 8 ± 3 dB;

RLR = 2 ± 3 dB;

RLR (binaural headset) = 8 ± 3 dB for each earphone.

Where a user-controlled receiving volume control is provided, the RLR shall meet the nominal value for at least one setting of the control. When the control is set to maximum, the RLR shall not be \leq (equal or louder than) -13 dB.

With the volume control set to the minimum position the RLR shall not be \geq (equal or quieter than) 18 dB and shall not be \geq (equal or quieter than) 24 dB for a binaural headset.

Compliance shall be checked by the relevant tests described in 3GPP TS 26.132.

5.2.5a Connections with headset UE in the presence of background noise

In the presence of background noise, the RLR at maximum volume control shall not be \leq (equal or louder than) -13 dB.

Compliance shall be checked by the relevant tests described in TS 26.132.