

# ETSI TS 122 261 V15.8.0 (2019-10)



**5G;**  
**Service requirements for next generation new services and**  
**markets**  
**(3GPP TS 22.261 version 15.8.0 Release 15)**

*iTeh STANDARD PREVIEW  
(standards.iteh.ai)  
Full text of standards is available at  
<https://standards.iteh.ai/catalog/standards/sist/72844090-eccf-4aad-8190-e3d4b35d21ff/etsi-ts-122-261-v15-8-0-2019-10>*



---

Reference

RTS/TSGS-0122261vf80

---

Keywords

---

5G

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

---

The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

---

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

**GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

## Intellectual Property Rights

### Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

### Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

---

## Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

Intellectual Property Rights .....	2
Legal Notice .....	2
Modal verbs terminology.....	2
Foreword.....	6
Introduction .....	6
1 Scope .....	7
2 References .....	7
3 Definitions, symbols and abbreviations .....	8
3.1 Definitions .....	8
3.2 Abbreviations .....	9
4 Overview .....	9
5 High-level requirements .....	10
5.1 Migration to 5G .....	10
5.1.1 Description.....	10
5.1.2 Requirements .....	11
5.1.2.1 Interworking between 5G systems .....	11
5.1.2.2 Legacy service support.....	11
5.1.2.3 Interoperability with legacy 3GPP systems.....	11
6 Basic capabilities.....	11
6.1 Network slicing .....	11
6.1.1 Description.....	11
6.1.2 Requirements .....	11
6.2 Diverse mobility management.....	12
6.2.1 Description.....	12
6.2.2 General requirements.....	13
6.2.3 Service continuity requirements .....	13
6.3 Multiple access technologies.....	13
6.3.1 Description.....	13
6.3.2 Requirements .....	13
6.3.2.1 General .....	13
6.3.2.2 E-UTRA access .....	14
6.3.2.3 Void.....	14
6.3.2.4 Void.....	14
6.4 Resource efficiency .....	14
6.4.1 Description.....	14
6.4.2 Requirements .....	15
6.4.2.1 General .....	15
6.4.2.2 Void.....	15
6.4.2.3 Void.....	15
6.4.2.4 Efficient control plane.....	15
6.5 Efficient user plane.....	16
6.5.1 Description.....	16
6.5.2 Requirements .....	16
6.6 Efficient content delivery .....	17
6.6.1 Description.....	17
6.6.2 Requirements .....	17
6.7 Priority, QoS, and policy control.....	17
6.7.1 Description.....	17
6.7.2 Requirements .....	18
6.8 Dynamic policy control .....	18
6.9 Void.....	19
6.9.1 Void .....	19

6.9.2	Void .....	19
6.10	Network capability exposure .....	19
6.10.1	Description .....	19
6.10.2	Requirements .....	19
6.11	Context aware network .....	19
6.11.1	Description .....	19
6.11.2	Requirements .....	20
6.12	Void .....	20
6.13	Void .....	20
6.14	Subscription aspects .....	20
6.14.1	Description .....	20
6.14.2	Requirements .....	20
6.15	Energy efficiency .....	21
6.15.1	Description .....	21
6.15.2	Requirements .....	21
6.16	Markets requiring minimal service levels .....	21
6.16.1	Description .....	21
6.16.2	Requirements .....	22
6.17	Extreme long range coverage in low density areas .....	22
6.17.1	Description .....	22
6.17.2	Requirements .....	22
6.18	Void .....	22
6.19	3GPP access network selection .....	22
6.19.1	Description .....	22
6.19.2	Requirements .....	22
6.20	eV2X aspects .....	23
6.20.1	Description .....	23
6.20.2	Requirements .....	23
6.21	NG-RAN Sharing .....	23
6.21.1	Description .....	23
6.21.2	Requirements .....	23
6.22.2.1	General .....	24
6.22.2.2	Access identities .....	25
6.22.2.3	Access categories .....	25
7	Performance requirements .....	26
7.1	High data rates and traffic densities .....	26
7.2	Low latency and high reliability .....	28
7.2.1	Overview .....	28
7.2.2	Scenarios and KPIs .....	28
7.2.3	Other requirements .....	31
7.3	High accuracy positioning .....	31
7.3.1	Description .....	31
7.3.2	Requirements .....	31
8	Security .....	32
8.1	Description .....	32
8.2	General .....	32
8.3	Authentication .....	32
8.4	Authorization .....	33
8.5	Identity management .....	33
8.6	Regulatory .....	33
8.7	Fraud protection .....	33
8.8	Resource efficiency .....	33
9	Charging aspects .....	34
<b>Annex A (informative):</b>	<b>Latency needs to support example use cases from vertical industries .....</b>	<b>35</b>
<b>Annex B (informative):</b>	<b>Positioning accuracy needs to support example use cases from vertical industries .....</b>	<b>36</b>
<b>Annex C (informative):</b>	<b>Relation of communication service availability and reliability .....</b>	<b>37</b>

<b>Annex D (informative):</b>	<b>Low-latency and high-reliability communication use cases</b> .....	<b>40</b>
D.1	Discrete automation – motion control .....	40
D.1.1	Service area and connection density .....	41
D.1.2	Security .....	41
D.2	Discrete automation.....	41
D.2.1	Service area and connection density .....	43
D.2.2	Security .....	43
D.3	Process automation.....	43
D.3.1	Remote control.....	44
D.3.2	Monitoring .....	44
D.3.3	Service area.....	44
D.4	Electricity distribution.....	44
D.4.1	Medium voltage .....	44
D.4.1.1	Service area and connection density .....	46
D.4.1.2	Security .....	46
D.4.2	Energy distribution – high voltage.....	46
D.4.2.1	Service area and connection density .....	46
D.4.2.2	Security .....	46
D.5	Intelligent transport systems – infrastructure backhaul .....	47
D.5.1	Service area and connection density .....	47
<b>Annex E (informative):</b>	<b>Higher-accuracy positioning use cases</b> .....	<b>48</b>
E.1	Mobile objects on factory floor .....	48
<b>Annex F (informative):</b>	<b>Change history</b> .....	<b>49</b>
History .....		52

**PREVIEW**  
**STANDARD**  
**PREVIEW**  
 (standards.iteh.ai)  
 Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/72644090-eeccf-4aad-8190-e3d4b35d2fff/etsi-ts-122-261-v15.8.0-2019-10>

---

# Foreword

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

---

# Introduction

The need to support different kinds of UEs (e.g., for the Internet of Things (IoT)), services, and technologies is driving the technology revolution to a high-performance and highly efficient 3GPP system. The drivers include IoT, Virtual Reality (VR), industrial control, ubiquitous on-demand coverage, as well as the opportunity to meet customized market needs. These drivers require enhancements to the devices, services, and technologies well established by 3GPP. The key objective with the 5G system is to be able to support new deployment scenarios to address diverse market segments.

This document compiles requirements that define a 5G system.

The 5G system is characterised, for example, by:

- Support for multiple access technologies
- Scalable and customizable network
- Advanced Key Performance Indicators (KPIs) (e.g., availability, latency, reliability, user experienced data rates, area traffic capacity)
- Flexibility and programmability (e.g., network slicing, diverse mobility management, Network Function Virtualization)
- Resource efficiency (both user plane and control plane)
- Seamless mobility in densely populated and heterogeneous environment
- Support for real time and non-real time multimedia services and applications with advanced Quality of Experience (QoE)

---

# 1 Scope

The present document describes the service and operational requirements for a 5G system, including a UE, NG-RAN, and 5G Core network. Requirements for a 5G E-UTRA-NR Dual Connectivity in E-UTRAN connected to EPC are found in TS 22.278 [5].

---

# 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] NGMN 5G White Paper v1.0, February 2015.
- [3] 3GPP TS 22.011: "Service accessibility".
- [4] NGMN, "Perspectives on Vertical Industries and Implications for 5G, v2.0", September 2016.
- [5] 3GPP TS 22.278: "Service requirements for the Evolved Packet System (EPS)".
- [6] 3GPP TS 22.101: "Service aspects; Service principles".
- [7] 3GPP TS 22.146: "Multimedia Broadcast/Multicast Service (MBMS)".
- [8] 3GPP TS 22.246: "Multimedia Broadcast/Multicast Service (MBMS) user services".
- [9] 3GPP TS 22.186: "Enhancement of 3GPP support for V2X scenarios".
- [10] NGMN, "Recommendations for NGMN KPIs and Requirements for 5G", June 2016
- [11] 3GPP TS 22.115: "Service aspects; Charging and billing".
- [12] Communication network dependability engineering. IEC 61907:2009.
- [13] Soriano, R., Alberto, M., Collazo, J., Gonzales, I., Kupzo, F., Moreno, L., & Lorenzo, J. OpenNode. Open Architecture for Secondary Nodes of the Electricity Smartgrid. In Proceedings CIRED 2011 21st International Conference on Electricity Distribution, CD1. June 2011.
- [14] North American Electric Reliability Council. Frequently Asked Questions (FAQs) Cyber Security Standards CIP-002-1 through CIP-009-1. Available: [http://www.nerc.com/docs/standards/sar/Revised\\_CIP-002-009\\_FAQs\\_06Mar06.pdf](http://www.nerc.com/docs/standards/sar/Revised_CIP-002-009_FAQs_06Mar06.pdf). 2006.
- [15] McTaggart, Craig, et al. "Improvements in power system integrity protection schemes." Developments in Power System Protection (DPSP 2010). Managing the Change, 10th IET International Conference on. IET, 2010.
- [16] IEEE Power Engineering Society – Power System Relaying Committee – System Protection Subcommittee Working Group C-6. Wide Area Protection and Emergency Control.
- [17] Begovic, Miroslav, et al. "Wide-area protection and emergency control." Proceedings of the IEEE 93.5, pp. 876-891, 2005.
- [18] 3GPP TR 38.913: "Study on scenarios and requirements for next generation access technologies".



## 3 Definitions, symbols and abbreviations

### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

**active communication:** a UE is in active communication when it has one or more connections established. A UE may have any combination of PS connections (e.g., PDP contexts, active PDN connections).

**activity factor:** percentage value of the amount of simultaneous active UEs to the total number of UEs where active means the UEs are exchanging data with the network.

**area traffic capacity:** total traffic throughput served per geographic area.

**communication service availability:** percentage value of the amount of time the end-to-end communication service is delivered according to an agreed QoS, divided by the amount of time the system is expected to deliver the end-to-end service according to the specification in a specific area.

NOTE 1: The end point in "end-to-end" is assumed to be the communication service interface.

**direct network connection:** one mode of network connection, where there is no relay UE between a UE and the 5G network.

**end-to-end latency:** the time that takes to transfer a given piece of information from a source to a destination, measured at the communication interface, from the moment it is transmitted by the source to the moment it is successfully received at the destination.

**Hosted Service:** a service containing the operator's own application(s) and/or trusted 3<sup>rd</sup> party application(s) in the Service Hosting Environment, which can be accessed by the user.

**IoT device:** a type of UE which is dedicated for a set of specific use cases or services and which is allowed to make use of certain features restricted to this type of UEs.

NOTE 3: An IoT device may be optimized for the specific needs of services and application being executed (e.g., smart home/city, smart utilities, e-Health and smart wearables). Some IoT devices are not intended for human type communications.

**network slice:** a set of network functions and corresponding resources necessary to provide the required telecommunication services and network capabilities.

**NG-RAN:** a radio access network connecting to the 5G core network which uses NR, E-UTRA, or both.

**NR:** the new 5G radio access technology.

**priority service:** a service that requires priority treatment based on regional/national or operator policies.

**private network:** an isolated network deployment that does not interact with a public network.

**reliability:** in the context of network layer packet transmissions, percentage value of the amount of sent network layer packets successfully delivered to a given system entity within the time constraint required by the targeted service, divided by the total number of sent network layer packets.

**satellite access:** direct connectivity between the UE and the satellite.

**service area:** geographic region where a 3GPP communication service is accessible.

NOTE 4: The service area can be indoors.

NOTE 5: For some deployments, e.g., in process industry, the vertical dimension of the service area can be considerable.

**service continuity:** the uninterrupted user experience of a service that is using an active communication when a UE undergoes an access change without, as far as possible, the user noticing the change.

NOTE 6: In particular service continuity encompasses the possibility that after a change the user experience is maintained by a different telecommunication service (e.g., tele- or bearer service) than before the change.

NOTE 7: Examples of access changes include the following. For EPS: CS/PS domain change. For EPS and 5G: radio access change.

**Service Hosting Environment:** the environment, located inside of 5G network and fully controlled by the operator, where Hosted Services are offered from.

**survival time:** the time that an application consuming a communication service may continue without an anticipated message.

**User Equipment:** An equipment that allows a user access to network services via 3GPP and/or non-3GPP accesses.

**user experienced data rate:** the minimum data rate required to achieve a sufficient quality experience, with the exception of scenario for broadcast like services where the given value is the maximum that is needed.

**wireless backhaul:** a link which provides an interconnection between 5G network nodes and/or transport network using 5G radio access technology.

## 3.2 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

3D	Three Dimensional
5G	Fifth Generation
AR	Augmented Reality
A/S	Actuator/sensor
E2E	End to End
eFMSS	Enhancement to Flexible Mobile Service Steering
FMSS	Flexible Mobile Service Steering
ICP	Internet Content Provider
ID	Identification
IOPS	Isolated E-UTRAN Operation for Public Safety
IoT	Internet of Things
KPI	Key Performance Indicator
MBB	Mobile BroadBand
MIoT	Massive Internet of Things
MNO	Mobile Network Operator
MPS	Multimedia Priority Service
MVNO	Mobile Virtual Network Operator
NGMN	Next Generation Mobile Networks
QoE	Quality of Experience
SEES	Service Exposure and Enablement Support
SST	Slice/Service Type
UAV	Unmanned Aerial Vehicle
UHD	Ultra High Definition
VR	Virtual Reality

## 4 Overview

Unlike previous 3GPP systems that attempted to provide a 'one size fits all' system, the 5G system is expected to be able to provide optimized support for a variety of different services, different traffic loads, and different end user communities. Various industry white papers, most notably, the NGMN 5G White Paper [2], describe a multi-faceted 5G system capable of simultaneously supporting multiple combinations of reliability, latency, throughput, positioning, and availability. This technology revolution is achievable with the introduction of new technologies, both in access and the

core, such as flexible, scalable assignment of network resources. In addition to increased flexibility and optimization, a 5G system needs to support stringent KPIs for latency, reliability, throughput, etc. Enhancements in the air interface contribute to meeting these KPIs as do enhancements in the core network, such as network slicing, in-network caching and hosting services closer to the end points.

A 5G system also supports new business models such as those for IoT and enterprise managed networks. Drivers for the 5G KPIs include services such as Unmanned Aerial Vehicle (UAV) control, Augmented Reality (AR), and factory automation. Network flexibility enhancements support self-contained enterprise networks, installed and maintained by network operators while being managed by the enterprise. Enhanced connection modes and evolved security facilitate support of massive IoT, expected to include tens of millions of UEs sending and receiving data over the 5G network.

Flexible network operations are the mainstay of the 5G system. The capabilities to provide this flexibility include network slicing, network capability exposure, scalability, and diverse mobility. Other network operations requirements address the necessary control and data plane resource efficiencies, as well as network configurations that optimize service delivery by minimizing routing between end users and application servers. Enhanced charging and security mechanisms handle new types of UEs connecting to the network in different ways.

Mobile Broadband (MBB) enhancements aim to meet a number of new KPIs. These pertain to high data rates, high user density, high user mobility, highly variable data rates, deployment, and coverage. High data rates are driven by the increasing use of data for services such as streaming (e.g., video, music, and user generated content), interactive services (e.g., AR), and IoT. These services come with stringent requirements for user experienced data rates as well as associated requirements for latency to meet service requirements. Additionally, increased coverage in densely populated areas such as sports arenas, urban areas, and transportation hubs has become essential for pedestrians and users in urban vehicles. New KPIs on traffic and connection density enable both the transport of high volumes of data traffic per area (traffic density) and transport of data for a high number of connections (e.g., UE density or connection density). Many UEs are expected to support a variety of services which exchange either a very large (e.g., streaming video) or very small (e.g., data burst) amount of data. The 5G system will handle this variability in a resource efficient manner. All of these cases introduce new deployment requirements for indoor and outdoor, local area connectivity, high user density, wide area connectivity, and UEs travelling at high speeds.

Another aspect of 5G KPIs includes requirements for various combinations of latency and reliability, as well as higher accuracy for positioning. These KPIs are driven by support for both commercial and public safety services. On the commercial side, industrial control, industrial automation, UAV control, and AR are examples of those services. Services such as UAV control will require more precise positioning information that includes altitude, speed, and direction, in addition to horizontal coordinates.

Support for Massive Internet of Things (MIoT) brings many new requirements in addition to those for the enhanced KPIs. The expansion of connected things introduces a need for significant improvements in resource efficiency in all system components (e.g., UEs, IoT devices, radio, access network, core network).

The 5G system also aims to enhance its capability to meet KPIs that emerging V2X applications require. For these advanced applications, the requirements, such as data rate, reliability, latency, communication range and speed, are made more stringent.

---

## 5 High-level requirements

### 5.1 Migration to 5G

#### 5.1.1 Description

The 5G system supports most of the existing EPS services, in addition to many new services. The existing EPS services may be accessed using the new 5G access technologies even where the EPS specifications might indicate E-UTRA(N) only. Only new or changed service requirements for new or changed services are specified in this TS. The few EPS capabilities that are not supported by the 5G system are identified in clause 5.1.2.2 below.

## 5.1.2 Requirements

### 5.1.2.1 Interworking between 5G systems

The 5G system shall support a UE with a 5G subscription roaming into a 5G Visited Mobile Network which has a roaming agreement with the UE's 5G Home Mobile Network.

The 5G system shall enable a Visited Mobile Network to provide support for establishing home network provided data connectivity as well as visited network provided data connectivity.

The 5G system shall enable a Visited Mobile Network to provide support for services provided in the home network as well as provide services in the visited network. Whether a service is provided in the visited network or in the home network is determined on a service by service basis.

The 5G system shall provide a mechanism for a network operator to limit access to its services for a roaming UE, (e.g., based on roaming agreement).

The 5G system shall provide a mechanism for a network operator to direct a UE onto a partnership network for routing all or some of the UE user plane and associated control plane traffic over the partnership network, subject to an agreement between the operators.

### 5.1.2.2 Legacy service support

The 5G system shall support all EPS capabilities (e.g., from TSs 22.011, 22.101, 22.278, 22.185, 22.071, 22.115, 22.153, 22.173) with the following exceptions:

- CS voice service continuity and/or fallback to GERAN or UTRAN,
- seamless handover between NG-RAN and GERAN,
- seamless handover between NG-RAN and UTRAN, and
- access to a 5G core network via GERAN or UTRAN.

### 5.1.2.3 Interoperability with legacy 3GPP systems

The 5G system shall support mobility procedures between a 5G core network and an EPC with minimum impact to the user experience (e.g. QoS, QoE).

---

## 6 Basic capabilities

### 6.1 Network slicing

#### 6.1.1 Description

Network slicing allows the operator to provide customised networks. For example, there can be different requirements on functionality (e.g., priority, charging, policy control, security, and mobility), differences in performance requirements (e.g., latency, mobility, availability, reliability and data rates), or they can serve only specific users (e.g., MPS users, Public Safety users, corporate customers, roamers, or hosting an MVNO).

A network slice can provide the functionality of a complete network, including radio access network functions and core network functions (e.g., potentially from different vendors). One network can support one or several network slices.

#### 6.1.2 Requirements

The 5G system shall allow the operator to create, modify, and delete a network slice.

The 5G system shall allow the operator to define and update the set of services and capabilities supported in a network slice.

The 5G system shall allow the operator to configure the information which associates a UE to a network slice.

The 5G system shall allow the operator to configure the information which associates a service to a network slice.

The 5G system shall allow the operator to assign a UE to a network slice, to move a UE from one network slice to another, and to remove a UE from a network slice based on subscription, UE capabilities, the access technology being used by the UE, operator's policies and services provided by the network slice.

The 5G system shall support a mechanism for the VPLMN to assign a UE to a network slice with the needed services and authorised by the HPLMN, or to a default network slice.

The 5G system shall enable a UE to be simultaneously assigned to and access services from more than one network slice of one operator.

Traffic and services in one network slice shall have no impact on traffic and services in other network slices in the same network.

Creation, modification, and deletion of a network slice shall have no or minimal impact on traffic and services in other network slices in the same network.

The 5G system shall support scaling of a network slice, i.e., adaptation of its capacity.

The 5G system shall enable the network operator to define a minimum available capacity for a network slice. Scaling of other network slices on the same network shall have no impact on the availability of the minimum capacity for that network slice.

The 5G system shall enable the network operator to define a maximum capacity for a network slice.

The 5G system shall enable the network operator to define a priority order between different network slices in case multiple network slices compete for resources on the same network.

The 5G system shall support means by which the operator can differentiate policy control, functionality and performance provided in different network slices.

The serving 5G network shall support providing connectivity to home and roaming users in the same network slice.

In shared 5G network configuration, each operator shall be able to apply all the requirements from this clause to their allocated network resources.

The 5G system shall support a mechanism to configure a specific geographic area in which a network slice is accessible, i.e., a UE shall be within the geographical area in order to access the network slice.

## 6.2 Diverse mobility management

### 6.2.1 Description

A key feature of 5G is support for UEs with different mobility management needs. 5G will support UEs with a range of mobility management needs, including UEs that are

- stationary during their entire usable life (e.g., sensors embedded in infrastructure),
- stationary during active periods, but nomadic between activations (e.g., fixed access),
- mobile within a constrained and well-defined space (e.g., in a factory), and
- fully mobile.

Moreover, some applications require the network to ensure seamless mobility of a UE so that mobility is hidden from the application layer to avoid interruptions in service delivery while other applications have application specific means to ensure service continuity. But these other applications may still require the network to minimize interruption time to ensure that their application-specific means to ensure service continuity work effectively.