

ETSI TS 136 113 V15.4.0 (2019-10)



**LTE;
Evolved Universal Terrestrial Radio Access (E-UTRA);
Base Station (BS) and repeater
ElectroMagnetic Compatibility (EMC)
(3GPP TS 36.113 version 15.4.0 Release 15)**



ReferenceRTS/TSGR-0436113vf40

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	5
1 Scope	6
2 References	6
3 Definitions, symbols and abbreviations	7
3.1 Definitions	7
3.2 Symbols.....	10
3.3 Abbreviations	10
4 Test conditions	10
4.1 General	10
4.2 Arrangements for establishing a communication link	10
4.2.1 Multiple enclosure BS solution.....	11
4.3 Narrow band responses on receivers	11
4.4 Test condition for Repeater	11
4.4.1 Arrangements for test signals for repeaters.....	11
4.5 Exclusion bands.....	12
4.5.1 Transmitter exclusion band.....	12
4.5.2 Receiver exclusion band	12
4.6 BS test configurations	12
5 Performance assessment.....	13
5.1 General	13
5.2 Assessment of throughput in Downlink	13
5.3 Assessment of throughput in Uplink	13
5.4 Ancillary equipment	14
5.5 Repeaters	14
6 Performance Criteria	14
6.1 Performance criteria for continuous phenomena for BS	14
6.2 Performance criteria for transient phenomena for BS	15
6.3 Performance criteria for continuous phenomena for Ancillary equipment.....	17
6.4 Performance criteria for transient phenomena for Ancillary equipment	17
6.5 Performance criteria for continuous phenomena for repeaters	17
6.6 Performance criteria for transient phenomena for repeaters.....	17
7 Applicability overview	18
7.1 Emission	18
7.2 Immunity	18
7.3 Applicability of requirements in TS 37.113	19
8 Emission	19
8.1 Test configurations	19
8.2 Radiated emission from Base station, Repeater and ancillary equipment	20
8.2.1 Radiated emission, Base stations and Repeater	20
8.2.1.1 Definition	20
8.2.1.2 Test method.....	20
8.2.1.3 Limits	21
8.2.1.4 Interpretation of the measurement results	21
8.2.2 Radiated emission, Ancillary equipment	22
8.2.2.1 Definition	22
8.2.2.2 Test method.....	22
8.2.2.3 Limits	22
8.3 Conducted emission DC power input/output port	22

8.3.1	Definition	22
8.3.2	Test method	23
8.3.3	Limits	23
8.4	Conducted emissions, AC mains power input/output port	23
8.4.1	Definition	23
8.4.2	Test method	23
8.4.3	Limits	23
8.5	Harmonic Current emissions (AC mains input port)	24
8.6	Voltage fluctuations and flicker (AC mains input port)	24
8.7	Telecommunication ports	24
8.7.1	Definition	24
8.7.2	Test method	24
8.7.3	Limits	25
9	Immunity	25
9.1	Test methods and levels for immunity tests	25
9.2	Test configurations	25
9.3	RF electromagnetic field (80 MHz - 6000 MHz)	26
9.3.1	Definition	26
9.3.2	Test method and level	26
9.3.3	Performance criteria	27
9.4	Electrostatic discharge	27
9.4.1	Definition	27
9.4.2	Test method and level	27
9.4.3	Performance criteria	27
9.5	Fast transients common mode	27
9.5.1	Definition	28
9.5.2	Test method and level	28
9.5.3	Performance criteria	28
9.6	RF common mode (0,15 MHz - 80 MHz)	28
9.6.1	Definition	28
9.6.2	Test method and level	28
9.6.3	Performance criteria	29
9.7	Voltage dips and interruptions	29
9.7.1	Definition	29
9.7.2	Test method and level	29
9.7.3	Performance criteria	29
9.8	Surges, common and differential mode	30
9.8.1	Definition	30
9.8.2	Test method and level	30
9.8.2.1	Test method for telecommunication ports directly connected to outdoor cables	30
9.8.2.2	Test method for telecommunication ports connected to indoor cables	30
9.8.2.3	Test method for AC power ports	31
9.8.3	Performance criteria	31
Annex A (informative):	Change history	32
History		34

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

ETSI STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/66c6381f-3389-4ceb-9b30-13ca95ea2704/etsi-ts-136-113-v15.4.0-2019-10>

1 Scope

The present document covers the assessment of E-UTRA, E-UTRA with NB-IoT or NB-IoT base stations, repeaters and associated ancillary equipment in respect of Electromagnetic Compatibility (EMC).

The present document specifies the applicable test conditions, performance assessment and performance criteria for E-UTRA, E-UTRA with NB-IoT or NB-IoT base stations, repeaters and associated ancillary equipment in one of the following categories:

- base stations of E-UTRA, E-UTRA with NB-IoT or NB-IoT meeting the requirements of TS 36.104 [2], with conformance demonstrated by compliance to TS 36.141 [3].
- repeaters of E-UTRA meeting the requirements of TS 36.106 [4], with conformance demonstrated by compliance to TS 36.143 [5].

Technical requirements related to the antenna port of E-UTRA, E-UTRA with NB-IoT or NB-IoT base stations or repeaters are not included in the present document. These are found in the relevant product standards [2-5].

The environment classification used in the present document refers to the residential, commercial and light industrial environment classification used in IEC 61000-6-1 [6] and IEC 61000-6-3 [7].

The EMC requirements have been selected to ensure an adequate level of compatibility for apparatus at residential, commercial and light industrial environments. The levels, however, do not cover extreme cases which may occur in any location but with low probability of occurrence.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TR 36.104: "Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) radio transmission and reception".
- [3] 3GPP TR 36.141: "Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) conformance testing".
- [4] 3GPP TR 36.106: "Evolved Universal Terrestrial Radio Access (E-UTRA); Repeater radio transmission and reception".
- [5] 3GPP TR 36.143: "Evolved Universal Terrestrial Radio Access (E-UTRA); Repeater conformance testing".
- [6] IEC 61000-6-1: 2005; "Electromagnetic compatibility (EMC) - Part 6: Generic standards - Section 1: Immunity for residential, commercial and light-industrial environments".
- [7] IEC 61000-6-3:2006/AMD1:2010: "Electromagnetic compatibility (EMC) - Part 6: Generic standards - Section 3: Emission standard for residential, commercial and light industrial environments".
- [8] IEC 60050(161): "International Electrotechnical Vocabulary - Chapter 161: Electromagnetic compatibility".

- [9] 3GPP TR 36.101: "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) radio transmission and reception".
- [10] ITU-R Rec. SM.329: "Unwanted emissions in the spurious domain".
- [11] Void
- [12] Void
- [13] IEC 61000-3-2 (2004): "Electromagnetic compatibility (EMC) - Part 3: Limits - Section 2: Limits for harmonic current emissions (equipment input current ≤ 16 A)".
- [14] IEC 61000-3-12 (2005): "Electromagnetic compatibility (EMC) - Part 3-12: Limits- Limits for harmonic current produced by equipment connected to public low-voltage system with input current >16 A and ≤ 75 A".
- [15] IEC 61000-3-3 (2002): "Electromagnetic compatibility (EMC) - Part 3: Limits - Section 3: Limitation of voltage fluctuations and flicker in low-voltage supply systems for equipment with rated current ≤ 16 A".
- [16] IEC 61000-3-11 (2000): "Electromagnetic compatibility (EMC) - Part 3-11: Limits –Limitation of voltage fluctuations and flicker in low-voltage supply systems for equipment with rated current ≤ 75 A and subject to conditional connections".
- [17] IEC 61000-4-3: "Electromagnetic compatibility (EMC) - Part 4: Testing and measurement techniques - Section 3: Radiated, radio-frequency electromagnetic field immunity test".
- [18] IEC 61000-4-2: "Electromagnetic compatibility (EMC) - Part 4: Testing and measurement techniques - Section 2: Electrostatic discharge immunity test".
- [19] IEC 61000-4-4: "Electromagnetic compatibility (EMC) - Part 4: Testing and measurement techniques - Section 4: Electrical fast transient/burst immunity test".
- [20] IEC 61000-4-6: "Electromagnetic compatibility (EMC) - Part 4: Testing and measurement techniques - Section 6: Immunity to contacted disturbances, induced by radio frequency fields".
- [21] IEC 61000-4-11: "Electromagnetic compatibility (EMC) - Part 4: Testing and measurement techniques - Section 11: Voltage dips, short interruptions and voltage variations. Immunity tests".
- [22] IEC 61000-4-5: "Electromagnetic compatibility (EMC) - Part 4: Testing and measurement techniques - Section 5: Surge immunity test".
- [23] ITU-R Recommendation SM.1539 (2001): "Variation of the boundary between the out-of-band and spurious domains required for the application of Recommendations ITU-R SM.1541 and ITU-R SM.329".
- [24] 3GPP TS 37.113: "E-UTRA, UTRA and GSM/EDGE; Multi-Standard Radio (MSR) Base Station (BS) Electromagnetic Compatibility (EMC)".
- [25] CISPR 32: "Electromagnetic compatibility of multimedia equipment - Emission requirements".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in TR 21.905 [1].

Ancillary equipment: Equipment (apparatus), used in connection with a receiver, transmitter or transceiver is considered as an ancillary equipment (apparatus) if:

- the equipment is intended for use in conjunction with a receiver, transmitter or transceiver to provide additional operational and/or control features to the radio equipment, (e.g. to extend control to another position or location); and
- the equipment cannot be used on a stand-alone basis to provide user functions independently of a receiver, transmitter or transceiver; and
- the receiver, transmitter or transceiver to which it is connected, is capable of providing some intended operation such as transmitting and/or receiving without the ancillary equipment (i.e. it is not a sub-unit of the main equipment essential to the main equipment basic functions).

Base Station equipment: Radio and/or ancillary equipment intended for operation at a fixed location and powered directly or indirectly (e.g. via an AC/DC converter or power supply) by AC mains network, or an extended local DC mains network.

Channel bandwidth: The RF bandwidth supporting a single E-UTRA RF carrier with the transmission bandwidth configured in the uplink or downlink of a cell. The channel bandwidth is measured in MHz and is used as a reference for transmitter and receiver RF requirements.

Continuous phenomena (continuous disturbance): Electromagnetic disturbance, the effects of which on a particular device or equipment cannot be resolved into a succession of distinct effects (IEC 60050-161 [8]).

Maximum throughput: The maximum achievable throughput for a reference measurement channel.

Multi-band Base Station: Base Station characterized by the ability of its transmitter and/or receiver to process two or more carriers in common active RF components simultaneously, where at least one carrier is configured at a different non-overlapping operating band than the other carrier(s).

NB-IoT In-band operation: NB-IoT is operating in-band when it utilizes the resource block(s) within a normal E-UTRA carrier

NB-IoT guard band operation: NB-IoT is operating in guard band when it utilizes the unused resource block(s) within a E-UTRA carrier's guard-band.

NB-IoT standalone operation: NB-IoT is operating standalone when it utilizes its own spectrum, for example the spectrum currently being used by GERAN systems as a replacement of one or more GSM carriers, as well as scattered spectrum for potential IoT deployment.

Radio communications equipment : Telecommunications equipment which includes one or more transmitters and/or receivers and/or parts thereof for use in a fixed, mobile or portable application. It can be operated with ancillary equipment but if so, is not dependent on it for basic functionality.

Radio equipment: Equipment which contains Radio digital unit and Radio unit.

Radio digital unit: Equipment which contains base band and functionality for controlling Radio unit.

Radio unit: Equipment which contains transmitter and/or receiver.

receiver exclusion band: Band of frequencies over which no tests of radiated immunity of a receiver are made, and is expressed relative to the BS receive band.

Port: A particular interface, of the specified equipment (apparatus), with the electromagnetic environment. For example, any connection point on an equipment intended for connection of cables to or from that equipment is considered as a port (see Figure 3.1.1).

Receiver exclusion band: The receiver exclusion band is the band of frequencies over which no tests of radiated immunity of a receiver are made. The exclusion band for receivers is expressed relative to the base station receive band.

Repeater: A device that receives, amplifies and transmits the radiated or conducted RF carrier both in the down-link direction (from the base station to the mobile area) and in the up-link direction (from the mobile to the base station). In operating bands specified with only down-link or up-link, only the up-link or down-link as specified for the operating band is repeated.

Signal and control : Port which carries information or control signals, excluding antenna ports.

Telecommunication port: Ports which are intended to be connected to telecommunication networks (e.g. public switched telecommunication networks, integrated services digital networks), local area networks (e.g. Ethernet, Token Ring) and similar networks.

Throughput: The number of payload bits successfully received per second for a reference measurement channel in a specified reference condition.

Transient phenomena: Pertaining to or designating a phenomena or a quantity which varies between two consecutive steady states during a time interval short compared with the time-scale of interest (IEC 60050-161 [8]).

Transmitter exclusion band: Band of frequencies over which no tests of radiated immunity of a transmitter are made and is expressed relative to the carrier frequencies used (the carrier frequencies of the base stations activated transmitter(s)).




Figure 3.1.1: Examples of ports



Figure 3.1.2: BS with single enclosure solution




Figure 3.1.3: BS with multiple enclosure solution

3.2 Symbols

For the purposes of the present document, the following symbols apply:

BW_{Channel}	Channel bandwidth
Δf_{OOB}	Maximum offset of the out-of-band boundary from the uplink operating band edge
$F_{\text{UL,low}}$	The lowest frequency of the uplink operating band
$F_{\text{UL,high}}$	The highest frequency of the uplink operating band

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [1].

AC	Alternating Current
AMN	Artificial Mains Network
CDN	Coupling/Decoupling Network
DC	Direct Current
E-UTRA	Evolved Universal Terrestrial Radio Access
EMC	Electromagnetic Compatibility
EPC	Evolved Packet Core
ESD	Electrostatic Discharge
EUT	Equipment Under Test
FRC	Fixed Reference Channel
NB-IoT	Narrowband – Internet of Things
RF	Radio frequency
rms	root mean square
SDL	Supplementary Downlink

4 Test conditions

4.1 General

The equipment shall be tested in normal test environment defined in base station conformance testing specification TS 36.141 [3] or in the E-UTRA repeater conformance testing specification TS 36.143 [5]. The test conditions shall be recorded in the test report.

For an EUT which contains more than one BS, it is sufficient to perform tests relating to each type of port of each representative type of the BS forming part of the EUT.

For BS capable of multi-band operation, the requirements in the present document apply for each supported operating band unless otherwise stated. Operating bands shall be activated according to the test configuration in subclause 4.6. Tests shall be performed relating to each type of port and all bands shall be assessed during the tests.

4.2 Arrangements for establishing a communication link

The wanted RF input signal nominal frequency shall be selected by setting the E-UTRA Absolute Radio Frequency Channel Number (EARFCN) to an appropriate number.

A communication link shall be set up with a suitable test system capable of evaluating the required performance criteria (hereafter called "the test system") at the air interface and/or the S1 interface. The test system shall be located outside of the test environment.

When the EUT is required to be in the transmit/receive mode, the following conditions shall be met: