

ETSI TS 137 105 v15.7.0 (2019-10)



Universal Mobile Telecommunications System (UMTS); Long Term Evolution (LTE); Active Antenna System (AAS) Base Station (BS) transmission and reception (3GPP TS 37.105 version 15.7.0 Release 15)

The Telecommunications System LTE; Aina System (AAS) Base Station Transmission and reception 37.105 version 15.7.0 Rel



Reference

RTS/TSGR-0437105vF70

Keywords

LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and
of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	11
1 Scope	12
2 References	12
3 Definitions, symbols and abbreviations	13
3.1 Definitions.....	13
3.2 Symbols.....	18
3.3 Abbreviations	19
4 General	19
4.1 Relationship between the AAS BS specification and non-AAS BS single RAT & MSR specifications	19
4.2 Relationship between minimum requirements and test requirements	20
4.3 Conducted and radiated requirement reference points	21
4.4 Base station classes for AAS BS	22
4.5 Regional requirements.....	22
4.6 Operating Bands and Band Categories.....	24
4.7 Channel arrangements	24
4.8 Requirements for contiguous and non-contiguous spectrum.....	24
4.9 Requirements for AAS BS capable of operation in multiple operating bands	24
4.10 OTA Co-location with other base stations	25
5 Applicability of Requirements	26
5.1 General	26
5.2 Band category 1 (BC1) and band category 2 (BC2),.....	27
5.3 Band category 3 (BC3).....	30
6 Conducted transmitter characteristics	33
6.1 General	33
6.2 Base station output power	33
6.2.1 General.....	33
6.2.2 Maximum output power.....	34
6.2.2.1 General	34
6.2.2.2 Minimum requirement for MSR operation	34
6.2.2.2.1 General	34
6.2.2.2.2 Additional requirements (regional).....	34
6.2.2.3 Minimum requirement for single RAT UTRA operation.....	34
6.2.2.4 Minimum requirement for single RAT E-UTRA operation.....	34
6.2.2.4.1 General	34
6.2.2.4.2 Additional requirements (regional).....	34
6.2.3 UTRA FDD primary CPICH power	34
6.2.3.1 General	34
6.2.3.2 Minimum requirement for MSR operation	35
6.2.3.3 Minimum requirement for single RAT UTRA operation.....	35
6.2.3.4 Minimum requirement for single RAT E-UTRA operation.....	35
6.2.4 UTRA TDD primary CCPCH power.....	35
6.2.4.1 General	35
6.2.4.2 Minimum requirement for MSR operation	35
6.2.4.3 Minimum requirement for single RAT UTRA operation.....	35
6.2.4.4 Minimum requirement for single RAT E-UTRA operation.....	36
6.2.5 UTRA FDD additional CPICH power for MIMO mode	36
6.2.5.1 General	36
6.2.5.2 Minimum requirement for MSR operation	37
6.2.5.3 Minimum requirement for single RAT UTRA operation.....	37

6.2.5.4	Minimum requirement for single RAT E-UTRA operation.....	38
6.2.6	E-UTRA DL RS power.....	38
6.2.6.1	General.....	38
6.2.6.2	Minimum requirement for MSR operation	38
6.2.6.3	Minimum requirement for single RAT UTRA operation.....	38
6.2.6.4	Minimum requirement for single RAT E-UTRA operation.....	38
6.3	Output power dynamics.....	38
6.3.1	General.....	38
6.3.2	UTRA Inner loop power control in the downlink.....	39
6.3.2.1	General.....	39
6.3.2.2	Minimum requirement for MSR operation	39
6.3.2.3	Minimum requirement for single RAT UTRA operation.....	39
6.3.2.4	Minimum requirement for single RAT E-UTRA operation.....	39
6.3.3	Power control dynamic range	40
6.3.3.1	General.....	40
6.3.3.2	Minimum requirement for MSR operation	40
6.3.3.3	Minimum requirement for single RAT UTRA operation.....	40
6.3.3.4	Minimum requirement for single RAT E-UTRA operation.....	40
6.3.4	Total power dynamic range	40
6.3.4.1	General.....	40
6.3.4.2	Minimum requirement for MSR operation	40
6.3.4.3	Minimum requirement for single RAT UTRA operation.....	41
6.3.4.4	Minimum requirement for single RAT E-UTRA operation.....	41
6.3.5	IPDL time mask	41
6.3.5.1	General.....	41
6.3.5.2	Minimum requirement for MSR operation	41
6.3.5.3	Minimum requirement for single RAT UTRA operation.....	41
6.3.5.4	Minimum requirement for single RAT E-UTRA operation.....	41
6.3.6	RE Power control dynamic range	41
6.3.6.1	General.....	41
6.3.6.2	Minimum requirement for MSR operation	42
6.3.6.3	Minimum requirement for single RAT UTRA operation.....	42
6.3.6.4	Minimum requirement for single RAT E-UTRA operation.....	42
6.4	Transmit ON/OFF power	42
6.4.1	General.....	42
6.4.2	Transmitter OFF power	42
6.4.2.1	General.....	42
6.4.2.2	Minimum requirement for MSR operation	42
6.4.2.3	Minimum requirement for single RAT UTRA operation.....	42
6.4.2.4	Minimum requirement for single RAT E-UTRA operation.....	42
6.4.3	Transmitter transient period.....	43
6.4.3.1	General.....	43
6.4.3.2	Minimum requirement for MSR operation	43
6.4.3.3	Minimum requirement for single RAT UTRA operation.....	43
6.4.3.4	Minimum requirement for single RAT E-UTRA operation.....	43
6.5	Transmitted signal quality	43
6.5.1	General.....	43
6.5.2	Frequency Error	43
6.5.2.1	General	43
6.5.2.2	Minimum requirement for MSR operation	44
6.5.2.3	Minimum requirement for single RAT UTRA operation.....	44
6.5.2.4	Minimum requirement for single RAT E-UTRA operation.....	44
6.5.3	Time alignment error	44
6.5.3.1	General	44
6.5.3.2	Minimum requirement for MSR operation	45
6.5.3.3	Minimum requirement for single RAT UTRA operation.....	45
6.5.3.4	Minimum requirement for single RAT E-UTRA operation.....	45
6.5.4	Modulation quality.....	45
6.5.4.1	General	45
6.5.4.2	Minimum requirement for MSR operation	45
6.5.4.3	Minimum requirement for single RAT UTRA operation.....	45
6.5.4.4	Minimum requirement for single RAT E-UTRA operation.....	46

6.5.5	Transmit pulse shape filter.....	46
6.5.5.1	General	46
6.5.5.2	Void.....	47
6.5.5.3	Void.....	47
6.5.5.4	Void.....	47
6.6	Unwanted Emissions	47
6.6.1	General.....	47
6.6.2	Occupied bandwidth	47
6.6.2.1	General	47
6.6.2.2	Minimum requirement for MSR operation	48
6.6.2.3	Minimum requirement for single RAT UTRA operation.....	48
6.6.2.4	Minimum requirement for single RAT E-UTRA operation.....	48
6.6.3	Adjacent Channel Leakage power Ratio.....	48
6.6.3.1	General	48
6.6.3.2	Minimum requirement for MSR operation	48
6.6.3.3	Minimum requirement for single RAT UTRA operation.....	49
6.6.3.4	Minimum requirement for single RAT E-UTRA operation.....	49
6.6.4	Spectrum emission mask	49
6.6.4.1	General	49
6.6.4.2	Minimum requirement for MSR operation	49
6.6.4.3	Minimum requirement for single RAT UTRA operation.....	49
6.6.4.3.1	General	49
6.6.4.3.2	Basic limits for single RAT UTRA FDD operation	50
6.6.4.3.3	Basic limits for single RAT UTRA TDD 1,28Mcps operation	55
6.6.4.4	Minimum requirement for single RAT E-UTRA operation.....	57
6.6.5	Operating band unwanted emission	58
6.6.5.1	General	58
6.6.5.2	Minimum requirement for MSR operation.....	58
6.6.5.2.1	General	58
6.6.5.2.2	Basic limits for Band Categories 1 and 3.....	58
6.6.5.2.3	Basic limit for Band Category 2	64
6.6.5.2.4	Additional requirements	71
6.6.5.3	Minimum requirement for single RAT UTRA operation.....	71
6.6.5.4	Minimum requirement for single RAT E-UTRA operation.....	71
6.6.5.4.1	General	71
6.6.5.4.2	Basic limits for Wide Area BS (Category A)	73
6.6.5.4.3	Basic limits for Wide Area BS (Category B)	75
6.6.5.4.3.1	General.....	75
6.6.5.4.3.2	Category B requirements (Option 1).....	75
6.6.5.4.3.3	Category B (Option 2)	79
6.6.5.4.4	Basic limits for Local Area BS (Category A and B)	81
6.6.5.4.5	Basic limits for Medium Range BS (Category A and B).....	82
6.6.5.4.7	Additional requirements	84
6.6.6	Spurious emission	84
6.6.6.1	General	84
6.6.6.2	Minimum requirement for MSR operation	84
6.6.6.3	Minimum requirement for single RAT UTRA operation.....	85
6.6.6.4	Minimum requirement for single RAT E-UTRA operation.....	85
6.7	Transmitter intermodulation	85
6.7.1	General.....	85
6.7.2	Minimum requirement for MSR operation	86
6.7.2.1	General co-location minimum requirement.....	86
6.7.2.2	Additional co-location minimum requirement (BC1 and BC2)	87
6.7.2.3	Additional co-location minimum requirement (BC3)	87
6.7.2.4	Additional co-location minimum requirements.....	88
6.7.2.5	Intra-system minimum requirement	88
6.7.3	Minimum requirement for single RAT UTRA operation	88
6.7.3.1	General co-location minimum requirement for FDD UTRA	88
6.7.3.2	General co-location minimum requirement for 1,28 Mcps TDD UTRA	89
6.7.3.3	Intra-system minimum requirement	89
6.7.4	Minimum requirement for single RAT E-UTRA operation.....	90
6.7.4.1	General co-location minimum requirement.....	90

6.7.4.2	Additional requirement for Band 41	90
6.7.4.3	Intra-system minimum requirement	91
7	Conducted receiver characteristics	91
7.1	General	91
7.2	Reference sensitivity level.....	92
7.2.1	General.....	92
7.2.2	Minimum requirement for MSR operation	92
7.2.3	Minimum requirement for single RAT UTRA operation	92
7.2.4	Minimum requirement for single RAT E-UTRA operation.....	92
7.3	Dynamic range	93
7.3.1	General.....	93
7.3.2	Minimum requirement for MSR operation	93
7.3.3	Minimum requirement for single RAT UTRA operation	93
7.3.4	Minimum requirement for single RAT E-UTRA operation.....	93
7.4	Adjacent channel selectivity, general blocking, and narrowband blocking.....	94
7.4.1	General.....	94
7.4.2	Minimum requirement for MSR operation	94
7.4.2.1	General minimum requirement	94
7.4.2.2	General narrowband blocking minimum requirement	95
7.4.2.3	Additional BC3 blocking minimum requirement.....	96
7.4.3	Minimum requirement for single RAT UTRA operation	97
7.4.4	Minimum requirement for single RAT E-UTRA operation.....	97
7.5	Blocking	97
7.5.1	General.....	97
7.5.2	Minimum requirement for MSR operation	97
7.5.2.1	General minimum requirement	97
7.5.2.2	Co-location minimum requirement	98
7.5.3	Minimum requirement for single RAT UTRA operation	102
7.5.3.1	General minimum requirement	102
7.5.3.2	Co-location minimum requirement.....	103
7.5.4	Minimum requirement for single RAT E-UTRA operation.....	103
7.5.4.1	General minimum requirement	103
7.5.4.2	Co-location minimum requirement	107
7.6	Receiver spurious emissions.....	107
7.6.1	General.....	107
7.6.2	Minimum requirement for MSR operation	108
7.6.2.1	General minimum requirement	108
7.6.3	Minimum requirement for single RAT UTRA operation	108
7.6.4	Minimum requirement for single RAT E-UTRA operation.....	109
7.7	Receiver intermodulation	109
7.7.1	General.....	109
7.7.2	Minimum requirement for MSR operation	109
7.7.2.1	General intermodulation minimum requirement	109
7.7.2.2	General narrowband intermodulation minimum requirement	111
7.7.3	Minimum requirement for single RAT UTRA operation	115
7.7.4	Minimum requirement for single RAT E- UTRA operation.....	115
7.8	In-channel selectivity	115
7.8.1	General.....	115
7.8.2	Minimum requirement for MSR operation	115
7.8.3	Minimum requirement for single RAT UTRA operation	115
7.8.4	Minimum requirement for single RAT E-UTRA operation.....	116
8	Performance requirements.....	116
8.1	General	116
8.1.1	UTRA operation	116
8.1.2	E-UTRA operation.....	117
8.2	Minimum requirements for MSR operation	118
8.3	Minimum requirements for UTRA operation.....	118
8.4	Minimum requirements for E-UTRA operation.....	118
9	Radiated transmitter characteristics.....	118
9.1	General	118

9.2	Radiated transmit power.....	119
9.2.1	General.....	119
9.2.2	Minimum requirement for MSR operation	119
9.2.3	Minimum requirement for single RAT UTRA operation	119
9.2.4	Minimum requirement for single RAT E-UTRA operation.....	119
9.3	OTA Base Station output power.....	120
9.3.1	General.....	120
9.3.2	OTA Maximum output power	120
9.3.2.1	General	120
9.3.2.2	Minimum requirement for MSR operation	120
9.3.2.2.1	General	120
9.3.2.2.2	Additional requirements (regional).....	120
9.3.2.3	Minimum requirement for single RAT UTRA operation.....	120
9.3.2.4	Minimum requirement for single RAT E-UTRA operation.....	120
9.3.2.4.1	General	120
9.3.2.4.2	Additional requirements (regional).....	121
9.3.3	OTA E-UTRA DL RS power	121
9.3.3.1	General.....	121
9.3.3.2	Minimum requirement for MSR operation	121
9.3.3.3	Minimum requirement for single RAT UTRA operation.....	121
9.3.3.4	Minimum requirement for single RAT E-UTRA operation.....	121
9.4	OTA Output power dynamics	121
9.4.1	General.....	121
9.4.2	OTA UTRA Inner loop power control in the downlink.....	121
9.4.2.1	General	121
9.4.2.2	Minimum requirement for MSR operation	121
9.4.2.3	Minimum requirement for single RAT UTRA operation.....	122
9.4.2.4	Minimum requirement for single RAT E-UTRA operation.....	122
9.4.3	OTA Power control dynamic range	122
9.4.3.1	General	122
9.4.3.2	Minimum requirement for MSR operation	122
9.4.3.3	Minimum requirement for single RAT UTRA operation.....	122
9.4.3.4	Minimum requirement for single RAT E-UTRA operation.....	123
9.4.4	OTA Total power dynamic range	123
9.4.4.1	General	123
9.4.4.2	Minimum requirement for MSR operation	123
9.4.4.3	Minimum requirement for single RAT UTRA operation.....	123
9.4.4.4	Minimum requirement for single RAT E-UTRA operation.....	123
9.4.5	OTA IPDL time mask.....	124
9.4.5.1	General	124
9.4.5.2	Minimum requirement for MSR operation	124
9.4.5.3	Minimum requirement for single RAT UTRA operation.....	124
9.4.5.4	Minimum requirement for single RAT E-UTRA operation.....	124
9.4.6	OTA RE Power control dynamic range	124
9.4.6.1	General	124
9.4.6.2	Minimum requirement for MSR operation	125
9.4.6.3	Minimum requirement for single RAT UTRA operation.....	125
9.4.6.4	Minimum requirement for single RAT E-UTRA operation.....	125
9.5	OTA Transmit ON/OFF power	125
9.5.1	General.....	125
9.5.2	OTA Transmitter OFF power	125
9.5.2.1	General	125
9.5.2.2	Minimum requirement for MSR operation	126
9.5.2.3	Minimum requirement for single RAT UTRA operation.....	126
9.5.2.4	Minimum requirement for single RAT E-UTRA operation.....	126
9.5.3	OTA Transmitter transient period.....	126
9.5.3.1	General	126
9.5.3.2	Minimum requirement for MSR operation	126
9.5.3.3	Minimum requirement for single RAT UTRA operation.....	127
9.5.3.4	Minimum requirement for single RAT E-UTRA operation.....	127
9.6	OTA Transmitted signal quality.....	127
9.6.1	General.....	127

9.6.2	OTA Frequency Error	127
9.6.2.1	General	127
9.6.2.2	Minimum requirement for MSR operation	127
9.6.2.3	Minimum requirement for single RAT UTRA operation.....	127
9.6.2.4	Minimum requirement for single RAT E-UTRA operation.....	127
9.6.3	OTA Time alignment error	128
9.6.3.1	General	128
9.6.3.2	Minimum requirement for MSR operation	128
9.6.3.3	Minimum requirement for single RAT UTRA operation.....	128
9.6.3.4	Minimum requirement for single RAT E-UTRA operation.....	128
9.6.4	OTA Modulation quality	129
9.6.4.1	General	129
9.6.4.2	Minimum requirement for MSR operation	129
9.6.4.3	Minimum requirement for single RAT UTRA operation.....	129
9.6.4.4	Minimum requirement for single RAT E-UTRA operation.....	129
9.6.5	OTA Transmit pulse shape filter.....	129
9.6.5.1	General	129
9.7	OTA Unwanted Emissions	130
9.7.1	General.....	130
9.7.2	OTA occupied bandwidth	130
9.7.2.1	General	130
9.7.2.2	Minimum requirement for MSR operation	131
9.7.2.3	Minimum requirement for single RAT UTRA operation.....	131
9.7.2.4	Minimum requirement for single RAT E-UTRA operation.....	131
9.7.3	OTA Adjacent Channel Leakage power Ratio.....	131
9.7.3.1	General	131
9.7.3.2	Minimum requirement for MSR operation	131
9.7.3.3	Minimum requirement for single RAT UTRA operation.....	132
9.7.3.4	Minimum requirement for single RAT E-UTRA operation.....	132
9.7.4	OTA Spectrum emission mask	133
9.7.4.1	General	133
9.7.4.2	Minimum requirement for MSR operation	133
9.7.4.3	Minimum requirement for single RAT UTRA operation.....	133
9.7.4.3.1	General	133
9.7.4.3.2	Minimum requirements for single RAT UTRA FDD operation.....	133
9.7.4.4	Minimum requirement for single RAT E-UTRA operation.....	139
9.7.5	OTA Operating band unwanted emission	139
9.7.5.1	General	139
9.7.5.2	Minimum requirement for MSR operation	141
9.7.5.2.1	General	141
9.7.5.2.2	Minimum requirements for Band Categories 1 and 3.....	141
9.7.5.2.3	Minimum requirement for Band Category 2.....	145
9.7.5.2.4	Additional requirements	151
9.7.5.2.4.1	Limits in FCC Title 47.....	151
9.7.5.2.4.2	Unsynchronized operation for BC3	151
9.7.5.2.4.3	Protection of DTT	152
9.7.5.3	Minimum requirement for single RAT UTRA operation.....	152
9.7.5.4	Minimum requirement for single RAT E-UTRA operation.....	152
9.7.5.4.1	General	152
9.7.5.4.2	Minimum requirements for Wide Area BS (Category A)	153
9.7.5.4.3	Minimum requirements for Wide Area BS (Category B)	156
9.7.5.4.3.1	General	156
9.7.5.4.3.2	Category B requirements (Option 1).....	156
9.7.5.4.3.3	Category B requirements (Option 2).....	159
9.7.5.4.4	Minimum requirements for Local Area BS (Category A and B).....	161
9.7.5.4.5	Minimum requirements for Medium Range BS (Category A and B).....	163
9.7.5.4.6	Additional requirements	165
9.7.6	OTA Spurious emission.....	165
9.7.6.1	General	165
9.7.6.2	MSR operation	166
9.7.6.2.1	Minimum requirement for MSR operation.....	166
9.7.6.2.1.1	Minimum requirement (Category A)	166

9.7.6.2.1.2	Minimum requirement (Category B)	166
9.7.6.2.1.3	(void).....	166
9.7.6.2.2	Protection of the BS receiver of own or different BS	166
9.7.6.2.3	Additional spurious emissions requirements	166
9.7.6.2.4	Co-location with other base stations.....	167
9.7.6.3	Minimum requirement for single RAT UTRA operation.....	167
9.7.6.3.1	Mandatory Requirements	167
9.7.6.3.1.1	Minimum requirement (Category A)	167
9.7.6.3.1.2	Minimum requirement (Category B)	167
9.7.6.3.2	Protection of the BS receiver of own or different BS	168
9.7.6.3.3	Additional spurious emissions requirements	168
9.7.6.3.4	Co-location with other base stations.....	175
9.7.6.3.4.1	General.....	175
9.7.6.3.4.2	Minimum Requirement	175
9.7.6.4	Minimum requirement for single RAT E-UTRA operation.....	181
9.7.6.4.1	Mandatory Requirements	181
9.7.6.4.1.1	Minimum requirement (Category A)	181
9.7.6.4.1.2	Minimum Requirement (Category B)	181
9.7.6.4.2	Protection of the BS receiver of own or different BS	181
9.7.6.4.3	Additional spurious emissions requirements	181
9.7.6.4.3.1	General.....	181
9.7.6.4.3.2	Minimum Requirement	182
9.7.6.4.4	Co-location with other base stations.....	192
9.7.6.4.4.1	General.....	192
9.7.6.4.4.2	Minimum Requirement	192
9.8	OTA Transmitter intermodulation.....	198
9.8.1	General.....	198
9.8.2	Minimum requirement for MSR operation	198
9.8.2.1	General minimum requirement	198
9.8.2.2	Additional minimum requirement (BC1 and BC2)	199
9.8.2.3	Additional minimum requirement (BC3)	199
9.8.2.4	Additional minimum requirements	200
9.8.3	Minimum requirement for single RAT UTRA operation	200
9.8.3.1	General minimum requirement for FDD UTRA	200
9.8.4	Minimum requirement for single RAT E-UTRA operation.....	201
9.8.4.1	General minimum requirement	201
9.8.4.2	Additional requirement for Band 41	201
10	Radiated receiver characteristics.....	202
10.1	General	202
10.2	OTA sensitivity	202
10.2.1	General.....	202
10.2.2	Minimum requirement for MSR operation	203
10.2.3	Minimum requirement for single RAT UTRA operation	203
10.2.4	Minimum requirement for single RAT E-UTRA operation.....	203
10.3	OTA Reference sensitivity level	204
10.3.1	General.....	204
10.3.2	Minimum requirement for MSR operation	204
10.3.3	Minimum requirement for single RAT UTRA operation	204
10.3.4	Minimum requirement for single RAT E-UTRA operation.....	205
10.4	OTA Dynamic range	206
10.4.1	General	206
10.4.2	Minimum requirement for MSR operation	206
10.4.3	Minimum requirement for single RAT UTRA operation.....	206
10.4.4	Minimum requirement for single RAT E-UTRA operation.....	207
10.5	OTA Adjacent channel selectivity, general blocking, and narrowband blocking.....	209
10.5.1	General.....	209
10.5.2	Minimum requirement for MSR operation	210
10.5.2.1	General minimum requirement	210
10.5.2.2	General narrowband blocking minimum requirement	211
10.5.2.3	Additional BC3 blocking minimum requirement.....	212
10.5.3	Minimum requirement for single RAT UTRA operation	213

10.5.3.1	General	213
10.5.3.2	Minimum requirement	213
10.5.3.3	Minimum requirement - Co-location with UTRA-TDD	213
10.5.4	Minimum requirement for single RAT E-UTRA operation.....	214
10.5.4.1	General	214
10.5.4.2	Minimum requirement	214
10.6	OTA Blocking	216
10.6.1	General.....	216
10.6.2	Minimum requirement for MSR operation	216
10.6.2.1	General minimum requirement	216
10.6.2.2	Co-location minimum requirement	217
10.6.3	Minimum requirement for single RAT UTRA operation	221
10.6.3.1	General minimum requirement	221
10.6.3.2	Co-location minimum requirement	223
10.6.4	Minimum requirement for single RAT E-UTRA operation.....	227
10.6.4.1	General minimum requirement	227
10.6.4.2	Co-location minimum requirement	229
10.7	OTA Receiver spurious emissions	233
10.7.1	General.....	233
10.7.2	Minimum requirement for MSR operation	234
10.7.2.1	General minimum requirement	234
10.7.3	Minimum requirement for single RAT UTRA operation	234
10.7.4	Minimum requirement for single RAT E-UTRA operation.....	234
10.8	OTA Receiver intermodulation	235
10.8.1	General.....	235
10.8.2	Minimum requirement for MSR operation	235
10.8.2.1	General intermodulation minimum requirement	235
10.8.2.2	General narrowband intermodulation minimum requirement	237
10.8.3	Minimum requirement for single RAT UTRA operation	240
10.8.4	Minimum requirement for single RAT E-UTRA operation.....	241
10.9	OTA In-channel selectivity	245
10.9.1	General.....	245
10.9.2	Minimum requirement for MSR operation	245
10.9.3	Minimum requirement for single RAT UTRA operation	246
10.9.4	Minimum requirement for single RAT E-UTRA operation.....	246
11	Radiated performance requirements.....	247
11.1	General	247
11.1.1	OTA demodulation branches	247
11.1.2	UTRA operation	247
11.1.3	E-UTRA operation.....	248
11.2	Minimum requirements for MSR operation	249
11.3	Minimum requirements for UTRA operation.....	249
11.4	Minimum requirements for E-UTRA operation.....	249
Annex A (normative):	Environmental requirements for the BS equipment	250
Annex B (Informative):	Calculation of EIRP based on fixed assumption of passive antenna gain	251
B.1	Calculation of EIRP based on fixed assumption of passive antenna gain	251
Annex C (informative):	Change history	252
History		256

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP) Technical Specification Group (TSG) Radio Access Networks (RAN).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

iTeh STANDARD PREVIEW
(Standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/b0da8400-32c4-47b4-908b-90c7361a20f2/etsi-ts-137-105-v15.7.0-2019-10>

1 Scope

The present document establishes 2 sets of minimum requirements and minimum performance requirements; *hybrid requirements set* which specify requirements for a *hybrid AAS BS* with both a conducted and a radiated interface and *OTA requirements set* which specify requirements for an *OTA AAS BS* which has a radiated interface only.

The *hybrid AAS BS* requirements are specified for E-UTRA AAS Base Station (BS), the FDD mode of UTRA AAS Base Station (BS), the 1,28 Mcps TDD mode of UTRA AAS Base Station (BS) in single RAT and any MSR AAS Base Station (BS) implementation of these RATs (including NR BS type 1-H MSR configurations).

The *OTA AAS BS* requirements are specified for E-UTRA AAS Base Station (BS), the FDD mode of UTRA AAS Base Station (BS), in single RAT and any MSR AAS Base Station (BS) implementation of these RATs (including NR BS type 1-O MSR configurations).

The present document does not establish minimum RF characteristics or minimum performance requirements for Narrow-Band Internet of Things (NB-IoT) in band, NB-IoT guard band, or standalone NB-IoT operation, for AAS BS in *single RAT E-UTRA operation* or in *MSR operation* using E-UTRA.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 25.104: "Base Station (BS) radio transmission and reception (FDD)".
- [3] 3GPP TS 25.105: "Base Station (BS) radio transmission and reception (TDD)".
- [4] 3GPP TS 36.104: "Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) radio transmission and reception".
- [5] 3GPP TS 37.104: "NR, E-UTRA, UTRA and GSM/EDGE Multi-Standard Radio (MSR) Base Station (BS) radio transmission and reception".
- [6] 3GPP TS 25.104 (V14.2.0): "Base Station (BS) radio transmission and reception (FDD) (Release 14)".
- [7] 3GPP TS 25.105 (V14.0.0): "Base Station (BS) radio transmission and reception (TDD) (Release 14)".
- [8] 3GPP TS 36.104 (V14.4.0): "Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) radio transmission and reception (Release 14)".
- [9] 3GPP TS 37.104 (V14.4.0): "E-UTRA, UTRA and GSM/EDGE Multi-Standard Radio (MSR) Base Station (BS) radio transmission and reception (Release 14)".
- [10] 3GPP TS 25.142 (V14.0.0): "Base Station (BS) conformance testing (TDD) (Release 14)".
- [11] Recommendation ITU-R M.1545: "Measurement uncertainty as it applies to test limits for the terrestrial component of International Mobile Telecommunications-2000".
- [12] 3GPP TS 25.942: "Radio Frequency (RF) system scenarios".