

ETSI TS 138 101-2 V15.7.0 (2019-10)



**5G;
NR;**
User Equipment (UE) radio transmission and reception;
Part 2: Range 2 Standalone
(3GPP TS 38.101-2 version 15.7.0 Release 15)



ReferenceRTS/TSGR-0438101-2v70

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	10
1 Scope	11
2 References	11
3 Definitions, symbols and abbreviations	12
3.1 Definitions	12
3.2 Symbols.....	13
3.3 Abbreviations	15
4 General	16
4.1 Relationship between minimum requirements and test requirements	16
4.2 Applicability of minimum requirements	16
4.3 Specification suffix information.....	16
5 Operating bands and channel arrangement.....	17
5.1 General	17
5.2 Operating bands.....	17
5.2A Operating bands for CA	17
5.2A.1 Intra-band CA	17
5.2A.2 Void	18
5.2D Operating bands for UL MIMO	18
5.3 UE Channel bandwidth	19
5.3.1 General.....	19
5.3.2 Maximum transmission bandwidth configuration.....	19
5.3.3 Minimum guardband and transmission bandwidth configuration.....	20
5.3.4 RB alignment.....	21
5.3A UE channel bandwidth for CA	22
5.3A.1 General.....	22
5.3A.2 Minimum guardband and transmission bandwidth configuration for CA	22
5.3A.3 RB alignment with different numerologies for CA.....	23
5.3A.4 UE channel bandwidth per operating band for CA.....	23
5.3D Channel bandwidth for UL MIMO.....	24
5.4 Channel arrangement.....	24
5.4.1 Channel spacing.....	24
5.4.1.1 Channel spacing for adjacent NR carriers.....	24
5.4.2 Channel raster	25
5.4.2.1 NR-ARFCN and channel raster.....	25
5.4.2.2 Channel raster to resource element mapping.....	25
5.4.2.3 Channel raster entries for each operating band	26
5.4.3 Synchronization raster	26
5.4.3.1 Synchronization raster and numbering.....	26
5.4.3.2 Synchronization raster to synchronization block resource element mapping.....	26
5.4.3.3 Synchronization raster entries for each operating band.....	27
5.4A Channel arrangement for CA.....	27
5.4A.1 Channel spacing for CA.....	27
5.5 Configurations	28
5.5A Configurations for CA.....	28
5.5A.1 Configurations for intra-band contiguous CA.....	28
5.5A.2 Configurations for intra-band non-contiguous CA	29
5.5D Configurations for UL MIMO.....	32
6 Transmitter characteristics	33
6.1 General	33

6.2	Transmitter power	33
6.2.1	UE maximum output power	33
6.2.1.0	General	33
6.2.1.1	UE maximum output power for power class 1	33
6.2.1.2	UE maximum output power for power class 2	34
6.2.1.3	UE maximum output power for power class 3	35
6.2.1.4	UE maximum output power for power class 4	36
6.2.2	UE maximum output power reduction	37
6.2.2.1	UE maximum output power reduction for power class 1	37
6.2.2.2	UE maximum output power reduction for power class 2	38
6.2.2.3	UE maximum output power reduction for power class 3	38
6.2.2.4	UE maximum output power reduction for power class 4	39
6.2.3	UE maximum output power with additional requirements	39
6.2.3.1	General	39
6.2.3.2	A-MPR for NS_201	40
6.2.3.2.1	A-MPR for NS_201 for power class 1	40
6.2.3.2.2	A-MPR for NS_201 for power class 2	40
6.2.3.2.3	A-MPR for NS_201 for power class 3	41
6.2.3.2.4	A-MPR for NS_201 for power class 4	41
6.2.3.3	A-MPR for NS_202	41
6.2.3.3.1	A-MPR for NS_202 for power class 1	41
6.2.3.3.2	A-MPR for NS_202 for power class 2	41
6.2.3.3.3	A-MPR for NS_202 for power class 3	41
6.2.3.3.4	A-MPR for NS_202 for power class 4	41
6.2.4	Configured transmitted power	41
6.2A	Transmitter power for CA	42
6.2A.1	UE maximum output power for CA	42
6.2A.2	UE maximum output power reduction for CA	43
6.2A.2.1	General	43
6.2A.2.2	Maximum output power reduction for power class 1	43
6.2A.2.3	Maximum output power reduction for power class 2	44
6.2A.2.4	Maximum output power reduction for power class 3	44
6.2A.2.5	Maximum output power reduction for power class 4	45
6.2A.3	UE maximum output power with additional requirements for CA	45
6.2A.3.1	General	45
6.2A.3.2	A-MPR for CA_NS_201	46
6.2A.3.2.1	A-MPR for CA_NS_201 for power class 1	46
6.2A.3.2.2	A-MPR for CA_NS_201 for power class 2	46
6.2A.3.2.3	A-MPR for CA_NS_201 for power class 3	46
6.2A.3.2.4	A-MPR for CA_NS_201 for power class 4	47
6.2A.3.3	A-MPR for CA_NS_202	47
6.2A.3.3.1	A-MPR for CA_NS_202 for power class 1	47
6.2A.3.3.2	A-MPR for CA_NS_202 for power class 2	47
6.2A.3.3.3	A-MPR for CA_NS_202 for power class 3	47
6.2A.3.3.4	A-MPR for CA_NS_202 for power class 4	47
6.2A.4	Configured transmitted power for CA	47
6.2D	Transmitter power for UL MIMO	48
6.2D.1	UE maximum output power for UL MIMO	48
6.2D.1.1	UE maximum output power for UL MIMO for power class 1	48
6.2D.1.2	UE maximum output power for UL MIMO for power class 2	49
6.2D.1.3	UE maximum output power for UL MIMO for power class 3	50
6.2D.1.4	UE maximum output power for UL MIMO for power class 4	50
6.2D.2	UE maximum output power reduction for modulation / channel bandwidth for UL MIMO	51
6.2D.2.1	UE maximum output power reduction for modulation / channel bandwidth for UL MIMO for power class 1	51
6.2D.2.2	UE maximum output power reduction for modulation / channel bandwidth for UL MIMO for power class 2	52
6.2D.2.3	UE maximum output power reduction for modulation / channel bandwidth for UL MIMO for power class 3	52
6.2D.2.4	UE maximum output power reduction for modulation / channel bandwidth for UL MIMO for power class 4	52
6.2D.3	UE maximum output power reduction with additional requirements for UL MIMO	52

6.2D.3.1	UE maximum output power reduction with additional requirements for UL MIMO for power class 1	52
6.2D.3.2	UE maximum output power reduction with additional requirements for UL MIMO for power class 2	52
6.2D.3.3	UE maximum output power reduction with additional requirements for UL MIMO for power class 3	52
6.2D.3.4	UE maximum output power reduction with additional requirements for UL MIMO for power class 4	53
6.2D.4	Configured transmitted power for UL MIMO	53
6.3	Output power dynamics	53
6.3.1	Minimum output power	53
6.3.1.0	General	53
6.3.1.1	Minimum output power for power class 1	53
6.3.1.2	Minimum output power for power class 2, 3, and 4	53
6.3.2	Transmit OFF power	53
6.3.3	Transmit ON/OFF time mask	54
6.3.3.1	General	54
6.3.3.2	General ON/OFF time mask	54
6.3.3.3	Transmit power time mask for slot and short or long subslot boundaries	55
6.3.3.4	PRACH time mask	55
6.3.3.5	Void	56
6.3.3.6	SRS time mask	56
6.3.3.7	PUSCH-PUCCH and PUSCH-SRS time masks	57
6.3.3.8	Transmit power time mask for consecutive slot or long subslot transmission and short subslot transmission boundaries	57
6.3.3.9	Transmit power time mask for consecutive short subslot transmissions boundaries	58
6.3.4	Power control	59
6.3.4.1	General	59
6.3.4.2	Absolute power tolerance	59
6.3.4.3	Relative power tolerance	59
6.3.4.4	Aggregate power tolerance	60
6.3A	Output power dynamics for CA	60
6.3A.1	Minimum output power for CA	60
6.3A.1.0	General	60
6.3A.1.1	Minimum output power for power class 1	61
6.3A.1.2	Minimum output power for power class 2, 3, and 4	61
6.3A.2	Transmit OFF power for CA	61
6.3A.3	Transmit ON/OFF time mask for CA	61
6.3A.4	Power control for CA	62
6.3A.4.1	General	62
6.3D	Output power dynamics for UL MIMO	63
6.3D.1	Minimum output power for UL MIMO	63
6.3D.1.1	Minimum output power for UL MIMO for power class 1	63
6.3D.1.2	Minimum output power for UL MIMO for power class 2, 3 and 4	63
6.3D.2	Transmit OFF power for UL MIMO	63
6.3D.3	Transmit ON/OFF time mask for UL MIMO	63
6.4	Transmit signal quality	63
6.4.1	Frequency Error	63
6.4.2	Transmit modulation quality	63
6.4.2.0	General	63
6.4.2.1	Error vector magnitude	64
6.4.2.2	Carrier leakage	65
6.4.2.2.1	General	65
6.4.2.2.2	Carrier leakage for power class 1	65
6.4.2.2.3	Carrier leakage for power class 2	65
6.4.2.2.4	Carrier leakage for power class 3	65
6.4.2.2.5	Carrier leakage for power class 4	65
6.4.2.3	In-band emissions	66
6.4.2.3.1	General	66
6.4.2.3.2	In-band emissions for power class 1	66
6.4.2.3.3	In-band emissions for power class 2	66
6.4.2.3.4	In-band emissions for power class 3	67

6.4.2.3.5	In-band emissions for power class 4.....	68
6.4.2.4	EVM equalizer spectrum flatness	69
6.4.2.5	EVM spectral flatness for Pi/2 BPSK modulation	70
6.4A	Transmit signal quality for CA.....	71
6.4A.1	Frequency error.....	71
6.4A.2	Transmit modulation quality.....	71
6.4A.2.0	General	71
6.4A.2.1	Error Vector magnitude.....	72
6.4A.2.2	Carrier leakage	72
6.4A.2.2.1	General	72
6.4A.2.2.2	Carrier leakage for power class 1	72
6.4A.2.2.3	Carrier leakage for power class 2	72
6.4A.2.2.4	Carrier leakage for power class 3	72
6.4A.2.2.5	Carrier leakage for power class 4	72
6.4A.2.3	Inband emissions.....	73
6.4A.2.3.1	General	73
6.4A.2.3.2	Inband emissions for power class 1	73
6.4A.2.3.3	Inband emissions for power class 2	73
6.4A.2.3.4	Inband emissions for power class 3	74
6.4A.2.3.5	Inband emissions for power class 4	75
6.4A.2.4	EVM equalizer spectrum flatness	76
6.4D	Transmit signal quality for UL MIMO.....	76
6.4D.0	General.....	76
6.4D.1	Frequency error for UL MIMO.....	76
6.4D.2	Transmit modulation quality for UL MIMO.....	76
6.4D.3	Time alignment error for UL MIMO	76
6.4D.4	Requirements for coherent UL MIMO	76
6.5	Output RF spectrum emissions.....	77
6.5.1	Occupied bandwidth	77
6.5.2	Out of band emissions.....	77
6.5.2.0	General	77
6.5.2.1	Spectrum emission mask	78
6.5.2.2	Void.....	78
6.5.2.3	Adjacent channel leakage ratio	78
6.5.3	Spurious emissions	79
6.5.3.1	Spurious emission band UE co-existence	79
6.5.3.2	Additional spurious emissions	80
6.5.3.2.1	General	80
6.5.3.2.2	Additional spurious emission requirements for NS_201	80
6.5.3.2.3	Additional spurious emission requirements for NS_202	80
6.5A	Output RF spectrum emissions for CA.....	81
6.5A.1	Occupied bandwidth for CA	81
6.5A.2	Out of band emissions.....	81
6.5A.2.1	Spectrum emission mask for CA.....	81
6.5A.2.3	Adjacent channel leakage ratio for CA	81
6.5A.3	Spurious emissions for CA	81
6.5A.3.1	Spurious emission band UE co-existence for CA	82
6.5A.3.2	Additional spurious emissions	82
6.5A.3.2.1	General	82
6.5A.3.2.2	Additional spurious emission requirements for CA_NS_201	82
6.5A.3.2.3	Additional spurious emission requirements for CA_NS_202	83
6.5D	Output RF spectrum emissions for UL MIMO.....	83
6.5D.1	Occupied bandwidth for UL MIMO	83
6.5D.2	Out of band emissions for UL MIMO	83
6.5D.3	Spurious emissions for UL MIMO	83
6.6	Beam correspondence.....	83
6.6.1	General.....	83
6.6.2	(Void).....	83
6.6.3	(Void).....	83
6.6.4	Beam correspondence for power class 3.....	83
6.6.4.1	General	83
6.6.4.2	Beam correspondence tolerance for power class 3.....	84

6.6.5	(Void).....	84
6.6A	Beam correspondence for CA	84
7	Receiver characteristics	85
7.1	General	85
7.2	Diversity characteristics	85
7.3	Reference sensitivity	85
7.3.1	General.....	85
7.3.2	Reference sensitivity power level	85
7.3.2.1	Reference sensitivity power level for power class 1	85
7.3.2.2	Reference sensitivity power level for power class 2	86
7.3.2.3	Reference sensitivity power level for power class 3	86
7.3.2.4	Reference sensitivity power level for power class 4	87
7.3.3	Void	87
7.3.4	EIS spherical coverage.....	87
7.3.4.3	EIS spherical coverage for power class 3.....	88
7.3A	Reference sensitivity for CA	89
7.3A.1	General.....	89
7.3A.2	Reference sensitivity power level for CA	89
7.3A.2.1	Intra-band contiguous CA	89
7.3D	Reference sensitivity for UL MIMO	90
7.4	Maximum input level	90
7.4A	Maximum input level for CA	90
7.4D	Maximum input level for UL MIMO	91
7.5	Adjacent channel selectivity	91
7.5A	Adjacent channel selectivity for CA.....	92
7.5D	Adjacent channel selectivity for UL MIMO.....	94
7.6	Blocking characteristics	94
7.6.1	General.....	94
7.6.2	In-band blocking.....	94
7.6.3	Void	95
7.6A	Blocking characteristics for CA	95
7.6A.1	General.....	95
7.6A.2	In-band blocking.....	95
7.6D	Blocking characteristics for UL MIMO	97
7.7	Void.....	97
7.8	Void.....	97
7.9	Spurious emissions	97
7.10	Void.....	97
Annex A (normative):	Measurement channels.....	98
A.1	General	98
A.2	UL reference measurement channels	98
A.2.1	General	98
A.2.2	Void.....	98
A.2.3	Reference measurement channels for TDD.....	99
A.2.3.1	DFT-s-OFDM Pi/2-BPSK	100
A.2.3.2	DFT-s-OFDM QPSK.....	102
A.2.3.3	DFT-s-OFDM 16QAM.....	104
A.2.3.4	DFT-s-OFDM 64QAM.....	106
A.2.3.5	CP-OFDM QPSK	108
A.2.3.6	CP-OFDM 16QAM	110
A.2.3.7	CP-OFDM 64QAM	112
A.3	DL reference measurement channels	114
A.3.1	General	114
A.3.2	Void.....	116
A.3.3	DL reference measurement channels for TDD.....	116
A.3.3.1	General	116
A.3.3.2	FRC for receiver requirements for QPSK	117
A.3.3.3	FRC for receiver requirements for 16QAM.....	118

A.3.3.4	FRC for receiver requirements for 64QAM	119
A.4	Void	121
A.5	OFDMA Channel Noise Generator (OCNG)	121
A.5.1	OCNG Patterns for FDD	121
A.5.2	OCNG Patterns for TDD	121
A.5.2.1	OCNG TDD pattern 1: Generic OCNG TDD Pattern for all unused REs	121
Annex B (informative):	Void	122
Annex C (normative):	Downlink physical channels	123
C.1	General	123
C.2	Setup	123
C.3	Connection	123
C.3.1	Measurement of Receiver Characteristics	123
Annex D (normative):	Characteristics of the interfering signal	124
D.1	General	124
D.2	Interference signals	124
Annex E (normative):	Environmental conditions	125
E.1	General	125
E.2	Environmental	125
E.2.1	Temperature	125
E.2.2	Voltage	125
E.2.3	Void	126
Annex F (normative):	Transmit modulation	127
F.1	Measurement Point	127
F.2	Basic Error Vector Magnitude measurement	127
F.3	Basic in-band emissions measurement	127
F.4	Modified signal under test	128
F.5	Window length	130
F.5.1	Timing offset	130
F.5.2	Window length	130
F.5.3	Window length for normal CP	130
F.5.4	Window length for Extended CP	131
F.5.5	Window length for PRACH	131
F.6	Averaged EVM	132
F.7	Spectrum Flatness	133
Annex G (informative):	Void	134
Annex H (informative):	Void	134
Annex I (informative):	Void	134
Annex J (normative):	UE coordinate system	135
J.1	Reference coordinate system	135
J.2	Test conditions and angle definitions	136
J.3	DUT positioning guidelines	140
Annex K (informative):	Void	142

Annex L (informative): Change history143
History151

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/8c5d4dea-038b-4a91-842e-92db270f63d/etsi-ts-138-101-2-v15.7.0-2019-10>

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/8c5d44dea-038b-4a91-842e-92db2f70f63d/etsi-ts-138-101-2-v15.7.0-2019-10>

1 Scope

The present document establishes the minimum RF requirements for NR User Equipment (UE) operating on frequency Range 2.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 38.101-1: "NR; User Equipment (UE) radio transmission and reception; Part 1: Range 1 Standalone"
- [3] 3GPP TS 38.101-3: "NR; User Equipment (UE) radio transmission and reception; Part 3: Range 1 and Range 2 Interworking operation with other radios"
- [4] Void
- [5] 3GPP TS 38.521-2: "NR; User Equipment (UE) conformance specification; Radio transmission and reception; Part 2: Range 2 Standalone"
- [6] Recommendation ITU-R M.1545: "Measurement uncertainty as it applies to test limits for the terrestrial component of International Mobile Telecommunications-2000"
- [7] ITU-R Recommendation SM.329-10, "Unwanted emissions in the spurious domain"
- [8] 47 CFR Part 30, "UPPER MICROWAVE FLEXIBLE USE SERVICE, §30.202 Power limits", FCC.
- [9] 3GPP TS 38.211: "NR; Physical channels and modulation".
- [10] 3GPP TS 38.213: "NR; Physical layer procedures for control".
- [11] 3GPP TS 38.215: "NR; Physical layer measurements".
- [12] 3GPP TS 38.133: "NR; Requirements for support of radio resource management".
- [13] 3GPP TS 38.331: "NR; Radio Resource Control (RRC); Protocol specification".
- [14] 3GPP TS 38.306: "NR; User Equipment (UE) radio access capabilities".
- [15] IEEE Std 149: "IEEE Standard Test Procedures for Antennas", IEEE.

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

Aggregated Channel Bandwidth: The RF bandwidth in which a UE transmits and receives multiple contiguously aggregated carriers.

Beam correspondence: the ability of the UE to select a suitable beam for UL transmission based on DL measurements with or without relying on UL beam sweeping.

Carrier aggregation: Aggregation of two or more component carriers in order to support wider transmission bandwidths.

Carrier aggregation band: A set of one or more operating bands across which multiple carriers are aggregated with a specific set of technical requirements.

Carrier aggregation bandwidth class: A class defined by the aggregated transmission bandwidth configuration and maximum number of component carriers supported by a UE.

Carrier aggregation configuration: A combination of CA operating band(s) and CA bandwidth class(es) supported by a UE.

NOTE: Carriers aggregated in each band can be contiguous or non-contiguous.

EIRP(Link=Link angle, Meas=Link angle): measurement of the UE such that the link angle is aligned with the measurement angle. EIRP (indicator to be measured) can be replaced by EIS, Frequency, EVM, carrier Leakage, In-band emission and OBW. Beam peak search grids, TX beam peak direction, and RX beam peak direction can be selected to describe Link.

EIRP(Link=Link angle, Meas=beam peak direction): measurement of the EIRP of the UE such that the measurement angle is aligned with the beam peak direction within an acceptable measurement error uncertainty.

EIS (equivalent isotropic sensitivity): sensitivity for an isotropic directivity device equivalent to the sensitivity of the discussed device exposed to an incoming wave from a defined AoA

NOTE 1: The sensitivity is the minimum received power level at which specific requirement is met.

NOTE 2: Isotropic directivity is equal in all directions (i.e. 0 dBi).

Fallback group: Group of carrier aggregation bandwidth classes for which it is mandatory for a UE to be able to fallback to lower order CA bandwidth class configuration. It is not mandatory for a UE to be able to fallback to lower order CA bandwidth class configuration that belong to a different fallback group

Inter-band carrier aggregation: Carrier aggregation of component carriers in different operating bands.

NOTE: Carriers aggregated in each band can be contiguous or non-contiguous.

Intra-band contiguous carrier aggregation: Contiguous carriers aggregated in the same operating band.

Intra-band non-contiguous carrier aggregation: Non-contiguous carriers aggregated in the same operating band.

Link angle: a DL-signal AoA from the view point of the UE, as described in Annex J.

Measurement angle: the angle of measurement of the desired metric from the view point of the UE, as described in Annex J

radiated interface boundary: operating band specific radiated requirements reference point where the radiated requirements apply