

ETSI TS 138 101-1 V15.7.0 (2019-10)



**5G;
NR;**
User Equipment (UE) radio transmission and reception;
Part 1: Range 1 Standalone
(3GPP TS 38.101-1 version 15.7.0 Release 15)

Redacted Standard Review
<https://standards.itea.eu/documents/sist/9a62496-7442-4728-a788-b3497a81ad0c941ts/38-101-1-v15.7.0-2019-10>



Reference

RTS/TSGR-0438101-1vf70

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and

of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and
of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	11
1 Scope	12
2 References	12
3 Definitions, symbols and abbreviations	12
3.1 Definitions.....	12
3.2 Symbols.....	13
3.3 Abbreviations	15
4 General	16
4.1 Relationship between minimum requirements and test requirements	16
4.2 Applicability of minimum requirements	16
4.3 Specification suffix information.....	16
5 Operating bands and channel arrangement.....	17
5.1 General	17
5.2 Operating bands.....	17
5.2A Operating bands for CA	18
5.2A.1 Intra-band CA	18
5.2A.2 Inter-band CA	19
5.2B Void.....	19
5.2C Operating band combination for SU.....	19
5.3 UE channel bandwidth	20
5.3.1 General.....	20
5.3.2 Maximum transmission bandwidth configuration	20
5.3.3 Minimum guardband and transmission bandwidth configuration.....	21
5.3.4 RB alignment	22
5.3.5 UE channel bandwidth per operating band	22
5.3.6 Asymmetric channel bandwidths.....	24
5.3A UE channel bandwidth for CA	24
5.3A.1 General.....	24
5.3A.2 Maximum transmission bandwidth configuration for CA	24
5.3A.3 Minimum guardband and transmission bandwidth configuration for CA	25
5.3A.4 Void	26
5.3A.5 UE channel bandwidth per operating band for CA.....	26
5.4 Channel arrangement.....	27
5.4.1 Channel spacing	27
5.4.1.1 Channel spacing for adjacent NR carriers	27
5.4.2 Channel raster	27
5.4.2.1 NR-ARFCN and channel raster.....	27
5.4.2.2 Channel raster to resource element mapping.....	28
5.4.2.3 Channel raster entries for each operating band	28
5.4.3 Synchronization raster	29
5.4.3.1 Synchronization raster and numbering	29
5.4.3.2 Synchronization raster to synchronization block resource element mapping.....	30
5.4.3.3 Synchronization raster entries for each operating band	30
5.4.4 TX-RX frequency separation	31
5.4A Channel arrangement for CA.....	32
5.4A.1 Channel spacing for CA.....	32
5.4A.2 Channel raster for CA	32
5.4A.3 Synchronization raster for CA	32
5.4A.4 Tx-Rx frequency separation for CA.....	32
5.5 Void.....	33

5.5A	Configurations for CA	33
5.5A.1	Configurations for intra-band contiguous CA	33
5.5A.2	Void	34
5.5A.3	Configurations for inter-band CA	34
5.5B	Void.....	37
5.5C	Configurations for SUL.....	37
6	Transmitter characteristics	38
6.1	General	38
6.2	Transmitter power	38
6.2.1	UE maximum output power.....	38
6.2.2	UE maximum output power reduction.....	39
6.2.3	UE additional maximum output power reduction.....	40
6.2.3.1	General	40
6.2.3.2	A-MPR for NS_04	44
6.2.3.3	A-MPR for NS_10	45
6.2.3.4	A-MPR for NS_05 and NS_05U.....	46
6.2.3.5	A-MPR for NS_40	49
6.2.3.6	A-MPR for NS_43 and NS_43U.....	49
6.2.3.7	A-MPR for NS_03 and NS_03U.....	50
6.2.3.8	A-MPR for NS_37	50
6.2.3.9	A-MPR for NS_38	51
6.2.3.10	A-MPR for NS_39	51
6.2.3.11	A-MPR for NS_41	52
6.2.3.12	A-MPR for NS_42	53
6.2.3.13	A-MPR for NS_18	53
6.2.4	Configured transmitted power	53
6.2A	Transmitter power for CA	55
6.2A.1	UE maximum output power for CA	55
6.2A.1.1	Void.....	55
6.2A.1.2	Void.....	55
6.2A.1.3	UE maximum output power for Inter-band CA	55
6.2A.2	UE maximum output power reduction for CA	56
6.2A.2.1	Void.....	56
6.2A.2.2	Void.....	56
6.2A.2.3	UE maximum output power reduction for Inter-band CA	56
6.2A.3	UE additional maximum output power reduction for CA	56
6.2A.3.1.1	Void.....	56
6.2A.3.1.2	Void.....	56
6.2A.3.1.3	UE additional maximum output power reduction for Inter-band CA	56
6.2A.4	Configured output power for CA	56
6.2A.4.1	Configured transmitted power level	56
6.2A.4.1.1	Void.....	56
6.2A.4.1.2	Void.....	56
6.2A.4.1.3	Configured transmitted power for Inter-band CA	56
6.2A.4.2	$\Delta T_{IB,c}$ for CA	58
6.2A.4.2.1	Void.....	58
6.2A.4.2.2	Void.....	58
6.2A.4.2.3	$\Delta T_{IB,c}$ for Inter-band CA.....	58
6.2B	Void.....	59
6.2C	Transmitter power for SUL	59
6.2C.1	Configured transmitted power for SUL	59
6.2C.2	$\Delta T_{IB,c}$	59
6.2D	Transmitter power for UL MIMO	60
6.2D.1	UE maximum output power for UL MIMO.....	60
6.2D.2	UE maximum output power reduction for UL MIMO.....	60
6.2D.3	UE additional maximum output power reduction for UL MIMO.....	61
6.2D.4	Configured transmitted power for UL MIMO	61
6.3	Output power dynamics.....	61
6.3.1	Minimum output power	61
6.3.2	Transmit OFF power.....	62
6.3.3	Transmit ON/OFF time mask	62

6.3.3.1	General	62
6.3.3.2	General ON/OFF time mask	63
6.3.3.3	Transmit power time mask for slot and short or long subslot boundaries	63
6.3.3.4	PRACH time mask	63
6.3.3.5	Void	64
6.3.3.6	SRS time mask	64
6.3.3.7	PUSCH-PUCCH and PUSCH-SRS time masks	66
6.3.3.8	Transmit power time mask for consecutive slot or long subslot transmission and short subslot transmission boundaries	67
6.3.3.9	Transmit power time mask for consecutive short subslot transmissions boundaries	67
6.3.4	Power control	68
6.3.4.1	General	68
6.3.4.2	Absolute power tolerance	68
6.3.4.3	Relative power tolerance	68
6.3.4.4	Aggregate power tolerance	69
6.3A	Output power dynamics for CA	69
6.3A.1	Minimum output power for CA	69
6.3A.1.1	Void	69
6.3A.1.2	Void	69
6.3A.1.3	Minimum output power for inter-band CA	69
6.3A.2	Transmit OFF power for CA	70
6.3A.2.1	Void	70
6.3A.2.2	Void	70
6.3A.2.3	Transmit OFF power for inter-band CA	70
6.3A.3	Transmit ON/OFF time mask for CA	70
6.3A.3.1	Void	70
6.3A.3.2	Void	70
6.3A.3.3	Transmit ON/OFF time mask for inter-band CA	70
6.3A.4	Power control for CA	70
6.3A.4.1	Void	70
6.3A.4.2	Void	70
6.3A.4.3	Power control for inter-band CA	70
6.3D	Output power dynamics for UL MIMO	70
6.3D.1	Minimum output power for UL MIMO	70
6.3D.2	Transmit OFF power for UL MIMO	70
6.3D.3	Transmit ON/OFF time mask for UL MIMO	71
6.3D.4	Power control for UL MIMO	71
6.4	Transmit signal quality	71
6.4.1	Frequency error	71
6.4.2	Transmit modulation quality	71
6.4.2.1	Error Vector Magnitude	71
6.4.2.2	Carrier leakage	72
6.4.2.3	In-band emissions	72
6.4.2.4	EVM equalizer spectrum flatness	73
6.4.2.4.1	Requirements for Pi/2 BPSK modulation	74
6.4A	Transmit signal quality for CA	75
6.4A.1	Frequency error for CA	75
6.4A.1.1	Void	75
6.4A.1.2	Void	75
6.4A.1.3	Frequency error for inter-band CA	75
6.4A.2	Transmit modulation quality for CA	76
6.4A.2.1	Void	76
6.4A.2.2	Void	76
6.4A.2.3	Transmit modulation quality for inter-band CA	76
6.4D	Transmit signal quality for UL MIMO	76
6.4D.1	Frequency error for UL MIMO	76
6.4D.2	Transmit modulation quality for UL MIMO	76
6.4D.2.1	Error Vector Magnitude	76
6.4D.2.2	Carrier leakage	76
6.4D.2.3	In-band emissions	76
6.4D.2.4	EVM equalizer spectrum flatness for UL MIMO	77
6.4D.3	Time alignment error for UL MIMO	77

6.4D.4	Requirements for coherent UL MIMO	77
6.5	Output RF spectrum emissions.....	77
6.5.1	Occupied bandwidth	77
6.5.2	Out of band emission	78
6.5.2.1	General	78
6.5.2.2	Spectrum emission mask.....	78
6.5.2.3	Additional spectrum emission mask	79
6.5.2.3.1	Requirements for network signalled value "NS_35"	79
6.5.2.3.2	Requirements for network signalled value "NS_04"	80
6.5.2.3.3	Requirements for network signalled value "NS_03"	80
6.5.2.3.4	Requirements for network signalled value "NS_06"	81
6.5.2.3.5	Void.....	82
6.5.2.3.6	Void.....	82
6.5.2.3.7	Void.....	82
6.5.2.4	Adjacent channel leakage ratio	82
6.5.2.4.1	NR ACLR.....	82
6.5.2.4.2	UTRA ACLR	82
6.5.3	Spurious emissions	83
6.5.3.1	General spurious emissions	83
6.5.3.2	Spurious emissions for UE co-existence	84
6.5.3.3	Additional spurious emissions	88
6.5.3.3.1	Requirement for network signalled value "NS_04".....	88
6.5.3.3.2	Requirement for network signalled value "NS_17".....	88
6.5.3.3.3	Requirement for network signalled value "NS_18".....	89
6.5.3.3.4	Requirement for network signalled value "NS_05".....	89
6.5.3.3.5	Requirement for network signalled value "NS_43".....	89
6.5.3.3.6	Requirement for network signalled value "NS_37".....	89
6.5.3.3.7	Requirement for network signalled value "NS_38".....	90
6.5.3.3.8	Requirement for network signalled value "NS_39".....	90
6.5.3.3.9	Requirement for network signalled value "NS_40".....	90
6.5.3.3.10	Requirement for network signalled value "NS_41".....	90
6.5.3.3.11	Requirement for network signalled value "NS_42".....	91
6.5.4	Transmit intermodulation.....	91
6.5A	Output RF spectrum emissions for CA.....	91
6.5A.1	Occupied bandwidth for CA	92
6.5A.1.1	Void.....	92
6.5A.1.2	Void.....	92
6.5A.1.3	Occupied bandwidth for Inter-band CA	92
6.5A.2	Out of band emission for CA	92
6.5A.2.1	General	92
6.5A.2.2	Spectrum emission mask	92
6.5A.2.2.1	Void.....	92
6.5A.2.2.2	Void.....	92
6.5A.2.2.3	Spectrum emission mask for Inter-band CA.....	92
6.5A.2.3	Additional spectrum emission mask	93
6.5A.2.3.1	Void.....	93
6.5A.2.3.2	Void.....	93
6.5A.2.3.3	Additional spectrum emission mask for Inter-band CA	93
6.5A.2.4	Adjacent channel leakage ratio	93
6.5A.2.4.1	NR ACLR.....	93
6.5A.2.4.1.1	Void	93
6.5A.2.4.1.2	Void	93
6.5A.2.4.1.3	NR ACLR for Inter-band CA.....	93
6.5A.2.4.2	UTRA ACLR	93
6.5A.2.4.2.1	Void	93
6.5A.2.4.2.2	Void	93
6.5A.2.4.2.3	UTRA ACLR for Inter-band CA	93
6.5A.3	Spurious emission for CA.....	93
6.5A.3.1	General spurious emissions	93
6.5A.3.2	Spurious emissions for UE co-existence	94
6.5A.3.2.1	Void.....	94
6.5A.3.2.2	Void.....	94

6.5A.3.2.3	Spurious emissions for UE co-existence for Inter-band CA.....	94
6.5A.4	Transmit intermodulation for CA	95
6.5A.4.1	Void.....	95
6.5A.4.2	Void.....	95
6.5A.4.3	Transmit intermodulation for Inter-band CA	95
6.5D	Output RF spectrum emissions for UL MIMO.....	95
6.5D.1	Occupied bandwidth for UL MIMO	95
6.5D.2	Out of band emission for UL MIMO	95
6.5D.3	Spurious emission for UL MIMO.....	95
6.5D.4	Transmit intermodulation for UL MIMO	95
7	Receiver characteristics.....	96
7.1	General	96
7.2	Diversity characteristics	96
7.3	Reference sensitivity	96
7.3.1	General.....	96
7.3.2	Reference sensitivity power level	96
7.3.3	$\Delta R_{IB,c}$	102
7.3A	Reference sensitivity for CA	102
7.3A.1	General.....	102
7.3A.2	Reference sensitivity power level for CA	102
7.3A.2.1	Reference sensitivity power level for Intra-band contiguous CA	102
7.3A.2.2	Void.....	102
7.3A.2.3	Reference sensitivity power level for Inter-band CA.....	102
7.3A.2.4	Reference sensitivity power level for SDL bands	103
7.3A.3	$\Delta R_{IB,c}$ for CA	105
7.3A.3.1	General.....	105
7.3A.3.2	$\Delta R_{IB,c}$ for Inter-band CA.....	105
7.3A.3.2.1	$\Delta R_{IB,c}$ for two bands	105
7.3A.3.2.2	Void.....	105
7.3A.4	Reference sensitivity exceptions due to UL harmonic interference for CA.....	105
7.3A.5	Reference sensitivity exceptions due to intermodulation interference due to 2UL CA	108
7.3A.6	Reference sensitivity exceptions due to cross band isolation for CA	108
7.3B	Void.....	109
7.3C	Reference sensitivity for SUL	109
7.3C.1	General.....	109
7.3C.2	Reference sensitivity power level for SUL	109
7.3C.3	$\Delta R_{IB,c}$ for SUL	111
7.3C.3.1	General.....	111
7.3C.3.2	SUL band combination	111
7.3C.3.2.1	$\Delta R_{IB,c}$ for two bands	111
7.3D	Reference sensitivity for UL MIMO	111
7.4	Maximum input level	111
7.4A	Maximum input level for CA	112
7.4A.1	Maximum input level for Intra-band contiguous CA.....	112
7.4A.2	Void	112
7.4A.3	Maximum input level for Inter-band CA	112
7.4D	Maximum input level for UL MIMO	113
7.5A	Adjacent channel selectivity for CA.....	117
7.5A.1	Adjacent channel selectivity for Intra-band contiguous CA	117
7.5A.2	Void	119
7.5A.3	Adjacent channel selectivity Inter-band CA	119
7.5D	Adjacent channel selectivity for UL MIMO.....	119
7.6	Blocking characteristics	119
7.6.1	General.....	119
7.6.2	In-band blocking	119
7.6.3	Out-of-band blocking.....	121
7.6.4	Narrow band blocking	124
7.6A	Blocking characteristics for CA	125
7.6A.1	General.....	125
7.6A.2	In-band blocking for CA	125
7.6A.2.1	In-band blocking for Intra-band contiguous CA.....	125

7.6A.2.2	Void.....	126
7.6A.2.3	In-band blocking for Inter-band CA.....	126
7.6A.3	Out-of-band blocking for CA.....	126
7.6A.3.1	Out-of-band blocking for Intra-band contiguous CA.....	126
7.6A.3.2	Void.....	127
7.6A.3.3	Out-of-band blocking for Inter-band CA	127
7.6A.4	Narrow band blocking for CA	128
7.6A.4.1	Narrow band blocking for Intra-band contiguous CA.....	128
7.6A.4.2	Void.....	129
7.6A.4.3	Narrow band blocking for Inter-band CA.....	129
7.6C	Blocking characteristics for SUL	129
7.6C.1	General.....	129
7.6C.2	In-band blocking for SUL.....	129
7.6C.3	Out-of-band blocking for SUL.....	129
7.6C.4	Narrow band blocking for SUL	130
7.6D	Blocking characteristics for UL MIMO	130
7.7	Spurious response.....	130
7.7A	Spurious response for CA.....	132
7.7A.1	Spurious response for Intra-band contiguous CA	132
7.7A.2	Void	132
7.7A.3	Spurious response for Inter-band CA.....	132
7.7D	Spurious response for UL MIMO.....	132
7.8	Intermodulation characteristics	132
7.8.1	General.....	132
7.8.2	Wide band Intermodulation	133
7.8A	Intermodulation characteristics for CA	135
7.8A.1	General.....	135
7.8A.2	Wide band intermodulation for CA	135
7.8A.2.1	Wide band intermodulation for Intra-band contiguous CA.....	135
7.8A.2.2	Void.....	136
7.8A.2.3	Wide band intermodulation for Inter-band CA	136
7.8D	Intermodulation characteristics for UL MIMO.....	136
7.9	Spurious emissions	136
7.9A	Spurious emissions for CA	137
7.9A.1	Void	137
7.9A.2	Void	137
7.9A.3	Spurious emissions for Inter-band CA.....	137

Annex A (normative): Measurement channels.....138

A.1	General	138
A.2	UL reference measurement channels	138
A.2.1	General	138
A.2.2	Reference measurement channels for FDD	139
A.2.2.1	DFT-s-OFDM Pi/2-BPSK	139
A.2.2.2	DFT-s-OFDM QPSK.....	142
A.2.2.3	DFT-s-OFDM 16QAM.....	145
A.2.2.4	DFT-s-OFDM 64QAM.....	148
A.2.2.5	DFT-s-OFDM 256QAM.....	151
A.2.2.6	CP-OFDM QPSK	154
A.2.2.7	CP-OFDM 16QAM	157
A.2.2.8	CP-OFDM 64QAM	160
A.2.2.9	CP-OFDM 256QAM	163
A.2.3	Reference measurement channels for TDD.....	166
A.2.3.1	DFT-s-OFDM Pi/2-BPSK	166
A.2.3.2	DFT-s-OFDM QPSK.....	169
A.2.3.3	DFT-s-OFDM 16QAM.....	172
A.2.3.4	DFT-s-OFDM 64QAM.....	175
A.2.3.5	DFT-s-OFDM 256QAM.....	178
A.2.3.6	CP-OFDM QPSK	181
A.2.3.7	CP-OFDM 16QAM	184
A.2.3.8	CP-OFDM 64QAM	187

A.2.3.9	CP-OFDM 256QAM	190
A.3	DL reference measurement channels	193
A.3.1	General	193
A.3.2	DL reference measurement channels for FDD	194
A.3.2.1	General.....	194
A.3.2.2	FRC for receiver requirements for QPSK.....	194
A.3.2.3	FRC for maximum input level for 64QAM	197
A.3.2.4	FRC for maximum input level for 256 QAM	200
A.3.3	DL reference measurement channels for TDD	203
A.3.3.1	General.....	203
A.3.3.2	FRC for receiver requirements for QPSK.....	204
A.3.3.3	FRC for maximum input level for 64QAM	207
A.3.3.4	FRC for maximum input level for 256 QAM	210
A.4	CSI reference measurement channels.....	213
A.5	OFDMA Channel Noise Generator (OCNG)	213
A.5.1	OCNG Patterns for FDD	213
A.5.1.1	OCNG FDD pattern 1: Generic OCNG FDD Pattern for all unused REs.....	213
A.5.2	OCNG Patterns for TDD.....	213
A.5.2.1	OCNG TDD pattern 1: Generic OCNG TDD Pattern for all unused REs	213
A.6	Void.....	214
Annex B (informative):	Void	215
Annex C (informative):	Downlink physical channels.....	216
C.1	General	216
C.2	Setup.....	216
C.3	Connection	216
C.3.1	Measurement of Receiver Characteristics	216
Annex D (normative):	Characteristics of the interfering signal	218
D.1	General	218
D.2	Interference signals.....	218
Annex E (normative):	Environmental conditions	220
E.1	General	220
E.2	Environmental	220
E.2.1	Temperature	220
E.2.2	Voltage	220
E.2.3	Vibration.....	221
Annex F (normative):	Transmit modulation.....	222
F.0	General	222
F.1	Measurement Point.....	222
F.2	Basic Error Vector Magnitude measurement	222
F.3	Basic in-band emissions measurement.....	223
F.4	Modified signal under test.....	223
F.5	Window length	225
F.5.1	Timing offset	225
F.5.2	Window length	225
F.5.3	Window length for normal CP	225
F.5.4	Window length for Extended CP.....	227
F.5.5	Window length for PRACH	227

F.6	Averaged EVM	228
F.7	Spectrum Flatness	229
Annex G (informative):	Void	230
Annex H (informative):	Void	230
Annex I (informative):	Void	230
Annex J (informative):	Void	230
Annex K (informative):	Void	230
Annex L (informative):	Change history	231
History		241

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/9a62496-7442-4728-a788-b3497a81ad0c/etsi-ts-138-101-1-v15.7.0-2019-10>

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/9a62496-7442/4728-a788-b3497a81ad0c/etsi-ts-138-101-1-v15.7.0-2019-10>

1 Scope

The present document establishes the minimum RF requirements for NR User Equipment (UE) operating on frequency Range 1.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.

For a specific reference, subsequent revisions do not apply.

For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document in the same Release as the present document.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 38.101-2: "NR; User Equipment (UE) radio transmission and reception; Part 2: Range 2 Standalone".
- [3] 3GPP TS 38.101-3: "NR; User Equipment (UE) radio transmission and reception; Part 3: Range 1 and Range 2 Interworking operation with other radios".
- [4] 3GPP TS 38.521-1: "NR; User Equipment (UE) conformance specification; Radio transmission and reception; Part 1: Range 1 Standalone".
- [5] Recommendation ITU-R M.1545: "Measurement uncertainty as it applies to test limits for the terrestrial component of International Mobile Telecommunications-2000".
- [6] 3GPP TS 38.211: "NR; Physical channels and modulation".
- [7] 3GPP TS 38.331: "Radio Resource Control (RRC) protocol specification".
- [8] 3GPP TS 38.213: "NR; Physical layer procedures for control".
- [9] ITU-R Recommendation SM.329-10, "Unwanted emissions in the spurious domain".
- [10] 3GPP TS 38.214: "NR; Physical layer procedures for data".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

Aggregated Channel Bandwidth: The RF bandwidth in which a UE transmits and receives multiple contiguously aggregated carriers.

Carrier aggregation: Aggregation of two or more component carriers in order to support wider transmission bandwidths.

Carrier aggregation band: A set of one or more operating bands across which multiple carriers are aggregated with a specific set of technical requirements.