



**Universal Mobile Telecommunications System (UMTS);  
LTE;  
IP Multimedia Subsystem (IMS);  
Multimedia telephony;  
Media handling and interaction  
(3GPP TS 26.114 version 15.6.0 Release 15)**



## Reference

---

RTS/TSGS-0426114vf60

## Keywords

---

LTE,UMTS

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

---

The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

---

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

**GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

---

# Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

---

# Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

Intellectual Property Rights .....	2
Legal Notice .....	2
Modal verbs terminology.....	2
Foreword.....	15
Introduction .....	15
1 Scope .....	16
2 References .....	16
3 Definitions and abbreviations.....	23
3.1 Definitions .....	23
3.2 Abbreviations .....	24
4 System description .....	26
4.1 System .....	26
4.2 Client .....	27
4.3 MRFP and MGW .....	28
5 Media codecs.....	28
5.1 Media components .....	28
5.2 Codecs for MTSI clients in terminals.....	29
5.2.1 Speech.....	29
5.2.1.1 General codec requirements .....	29
5.2.1.2 Detailed codec requirements, AMR.....	29
5.2.1.3 Detailed codec requirements, AMR-WB.....	29
5.2.1.4 Detailed codec requirements, EVS.....	30
5.2.1.5 Offering multiple audio bandwidths and multiple channels.....	30
5.2.1.6 Codec preference order.....	30
5.2.2 Video .....	30
5.2.3 Real-time text.....	32
6 Media configuration .....	32
6.1 General .....	32
6.2 Session setup procedures.....	33
6.2.1 General.....	33
6.2.1a RTP profile negotiation .....	33
6.2.1a.1 General .....	33
6.2.1a.2 Using SDPCapNeg in SDP offer.....	33
6.2.1a.3 Answering to an SDP offer using SDPCapNeg .....	34
6.2.2 Speech.....	34
6.2.2.1 General .....	34
6.2.2.2 Generating SDP offers .....	35
6.2.2.3 Generating SDP answer .....	38
6.2.3 Video .....	46
6.2.3.1 Introduction.....	46
6.2.3.2 Common Session Setup Procedures.....	47
6.2.3.3 Coordination of Video Orientation (CVO) .....	48
6.2.3.4 Video Region-of-Interest (ROI) .....	48
6.2.3.5 RTP Retransmission.....	51
6.2.3.6 Forward Error Correction (FEC).....	51
6.2.4 Text.....	51
6.2.5 Bandwidth negotiation.....	52
6.2.5.1 General .....	52
6.2.5.2 Speech .....	54
6.2.5.3 Video.....	56
6.2.6 The Synchronization Info attribute "3gpp_sync_info" .....	57
6.2.7 Negotiated QoS parameters .....	58

6.2.7.1	General .....	58
6.2.7.2	Alignment of negotiated QoS parameters and b=AS bandwidth modifier .....	58
6.2.7.3	Alignment of negotiated QoS parameters and a=bw-info attribute .....	59
6.3	Session control procedures .....	59
7	Data transport .....	60
7.1	General .....	60
7.2	RTP profiles .....	60
7.3	RTCP usage .....	60
7.3.1	General .....	60
7.3.2	Speech .....	61
7.3.3	Video .....	62
7.3.4	Real-time text .....	63
7.3.5	Void .....	63
7.3.6	Reduced-Size RTCP .....	63
7.3.7	Video Region-of-Interest (ROI) Signaling .....	64
7.4	RTP payload formats for MTSI clients .....	67
7.4.1	General .....	67
7.4.2	Speech .....	67
7.4.3	Video .....	68
7.4.4	Real-time text .....	68
7.4.5	Coordination of Video Orientation .....	69
7.4.6	RTP Retransmission .....	71
7.4.7	Forward Error Correction (FEC) .....	71
7.5	Media flow .....	71
7.5.1	General .....	71
7.5.2	Media specific .....	71
7.5.2.1	Speech .....	71
7.5.2.1.1	General .....	71
7.5.2.1.2	Default operation .....	71
7.5.2.1.2.1	General .....	71
7.5.2.1.2.2	Codec Mode Requests .....	72
7.5.2.1.2.3	Frame aggregation and redundancy .....	72
7.5.2.1.3	HSPA .....	72
7.5.2.1.4	EGPRS .....	73
7.5.2.1.5	GIP .....	73
7.5.2.1.6	Initial codec mode for AMR and AMR-WB .....	73
7.5.2.1.7	E-UTRAN and NR .....	74
7.5.2.1.8	Initial codec mode for EVS .....	74
7.5.2.1.9	Dual-mono .....	74
7.5.2.2	Video .....	74
7.5.2.3	Text .....	74
7.5.3	Media synchronization .....	75
7.5.3.1	General .....	75
7.5.3.2	Text .....	75
7.5.4	ECN usage in RTP sessions .....	75
7.5.5	Handling of bit-rate variations .....	75
7.5.5.1	General .....	75
7.5.5.2	Video .....	76
7.5.5.3	Speech .....	76
8	Jitter buffer management in MTSI clients in terminals .....	76
8.1	General .....	76
8.2	Speech .....	76
8.2.1	Terminology .....	76
8.2.2	Functional requirements for jitter-buffer management .....	78
8.2.3	Minimum performance requirements for jitter-buffer management .....	78
8.2.3.1	General .....	78
8.2.3.2	Objective performance requirements .....	79
8.2.3.2.1	General .....	79
8.2.3.2.2	Jitter buffer delay criteria .....	79
8.2.3.2.3	Jitter induced concealment operations .....	80

8.2.3.3	Delay and error profiles .....	81
8.2.3.4	Speech material for JBM minimum performance evaluation.....	81
8.3	Video .....	81
8.4	Text .....	81
9	Packet-loss handling.....	82
9.1	General .....	82
9.2	Speech .....	82
9.2.1	General.....	82
9.2.2	Transmitting redundant frames .....	82
9.2.3	Receiving redundant frames .....	85
9.3	Video .....	86
9.3.1	General.....	86
9.3.2	Receiver behaviour .....	86
9.3.3	Sender behaviour .....	86
9.3.4	Recommendations for packet loss recovery mechanisms usage .....	87
9.4	Text .....	88
10	Adaptation .....	88
10.1	General .....	88
10.2	Speech .....	88
10.2.0	General.....	88
10.2.1	RTCP-APP with codec control requests .....	90
10.2.1.1	General .....	90
10.2.1.2	General Format of RTCP-APP packet with codec control requests .....	90
10.2.1.2a	Padding .....	91
10.2.1.3	Redundancy Request.....	91
10.2.1.4	Frame Aggregation Request.....	92
10.2.1.5	Codec Mode Request .....	92
10.2.1.6	Generation of RTP payloads for multiple codec control requests .....	93
10.2.1.7	EVS Primary Rate Request .....	94
10.2.1.8	EVS Bandwidth Request .....	95
10.2.1.9	EVS Channel Aware Request .....	95
10.2.1.10	EVS Primary mode to EVS AMR-WB IO mode Switching Request .....	96
10.2.1.11	EVS AMR-WB IO mode to EVS Primary mode Switching Request .....	97
10.2.2	Example use cases .....	97
10.2.3	SDP negotiation for RTCP-APP.....	99
10.3	Video .....	101
10.3.1	General.....	101
10.3.2	Signaling mechanisms .....	101
10.3.3	Adaptation triggers .....	102
10.3.4	Sender behavior, downswitching .....	103
10.3.4.1	Downswitching divided into phases.....	103
10.3.4.2	Rate reduction phase .....	103
10.3.4.3	Delay recovery phase .....	104
10.3.5	Sender behavior, up-switching.....	104
10.3.6	Receiver behavior, down-switching.....	104
10.3.7	Receiver behavior, up-switch.....	104
10.3.8	ECN triggered adaptation .....	105
10.4	Text .....	106
10.5	Explicit Congestion Notification.....	106
10.6	Using the a=bw-info attribute for adaptation .....	106
10.7	Access network bitrate recommendation.....	107
10.7.1	General.....	107
10.7.2	Relation to session signaling bitrate information.....	107
10.7.3	Use with dynamic bitrate adaptation.....	108
10.7.3.1	General .....	108
10.7.3.2	Adaptation of sent media .....	108
10.7.3.3	Adaptation of received media .....	111
10.7.4	Message mapping for LTE access .....	111
10.7.5	Message mapping for NR access .....	111
11	Front-end handling .....	112

11.1	General .....	112
12	Inter-working.....	113
12.1	General .....	113
12.2	3G-324M .....	113
12.2.1	General.....	113
12.2.2	Codec usage .....	113
12.2.2.1	General .....	113
12.2.2.2	Text .....	113
12.2.3	Payload format .....	113
12.2.4	MTSI media gateway trans-packetization.....	113
12.2.4.1	General .....	113
12.2.4.2	Speech de-jitter buffer.....	113
12.2.4.3	Video bitrate equalization .....	114
12.2.4.4	Data loss detection .....	114
12.2.4.5	Data integrity indication.....	114
12.2.4.6	Packet size considerations .....	114
12.2.4.6.0	General .....	114
12.2.4.6.1	The Maximum Receive SDU Size attribute "3gpp_MaxRecvSDUSize" .....	115
12.2.4.7	Setting RTP timestamps .....	115
12.2.4.8	Protocol termination.....	115
12.2.4.9	Media synchronization .....	115
12.2.5	Session control.....	116
12.3	GERAN/UTRAN CS inter-working.....	116
12.3.0	3G-324M .....	116
12.3.1	Codecs for MTSI media gateways.....	116
12.3.1.1	Speech interworking between 3GPP PS access and CS GERAN/UTRAN.....	116
12.3.1.1a	Speech inter-working between fixed access and CS GERAN/UTRAN.....	117
12.3.1.2	Text .....	117
12.3.2	RTP payload formats for MTSI media gateways.....	118
12.3.2.1	Speech.....	118
12.3.2.2	Text .....	119
12.3.3	Explicit Congestion Notification .....	119
12.3.4	Codec switching procedures with SRVCC.....	119
12.4	PSTN.....	120
12.4.1	3G-324M .....	120
12.4.2	Text.....	120
12.5	GIP inter-working.....	120
12.5.1	Text.....	120
12.5.2	Speech.....	120
12.6	Void.....	121
12.6.1	Void .....	121
12.6.2	Void .....	121
12.7	Inter-working with other IMS and non-IMS IP networks .....	121
12.7.1	General.....	121
12.7.2	Speech.....	121
12.7.2.1	General .....	121
12.7.2.2	Speech codecs and formats .....	121
12.7.2.2.1	MTSI MGW for interworking between MTSI client in terminal using 3GPP access and other IMS or non-IMS IP networks .....	121
12.7.2.2.2	MTSI MGW for interworking between MTSI client in terminal using fixed access and other IMS or non-IMS IP networks .....	122
12.7.2.2.3	Common procedures.....	122
12.7.2.3	Codec preference order for session negotiation .....	122
12.7.2.4	RTP profiles .....	123
12.7.2.5	RTP payload formats.....	123
12.7.2.6	Packetization .....	123
12.7.2.7	RTCP usage and adaptation .....	124
12.7.2.8	RTP usage .....	124
12.7.2.9	Session setup and session modification.....	125
12.7.2.10	Audio level alignment .....	125
12.7.3	Explicit Congestion Notification .....	125



12.7.4	Text.....	126
12.7.5	Inter-working IPv4 and IPv6 networks.....	126
12.8	MGW handling for NO_REQ interworking.....	126
13	Void.....	127
13a	Media types, codecs and formats used for MSRP transport.....	127
13a.1	General.....	127
13a.2	Difference relative to 3GPP TS 26.141.....	127
13a.2.1	Video.....	127
14	Supplementary services.....	127
14.1	General.....	127
14.2	Media formats and transport.....	127
14.3	Media handling in hold procedures.....	128
15	Network preference management object.....	128
15.1	General.....	128
15.2	Nodes Definition.....	128
15.3	Example Configuration of 3GPP MTSINP MO.....	140
16	Quality of Experience.....	142
16.1	General.....	142
16.2	Metrics Definition.....	142
16.2.1	Corruption duration metric.....	142
16.2.2	Successive loss of RTP packets.....	143
16.2.3	Frame rate.....	143
16.2.4	Jitter duration.....	144
16.2.5	Sync loss duration.....	144
16.2.6	Round-trip time.....	144
16.2.7	Average codec bitrate.....	145
16.2.8	Codec information.....	145
16.3	Metric Configuration.....	145
16.3.1	QoE metrics reporting management object.....	146
16.3.2	QoE metric reporting configuration.....	152
16.3.3	QoE reporting rule definition.....	152
16.4	Metrics Reporting.....	153
16.4.1	XML schema for QoE report message.....	154
16.4.2	Example XML for QoE report message.....	155
16.5	QoE Measurement Collection Functionalities.....	156
16.5.1	Configuration and reporting.....	156
16.5.2	XML configuration.....	157
17	Management of Media Adaptation.....	159
17.1	General.....	159
17.2	Media adaptation management object.....	159
17.3	Management procedures.....	182
17.3.1	Management of speech adaptation.....	182
17.3.2	Management of video adaptation.....	184
18	MTSI client in terminal using fixed access.....	186
18.1	General.....	186
18.2	Media codecs.....	186
18.2.1	General.....	186
18.2.2	Speech.....	186
18.2.2.1	Speech codecs.....	186
18.2.2.2	Error concealment procedures.....	187
18.2.2.3	Source controlled rate operation.....	187
18.2.3	Video.....	187
18.2.4	Real-time text.....	188
18.3	Media configuration.....	188
18.3.1	General.....	188
18.3.2	Session setup procedures.....	188
18.3.2.1	General.....	188



18.3.2.2	Speech .....	188
18.3.2.3	Video .....	189
18.3.2.4	Text .....	189
18.3.2.5	Bandwidth negotiation .....	189
18.3.3	Session control procedures .....	189
18.4	Data transport .....	190
18.4.1	General .....	190
18.4.2	Packetization .....	190
18.4.3	RTP payload format .....	190
18.5	Jitter buffer management .....	191
18.6	Packet-loss handling .....	191
18.7	Adaptation .....	191
18.8	Front-end handling .....	191
18.9	Supplementary services .....	191
19	Additional bandwidth information .....	192
19.1	General .....	192
19.2	Bandwidth properties .....	192
19.2.1	General description .....	192
19.2.2	Maximum Supported Bandwidth .....	193
19.2.3	Maximum Desired Bandwidth .....	193
19.2.4	Minimum Desired Bandwidth .....	194
19.2.5	Minimum Supported Bandwidth .....	194
19.2.6	IP version .....	194
19.2.7	Maximum Packet Rate .....	195
19.2.8	Minimum Packet Rate .....	195
19.3	SDP attribute .....	195
19.3.1	Definition .....	195
19.3.2	SDP grammar .....	196
19.3.3	Declarative use .....	197
19.3.4	Usage in offer/answer .....	197
19.4	Modifications of the bandwidth information by intermediate network nodes .....	198
<b>Annex A (informative): Examples of SDP offers and answers .....</b>		<b>200</b>
A.1	SDP offers for speech sessions initiated by MTSI client in terminal .....	200
A.1.1	HSPA or unknown access technology .....	200
A.1.1.1	Only AMR-NB supported by MTSI client in terminal .....	200
A.1.1.2	AMR and AMR-WB are supported by MTSI client in terminal .....	201
A.1.1.2.1	One-phase approach .....	201
A.1.1.2.2	Two-phase approach .....	202
A.1.2	EGPRS .....	203
A.1.3	Generic Access .....	204
A.2	SDP offers for speech sessions initiated by media gateway .....	204
A.2.1	General .....	204
A.2.2	MGW between GERAN UE and MTSI .....	204
A.2.3	MGW between legacy UTRAN UE and MTSI .....	205
A.2.4	MGW between CS UE and MTSI .....	205
A.2.5	MGW between GERAN UE and MTSI when wideband speech is supported .....	206
A.3	SDP answers to SDP speech session offers .....	206
A.3.1	General .....	206
A.3.1a	SDP answer from an MTSI client in terminal when only narrowband speech was offered .....	207
A.3.2	SDP answer from an MTSI client in terminal .....	207
A.3.2a	SDP answer from a non-MTSI UE with AVP .....	208
A.3.3	SDP answer from an MTSI client in terminal supporting only AMR .....	209
A.3.4	SDP answer from an MTSI client in terminal using EGPRS access when both AMR and AMR-WB are supported .....	210
A.3.4a	SDP answer from an MTSI client in terminal using EGPRS access when only AMR is supported .....	211
A.3.4b	SDP answer from an MTSI client in terminal using WLAN .....	211
A.3.5	SDP answer from MTSI MGW supporting only one codec mode set for AMR and AMR-WB each .....	212
A.3.5a	SDP answer from MTSI MGW supporting only one codec mode set for AMR .....	214

A.3.6	SDP answer from MTSI client in terminal on HSPA for session initiated from MTSI MGW interfacing UE on GERAN.....	214
A.3.7	SDP answer from MTSI client in terminal on HSPA for session initiated from MTSI MGW interfacing legacy UE on UTRAN .....	215
A.4	SDP offers and answers for video sessions .....	216
A.4.1	Void.....	216
A.4.2	Void.....	216
A.4.2a	H.264/AVC .....	216
A.4.2b	High Granularity CVO example.....	218
A.4.2c	RTP Retransmission.....	218
A.4.2d	RTP Forward Error Correction (FEC).....	219
A.4.2e	SDP Examples with ROI.....	220
A.4.3	Void.....	226
A.4.4	Void.....	226
A.4.4a	H.264/AVC with "imageattr" attribute.....	226
A.4.4a.1	H.264/AVC with "imageattr" attribute – different image sizes in SDP offer and answer .....	228
A.4.4a.2	H.264/AVC with "imageattr" attribute – different payload type numbers in offer and answer .....	229
A.4.4b	H.264/AVC with "imageattr" attribute with multiple rtpmaps.....	230
A.4.5	H.264 with asymmetric video streams .....	232
A.4.6	H.264/AVC with "imageattr" attribute for non-CVO operation.....	233
A.4.7	H.264 (AVC) and H.265 (HEVC).....	235
A.4.7.1	MTSI client with 848x480 resolution 5 inch display.....	235
A.4.7.2	MTSI client with 1280x720 resolution 5 inch display .....	236
A.4.7.3	MTSI client with 848x480 resolution 10 inch display.....	237
A.4.7.4	MTSI client with 1280x720 resolution 10 inch display.....	238
A.4.8	H.264 (AVC) and H.265 (HEVC) with asymmetric video streams.....	239
A.5	SDP offers for text.....	240
A.5.1	T.140 with and without redundancy .....	240
A.6	SDP example with bandwidth information.....	242
A.6.1	General .....	242
A.6.2	SDP examples with bandwidth information declared with bandwidth modifiers.....	242
A.6.3	SDP examples giving additional bandwidth information using the a=bw-info attribute.....	243
A.7	SDP examples with "3gpp_sync_info" attribute .....	246
A.7.1	Synchronized streams.....	246
A.7.2	Nonsynchronized streams.....	246
A.8	SDP example with QoS negotiation.....	247
A.9	Void.....	251
A.9a	SDP offer/answer regarding the use of Reduced-Size RTCP.....	251
A.10	Examples of SDP offers and answers for inter-working with other IMS or non-IMS IP networks .....	252
A.10.1	General .....	252
A.10.2	Session initiated by MTSI client in terminal .....	252
A.10.2.1	SDP offers from an MTSI client in terminal.....	252
A.10.2.2	SDP offers modified by MTSI MGW when pre-emptively adding inter-working formats .....	253
A.10.2.3	SDP modified by MGW when adding inter-working formats only when the original SDP offer was rejected.....	254
A.11	Adding or removing a video component to/from an on-going video call session.....	256
A.12	SDP examples when using ECN .....	260
A.12.1	SDP examples when using ECN for speech.....	260
A.12.1.1	With RTP/AVP and zero RTCP bandwidth.....	260
A.12.1.2	With RTP/AVPF and non-zero RTCP bandwidth .....	261
A.12.1.3	With RTCP ECN feedback messages and RTCP XR ECN summary reports for inter-working with non-MTSI clients .....	262
A.12.2	SDP examples when using ECN for video in RTP.....	263
A.12.2.1	Without RTCP AVPF ECN feedback messages and RTCP XR ECN summary reports .....	263

A.12.2.2	With RTCP AVPF ECN feedback messages and RTCP XR ECN summary reports for inter-working with non-MTSI clients .....	264
A.13	SDP examples for MTSI client in terminal using fixed access .....	265
A.13.1	General .....	265
A.13.2	SDP examples for PCM .....	265
A.13.3	SDP example for G.722.....	266
A.13.4	SDP example for EVS, AMR-WB, G.722, AMR, PCM and DTMF .....	266
A.14	SDP offers and answers for speech sessions with EVS .....	267
A.14.1	SDP offers initiated by MTSI client in terminal.....	267
A.14.1.1	Unknown access technology.....	267
A.14.1.2	EGPRS.....	268
A.14.1.3	NR/E-UTRAN/HSPA.....	269
A.14.1.4	Dual-mono .....	269
A.14.2	SDP offers initiated by media gateway .....	270
A.14.2.1	Network between MTSI using fixed access and MTSI modifying SDP offer to configure EVS AMR-WB IO mode.....	271
A.14.3	SDP answers from MTSI client in terminal .....	272
A.14.3.1	SDP answer from MTSI client in terminal when narrowband speech is negotiated .....	272
A.14.3.2	SDP answer from MTSI client in terminal when up to wideband speech is negotiated .....	272
A.14.3.3	SDP answer from MTSI client in terminal when only wideband speech is negotiated .....	273
A.14.3.4	SDP answer from MTSI client in terminal when up to super-wideband speech is negotiated .....	273
A.14.3.5	SDP answer from MTSI client in terminal when only super-wideband speech is negotiated .....	273
A.14.3.6	SDP answer from MTSI client in terminal using WLAN.....	274
A.14.3.7	SDP answer from MTSI client in terminal supporting dual-mono .....	274
A.14.3.8	SDP answer from MTSI client in terminal supporting dual-mono for send direction .....	274
A.14.3.9	SDP answer from MTSI client in terminal when SC-VBR is negotiated .....	275
A.14.4	SDP answers from MTSI client in terminal using fixed access.....	275
A.14.4.1	SDP answer from MTSI client in terminal using fixed access when narrowband speech is negotiated .....	275
A.14.4.2	SDP answer from MTSI client in terminal using fixed access when only wideband speech is negotiated.....	276
A.14.4.3	SDP answer from MTSI client in terminal using fixed access when only super-wideband speech is negotiated.....	276
<b>Annex B (informative):</b>	<b>Examples of adaptation scenarios .....</b>	<b>278</b>
B.1	Video bitrate adaptation .....	278
<b>Annex C (informative):</b>	<b>Example adaptation mechanisms for speech.....</b>	<b>279</b>
C.1	Example of feedback and adaptation for speech and video.....	279
C.1.1	Introduction .....	279
C.1.2	Signalling state considerations .....	280
C.1.3	Adaptation state machine implementations .....	282
C.1.3.1	General.....	282
C.1.3.2	Adaptation state machine with four states .....	284
C.1.3.3	Adaptation state machine with four states (simplified version without frame aggregation).....	287
C.1.3.4	Adaptation state machine with two states .....	289
C.1.3.5	Adaptation when using ECN .....	290
C.2	Example criteria for video bit rate feedback and adaptation.....	292
C.2.1	Introduction .....	292
C.2.2	Media sender side.....	293
C.2.3	Media receiver side .....	293
C.2.4	Video encoder bitrate adaptation, down-switch .....	293
C.2.5	Video encoder bitrate adaptation, receiver-driven up-switch.....	295
C.2.6	Video encoder bitrate adaptation, recovery phase.....	295
<b>Annex D (informative):</b>	<b>Reference delay computation algorithm.....</b>	<b>297</b>
<b>Annex E (informative):</b>	<b>QoS profiles .....</b>	<b>299</b>
E.1	General .....	299

E.2	Bi-directional speech (AMR12.2, IPv4, RTCP and MBR=GBR bearer).....	299
E.3	Void.....	300
E.4	Bi-directional real-time text (3 kbps, IPv4 or IPv6, RTCP and MBR=GBR bearer).....	301
E.5	Bi-directional speech (AMR-WB23.85, IPv4, RTCP and MBR=GBR bearer).....	303
E.6	Bi-directional video (H.264 AVC level 1.1, 192 kbps, IPv4, RTCP and MBR=GBR bearer).....	303
E.7	Bi-directional speech (AMR12.2, IPv6, RTCP and MBR=GBR bearer).....	304
E.8	Bi-directional speech (AMR-WB23.85, IPv6, RTCP and MBR=GBR bearer).....	305
E.9	Void.....	306
E.10	Bi-directional video (H.264 AVC level 1.1, 192 kbps, IPv6, RTCP and MBR=GBR bearer).....	306
E.11	Bi-directional speech (AMR, IPv4, RTCP and MBR>GBR bearer).....	307
E.12	Bi-directional speech (AMR-WB, IPv4, RTCP and MBR>GBR bearer).....	308
E.13	Void.....	309
E.14	Bi-directional video (H.264 AVC level 1.1, IPv4, RTCP and MBR>GBR bearer).....	309
E.15	Bi-directional speech (AMR, IPv6, RTCP and MBR>GBR bearer).....	310
E.16	Bi-directional speech (AMR-WB, IPv6, RTCP and MBR>GBR bearer).....	311
E.17	Void.....	312
E.18	Bi-directional video (H.264 AVC level 1.1, IPv6, RTCP and MBR>GBR bearer).....	312
E.19	Bi-directional video (H.264 AVC level 1.2, 384 kbps, IPv4, RTCP and MBR=GBR bearer).....	313
E.20	Bi-directional video (H.264 AVC level 1.2, 384 kbps, IPv6, RTCP and MBR=GBR bearer).....	314
E.21	Bi-directional video (H.264 AVC level 1.2, IPv4, RTCP and MBR>GBR bearer).....	316
E.22	Bi-directional video (H.264 AVC level 1.2, IPv6, RTCP and MBR>GBR bearer).....	319
E.23	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 500 kbps, IPv6, RTCP and MBR=GBR bearer).....	320
E.24	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 500/40 kbps, IPv6, RTCP and MBR>GBR bearer).....	321
E.25	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 600 kbps, IPv6, RTCP and MBR=GBR bearer).....	322
E.26	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 600/40 kbps, IPv6, RTCP and MBR>GBR bearer).....	323
E.27	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 650 kbps, IPv6, RTCP and MBR=GBR bearer).....	324
E.28	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 650/40 kbps, IPv6, RTCP and MBR>GBR bearer).....	325
E.29	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 750 kbps, IPv6, RTCP and MBR=GBR bearer).....	326
E.30	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 750/40 kbps, IPv6, RTCP and MBR>GBR bearer).....	327
E.31	Bi-directional speech (EVS 13.2, IPv4, RTCP and MBR=GBR bearer).....	328
E.32	Bi-directional speech (EVS 24.4, IPv4, RTCP and MBR=GBR bearer).....	329
E.33	Bi-directional speech (EVS 13.2, IPv6, RTCP and MBR=GBR bearer).....	330
E.34	Bi-directional speech (EVS 24.4, IPv6, RTCP and MBR=GBR bearer).....	331

**Annex F (Normative): Void 333****Annex G (Normative): DTMF events .....334**

G.1 General .....334

G.2 Encoding of DTMF events .....334

G.3 Session setup .....334

G.4 Data transport for DTMF events .....336

**Annex H (informative): Network Preference Management Object Device Description Framework...338****Annex I (informative): QoE Reporting Management Object Device Description Framework.....339****Annex J (informative): Media Adaptation Management Object Device Description Framework .....340****Annex K (informative): Computation of b=AS for AMR and AMR-WB .....341**

K.1 General .....341

K.2 Procedure for computing the bandwidth .....341

K.3 Computation of RTP payload size.....341

K.4 Detailed computation .....342

**Annex L (Normative): Facsimile transmission .....351**

L.1 General .....351

L.2 FoIP support in MTSI clients .....351

L.2.1 FoIP support in MTSI client in terminal .....351

L.2.2 FoIP support in MTSI MGW .....351

L.2.3 Recommended configuration.....351

L.3 Session setup .....352

L.3.1 Session setup for any MTSI client supporting facsimile transmission .....352

L.3.2 Session setup when the recommended profile is supported .....352

L.4 Data transport using UDP/IP .....353

L.5 CS GERAN inter-working .....353

L.6 PSTN inter-working .....354

L.7 SDP examples .....354

L.7.1 Facsimile-only session .....354

**Annex M (informative): IANA registration information for SDP attributes.....356**

M.1 Introduction .....356

M.2 3gpp\_sync\_info .....356

M.3 3gpp\_MaxRecvSDUSize.....356

M.4 3gpp\_mtsi\_app\_adapt.....357

M.5 predefined\_ROI.....357

M.6 bw-info .....358

M.7 ccc\_list.....359

**Annex N (informative): Computation of b=AS for Video Codec .....360**

N.1 General .....360

N.2 Examples .....360