

ETSI TS 126 114 V13.9.0 (2019-10)



**Universal Mobile Telecommunications System (UMTS);
LTE;
IP Multimedia Subsystem (IMS);
Multimedia telephony;
Media handling and interaction
(3GPP TS 26.114 version 13.9.0 Release 13)**

<https://standards.1e11.com/standards/sistr/c3/area-77d3-4ac7-9e09-0a97b663d11c/sistr-ts-26-114-v13.9.0-201910>



Reference

RTS/TSGS-0426114vd90

Keywords

LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2019.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	15
Introduction	15
1 Scope	16
2 References	16
3 Definitions and abbreviations.....	23
3.1 Definitions	23
3.2 Abbreviations	24
4 System description	26
4.1 System	26
4.2 Client	26
4.3 MRFP and MGW	28
5 Media codecs.....	28
5.1 Media components	28
5.2 Codecs for MTSI clients in terminals.....	29
5.2.1 Speech.....	29
5.2.1.1 General codec requirements	29
5.2.1.2 Detailed codec requirements, AMR.....	29
5.2.1.3 Detailed codec requirements, AMR-WB	29
5.2.1.4 Detailed codec requirements, EVS.....	30
5.2.1.5 Offering multiple audio bandwidths and multiple channels.....	30
5.2.1.6 Codec preference order	30
5.2.2 Video	30
5.2.3 Real-time text.....	32
6 Media configuration	32
6.1 General	32
6.2 Session setup procedures.....	33
6.2.1 General.....	33
6.2.1a RTP profile negotiation	33
6.2.1a.1 General	33
6.2.1a.2 Using SDPCapNeg in SDP offer.....	34
6.2.1a.3 Answering to an SDP offer using SDPCapNeg	34
6.2.2 Speech.....	34
6.2.2.1 General	34
6.2.2.2 Generating SDP offers	35
6.2.2.3 Generating SDP answer	38
6.2.3 Video	46
6.2.3.1 Introduction.....	46
6.2.3.2 Common Session Setup Procedures	47
6.2.3.3 Coordination of Video Orientation (CVO)	48
6.2.3.4 Video Region-of-Interest (ROI)	48
6.2.3.5 RTP Retransmission.....	51
6.2.3.6 Forward Error Correction (FEC).....	51
6.2.4 Text.....	51
6.2.5 Bandwidth negotiation.....	52
6.2.5.1 General	52
6.2.5.2 Speech	53
6.2.5.3 Video.....	55
6.2.6 The Synchronization Info attribute "3gpp_sync_info"	56
6.2.7 Negotiated QoS parameters	57

6.2.7.1	General	57
6.2.7.2	Alignment of negotiated QoS parameters and b=AS bandwidth modifier	57
6.2.7.3	Alignment of negotiated QoS parameters and a=bw-info attribute	58
6.3	Session control procedures	58
7	Data transport	59
7.1	General	59
7.2	RTP profiles	59
7.3	RTCP usage	59
7.3.1	General	59
7.3.2	Speech	60
7.3.3	Video	61
7.3.4	Real-time text	62
7.3.5	Void	62
7.3.6	Reduced-Size RTCP	62
7.3.7	Video Region-of-Interest (ROI) Signaling	63
7.4	RTP payload formats for MTSI clients	66
7.4.1	General	66
7.4.2	Speech	66
7.4.3	Video	67
7.4.4	Real-time text	67
7.4.5	Coordination of Video Orientation	68
7.4.6	RTP Retransmission	70
7.4.7	Forward Error Correction (FEC)	70
7.5	Media flow	70
7.5.1	General	70
7.5.2	Media specific	70
7.5.2.1	Speech	70
7.5.2.1.1	General	70
7.5.2.1.2	Default operation	70
7.5.2.1.2.1	General	70
7.5.2.1.2.2	Codec Mode Requests	71
7.5.2.1.2.3	Frame aggregation and redundancy	71
7.5.2.1.3	HSPA	71
7.5.2.1.4	EGPRS	72
7.5.2.1.5	GIP	72
7.5.2.1.6	Initial codec mode for AMR and AMR-WB	72
7.5.2.1.7	E-UTRAN	73
7.5.2.1.8	Initial codec mode for EVS	73
7.5.2.1.9	Dual-mono	73
7.5.2.2	Video	73
7.5.2.3	Text	73
7.5.3	Media synchronization	74
7.5.3.1	General	74
7.5.3.2	Text	74
7.5.4	ECN usage in RTP sessions	74
7.5.5	Handling of bit-rate variations	74
7.5.5.1	General	74
7.5.5.2	Video	75
7.5.5.3	Speech	75
8	Jitter buffer management in MTSI clients in terminals	75
8.1	General	75
8.2	Speech	75
8.2.1	Terminology	75
8.2.2	Functional requirements for jitter-buffer management	77
8.2.3	Minimum performance requirements for jitter-buffer management	77
8.2.3.1	General	77
8.2.3.2	Objective performance requirements	78
8.2.3.2.1	General	78
8.2.3.2.2	Jitter buffer delay criteria	78
8.2.3.2.3	Jitter induced concealment operations	79

8.2.3.3	Delay and error profiles	80
8.2.3.4	Speech material for JBM minimum performance evaluation.....	80
8.3	Video	80
8.4	Text	80
9	Packet-loss handling.....	81
9.1	General	81
9.2	Speech	81
9.2.1	General.....	81
9.2.2	Transmitting redundant frames	81
9.2.3	Receiving redundant frames	84
9.3	Video	85
9.3.1	General.....	85
9.3.2	Receiver behaviour	85
9.3.3	Sender behaviour	85
9.3.4	Recommendations for packet loss recovery mechanisms usage	86
9.4	Text	87
10	Adaptation	87
10.1	General	87
10.2	Speech	87
10.2.0	General.....	87
10.2.1	RTCP-APP with codec control requests	89
10.2.1.1	General	89
10.2.1.2	General Format of RTCP-APP packet with codec control requests.....	89
10.2.1.2a	Padding	90
10.2.1.3	Redundancy Request.....	90
10.2.1.4	Frame Aggregation Request.....	91
10.2.1.5	Codec Mode Request	91
10.2.1.6	Generation of RTP payloads for multiple codec control requests	92
10.2.1.7	EVS Primary Rate Request	93
10.2.1.8	EVS Bandwidth Request	94
10.2.1.9	EVS Channel Aware Request	94
10.2.1.10	EVS Primary mode to EVS AMR-WB IO mode Switching Request	95
10.2.1.11	EVS AMR-WB IO mode to EVS Primary mode Switching Request	96
10.2.2	Example use cases	96
10.2.3	SDP negotiation for RTCP-APP	98
10.3	Video	100
10.3.1	General.....	100
10.3.2	Signaling mechanisms	100
10.3.3	Adaptation triggers	101
10.3.4	Sender behavior, downswitching	101
10.3.4.1	Downswitching divided into phases.....	101
10.3.4.2	Rate reduction phase	102
10.3.4.3	Delay recovery phase	103
10.3.5	Sender behavior, up-switching.....	103
10.3.6	Receiver behavior, down-switching.....	103
10.3.7	Receiver behavior, up-switch.....	103
10.3.8	ECN triggered adaptation	103
10.4	Text	104
10.5	Explicit Congestion Notification.....	105
10.6	Using the a=bw-info attribute for adaptation	105
11	Front-end handling	105
11.1	General	105
12	Inter-working.....	106
12.1	General	106
12.2	3G-324M	107
12.2.1	General.....	107
12.2.2	Codec usage	107
12.2.2.1	General	107
12.2.2.2	Text	107

12.2.3	Payload format.....	107
12.2.4	MTSI media gateway trans-packetization.....	107
12.2.4.1	General.....	107
12.2.4.2	Speech de-jitter buffer.....	107
12.2.4.3	Video bitrate equalization.....	107
12.2.4.4	Data loss detection.....	108
12.2.4.5	Data integrity indication.....	108
12.2.4.6	Packet size considerations.....	108
12.2.4.6.0	General.....	108
12.2.4.6.1	The Maximum Receive SDU Size attribute “3gpp_MaxRecvSDUSize”.....	108
12.2.4.7	Setting RTP timestamps.....	109
12.2.4.8	Protocol termination.....	109
12.2.4.9	Media synchronization.....	109
12.2.5	Session control.....	109
12.3	GERAN/UTRAN CS inter-working.....	110
12.3.0	3G-324M.....	110
12.3.1	Codecs for MTSI media gateways.....	110
12.3.1.1	Speech interworking between 3GPP PS access and CS GERAN/UTRAN.....	110
12.3.1.1a	Speech inter-working between fixed access and CS GERAN/UTRAN.....	111
12.3.1.2	Text.....	111
12.3.2	RTP payload formats for MTSI media gateways.....	111
12.3.2.1	Speech.....	111
12.3.2.2	Text.....	112
12.3.3	Explicit Congestion Notification.....	113
12.3.4	Codec switching procedures with SRVCC.....	113
12.4	PSTN.....	113
12.4.1	3G-324M.....	113
12.4.2	Text.....	113
12.5	GIP inter-working.....	114
12.5.1	Text.....	114
12.5.2	Speech.....	114
12.6	Void.....	114
12.6.1	Void.....	114
12.6.2	Void.....	114
12.7	Inter-working with other IMS and non-IMS IP networks.....	114
12.7.1	General.....	114
12.7.2	Speech.....	115
12.7.2.1	General.....	115
12.7.2.2	Speech codecs and formats.....	115
12.7.2.2.1	MTSI MGW for interworking between MTSI client in terminal using 3GPP access and other IMS or non-IMS IP networks.....	115
12.7.2.2.2	MTSI MGW for interworking between MTSI client in terminal using fixed access and other IMS or non-IMS IP networks.....	115
12.7.2.2.3	Common procedures.....	116
12.7.2.3	Codec preference order for session negotiation.....	116
12.7.2.4	RTP profiles.....	116
12.7.2.5	RTP payload formats.....	116
12.7.2.6	Packetization.....	117
12.7.2.7	RTCP usage and adaptation.....	117
12.7.2.8	RTP usage.....	118
12.7.2.9	Session setup and session modification.....	118
12.7.2.10	Audio level alignment.....	118
12.7.3	Explicit Congestion Notification.....	119
12.7.4	Text.....	119
12.7.5	Inter-working IPv4 and IPv6 networks.....	119
13	Void.....	119
13a	Media types, codecs and formats used for MSRP transport.....	120
13a.1	General.....	120
13a.2	Difference relative to 3GPP TS 26.141.....	120
13a.2.1	Video.....	120

14	Supplementary services	120
14.1	General	120
14.2	Media formats and transport	120
14.3	Media handling in hold procedures	121
15	Network preference management object	121
15.1	General	121
15.2	Nodes Definition	121
15.3	Example Configuration of 3GPP MTSINP MO	133
16	Quality of Experience	135
16.1	General	135
16.2	Metrics Definition	135
16.2.1	Corruption duration metric	135
16.2.2	Successive loss of RTP packets	136
16.2.3	Frame rate	136
16.2.4	Jitter duration	137
16.2.5	Sync loss duration	137
16.2.6	Round-trip time	137
16.2.7	Average codec bitrate	138
16.2.8	Codec information	138
16.3	Metric Configuration	138
16.3.1	QoE metrics reporting management object	139
16.3.2	QoE metric reporting configuration	142
16.3.3	QoE reporting rule definition	143
16.4	Metrics Reporting	144
16.4.1	XML schema for QoE report message	145
16.4.2	Example XML for QoE report message	146
17	Management of Media Adaptation	147
17.1	General	147
17.2	Media adaptation management object	147
17.3	Management procedures	170
17.3.1	Management of speech adaptation	170
17.3.2	Management of video adaptation	172
18	MTSI client in terminal using fixed access	174
18.1	General	174
18.2	Media codecs	174
18.2.1	General	174
18.2.2	Speech	174
18.2.2.1	Speech codecs	174
18.2.2.2	Error concealment procedures	175
18.2.2.3	Source controlled rate operation	175
18.2.3	Video	175
18.2.4	Real-time text	176
18.3	Media configuration	176
18.3.1	General	176
18.3.2	Session setup procedures	176
18.3.2.1	General	176
18.3.2.2	Speech	176
18.3.2.3	Video	177
18.3.2.4	Text	177
18.3.2.5	Bandwidth negotiation	177
18.3.3	Session control procedures	177
18.4	Data transport	178
18.4.1	General	178
18.4.2	Packetization	178
18.4.3	RTP payload format	178
18.5	Jitter buffer management	179
18.6	Packet-loss handling	179
18.7	Adaptation	179
18.8	Front-end handling	179

18.9	Supplementary services	179
19	Additional bandwidth information	180
19.1	General	180
19.2	Bandwidth properties	180
19.2.1	General description	180
19.2.2	Maximum Supported Bandwidth	181
19.2.3	Maximum Desired Bandwidth	181
19.2.4	Minimum Desired Bandwidth	182
19.2.5	Minimum Supported Bandwidth	182
19.2.6	IP version	182
19.2.7	Maximum Packet Rate	183
19.2.8	Minimum Packet Rate	183
19.3	SDP attribute	183
19.3.1	Definition	183
19.3.2	SDP grammar	184
19.3.3	Declarative use	185
19.3.4	Usage in offer/answer	185
19.4	Modifications of the bandwidth information by intermediate network nodes	186

Annex A (informative): Examples of SDP offers and answers188

A.1	SDP offers for speech sessions initiated by MTSI client in terminal	188
A.1.1	HSPA or unknown access technology	188
A.1.1.1	Only AMR-NB supported by MTSI client in terminal	188
A.1.1.2	AMR and AMR-WB are supported by MTSI client in terminal	189
A.1.1.2.1	One-phase approach	189
A.1.1.2.2	Two-phase approach	190
A.1.2	EGPRS	191
A.1.3	Generic Access	191
A.2	SDP offers for speech sessions initiated by media gateway	192
A.2.1	General	192
A.2.2	MGW between GERAN UE and MTSI	192
A.2.3	MGW between legacy UTRAN UE and MTSI	192
A.2.4	MGW between CS UE and MTSI	193
A.2.5	MGW between GERAN UE and MTSI when wideband speech is supported	193
A.3	SDP answers to SDP speech session offers	194
A.3.1	General	194
A.3.1a	SDP answer from an MTSI client in terminal when only narrowband speech was offered	195
A.3.2	SDP answer from an MTSI client in terminal	195
A.3.2a	SDP answer from a non-MTSI UE with AVP	196
A.3.3	SDP answer from an MTSI client in terminal supporting only AMR	197
A.3.4	SDP answer from an MTSI client in terminal using EGPRS access when both AMR and AMR-WB are supported	198
A.3.4a	SDP answer from an MTSI client in terminal using EGPRS access when only AMR is supported	199
A.3.4b	SDP answer from an MTSI client in terminal using WLAN	199
A.3.5	SDP answer from MTSI MGW supporting only one codec mode set for AMR and AMR-WB each	200
A.3.5a	SDP answer from MTSI MGW supporting only one codec mode set for AMR	202
A.3.6	SDP answer from MTSI client in terminal on HSPA for session initiated from MTSI MGW interfacing UE on GERAN	202
A.3.7	SDP answer from MTSI client in terminal on HSPA for session initiated from MTSI MGW interfacing legacy UE on UTRAN	203
A.4	SDP offers and answers for video sessions	204
A.4.1	Void	204
A.4.2	Void	204
A.4.2a	H.264/AVC	204
A.4.2b	High Granularity CVO example	206
A.4.2c	RTP Retransmission	206
A.4.2d	RTP Forward Error Correction (FEC)	207
A.4.2e	SDP Examples with ROI	208
A.4.3	Void	214

A.4.4	Void.....	214
A.4.4a	H.264/AVC with "imageattr" attribute.....	214
A.4.4a.1	H.264/AVC with "imageattr" attribute – different image sizes in SDP offer and answer.....	216
A.4.4a.2	H.264/AVC with "imageattr" attribute – different payload type numbers in offer and answer.....	217
A.4.4b	H.264/AVC with "imageattr" attribute with multiple rtpmaps.....	218
A.4.5	H.264 with asymmetric video streams.....	220
A.4.6	H.264/AVC with "imageattr" attribute for non-CVO operation.....	221
A.4.7	H.264 (AVC) and H.265 (HEVC).....	223
A.4.7.1	MTSI client with 848x480 resolution 5 inch display.....	223
A.4.7.2	MTSI client with 1280x720 resolution 5 inch display.....	224
A.4.7.3	MTSI client with 848x480 resolution 10 inch display.....	225
A.4.7.4	MTSI client with 1280x720 resolution 10 inch display.....	226
A.4.8	H.264 (AVC) and H.265 (HEVC) with asymmetric video streams.....	227
A.5	SDP offers for text.....	228
A.5.1	T.140 with and without redundancy.....	228
A.6	SDP example with bandwidth information.....	230
A.6.1	General.....	230
A.6.2	SDP examples with bandwidth information declared with bandwidth modifiers.....	230
A.6.3	SDP examples giving additional bandwidth information using the a=bw-info attribute.....	231
A.7	SDP examples with "3gpp_sync_info" attribute.....	234
A.7.1	Synchronized streams.....	234
A.7.2	Nonsynchronized streams.....	234
A.8	SDP example with QoS negotiation.....	235
A.9	Void.....	239
A.9a	SDP offer/answer regarding the use of Reduced-Size RTCP.....	239
A.10	Examples of SDP offers and answers for inter-working with other IMS or non-IMS IP networks.....	240
A.10.1	General.....	240
A.10.2	Session initiated by MTSI client in terminal.....	240
A.10.2.1	SDP offers from an MTSI client in terminal.....	240
A.10.2.2	SDP offers modified by MTSI MGW when pre-emptively adding inter-working formats.....	241
A.10.2.3	SDP modified by MGW when adding inter-working formats only when the original SDP offer was rejected.....	242
A.11	Adding or removing a video component to/from an on-going video call session.....	244
A.12	SDP examples when using ECN.....	248
A.12.1	SDP examples when using ECN for speech.....	248
A.12.1.1	With RTP/AVP and zero RTCP bandwidth.....	248
A.12.1.2	With RTP/AVPF and non-zero RTCP bandwidth.....	249
A.12.1.3	With RTCP ECN feedback messages and RTCP XR ECN summary reports for inter-working with non-MTSI clients.....	250
A.12.2	SDP examples when using ECN for video in RTP.....	251
A.12.2.1	Without RTCP AVPF ECN feedback messages and RTCP XR ECN summary reports.....	251
A.12.2.2	With RTCP AVPF ECN feedback messages and RTCP XR ECN summary reports for inter-working with non-MTSI clients.....	252
A.13	SDP examples for MTSI client in terminal using fixed access.....	253
A.13.1	General.....	253
A.13.2	SDP examples for PCM.....	253
A.13.3	SDP example for G.722.....	254
A.13.4	SDP example for EVS, AMR-WB, G.722, AMR, PCM and DTMF.....	254
A.14	SDP offers and answers for speech sessions with EVS.....	255
A.14.1	SDP offers initiated by MTSI client in terminal.....	255
A.14.1.1	Unknown access technology.....	255
A.14.1.2	EGPRS.....	256
A.14.1.3	E-UTRAN/HSPA.....	257
A.14.1.4	Dual-mono.....	257
A.14.2	SDP offers initiated by media gateway.....	258

A.14.2.1	Network between MTSI using fixed access and MTSI modifying SDP offer to configure EVS AMR-WB IO mode	259
A.14.3	SDP answers from MTSI client in terminal	260
A.14.3.1	SDP answer from MTSI client in terminal when narrowband speech is negotiated	260
A.14.3.2	SDP answer from MTSI client in terminal when up to wideband speech is negotiated	260
A.14.3.3	SDP answer from MTSI client in terminal when only wideband speech is negotiated	261
A.14.3.4	SDP answer from MTSI client in terminal when up to super-wideband speech is negotiated	261
A.14.3.5	SDP answer from MTSI client in terminal when only super-wideband speech is negotiated	261
A.14.3.6	SDP answer from MTSI client in terminal using WLAN	262
A.14.3.7	SDP answer from MTSI client in terminal supporting dual-mono	262
A.14.3.8	SDP answer from MTSI client in terminal supporting dual-mono for send direction	262
A.14.3.9	SDP answer from MTSI client in terminal when SC-VBR is negotiated	263
A.14.4	SDP answers from MTSI client in terminal using fixed access	263
A.14.4.1	SDP answer from MTSI client in terminal using fixed access when narrowband speech is negotiated ...	263
A.14.4.2	SDP answer from MTSI client in terminal using fixed access when only wideband speech is negotiated	264
A.14.4.3	SDP answer from MTSI client in terminal using fixed access when only super-wideband speech is negotiated	264
Annex B (informative): Examples of adaptation scenarios		266
B.1	Video bitrate adaptation	266
Annex C (informative): Example adaptation mechanisms for speech		267
C.1	Example of feedback and adaptation for speech and video	267
C.1.1	Introduction	267
C.1.2	Signalling state considerations	268
C.1.3	Adaptation state machine implementations	270
C.1.3.1	General	270
C.1.3.2	Adaptation state machine with four states	272
C.1.3.3	Adaptation state machine with four states (simplified version without frame aggregation)	275
C.1.3.4	Adaptation state machine with two states	277
C.1.3.5	Adaptation when using ECN	278
C.2	Example criteria for video bit rate feedback and adaptation	280
C.2.1	Introduction	280
C.2.2	Media sender side	281
C.2.3	Media receiver side	281
C.2.4	Video encoder bitrate adaptation, down-switch	281
C.2.5	Video encoder bitrate adaptation, receiver-driven up-switch	283
C.2.6	Video encoder bitrate adaptation, recovery phase	283
Annex D (informative): Reference delay computation algorithm		285
Annex E (informative): QoS profiles		287
E.1	General	287
E.2	Bi-directional speech (AMR12.2, IPv4, RTCP and MBR=GBR bearer)	287
E.3	Void	288
E.4	Bi-directional real-time text (3 kbps, IPv4 or IPv6, RTCP and MBR=GBR bearer)	289
E.5	Bi-directional speech (AMR-WB23.85, IPv4, RTCP and MBR=GBR bearer)	291
E.6	Bi-directional video (H.264 AVC level 1.1, 192 kbps, IPv4, RTCP and MBR=GBR bearer)	291
E.7	Bi-directional speech (AMR12.2, IPv6, RTCP and MBR=GBR bearer)	292
E.8	Bi-directional speech (AMR-WB23.85, IPv6, RTCP and MBR=GBR bearer)	293
E.9	Void	294
E.10	Bi-directional video (H.264 AVC level 1.1, 192 kbps, IPv6, RTCP and MBR=GBR bearer)	294

E.11	Bi-directional speech (AMR, IPv4, RTCP and MBR>GBR bearer).....	295
E.12	Bi-directional speech (AMR-WB, IPv4, RTCP and MBR>GBR bearer).....	296
E.13	Void.....	297
E.14	Bi-directional video (H.264 AVC level 1.1, IPv4, RTCP and MBR>GBR bearer).....	297
E.15	Bi-directional speech (AMR, IPv6, RTCP and MBR>GBR bearer).....	298
E.16	Bi-directional speech (AMR-WB, IPv6, RTCP and MBR>GBR bearer).....	299
E.17	Void.....	300
E.18	Bi-directional video (H.264 AVC level 1.1, IPv6, RTCP and MBR>GBR bearer).....	300
E.19	Bi-directional video (H.264 AVC level 1.2, 384 kbps, IPv4, RTCP and MBR=GBR bearer).....	301
E.20	Bi-directional video (H.264 AVC level 1.2, 384 kbps, IPv6, RTCP and MBR=GBR bearer).....	302
E.21	Bi-directional video (H.264 AVC level 1.2, IPv4, RTCP and MBR>GBR bearer).....	304
E.22	Bi-directional video (H.264 AVC level 1.2, IPv6, RTCP and MBR>GBR bearer).....	307
E.23	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 500 kbps, IPv6, RTCP and MBR=GBR bearer).....	308
E.24	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 500/40 kbps, IPv6, RTCP and MBR>GBR bearer).....	309
E.25	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 600 kbps, IPv6, RTCP and MBR=GBR bearer).....	310
E.26	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 600/40 kbps, IPv6, RTCP and MBR>GBR bearer).....	311
E.27	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 650 kbps, IPv6, RTCP and MBR=GBR bearer).....	312
E.28	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 650/40 kbps, IPv6, RTCP and MBR>GBR bearer).....	313
E.29	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 750 kbps, IPv6, RTCP and MBR=GBR bearer).....	314
E.30	Bi-directional video (H.265 (HEVC) Main profile, Main tier, level 3.1, 750/40 kbps, IPv6, RTCP and MBR>GBR bearer).....	315
E.31	Bi-directional speech (EVS 13.2, IPv4, RTCP and MBR=GBR bearer).....	316
E.32	Bi-directional speech (EVS 24.4, IPv4, RTCP and MBR=GBR bearer).....	317
E.33	Bi-directional speech (EVS 13.2, IPv6, RTCP and MBR=GBR bearer).....	318
E.34	Bi-directional speech (EVS 24.4, IPv6, RTCP and MBR=GBR bearer).....	319
Annex F (Normative):	Void.....	321
Annex G (Normative):	DTMF events.....	322
G.1	General.....	322
G.2	Encoding of DTMF signals.....	322
G.3	Session setup.....	322
G.4	Data transport.....	323
Annex H (informative):	Network Preference Management Object Device Description Framework.....	325

Annex I (informative):	QoE Reporting Management Object Device Description Framework ...	326
Annex J (informative):	Media Adaptation Management Object Device Description Framework	327
Annex K (informative):	Computation of b=AS for AMR and AMR-WB	328
K.1	General	328
K.2	Procedure for computing the bandwidth	328
K.3	Computation of RTP payload size.....	328
K.4	Detailed computation	329
Annex L (Normative):	Facsimile transmission	338
L.1	General	338
L.2	FoIP support in MTSI clients	338
L.2.1	FoIP support in MTSI client in terminal	338
L.2.2	FoIP support in MTSI MGW	338
L.2.3	Recommended configuration.....	338
L.3	Session setup	339
L.3.1	Session setup for any MTSI client supporting facsimile transmission	339
L.3.2	Session setup when the recommended profile is supported	339
L.4	Data transport using UDP/IP	340
L.5	CS GERAN inter-working	340
L.6	PSTN inter-working	341
L.7	SDP examples	341
L.7.1	Facsimile-only session	341
Annex M (informative):	IANA registration information for SDP attributes.....	343
M.1.	Introduction	343
M.2	3gpp_sync_info	343
M.3	3gpp_MaxRecvSDUSize.....	343
M.4	3gpp_mtsi_app_adapt.....	344
M.5	predefined_ROI.....	344
M.6	bw-info	345
Annex N (informative):	Computation of b=AS for Video Codec	347
N.1	General	347
N.2	Examples	347
Annex O (informative):	IANA registration information for RTP Header Extensions.....	348
O.1.	Introduction	348
O.2	urn:3gpp:video-orientation	348
O.3	urn:3gpp:video-orientation:6.....	348
O.4	urn:3gpp:roi-sent	349
O.5	urn:3gpp:predefined-roi-sent.....	349
Annex P (informative):	Video packet loss handling operation principles and examples	350
P.1	General	350