

Final draft **ETSI EN 303 423** V1.3.0 (2021-04)



**Environmental Engineering (EE);  
Electrical and electronic household and office equipment;  
Measurement of networked standby power consumption of  
Interconnecting equipment**

<https://standards.iteh.ai/catalog/standards/sist/acf29f3e-76fe-4f7a-9053-3d7e4eb5ba50/etsi-en-303-423-v1-3-0-2021-04>

---

**Reference**REN/EE-007005

---

**Keywords**customer premises networks, energy efficiency,  
network, power measurement**ETSI**650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° w061004871

---

**Important notice**

---

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

---

**Notice of disclaimer & limitation of liability**

---

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

---

**Copyright Notification**

---

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.  
All rights reserved.

# Contents

Intellectual Property Rights .....	5
Foreword.....	5
Modal verbs terminology.....	6
Introduction .....	6
1 Scope .....	7
1.1 Equipment in the scope of the present document .....	7
1.2 Equipment not in the scope of the present document .....	7
2 References .....	7
2.1 Normative references .....	7
2.2 Informative references.....	8
3 Definition of terms, symbols and abbreviations.....	9
3.1 Terms.....	9
3.2 Symbols.....	10
3.3 Abbreviations .....	10
4 Information required for testing purposes .....	10
4.1 Information about networked port(s).....	10
4.2 Power management function - periods & conditions .....	11
4.3 Activation and deactivation of wireless network connections.....	11
5 Measurement conditions.....	11
5.1 Common requirements .....	11
5.2 Test room.....	12
5.3 Power supply .....	12
5.4 Power measuring instruments.....	12
5.5 Configuration of network ports.....	12
5.6 Measurement uncertainty .....	14
6 Measurement procedures.....	15
6.1 General .....	15
6.2 Wireless network port management .....	15
6.2.0 General.....	15
6.2.1 Test sequence.....	15
6.2.2 Verifying that wireless connections are deactivated.....	15
6.2.3 Verifying that wireless logical network port is active.....	15
6.3 Preparation of the EUT and general testing aspects .....	15
6.4 Power management, reactivation and networked standby power consumption .....	16
6.5 Measurement of standby power consumption with all network ports disconnected .....	17
6.6 Measurement of networked standby power consumption with all network ports connected .....	17
7 Test report .....	17
7.1 Test and laboratory details.....	17
7.2 Details of product under test.....	17
7.3 Test parameters and network configuration .....	18
7.4 Measured and documented data .....	18
<b>Annex A (informative): Relationship between the present document and the ecodesign requirements of Commission Regulation (EC) No 1275/2008, as amended by Commission Regulation (EU) No 801/2013.....</b>	<b>19</b>
<b>Annex B (informative): Equipment classification .....</b>	<b>22</b>
B.1 General .....	22
<b>Annex C (informative): General information on network technologies and network configurations with respect to power consumption .....</b>	<b>24</b>

C.1	Examples of network port configuration.....	24
<b>Annex D (informative):</b>	<b>Information to be provided to the user and other interested parties.....</b>	<b>25</b>
D.1	Information to be provided to the user and other interested parties .....	25
D.1.1	Information available on-line .....	25
D.1.2	Information available in the user manual .....	25
<b>Annex E (informative):</b>	<b>Example of a test report template .....</b>	<b>26</b>
<b>Annex F (informative):</b>	<b>Bibliography.....</b>	<b>28</b>
<b>Annex G (informative):</b>	<b>Change history .....</b>	<b>29</b>
History .....		30

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[ETSI EN 303 423 V1.3.0 \(2021-04\)](https://standards.iteh.ai/catalog/standards/sist/acf29f3e-76fe-4f7a-9053-3d7e4eb5ba50/etsi-en-303-423-v1-3-0-2021-04)

<https://standards.iteh.ai/catalog/standards/sist/acf29f3e-76fe-4f7a-9053-3d7e4eb5ba50/etsi-en-303-423-v1-3-0-2021-04>

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

ITEH STANDARD PREVIEW  
(standards.iteh.ai)

## Foreword

ETSI EN 303 423 V1.3.0 (2021-04)

This final draft Harmonised European Standard (EN) has been produced by ETSI Technical Committee Environmental Engineering (EE), and is now submitted for the Vote phase of the ETSI standards EN Approval Procedure.

The present document has been prepared under the Commission's standardisation request M/544, C(2015) 9468 final of 5 January 2016, to the European standardisation organizations as regards ecodesign requirements for networked standby in support of Regulation (EC) No 1275/2008 [i.1] and Regulation (EC) No 642/2009 [i.10] (see note 2), to provide one voluntary means of conforming to the ecodesign requirements on networked standby of the following:

- Commission Regulation (EC) No 1275/2008 [i.1] of 17 December 2008 implementing Directive 2005/32/EC of the European Parliament and of the Council with regard to ecodesign requirements for standby and off mode, and networked standby, electric power consumption of electrical and electronic household and office equipment; and
- Commission Regulation (EC) No 642/2009 [i.10] of 22 July 2009, implementing Directive 2005/32/EC of the European Parliament and of the Council with regard to ecodesign requirements for televisions.

NOTE 1: Regulation (EC) No 1275/2008 [i.1] and Regulation (EC) No 642/2009 [i.10] were amended by Commission Regulation (EU) No 801/2013 [i.2] of 22 August 2013.

NOTE 2: Commission Regulation (EC) No 642/2009 [i.10] of 22 July 2009, implementing Directive 2005/32/EC of the European Parliament and of the Council with regard to ecodesign requirements for televisions is quoted in the introduction of annex A, but no relationship with the present document and the requirements of Commission Regulation (EC) No 642/2009 are provided because televisions are out of scope of the present document.

Once the present document is cited in the Official Journal of the European Union under that Regulation, compliance with the normative clauses of the present document given in table A.1 confers, within the limits of the scope of the present document, a presumption of conformity with the corresponding ecodesign requirements of that Regulation and associated EFTA Regulations.

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	18 months after doa

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

## Introduction

The methods defined in the present document are intended to define requirements for the measurement of the power consumed by the interconnecting equipment having one or more wired or wireless networked port(s) able to resume a function by way of a remotely initiated trigger or reactivation trigger from a network connection. The present document also provides a method to test power management and whether it is possible to deactivate wireless network connection(s).

For the measurement of low power modes, reference is made to EN 50564 [1].

[ETSI EN 303 423 V1.3.0 \(2021-04\)](#)

<https://standards.iteh.ai/catalog/standards/sist/acf29f3e-76fe-4f7a-9053-3d7e4eb5ba50/etsi-en-303-423-v1-3-0-2021-04>

---

# 1 Scope

## 1.1 Equipment in the scope of the present document

The present document specifies methods of measurement of electrical power consumption in networked standby and the reporting of the results for network interconnecting equipment.

Example of interconnecting equipment are in Annex B.

Power consumption in standby (other than networked standby) is covered by EN 50564 [1], including the input voltage range.

The present document also provides a method to test power management and whether it is possible to deactivate wireless network connection(s).

The present document applies to electrical products with a rated input voltage of 230 V a.c. for single phase products and 400 V a.c. for three phase products.

The present document is produced under the mandate M/544 and can be used to demonstrate compliance to the EU Regulation (EC) No 1275/2008 [i.1] amended by Regulation 801/2013 [i.2].

The present document does not apply to televisions as defined in Regulation (EC) No 642/2009 [i.10].

NOTE 1: The EU regulation 801/2013 [i.2] applies to equipment designed for use with a nominal voltage rating of 250 V and below.

NOTE 2: EU regulation 801/2013 [i.2] does not apply to electrical and electronic household and office equipment placed on the market with a low voltage external power supply to work as intended.

NOTE 3: "Low voltage external power supply" is the definition provided in EU regulation 278/2009 [i.3].

NOTE 4: The measurement of energy consumption and performance of equipment during intended use are generally specified in product standards and are not covered by the present document.

NOTE 5: Where the present document is referenced by more specific standards or procedures, these should define and name the relevant conditions to which this test procedure is applied.

## 1.2 Equipment not in the scope of the present document

The present document does not apply to the measurement of electrical power consumption in networked standby for edge equipment. The edge equipment is a networked equipment that can be connected to a network and interact with that network or other devices and that does not have, as its primary function, the passing of network traffic to provide a network. Edge equipment are covered in EN 50643 [i.8].

---

# 2 References

## 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] EN 50564:2011: "Electrical and electronic household and office equipment - measurement of low power consumption", produced by CENELEC.

## 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Commission Regulation (EC) No 1275/2008 of 17 December 2008 implementing Directive 2005/32/EC of the European Parliament and of the Council with regard to ecodesign requirements for standby and off mode electric power consumption of electrical and electronic household and office equipment.
- [i.2] Commission Regulation (EU) No 801/2013 of 22 August 2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions.
- [i.3] Commission Regulation (EC) No 278/2009 of 6 April 2009 implementing Directive 2005/32/EC of the European Parliament and of the Council with regard to ecodesign requirements for no-load condition electric power consumption and average active efficiency of external power supplies.
- [i.4] ETSI EN 301 575 (05-2012): "Environmental Engineering (EE); Measurement method for energy consumption of Customer Premises Equipment (CPE)".  
[https://standards.ietf.org/catalog/standards/sis/ac1295e-76fe-4f7a-9053-3e17-4eb5ba50/etsi\\_en\\_303\\_423\\_v1\\_3\\_0\\_2021\\_04](https://standards.ietf.org/catalog/standards/sis/ac1295e-76fe-4f7a-9053-3e17-4eb5ba50/etsi_en_303_423_v1_3_0_2021_04)
- [i.5] European Commission Directorate-General, Joint Research Centre: "Code Of Conduct on Energy Consumption of Broadband Communication Equipment"; Final V5: 20 December 2013.

NOTE: Available at [Broadband Communication Equipment Codes of Conduct | E3P \(europa.eu\)](https://ec.europa.eu/eip/eip3/eip3_broadband_communication_equipment_codes_of_conduct_en).

- [i.6] Cablelabs: "Data-Over-Cable Service Interface Specifications - DOCSIS® 2.0 Interface".
- [i.7] Cablelabs: "Data-Over-Cable Service Interface Specifications- DOCSIS® 3.0 Interface".
- [i.8] EN 50643: "Electrical and electronic household and office equipment - Measurement of networked standby power consumption of edge equipment", produced by CENELEC.
- [i.9] IEC 60050: "International Electrotechnical Vocabulary".
- [i.10] Commission Regulation (EC) No 642/2009 of 22 July 2009 implementing Directive 2005/32/EC of the European Parliament and of the Council with regard to ecodesign requirements for televisions.
- [i.11] IEC IEV ref 904-03-01: "Environmental standardization for electrical and electronic products and systems".

NOTE: Available at <http://www.electropedia.org/iev/iev.nsf/display?openform&ievref=904-03-01>.

- [i.12] IEEE 802.11™-2012: "IEEE Standard for Information technology -- Telecommunications and information exchange between systems Local and metropolitan area networks -- Specific requirements; Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications".



## 3 Definition of terms, symbols and abbreviations

### 3.1 Terms

For the purposes of the present document, the terms given in EN 50564 [1] and the following apply:

NOTE: When the present document is used to provide presumption of conformity to a European Directive or Regulation, definitions given in the Directive or Regulation prevail.

**edge equipment:** networked equipment that can be connected to a network and interact with that network or other equipment and that does not have, as its primary function, the passing of network traffic to provide a network

NOTE: Examples of edge equipment are given in Annex B.

**interconnecting equipment:** networked equipment that has, as its primary function, the passing of network traffic to provide a network

NOTE: Examples of interconnecting equipment are given in Annex B.

**logical network port:** network technology running over a physical network port

NOTE 1: EU Commission Regulation No 801/2013 [i.2] definition.

NOTE 2: Different communication protocols result in different network technologies.

**low voltage external power supply:** external power supply with a nameplate output voltage of less than 6 volts and a nameplate output current greater than or equal to 550 milliamperes

NOTE: EC Commission Regulation No 278/2009 [i.3] definition.

**network:** communication infrastructure with a topology of links, an architecture, including the physical components, organizational principles, communication procedures and formats (protocols)

NOTE: EU Commission Regulation No 801/2013 [i.2] definition.

**network availability:** capability of the equipment to resume functions after a remotely initiated trigger has been detected by a network port

NOTE: EU Commission Regulation No 801/2013 [i.2] definition.

**network port:** wired or wireless physical interface of the network connection located on the equipment through which the equipment can be remotely activated

NOTE 1: EU Commission Regulation No 801/2013 [i.2] definition.

NOTE 2: The International Electrotechnical Vocabulary (IEC 60050 [i.9]) defines "port (of a network)" as: "*a termination through which signals can enter or leave a network*".

**networked equipment:** equipment that can connect to a network and has one or more network ports

NOTE: EU Commission Regulation No 801/2013 [i.2] definition.

**networked standby:** condition in which the equipment is able to resume a function by way of a remotely initiated trigger from a network connection

NOTE: EU Commission Regulation No 801/2013 [i.2] definition.

**physical network port:** physical (hardware) medium of a network port. A physical network port can host two or more network technologies

NOTE 1: EU Commission Regulation No 801/2013 [i.2] definition.

NOTE 2: A "physical network port" can consist of multiple "logical network ports".

**power management:** automatic control mechanism that achieves the smallest input power consistent with a pre-determined level of functionality

NOTE: Source: IEV 904-03-01 [i.11], modified by omission of the note to entry.

**reactivation trigger:** signal that brings the equipment back to active mode

NOTE: The reactivation may be remotely initiated.

**remotely initiated trigger:** signal that comes from outside the equipment via a network

NOTE: EU Commission Regulation No 801/2013 [i.2] definition.

## 3.2 Symbols

Void.

## 3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ADSL	Asymmetric Digital Subscriber Line
ADSL2plus	Second generation ADSL with extended bandwidth
AP	Access Point
CRC	Cyclic Redundancy Check
DOCSIS®	Data Over Cable Service Interface Specification
DSL	Digital Subscriber Line
EFTA	European Free Trade Association
EPON	Ethernet Passive Optical Network
EUT	Equipment Under Test
FXS	Foreign eXchange Station
GPON	Gigabyte Passive Optical Network
HiNA	High Network Availability
HPNA	Home Phoneline Networking Alliance
LAN	Local Area Network
MoCA	Multimedia over Coax Alliance
POF	Plastic Optical Fibber
PSD	Power Spectral Density
QAM	Quadrature Amplitude Modulation
RF	Radio Frequency
USB	Universal Serial Bus
VDSL	Very high speed Digital Subscriber Line
VDSL2	Second generation VDSL
WAN	Wide Area Network
WiMAX	Worldwide interoperability for Microwave Access
XG-PON	10-Gigabit-capable Passive Optical Network

---

## 4 Information required for testing purposes

### 4.1 Information about networked port(s)

For each type of physical and associated logical networked port, the following information shall be provided by the manufacturer:

- a) the default time after which the power management function, or a similar function, automatically switches the equipment into networked standby, and if available, the procedure for:
  - 1) setting a time shorter than the default time; and/or

- 2) manually switching the equipment into networked standby;
- b) the characteristics of the reactivation trigger (message, signal, etc.) that is used to reactivate the equipment when in networked standby and how to remotely initiate it;
- c) the maximum performance specifications, e.g. the maximum speed or data rate supported by that networked port;
- d) the (maximum) power consumption of the equipment in a condition providing networked standby into which power management function, or a similar function, will switch the equipment, if only this port is used for remote activation, e.g. the declared power consumption of the equipment under defined conditions for a type of port;
- e) the communication protocol used by equipment;
- f) the radio frequency range at which each radio wireless logical network port operates;
- g) the characteristics of wireless logical network ports other than radio wireless logical network ports.

NOTE: Annex D describes examples of product information for network equipment.

## 4.2 Power management function - periods & conditions

The manufacturer shall provide information on:

- whether the equipment under test provides a power management or a similar function. If the EUT does not provide power management or a similar function, the manufacturer shall indicate why such a function would be inappropriate for the intended use;
- the default period of time after which the power management function, or a similar function, switches the equipment automatically into a condition providing networked standby.

NOTE: According to European Regulation No 1275/2008 [1] (as amended by EU Regulation No 801/2013 [2]), the maximum default period is given as 20 minutes during which the equipment has not been providing its main function. [etsi-en-303-423-v1-3-0-2021-04](https://standards.iteh.ai/catalog/standards/etsi-en-303-423-v1-3-0-2021-04)

## 4.3 Activation and deactivation of wireless network connections

The manufacturer shall provide information on the procedure the user needs to follow in order to activate and deactivate each wireless network connection, if any.

The above requirement does not apply to equipment which relies on a single wireless network connection for intended use and does not have a wired network connection.

---

# 5 Measurement conditions

## 5.1 Common requirements

The general conditions for measurements specified in clause 4.1 of EN 50564 [1] shall apply.

The tests described in clause 6 of the present document shall be repeated, if applicable, for each type of network port.

Each type of logical network port (as declared by the manufacturer) using the same physical network port shall be tested.

Where the manufacturer declares that multiple physical network ports have the same technical and logical specification(s), tests shall be executed with any one of these physical network ports being connected (the other ones being deactivated for wireless network ports and disconnected for wired network ports).

When a logical network port, as declared by the manufacturer, supports multiple editions of a communication technology standard (e.g. for backward compatibility), the logical network port is tested only according to the specifications of the latest standard edition used by the EUT for retrieving a reactivation message. Examples are shown in Annex C.

**NOTE:** Some devices can be designed to switch to a lower data rate during networked standby in order to further reduce energy consumption.

In order to restrict influence of external factors, the reactivation trigger shall be initiated within a local test network without external network connections. In the case that a network connection external to the local test network is necessary for remote activation, this external network connection shall be established and maintained during testing so that the reactivation trigger can be received; where identified in the information provided by the manufacturer (see clause 4), the stability of this external network connection may be checked or monitored.

**EXAMPLE 1:** External factors can be maintenance, information/software update or a denial of service attack.

**EXAMPLE 2:** External network connections can be WAN, cable network, satellite link, etc.

## 5.2 Test room

The requirements specified in clause 4.2 of EN 50564 [1] shall apply.

## 5.3 Power supply

The requirements specified in clause 4.3 of EN 50564 [1] shall apply.

## 5.4 Power measuring instruments

The requirements specified in clause 4.4 of EN 50564 [1] shall apply.

## 5.5 Configuration of network ports

When testing only one type of network port, the procedure given in clause 6 shall apply. The network ports of the equipment under test, other than the network port under test shall be deactivated for wireless network ports and disconnected for wired network ports, if possible. Logical network ports which can only be activated and deactivated together shall be tested together following the same procedures used for individual network ports.

**NOTE:** If a product relies on active wired connection(s) to one or more network port(s) for the intended use, manual deactivation of these network port(s) is allowed instead of physical wire disconnection. The manual deactivation demands manual activation of network port(s) to resume the operational state of the device. As an example some of the technologies that are always relayed on downstream reception like DOCSIS, DSL starts continuous carrier scanning in respective frequency bands to recover its lost connection and consequently the measured power consumption is not representative of the real power consumption of the device; when it is in networked standby.

The network port under test shall have networked standby functionality enabled and shall be connected to the appropriate test equipment which will form the network configuration for the test. In case more than one type of reactivation trigger is available per type of network port to reactivate the equipment under test when in networked standby, the configuration resulting in the highest power consumption in networked standby shall be determined, as given below:

- a) At least once, all configurations shall be set-up with the information provided according clause 4.1 and tested following the procedure given in clause 6 to determine the related power consumption to determine the configuration with the highest power consumption.
- b) When the configuration with the reactivation trigger resulting in the highest power consumption in networked standby is known, this configuration shall be selected to conduct the measurement. The source of this information shall be additionally given in the test report.