



Satellite Earth Stations and Systems (SES); GNSS based location systems; Part 1: Functional requirements

iTeh STANDARDS PREVIEW
(standards.iteh.ai)
Full standard/standards catalog
https://standards.iteh.ai/catalog/standards/sis/2c95ef60-3eac-469c-b090-89b6b833edfd/etsi-ts-103-246-1-2020-10

Reference

RTS/SES-00451

Keywords

functional, GNSS, location, navigation, receiver, requirements, satellite, system, terminal

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

| | |
|---|-----------|
| Intellectual Property Rights | 4 |
| Foreword..... | 4 |
| Introduction | 4 |
| Modal verbs terminology..... | 5 |
| 1 Scope | 6 |
| 2 References | 6 |
| 2.1 Normative references | 6 |
| 2.2 Informative references..... | 6 |
| 3 Definition of terms, symbols and abbreviations..... | 7 |
| 3.1 Terms..... | 7 |
| 3.2 Symbols..... | 10 |
| 3.3 Abbreviations | 10 |
| 4 Context description | 11 |
| 4.1 Location based applications requirements..... | 11 |
| 4.1.1 Reminder of ETSI TR 103 183 content | 11 |
| 4.1.2 Common requirements..... | 11 |
| 4.1.3 Specific requirements | 11 |
| 4.2 Generic location-based application use case | 13 |
| 4.3 GNSS-based location systems | 15 |
| 5 Functional requirements for GNSS-based Location system..... | 16 |
| 5.1 Functional requirements outline | 16 |
| 5.2 Mandatory requirements..... | 16 |
| 5.2.1 Positioning techniques | 16 |
| 5.2.2 Location-related data delivery | 16 |
| 5.2.3 Location system policies | 17 |
| 5.3 Requirements for optional features | 17 |
| 5.3.1 Positioning techniques | 17 |
| 5.3.2 Location-related data content..... | 17 |
| 5.3.3 Location-related data delivery | 18 |
| 5.4 GBLS Functional requirements summary | 19 |
| Annex A (informative): Common positioning techniques..... | 20 |
| A.1 GNSS methods | 20 |
| A.2 Assisted-GNSS methods | 20 |
| A.3 Differential GNSS methods..... | 21 |
| A.3.1 General | 21 |
| A.3.2 D-GNSS | 22 |
| A.3.3 RTK..... | 22 |
| A.3.4 NRTK..... | 23 |
| A.3.5 PPP..... | 24 |
| A.4 Mixing GNSS and telecommunication positioning techniques..... | 25 |
| A.4.1 Proximity sensing..... | 25 |
| A.4.2 Multilateration..... | 25 |
| A.4.3 Triangulation | 27 |
| A.5 Multi-sensor positioning through GNSS or Assisted/Differential GNSS hybridization | 27 |
| Annex B (informative): GBLS High level functional analysis..... | 29 |
| History | 30 |

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Satellite Earth Stations and Systems (SES).

The present document is part 1 of a multi-part deliverable covering the GNSS based location systems, as identified below:

- Part 1: "**Functional requirements**";
- Part 2: "Reference Architecture";
- Part 3: "Performance requirements";
- Part 4: "Requirements for location data exchange protocols";
- Part 5: "Performance Test Specification".

Introduction

The increasing expansion of location-based applications aims to satisfy more and more complex and diversified user requirements: this is highlighted for example by the widespread adoption of multi-functional smart-phones or by the ever wider adoption of tracking devices (e.g. in transport), etc. This requirement for new and innovative location-based applications is generating a requirement for increasingly complex location systems.

The wide spectrum of location-based applications identified in ETSI TR 103 183 [i.1] calls for a new and broader concept for location systems, taking into account solutions in which GNSS technologies are complemented with other technologies to improve robustness and performance. The notion of **GNSS-based location systems** is introduced and defined in the present document.

Additional clauses and information related to the implementation in **GNSS-based location systems** of the various differential GNSS technologies, namely D-GNSS, RTK and PPP are also included in order to facilitate the use of this set of standards by manufacturers and service providers.

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are **NOT** allowed in ETSI deliverables except when used in direct citation.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/2c109fd0-3eac-469c-b090-89b6b833edfd/etsi-ts-103-246-1-v1.3.1-2020-10>

1 Scope

The present document defines the functional requirements applicable to location systems, based on a summary of types of applications relying on location-related data provided by location systems.

The present document can be considered as the Stage 1 characterization of location systems according to the ITU/3GPP approach [i.2].

ETSI TS 103 246 parts 2 [i.14], 3 [i.15], 4 [i.16] and 5 [i.17] address integrated GNSS based location systems (GBLS) that combine Global Navigation Satellite Systems (GNSS), with other navigation technologies, as well as with telecommunication networks in order to deliver location-based services to users. As a consequence the present document is not applicable to GNSS only receivers.

ETSI TS 103 246 parts 2 [i.14], 3 [i.15], 4 [i.16] and 5 [i.17] propose a list of functional and performance requirements and related test procedures. For each performance requirement, different classes are defined allowing the benchmark of different GNSS Based Location Systems (GBLS) addressing the same applications. The requirements are intended to address the growing use of complex location systems required for the provision of location-based applications particularly for the mass-market (refer to ETSI TR 103 183 [i.1]).

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

Not applicable.

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI TR 103 183: "Satellite Earth Stations and Systems (SES); Global Navigation Satellite Systems (GNSS) based applications and standardisation needs".
- [i.2] Recommendation ITU-T I.130: "Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN".
- [i.3] IS-GPS-200K: "Navstar GPS Space Segment/Navigation User Segment Interfaces".
- [i.4] IS-GPS-705F: "Navstar GPS Space Segment/User Segment L5 Interfaces".
- [i.5] IS-GPS-800F: "Navstar GPS Space Segment/User Segment L1C Interfaces".

- [i.6] "European GNSS (Galileo) Open Service: Signal In Space Interface Control Document", Issue 1.3.
- [i.7] "Global Navigation Satellite System GLONASS Interface Control Document", Version 5.1.
- [i.8] DTFA01-96-C-00025: "Specification for the Wide Area Augmentation System (WAAS)", US Department of Transportation, Federal Aviation Administration.
- [i.9] RTCA DO-229E: "Minimum Operational Performance Standards for Global Positioning System/Satellite-Based Augmentation System Airborne Equipment", SBAS ICD Annex 1.
- [i.10] IS-QZSS-PNT-003: "Quasi-Zenith Satellite System Interface Specification Satellite Positioning, Navigation and Timing Service", Revision 003.
- [i.11] BDS-SIS-ICD-B1I-3.0: "BeiDou Navigation Satellite System Signal In Space Interface Control Document; Open Service Signal B1I (Version 3.0)".
- [i.12] BDS-SIS-ICD-B1C-1.0: "BeiDou Navigation Satellite System Signal In Space Interface Control Document; Open Service Signal B1C (Version 1.0)".
- [i.13] ISRO-IRNSS-ICD-SPS-1.1: "Signal In Space ICD For Standard Positioning Service Version 1.1".
- [i.14] ETSI TS 103 246-2: "Satellite Earth Stations and Systems (SES); GNSS based location systems; Part 2: Reference Architecture".
- [i.15] ETSI TS 103 246-3: "Satellite Earth Stations and Systems (SES); GNSS based location systems; Part 3: Performance requirements".
- [i.16] ETSI TS 103 246-4: "Satellite Earth Stations and Systems (SES); GNSS based location systems; Part 4: Requirements for location data exchange protocols".
- [i.17] ETSI TS 103 246-5: "Satellite Earth Stations and Systems (SES); GNSS based location systems; Part 5: Performance Test Specification".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document the following terms apply:

Accumulated Delta (or Doppler) Range (ADR): pseudorange-rate measurement using the carrier which measures the instantaneous phase of the signal (modulo 1 cycle) plus some arbitrary number of integer cycles

NOTE: Once the receiver is tracking the satellite, the integer number of cycles correctly accumulates the change in range seen by the receiver. Also see carrier phase measurement.

accuracy (or error): difference between a measured or estimated value and its real value

authentication: process/protocol to provide authenticity

authenticity: assurance that the location-related data associated with a location target has been derived from real and not falsified signals

availability: percentage of time when a location system is able to provide the required location-related data

carrier phase measurement: measure of the range between the satellite and receiver expressed in units of cycles of the carrier frequency

continuity: likelihood that the location system functionality will be available during the complete duration of the intended operation if the system is operational at the beginning of the operation

D-GNSS: technique aiming at enhancing position accuracy and integrity of a GNSS receiver by using differential pseudo range corrections and "do not use flag" for faulty satellites delivered by a GNSS reference station located at a known location

NOTE: In the present document, the term D-GNSS refers to conventional differential GNSS.

electromagnetic interference: any source of RF transmission that is within the frequency band used by a communication link, which degrades the performance of this link

fraud: any kind of activity of a location-based application stakeholder aiming at jeopardizing the application objective

GNSS-Based Location System (GBLS): location system using GNSS as the primary source of positioning

GNSS only receiver: location receiver using GNSS as the unique source of positioning

data integrity: assurance that the consistency of data is guaranteed

integrity (equivalent to "location integrity" in GBLS context): measure of the trust in the accuracy of the location-related data provided by the location system and the ability to provide timely and valid warnings to users when the location system does not fulfil the condition for intended operation

NOTE: Integrity is expressed through the computation of a protection level. The Integrity function is designed to deliver a warning (or alert) of any malfunction to users within a given period of time (time-to-alert). Related to the Integrity concept, a Loss of Integrity event occurs when an unsafe condition (i.e. a positioning error higher than the protection level) occurs without a warning to the users for a time longer than the time-to-alert limit.

jamming: deliberate transmission of interference in order to disrupt communications

NOTE: In the present technical context, targeted communication signals are GNSS or telecommunication signals.

latency: measure of the time elapsed between the event triggering the determination of the location-related data for a location target and the availability of the location-related data at the user interface

location-based application: application which is able to deliver a service to one or several users, built on the processing of the location information (location-related data) related to one or several targets

location-related data: set of data associated with a given location target, containing one or several of the following time-tagged information elements: target position, target motion indicators (velocity and acceleration), quality of service indicators (estimates of the position accuracy, reliability or authenticity)

location system: system responsible for providing to a location based application the location-related data of one or several location targets

location target: physical entity (mobile or stationary) whose position is the focus of the location related data to be built by the location system

Precise Point Positioning (PPP): differential GNSS technique that uses a worldwide distributed network of reference stations to provide, in quasi real time, a highly accurate geodetic positioning of a receiver

privacy: function of a location system that aims at ensuring that the location target user private information (identity, bank accounts, etc.) and its location-related data cannot be accessed by a non-authorized third party

Protection Level (PL): upper bound to the position error such that: $P(\epsilon > PL) < I_{\text{risk}}$, where I_{risk} is the Integrity risk and ϵ is the actual position error

NOTE: The protection level is provided by the location system, and with the integrity risk, is one of the two sub-features of the integrity system. The protection level is computed both in the vertical and in the horizontal position domain and it is based on conservative assumptions that can be made on the properties of the GNSS sensor measurements, i.e. the measurement error can be bounded by a statistical model and the probability of multiple simultaneous measurement errors can be neglected.

pseudo range: pseudo distance between a satellite and a navigation receiver computed by multiplying the propagation delay determined by the receiver with the speed of light

NOTE: The prefix "pseudo" highlights the fact that the propagation delay accessible to the receiver encompasses contributions (such as receiver local clock offset with respect to satellite time) which do not allow it to determine directly the actual geometrical distance.

Pseudo Range Correction (PRC): simple difference between a pseudo range measured by a GNSS reference station, set at a known location and the estimated range between the satellite and this known location

NOTE 1: The estimated range generally uses the computed satellite clock bias correction and may use the estimated receiver clock bias correction.

NOTE 2: The Pseudo Range Correction represents an estimate of the total GNSS systematic error observed on one satellite line-of-sight, comprising ionospheric delay, tropospheric delay and orbital bias residual error. It can be directly used in a local area around the reference station to cancel most of the systematic errors.

quality of service: set of indicators that can accompany the location target's position/motion information and is intended to reflect the quality of the information provided by the location system

NOTE: QoS indicators can include an accuracy estimate, a protection level statistic, the integrity risk, an authentication flag.

Real Time Kinematic (RTK): particular Differential GNSS technique that provides, in real time, highly accurate positioning of a target based on carrier phase measurements

NOTE 1: In the RTK context, the target is called the "rover", as opposed to the stationary reference station(s). RTK makes use of the carrier phase measurements, both in the reference station and in the rover, and this technique allows the ambiguities affecting these accurate measurements to be resolved.

NOTE 2: If the reference station is at an accurately known location, the rover can compute its accurate geodetic (or absolute) location. Alternatively, if the reference station's geodetic location is only roughly known, RTK can still provide high accuracy, but only on a relative and not absolute basis.

reference receiver: receiver placed at a known and surveyed position used for differential GNSS technique

NOTE: A reference receiver is an essential component of a reference station.

reference station: station placed at a known and surveyed position aiming at determining and sharing the systematic errors of at least one GNSS constellation

rover: target or location target, mainly used in the context of Differential GNSS/RTK

security: function of a location system that aims at ensuring that the location-related data is safeguarded against unapproved disclosure or usage inside or outside the location system, and that it is also provided in a secure and reliable manner that ensures it is neither lost nor corrupted

spoofing: transmission of signals intended to deceive location processing into reporting false target data

target: See location target.

terminal: target or location target, mainly used in the context of Assisted GNSS

terminal-assisted: mode in which the terminal performs only the GNSS measurements (pseudo ranges, pseudo Doppler, etc.) and sends these measurements to a remote central facility where the position calculation takes place

NOTE: This calculation may possibly use additional measurements or data from other sources (GNSS server assistance, differential GNSS services or non GNSS sensors etc.).

terminal-based: mode in which the terminal performs the GNSS measurements and calculates its own location

NOTE: This calculation may possibly use additional measurements or data from other sources (GNSS server assistance, differential GNSS services or non GNSS sensors etc.).

time-to-alert: time from when an unsafe integrity condition occurs to when an alerting message reaches the user

3.2 Symbols

Void.

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

| | |
|----------|---|
| 3GPP | 3 rd Generation Partnership Project |
| ADAS | Advanced Driver Assistance Systems |
| ADR | Accumulated Delta (or Doppler) Range |
| ADS-B | Automatic Dependent Surveillance – Broadcast |
| A-SMGCS | Advanced Surface Movement Guidance and Control System |
| ATC | Air Traffic Control |
| CID | Cell-ID |
| D-GNSS | Differential GNSS |
| E-CID | Enhanced Cell-ID |
| EGNOS | European Geostationary Navigation Overlay System |
| E-OTD | Enhanced Observed Time Difference |
| FKP | Flachen Korrektur Parameter (German) |
| GAGAN | GPS-Aided Geo-Augmented Navigation |
| GBLS | GNSS-Based Location Systems |
| GEO | Geostationary Earth Orbit |
| GLONASS | Global Navigation Satellite System (Russian based system) |
| GNSS | Global Navigation Satellite System |
| GPS | Global Positioning System |
| GSM | Global System for Mobile communications |
| INS | Inertial Navigation Sensor |
| IRNSS | Indian Regional Navigational Satellite System |
| IT | Information Technology |
| ITS | Intelligent Transport Systems |
| LAD-GNSS | Local Area Differential GNSS |
| LTE | Long Term Evolution |
| M&C | Monitoring and Control |
| MAC | Master Auxiliary Correction |
| MMI | Man-Machine Interface |
| MNO | Mobile Network Operator |
| MSAS | Multi-functional Satellite Augmentation System |
| NRTK | Network RTK |
| OBU | On-Board Unit |
| OSR | Observation State Representation |
| OTDOA | Observed Time Difference Of Arrival |
| PAYD | Pay As You Drive |
| PL | Protection Level |
| PPP | Precise Point Positioning |
| PRC | Pseudo-Range Correction |
| PVT | Position, Velocity and Time |
| QoS | Quality of Service |
| QZSS | Quasi-Zenith Satellite System |
| RF | Radio Frequency |
| RTCA | Radio Technical Commission for Aeronautics |
| RTK | Real Time Kinematic |
| SBAS | Satellite Based Augmentation System |
| SNR | Signal to Noise Ratio |
| SSR | Space State Representation |
| UDRE | User Differential Range Errors |
| UHF | Ultra High Frequency |
| UMTS | Universal Mobile Telecommunications System |
| UTDOA | Uplink Time Difference of Arrival |
| VHF | Very High Frequency |
| VRS | Virtual Reference Station |

| | |
|----------|-------------------------------|
| WAAS | Wide Area Augmentation System |
| WAD-GNSS | Wide Area Differential GNSS |
| WLAN | Wireless Local Area Network |

4 Context description

4.1 Location based applications requirements

4.1.1 Reminder of ETSI TR 103 183 content

ETSI TR 103 183 [i.1] provides a thorough inventory of the location based applications which is used as a reference in the present document. The present clause summarizes the classification work which was conducted in order to identify those applications driving the requirements.

These requirements were organized into two separate categories:

- Basic requirements common to all location-based applications.
- Additional specific requirements, only required by certain applications.

Examples of location based applications are given in table 4-1 (see clause 4.2).

4.1.2 Common requirements

Based on ETSI TR 103 183 [i.1], the following requirements were identified as shared by all location-based applications:

- Services remain available over a predefined service area.
- **Management of multiple end users:**
 - The application shall be used by one or multiple end users.
- **Management of the location targets:**
 - The application shall be able to cope with one or **multiple location targets**.
 - The application shall be able to cope with location target(s) distributed **arbitrarily** over a predefined service area.
 - The application shall be able to cope with location target(s) with **a priori unknown location-related data**.
- **Service policy:** the application shall implement mechanisms allowing the enforcement of service policy such as:
 - **Privacy protection policy** to protect the location target user identity (where relevant).
 - **Data protection policy** to control access to information identified as sensitive (through confidentiality, authentication and data integrity mechanisms).

4.1.3 Specific requirements

Application classes were established in ETSI TR 103 183 [i.1] by gathering location-based applications having the same differentiating requirement(s). An inventory of these requirements is summarized below in order to list the requirements specific to a subset of applications.