



SLOVENSKI STANDARD
oSIST prEN 303 648 V1.1.2:2020
01-junij-2020

Radijski sistemi z možnostjo preoblikovanja (RRS) - Arhitektura preoblikovanja radijske opreme (RE)

Reconfigurable Radio Systems (RRS) - Radio Equipment (RE) reconfiguration architecture

Ta slovenski standard je istoveten z: **ETSI EN 303 648 V1.1.2 (2020-03)**

ICS:

33.060.01	Radijske komunikacije na splošno	Radiocommunications in general
-----------	----------------------------------	--------------------------------

oSIST prEN 303 648 V1.1.2:2020 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/5edb531d-c8df-47cf-8dc2-703ad5cfea3b/osist-pren-303-648-v1.1.2-2020>

Draft ETSI EN 303 648 V1.1.2 (2020-03)



Reconfigurable Radio Systems (RRS); Radio Equipment (RE) reconfiguration architecture

ITeH STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sis/5e6931d-c8df-47cf-8dc2-703ad5cfea3b/osist-pren-303-648-v1.1.2-2020>

Reference

REN/RRS-0227

Keywords

architecture, radio, SDR

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	5
Foreword.....	5
Modal verbs terminology.....	5
1 Scope	6
2 References	6
2.1 Normative references	6
2.2 Informative references.....	6
3 Definition of terms, symbols and abbreviations.....	7
3.1 Terms.....	7
3.2 Symbols.....	10
3.3 Abbreviations	10
4 Architectural Reference Model for Reconfigurable Radio Equipment	11
4.1 Introduction	11
4.2 Reconfigurable Radio Equipment - Architecture Components for Radio Reconfiguration	12
4.2.1 High level description.....	12
4.2.2 Communication Services Layer (CSL).....	13
4.2.3 Radio Control Framework (RCF)	16
4.2.4 Unified Radio Application (URA).....	17
4.2.5 Architectural Components System Requirements mapping.....	17
4.3 Reconfigurable Radio Equipment - Architecture Reference Model for Multiradio Applications	17
4.3.1 High level description.....	17
4.3.2 Reference Model System Requirements mapping	19
4.4 Reconfigurable Radio Equipment - radio computer	19
4.4.1 High level description.....	19
4.4.2 radio computer System Requirement Mapping.....	22
4.5 Reconfigurable Radio Equipment - the Radio Virtual Machine.....	23
4.5.1 Radio Virtual Machine basic principles.....	23
4.5.2 RVM System Requirement Mapping.....	23
4.6 Reconfigurable Radio Equipment - Unified Radio Applications	24
4.6.1 Introduction.....	24
4.6.2 Distribution and Installation of RAP	24
4.6.3 Operational Structure of URA.....	31
4.6.4 URA System Requirement Mapping	35
4.7 Security architecture for reconfigurable Radio Equipment	35
4.7.1 Description.....	35
4.7.2 Security Components System Requirements mapping	36
5 Reference Points.....	38
5.1 Introduction	38
5.2 Reference Points required for Installation/uninstallation and creating/deleting an instance of a URA.....	39
5.3 Reference Points required for list checking of URA	39
5.3.1 Reference Points required for updating instance of URA	40
5.3.2 Reference Points required for configuring URA parameters.....	40
5.4 Reference Points required for activation/deactivation of URA	41
5.5 Reference Points required for transferring context information.....	41
5.6 Reference Points required for creating data flow and sending/receiving user data	42
5.7 Reference Points required for radio environment measurements	43
5.8 Reference Points required for reporting discovered peer equipment.....	43
5.9 Reference Points required for flexible data flow	44
5.10 Reference Points required for data flow control.....	44
5.11 Reference Points required for synchronizing radio time	45
5.12 Reference Points required for control of reconfigurable RF transceiver	45
5.13 Reference points required for security functions.....	46
6 Reconfigurable RE high level operating procedures.....	48

6.0	Introduction	48
6.1	Procedures for installation/uninstallation and creating/deleting instance of a URA	48
6.2	Procedures for list checking of URA.....	53
6.2.0	General.....	53
6.2.1	Procedures for updating instance of URA	54
6.2.2	Procedures for configuring URA parameters.....	56
6.3	Procedures for activation/deactivation of URA.....	57
6.4	Procedures for transferring context information.....	58
6.5	Procedure for creating data flow and sending/receiving user data	60
6.6	Procedures for radio environment measurements.....	65
6.7	Procedure for reporting discovered peer equipment.....	66
6.8	Procedure for flexible data flow	66
6.9	Procedure for data flow control	67
6.10	Procedure for synchronizing radio time	69
6.11	Procedure for control of reconfigurable RF transceiver	70
6.12	Procedure for RE Configuration Policy endorsement, distribution and validation	78
6.13	Procedure for configuration enforcement.....	80
6.14	Procedures for long-term management.....	82
Annex A (informative): Distributed Computations on Multiple radio computers.....		88
A.0	Introduction	88
A.1	Procedures of RA Distributed Installation on Multiple radio computers	88
History		89

iTeh STANDARD PREVIEW
 (standards.iteh.ai)
 Full standard:
<https://standards.iteh.ai/catalog/standards/sist/5eddb531d-c8dd-47cf-8dc2-703ad5cfea3b/osist-pren-303-648-v1.1.2-2020>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This draft European Standard (EN) has been produced by ETSI Technical Committee Reconfigurable Radio Systems (RRS), and is now submitted for the combined Public Enquiry and Vote phase of the ETSI standards EN Approval Procedure.

Proposed national transposition dates	
Date of latest announcement of this EN (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The scope of the present document is to define the radio reconfiguration related architecture for reconfigurable Radio Equipment except for reconfigurable mobile devices which are covered in ETSI EN 303 095 [i.4], ETSI EN 302 969 [i.9] to ETSI EN 303 146-4 [i.13]. The work is based on the system requirements defined in ETSI EN 303 641 [1] and the Use Cases defined in ETSI TR 103 062 [i.1], ETSI TR 102 944 [i.2], ETSI TR 103 585 [i.3].

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 303 641: "Reconfigurable Radio Systems (RRS); Radio Equipment (RE) reconfiguration requirements".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI TR 103 062: "Reconfigurable Radio Systems (RRS) Use Cases and Scenarios for Software Defined Radio (SDR) Reference Architecture for Mobile Device".
- [i.2] ETSI TR 102 944: "Reconfigurable Radio Systems (RRS); Use Cases for Baseband Interfaces for Unified Radio Applications of Mobile Device".
- [i.3] ETSI TR 103 585: "Reconfigurable Radio Systems (RRS); Radio Equipment (RE) reconfiguration use cases".
- [i.4] ETSI EN 303 095: "Reconfigurable Radio Systems (RRS); Radio reconfiguration related architecture for Mobile Devices (MD)".
- [i.5] Recommendation ITU-T M.60: "Maintenance Terminology and Definitions".
- [i.6] ETSI TS 103 436: "Reconfigurable Radio Systems (RRS); Security requirements for reconfigurable radios".
- [i.7] ETSI TR 103 087: "Reconfigurable Radio Systems (RRS); Security related use cases and threats".
- [i.8] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of Radio Equipment and repealing Directive 1999/5/EC.

- [i.9] ETSI EN 302 969: "Reconfigurable Radio Systems (RRS); Radio Reconfiguration related requirements for Mobile Devices".
- [i.10] ETSI EN 303 146-1: "Reconfigurable Radio Systems (RRS); Mobile Device (MD) information models and protocols; Part 1: Multiradio Interface (MURI)".
- [i.11] ETSI EN 303 146-2: "Reconfigurable Radio Systems (RRS); Mobile Device (MD) information models and protocols; Part 2: Reconfigurable Radio Frequency Interface (RRFI)".
- [i.12] ETSI EN 303 146-3: "Reconfigurable Radio Systems (RRS); Mobile Device (MD) information models and protocols; Part 3: Unified Radio Application Interface (URAI)".
- [i.13] ETSI EN 303 146-4: "Reconfigurable Radio Systems (RRS); Mobile Device (MD) information models and protocols; Part 4: Radio Programming Interface (RPI)".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the following terms apply:

Baseband Parameter Aggregation (BPA): unit collecting all the context information to be transferred to the monitor

NOTE: The BPA unit converts the context information into metric(s) such that a minimum bandwidth is consumed during the procedure of transferring the context information to the monitor. Those metrics may include Received Signal Strength Indication (RSSI) measurement, multi-RAT performance metrics, etc.

broadcast identifier (broadcast ID): identifier linking a data packet to all available radio computers

Communication Services Layer (CSL): layer related to communication services supporting generic applications

NOTE: A communication services layer supports generic applications like Internet access. In the present document, it consists of Administrator, Mobility Policy Manager (MPM), Networking stack and Monitor.

computational resources: part of Radio Equipment hardware working under OS control and on which Applications, among others, are executed

configcodes: result of compiling the source codes of a Radio Application (RA), which is either configuration codes of Radio Virtual Machine (RVM) or executable codes for a particular target platform

NOTE: In the case when RA provider makes a high level code based on a target platform, a result of compiling RA source codes is configcodes which is executable on the target platform. In the other case, when RA provider makes a high level code without considering a target platform, a result of front-end compiling of RA source codes is an Intermediate Representation (IR) which should be back-end compiled for operating on a specific target platform.

data flow: logical channel between Flow Controller (FC) and an Unified Radio Applications (URA) created by FC to send to or receive data elements (octets, packets or other granularity) from URA

distributed computations: computational model in which components located on networked computers communicate and coordinate their actions by passing messages interacting with each other in order to achieve a common goal

environmental information: set of values that can affect the execution of RAs on a radio computer

NOTE: Environmental Information consists of information related to the execution of RA(s), such as Buffer Overflow, Resource Allocation, etc.

Functional Block (FB): function needed for real-time implementation of RA(s)

NOTE 1: A functional block includes not only the modem functions in Layer1 (L1), Layer2 (L2), and Layer 3 (L3) but also all the control functions that should be processed in real-time for implementing given RA(s).

NOTE 2: Functional blocks are categorized into Standard Functional Blocks (SFBs) and User Defined Functional Blocks (UDFBs). In more details:

- 1) *SFB* can be shared by many RAs. For example, Forward Error Correction (FEC), Fast Fourier Transform (FFT)/Inverse Fast Fourier Transform (IFFT), (de)interleaver, Turbo coding, Viterbi coding, Multiple Input Multiple Output (MIMO), Beamforming, etc. are the typical category of standard functional block.
- 2) *UDFB* include those functional blocks that are dependent upon a specific RA. They are used to support special function(s) required in a specific RA or to support a special algorithm used for performance improvement. In addition, a user defined functional block can be used as a baseband controller functional block which controls the functional blocks operating in baseband processor in real-time and to control some context information processed in real-time.

NOTE 3: Each functional block has its unique name, Input, Output, and properties.

multicast identifier (multicast ID): identifier linking a data packet to a group of radio computers

NOTE: A group of radio computers consists of at least two radio computers. The way for implementing the radio computer grouping is the choice of the manufacturers.

peer equipment: any communication counterpart of a reconfigurable Radio Equipment

NOTE: The peer equipment can be reached by establishing a (logical) communications link (i.e. an association) between the reconfigurable Radio Equipment and peer equipment. Examples of peer equipment include Wide Local Area Network (WLAN) access points, Internet Protocol (IP) access nodes, etc.

Radio Application (RA): software which enforces the generation of the transmit RF signals or the decoding of the receive RF signals

NOTE 1: The Software is executed on a particular radio platform or an RVM as part of the radio platform.

NOTE 2: RAs might have different forms of representation. They are represented as:

- Source codes including Radio Library calls of Radio Library native implementation and Radio HAL calls;
- IRs including Radio Library calls of Radio Library native implementation and radio HAL calls;
- Executable codes for a particular radio platform.

radio computer: part of Radio Equipment working under ROS control and on which RAs are executed

NOTE 1: A radio computer typically includes programmable processors, hardware accelerators, peripherals, software, etc. RF part is considered to be part of peripherals.

NOTE 2: The Radio Platform is the hardware part of the radio computer.

Radio Control Framework (RCF): control framework which, as a part of the OS, extends OS capabilities in terms of radio resource management

NOTE: RCF is a control framework which consists of Configuration Manager (CM), Radio Connection Manager (RCM), Flow Controller (FC) and Multiradio Controller (MRC). The Resource Manager (RM) is typically part of OS.

Radio Controller (RC): functional component of RA for transferring context information from corresponding RAs to monitor

NOTE: A RC, which may operate in computational resources in non real-time, accesses RAs which operates in radio computer in real time. The monitor, to which the context information is transferred using RC, provides context information to Administrator and/or Mobility Policy Manager (MPM) for application(s) to be performed using the context information, for example, terminal-centric configuration.

Radio Equipment (RE): As defined in the Radio Equipment Directive, Article 2(1)(1) [i.8].

NOTE: Excerpt from the Radio Equipment Directive: "*radio equipment' means an electrical or electronic product, which intentionally emits and/or receives radio waves for the purpose of radio communication and/or radiodetermination, or an electrical or electronic product which must be completed with an accessory, such as antenna, so as to intentionally emit and/or receive radio waves for the purpose of radio communication and/or radiodetermination*".

radio frequency transceiver (RF transceiver): part of Radio Platform converting, for transmission, baseband signals into radio signals, and, for reception, radio signals into baseband signals

radio library: library of SFB that is provided by a platform vendor in a form of platform-specific executable code

NOTE 1: SFBs implement reference codes of functions which are typical for radio signal processing. They are not atomic and their source codes are typed and visible for RA developers.

NOTE 2: A SFB is implemented through a Radio Hardware Abstraction Layer (HAL) when the SFB is implemented on hardware accelerators. Radio HAL is part of ROS.

Radio Operating System (ROS): any appropriate OS empowered by RCF

NOTE: ROS provides RCF capabilities as well as traditional management capabilities related to management of RP such as resource management, file system support, unified access to hardware resources, etc.

radio platform: part of Radio Equipment hardware which relates to radio processing capability, including programmable hardware components, hardware accelerators, RF transceiver, and antenna(s)

NOTE 1: A Radio Platform is a piece of hardware capable of generating RF signals or receiving RF signals, including Base-Band and RF processing. By nature, it is heterogeneous hardware including different processing elements such as fixed accelerators, e.g. Application-Specific Integrated Circuit (ASIC), or reconfigurable accelerators, e.g. FPGAs, etc.

NOTE 2: In case of multiple radio computers, there is an independent Radio Platform for each of the radio computers.

radio reconfiguration: reconfiguration of parameters related to air interface

Radio Virtual Machine (RVM): abstract machine which supports reactive and concurrent executions

NOTE: A RVM may be implemented as a controlled execution environment which allows the selection of a trade-off between flexibility of base band code development and required (re-)certification efforts.

reconfigurable Radio Equipment: Radio Equipment with radio communication capabilities providing support for radio reconfiguration

NOTE: Reconfigurable Radio Equipment includes Smartphones, Feature phones, Tablets, Laptops, Connected Vehicle communication platform, Network platform, IoT device, etc.

reference point: conceptual point at the conjunction of two non-overlapping functions that can be used to identify the type of information passing between these functions

NOTE: This definition is introduced by Recommendation ITU-T M.60 [i.5].

routing entity: entity which directs network packets from their source toward their destination through intermediate network nodes by specific packet forwarding mechanisms

NOTE 1: In the present document, source and destination relate either to CSL or radio computers.

NOTE 2: The directing of packets may include decision making and physical routing.

shadow radio platform: platform where configcodes can be directly executed when it corresponds to the target radio platform or, when it corresponds to an RVM, compiled and executed

NOTE: If the shadow radio platform is equivalent to the target radio platform, then a front-end compiler will generate the executable code for the target radio platform and configcodes are equivalent to the executable code for that radio platform.

unicast identifier (unicast ID): identifier linking a data packet to a specific radio computer

Unified Radio Application (URA): Radio Application which complies with the reconfigurable RE framework defined in the present document

3.2 Symbols

For the purposes of the present document, the following symbols apply:

M_1	Number of SFBs implemented on Radio computer
M_2	Number of SFBs implemented on hardware accelerators

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AOT	Ahead-Of-Time
ASF	Administrator Security Function
ASIC	Applications-Specific Integrated Circuit
BE	Back End
BPA	Baseband Parameter Aggregation
CII	Context Information Interface
CM	Configuration Manager
CSL	Communication Services Layer
FC	Flow Controller
FEC	Forward Error Correction
FFT	Fast Fourier Transform
FM	File Manager
GGSN	Gateway GPRS Support Node
gMURI	generalized MultiRadio Interface
GPRS	General Packet Radio Service
GPS	Global Positioning System
gRPI	generalized Radio Programming Interface
gRRFI	generalized Reconfigurable Radio Frequency Interface
gURAI	generalized Unified Radio Applications Interface
HAL	Hardware Abstraction Layer
HW	HardWare
HW/SW	Hardware/Software
ID	IDentification
IFFT	Inverse Fast Fourier Transform
IP	Internet Protocol
IR	Intermediate Representation
JIT	Just-In-Time
KMS	Key Management System
MAC	Medium Access Control
MIMO	Multi-Input-Multi-Output
MPM	Mobility Policy Manager
MRC	MultiRadio Controller
MURI	MULTiRadio Interface
OEM	Original Equipment Manufacturer
OS	Operating System
RA	Radio Application
RAP	Radio Application Package
RAT	Radio Access Technology
RC	Radio Controller
RCF	Radio Control Framework
RCM	Radio Connection Manager
RE	Radio Equipment
RERC	Radio Equipment Reconfiguration Class
RF	Radio Frequency

RM	Resource Manager
ROS	Radio Operating System
RPI	Radio Programming Interface
RRFI	Reconfigurable Radio Frequency Interface
RRS-CM	RRS Configuration Manager
RRS-CP	RRS Configuration Provider
RVM	Radio Virtual Machine
SDR	Software Defined Radio
SFB	Standard Functional Block
SW	SoftWare
TAD	Transfer of Authority Document
TCP	Transmission Control Protocol
TX/RX	Transmission/Reception
UDFB	User Defined Functional Block
URA	Unified Radio Applications
URAI	Unified Radio Applications Interface
WLAN	Wireless Local Area Network

4 Architectural Reference Model for Reconfigurable Radio Equipment

4.1 Introduction

The present document describes those elements of a Radio Equipment which is related to the software radio reconfiguration only. For this reason, the usage of the term "architecture" is limited to those elements and not to the overall HW/SW architecture of a Radio Equipment which is out of the scope of the present document.

The present document is organized as follows:

- Clause 4.2 describes the reconfigurable Radio Equipment architecture in term of its components and entities.
- Clause 4.3 describes the architecture reference model for multiradio applications.
- Clause 4.4 describes the "radio computer".
- Clause 4.5 describes the Radio Virtual Machine as part of the architecture.
- Clause 4.6 describes the Unified Radio Application.
- Clause 4.7 describes the security architecture for reconfigurable Radio Equipment.
- Clause 5 describes the (logical) interfaces between the identified components/entities.
- Clause 6 lists the operating procedures of a reconfigurable Radio Equipment.
- Clause 4 includes a list of Tables mapping the system requirements as defined in ETSI EN 303 641 [1] to the different entities/components/units which have been identified. In general, according to the Radio Equipment Reconfiguration Class (RERC) [1], all the related mandatory functional requirements described in ETSI EN 303 641 [1] shall be implemented.