

SLOVENSKI STANDARD SIST EN 14304:2016

01-februar-2016

Nadomešča:

SIST EN 14304:2010+A1:2013

Toplotnoizolacijski proizvodi za opremo stavb in industrijske inštalacije - Proizvodi iz fleksibilne elastomerne pene (FEF) - Specifikacija

Thermal insulation products for building equipment and industrial installations - Factory made flexible elastomeric foam (FEF) products - Specification

Wärmedämmstoffe für die technische Gebäudeausrüstung und für betriebstechnische Anlagen in der Industrie - Werkmäßig hergestellte Produkte aus flexiblem Elastomerschaum (FEF) - Spezifikation

SIST EN 14304:2016

Produits isolants thermiques pour l'équipement du bâtiment et les installations industrielles - Produits manufactures en mousse élastomère flexible (FEF) - Spécification

Ta slovenski standard je istoveten z: EN 14304:2015

ICS:

91.100.60 Materiali za toplotno in

zvočno izolacijo

Thermal and sound insulating

materials

SIST EN 14304:2016 en,fr,de

SIST EN 14304:2016

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST EN 14304:2016

https://standards.iteh.ai/catalog/standards/sist/74ff37df-ffb4-44de-9c63-de219d287fcc/sist-en-14304-2016

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM EN 14304

December 2015

ICS 91.100.60

Supersedes EN 14304:2009+A1:2013

English Version

Thermal insulation products for building equipment and industrial installations - Factory made flexible elastomeric foam (FEF) products - Specification

Produits isolants thermiques pour l'équipement du bâtiment et les installations industrielles - Produits manufacturés en mousse élastomère flexible (FEF) -Spécification Wärmedämmstoffe für die technische Gebäudeausrüstung und für betriebstechnische Anlagen in der Industrie - Werkmäßig hergestellte Produkte aus flexiblem Elastomerschaum (FEF) -Spezifikation

This European Standard was approved by CEN on 24 October 2015.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

https://standards.iteh.ai/catalog/standards/sist/74ff37df-ffb4-44de-9c63-

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Conte	ents	Page		
Europ	ean foreword	4		
1	Scope	6		
2	Normative references	6		
3 3.1	Terms, definitions, symbols, units and abbreviated terms			
3.1 3.1.1	Terms and definitions as given in EN ISO 9229:2007			
3.1.1 3.1.2	Additional terms and definitions			
3.1.2 3.2	Symbols, units and abbreviated terms	_		
3.2.1	Symbols and units used in this standard			
3.2.2	Abbreviated terms used in this standard			
4	Requirements			
4.1	General			
4.2	For all applications	_		
4.2.1	Thermal conductivity			
4.2.2	Dimensions and tolerances			
4.2.3	Dimensional stability			
4.2.4	Reaction to fire of the product as placed on the market	12		
4.2.5	Reaction to fire of the product as placed on the market. Durability characteristics A A A A A A A A A A A A A A A A A A A	12		
4.3	For specific applications.	13		
4.3.1	For specific applications (standards.itelr.ai) General	13		
4.3.2	Maximum service temperature	13		
4.3.3	Minimum service temperature SIST EN 14304:2016	13		
4.3.4	Water absorption https://standards.iteh.ai/catalog/standards/sist/74ff37df-ff64-44de-9c63-	14		
4.3.5	Water vapour diffusion resistance	14		
4.3.6	Trace quantities of water soluble ions and the pH-value	14		
4.3.7	Structure-borne sound transmission			
4.3.8	Sound absorption	14		
4.3.9	Release of dangerous substances	15		
4.3.10	Continuous glowing combustion	15		
5	Test methods	15		
5.1	Sampling			
5.2	Conditioning			
5.2 5.3	Testing			
5.3.1	General			
5.3.2	Thermal conductivity			
5.3.3	Reaction to fire			
6	Designation code			
7				
	Assessment and Verification of the Constancy of Performance (AVCP)			
7.1 7.2	General Product Type Determination (PTD)			
7.2 7.3	Factory Production Control (FPC)			
8	Marking and labelling			
Annex	Annex A (normative) Factory production control			
Annex	Annex B (normative) Determination of minimum service temperature			

B.1	Definitions	23
B.2	Principle	23
B.3	Apparatus	23
B.4	Test specimens	23
B.5	Procedure	24
B.6	Calculation and expression of results	24
B.7	Test report	25
Annex	C (normative) Thermal conductivity measurement	26
Annex	D (informative) Additional properties	27
D.1	General	27
D.2	Water vapour diffusion resistance	27
D.3	Fire resistance of penetrations	27
D.4	Density	27
D.5	Compressive Strength	28
Annex	ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Regulation	29
ZA.1	Scope and relevant characteristics ARD PREVIEW	29
ZA.2	Procedures for AVCP of factory made flexible elastomeric foam (FEF) products	31
ZA.3	CE Marking and labellingSIST EN 14304:2016	37
Bibliog	SIST EN 14304:2016 graphyhttps://standarde.iteh.ai/eatakee/etandarde/sist/74ff37df-ffb4-44de-9e63	39
	de219d287fcc/sist-en-14304-2016	

European foreword

This document (EN 14304:2015) has been prepared by Technical Committee CEN/TC 88 "Thermal insulating materials and products", the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by June 2016, and conflicting national standards shall be withdrawn at the latest by September 2017.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 14304:2009+A1:2013.

This document is identifying those clauses of the standard which are needed for the compliance of the European Standard with the Construction Products Regulation (CPR).

The main technical changes that have been made in this new edition of EN 14304 are the following:

- a) an addition to the foreword;
- b) an addition in Clause 3; iTeh STANDARD PREVIEW
- c) a new 4.3.9;

(standards.iteh.ai)

d) modification of 5.3.2;

SIST EN 14304:2016

- e) modification of Clause 7,ttps://standards.iteh.ai/catalog/standards/sist/74ff37df-ffb4-44de-9c63-de219d287fcc/sist-en-14304-2016
- f) modification of Clause 8:
- g) modification of Annex A;
- h) a new Annex ZA.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of Regulation (EU) No. 305/2011.

For relationship with Regulation (EU) No. 305/2011, see informative Annex ZA, which is an integral part of this document.

Locally responsible authorities and contracting entities, who are bound by EU Directives to specify their requirements using European harmonized product standards, are allowed to demand additional properties outside the provisions of this standard if this is technically necessary because of prevailing operational conditions of the building equipment or the industrial installation projected or because of safety regulations.

This European Standard contains five annexes:

- Annex A (normative), Factory production control;
- Annex B (normative), Determination of minimum service temperature;
- Annex C (normative), Thermal conductivity measurement;

- Annex D (informative), Additional properties;
- Annex ZA (informative), Clauses of this European Standard addressing the provisions of the EU Construction Products Regulation.

This document includes a bibliography.

This European Standard is one of a series of standards for insulation products used in building equipment and industrial installations, but this standard can be used in other areas, where appropriate.

In pursuance of Resolution BT 20/1993 revised, CEN/TC 88 have proposed defining the standards listed below as a European package of standards, setting (21 months after availability) as the date of withdrawal (dow) of national standards which conflict with the European standards of this package.

The package of standards comprises the following group of interrelated standards for the specifications of factory made thermal insulation products, all of which come within the scope of CEN/TC 88:

EN 14303, Thermal insulation products for building equipment and industrial installations — Factory made mineral wool (MW) products — Specification

EN 14304, Thermal insulation products for building equipment and industrial installations — Factory made flexible elastomeric foam (FEF) products — Specification

EN 14305, Thermal insulation products for building equipment and industrial installations — Factory made cellular glass (CG) products — Specification

EN 14306, Thermal insulation products for building equipment and industrial installations — Factory made calcium silicate (CS) products — Specification

EN 14307, Thermal insulation products for building equipment and industrial installations — Factory made extruded polystyrene foam (XPS) products—Specification

EN 14308, Thermal insulation products for building equipment and industrial installations — Factory made rigid polyurethane foam (PUR) and polyisocyanurate foam (PIR) products — Specification

EN 14309, Thermal insulation products for building equipment and industrial installations — Factory made products of expanded polystyrene (EPS) — Specification

EN 14313, Thermal insulation products for building equipment and industrial installations — Factory made polyethylene foam (PEF) products — Specification

EN 14314, Thermal insulation products for building equipment and industrial installations — Factory made phenolic foam (PF) products — Specification

EN 15501, Thermal insulation products for building equipment and industrial installations — Factory made expanded perlite (EP) and exfoliated vermiculite (EV) products — Specification

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

1 Scope

This European Standard specifies the requirements for factory made flexible elastomeric foam products which are used for the thermal insulation of building equipment and industrial installations with an operating temperature in the range of approximately - $200 \,^{\circ}$ C to + $175 \,^{\circ}$ C.

Below an operating temperature of - 50 °C, tests regarding the suitability of the products in the intended application should be performed. Manufacturer's advice should be heeded in all cases.

The products are manufactured in the form of sheets, tubes, rolls and tapes with or without coating and/or self-adhesive backing and/or different closure systems.

This European Standard describes product characteristics and includes procedures for testing, evaluation of conformity, marking and labelling.

Products covered by this standard are also used in prefabricated thermal insulation systems and composite panels; the performance of systems incorporating these products is not covered.

This European Standard does not specify the required level of a given property that should be achieved by a product to demonstrate fitness for purpose in a particular application. The levels required for a given application can be found in regulations and invitations to tender.

Products with a declared thermal conductivity greater than 0,050 W/($m\cdot K$) at 10 °C are not covered by this standard.

This European Standard does not cover products for the insulation of the building structure.

The normative part of this European Standard does not cover compressive stress (see D.5).

2 Normative references

(standards.iteh.ai)

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 822, Thermal insulating products for building applications - Determination of length and width

EN 823, Thermal insulating products for building applications - Determination of thickness

EN 824, Thermal insulating products for building applications - Determination of squareness

EN 1604, Thermal insulating products for building applications - Determination of dimensional stability under specified temperature and humidity conditions

EN 1609, Thermal insulating products for building applications - Determination of short term water absorption by partial immersion

EN 12085, Thermal insulating products for building applications - Determination of linear dimensions of test specimens

EN 12086:2013, Thermal insulating products for building applications - Determination of water vapour transmission properties

EN 12667, Thermal performance of building materials and products - Determination of thermal resistance by means of guarded hot plate and heat flow meter methods - Products of high and medium thermal resistance

EN 12939, Thermal performance of building materials and products - Determination of thermal resistance by means of guarded hot plate and heat flow meter methods - Thick products of high and medium thermal resistance

EN 13172:2012, Thermal insulation products - Evaluation of conformity

EN 13467, Thermal insulating products for building equipment and industrial installations - Determination of dimensions, squareness and linearity of preformed pipe insulation

EN 13468, Thermal insulating products for building equipment and industrial installations - Determination of trace quantities of water soluble chloride, fluoride, silicate, sodium ions and pH

EN 13469, Thermal insulating products for building equipment and industrial installations - Determination of water vapour transmission properties of preformed pipe insulation

EN 13472, Thermal insulating products for building equipment and industrial installations - Determination of short term water absorption by partial immersion of preformed pipe insulation

EN 13501-1:2007+A1:2009, Fire classification of construction products and building elements - Part 1: Classification using data from reaction to fire tests

EN 13823, Reaction to fire tests for building products — Building products excluding flooring exposed to the thermal attack by a single burning item

ITCH STANDARD PREVIEWEN 14366:2004, Laboratory measurement of noise from waste water installations

(Standards.iteh.al)
EN 14706, Thermal insulating products for building equipment and industrial installations Determination of maximum service temperature 14304:2016

https://standards.iteh.ai/catalog/standards/sist/74ff37df-ffb4-44de-9c63-

EN 14707, Thermal insulating products/forst-building2@equipment and industrial installations - Determination of maximum service temperature for preformed pipe insulation

EN 15715:2009, Thermal insulation products - Instructions for mounting and fixing for reaction to fire testing - Factory made products

EN ISO 354, Acoustics - Measurement of sound absorption in a reverberation room (ISO 354)

EN ISO 3822-1, Acoustics - Laboratory tests on noise emission from appliances and equipment used in water supply installations - Part 1: Method of measurement (ISO 3822-1)

EN ISO 4589-1, Plastics - Determination of burning behaviour by oxygen index - Part 1: Guidance (ISO 4589-1)

EN ISO 8497, Thermal insulation - Determination of steady-state thermal transmission properties of thermal insulation for circular pipes (ISO 8497)

EN ISO 9229:2007, Thermal insulation - Vocabulary (ISO 9229:2007)

EN ISO 11654, Acoustics - Sound absorbers for use in buildings - Rating of sound absorption (ISO 11654)

EN ISO 11925-2, Reaction to fire tests - Ignitability of products subjected to direct impingement of flame - Part 2: Single-flame source test (ISO 11925-2)

EN ISO 13787, Thermal insulation products for building equipment and industrial installations -Determination of declared thermal conductivity (ISO 13787)

Terms, definitions, symbols, units and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1.1 Terms and definitions as given in EN ISO 9229:2007

3.1.1.1

flexible elastomeric foam

closed cell flexible foam, made of natural or synthetic rubber, or a mixture of the two and containing other polymers and other chemicals which may be modified by organic or inorganic additives

3.1.1.2

tube

(insulation) product for application on cylindrical objects

3.1.1.3

roll

(insulation) product supplied in the form of a wound cylinder

3.1.1.4

iTeh STANDARD PREVIEW

insulation product designed to fit around pipes (standards.iteh.ai)

3.1.1.5

SIST EN 14304:2016

thermal insulation

https://standards.iteh.ai/catalog/standards/sist/74ff37df-ffb4-44de-9c63-

process of reducing heat transfer through a system, or to describe a product, component or system which performs that function

3.1.1.6

test specimen

single item within a sample or part of an item used for a test

3.1.1.7

building equipment

system incorporated in a permanent manner in construction works forming part of the heating, cooling and ventilation installation of those works

3.1.1.8

industrial installation

plant and associated vessels, pipes, ducts etc. used by industry to manufacture or store a product or to transfer a fluid

3.1.2 Additional terms and definitions

3.1.2.1

sheet

flexible insulation product of rectangular shape with or without facing or adhesive backing

3.1.2.2

tape

thin, narrow strip of insulation material with or without adhesive backing supplied in rolls

3.1.2.3

form pieces

prefabricated elbows, T-pieces or else formed from tubes, sheets or rolls etc

3.1.2.4

level

given value, which is the upper or lower limit of a requirement

Note 1 to entry: The level is given by the declared value of the characteristic concerned.

3.1.2.5

class

combination of two levels of the same property between which the performance will fall

3.1.2.6

production line

assemblage of equipment that produces products using a continuous process

3.1.2.7

production unit iTeh STANDARD PREVIEW

assemblage of equipment that produces products using a discontinuous process standards.iteh.ai)

3.2 Symbols, units and abbreviated terms

3.2.1 Symbols and units used in this standard ards/sist/74ff37df-ffb4-44de-9c63-

de219d287fcc/sist-en-14304-2016

$\alpha_{\mathbf{p}}$	is the practical sound absorption coefficient	_
α_{W}	is the weighted sound absorption coefficient	_
b	is the width	mm
D_{i}	is the inside diameter	mm
$D_{\rm i,D}$	is the declared inside diameter of a tube	mm
d	is the thickness	mm
d_{D}	is the declared thickness of the product	mm
$\Delta \varepsilon_{\mathrm{D}}$	is the relative change in thickness	%
1	is the length	m or mm
$L_{SC,A}$	is the single number descriptor of structure-borne sound	
λ	is the thermal conductivity	W/(m·K)
λ_{D}	is the declared thermal conductivity	$W/(m \cdot K)$
μ	is the water vapour diffusion resistance factor	_
v	is the deviation from squareness for tubes	mm
$S_{\mathbf{b}}$	is the deviation from squareness for sheets and rolls on length and width	mm/m

is the short-term water absorption $W_{\mathbf{p}}$ kg/m^2 AP is the declared level of practical sound absorption coefficient is the symbol of the declared level of weighted sound absorption coefficient AW is the symbol of the declared level of soluble chloride ions CL

DS(TH) is the symbol of the declared value for dimensional stability under specified

temperature and relative humidity conditions

F is the symbol of the declared level of soluble fluoride ions

is the symbol of the declared level of water vapour diffusion resistance factor MU

is the symbol of the declared level of soluble sodium ions NA

is the symbol of the declared level of the pH-value рН

SI is the symbol of the declared level of soluble silicate ions

ST(+)is the symbol of the declared level for maximum service temperature ST(-) is the symbol of the declared level for minimum service temperature WS is the symbol of the declared level for short-term water absorption

3.2.2 Abbreviated terms used in this standard

is Assessment and Verification of Constancy of Performance (previously named attestation of **AVCP**

conformity) iTeh STANDARD PREVIEW

is Declaration of Performance DoP

(standards.iteh.ai) is Flexible Elastomeric Foam **FEF**

is Factory Production Control **FPC** SIST EN 14304:2016

is Product Type Determination (previously named ITT for Initial Type Test)3-**PTD**

de219d287fcc/sist-en-14304-2016

RtF is Reaction to Fire

Thibell is Thermal Insulation for Building Equipment and Industrial Installations

is Verification of Constancy of Performance (previously named evaluation of conformity) **VCP**

Requirements

4.1 General

Product properties shall be assessed in accordance with Clause 5. To comply with this standard, products shall meet the requirements of 4.2, and the requirements of 4.3 as appropriate.

Information on additional properties is given in Annex D. NOTE

One test result for a product property is the average of the measured values on the number of test specimens given in Table 2.

4.2 For all applications

4.2.1 Thermal conductivity

For flat specimens, thermal conductivity shall be based upon measurements carried out in accordance with EN 12667 or EN 12939 for thick products. For cylindrical specimens EN ISO 8497 shall be used as specified in 5.3.2.

In both cases, the thermal conductivity values shall be determined by the manufacturer and verified in accordance with EN ISO 13787. They shall be declared by the manufacturer according to measuring standards mentioned above covering the product service temperature range. The following conditions apply:

- the measured values shall be expressed with three significant figures;
- the declared thermal conductivity curve shall be given as a limit curve, defined in EN ISO 13787;
- the value of the declared thermal conductivity, λ_D , shall be rounded upwards to the nearest 0,001 W/(m·K);
- the lowest reference mean test temperature required is 170 °C.

The declared equation/limit curve is the "declared reference" with three significant figures, that is to 0,000 1 W/(m·K) for λ values below 0,1 W/(m·K) and in 0,001 W/(m·K) for λ values above 0,1 W/(m·K). This shall be used as a reference for the verification of the declaration.

When thermal conductivity is declared as table derived from the equation, rounding upwards to the next $0.001 \text{ W/(m\cdot K)}$ has to be done for the full range of the thermal conductivity.

NOTE Determinations of the declared thermal conductivity of pipe sections, following EN ISO 8497 having joints in the metering area, include joints as defined in EN ISO 23993.

4.2.2 Dimensions and tolerances TANDARD PREVIEW

4.2.2.1 Linear dimensions (standards.iteh.ai)

The length, l, width, b, and thickness, d, of sheets, rolls and tapes shall be determined in accordance with EN 822 and EN 823. The length, l, thickness, d, and inside diameter, $D_{\rm i}$, of tubes shall be determined in accordance with EN 13467. No test result shall deviate from the declared values by more than the tolerances given in Table 1.

4.2.2.2 Squareness

Deviation from squareness, S_b , of sheets and rolls shall be determined in accordance with EN 824. Deviation from squareness, v, of tubes shall be determined in accordance with EN 13467. No test result shall deviate from the declared values by more than the tolerances given in Table 1.