



SLOVENSKI STANDARD

SIST EN 62601:2016

01-september-2016

Industrijska komunikacijska omrežja - Brežično komunikacijsko omrežje in komunikacijski profili - WIA-PA (IEC 62601:2015)

Industrial communication networks - Wireless communication network and communication profiles - WIA-PA (IEC 62601:2015)

Industrielle Kommunikationsnetze - Kommunikationsnetze und Kommunikationsprofile - WIA-PA (IEC 62601:2015)

Réseaux industriels de communication - Réseau de communications sans fil et profils de communication - WIA-PA (IEC 62601:2015)

<https://standards.iteh.ai/catalog/standards/sist/27753dc6-7257-4204-9264-1531d05b506e/sist-en-62601-2016>

Ta slovenski standard je istoveten z: EN 62601:2016

ICS:

25.040.40	Merjenje in krmiljenje industrijskih postopkov	Industrial process measurement and control
35.100.05	Večslojne uporabniške rešitve	Multilayer applications
35.240.50	Uporabniške rešitve IT v industriji	IT applications in industry

SIST EN 62601:2016

en,fr,de

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 62601:2016

<https://standards.iteh.ai/catalog/standards/sist/27753dc6-7257-4204-9264-1531d05b506e/sist-en-62601-2016>

EUROPEAN STANDARD

EN 62601

NORME EUROPÉENNE

EUROPÄISCHE NORM

April 2016

ICS 25.040.40; 35.100.05

English Version

**Industrial networks - Wireless communication network and
communication profiles - WIA-PA
(IEC 62601:2015)**

Réseaux industriels - Réseau de communications sans fil et
profils de communication - WIA-PA
(IEC 62601:2015)

Industrielle Kommunikationsnetze - Kommunikationsnetze
und Kommunikationsprofile - WIA-PA
(IEC 62601:2015)

This European Standard was approved by CENELEC on 2016-01-13. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

EN 62601:2016**European foreword**

The text of document 65C/821/FDIS, future edition 2 of IEC 62601, prepared by SC 65C "Industrial networks" of IEC/TC 65 "Industrial process measurement, control and automation" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 62601:2016.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2016-10-13
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2019-01-13

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 62601:2015 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 61804-2	NOTE	Harmonized as EN 61804-2.
IEC 61499-1	NOTE	Harmonized as EN 61499-1.
IEC 61499-2	NOTE	Harmonized as EN 61499-2.
ISO 3166-1	NOTE	Harmonized as EN ISO 3166-1.

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 When an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cenelec.eu

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
ISO/IEC 9899	-	Information technology - Programming languages - C	-	-
ISO 3166-1	-	Codes for the representation of names of countries and their subdivisions - Part 1: Country codes	EN ISO 3166-1	-
IEEE 802.15.4	2011 ¹⁾	IEEE Standard for Local and metropolitan area networks - Part 15.4: Low-Rate Wireless Personal Area Networks (LR-WPANS)	-	-

SIST EN 62601:2016

<https://standards.itech.ai/catalog/standards/sist/27753dc6-7257-4204-9264-1531d05b506e/sist-en-62601-2016>

¹⁾ Superseded by IEEE 802.15.4-2015.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 62601:2016

<https://standards.iteh.ai/catalog/standards/sist/27753dc6-7257-4204-9264-1531d05b506e/sist-en-62601-2016>



IEC 62601

Edition 2.0 2015-12

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Industrial networks – Wireless communication network and communication profiles – WIA-PA

(standards.iteh.ai)

Réseaux industriels – Réseau de communications sans fil et profils de communication – WIA-PA

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 25.040.40 ; 35.100.05

ISBN 978-2-8322-3040-4

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD.....	13
1 Scope.....	15
2 Normative references	15
3 Terms, definitions and abbreviations	15
3.1 Terms and definitions.....	15
3.2 Abbreviations.....	19
4 Definition of data types.....	21
5 WIA-PA overview.....	22
5.1 Device types.....	22
5.2 Network topology.....	22
5.3 Protocol architecture.....	24
5.4 Interconnection.....	25
6 System management.....	26
6.1 General.....	26
6.2 Framework of system management.....	27
6.3 Joining process.....	28
6.3.1 Provisioning process.....	28
6.3.2 Joining process of routing device.....	29
6.3.3 Joining process of field device.....	30
6.3.4 Addressing and address assignment.....	31
6.4 Virtual Communication Relationship (VCR).....	32
6.4.1 Definition.....	32
6.4.2 Protocol support for VCR.....	33
6.4.3 VCR establishment.....	33
6.4.4 VCR release.....	34
6.5 Routing configuration and communication resource allocation.....	34
6.5.1 Routing configuration.....	34
6.5.2 Framework of communication resource allocation.....	34
6.5.3 DLPDU priority and scheduling rules.....	35
6.5.4 Communication resource allocation to routing device.....	35
6.5.5 Communication resource allocation to field device.....	37
6.6 Aggregation and disaggregation.....	39
6.6.1 Aggregation.....	39
6.6.2 Disaggregation.....	41
6.6.3 An example of the two level aggregation process.....	41
6.6.4 Management of aggregation and disaggregation objects.....	43
6.7 Performance monitoring.....	45
6.7.1 Path failure report.....	45
6.7.2 Device status report.....	45
6.7.3 Channel condition report.....	46
6.8 Leaving process.....	46
6.8.1 General.....	46
6.8.2 Leaving process of routing device.....	46
6.8.3 Leaving process of field device.....	48
6.9 Management information base and services.....	49
6.9.1 Management information base.....	49

6.9.2	MIB services	63
7	Physical layer	65
7.1	General	65
7.2	General requirements based on IEEE STD 802.15.4-2011	66
7.3	Additional requirements	67
7.3.1	General	67
7.3.2	Frequency allocations	67
7.3.3	Channel numbers and frequency assignments	67
7.3.4	Radio transceivers	67
7.3.5	Unspecified or improved required radio performance	67
7.3.6	Transmit power	68
7.3.7	Output power control	68
7.3.8	Receiver sensitivity	68
7.3.9	PHY PIB attributes	68
8	Data link layer	69
8.1	General	69
8.2	Protocol stack	69
8.3	MAC overview and function extension	70
8.3.1	MAC overview	70
8.3.2	General requirements based on IEEE STD 802.15.4-2011	70
8.3.3	MAC function extension	73
8.4	DLSL function description	74
8.4.1	General	74
8.4.2	Coexistence	75
8.4.3	Timeslot communication	75
8.4.4	WIA-PA superframe	76
8.4.5	Frequency hopping	76
8.4.6	Transmission of long cycle data	78
8.4.7	Retry strategy	79
8.4.8	Management service	79
8.4.9	Radio link quality and channel condition measurement	79
8.4.10	Security	80
8.4.11	Country code	80
8.4.12	DLSL state machine	80
8.5	Data link sub-layer data services	86
8.5.1	General	86
8.5.2	DLDE-DATA.request	86
8.5.3	DLDE-DATA.confirm	87
8.5.4	DLDE-DATA.indication	88
8.5.5	Time sequence of DLSL data service	89
8.6	Data link sub-layer management services	90
8.6.1	General	90
8.6.2	Network discovery services	90
8.6.3	Device joining services	92
8.6.4	Device leaving services	94
8.6.5	DLME-CHANNEL-CONDITION.indication	96
8.6.6	DLME-NEIGHBOUR-INFO.indication	96
8.6.7	DLME-COMM-STATUS.indication	97
8.6.8	Keep-alive services	97

8.6.9	Time synchronization services	98
8.7	DLSL frame formats	99
8.7.1	General frame format	99
8.7.2	Date frame format	100
8.7.3	Command frame format	100
9	Network layer	102
9.1	General	102
9.2	Protocol stack	102
9.3	Function description	103
9.3.1	General	103
9.3.2	Addressing	103
9.3.3	Routing	104
9.3.4	Packet lifecycle management	104
9.3.5	Joining and leaving network of device	104
9.3.6	End-to-end network performance monitoring	105
9.3.7	Fragmentation and reassembly	105
9.3.8	Network layer state machine	105
9.4	Network layer data services	110
9.4.1	General	110
9.4.2	NLDE-DATA.request	110
9.4.3	NLDE-DATA.confirm	111
9.4.4	NLDE-DATA.indication	111
9.4.5	Time sequence of NL data services	112
9.5	Network layer management services	112
9.5.1	General	112
9.5.2	Network communication status report services	112
9.5.3	Network joining services	115
9.5.4	Network leaving services	120
9.5.5	Cluster member report services	124
9.5.6	Neighbour information report services	126
9.5.7	Route allocation services	128
9.5.8	Communication resource allocation services	134
9.5.9	Aggregation and disaggregation services	150
9.5.10	Device status report services	151
9.5.11	Channel condition report services	153
9.5.12	Failure path report services	155
9.5.13	Network attribute getting services	156
9.5.14	Network attribute setting services	160
9.6	Network layer packet formats	163
9.6.1	Common packet format	163
9.6.2	Data packet format	164
9.6.3	Aggregated packet format	165
9.6.4	Command packet format	165
10	Application layer	182
10.1	Overview	182
10.1.1	General	182
10.1.2	AL structure	182
10.1.3	Functions of UAP	182
10.1.4	Functions of ASL	183

10.2	UAP.....	183
10.2.1	General	183
10.2.2	UAO	183
10.2.3	Method definition	184
10.3	Application sub-layer	188
10.3.1	General	188
10.3.2	Application sub-layer data entity	188
10.4	Application sub-layer packet formats.....	193
10.4.1	General	193
10.4.2	ASL general packet format	193
10.4.3	Packet formats	195
11	Security.....	196
11.1	General.....	196
11.2	Security management framework	197
11.3	Secure communication protocol stack	198
11.3.1	General	198
11.3.2	Data link sub-layer security.....	199
11.3.3	Application sub-layer security	200
11.4	Key management.....	201
11.4.1	Key type	201
11.4.2	Key distribution	202
11.4.3	Key update	202
11.4.4	Key status	202
11.5	Secure joining process.....	203
11.5.1	Secure joining process of a new WIA-PA device	203
11.5.2	Device security material getting services.....	204
11.6	Secure transportation.....	211
11.6.1	Process of secure transportation from field device to host configuration computer	211
11.6.2	Process of secure transportation from host configuration computer to field device	212
Annex A	(informative) Security strategy for WIA-PA network.....	213
A.1	Risk analysis for WIA-PA network	213
A.2	Security principles for WIA-PA network	213
A.3	Security objectives for WIA-PA network	213
A.4	Graded and layered security system	213
Annex B	(informative) Format description	215
B.1	Time sequence diagram	215
B.2	Packet or frame format	215
Annex C	(informative) Example of UAO	217
C.1	General.....	217
C.2	Analog input object	217
C.2.1	Overview	217
C.2.2	Class attribute of AIO	217
C.2.3	Instance attribute of AIO	217
Annex D	(informative) Country-specific and region-specific provisions	219
Annex E	(informative) Regional modification for compliance with ETSI standards	220
E.1	General.....	220
E.2	Compliance with EN 300 440-2 V1.4.1	220

E.3 Compliance with EN 300 328 V1.8.1	220
Bibliography.....	222
Figure 1 – Example of WIA-PA physical topology (combination of star and mesh).....	23
Figure 2 – Example of WIA-PA physical topology (star-only).....	23
Figure 3 – OSI basic reference model mapped to WIA-PA	24
Figure 4 – The architecture of WIA-PA gateway.....	25
Figure 5 – DMAP in system management.....	26
Figure 6 – Hybrid centralized and distributed system management scheme	28
Figure 7 – Joining process of routing device through the gateway device.....	29
Figure 8 – Joining process of routing device through an online routing device	30
Figure 9 – Joining process of field device through a gateway device.....	31
Figure 10 – Joining process of field device through a routing device.....	31
Figure 11 – Long address structure of device.....	31
Figure 12 – Short address structure of routing device	32
Figure 13 – Short address structure of field device	32
Figure 14 – An example of resource allocation.....	35
Figure 15 – Allocation process of routing device's communication resources	36
Figure 16 – Allocation process of field device's communication resources	38
Figure 17 – Example of aggregation and disaggregation.....	42
Figure 18 – Process of path failure report	45
Figure 19 – Device status report process of field device.....	45
Figure 20 – Device status report process of routing device.....	46
Figure 21 – Process of channel condition report	46
Figure 22 – Active leaving process of routing device.....	47
Figure 23 – Passive leaving process of routing device	47
Figure 24 – Active leaving process of field device (leaving from gateway device).....	48
Figure 25 – Active leaving process of field device (leaving from routing device).....	48
Figure 26 – Passive leaving process of field device (leaving from gateway device)	49
Figure 27 – Passive leaving process of field device (leaving from routing device)	49
Figure 28 – WIA-PA DLL protocol stack	69
Figure 29 – WIA-PA DLSL reference model	75
Figure 30 – WIA-PA superframe	76
Figure 31 – R1, R2 and R3 superframe structures	78
Figure 32 – An example of long cycle data transmission	79
Figure 33 – DLSL state machine for device joining.....	81
Figure 34 – DLSL state machine for in-network running	83
Figure 35 – Time sequence of data service	89
Figure 36 – Time sequence of network discovery.....	92
Figure 37 – General frame format	99
Figure 38 – WIA-PA network layer protocol stack.....	102
Figure 39 – WIA-PA network layer reference model	103
Figure 40 – Network layer state machine	105

Figure 41 – Time sequence of NL data services	112
Figure 42 – Time sequence for field device joining through routing device	118
Figure 43 – One-hop joining process for routing device	119
Figure 44 – Multi-hop join process of routing device	119
Figure 45 – Active leaving process of field device (leaving routing device)	122
Figure 46 – Passive leaving of field device	122
Figure 47 – Active leaving process of routing device	123
Figure 48 – Passive leaving process of routing device	123
Figure 49 – Cluster member reporting process	126
Figure 50 – Neighbour information reporting process	128
Figure 51 – Time sequence for route adding	130
Figure 52 – Time sequence for route updating	132
Figure 53 – Time sequence for route deleting	134
Figure 54 – Adding a link originating from gateway device to routing device	137
Figure 55 – Adding a link originating from routing device to field device	137
Figure 56 – Updating a link originating by gateway device to routing device	139
Figure 57 – Updating a link originating from routing device to field device	140
Figure 58 – Releasing a link originating from gateway device to routing device	142
Figure 59 – Releasing a link originating from routing device to field device	142
Figure 60 – Adding a superframe originating from gateway device to routing device	144
Figure 61 – Adding a superframe originating from routing device to field device	144
Figure 62 – Updating a superframe originating from gateway device to routing device	146
Figure 63 – Updating a superframe originating from routing device to field device	147
Figure 64 – Releasing a superframe originating from gateway device to routing device	149
Figure 65 – Releasing a superframe originating from routing device to field device	149
Figure 66 – Device status reporting process from field device to routing device	152
Figure 67 – Device status reporting process from routing device to gateway device	153
Figure 68 – Channel condition reporting process from field device to routing device	154
Figure 69 – Channel condition reporting process from routing device to gateway device	155
Figure 70 – Failure path reporting process	156
Figure 71 – AL structure	182
Figure 72 – User application process	183
Figure 73 – C/S communication process	191
Figure 74 – P/S communication process (disable aggregation function)	192
Figure 75 – P/S communication process (enable aggregation function)	192
Figure 76 – R/S communication process	193
Figure 77 – Security management framework of WIA-PA network	197
Figure 78 – Security communication protocol stack	199
Figure 79 – Key lifecycle	202
Figure 80 – Secure joining process of WIA-PA device	203
Figure 81 – Time sequence for field device joining (field device to routing device)	207
Figure 82 – Time sequence for field device joining (routing device to gateway device)	208
Figure 83 – One-hop joining process for routing device	209

Figure 84 – Multi-hop join process of routing device (new routing device to routing device).....	210
Figure 85 – Multi-hop join process of routing device (routing device to gateway device)	211
Figure B.1 – Time sequence diagram.....	215
Table 1 – Definition of data types.....	22
Table 2 – Protocol support for VCR.....	33
Table 3 – Relations between VCR and aggregation function	39
Table 4 – Format of aggregated data followed by field device's DAGO.....	41
Table 5 – Format of aggregated packet followed by routing device's PAGO	41
Table 6 – DAGO class attributes	43
Table 7 – DAGO instance attributes	43
Table 8 – MEM_STRUCT structure	44
Table 9 – PAGO class attributes	44
Table 10 – PAGO instance attributes	44
Table 11 – DGO class attributes	44
Table 12 – DGO instance attributes	45
Table 13 – Unstructured attributes (1 of 5).....	50
Table 14 – Structured attributes	55
Table 15 – NLRRoute_Struct structure	56
Table 16 – Superframe_Struct structure.....	56
Table 17 – Link_Struct structure	57
Table 18 – Neighbour_Struct structure	58
Table 19 – ChanCon_Struct structure	58
Table 20 – Device_struct structure (1 of 3)	59
Table 21 – VCR_Struct structure.....	61
Table 22 – DevConRep_Struct structure	62
Table 23 – Key_Struct structure.....	62
Table 24 – ObjList_Struct structure	62
Table 25 – DMAP-MIB-GET.request parameters	63
Table 26 – DMAP-MIB-GET.confirm parameters	64
Table 27 – DMAP-MIB-SET.request parameters	64
Table 28 – DMAP-MIB-SET.confirm parameters.....	65
Table 29 – PHY protocol selection	66
Table 30 – Frequency band and data rate	67
Table 31 – Frequency assignments.....	67
Table 32 – PHY PIB attributes (1 of 2)	68
Table 33 – MAC protocol selection (1 of 2)	71
Table 34 – MAC PIB attributes.....	73
Table 35 – MAC extended PIB attributes.....	73
Table 36 – Beacon payload.....	74
Table 37 – Format of Capability Information field	74
Table 38 – Hopping mechanisms	77

Table 39 – DLSL state transitions for device joining	82
Table 40 – DLSL state transitions for in-network running (1 of 3)	83
Table 41 – DLDE-DATA.request parameters	87
Table 42 – DLDE-DATA.confirm parameters	88
Table 43 – Status table	88
Table 44 – DLDE-DATA.indication parameters	89
Table 45 – DLME-DISCOVERY.request parameters	90
Table 46 – DLME- DISCOVERY.confirm parameters	91
Table 47 – Network descriptor list	91
Table 48 – DLME-JOIN.request parameters	93
Table 49 – DLME-JOIN.indication parameters	93
Table 50 – DLME-JOIN.response parameters	94
Table 51 – DLME-JOIN.confirm parameters	94
Table 52 – DLME-LEAVE.request parameters	95
Table 53 – DLME-LEAVE.indication parameters	95
Table 54 – DLME-LEAVE.confirm parameters	95
Table 55 – DLME-CHANNEL-CONDITION.indication parameters	96
Table 56 – DLME-NEIGHBOUR-INFO.indication parameters	96
Table 57 – DLME-COMM-STATUS.indication parameters	97
Table 58 – DLME -KEEP-LIVE.confirm parameters	98
Table 59 – DLME -KEEP-LIVE.indication parameters	98
Table 60 – DLME-TIME-SYN.request parameters	98
Table 61 – DLME -TIME-SYN.confirm parameters	99
Table 62 – DLME-TIME-SYN.indication parameters	99
Table 63 – DLSL frame control field	100
Table 64 – Date frame format	100
Table 65 – General command frame format	100
Table 66 – DLSL command frame	101
Table 67 – Format of keep-alive command frame	101
Table 68 – Format of time synchronization command frame	102
Table 69 – Example of a routing table	104
Table 70 – NL state transitions (1 of 4)	106
Table 71 – NLDE-DATA.request parameters	111
Table 72 – NLDE-DATA.confirm parameters	111
Table 73 – NLDE-DATA.indication parameters	112
Table 74 – NLME-COMM-STATUS.request parameters	113
Table 75 – NLME-COMM-STATUS.indication parameters	114
Table 76 – NLME-COMM-STATUS.confirm parameters	114
Table 77 – NLME-JOIN.request parameters	115
Table 78 – NLME-JOIN.indication parameters	116
Table 79 – NLME-JOIN.response parameters	116
Table 80 – NLME-JOIN.confirm parameters	117
Table 81 – NLME-LEAVE.request parameters	120