



**Digital cellular telecommunications system (Phase 2+) (GSM);
Universal Mobile Telecommunications System (UMTS);
LTE;
IP Multimedia Subsystem (IMS)
Application Level Gateway (IMS-ALG) -
IMS Access Gateway (IMS-AGW) interface:
Procedures descriptions
(3GPP TS 23.334 version 13.10.0 Release 13)**



Reference

RTS/TSGC-0423334vda0

Keywords

GSM,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and

of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and
of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	8
1 Scope	9
2 References	9
3 Definitions, symbols and abbreviations	13
3.1 Definitions.....	13
3.2 Symbols.....	13
3.3 Abbreviations	14
4 Architecture	14
4.1 Reference architecture.....	14
4.2 NAT Function	16
4.3 ATCF/ATGW Function	17
4.4 eP-CSCF/eIMS-AGW Function.....	17
5 Functional Requirements.....	18
5.1 General	18
5.2 Gate Control & Local NAT	18
5.3 IP realm indication and availability.....	18
5.4 Remote NAT traversal support.....	19
5.5 Remote Source Address/Port Filtering	19
5.6 Traffic Policing	19
5.7 Hanging Termination Detection	19
5.8 QoS Packet Marking	20
5.9 Handling of RTCP streams.....	20
5.10 Media Inactivity Detection	21
5.11 IMS Media Plane Security	21
5.11.1 General.....	21
5.11.2 End-to-access-edge Security	22
5.11.2.1 End-to-access-edge security for RTP based media using SDES	22
5.11.2.2 End-to-access-edge security for TCP based media using TLS.....	23
5.11.2.2.1 General	23
5.11.2.2.2 e2ae security for session based messaging (MSRP)	24
5.11.2.2.3 e2ae security for conferencing (BFCP)	25
5.11.2.3 End-to-access-edge security for UDP based media using DTLS	25
5.11.2.3.1 General	25
5.11.2.3.2 e2ae security for T.38 fax over UDP/UDPTL transport	25
5.11.2.4 End-to-access-edge security for RTP based media using DTLS-SRTP	26
5.11.2.5 End-to-access-edge security for RTP based voice and video media using DTLS-SRTP over TCP.....	27
5.11.2.6 End-to-access-edge security for WebRTC data channels using UDP/DTLS/SCTP transport	28
5.11.3 End-to-end Security	28
5.11.3.1 End-to-end security for RTP based media	28
5.11.3.2 End-to-end security for TCP-based media using TLS	28
5.12 Explicit Congestion Notification support	28
5.12.1 General.....	28
5.12.2 Incoming SDP offer with ECN	29
5.12.3 Incoming SDP offer without ECN	29
5.12.4 Detection of ECN failures by IMS-AGW	29
5.13 Transcoding	29
5.13.1 General.....	29
5.13.2 Handling of common codec parameters.....	30
5.13.3 Handling of the EVS speech codec.....	31
5.13.4 Handling of the OPUS speech and audio codec for WebRTC.....	48

5.14	Multimedia Priority Service (MPS) Support	51
5.15	Coordination of Video Orientation.....	52
5.16	Generic image attributes.....	53
5.17	TCP bearer connection control.....	53
5.17.1	Stateless TCP handling	53
5.17.2	State-aware TCP handling	54
5.17.2.1	General	54
5.17.2.2	State-aware TCP handling without support of modifying the TCP setup direction	54
5.17.2.3	State-aware TCP handling with support of modifying the TCP setup direction	55
5.18	Interactive Connectivity Establishment (ICE).....	57
5.18.1	General.....	57
5.18.2	ICE lite.....	57
5.18.3	Full ICE	59
5.18.4	STUN consent freshness for WebRTC	61
5.19	MSRP handling	61
5.19.1	General.....	61
5.19.2	IMS-ALG procedures to support IETF RFC 6714 with application agnostic MSRP handling by the IMS-AGW	62
5.19.3	IMS-ALG procedures to support IETF draft-ietf-simple-msrp-sessmatch with application agnostic MSRP handling by the IMS-AGW	62
5.19.4	IMS-ALG procedures for application aware MSRP interworking by the IMS-AGW	63
5.19.5	Application-aware MSRP interworking at the IMS-AGW	63
5.19.6	MSRP data channels	63
5.20	Web Real-Time Communication (WebRTC).....	64
5.20.1	General.....	64
5.20.2	WebRTC data channel	65
5.20.2.1	General	65
5.20.2.2	Data Channel Establishment	65
5.20.2.3	Data Channel Release	70
5.20.2.3.1	General	70
5.20.2.3.2	Release of one WebRTC data channel	71
5.20.2.3.3	Release of all or last active WebRTC data channels within an SCTP Association	72
5.20.3	Media Plane Optimization	72
5.20.3.1	General	72
5.20.3.2	WIC originating call.....	73
5.20.3.3	WIC terminating call	73
5.21	Alternate Connection (ALTC) Addresses Management	74
5.21.1	General.....	74
5.22	Video Region-of-Interest (ROI)	74
5.22.1	General.....	74
5.22.2	"Far End Camera Control" mode	75
5.22.3	"Predefined ROI" mode	75
5.22.4	"Arbitrary ROI" mode.....	76
5.23	SDP Capability Negotiation (SDPCapNeg)	77
6	IMS-ALG to IMS-AGW Procedures	77
6.1	Non-Call Related Procedures	77
6.1.1	General.....	77
6.1.2	IMS-AGW Unavailable	78
6.1.3	IMS-AGW Available	78
6.1.4	IMS-AGW Recovery	79
6.1.5	IMS-ALG Recovery	80
6.1.5.1	General	80
6.1.5.2	IMS-ALG Restoration.....	80
6.1.6	IMS-AGW Re-register.....	80
6.1.7	IMS-AGW Re-registration Ordered by IMS-ALG	81
6.1.8	Audit of IMS-AGW	81
6.1.8.1	Audit of Value.....	81
6.1.8.2	Audit of Capability.....	82
6.1.9	IMS-AGW Capability Change.....	82
6.1.10	IMS-ALG Out of service	82
6.1.11	IMS-AGW Resource Congestion Handling - Activate	83

6.1.12	MGW Resource Congestion Handling -Indication	83
6.1.13	Control association monitoring.....	83
6.1.14	Realm Availability Monitoring.....	84
6.1.15	Failure of IP Port, Interface or Group of Interfaces	85
6.2	Call Related Procedures	85
6.2.1	Gate Control & Local NA(P)T procedure.....	85
6.2.2	IP realm indication procedure.....	88
6.2.3	Remote NA(P)T traversal support procedure	88
6.2.4	Remote Source Address/Port Filtering	88
6.2.5	Traffic Policing	89
6.2.6	Hanging Termination Detection	89
6.2.7	QoS Packet Marking	90
6.2.8	Media Inactivity Detection	90
6.2.9	Handling of RTCP streams	91
6.2.10	IMS end-to-access-edge Media Plane Security.....	91
6.2.10.1	General	91
6.2.10.2	End-to-access-edge security for RTP based media using SDES	91
6.2.10.3	End-to-access-edge security for TCP-based media using TLS	91
6.2.10.3.1	End-to-access-edge security for session based messaging (MSRP)	91
6.2.10.3.1.1	IMS UE originating procedures for e2ae	91
6.2.10.3.1.1.1	Incoming TCP bearer establishment triggers an outgoing TCP bearer establishment	91
6.2.10.3.1.1.2	IMS-ALG requests sending an outgoing TCP bearer establishment	94
6.2.10.3.1.2	IMS UE terminating procedures for e2ae	96
6.2.10.3.1.2.1	Incoming TCP bearer establishment triggers an outgoing TCP bearer establishment	96
6.2.10.3.1.2.2	IMS-ALG requests sending an outgoing TCP bearer establishment	99
6.2.10.3.2	End-to-access-edge security for conferencing (BFCP).....	101
6.2.10.3.2.1	IMS UE originating procedures for e2ae	101
6.2.10.3.2.1.1	Incoming TCP bearer establishment triggers an outgoing TCP bearer establishment	101
6.2.10.3.2.2	IMS UE terminating procedures for e2ae	104
6.2.10.3.2.2.1	Incoming TCP bearer establishment triggers an outgoing TCP bearer establishment	104
6.2.10.4	End-to-access-edge security for UDP based media using DTLS	107
6.2.10.4.1	General	107
6.2.10.4.2	Session establishment from IMS access network for T.38 fax using "UDP/TLS/UDPTL"	107
6.2.10.4.3	Session establishment towards IMS access network for T.38 fax using "UDP/TLS/UDPTL"	110
6.2.10.4.4	IMS-AGW procedure for e2ae security of T.38 fax using "UDP/TLS/UDPTL"	112
6.2.10.4.5	DTLS session establishment failure indication	112
6.2.10.5	End-to-access-edge security for RTP based media using DTLS-SRTP	113
6.2.10.6	End-to-access-edge security for WebRTC data channels using SCTP-over-DTLS transport.....	117
6.2.10.6.1	General	117
6.2.10.6.2	Call flow for data channel establishment from WIC towards IMS access network and MSRP session establishment.....	117
6.2.10A	IMS end-to-end Media Plane Security	120
6.2.10A.1	End-to-end security for RTP based media using SDES	120
6.2.10A.2	End-to-end security for TCP-based media using TLS	120
6.2.11	Change Through-Connection.....	120
6.2.12	Emergency Calls	120
6.2.13	Explicit Congestion Notification support	120
6.2.13.1	General	120
6.2.13.2	ECN Active Indicated (ECN transparent).....	120
6.2.13.3	ECN support requested (ECN endpoint)	121
6.2.13.4	ECN Failure Indication (ECN endpoint).....	121
6.2.14	Access Transfer procedures with media anchored in IMS-AGW (ATGW)	122
6.2.14.1	General	122
6.2.14.2	H.248 context model	122
6.2.14.3	PS session origination or termination with media anchoring in IMS-AGW (ATGW) signaling procedures	124
6.2.14.4	PS to CS Access Transfer procedure with media anchored in IMS-AGW (ATGW).....	126
6.2.14.5	ECN support during PS to CS Access Transfer procedure with media anchored in IMS-AGW (ATGW)	127
6.2.14.6	Support of generic image attributes	128
6.2.14.6.1	General	128
6.2.14.6.2	Indication of generic image attributes	129

6.2.14.7	Handling of common codec parameters	129
6.2.14.8	EVS speech codec support	130
6.2.15	Multimedia Priority Congestion Control Procedures	145
6.2.15.1	General	145
6.2.15.2	IMS-AGW Resource Congestion in ADD response, request is queued	145
6.2.15.3	IMS-AGW Resource Congestion in ADD response, IMS-ALG seizes new IMS-AGW	146
6.2.15.4	IMS-AGW Priority Resource Allocation	146
6.2.15.5	IMS-AGW Priority User Data marking	147
6.2.15.6	IMS-AGW Priority Modification	147
6.2.16	Coordination of Video Orientation	148
6.2.17	Procedures for Interactive Connectivity Establishment (ICE)	149
6.2.17.1	ICE lite	149
6.2.17.2	Full ICE	149
6.2.17.3	Connectivity check result notification (full ICE)	150
6.2.17.4	New peer reflexive candidate notification (full ICE)	150
6.2.17.5	STUN consent freshness test	151
6.2.17.6	STUN Consent Freshness Test Failure Notification	152
6.2.18	TCP bearer connection control	152
6.2.18.1	General	152
6.2.18.2	Stateless TCP handling	152
6.2.18.3	State-aware TCP handling without support of modifying the TCP setup direction	152
6.2.18.4	State-aware TCP handling with support of modifying the TCP setup direction	152
6.2.19	Application-aware MSRP interworking at the IMS-AGW	154
6.2.20	Alternate Connection (ALTC) Addresses Management	155
6.2.21	Video Region-of-Interest (ROI)	157
6.2.21.1	Video Region-of-Interest (ROI) using FECC	157
6.2.21.2	"Predefined ROI" mode	158
6.2.21.3	"Arbitrary ROI" mode	159
6.2.22	WebRTC	160
6.2.22.1	Establishment of a WebRTC data channel	160
6.2.22.2	Release of a WebRTC data channel	160
6.2.22.3	Media Plane Optimization	162
7	Charging	164
8	Messages/Procedures and Contents	164
8.1	General	164
8.2	Reserve and Configure AGW Connection Point	165
8.3	Reserve AGW Connection Point Procedure	173
8.4	Configure AGW Connection Point Procedure	180
8.5	Release AGW Termination	188
8.6	Termination heartbeat indication	188
8.7	IMS-AGW Out-of-Service	189
8.8	IMS-AGW Communication Up	189
8.9	IMS-AGW Restoration	190
8.10	IMS-AGW Register	190
8.11	IMS-ALG Restoration	191
8.12	IMS-AGW Re-register	191
8.13	IMS-ALG Ordered Re-registration	192
8.14	Audit Value	192
8.15	Audit Capability	193
8.16	Capability Update	193
8.17	IMS-ALG Out of Service	194
8.18	IMS-AGW Resource Congestion Handling - Activate	194
8.19	IMS-AGW Resource Congestion Handling - Indication	195
8.20	Inactivity Timeout Activate	195
8.21	Inactivity Timeout Notification	196
8.22	Command Reject	196
8.23	Realm Availability Activate	197
8.24	Realm Availability Notification	197
8.25	IP Bearer Released	198
8.26	Media Inactivity Notification	198

8.27	Termination Out-of-Service	199
8.28	Change Through-Connection	199
8.29	Change Flow Direction	200
8.30	ECN Failure Indication	200
8.31	Notify (D)TLS session establishment Failure Indication	201
8.32	Notify TCP connection establishment Failure Indication.....	201
8.33	ICE Connectivity Check Result Notification	202
8.34	ICE New Peer Reflexive Candidate Notification	202
8.35	STUN Consent Freshness Test Failure Notification	203
8.36	Notify SCTP Stream Reset.....	203
8.37	Notify SCTP Stream Reset Result.....	204
Annex A (informative):	Change history	205
History		207

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/e50300cc-363d-42ab-ae2b-b25a5351ae8/etsi-ts-123-334-v13.10.0-2020-01>

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/e50300cc-363d-42ab-ae2b-b25a5351ae8/etsi-ts-123-334-v13.10.0-2020-01>

1 Scope

Annex G of 3GPP TS 23.228 [2] gives out an IMS Application Level Gateway (IMS-ALG) and IMS Access Media Gateway (IMS-AGW) based reference model to support NAPT-PT, gate control and traffic policing between IP-CAN and IMS domain.




Figure 1.1: Scope of the specification

Figure 1.1 illustrates the reference model for Iq:

- the dashed line represents the IP signalling-path with SIP (at Gm) as call/session control protocol between the UE and the P-CSCF (IMS-ALG);
- the bold, horizontal line represents the IP media-path (also known as (IP) bearer-path or (IP) data-path; the notion 'media' is used as generic term for "IP application data"); and
- the vertical line represents the Iq control-path with H.248 as gateway/policy control protocol between the IMS-ALG and the IMS-AGW (H.248 messages are transported over IP).

The Iq reference point is between the P-CSCF (IMS-ALG) and the IMS-AGW. It conveys the necessary information that is needed to allocate, modify and release (IP) transport addresses.

The present document defines the stage 2 description for the Iq reference point. The stage 2 shall cover the information flow between the P-CSCF (IMS-ALG) and IMS-AGW. The protocol used over the Iq interface is the gateway control protocol according ITU-T Recommendation H.248 (which is specified for Iq by an H.248 profile according 3GPP TS 29.334 [3]).

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

[1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".

[2] 3GPP TS 23.228: "IP Multimedia Subsystem (IMS), stage 2".

- [3] 3GPP TS 29.334: "IMS Application Level Gateway (IMS-ALG) – IMS Access Gateway (IMS-AGW) Iq interface, stage 3".
- [4] IETF RFC 2663: "IP Network Address Translator (NAT) Terminology and Considerations".
- [5] 3GPP TS 32.260: "Telecommunication management; Charging management; IP Multimedia Subsystem (IMS) charging".
- [6] IETF RFC 3556: "Session Description Protocol (SDP) Bandwidth Modifiers for RTP Control Protocol (RTCP) Bandwidth".
- [7] IETF RFC 3605: "Real Time Control Protocol (RTCP) attribute in Session Description Protocol (SDP)".
- [8] 3GPP TS 23.205: "Bearer independent circuit-switched core network; Stage 2".
- [9] ITU-T Recommendation H.248.1 (05/2002): "Gateway Control Protocol: Version 2" including the Corrigendum1 for Version 2 (03/04).
- [10] IETF RFC 2216: "Network Element Service Template".
- [11] 3GPP TS 24.229: "IP Multimedia Call Control Protocol based on SIP and SDP".
- [12] 3GPP TS 33.328: "IMS Media Plane Security".
- [13] IETF RFC 4568: "Session Description Protocol (SDP) Security Descriptions for Media Streams".
- [14] IETF RFC 3711: "The Secure Real-time Transport Protocol (SRTP)".
- [15] IETF RFC 5124: "Extended Secure RTP Profile for Real-time Transport Control Protocol (RTCP)-Based Feedback (RTP/SAVPF)".
- [16] IETF RFC 3168: "The Addition of Explicit Congestion Notification (ECN) to IP".
- [17] IETF RFC 6679: "Explicit Congestion Notification (ECN) for RTP over UDP".
- [18] 3GPP TS 23.237: "IP Multimedia subsystem (IMS) Service Continuity; Stage 2".
- [19] 3GPP TS 24.237: "IP Multimedia subsystem (IMS) Service Continuity; Stage 3".
- [20] 3GPP TS 29.162: "Interworking between the IM CN subsystem and IP networks".
- [21] 3GPP TS 26.114: "IP Multimedia Subsystem (IMS); Multimedia Telephony; Media handling and interaction".
- [22] 3GPP TS 22.153: "Multimedia Priority Service".
- [23] IETF RFC 5285: "A General Mechanism for RTP Header Extensions".
- [24] IETF RFC 6236: "Negotiation of Generic Image Attributes in the Session Description Protocol (SDP)".
- [25] IETF RFC 4975: "The Message Session Relay Protocol (MSRP)".
- [26] IETF RFC 6714: "Connection Establishment for Media Anchoring (CEMA) for the Message Session Relay Protocol (MSRP)".
- [27] IETF RFC 4583: "Session Description Protocol (SDP) Format for Binary Floor Control Protocol (BFCP) Streams".
- [28] IETF RFC 5246: "The Transport Layer Security (TLS) Protocol Version 1.2".
- [29] IETF RFC 793: "Transmission Control Protocol – DARPA Internet Program – Protocol Specification".
- [30] IETF RFC 4145: "TCP-Based Media Transport in the Session Description Protocol (SDP)".
- [31] IETF RFC 4582: "The Binary Floor Control Protocol (BFCP)".

- [32] IETF RFC 6347: "Datagram Transport Layer Security Version 1.2".
- [33] IETF RFC 7345: "UDP Transport Layer (UDPTL) over Datagram Transport Layer Security (DTLS)".
- [34] IETF draft-schwarz-mmusic-sdp-for-gw-04: "SDP codepoints for gateway control".

Editor's note: The above document cannot be formally referenced until it is published as an RFC.

- [35] GSM Association RCC.07: "Rich Communication Suite 5.1 Advanced Communications Services and Client Specification, Version 2.0, 03 May 2013".
- [36] GSM Association RCC.07: "Rich Communication Suite 5.1 Advanced Communications Services and Client Specification, Version 3.0, 25 September 2013".
- [37] Void.
- [38] ITU-T Recommendation H.248.84 (07/2012): "Gateway control protocol: NAT-traversal for peer-to-peer services".
- [39] IETF RFC 5245: "Interactive Connectivity Establishment (ICE): A Protocol for Network Address Translator (NAT) Traversal for Offer/Answer Protocols".
- [40] IETF RFC 5389: "Session Traversal Utilities for NAT (STUN)".
- [41] IETF RFC 5766: "Traversal Using Relays around NAT (TURN): Relay Extensions to Session Traversal Utilities for NAT (STUN)".
- [42] IETF RFC 5763: "Framework for Establishing a Secure Real-time Transport Protocol (SRTP) Security Context Using Datagram Transport Layer Security (DTLS)".
- [43] IETF RFC 5764: "Datagram Transport Layer Security (DTLS) Extension to Establish Keys for the Secure Real-time Transport Protocol (SRTP)".
- [44] 3GPP TS 24.371: "Web Real-Time Communications (WebRTC) client access to the IP Multimedia (IM) Core Network (CN) subsystem; Protocol specification".
- [45] IETF RFC 6135: "An Alternative Connection Model for the Message Session Relay Protocol (MSRP)".
- [46] [OMA-TS-CPM_Conversation_Function-V2_0-20150113-C](#): "CPM Conversation Functions, Candidate Version 2.0 – 13 Jan 2015".
- [47] IETF RFC 5746: "Transport Layer Security (TLS) Renegotiation Indication Extension".
- [48] 3GPP TS 33.310: "Network Domain Security (NDS); Authentication Framework (AF)".
- [49] IETF RFC 7675: "Session Traversal Utilities for NAT (STUN) Usage for Consent Freshness".
- [50] IETF RFC 6716: "Definition of the Opus Audio Codec".
- [51] 3GPP TS 26.441: "Codec for Enhanced Voice Services (EVS); General Overview".
- [52] 3GPP TS 26.445: "Codec for Enhanced Voice Services (EVS); Detailed Algorithmic Description".
- [53] IETF RFC 4566: "SDP: Session Description Protocol".
- [54] IETF RFC 4867: "RTP Payload Format and File Storage Format for the Adaptive Multi-Rate (AMR) and Adaptive Multi-Rate Wideband (AMR-WB) Audio Codecs".
- [55] IETF RFC 4566: "SDP: Session Description Protocol".
- [56] IETF RFC 7587: "RTP Payload Format for the Opus Speech and Audio Codec".
- [57] IETF RFC 6544: "TCP Candidates with Interactive Connectivity Establishment (ICE)".

- [58] IETF RFC 4571: "Framing Real-time Transport Protocol (RTP) and RTP Control Protocol (RTCP) Packets over Connection-Oriented Transport".
- [59] IETF RFC 6947: "The Session Description Protocol (SDP) Alternate Connectivity (ALTC) Attribute".
- [60] IETF RFC 5761: "Multiplexing RTP Data and Control Packets on a Single Port".
- [61] IETF draft-ietf-rtcweb-data-channel-13: "WebRTC Data Channels".

Editor's note: The above document cannot be formally referenced until it is published as an RFC.

- [62] IETF draft-ietf-mmmusic-msrp-usage-data-channel-13: "MSRP over Data Channels".

Editor's note: The above document cannot be formally referenced until it is published as an RFC.

- [63] IETF RFC 4960: "Stream Control Transmission Protocol".

- [64] IETF draft-ietf-mmmusic-sctp-sdp-26: "Session Description Protocol (SDP) Offer/Answer Procedures For Stream Control Transmission Protocol (SCTP) over Datagram Transport Layer Security (DTLS) Transport".

Editor's note: The above document cannot be formally referenced until it is published as an RFC.

- [65] IETF draft-ietf-mmmusic-data-channel-sdpneg-10: "SDP-based Data Channel Negotiation".

Editor's note: The above document cannot be formally referenced until it is published as an RFC.

- [66] IETF RFC 5939: "Session Description Protocol (SDP) Capability Negotiation".

- [67] IETF RFC 6871: "Session Description Protocol (SDP) Media Capabilities Negotiation".

- [68] IETF RFC 4573: "MIME Type Registration for RTP Payload Format for H.224".

- [69] ITU-T Recommendation H.224 (01/2005): "A real time control protocol for simplex applications using the H.221 LSD/HSD/MLP channels".

- [70] ITU-T Recommendation H.281 (11/1994): "A far end camera control protocol for videoconferences using H.224".

- [71] Void

- [72] Void

- [73] Void

- [74] Void

- [75] Void

- [76] Void

- [77] Void

- [78] Void

- [79] Void

- [80] IETF RFC 8122: "Connection-Oriented Media Transport over the Transport Layer Security (TLS) Protocol in the Session Description Protocol (SDP)".

- [81] IETF draft-ietf-mmmusic-dtls-sdp-32: "Session Description Protocol (SDP) Offer/Answer Considerations for Datagram Transport Layer Security (DTLS) and Transport Layer Security (TLS)".

Editor's note: The above document cannot be formally referenced until it is published as an RFC.