



**5G;
5G System;
Common Data Types for Service Based Interfaces;
Stage 3
(3GPP TS 29.571 version 15.6.0 Release 15)**

PREVIEW
https://standards.iteh.ai/catalog/standards/sist/e71a0719-2eae-4202-a662-fe572db965a1/etsi-ts-129-571-v15.6.0-2020-01



Reference

RTS/TSGC-0429571vf60

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	6
1 Scope	7
2 References	7
3 Definitions and abbreviations.....	8
3.1 Definitions	8
3.2 Abbreviations	8
4 Overview	8
5 Common Data Types.....	8
5.1 Introduction	8
5.2 Data Types for Generic Usage	9
5.2.1 Introduction.....	9
5.2.2 Simple Data Types.....	9
5.2.3 Enumerations	13
5.2.3.1 Enumeration: PatchOperation	13
5.2.3.2 Enumeration: UriScheme	14
5.2.3.3 Enumeration: ChangeType.....	14
5.2.4 Structured Data Types	15
5.2.4.1 Type: ProblemDetails.....	15
5.2.4.2 Type: Link.....	15
5.2.4.3 Type PatchItem	16
5.2.4.4 Type: LinksValueSchema	16
5.2.4.5 Type: SelfLink	16
5.2.4.6 Type: InvalidParam	16
5.2.4.7 Type: LinkRm	16
5.2.4.8 Type ChangeItem	17
5.2.4.9 Type NotifyItem.....	17
5.2.4.10 Type: ComplexQuery.....	17
5.2.4.11 Type: Cnf	18
5.2.4.12 Type: Dnf	18
5.2.4.13 Type: CnfUnit	18
5.2.4.14 Type: DnfUnit.....	18
5.2.4.15 Type: Atom	18
5.3 Data Types related to Subscription, Identification and Numbering	19
5.3.1 Introduction.....	19
5.3.2 Simple Data Types.....	19
5.3.3 Enumerations	22
5.3.4 Structured Data Types	22
5.3.4.1 Type: Guami	22
5.3.4.2 Type: NetworkId	22
5.3.4.3 Type: GuamiRm.....	22
5.4 Data Types related to 5G Network.....	22
5.4.1 Introduction.....	22
5.4.2 Simple Data Types.....	22
5.4.3 Enumerations	25
5.4.3.1 Enumeration: AccessType	25
5.4.3.2 Enumeration: RatType	25
5.4.3.3 Enumeration: PduSessionType	26
5.4.3.4 Enumeration: UpIntegrity	26
5.4.3.5 Enumeration: UpConfidentiality	26
5.4.3.6 Enumeration: SscMode	26

5.4.3.7	Enumeration: DnaiChangeType	26
5.4.3.8	Enumeration: RestrictionType	27
5.4.3.9	Enumeration: CoreNetworkType	27
5.4.3.10	Enumeration: AccessTypeRm	27
5.4.3.11	Enumeration: RatTypeRm	27
5.4.3.12	Enumeration: PduSessionTypeRm	27
5.4.3.13	Enumeration: UpIntegrityRm	27
5.4.3.14	Enumeration: UpConfidentialityRm	27
5.4.3.15	Enumeration: SscModeRm	28
5.4.3.17	Enumeration: DnaiChangeTypeRm	28
5.4.3.18	Enumeration: RestrictionTypeRm	28
5.4.3.19	Enumeration: CoreNetworkType	28
5.4.3.20	Enumeration: PresenceState	28
5.4.4	Structured Data Types	28
5.4.4.1	Type: SubscribedDefaultQos	28
5.4.4.2	Type: Snsai	29
5.4.4.3	Type: PlmnId	29
5.4.4.4	Type: Tai	29
5.4.4.5	Type: Ecgi	30
5.4.4.6	Type: Ncgi	30
5.4.4.7	Type: UserLocation	30
5.4.4.8	Type: EutraLocation	31
5.4.4.9	Type: NrLocation	32
5.4.4.10	Type: N3gaLocation	33
5.4.4.11	Type: UpSecurity	33
5.4.4.12	Type: NgApCause	34
5.4.4.13	Type: BackupAmfInfo	34
5.4.4.14	Type: RefToBinaryData	34
5.4.4.15	Type RouteToLocation	34
5.4.4.16	Type RouteInformation	35
5.4.4.17	Type: Area	35
5.4.4.18	Type: ServiceAreaRestriction	35
5.4.4.19	Type: PlmnIdRm	35
5.4.4.20	Type: TaiRm	36
5.4.4.21	Type: EcgiRm	36
5.4.4.22	Type: NcgiRm	36
5.4.4.23	Type: EutraLocationRm	36
5.4.4.24	Type: NrLocationRm	36
5.4.4.25	Type: UpSecurityRm	36
5.4.4.26	Type: RefToBinaryDataRm	36
5.4.4.27	Type: PresenceInfo	37
5.4.4.28	Type: GlobalRanNodeId	37
5.4.4.29	Type: GNBId	38
5.4.4.30	Type: PresenceInfoRm	38
5.5	Data Types related to 5G QoS	38
5.5.1	Introduction	38
5.5.2	Simple Data Types	38
5.5.3	Enumerations	41
5.5.3.1	Enumeration: PreemptionCapability	41
5.5.3.2	Enumeration: PreemptionVulnerability	41
5.5.3.3	Enumeration: ReflectiveQosAttribute	41
5.5.3.4	Void	41
5.5.3.5	Enumeration: NotificationControl	41
5.5.3.6	Enumeration: QosResourceType	42
5.5.3.7	Enumeration: PreemptionCapabilityRm	42
5.5.3.8	Enumeration: PreemptionVulnerabilityRm	42
5.5.3.9	Enumeration: ReflectiveQosAttributeRm	42
5.5.3.10	Enumeration: NotificationControlRm	42
5.5.3.11	Enumeration: QosResourceTypeRm	42
5.5.3.12	Enumeration: AdditionalQosFlowInfo	42
5.5.4	Structured Data Types	43
5.5.4.1	Type: Arp	43

5.5.4.2	Type: Ambr	43
5.5.4.3	Type: Dynamic5Qi	43
5.5.4.4	Type: NonDynamic5Qi	44
5.5.4.5	Type: ArpRm	44
5.5.4.6	Type: AmbrRm	44
5.6	Data Types related to 5G Trace	44
5.6.1	Introduction	44
5.6.2	Simple Data Types	44
5.6.3	Enumerations	44
5.6.3.1	Enumeration: TraceDepth	44
5.6.3.2	Enumeration: TraceDepthRm	45
5.6.4	Structured Data Types	46
5.6.4.1	Type: TraceData	46
5.7	Data Types related to 5G Operator Determined Barring	48
5.7.1	Introduction	48
5.7.2	Simple Data Types	48
5.7.3	Enumerations	48
5.7.3.1	Enumeration: RoamingOdb	48
5.7.3.2	Enumeration: OdbPacketServices	48
5.7.4	Structured Data Types	49
5.7.4.1	Type: OdbData	49
5.8	Data Types related to Charging	49
5.8.1	Introduction	49
5.8.2	Simple Data Types	49
5.8.3	Enumerations	49
5.8.4	Structured Data Types	49
5.8.4.1	Type: SecondaryRatUsageReport	49
5.8.4.2	Type: QoSFlowUsageReport	50
5.8.4.3	Type: SecondaryRatUsageInfo	50
5.8.4.4	Type: VolumeTimedReport	50
Annex A (normative):	OpenAPI specification	51
A.1	General	51
A.2	Data related to Common Data Types	51
Annex B (informative):	Change history	75
History		78

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

PREVIEW
iTech STANDARD
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/e71a0719-2eae-4202-a662-fe572db965a/etsi-ts-129-571-v15.6.0-2020-01>

1 Scope

The present document specifies the stage 3 protocol and data model for common data types that are used or may be expected to be used by multiple Service Based Interface APIs supported by the same or different Network Function(s).

The Principles and Guidelines for Services Definition are specified in 3GPP TS 29.501 [2].

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 29.501: "5G System; Principles and Guidelines for Services Definition; Stage 3".
- [3] OpenAPI: "OpenAPI 3.0.0 Specification", <https://github.com/OAI/OpenAPI-Specification/blob/master/versions/3.0.0.md>.
- [4] IETF RFC 1166: "Internet Numbers".
- [5] IETF RFC 5952: "A recommendation for IPv6 address text representation".
- [6] IETF RFC 3986: "Uniform Resource Identifier (URI): Generic Syntax".
- [7] 3GPP TS 23.003: "Numbering, addressing and identification".
- [8] 3GPP TS 23.501: "System Architecture for the 5G System; Stage 2".
- [9] IETF RFC 7807: "Problem Details for HTTP APIs".
- [10] IETF RFC 3339: "Date and Time on the Internet: Timestamps".
- [11] 3GPP TS 38.413: "NG-RAN; NG Application Protocol (NGAP) ".
- [12] IETF RFC 6901: "JavaScript Object Notation (JSON) Pointer".
- [13] 3GPP TS 24.007: "Mobile radio interface signalling layer 3; General aspects".
- [14] IETF RFC 6902: "JavaScript Object Notation (JSON) Patch".
- [15] IETF RFC 4122: "A Universally Unique IDentifier (UUID) URN Namespace".
- [16] 3GPP TS 36.413: "Evolved Universal Terrestrial Radio Access Network (E-UTRAN); S1 Application Protocol (S1AP)".
- [17] IETF RFC 7042: "IANA Considerations and IETF Protocol and Documentation Usage for IEEE 802 Parameters".
- [18] IETF RFC 6733: "Diameter Base Protocol".
- [19] 3GPP TS 32.422: "Telecommunication management; Subscriber and equipment trace; Trace control and configuration management".
- [20] 3GPP TS 24.501: "Non-Access-Stratum (NAS) Protocol for 5G System (5GS); Stage 3".

- [21] 3GPP TS 29.002: "Mobile Application Part (MAP) specification".
- [22] Void.
- [23] 3GPP TS 23.032: "Universal Geographical Area Description (GAD)".
- [24] ITU-T Recommendation Q.763 (1999): "Specifications of Signalling System No.7; Formats and codes".
- [25] 3GPP TS 29.500: "5G System; Technical Realization of Service Based Architecture; Stage 3".
- [26] 3GPP TS 23.015: "Technical Realization of Operator Determined Barring".
- [27] 3GPP TR 21.900: "Technical Specification Group working methods".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

5GC	5G Core Network
DNAI	Data Network Access Identifier
GPSI	Generic Public Subscription Identifier
GUAMI	Globally Unique AMF Identifier
PEI	Permanent Equipment Identifier
SBI	Service Based Interface
SUPI	Subscription Permanent Identifier

4 Overview

For the different 5GC SBI API, data types shall be defined. Data types identified as common data types shall be defined in this Technical specification and should be referenced from individual 5GC SBI API specifications.

Data types applicable or intended to be applicable to several 5GC SBI API specifications should be interpreted as common data types.

5 Common Data Types

5.1 Introduction

In the following clauses, common data types for the following areas are defined:

- Data types for generic usage;
- Data types for Subscription, Identification and Numbering;
- Data types related to 5G Network;

- Data types related to 5G QoS;
- Data types related to 5G Trace;
- Data types related to 5G ODBs.

5.2 Data Types for Generic Usage

5.2.1 Introduction

This clause defines common data types for generic usage.

5.2.2 Simple Data Types

This clause specifies common simple data types.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

Full standard:
<https://standards.iteh.ai/catalog/standards/sist/e71a0719-2eae-4202-a662-fe572db965a/etsi-ts-129-571-v15.6.0-2020-01>

Table 5.2.2-1: Simple Data Types

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/e71a0719-2eae-4202-a662-fe572db965a/etsi-ts-129-571-v15.6.0-2020-01>

Type Name	Type Definition	Description
Binary	string	String with format "binary" as defined in OpenAPI Specification [3]
BinaryRm	string	This data type is defined in the same way as the "Binary" data type, but with the OpenAPI "nullable: true" property.
Bytes	string	String with format "byte" as defined in OpenAPI Specification [3], i.e. base64-encoded characters.
BytesRm	string	This data type is defined in the same way as the "Bytes" data type, but with the OpenAPI "nullable: true" property.
Date	string	String with format "date" as defined in OpenAPI Specification [3]
DateRm	string	This data type is defined in the same way as the "Date" data type, but with the OpenAPI "nullable: true" property.
DateTime	string	String with format "date-time" as defined in OpenAPI Specification [3]
DateTimeRm	string	This data type is defined in the same way as the "DateTime" data type, but with the OpenAPI "nullable: true" property.
DiameterIdentity	string	String containing a Diameter Identity, according to clause 4.3 of IETF RFC 6733 [18]. Pattern: '^([A-Za-z0-9]+([-A-Za-z0-9+\.])+[a-z]{2,})\$'
DiameterIdentityRm	string	This data type is defined in the same way as the "DiameterIdentity" data type, but with the OpenAPI "nullable: true" property.
Double	number	Number with format "double" as defined in OpenAPI Specification [3]
DoubleRm	number	This data type is defined in the same way as the "Double" data type, but with the OpenAPI "nullable: true" property.
DurationSec	integer	Unsigned integer identifying a period of time in units of seconds.
DurationSecRm	integer	This data type is defined in the same way as the "DurationSec" data type, but with the OpenAPI "nullable: true" property.
Float	number	Number with format "float" as defined in OpenAPI Specification [3]
FloatRm	number	This data type is defined in the same way as the "Float" data type, but with the OpenAPI "nullable: true" property.
Uint16	integer	Unsigned 16-bit integers, i.e. only value between 0 and 65535 are permissible.
Uint16Rm	integer	This data type is defined in the same way as the "Uint16" data type, but with the OpenAPI "nullable: true" property.
Int32	integer	Integer with format "int32" as defined in OpenAPI Specification [3]
Int32Rm	integer	This data type is defined in the same way as the "Int32" data type, but with the OpenAPI "nullable: true" property.
Int64	integer	Integer with format "int64" as defined in OpenAPI Specification [3]
Int64Rm	integer	This data type is defined in the same way as the "Int64" data type, but with the OpenAPI "nullable: true" property.
Ipv4Addr	string	String identifying a IPv4 address formatted in the "dotted decimal" notation as defined in in IETF RFC 1166 [4]. Pattern: '^([0-9]{1,3} [0-9]{4})\.([0-9]{1,3} [0-9]{4})\.([0-9]{1,3} [0-9]{4})\.([0-9]{1,3} [0-9]{4})\$'
Ipv4AddrRm	string	This data type is defined in the same way as the "Ipv4Addr" data type, but with the OpenAPI "nullable: true" property.
Ipv6Addr	string	String identifying an IPv6 address formatted according to clause 4 of IETF RFC 5952 [5]. The mixed IPv4 IPv6 notation according to clause 5 of IETF RFC 5952 [5] shall not be used. Pattern: '^(: 0? [1-9a-f]{0,3}) ((0? [1-9a-f]{0,3}) 0,6 :(0? [1-9a-f]{0,3}))\$' and Pattern: '^(((?:[0-9a-f]{1,4}) ::)([0-9a-f]{1,4})?::(((?:[0-9a-f]{1,4}) ::)))\$'
Ipv6AddrRm	string	This data type is defined in the same way as the "Ipv6Addr" data type, but with the OpenAPI "nullable: true" property.
Ipv6Prefix	string	String identifying an IPv6 address prefix formatted according to clause 4 of IETF RFC 5952 [5]. Pattern: '^(: 0? [1-9a-f]{0,3}) ((0? [1-9a-f]{0,3}) 0,6 :(0? [1-9a-f]{0,3}))\(((0-9){1,3} 0)(12[0-8])\$' and Pattern: '^(((?:[0-9a-f]{1,4}) ::)([0-9a-f]{1,4})?::(((?:[0-9a-f]{1,4}) ::)))\(((0-9){1,3} 0)(12[0-8])\$'

Ipv6PrefixRm	string	This data type is defined in the same way as the "Ipv6Prefix" data type, but with the OpenAPI "nullable: true" property.
MacAddr48	string	String identifying a MAC address formatted in the hexadecimal notation according to clause 1.1 and clause 2.1 of IETF RFC 7042 [17]. Pattern: <code>^\{0-9a-fA-F\}{2}\{(-\{0-9a-fA-F\}{2})\}{5}\\$</code>
MacAddr48Rm	string	This data type is defined in the same way as the "MacAddr48" data type, but with the OpenAPI "nullable: true" property.
SupportedFeatures	string	A string used to indicate the features supported by an API that is used as defined in clause 6.6 in 3GPP TS 29.500 [25]. The string shall contain a bitmask indicating supported features in hexadecimal representation: Each character in the string shall take a value of "0" to "9" or "A" to "F" and shall represent the support of 4 features as described in table 5.2.2-3. The most significant character representing the highest-numbered features shall appear first in the string, and the character representing features 1 to 4 shall appear last in the string. The list of features and their numbering (starting with 1) are defined separately for each API. If the string contains a lower number of characters than there are defined features for an API, all features that would be represented by characters that are not present in the string are not supported.
UInteger	integer	Unsigned Integer, i.e. only value 0 and integers above 0 are permissible.
UIntegerRm	integer	This data type is defined in the same way as the "UInteger" data type, but with the OpenAPI "nullable: true" property.
Uint32	integer	Unsigned 32-bit integers, i.e. only value 0 and 32-bit integers above 0 are permissible.
Uint32Rm	integer	This data type is defined in the same way as the "Uint32" data type, but with the OpenAPI "nullable: true" property.
Uint64	integer	Unsigned 64-bit integers, i.e. only value 0 and 64-bit integers above 0 are permissible.
Uint64Rm	integer	This data type is defined in the same way as the "Uint64" data type, but with the OpenAPI "nullable: true" property.
Uri	string	String providing an URI formatted according to IETF RFC 3986 [6].
UriRm	string	This data type is defined in the same way as the "Uri" data type, but with the OpenAPI "nullable: true" property.
VarUeld	string	String represents the SUPI or GPSI. Pattern: <code>^\{imsi-\{0-9\}\{5,15\}\nai-\.\+msisdn-\{0-9\}\{5,15\}\extid-\{^\+@\{^\+\}\}\}\\$</code> .
VarUeldRm	string	This data type is defined in the same way as the "VarUeld" data type, but with the OpenAPI "nullable: true" property.
TimeZone	string	String with format " <code><time-numoffset></code> " optionally appended by " <code><daylightSavingTime></code> ", where: - <code><time-numoffset></code> shall represent the time zone adjusted for daylight saving time and be encoded as time-numoffset as defined in clause 5.6 of IETF RFC 3339 [10]; - <code><daylightSavingTime></code> shall represent the adjustment that has been made and shall be encoded as "+1" or "+2" for a +1 or +2 hours adjustment. Example: "-08:00+1" (for 8 hours behind UTC, +1 hour adjustment for Daylight Saving Time).
TimeZoneRm	string	This data type is defined in the same way as the "TimeZone" data type, but with the OpenAPI "nullable: true" property.