

ETSI TS 136 306 V15.7.0 (2020-01)



LTE;
**Evolved Universal Terrestrial Radio Access (E-UTRA);
User Equipment (UE) radio access capabilities
(3GPP TS 36.306 version 15.7.0 Release 15)**

iTeh 5G Network PREVIEW
Full standard
<https://standards.iteh.ai/catalog/etsi-ts-136-306-v15.7.0-2020-01-4538-8062-4d3a835fc478/etsi-ts-136-306-v15.7.0-2020-01>



Reference

RTS/TSGR-0236306vf70

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and
of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	16
1 Scope	17
2 References	17
3 Definitions, symbols and abbreviations	19
3.1 Definitions.....	19
3.2 Symbols.....	19
3.3 Abbreviations	19
4 UE radio access capability parameters	20
4.1 <i>ue-Category</i>	22
4.1A <i>ue-CategoryDL</i> and <i>ue-CategoryUL</i>	25
4.1B <i>ue-CategorySL-C-RX</i> , <i>ue-CategorySL-C-TX</i> and <i>ue-CategorySL-D</i>	46
4.1C <i>ue-Category-NB</i>	47
4.2 Parameters set by the field <i>ue-Category</i> and <i>ue-CategoryDL</i> / <i>ue-CategoryUL</i>	48
4.2.1 Transport channel parameters in downlink.....	48
4.2.1.1 Maximum number of DL-SCH transport block bits received within a TTI	48
4.2.1.2 Maximum number of bits of a DL-SCH transport block received within a TTI	48
4.2.1.3 Total number of DL-SCH soft channel bits.....	48
4.2.1.4 Maximum number of bits of a MCH transport block received within a TTI	49
4.2.2 Transport channel parameters in uplink.....	49
4.2.2.1 Maximum number of bits of an UL-SCH transport block transmitted within a TTI.....	49
4.2.2.2 Maximum number of UL-SCH transport block bits transmitted within a TTI.....	49
4.2.3 Physical channel parameters in downlink (DL)	49
4.2.3.1 Maximum number of supported layers for spatial multiplexing in DL.....	49
4.2.4 Physical channel parameters in uplink (UL)	49
4.2.4.1 Support for 64QAM in UL.....	49
4.2.5 Total layer 2 buffer size	49
4.2.6 Half-duplex FDD operation type	49
4.2.7 RF parameters	49
4.2.7.1 Maximum UE channel bandwidth.....	49
4.2A Parameters set by <i>ue-CategorySL-C</i> / <i>ue-CategorySL-D</i>	50
4.2A.1 Transport channel parameters in sidelink (SL)	50
4.2A.1.1 Maximum number of SL-SCH transport block bits received within a TTI.....	50
4.2A.1.2 Maximum number of bits of a SL-SCH transport block received within a TTI.....	50
4.2A.1.3 Maximum number of SL-DCH transport block bits received within a TTI	50
4.2A.1.4 Maximum number of bits of a SL-DCH transport block received within a TTI	50
4.2A.1.5 Maximum number of bits of a SL-SCH transport block transmitted within a TTI	50
4.2A.1.6 Maximum number of SL-SCH transport block bits transmitted within a TTI	50
4.2A.1.7 Maximum number of bits of a SL-DCH transport block transmitted within a TTI.....	50
4.2A.1.8 Maximum number of SL-DCH transport block bits transmitted within a TTI.....	50
4.2A.2 Physical channel parameters in sidelink (SL)	50
4.2A.2.1 Maximum number of supported layers for spatial multiplexing in SL-C	50
4.2A.2.2 Maximum number of supported layers for spatial multiplexing in SL-D	50
4.3 Parameters independent of the field <i>ue-Category</i> and <i>ue-CategoryDL</i> / <i>ue-CategoryUL</i>	51
4.3.1 PDCP Parameters.....	51
4.3.1.1 <i>supportedROHC-Profiles</i>	51
4.3.1.1A <i>supportedROHC-Profiles-r13</i>	51
4.3.1.2 <i>maxNumberROHC-ContextSessions</i>	51
4.3.1.2A <i>maxNumberROHC-ContextSessions-r13</i>	52
4.3.1.3 <i>pdcpc-SN-Extension</i>	52
4.3.1.4 <i>supportRohcContextContinue</i>	52
4.3.1.5 <i>pdcpc-SN-Extension-18bits-r13</i>	52

4.3.1.6	<i>supportedUplinkOnlyROHC-Profiles</i>	52
4.3.1.7	<i>supportedUDC-r15</i>	52
4.3.1.8	<i>supportedStandardDic-r15</i>	52
4.3.1.9	<i>supportedOperatorDic-r15</i>	52
4.3.1.7	<i>pdcp-Duplication-r15</i>	52
4.3.1A	NR PDCP Parameters	52
4.3.2	RLC parameters	53
4.3.2.1	Void.....	53
4.3.2.2	<i>extended-RLC-LI-Field-r12</i>	53
4.3.2.3	<i>extendedRLC-SN-SO-Field-r13</i>	53
4.3.2.4	<i>extendedPollByte-r14</i>	53
4.3.2.5	<i>rlc-UM-r15</i>	53
4.3.2.6	<i>rlc-AM-Ooo-Delivery-r15</i>	53
4.3.2.7	<i>rlc-UM-Ooo-Delivery-r15</i>	53
4.3.2.8	<i>flexibleUM-AM-Combinations-r15</i>	53
4.3.3	Void	53
4.3.4	Physical layer parameters	53
4.3.4.1	<i>ue-TxAntennaSelectionSupported</i>	53
4.3.4.2	<i>ue-SpecificRefSigsSupported</i>	53
4.3.4.3	Void.....	54
4.3.4.4	<i>enhancedDualLayerFDD</i>	54
4.3.4.5	<i>enhancedDualLayerTDD</i>	54
4.3.4.6	<i>supportedMIMO-CapabilityUL-r10</i>	54
4.3.4.7	<i>supportedMIMO-CapabilityDL-r10</i>	54
4.3.4.8	<i>two-AntennaPortsForPUCCH-r10</i>	54
4.3.4.9	<i>tm9-With-8Tx-FDD-r10</i>	54
4.3.4.10	<i>pmi-Disabling-r10</i>	54
4.3.4.11	<i>crossCarrierScheduling-r10</i>	54
4.3.4.12	<i>simultaneousPUCCH-PUSCH-r10</i>	54
4.3.4.13	<i>multiClusterPUSCH-WithinCC-r10</i>	55
4.3.4.14	<i>nonContiguousUL-RA-WithinCC-Info-r10</i>	55
4.3.4.15	<i>crs-InterfHandl-r11</i>	55
4.3.4.16	Void.....	55
4.3.4.17	Void.....	55
4.3.4.18	<i>ePDCCH-r11</i>	55
4.3.4.19	<i>multiACK-CSl-Reporting-r11</i>	55
4.3.4.20	<i>ss-CCH-InterfHandl-r11</i>	55
4.3.4.21	<i>tdd-SpecialSubframe-r11</i>	55
4.3.4.21A	<i>tdd-SpecialSubframe-r14</i>	55
4.3.4.21B	<i>ssp10-TDD-Only-r14</i>	56
4.3.4.22	<i>txDiv-PUCCH1b-ChSelect-r11</i>	56
4.3.4.23	<i>ul-CoMP-r11</i>	56
4.3.4.24	<i>tm5-FDD</i>	56
4.3.4.25	<i>tm5-TDD</i>	56
4.3.4.26	<i>interBandTDD-CA-WithDifferentConfig-r11</i>	56
4.3.4.27	<i>e-HARQ-Pattern-FDD-r12</i>	56
4.3.4.28	<i>tdd-FDD-CA-PCellDuplex-r12</i>	56
4.3.4.29	<i>csi-SubframeSet-r12</i>	56
4.3.4.30	<i>phy-TDD-ReConfig-FDD-PCell-r12</i>	56
4.3.4.31	<i>phy-TDD-ReConfig-TDD-PCell-r12</i>	57
4.3.4.32	<i>pusch-SRS-PowerControl-SubframeSet-r12</i>	57
4.3.4.33	<i>enhanced-4TxCodebook-r12</i>	57
4.3.4.34	<i>pusch-FeedbackMode-r12</i>	57
4.3.4.35	<i>naics-Capability-List-r12</i>	57
4.3.4.36	<i>noResourceRestrictionForTTIBundling-r12</i>	57
4.3.4.37	Void.....	57
4.3.4.38	<i>discoverySignalsInDeactSCell-r12</i>	57
4.3.4.39	<i>ul-64QAM-r12</i>	57
4.3.4.40	<i>supportedMIMO-CapabilityDL-r12</i>	57
4.3.4.41	<i>alternativeTBS-Indices-r12</i>	57
4.3.4.42	<i>codebook-HARQ-ACK-r13</i>	58
4.3.4.43	<i>fdd-HARQ-TimingTDD-r13</i>	58

4.3.4.44	<i>maxNumberUpdatedCSI-Proc-r13</i>	58
4.3.4.45	<i>pucch-Format4-r13</i>	58
4.3.4.46	<i>pucch-Format5-r13</i>	58
4.3.4.47	<i>pucch-SCell-r13</i>	58
4.3.4.48	<i>supportedBlindDecoding-r13</i>	58
4.3.4.48.1	<i>maxNumberDecoding-r13</i>	58
4.3.4.48.2	<i>pdcch-CandidateReductions-r13</i>	58
4.3.4.48.3	<i>skipMonitoringDCI-Format0-1A-r13</i>	58
4.3.4.49	<i>crs-InterfMitigationTM10-r13</i>	58
4.3.4.49a	<i>crs-InterfMitigationTM1toTM9-r13</i>	59
4.3.4.50	<i>pdsch-CollisionHandling-r13</i>	59
4.3.4.51	<i>aperiodicCSI-Reporting-r13</i>	59
4.3.4.52	<i>crossCarrierScheduling-B5C-r13</i>	59
4.3.4.53	<i>spatialBundling-HARQ-ACK-r13</i>	59
4.3.4.54	<i>uci-PUSCH-Ext-r13</i>	59
4.3.4.55	<i>multiTone-r13</i>	59
4.3.4.56	<i>multiCarrier-r13</i>	60
4.3.4.57	<i>cch-InterfMitigation-RefRecTypeA-r13</i>	60
4.3.4.58	<i>cch-InterfMitigation-RefRecTypeB-r13</i>	60
4.3.4.59	<i>cch-InterfMitigation-MaxNumCCs-r13</i>	60
4.3.4.60	<i>tdd-TTI-Bundling-r14</i>	60
4.3.4.61	<i>dmrs-LessUpPTS-r14</i>	60
4.3.4.62	<i>twoHARQ-Proceses-r14</i>	60
4.3.4.63	<i>ce-PUSCH-NB-MaxTBS-r14</i>	60
4.3.4.64	<i>ce-PDSCH-PUSCH-MaxBandwidth-r14</i>	60
4.3.4.65	<i>ce-HARQ-AckBundling-r14</i>	61
4.3.4.66	<i>ce-PDSCH-TenProcesses-r14</i>	61
4.3.4.67	<i>ce-RetuningSymbols-r14</i>	61
4.3.4.68	<i>ce-PDSCH-PUSCH-Enhancement-r14</i>	61
4.3.4.69	<i>ce-SchedulingEnhancement-r14</i>	61
4.3.4.70	<i>ce-SRS-Enhancement-r14</i>	61
4.3.4.70A	<i>ce-SRS-EnhancementWithoutComb4-r14</i>	61
4.3.4.71	<i>ce-PUCCH-Enhancement-r14</i>	61
4.3.4.72	<i>ce-ClosedLoopTxAntennaSelection-r14</i>	61
4.3.4.73	<i>ul-256QAM-r14</i>	62
4.3.4.74	<i>alternativeTBS-Index-r14</i>	62
4.3.4.75	<i>multiCarrier-NPRACH-r14</i>	62
4.3.4.76	<i>multiCarrierPaging-r14</i>	62
4.3.4.77	<i>ul-256QAM-perCC-InfoListr14</i>	62
4.3.4.78	<i>unicast-fembmsMixedSCell-r14</i>	62
4.3.4.79	<i>emptyUnicastRegion-r14</i>	62
4.3.4.80	<i>interferenceRandomisation-r14</i>	62
4.3.4.81	<i>must-CapabilityPerBand-r14</i>	62
4.3.4.81.1	<i>must-TM234-UpTo2Tx-r14</i>	62
4.3.4.81.2	<i>must-TM89-UpToOneInterferingLayer-r14</i>	62
4.3.4.81.3	<i>must-TM10-UpToOneInterferingLayer-r14</i>	63
4.3.4.81.4	<i>must-TM89-UpToThreeInterferingLayers-r14</i>	63
4.3.4.81.5	<i>must-TM10-UpToThreeInterferingLayers-r14</i>	63
4.3.4.82	<i>crs-LessDwPTS-r14</i>	63
4.3.4.83	<i>dl-1024QAM-Slot-r15</i>	63
4.3.4.84	<i>dl-1024QAM-SubslotTA-1-r15</i>	63
4.3.4.85	<i>dl-1024QAM-SubslotTA-2-r15</i>	63
4.3.4.86	<i>dmrs-PositionPattern-r15</i>	63
4.3.4.87	<i>dmrs-RepetitionSubslotPDSCH-r15</i>	63
4.3.4.88	<i>dmrs-SharingSubslotPDSCH-r15</i>	63
4.3.4.89	<i>epdcch-SPT-differentCells-r15</i>	63
4.3.4.90	<i>epdcch-STI-differentCells-r15</i>	63
4.3.4.91	<i>maxLayersSlotOrSubslotPUSCH-r15</i>	64
4.3.4.92	<i>maxNumberUpdatedCSI-Proc-SPT-r15</i>	64
4.3.4.93	<i>Void</i>	64
4.3.4.94	<i>numberOfBlindDecodesUSS-r15</i>	64
4.3.4.95	<i>pdsch-SlotSubslotPDSCH-Decoding-r15</i>	64

4.3.4.96	<i>simultaneousTx-differentTx-duration-r15</i>	64
4.3.4.97	<i>slotPDSCH-TxDiv-TM8-r15</i>	64
4.3.4.98	<i>slotPDSCH-TxDiv-TM9and10-r15</i>	64
4.3.4.99	<i>spdcch-differentRS-types-r15</i>	64
4.3.4.100	<i>spt-Parameters-r15</i>	64
4.3.4.101	<i>sps-CyclicShift-r15</i>	64
4.3.4.102	<i>subslotPDSCH-TxDiv-TM9and10-r15</i>	64
4.3.4.103	<i>sTTI-SupportedCombinations-r15</i>	65
4.3.4.104	<i>Void</i>	65
4.3.4.105	<i>sTTI-SPT-BandParameters-r15</i>	65
4.3.4.106	<i>sTTI-SupportedCSI-Proc-r15</i>	65
4.3.4.107	<i>txDiv-SPUCCH-r15</i>	65
4.3.4.108	<i>ul-256QAM-Slot-r15</i>	65
4.3.4.109	<i>ul-256QAM-Subslot-r15</i>	65
4.3.4.110	<i>ue-TxAntennaSelection-SRS-1T4R-r15</i>	65
4.3.4.111	<i>ue-TxAntennaSelection-SRS-2T4R-2Pairs-r15</i>	65
4.3.4.112	<i>ue-TxAntennaSelection-SRS-2T4R-3Pairs-r15</i>	65
4.3.4.113	<i>wakeUpSignal-r15</i>	66
4.3.4.114	<i>wakeUpSignalMinGap-eDRX-r15</i>	66
4.3.4.115	<i>mixedOperationMode-r15</i>	66
4.3.4.116	<i>void</i>	66
4.3.4.117	<i>sr-WithHARQ-ACK-r15</i>	66
4.3.4.118	<i>sr-WithoutHARQ-ACK-r15</i>	66
4.3.4.119	<i>nprach-Format2-r15</i>	66
4.3.4.120	<i>ce-UL-HARQ-ACK-Feedback-r15</i>	66
4.3.4.121	<i>ce-PDSCH-FlexibleStartPRB-CE-ModeA-r15</i>	66
4.3.4.122	<i>ce-PDSCH-FlexibleStartPRB-CE-ModeB-r15</i>	66
4.3.4.123	<i>ce-PUSCH-FlexibleStartPRB-CE-ModeA-r15</i>	66
4.3.4.124	<i>ce-PUSCH-FlexibleStartPRB-CE-ModeB-r15</i>	67
4.3.4.125	<i>ce-CRS-IntfMitig-r15</i>	67
4.3.4.126	<i>ce-PDSCH-64QAM-r15</i>	67
4.3.4.127	<i>ce-CQI-AlternativeTable-r15</i>	67
4.3.4.128	<i>ce-PUSCH-SubPRB-Allocation-r15</i>	67
4.3.4.129	<i>wakeUpSignal-TDD-r15</i>	67
4.3.4.130	<i>wakeUpSignalMinGap-eDRX-TDD-r15</i>	67
4.3.4.131	<i>shortCqi-ForSCellActivation-r15</i>	67
4.3.4.132	<i>crs-IntfMitig-r15</i>	67
4.3.4.133	<i>srs-UpPTS-6sym-r14</i>	67
4.3.4.134	<i>multiCarrierPagingTDD-r15</i>	68
4.3.4.135	<i>altMCS-Table-r15</i>	68
4.3.4.136	<i>ul-PowerControlEnhancements-r15</i>	68
4.3.4.137	<i>additionalTransmissionSIB1-r15</i>	68
4.3.4.138	<i>aperiodicCsi-ReportingSTTI-r15</i>	68
4.3.4.139	<i>dmrs-BasedSPDCCH-MBSFN-r15</i>	68
4.3.4.140	<i>dmrs-BasedSPDCCH-nonMBSFN -r15</i>	68
4.3.4.141	<i>maxNumberUpdatedCSI-Proc-STTI-Comb77-r15</i>	68
4.3.4.142	<i>maxNumberUpdatedCSI-Proc-STTI-Comb27-r15</i>	68
4.3.4.143	<i>maxNumberUpdatedCSI-Proc-STTI-Comb22-Set1-r15</i>	68
4.3.4.144	<i>maxNumberUpdatedCSI-Proc-STTI-Comb22-Set2-r15</i>	68
4.3.4.145	<i>powerUCI-SlotPUSCH-r15</i>	69
4.3.4.146	<i>powerUCI-SubslotPUSCH-r15</i>	69
4.3.4.147	<i>spdcch-Reuse-r15</i>	69
4.3.4.148	<i>sps-STTI-r15</i>	69
4.3.4.149	<i>sTTI-FD-MIMO-Coexistence-r15</i>	69
4.3.4.150	<i>sTTI-SPT-Supported-r15</i>	69
4.3.4.151	<i>tm8-slotPDSCH-r15</i>	69
4.3.4.152	<i>tm9-slotSubslot-r15</i>	69
4.3.4.153	<i>tm9-slotSubslotMBSFN-r15</i>	69
4.3.4.154	<i>tm10-slotSubslot-r15</i>	69
4.3.4.155	<i>tm10-slotSubslotMBSFN-r15</i>	69
4.3.4.156	<i>ul-AsyncHarqSharingDiff-TTI-Lengths-r15</i>	70
4.3.4.157	<i>semiStaticCFI-r15</i>	70

4.3.4.158	<i>semiStaticCFI-Pattern-r15</i>	70
4.3.4.159	<i>pdSch-RepSubframe-r15</i>	70
4.3.4.160	<i>pdSch-RepSlot-r15</i>	70
4.3.4.161	<i>pdSch-RepSubslot-r15</i>	70
4.3.4.162	<i>pusch-SPS-SubframeRepPCell-r15</i>	70
4.3.4.163	<i>pusch-SPS-SubframeRepPSCell-r15</i>	70
4.3.4.164	<i>pusch-SPS-SubframeRepSCell-r15</i>	70
4.3.4.165	<i>pusch-SPS-SlotRepPCell-r15</i>	70
4.3.4.166	<i>pusch-SPS-SlotRepPSCell-r15</i>	70
4.3.4.167	<i>pusch-SPS-SlotRepSCell-r15</i>	71
4.3.4.168	<i>pusch-SPS-SubslotRepPCell-r15</i>	71
4.3.4.169	<i>pusch-SPS-SubslotRepPSCell-r15</i>	71
4.3.4.170	<i>pusch-SPS-SubslotRepSCell-r15</i>	71
4.3.4.171	<i>pusch-SPS-MaxConfigSubframe-r15</i>	71
4.3.4.172	<i>pusch-SPS-MultiConfigSubframe-r15</i>	71
4.3.4.173	<i>pusch-SPS-MaxConfigSlot-r15</i>	71
4.3.4.174	<i>pusch-SPS-MultiConfigSlot-r15</i>	71
4.3.4.175	<i>pusch-SPS-MaxConfigSubslot-r15</i>	71
4.3.4.176	<i>pusch-SPS-MultiConfigSubslot-r15</i>	71
4.3.4.177	<i>npusch-3dot75kHz-SCS-TDD-r15</i>	72
4.3.4.178	<i>crs-IM-TM1-toTM9-OneRX-Port</i>	72
4.3.4.179	<i>cch-IM-RefRecTypeA-OneRX-Port</i>	72
4.3.4.180	<i>dmrs-OverheadReduction-r15</i>	72
4.3.4.181	<i>srs-DCI7-TriggeringFS2-r15</i>	72
4.3.5	RF parameters	72
4.3.5.1	<i>supportedBandListEUTRA</i>	72
4.3.5.1.1	<i>ue-PowerClass-N-r13, ue-PowerClass-5-r13</i>	72
4.3.5.1.2	<i>intraFreq-CE-NeedForGaps-r13</i>	73
4.3.5.1.3	<i>ue-CA-PowerClass-N</i>	73
4.3.5.1A	<i>supportedBandList-r13</i>	73
4.3.5.1A.1	<i>powerClassNB-20dBm-r13</i>	73
4.3.5.1A.2	<i>powerClassNB-14dBm-r14</i>	73
4.3.5.2	<i>supportedBandCombination</i>	73
4.3.5.2.1	<i>supportedBandCombinationReduced-r13</i>	74
4.3.5.3	<i>multipleTimingAdvance</i>	74
4.3.5.4	<i>simultaneousRx-Tx</i>	74
4.3.5.5	<i>supportedCSI-Proc-r11</i>	75
4.3.5.6	<i>freqBandRetrieval-r11</i>	75
4.3.5.7	<i>dl-256QAM-r12</i>	75
4.3.5.8	<i>supportedNAICS-2CRS-AP-r12</i>	75
4.3.5.9	<i>dc-Support-r12</i>	75
4.3.5.9.1	<i>asynchronous-r12</i>	75
4.3.5.9.2	<i>supportedCellGrouping-r12</i>	75
4.3.5.10	<i>modifiedMPR-Behavior-r10</i>	75
4.3.5.11	<i>freqBandPriorityAdjustment-r12</i>	75
4.3.5.12	<i>commSupportedBandsPerBC-r12</i>	75
4.3.5.13	<i>supportedCSI-Proc-r12</i>	76
4.3.5.14	<i>fourLayerTM3-TM4-r10</i>	76
4.3.5.15	<i>fourLayerTM3-TM4-perCC-r12</i>	76
4.3.5.16	<i>multiNS-Pmax-r10</i>	76
4.3.5.16A	<i>multiNS-Pmax-r13</i>	76
4.3.5.17	<i>differentFallbackSupported-r13</i>	76
4.3.5.18	<i>maximumCCsRetrieval-r13</i>	76
4.3.5.19	<i>skipFallbackCombinations-r13</i>	76
4.3.5.20	<i>Void</i>	76
4.3.5.21	<i>reducedIntNonContComb-r13</i>	76
4.3.5.22	<i>additionalRx-Tx-PerformanceReq-r13</i>	77
4.3.5.23	<i>maxLayersMIMO-Indication-r12</i>	77
4.3.5.24	<i>rf-RetuningTimeDL-r14</i>	77
4.3.5.25	<i>rf-RetuningTimeUL-r14</i>	77
4.3.5.26	<i>diffFallbackCombReport-r14</i>	77
4.3.5.27	<i>v2x-SupportedTxBandCombListPerBC-r14, v2x-SupportedRxBandCombListPerBC-r14</i>	77

4.3.5.28	<i>txAntennaSwitchDL-r13</i>	77
4.3.5.29	<i>txAntennaSwitchUL-r13</i>	77
4.3.5.30	<i>supportedMIMO-CapabilityDL-r15</i>	78
4.3.5.31	<i>dl-1024QAM-r15</i>	78
4.3.5.32	<i>srs-MaxSimultaneousCCs-r14</i>	78
4.3.5.33	<i>powerClass-14dBm-r15</i>	78
4.3.5.34	<i>supportedMIMO-CapabilityDL-MRDC-r15</i>	78
4.3.5.35	<i>srs-FlexibleTiming-r14</i>	78
4.3.5.36	<i>srs-HARQ-ReferenceConfig-r14</i>	78
4.3.5.37	<i>fourLayerTM3-TM4-r15</i>	79
4.3.5.38	<i>supportedCSI-Proc-r15</i>	79
4.3.6	Measurement parameters	79
4.3.6.1	<i>interFreqNeedForGaps</i> and <i>interRAT-NeedForGaps</i>	79
4.3.6.2	<i>rsrqMeasWideband</i>	79
4.3.6.3	<i>timerT312-r12</i>	79
4.3.6.4	<i>alternativeTimeToTrigger-r12</i>	79
4.3.6.5	<i>benefitsFromInterruption-r11</i>	79
4.3.6.6	<i>incMonEUTRA-r12</i>	79
4.3.6.7	<i>incMonUTRA-r12</i>	79
4.3.6.8	<i>extendedMaxMeasId-r12</i>	80
4.3.6.9	<i>crs-DiscoverySignalsMeas-r12</i>	80
4.3.6.10	<i>csi-RS-DiscoverySignalsMeas-r12</i>	80
4.3.6.11	<i>extendedRSRQ-LowerRange-r12</i>	80
4.3.6.12	<i>rsrq-OnAllSymbols-r12</i>	80
4.3.6.13	<i>rs-SINR-Meas-r13</i>	80
4.3.6.14	<i>whiteCellList-r13</i>	80
4.3.6.15	<i>extendedFreqPriorities-r13</i>	80
4.3.6.16	<i>extendedMaxObjectIdx-r13</i>	80
4.3.6.17	<i>ul-PDCP-Delay-r13</i>	80
4.3.6.18	<i>Void</i>	81
4.3.6.19	<i>rssi-AndChannelOccupancyReporting-r13</i>	81
4.3.6.20	<i>multiBandInfoReport-r13</i>	81
4.3.6.21	<i>Void</i>	81
4.3.6.22	<i>Void</i>	81
4.3.6.23	<i>ceMeasurements-r14</i>	81
4.3.6.24	<i>ncsg-r14</i>	81
4.3.6.25	<i>perServingCellMeasurementGap-r14</i>	81
4.3.6.26	<i>shortMeasurementGap-r14</i>	81
4.3.6.27	<i>nonUniformGap-r14</i>	81
4.3.6.28	<i>rlm-ReportSupport-r14</i>	81
4.3.6.29	<i>Void</i>	81
4.3.6.30	<i>qoe-MeasReport-r15</i>	81
4.3.6.31	<i>ca-IdleModeMeasurements-r15</i>	82
4.3.6.32	<i>ca-IdleModeValidityArea-r15</i>	82
4.3.6.33	<i>qoe-MTSI-MeasReport-r15</i>	82
4.3.6.34	<i>multipleCellsMeasExtension-r15</i>	82
4.3.6.35	<i>heightMeas-r15</i>	82
4.3.6.36	<i>measGapPatterns-r15</i>	82
4.3.7	Inter-RAT parameters	82
4.3.7.1	<i>utraFDD</i>	82
4.3.7.2	<i>supportedBandListUTRA-FDD</i>	82
4.3.7.3	<i>utraTDD128</i>	82
4.3.7.4	<i>supportedBandListUTRA-TDD128</i>	82
4.3.7.5	<i>utraTDD384</i>	82
4.3.7.6	<i>supportedBandListUTRA-TDD384</i>	83
4.3.7.7	<i>utraTDD768</i>	83
4.3.7.8	<i>supportedBandListUTRA-TDD768</i>	83
4.3.7.9	<i>geran</i>	83
4.3.7.10	<i>supportedBandListGERAN</i>	83
4.3.7.11	<i>interRAT-PS-HO-ToGERAN</i>	83
4.3.7.12	<i>cdma2000-HRPD</i>	83
4.3.7.13	<i>supportedBandListHRPD</i>	83

4.3.7.14	<i>tx-ConfigHRPD</i>	83
4.3.7.15	<i>rx-ConfigHRPD</i>	83
4.3.7.16	<i>cdma2000-1xRTT</i>	83
4.3.7.17	<i>supportedBandList1XRTT</i>	84
4.3.7.18	<i>tx-Config1XRTT</i>	84
4.3.7.19	<i>rx-Config1XRTT</i>	84
4.3.7.20	<i>e-CSFB-1XRTT</i>	84
4.3.7.21	<i>e-CSFB-ConcPS-Mob1XRTT</i>	84
4.3.7.22	<i>e-RedirectionUTRA</i>	84
4.3.7.23	<i>e-RedirectionGERAN</i>	84
4.3.7.24	<i>dtm</i>	84
4.3.7.25	<i>e-CSFB-dual-1XRTT</i>	84
4.3.7.26	<i>e-RedirectionUTRA-TDD</i>	84
4.3.7.27	<i>cdma2000-NW-Sharing-r11</i>	84
4.3.7.28	<i>mfbi-UTRA</i>	85
4.3.7.29	<i>supportedBandListWLAN</i>	85
4.3.8	General parameters	85
4.3.8.1	<i>accessStratumRelease</i>	85
4.3.8.1A	<i>accessStratumRelease-r13</i>	85
4.3.8.2	<i>deviceType</i>	85
4.3.8.3	<i>Void</i>	85
4.3.8.4	<i>Void</i>	85
4.3.8.5	<i>multipleDRB-r13</i>	85
4.3.8.6	<i>Void</i>	85
4.3.8.7	<i>earlyData-UP-r15</i>	85
4.3.8.8	<i>void</i>	85
4.3.8.9	<i>extendedNumberOfDRBs-r15</i>	85
4.3.8.10	<i>reducedCP-Latency-r15</i>	85
4.3.9	<i>Void</i>	86
4.3.10	CSG Proximity Indication parameters	86
4.3.10.1	<i>intraFreqProximityIndication</i>	86
4.3.10.2	<i>interFreqProximityIndication</i>	86
4.3.10.3	<i>utran-ProximityIndication</i>	86
4.3.11	Neighbour cell SI acquisition parameters	86
4.3.11.1	<i>intraFreqSI-AcquisitionForHO</i>	86
4.3.11.2	<i>interFreqSI-AcquisitionForHO</i>	86
4.3.11.3	<i>utran-SI-AcquisitionForHO</i>	86
4.3.11.4	<i>reportCGI-NR-EN-DC-r15</i>	86
4.3.11.5	<i>reportCGI-NR-NoEN-DC-r15</i>	86
4.3.11.6	<i>eutra-CGI-Reporting-ENDC</i>	86
4.3.11.7	<i>utra-GERAN-CGI-Reporting-ENDC</i>	87
4.3.12	SON parameters	87
4.3.12.1	<i>rach-Report</i>	87
4.3.13	UE-based network performance measurement parameters	87
4.3.13.1	<i>loggedMeasurementsIdle</i>	87
4.3.13.2	<i>standaloneGNSS-Location</i>	87
4.3.13.3	<i>Void</i>	87
4.3.13.4	<i>loggedMBSFNMeasurements-r12</i>	87
4.3.13.5	<i>locationReport-r14</i>	87
4.3.13.6	<i>loggedMeasBT-r15</i>	87
4.3.13.7	<i>loggedMeasWLAN-r15</i>	87
4.3.13.8	<i>immMeasBT-r15</i>	87
4.3.13.9	<i>immMeasWLAN-r15</i>	87
4.3.14	IMS Voice parameters	88
4.3.14.1	<i>voiceOver-PS-HS-UTRA-FDD</i>	88
4.3.14.2	<i>voiceOver-PS-HS-UTRA-TDD128</i>	88
4.3.14.3	<i>srvc-FromUTRA-FDD-ToGERAN</i>	88
4.3.14.4	<i>srvc-FromUTRA-FDD-ToUTRA-FDD</i>	88
4.3.14.5	<i>srvc-FromUTRA-TDD128-ToGERAN</i>	88
4.3.14.6	<i>srvc-FromUTRA-TDD128-ToUTRA-TDD128</i>	88
4.3.15	Other parameters	88
4.3.15.1	<i>Void</i>	88

4.3.15.2	<i>inDeviceCoexInd-r11</i>	88
4.3.15.3	<i>powerPrefInd-r11</i>	88
4.3.15.4	<i>ue-Rx-TxTimeDiffMeasurements-r11</i>	88
4.3.15.5	<i>Void</i>	89
4.3.15.6	<i>Void</i>	89
4.3.15.7	<i>Void</i>	89
4.3.15.8	<i>inDeviceCoexInd-UL-CA-r11</i>	89
4.3.15.9	<i>bwPrefInd-r14</i>	89
4.3.15.10	<i>inDeviceCoexInd-HardwareSharingInd-r13</i>	89
4.3.15.11	<i>overheatingInd-r14</i>	89
4.3.15.12	<i>assistInfoBitForLC-r15</i>	89
4.3.15.13	<i>timeReferenceProvision-r15</i>	89
4.3.15.14	<i>flightPathPlan-r15</i>	89
4.3.15.15	<i>inDeviceCoexInd-ENDC-r15</i>	89
4.3.15.16	<i>nonCSG-SI-Reporting-r14</i>	89
4.3.16	Positioning parameters	89
4.3.16.1	<i>otdoa-UE-assisted</i>	89
4.3.16.2	<i>interFreqSTDmeasurement</i>	90
4.3.17	MBMS parameters	90
4.3.17.1	<i>mbms-SCell-r11</i>	90
4.3.17.2	<i>mbms-NonServingCell-r11</i>	90
4.3.17.3	<i>mbms-AsyncDC-r12</i>	90
4.3.17.4	<i>fembmsMixedCell-r14</i>	90
4.3.17.5	<i>fembmsDedicatedCell-r14</i>	90
4.3.17.6	<i>subcarrierSpacingMBMS-khz1dot25-r14, subcarrierSpacingMBMS-khz7dot5-r14</i>	90
4.3.17.7	<i>mbms-MaxBW-r14</i>	90
4.3.17.8	<i>mbms-ScalingFactor1dot25-r14, mbms-ScalingFactor7dot5-r14</i>	91
4.3.18	RAN-assisted WLAN interworking parameters	91
4.3.18.1	<i>wlan-IW-RAN-Rules-r12</i>	91
4.3.18.2	<i>wlan-IW-ANDSF-Policies-r12</i>	91
4.3.18.3	<i>rclwi-r13</i>	91
4.3.19	MAC parameters	91
4.3.19.1	<i>longDRX-Command-r12</i>	91
4.3.19.2	<i>logicalChannelSR-ProhibitTimer-r12</i>	91
4.3.19.3	<i>extendedMAC-LengthField-r13</i>	91
4.3.19.4	<i>extendedLongDRX-r13</i>	91
4.3.19.5	<i>shortSPS-IntervalFDD-r14</i>	91
4.3.19.6	<i>shortSPS-IntervalTDD-r14</i>	92
4.3.19.7	<i>skipUplinkDynamic-r14</i>	92
4.3.19.8	<i>skipUplinkSPS-r14</i>	92
4.3.19.9	<i>dataInactMon-r14</i>	92
4.3.19.10	<i>rai-Support-r14</i>	92
4.3.19.11	<i>multipleUplinkSPS-r14</i>	92
4.3.19.12	<i>min-Proc-TimelineSubslot-r15</i>	92
4.3.19.13	<i>skipSubframeProcessing-r15</i>	92
4.3.19.14	<i>earlyContentionResolution-r14</i>	92
4.3.19.15	<i>sr-SPS-BSR-r15</i>	93
4.3.19.16	<i>dormantSCellState-r15</i>	93
4.3.19.17	<i>directSCellActivation-r15</i>	93
4.3.19.18	<i>directSCellHibernation-r15</i>	93
4.3.19.19	<i>sps-ServingCell-r15</i>	93
4.3.19.20	<i>extendedLCID-Duplication-r15</i>	93
4.3.19.21	<i>eLCID-Support-r15</i>	93
4.3.20	Dual Connectivity parameters	93
4.3.20.1	<i>drb-TypeSplit-r12</i>	93
4.3.20.2	<i>drb-TypeSCG-r12</i>	93
4.3.20.3	<i>pdcp-TransferSplitUL-r13</i>	93
4.3.20.4	<i>ue-SSTD-Meas-r13</i>	93
4.3.21	Sidelink parameters	94
4.3.21.1	<i>commSupportedBands-r12</i>	94
4.3.21.2	<i>commSimultaneousTx-r12</i>	94
4.3.21.3	<i>discSupportedBands-r12</i>	94

4.3.21.4	<i>discScheduledResourceAlloc-r12</i>	94
4.3.21.5	<i>disc-UE-SelectedResourceAlloc-r12</i>	94
4.3.21.6	<i>disc-SLSS-r12</i>	94
4.3.21.7	<i>discSupportedProc-r12</i>	94
4.3.21.8	<i>commMultipleTx-r13</i>	94
4.3.21.9	<i>discInterFreqTx-r13</i>	94
4.3.21.10	<i>discPeriodicSLSS-r13</i>	95
4.3.21.11	<i>discSysInfoReporting-r13</i>	95
4.3.21.12	<i>zoneBasedPoolSelection-r14</i>	95
4.3.21.13	<i>v2x-HighReception-r14</i>	95
4.3.21.14	<i>v2x-eNB-Scheduled-r14</i>	95
4.3.21.15	<i>ue-AutonomousWithFullSensing-r14</i>	95
4.3.21.16	<i>ue-AutonomousWithPartialSensing-r14</i>	95
4.3.21.17	<i>slss-TxRx-r14</i>	95
4.3.21.18	<i>sl-CongestionControl-r14</i>	95
4.3.21.19	<i>v2x-TxWithShortResvInterval-r14</i>	95
4.3.21.20	<i>v2x-numberTxRxTiming-r14</i>	95
4.3.21.21	<i>v2x-nonAdjacentPSCCH-PSSCH-r14</i>	96
4.3.21.22	<i>v2x-HighPower-r14</i>	96
4.3.21.23	<i>v2x-SupportedBandCombinationList-r14</i>	96
4.3.21.24	<i>slss-SupportedTxFreq-r15</i>	96
4.3.21.25	<i>sl-64QAM-Tx-r15</i>	96
4.3.21.26	<i>sl-TxDiversity-r15</i>	96
4.3.21.27	<i>v2x-EnhancedHighReception-r15</i>	96
4.3.21.28	<i>sl-64QAM-Rx-r15</i>	96
4.3.21.29	<i>sl-RateMatchingTBSScaling-r15</i>	96
4.3.21.30	<i>sl-LowT2min-r15</i>	96
4.3.21.31	<i>v2x-SensingReportingMode3-r15</i>	96
4.3.22	SC-PTM parameters	97
4.3.22.1	<i>scptm-ParallelReception-r13</i>	97
4.3.22.2	<i>Void</i>	97
4.3.22.3	<i>scptm-SCell-r13</i>	97
4.3.22.4	<i>scptm-NonServingCell-r13</i>	97
4.3.22.5	<i>scptm-AsyncDC-r13</i>	97
4.3.23	LAA parameters.....	97
4.3.23.1	<i>downlinkLAA-r13</i>	97
4.3.23.2	<i>crossCarrierSchedulingLAA-DL-r13</i>	97
4.3.23.3	<i>csi-RS-DRS-RRM-MeasurementsLAA-r13</i>	97
4.3.23.4	<i>endingDwPTS-r13</i>	98
4.3.23.5	<i>secondSlotStartingPosition-r13</i>	98
4.3.23.6	<i>tm9-LAA-r13</i>	98
4.3.23.7	<i>tm10-LAA-r13</i>	98
4.3.23.8	<i>uplinkLAA-r14</i>	98
4.3.23.9	<i>crossCarrierSchedulingLAA-UL-r14</i>	98
4.3.23.10	<i>twoStepSchedulingTimingInfo-r14</i>	98
4.3.23.11	<i>uss-BlindDecodingAdjustment-r14</i>	98
4.3.23.12	<i>uss-BlindDecodingReduction-r14</i>	98
4.3.23.13	<i>outOfSequenceGrantHandling-r14</i>	98
4.3.23.14	<i>aul-r15</i>	98
4.3.23.15	<i>laa-PUSCH-Mode1-r15</i>	99
4.3.23.16	<i>laa-PUSCH-Mode2-r15</i>	99
4.3.23.17	<i>laa-PUSCH-Mode3-r15</i>	99
4.3.24	LWIP parameters	99
4.3.24.1	<i>lwip-r13</i>	99
4.3.24.2	<i>lwip-Aggregation-UL-r14</i>	99
4.3.24.3	<i>lwip-Aggregation-DL-r14</i>	99
4.3.25	LWA parameters.....	99
4.3.25.1	<i>lwa-r13</i>	99
4.3.25.2	<i>lwa-SplitBearer-r13</i>	99
4.3.25.3	<i>lwa-BufferSize-r13</i>	99
4.3.25.4	<i>wlan-MAC-Address-r13</i>	99
4.3.25.5	<i>lwa-HO-WithoutWT-Change-r14</i>	99

4.3.25.6	<i>lwa-UL-r14</i>	100
4.3.25.7	<i>Void</i>	100
4.3.25.8	<i>wlan-SupportedDataRate-r14</i>	100
4.3.25.9	<i>lwa-RLC-UM-r14</i>	100
4.3.26	<i>Void</i>	100
4.3.26.1	<i>Void</i>	100
4.3.27	Inter-RAT parameters WLAN	100
4.3.27.1	<i>supportedBandListWLAN-r13</i>	100
4.3.28	EBF FD-MIMO parameters.....	100
4.3.28.1	<i>beamformed-r13</i>	100
4.3.28.2	<i>channelMeasRestriction-r13</i>	100
4.3.28.3	<i>csi-RS-EnhancementsTDD-r13</i>	100
4.3.28.4	<i>dmrs-Enhancements-r13</i>	100
4.3.28.5	<i>interferenceMeasRestriction-r13</i>	101
4.3.28.6	<i>nonPrecoded-r13</i>	101
4.3.28.7	<i>srs-Enhancements-r13</i>	101
4.3.28.8	<i>srs-EnhancementsTDD-r13</i>	101
4.3.28.9	<i>csi-ReportingAdvanced-r14, csi-ReportingAdvancedMaxPorts-r14</i>	101
4.3.28.10	<i>mimo-CBSR-AdvancedCSI-r15</i>	101
4.3.28.11	<i>csi-ReportingNP-r14</i>	101
4.3.28.12	<i>relWeightTwoLayers-r13, relWeightFourLayers-r13, relWeightEightLayers-r13</i>	102
4.3.28.13	<i>totalWeightedLayers-r13</i>	102
4.3.28.14	<i>zp-CSI-RS-AperiodicInfo-r14</i>	102
4.3.28.15	<i>ul-dmrs-Enhancements-r14</i>	102
4.3.28.16	<i>densityReductionNP-r14, densityReductionBF-r14</i>	102
4.3.28.17	<i>hybridCSI-r14</i>	102
4.3.28.18	<i>semiOL-r14</i>	102
4.3.29	CE parameters.....	103
4.3.29.1	<i>ce-ModeA-r13</i>	103
4.3.29.2	<i>ce-ModeB-r13</i>	103
4.3.29.3	<i>intraFreqA3-CE-ModeA-r13</i>	103
4.3.29.4	<i>intraFreqA3-CE-ModeB-r13</i>	103
4.3.29.5	<i>intraFreqHO-CE-ModeA-r13</i>	103
4.3.29.6	<i>intraFreqHO-CE-ModeB-r13</i>	103
4.3.29.7	<i>ue-CE-NeedULGaps-r13</i>	103
4.3.29.8	<i>unicastFrequencyHopping-r13</i>	103
4.3.29.9	<i>ce-SwitchWithoutHO-r14</i>	103
4.3.29.10	<i>tm9-CE-ModeA-r13</i>	104
4.3.29.11	<i>tm9-CE-ModeB-r13</i>	104
4.3.29.12	<i>tm6-CE-ModeA-r13</i>	104
4.3.30	Mobility enhancement parameters.....	104
4.3.30.1	<i>makeBeforeBreak-r14</i>	104
4.3.30.2	<i>rach-Less-r14</i>	104
4.3.31	<i>Void</i>	104
4.3.31.1	<i>Void</i>	104
4.3.31.2	<i>Void</i>	104
4.3.32	MMTEL parameters	104
4.3.32.1	<i>delayBudgetReporting-r14</i>	104
4.3.32.2	<i>pusch-Enhancements-r14</i>	104
4.3.32.3	<i>recommendedBitRate-r14</i>	104
4.3.33	High speed enhancement parameters.....	105
4.3.33.1	<i>measurementEnhancements-r14</i>	105
4.3.33.2	<i>demodulationEnhancements-r14</i>	105
4.3.33.3	<i>prach-Enhancements-r14</i>	105
4.3.34	Inter-RAT Parameters NR	105
4.3.34.1	<i>en-DC-r15</i>	105
4.3.34.2	<i>supportedBandListEN-DC-r15</i>	105
4.3.34.3	<i>supportedBandListNR-SA-r15</i>	105
4.3.34.4	<i>eutra-5GC-HO-ToNR-FDD-FR1-r15</i>	105
4.3.34.5	<i>eutra-5GC-HO-ToNR-TDD-FR1-r15</i>	105
4.3.34.6	<i>eutra-5GC-HO-ToNR-FDD-FR2-r15</i>	105
4.3.34.7	<i>eutra-5GC-HO-ToNR-TDD-FR2-r15</i>	105