



LTE;
**Evolved Universal Terrestrial Radio Access (E-UTRA);
Radio Resource Control (RRC);
Protocol specification**
(3GPP TS 36.331 version 14.13.0 Release 14)

Redacted Standard Preview
https://standards.iteh.ai/standard/3gpp/36.331/v14.13.0-2020-01
4ad1-815e-b19750d20412a11a20b74e2-a904-



Reference

RTS/TSGR-0236331ved0

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and

of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and
of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	20
1 Scope	21
2 References	21
3 Definitions, symbols and abbreviations	24
3.1 Definitions	24
3.2 Abbreviations	26
4 General	29
4.1 Introduction	29
4.2 Architecture	30
4.2.1 UE states and state transitions including inter RAT	30
4.2.2 Signalling radio bearers	32
4.3 Services	33
4.3.1 Services provided to upper layers	33
4.3.2 Services expected from lower layers	33
4.4 Functions	33
4.5 Data available for transmission for NB-IoT	34
5 Procedures	35
5.1 General	35
5.1.1 Introduction.....	35
5.1.2 General requirements	35
5.2 System information	36
5.2.1 Introduction.....	36
5.2.1.1 General	36
5.2.1.2 Scheduling.....	37
5.2.1.2a Scheduling for NB-IoT	38
5.2.1.3 System information validity and notification of changes	38
5.2.1.4 Indication of ETWS notification	40
5.2.1.5 Indication of CMAS notification	40
5.2.1.6 Notification of EAB parameters change	41
5.2.1.7 Access Barring parameters change in NB-IoT	41
5.2.2 System information acquisition	41
5.2.2.1 General	41
5.2.2.2 Initiation	41
5.2.2.3 System information required by the UE	42
5.2.2.4 System information acquisition by the UE	42
5.2.2.5 Essential system information missing	46
5.2.2.6 Actions upon reception of the <i>MasterInformationBlock</i> message	46
5.2.2.7 Actions upon reception of the <i>SystemInformationBlockType1</i> message	47
5.2.2.8 Actions upon reception of <i>SystemInformation</i> messages	48
5.2.2.9 Actions upon reception of <i>SystemInformationBlockType2</i>	49
5.2.2.10 Actions upon reception of <i>SystemInformationBlockType3</i>	50
5.2.2.11 Actions upon reception of <i>SystemInformationBlockType4</i>	51
5.2.2.12 Actions upon reception of <i>SystemInformationBlockType5</i>	51
5.2.2.13 Actions upon reception of <i>SystemInformationBlockType6</i>	52
5.2.2.14 Actions upon reception of <i>SystemInformationBlockType7</i>	52
5.2.2.15 Actions upon reception of <i>SystemInformationBlockType8</i>	52
5.2.2.16 Actions upon reception of <i>SystemInformationBlockType9</i>	53
5.2.2.17 Actions upon reception of <i>SystemInformationBlockType10</i>	53
5.2.2.18 Actions upon reception of <i>SystemInformationBlockType11</i>	53
5.2.2.19 Actions upon reception of <i>SystemInformationBlockType12</i>	54

5.2.2.20	Actions upon reception of <i>SystemInformationBlockType13</i>	54
5.2.2.21	Actions upon reception of <i>SystemInformationBlockType14</i>	54
5.2.2.22	Actions upon reception of <i>SystemInformationBlockType15</i>	55
5.2.2.23	Actions upon reception of <i>SystemInformationBlockType16</i>	55
5.2.2.24	Actions upon reception of <i>SystemInformationBlockType17</i>	55
5.2.2.25	Actions upon reception of <i>SystemInformationBlockType18</i>	55
5.2.2.26	Actions upon reception of <i>SystemInformationBlockType19</i>	55
5.2.2.27	Actions upon reception of <i>SystemInformationBlockType20</i>	56
5.2.2.28	Actions upon reception of <i>SystemInformationBlockType21</i>	56
5.2.2.29	Actions upon reception of <i>SystemInformationBlockType22-NB</i>	56
5.2.3	Acquisition of an SI message.....	56
5.2.3a	Acquisition of an SI message by BL UE or UE in CE or a NB-IoT UE.....	57
5.2.3b	Acquisition of an SI message from MBMS-dedicated cell.....	57
5.3	Connection control	58
5.3.1	Introduction.....	58
5.3.1.1	RRC connection control.....	58
5.3.1.2	Security	59
5.3.1.2a	RN security	60
5.3.1.3	Connected mode mobility	60
5.3.1.4	Connection control in NB-IoT	61
5.3.2	Paging	62
5.3.2.1	General	62
5.3.2.2	Initiation.....	62
5.3.2.3	Reception of the <i>Paging</i> message by the UE	63
5.3.3	RRC connection establishment	64
5.3.3.1	General	64
5.3.3.1a	Conditions for establishing RRC Connection for sidelink communication/ discovery/ V2X sidelink communication	65
5.3.3.2	Initiation.....	67
5.3.3.3	Actions related to transmission of <i>RRCConnectionRequest</i> message	71
5.3.3.3a	Actions related to transmission of <i>RRCConnectionResumeRequest</i> message	72
5.3.3.4	Reception of the <i>RRCConnectionSetup</i> by the UE.....	73
5.3.3.4a	Reception of the <i>RRCConnectionResume</i> by the UE	75
5.3.3.5	Cell re-selection while T300, T302, T303, T305, T306, or T308 is running	77
5.3.3.6	T300 expiry	78
5.3.3.7	T302, T303, T305, T306, or T308 expiry or stop	79
5.3.3.8	Reception of the <i>RRCConnectionReject</i> by the UE	80
5.3.3.9	Abortion of RRC connection establishment.....	81
5.3.3.10	Handling of SSAC related parameters	81
5.3.3.11	Access barring check.....	82
5.3.3.12	EAB check	82
5.3.3.13	Access barring check for ACDC.....	83
5.3.3.14	Access Barring check for NB-IoT.....	84
5.3.3.15	Failure to deliver NAS information in RRCConnectionSetupComplete message	85
5.3.4	Initial security activation	85
5.3.4.1	General	85
5.3.4.2	Initiation	86
5.3.4.3	Reception of the <i>SecurityModeCommand</i> by the UE	86
5.3.5	RRC connection reconfiguration	87
5.3.5.1	General	87
5.3.5.2	Initiation	87
5.3.5.3	Reception of an <i>RRCConnectionReconfiguration</i> not including the <i>mobilityControlInfo</i> by the UE	88
5.3.5.4	Reception of an <i>RRCConnectionReconfiguration</i> including the <i>mobilityControlInfo</i> by the UE (handover)	89
5.3.5.5	Reconfiguration failure	94
5.3.5.6	T304 expiry (handover failure)	94
5.3.5.7	Void.....	95
5.3.5.7a	T307 expiry (SCG change failure)	95
5.3.5.8	Radio Configuration involving full configuration option.....	96
5.3.6	Counter check	97
5.3.6.1	General	97

5.3.6.2	Initiation	97
5.3.6.3	Reception of the <i>CounterCheck</i> message by the UE	97
5.3.7	RRC connection re-establishment.....	98
5.3.7.1	General	98
5.3.7.2	Initiation	99
5.3.7.3	Actions following cell selection while T311 is running.....	100
5.3.7.4	Actions related to transmission of <i>RRConnectionReestablishmentRequest</i> message	100
5.3.7.5	Reception of the <i>RRConnectionReestablishment</i> by the UE	101
5.3.7.6	T311 expiry	104
5.3.7.7	T301 expiry or selected cell no longer suitable.....	104
5.3.7.8	Reception of <i>RRConnectionReestablishmentReject</i> by the UE	104
5.3.8	RRC connection release.....	104
5.3.8.1	General	104
5.3.8.2	Initiation	105
5.3.8.3	Reception of the <i>RRConnectionRelease</i> by the UE	105
5.3.8.4	T320 expiry	106
5.3.8.5	T322 expiry or stop	106
5.3.8.6	UE actions upon receiving the expiry of <i>DataInactivityTimer</i>	106
5.3.9	RRC connection release requested by upper layers	106
5.3.9.1	General	106
5.3.9.2	Initiation	106
5.3.10	Radio resource configuration.....	107
5.3.10.0	General	107
5.3.10.1	SRB addition/ modification.....	107
5.3.10.2	DRB release	108
5.3.10.3	DRB addition/ modification	108
5.3.10.3a1	DC specific DRB addition or reconfiguration.....	109
5.3.10.3a2	LWA specific DRB addition or reconfiguration	111
5.3.10.3a3	LWIP specific DRB addition or reconfiguration.....	112
5.3.10.3a	SCell release.....	113
5.3.10.3b	SCell addition/ modification	113
5.3.10.3c	PSCell addition or modification	113
5.3.10.4	MAC main reconfiguration	114
5.3.10.5	Semi-persistent scheduling reconfiguration	114
5.3.10.6	Physical channel reconfiguration	114
5.3.10.7	Radio Link Failure Timers and Constants reconfiguration	115
5.3.10.8	Time domain measurement resource restriction for serving cell.....	116
5.3.10.9	Other configuration	116
5.3.10.10	SCG reconfiguration	118
5.3.10.11	SCG dedicated resource configuration	120
5.3.10.12	Reconfiguration SCG or split DRB by <i>drb-ToAddModList</i>	120
5.3.10.13	Neighbour cell information reconfiguration.....	120
5.3.10.14	Void.....	121
5.3.10.15	Sidelink dedicated configuration.....	121
5.3.10.15a	V2X sidelink Communication dedicated configuration	122
5.3.10.16	T370 expiry	123
5.3.11	Radio link failure related actions	123
5.3.11.1	Detection of physical layer problems in RRC_CONNECTED	123
5.3.11.1a	Early detection of physical layer problems in RRC_CONNECTED	123
5.3.11.1b	Detection of physical layer improvements in RRC_CONNECTED	123
5.3.11.2	Recovery of physical layer problems	123
5.3.11.2a	Recovery of early detection of physical layer problems	124
5.3.11.2b	Cancellation of physical layer improvements in RRC_CONNECTED	124
5.3.11.3	Detection of radio link failure	124
5.3.11.3a	Detection of early-out-of-sync event.....	126
5.3.11.3b	Detection of early-in-sync event	126
5.3.12	UE actions upon leaving RRC_CONNECTED	126
5.3.13	UE actions upon PUCCH/ SRS release request.....	127
5.3.14	Proximity indication	128
5.3.14.1	General	128
5.3.14.2	Initiation.....	128
5.3.14.3	Actions related to transmission of <i>ProximityIndication</i> message.....	128

5.3.15	Void	129
5.4	Inter-RAT mobility.....	129
5.4.1	Introduction.....	129
5.4.2	Handover to E-UTRA.....	129
5.4.2.1	General.....	129
5.4.2.2	Initiation.....	129
5.4.2.3	Reception of the <i>RRCCoNnectionReCofiguration</i> by the UE.....	130
5.4.2.4	Reconfiguration failure	131
5.4.2.5	T304 expiry (handover to E-UTRA failure).....	132
5.4.3	Mobility from E-UTRA.....	132
5.4.3.1	General.....	132
5.4.3.2	Initiation.....	133
5.4.3.3	Reception of the <i>MobilityFromEUTRACoMmand</i> by the UE	133
5.4.3.4	Successful completion of the mobility from E-UTRA.....	134
5.4.3.5	Mobility from E-UTRA failure	134
5.4.4	Handover from E-UTRA preparation request (CDMA2000)	135
5.4.4.1	General.....	135
5.4.4.2	Initiation.....	135
5.4.4.3	Reception of the <i>HandoverFromEUTRAPreparationRequest</i> by the UE	135
5.4.5	UL handover preparation transfer (CDMA2000)	136
5.4.5.1	General.....	136
5.4.5.2	Initiation.....	136
5.4.5.3	Actions related to transmission of the <i>ULHandoverPreparationTransfer</i> message.....	136
5.4.5.4	Failure to deliver the <i>ULHandoverPreparationTransfer</i> message	136
5.4.6	Inter-RAT cell change order to E-UTRAN.....	136
5.4.6.1	General.....	136
5.4.6.2	Initiation	137
5.4.6.3	UE fails to complete an inter-RAT cell change order	137
5.5	Measurements.....	137
5.5.1	Introduction.....	137
5.5.2	Measurement configuration	139
5.5.2.1	General	139
5.5.2.2	Measurement identity removal	140
5.5.2.2a	Measurement identity autonomous removal	140
5.5.2.3	Measurement identity addition/ modification	141
5.5.2.4	Measurement object removal	141
5.5.2.5	Measurement object addition/ modification	142
5.5.2.6	Reporting configuration removal	144
5.5.2.7	Reporting configuration addition/ modification	145
5.5.2.8	Quantity configuration	145
5.5.2.9	Measurement gap configuration	145
5.5.2.10	Discovery signals measurement timing configuration	147
5.5.2.11	RSSI measurement timing configuration	147
5.5.2.12	Measurement gap sharing configuration	147
5.5.3	Performing measurements	147
5.5.3.1	General	147
5.5.3.2	Layer 3 filtering	151
5.5.4	Measurement report triggering	151
5.5.4.1	General	151
5.5.4.2	Event A1 (Serving becomes better than threshold)	156
5.5.4.3	Event A2 (Serving becomes worse than threshold)	157
5.5.4.4	Event A3 (Neighbour becomes offset better than PCell/ PSCell)	157
5.5.4.5	Event A4 (Neighbour becomes better than threshold)	158
5.5.4.6	Event A5 (PCell/ PSCell becomes worse than threshold1 and neighbour becomes better than threshold2)	159
5.5.4.6a	Event A6 (Neighbour becomes offset better than SCell)	160
5.5.4.7	Event B1 (Inter RAT neighbour becomes better than threshold)	160
5.5.4.8	Event B2 (PCell becomes worse than threshold1 and inter RAT neighbour becomes better than threshold2)	161
5.5.4.9	Event C1 (CSI-RS resource becomes better than threshold).....	162
5.5.4.10	Event C2 (CSI-RS resource becomes offset better than reference CSI-RS resource)	162
5.5.4.11	Event W1 (WLAN becomes better than a threshold).....	163

5.5.4.12	Event W2 (All WLAN inside WLAN mobility set becomes worse than threshold1 and a WLAN outside WLAN mobility set becomes better than threshold2)	163
5.5.4.13	Event W3 (All WLAN inside WLAN mobility set becomes worse than a threshold).....	164
5.5.4.14	Event V1 (The channel busy ratio is above a threshold).....	165
5.5.4.15	Event V2 (The channel busy ratio is below a threshold).....	165
5.5.5	Measurement reporting	166
5.5.6	Measurement related actions.....	171
5.5.6.1	Actions upon handover and re-establishment.....	171
5.5.6.2	Speed dependant scaling of measurement related parameters.....	172
5.5.7	Inter-frequency RSTD measurement indication	172
5.5.7.1	General	172
5.5.7.2	Initiation	172
5.5.7.3	Actions related to transmission of <i>InterFreqRSTDMeasurementIndication</i> message.....	173
5.6	Other.....	173
5.6.0	General.....	173
5.6.1	DL information transfer	174
5.6.1.1	General	174
5.6.1.2	Initiation	174
5.6.1.3	Reception of the <i>DLInformationTransfer</i> by the UE	174
5.6.2	UL information transfer	174
5.6.2.1	General	174
5.6.2.2	Initiation	174
5.6.2.3	Actions related to transmission of <i>ULInformationTransfer</i> message.....	175
5.6.2.4	Failure to deliver <i>ULInformationTransfer</i> message.....	175
5.6.3	UE capability transfer	175
5.6.3.1	General	175
5.6.3.2	Initiation	176
5.6.3.3	Reception of the <i>UECapabilityEnquiry</i> by the UE	176
5.6.4	CSFB to 1x Parameter transfer	179
5.6.4.1	General	179
5.6.4.2	Initiation	180
5.6.4.3	Actions related to transmission of <i>CSFBParametersRequestCDMA2000</i> message.....	180
5.6.4.4	Reception of the <i>CSFBParametersResponseCDMA2000</i> message.....	180
5.6.5	UE Information	180
5.6.5.1	General	180
5.6.5.2	Initiation	180
5.6.5.3	Reception of the <i>UEInformationRequest</i> message	180
5.6.6	Logged Measurement Configuration	182
5.6.6.1	General	182
5.6.6.2	Initiation	182
5.6.6.3	Reception of the <i>LoggedMeasurementConfiguration</i> by the UE	182
5.6.6.4	T330 expiry	182
5.6.7	Release of Logged Measurement Configuration.....	183
5.6.7.1	General	183
5.6.7.2	Initiation	183
5.6.8	Measurements logging	183
5.6.8.1	General	183
5.6.8.2	Initiation	183
5.6.9	In-device coexistence indication.....	186
5.6.9.1	General	186
5.6.9.2	Initiation	186
5.6.9.3	Actions related to transmission of <i>InDeviceCoexIndication</i> message.....	187
5.6.10	UE Assistance Information	188
5.6.10.1	General	188
5.6.10.2	Initiation	188
5.6.10.3	Actions related to transmission of <i>UEAssistanceInformation</i> message	189
5.6.11	Mobility history information.....	191
5.6.11.1	General	191
5.6.11.2	Initiation	191
5.6.12	RAN-assisted WLAN interworking.....	191
5.6.12.1	General	191
5.6.12.2	Dedicated WLAN offload configuration.....	192

5.6.12.3	WLAN offload RAN evaluation	192
5.6.12.4	T350 expiry or stop	192
5.6.12.5	Cell selection/ re-selection while T350 is running	192
5.6.13	SCG failure information	193
5.6.13.1	General	193
5.6.13.2	Initiation	193
5.6.13.3	Actions related to transmission of <i>SCGFailureInformation</i> message	193
5.6.14	LTE-WLAN Aggregation	194
5.6.14.1	Introduction	194
5.6.14.2	Reception of LWA configuration	194
5.6.14.3	Release of LWA configuration	195
5.6.15	WLAN connection management	195
5.6.15.1	Introduction	195
5.6.15.2	WLAN connection status reporting	195
5.6.15.2.1	General	195
5.6.15.2.2	Initiation	196
5.6.15.2.3	Actions related to transmission of <i>WLANConnectionStatusReport</i> message	196
5.6.15.3	T351 Expiry (WLAN connection attempt timeout)	196
5.6.15.4	WLAN status monitoring	196
5.6.16	RAN controlled LTE-WLAN interworking	197
5.6.16.1	General	197
5.6.16.2	WLAN traffic steering command	197
5.6.17	LTE-WLAN aggregation with IPsec tunnel	198
5.6.17.1	General	198
5.6.17.2	LWIP reconfiguration	198
5.6.17.3	LWIP release	199
5.6.18	Void	199
5.7	Generic error handling	199
5.7.1	General	199
5.7.2	ASN.1 violation or encoding error	199
5.7.3	Field set to a not comprehended value	200
5.7.4	Mandatory field missing	200
5.7.5	Not comprehended field	201
5.8	MBMS	201
5.8.1	Introduction	201
5.8.1.1	General	201
5.8.1.2	Scheduling	202
5.8.1.3	MCCH information validity and notification of changes	202
5.8.2	MCCH information acquisition	203
5.8.2.1	General	203
5.8.2.2	Initiation	203
5.8.2.3	MCCH information acquisition by the UE	203
5.8.2.4	Actions upon reception of the <i>MBSFNAreaConfiguration</i> message	204
5.8.2.5	Actions upon reception of the <i>MBMSCountingRequest</i> message	204
5.8.3	MBMS PTM radio bearer configuration	204
5.8.3.1	General	204
5.8.3.2	Initiation	204
5.8.3.3	MRB establishment	204
5.8.3.4	MRB release	205
5.8.4	MBMS Counting Procedure	205
5.8.4.1	General	205
5.8.4.2	Initiation	205
5.8.4.3	Reception of the <i>MBMSCountingRequest</i> message by the UE	205
5.8.5	MBMS interest indication	206
5.8.5.1	General	206
5.8.5.2	Initiation	206
5.8.5.3	Determine MBMS frequencies of interest	207
5.8.5.4	Actions related to transmission of <i>MBMSInterestIndication</i> message	208
5.8a	SC-PTM	208
5.8a.1	Introduction	208
5.8a.1.1	General	208
5.8a.1.2	SC-MCCH scheduling	209

5.8a.1.3	SC-MCCH information validity and notification of changes.....	209
5.8a.1.4	Procedures.....	210
5.8a.2	SC-MCCH information acquisition	210
5.8a.2.1	General.....	210
5.8a.2.2	Initiation.....	210
5.8a.2.3	SC-MCCH information acquisition by the UE	210
5.8a.2.4	Actions upon reception of the <i>SCPTMConfiguration</i> message.....	211
5.8a.3	SC-PTM radio bearer configuration	211
5.8a.3.1	General.....	211
5.8a.3.2	Initiation.....	211
5.8a.3.3	SC-MRB establishment.....	211
5.8a.3.4	SC-MRB release	211
5.9	RN procedures.....	212
5.9.1	RN reconfiguration	212
5.9.1.1	General.....	212
5.9.1.2	Initiation	212
5.9.1.3	Reception of the <i>RNReconfiguration</i> by the RN	212
5.10	Sidelink	213
5.10.1	Introduction.....	213
5.10.1a	Conditions for sidelink communication operation.....	213
5.10.1d	Conditions for V2X sidelink communication operation	214
5.10.2	Sidelink UE information	214
5.10.2.1	General	214
5.10.2.2	Initiation	215
5.10.2.3	Actions related to transmission of <i>SidelinkUEInformation</i> message	220
5.10.3	Sidelink communication monitoring.....	222
5.10.4	Sidelink communication transmission	224
5.10.5	Sidelink discovery monitoring.....	225
5.10.6	Sidelink discovery announcement	226
5.10.6a	Sidelink discovery announcement pool selection	229
5.10.6b	Sidelink discovery announcement reference carrier selection	229
5.10.7	Sidelink synchronisation information transmission	230
5.10.7.1	General	230
5.10.7.2	Initiation	231
5.10.7.3	Transmission of SLSS	232
5.10.7.4	Transmission of <i>MasterInformationBlock-SL</i> or <i>MasterInformationBlock-SL-V2X</i> message	235
5.10.7.5	Void.....	236
5.10.8	Sidelink synchronisation reference	236
5.10.8.1	General	236
5.10.8.2	Selection and reselection of synchronisation reference	236
5.10.9	Sidelink common control information	238
5.10.9.1	General	238
5.10.9.2	Actions related to reception of <i>MasterInformationBlock-SL</i> / <i>MasterInformationBlock-SL-V2X</i> message	239
5.10.10	Sidelink relay UE operation	239
5.10.10.1	General	239
5.10.10.2	AS-conditions for relay related sidelink communication transmission by sidelink relay UE	239
5.10.10.3	AS-conditions for relay PS related sidelink discovery transmission by sidelink relay UE	239
5.10.10.4	Sidelink relay UE threshold conditions	240
5.10.11	Sidelink remote UE operation	240
5.10.11.1	General	240
5.10.11.2	AS-conditions for relay related sidelink communication transmission by sidelink remote UE	240
5.10.11.3	AS-conditions for relay PS related sidelink discovery transmission by sidelink remote UE	241
5.10.11.4	Selection and reselection of sidelink relay UE	241
5.10.11.5	Sidelink remote UE threshold conditions	241
5.10.12	V2X sidelink communication monitoring	242
5.10.13	V2X sidelink communication transmission	242
5.10.13.1	Transmission of V2X sidelink communication	242
5.10.13.1a	Transmission of P2X related V2X sidelink communication	245
5.10.13.2	V2X sidelink communication transmission pool selection	245
5.10.13.3	V2X sidelink communication transmission reference cell selection	247
5.10.14	DFN derivation from GNSS	247

6	Protocol data units, formats and parameters (tabular & ASN.1).....	248
6.1	General	248
6.2	RRC messages.....	249
6.2.1	General message structure	250
–	<i>EUTRA-RRC-Definitions</i>	250
–	<i>BCCH-BCH-Message</i>	250
–	<i>BCCH-BCH-Message-MBMS</i>	250
–	<i>BCCH-DL-SCH-Message</i>	250
–	<i>BCCH-DL-SCH-Message-BR</i>	251
–	<i>BCCH-DL-SCH-Message-MBMS</i>	251
–	<i>MCCH-Message</i>	251
–	<i>PCCH-Message</i>	252
–	<i>DL-CCCH-Message</i>	252
–	<i>DL-DCCH-Message</i>	252
–	<i>UL-CCCH-Message</i>	253
–	<i>UL-DCCH-Message</i>	253
–	<i>SC-MCCH-Message</i>	254
6.2.2	Message definitions	254
–	<i>CounterCheck</i>	254
–	<i>CounterCheckResponse</i>	255
–	<i>CSFBParametersRequestCDMA2000</i>	256
–	<i>CSFBParametersResponseCDMA2000</i>	256
–	<i>DLInformationTransfer</i>	257
–	<i>HandoverFromEUTRAPreparationRequest</i> (CDMA2000)	257
–	<i>InDeviceCoexIndication</i>	259
–	<i>InterFreqRSTDMeasurementIndication</i>	261
–	<i>LoggedMeasurementConfiguration</i>	263
–	<i>MasterInformationBlock</i>	264
–	<i>MasterInformationBlock-MBMS</i>	265
–	<i>MBMSCountingRequest</i>	265
–	<i>MBMSCountingResponse</i>	266
–	<i>MBMSInterestIndication</i>	267
–	<i>MBSFNAreaConfiguration</i>	267
–	<i>MeasurementReport</i>	268
–	<i>MobilityFromEUTRACommand</i>	269
–	<i>Paging</i>	272
–	<i>ProximityIndication</i>	273
–	<i>RNReconfiguration</i>	274
–	<i>RNReconfigurationComplete</i>	274
–	<i>RRCConnectionReconfiguration</i>	275
–	<i>RRCConnectionReconfigurationComplete</i>	281
–	<i>RRCConnectionReestablishment</i>	282
–	<i>RRCConnectionReestablishmentComplete</i>	283
–	<i>RRCConnectionReestablishmentReject</i>	284
–	<i>RRCConnectionReestablishmentRequest</i>	284
–	<i>RRCConnectionReject</i>	285
–	<i>RRCConnectionRelease</i>	286
–	<i>RRCConnectionRequest</i>	290
–	<i>RRCConnectionResume</i>	290
–	<i>RRCConnectionResumeComplete</i>	291
–	<i>RRCConnectionResumeRequest</i>	292
–	<i>RRCConnectionSetup</i>	293
–	<i>RRCConnectionSetupComplete</i>	293
–	<i>SCGFailureInformation</i>	295
–	<i>SCPTMConfiguration</i>	296
–	<i>SCPTMConfiguration-BR</i>	297
–	<i>SecurityModeCommand</i>	297
–	<i>SecurityModeComplete</i>	298
–	<i>SecurityModeFailure</i>	298
–	<i>SidelinkUEInformation</i>	299
–	<i>SystemInformation</i>	302
–	<i>SystemInformationBlockType1</i>	302

-	<i>SystemInformationBlockType1-MBMS</i>	309
-	<i>UEAssistanceInformation</i>	311
-	<i>UECapabilityEnquiry</i>	313
-	<i>UECapabilityInformation</i>	315
-	<i>UEInformationRequest</i>	316
-	<i>UEInformationResponse</i>	316
-	<i>ULHandoverPreparationTransfer (CDMA2000)</i>	322
-	<i>ULInformationTransfer</i>	323
-	<i>WLANConnectionStatusReport</i>	323
6.3	RRC information elements	324
6.3.1	System information blocks	324
-	<i>SystemInformationBlockType2</i>	324
-	<i>SystemInformationBlockType3</i>	328
-	<i>SystemInformationBlockType4</i>	332
-	<i>SystemInformationBlockType5</i>	333
-	<i>SystemInformationBlockType6</i>	338
-	<i>SystemInformationBlockType7</i>	341
-	<i>SystemInformationBlockType8</i>	342
-	<i>SystemInformationBlockType9</i>	346
-	<i>SystemInformationBlockType10</i>	346
-	<i>SystemInformationBlockType11</i>	347
-	<i>SystemInformationBlockType12</i>	348
-	<i>SystemInformationBlockType13</i>	348
-	<i>SystemInformationBlockType14</i>	349
-	<i>SystemInformationBlockType15</i>	349
-	<i>SystemInformationBlockType16</i>	351
-	<i>SystemInformationBlockType17</i>	351
-	<i>SystemInformationBlockType18</i>	352
-	<i>SystemInformationBlockType19</i>	353
-	<i>SystemInformationBlockType20</i>	356
-	<i>SystemInformationBlockType21</i>	359
6.3.2	Radio resource control information elements	360
-	<i>AntennaInfo</i>	360
-	<i>AntennaInfoUL</i>	362
-	<i>CQI-ReportAperiodic</i>	363
-	<i>CQI-ReportBoth</i>	366
-	<i>CQI-ReportConfig</i>	367
-	<i>CQI-ReportPeriodic</i>	369
-	<i>CQI-ReportPeriodicProcExtId</i>	372
-	<i>CrossCarrierSchedulingConfig</i>	372
-	<i>CSI-IM-Config</i>	373
-	<i>CSI-IM-ConfigId</i>	374
-	<i>CSI-Process</i>	374
-	<i>CSI-ProcessId</i>	375
-	<i>CSI-RS-Config</i>	376
-	<i>CSI-RS-ConfigBeamformed</i>	377
-	<i>CSI-RS-ConfigEMIMO</i>	378
-	<i>CSI-RS-ConfigNonPrecoded</i>	379
-	<i>CSI-RS-ConfigNZP</i>	380
-	<i>CSI-RS-ConfigNZPID</i>	381
-	<i>CSI-RS-ConfigZP</i>	382
-	<i>CSI-RS-ConfigZPID</i>	382
-	<i>DataInactivityTimer</i>	382
-	<i>DMRS-Config</i>	383
-	<i>DRB-Identity</i>	383
-	<i>EPDCCH-Config</i>	383
-	<i>EIMTA-MainConfig</i>	385
-	<i>LogicalChannelConfig</i>	386
-	<i>LWA-Configuration</i>	387
-	<i>LWIP-Configuration</i>	388
-	<i>MAC-MainConfig</i>	388
-	<i>P-C-AndCBSR</i>	394

-	<i>PDCCH-ConfigSCell</i>	395
-	<i>PDCP-Config</i>	396
-	<i>PDSCH-Config</i>	399
-	<i>PDSCH-RE-MappingQCL-ConfigId</i>	401
-	<i>PerCC-GapIndicationList</i>	402
-	<i>PHICH-Config</i>	402
-	<i>PhysicalConfigDedicated</i>	402
-	<i>P-Max</i>	410
-	<i>PRACH-Config</i>	411
-	<i>PresenceAntennaPort1</i>	414
-	<i>PUCCH-Config</i>	414
-	<i>PUSCH-Config</i>	419
-	<i>RACH-ConfigCommon</i>	425
-	<i>RACH-ConfigDedicated</i>	427
-	<i>RadioResourceConfigCommon</i>	427
-	<i>RadioResourceConfigDedicated</i>	432
-	<i>RCLWI-Configuration</i>	438
-	<i>RLC-Config</i>	439
-	<i>RLF-TimersAndConstants</i>	441
-	<i>RN-SubframeConfig</i>	442
-	<i>SchedulingRequestConfig</i>	443
-	<i>SoundingRS-UL-Config</i>	444
-	<i>SPS-Config</i>	447
-	<i>SRS-TPC-PDCCH-Config</i>	451
-	<i>TDD-Config</i>	452
-	<i>TimeAlignmentTimer</i>	453
-	<i>TPC-PDCCH-Config</i>	453
-	<i>TunnelConfigLWIP</i>	454
-	<i>UplinkPowerControl</i>	454
-	<i>WLAN-Id-List</i>	458
-	<i>WLAN-MobilityConfig</i>	458
6.3.3	Security control information elements	459
-	<i>NextHopChainingCount</i>	459
-	<i>SecurityAlgorithmConfig</i>	459
-	<i>ShortMAC-I</i>	459
6.3.4	Mobility control information elements	460
-	<i>AdditionalSpectrumEmission</i>	460
-	<i>ARFCN-ValueCDMA2000</i>	460
-	<i>ARFCN-ValueEUTRA</i>	460
-	<i>ARFCN-ValueGERAN</i>	461
-	<i>ARFCN-ValueUTRA</i>	461
-	<i>BandclassCDMA2000</i>	461
-	<i>BandIndicatorGERAN</i>	461
-	<i>CarrierFreqCDMA2000</i>	461
-	<i>CarrierFreqGERAN</i>	462
-	<i>CarrierFreqsGERAN</i>	462
-	<i>CarrierFreqListMBMS</i>	463
-	<i>CDMA2000-Type</i>	463
-	<i>CellIdentity</i>	463
-	<i>CellIndexList</i>	463
-	<i>CellReselectionPriority</i>	464
-	<i>CellSelectionInfoCE</i>	464
-	<i>CellSelectionInfoCE1</i>	464
-	<i>CellReselectionSubPriority</i>	465
-	<i>CSFB-RegistrationParam1XRTT</i>	465
-	<i>CellGlobalIdEUTRA</i>	466
-	<i>CellGlobalIdUTRA</i>	466
-	<i>CellGlobalIdGERAN</i>	467
-	<i>CellGlobalIdCDMA2000</i>	467
-	<i>CellSelectionInfoNFreq</i>	468
-	<i>CSG-Identity</i>	468
-	<i>FreqBandIndicator</i>	468