

ETSI TS 136 101 V13.18.0 (2020-02)



LTE;
Evolved Universal Terrestrial Radio Access (E-UTRA);
User Equipment (UE) radio transmission and reception
(3GPP TS 36.101 version 13.18.0 Release 13)

iTech STANDARD PREVIEW
(standards.iteh.ai)
Full standards catalog: <https://standards.iteh.ai/catalog/standards/sist/63fefcc-781f-40bf-840d-92837672455f/etsi-ts-136-101-13.18.0-2020-02>



Reference

RTS/TSGR-0436101vD10

Keywords

LTE**ETSI**

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal notice

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal notice	2
Modal verbs terminology.....	2
Foreword.....	25
1 Scope	26
2 References	26
3 Definitions, symbols and abbreviations	26
3.1 Definitions	26
3.2 Symbols.....	28
3.3 Abbreviations	31
4 General	32
4.1 Relationship between minimum requirements and test requirements	32
4.2 Applicability of minimum requirements	32
4.3 Void.....	33
4.3A Applicability of minimum requirements (CA, UL-MIMO, ProSe, Dual Connectivity, UE category 0, UE category M1, UE category NB1).....	33
4.4 RF requirements in later releases	34
5 Operating bands and channel arrangement.....	34
5.1 General	34
5.2 Void.....	34
5.3 Void.....	34
5.4 Void.....	34
5.5 Operating bands.....	34
5.5A Operating bands for CA	36
5.5B Operating bands for UL-MIMO	46
5.5C Operating bands for Dual Connectivity.....	46
5.5D Operating bands for ProSe.....	48
5.5E Operating bands for UE category 0 and UE category M1	49
5.5F Operating bands for category NB1.....	49
5.6 Channel bandwidth.....	49
5.6.1 Channel bandwidths per operating band.....	50
5.6A Channel bandwidth for CA.....	52
5.6A.1 Channel bandwidths per operating band for CA.....	54
5.6B Channel bandwidth for UL-MIMO	73
5.6B.1 Void	73
5.6C Channel bandwidth for Dual Connectivity.....	73
5.6C.1 Void	73
5.6D Channel bandwidth for ProSe.....	73
5.6D.1 Channel bandwidths per operating band for ProSe.....	73
5.6F Channel bandwidth for category NB1	74
5.7 Channel arrangement.....	75
5.7.1 Channel spacing	75
5.7.1A Channel spacing for CA.....	75
5.7.1F Channel spacing for category NB1	76
5.7.2 Channel raster	76
5.7.2A Channel raster for CA.....	76
5.7.2F Channel raster for category NB1	76
5.7.3 Carrier frequency and EARFCN.....	76
5.7.3F Carrier frequency and EARFCN for category NB1	78
5.7.4 TX–RX frequency separation	78
5.7.4A TX–RX frequency separation for CA	79
5.7.4E TX–RX frequency separation for category M1	79
5.7.4F TX–RX frequency separation for category NB1	79

6	Transmitter characteristics	80
6.1	General	80
6.2	Transmit power	80
6.2.1	Void	80
6.2.2	UE maximum output power	80
6.2.2A	UE maximum output power for CA	82
6.2.2B	UE maximum output power for UL-MIMO	84
6.2.2C	Void	86
6.2.2D	UE maximum output power for ProSe	86
6.2.2E	UE maximum output power for Category M1 UE	86
6.2.2F	UE maximum output power for category NB1	87
6.2.3	UE maximum output power for modulation / channel bandwidth	88
6.2.3A	UE Maximum Output power for modulation / channel bandwidth for CA	89
6.2.3B	UE maximum output power for modulation / channel bandwidth for UL-MIMO	90
6.2.3D	UE maximum output power for modulation / channel bandwidth for ProSe	91
6.2.3E	UE maximum output power for modulation / channel bandwidth for category M1	91
6.2.3F	UE maximum output power for modulation / channel bandwidth for category NB1	92
6.2.4	UE maximum output power with additional requirements	92
6.2.4A	UE maximum output power with additional requirements for CA	102
6.2.4A.1	A-MPR for CA_NS_01 for CA_1C	104
6.2.4A.2	A-MPR for CA_NS_02 for CA_1C	104
6.2.4A.3	A-MPR for CA_NS_03 for CA_1C	105
6.2.4A.4	A-MPR for CA_NS_04	106
6.2.4A.5	A-MPR for CA_NS_05 for CA_38C	107
6.2.4A.6	A-MPR for CA_NS_06	108
6.2.4A.7	A-MPR for CA_NS_07	109
6.2.4A.8	A-MPR for CA_NS_08	110
6.2.4B	UE maximum output power with additional requirements for UL-MIMO	111
6.2.4D	UE maximum output power with additional requirements for ProSe	112
6.2.4E	UE maximum output power with additional requirements for category M1 UE	112
6.2.4F	UE maximum output power with additional requirements for category NB1 UE	114
6.2.5	Configured transmitted power	114
6.2.5A	Configured transmitted power for CA	128
6.2.5B	Configured transmitted power for UL-MIMO	130
6.2.5C	Configured transmitted power for Dual Connectivity	131
6.2.5D	Configured transmitted power for ProSe	132
6.2.5F	Configured transmitted Power for category NB1	134
6.3	Output power dynamics	135
6.3.1	(Void)	135
6.3.2	Minimum output power	135
6.3.2.1	Minimum requirement	135
6.3.2A	UE Minimum output power for CA	135
6.3.2A.1	Minimum requirement for CA	135
6.3.2B	UE Minimum output power for UL-MIMO	136
6.3.2B.1	Minimum requirement	136
6.3.2C	Void	136
6.3.2D	UE Minimum output power for ProSe	136
6.3.2F	UE Minimum output power for category NB1	136
6.3.3	Transmit OFF power	137
6.3.3.1	Minimum requirement	137
6.3.3A	UE Transmit OFF power for CA	137
6.3.3A.1	Minimum requirement for CA	137
6.3.3B	UE Transmit OFF power for UL-MIMO	137
6.3.3B.1	Minimum requirement	138
6.3.3D	Transmit OFF power for ProSe	138
6.3.3F	Transmit OFF power for category NB1	138
6.3.4	ON/OFF time mask	138
6.3.4.1	General ON/OFF time mask	138
6.3.4.2	PRACH and SRS time mask	139
6.3.4.2.1	PRACH time mask	139
6.3.4.2.2	SRS time mask	140
6.3.4.3	Slot / Sub frame boundary time mask	140

6.3.4.4	PUCCH / PUSCH / SRS time mask.....	141
6.3.4A	ON/OFF time mask for CA	142
6.3.4B	ON/OFF time mask for UL-MIMO	142
6.3.4D	ON/OFF time mask for ProSe.....	142
6.3.4D.1	General time mask for ProSe	143
6.3.4D.2	PSSS/SSSS time mask	143
6.3.4D.3	PSSS / SSSS / PSBCH time mask.....	144
6.3.4D.4	PSSCH / SRS time mask.....	145
6.3.4F	ON/OFF time mask for category NB1	145
6.3.4F.1	General ON/OFF time mask	145
6.3.4F.2	NPRACH time mask	145
6.3.5	Power Control.....	146
6.3.5.1	Absolute power tolerance.....	146
6.3.5.1.1	Minimum requirements	146
6.3.5.2	Relative Power tolerance.....	146
6.3.5.2.1	Minimum requirements	146
6.3.5.3	Aggregate power control tolerance	147
6.3.5.3.1	Minimum requirement.....	148
6.3.5A	Power control for CA.....	148
6.3.5A.1	Absolute power tolerance.....	148
6.3.5A.1.1	Minimum requirements	148
6.3.5A.2	Relative power tolerance	148
6.3.5A.2.1	Minimum requirements	148
6.3.5A.3	Aggregate power control tolerance	149
6.3.5A.3.1	Minimum requirements	149
6.3.5B	Power control for UL-MIMO	149
6.3.5D	Power Control for ProSe.....	150
6.3.5D.1	Absolute power tolerance.....	150
6.3.5E	Power control for category M1	150
6.3.5E.1	Absolute power tolerance.....	150
6.3.5E.2	Relative Power tolerance.....	150
6.3.5E.3	Aggregate power control tolerance	150
6.3.5E.3.1	Minimum requirement.....	150
6.3.5F	Power Control for category NB1	151
6.3.5F.1	Absolute power tolerance.....	151
6.3.5F.2	Relative power tolerance	152
6.3.5F.3	Aggregate power control tolerance for category NB1	152
6.3.5F.3.1	Minimum requirement.....	152
6.4	Void.....	153
6.5	Transmit signal quality	153
6.5.1	Frequency error.....	153
6.5.1A	Frequency error for CA.....	153
6.5.1B	Frequency error for UL-MIMO	153
6.5.1D	Frequency error for ProSe.....	153
6.5.1E	Frequency error for UE category M1	153
6.5.1F	Frequency error for UE category NB1.....	153
6.5.2	Transmit modulation quality.....	154
6.5.2.1	Error Vector Magnitude	154
6.5.2.1.1	Minimum requirement.....	154
6.5.2.2	Carrier leakage	155
6.5.2.2.1	Minimum requirements	155
6.5.2.3	In-band emissions	155
6.5.2.3.1	Minimum requirements	155
6.5.2.4	EVM equalizer spectrum flatness	156
6.5.2.4.1	Minimum requirements	156
6.5.2A	Transmit modulation quality for CA.....	157
6.5.2A.1	Error Vector Magnitude	158
6.5.2A.2	Carrier leakage for CA.....	158
6.5.2A.2.1	Minimum requirements.....	158
6.5.2A.3	In-band emissions	158
6.5.2A.3.1	Minimum requirement for CA.....	158
6.5.2B	Transmit modulation quality for UL-MIMO	160

6.5.2B.1	Error Vector Magnitude	161
6.5.2B.2	Carrier leakage	161
6.5.2B.3	In-band emissions	161
6.5.2B.4	EVM equalizer spectrum flatness for UL-MIMO	161
6.5.2D	Transmit modulation quality for ProSe	161
6.5.2D.1	Error Vector Magnitude	161
6.5.2D.2	Carrier leakage	161
6.5.2D.3	In-band emissions	162
6.5.2D.4	EVM equalizer spectrum flatness for ProSe	162
6.5.2E	Transmit modulation quality for category M1	162
6.5.2E.1	Error Vector Magnitude	162
The Error Vector Magnitude is defined in section 6.5.2.1.		162
6.5.2E.2	Carrier leakage	162
6.5.2E.2.1	Minimum requirements	162
6.5.2E.3	In-band emissions	162
6.5.2E.3.1	Minimum requirements	162
6.5.2F	Transmit modulation quality for Category NB1	163
6.5.2F.1	Error Vector Magnitude	163
6.5.2F.2	Carrier leakage	163
6.5.2F.3	In-band emissions	163
6.6	Output RF spectrum emissions	164
6.6.1	Occupied bandwidth	165
6.6.1A	Occupied bandwidth for CA	165
6.6.1B	Occupied bandwidth for UL-MIMO	165
6.6.1F	Occupied bandwidth for category NB1	166
6.6.2	Out of band emission	166
6.6.2.1	Spectrum emission mask	166
6.6.2.1.1	Minimum requirement	166
6.6.2.1A	Spectrum emission mask for CA	166
6.6.2.2	Additional spectrum emission mask	167
6.6.2.2.1	Minimum requirement (network signalled value "NS_03", "NS_11", "NS_20", and "NS_21") ..	168
6.6.2.2.2	Minimum requirement (network signalled value "NS_04")	168
6.6.2.2.3	Minimum requirement (network signalled value "NS_06" or "NS_07")	169
6.6.2.2A	Additional Spectrum Emission Mask for CA	169
6.6.2.2A.1	Minimum requirement (network signalled value "CA_NS_04")	169
6.6.2.3	Adjacent Channel Leakage Ratio	170
6.6.2.3.1	Minimum requirement E-UTRA	170
6.6.2.3.1A	Void	171
6.6.2.3.1Aa	Void	171
6.6.2.3.2	Minimum requirements UTRA	171
6.6.2.3.2A	Minimum requirement UTRA for CA	172
6.6.2.3.3A	Minimum requirements for CA E-UTRA	173
6.6.2.4	Void	175
6.6.2.4.1	Void	175
6.6.2A	Void	175
6.6.2B	Out of band emission for UL-MIMO	175
6.6.2C	Void	175
6.6.2D	Out of band emission for ProSe	175
6.6.2F	Out of band emission for category NB1	175
6.6.2F.1	Spectrum emission mask	175
6.6.2F.2	Void	176
6.6.2F.3	Adjacent Channel Leakage Ratio for category NB1	176
6.6.3	Spurious emissions	176
6.6.3.1	Minimum requirements	177
6.6.3.1A	Minimum requirements for CA	177
6.6.3.2	Spurious emission band UE co-existence	178
6.6.3.2A	Spurious emission band UE co-existence for CA	184
6.6.3.3	Additional spurious emissions	191
6.6.3.3.1	Minimum requirement (network signalled value "NS_05")	191
6.6.3.3.2	Minimum requirement (network signalled value "NS_07")	191
6.6.3.3.3	Minimum requirement (network signalled value "NS_08")	192
6.6.3.3.4	Minimum requirement (network signalled value "NS_09")	192

6.6.3.3.5	Minimum requirement (network signalled value "NS_12")	192
6.6.3.3.6	Minimum requirement (network signalled value "NS_13")	193
6.6.3.3.7	Minimum requirement (network signalled value "NS_14")	193
6.6.3.3.8	Minimum requirement (network signalled value "NS_15")	193
6.6.3.3.9	Minimum requirement (network signalled value "NS_16")	193
6.6.3.3.10	Minimum requirement (network signalled value "NS_17")	194
6.6.3.3.11	Minimum requirement (network signalled value "NS_18")	194
6.6.3.3.12	Minimum requirement (network signalled value "NS_19")	194
6.6.3.3.13	Minimum requirement (network signalled value "NS_11")	194
6.6.3.3.14	Minimum requirement (network signalled value "NS_20")	195
6.6.3.3.15	Minimum requirement (network signalled value "NS_21")	195
6.6.3.3.16	Minimum requirement (network signalled value "NS_22")	195
6.6.3.3.17	Minimum requirement (network signalled value "NS_23")	196
6.6.3.3.18	Void	196
6.6.3.3.19	Minimum requirement (network signalled value "NS_04")	196
6.6.3.3.20	Minimum requirement (network signalled value "NS_24")	197
6.6.3.3.21	Minimum requirement (network signalled value "NS_25")	197
6.6.3.3.22	Minimum requirement (network signalled value "NS_26")	197
6.6.3.3.23 - 6.6.3.3.27	Void	198
6.6.3.3.28	Minimum requirement (network signalled value "NS_36")	198
6.6.3.3A	Additional spurious emissions for CA	198
6.6.3.3A.1	Minimum requirement for CA_1C (network signalled value "CA_NS_01")	198
6.6.3.3A.2	Minimum requirement for CA_1C (network signalled value "CA_NS_02")	198
6.6.3.3A.3	Minimum requirement for CA_1C (network signalled value "CA_NS_03")	199
6.6.3.3A.4	Minimum requirement for CA_38C (network signalled value "CA_NS_05")	199
6.6.3.3A.5	Minimum requirement for CA_7C (network signalled value "CA_NS_06")	199
6.6.3.3A.6	Minimum requirement for CA_39C and CA_39C-41A (network signalled value "CA_NS_07")	200
6.6.3.3A.7	Minimum requirement for CA_42C (network signalled value "CA_NS_08")	200
6.6.3.3A.8	Minimum requirement for CA_41C (network signalled value "CA_NS_04")	201
6.6.3A	Void	201
6.6.3B	Spurious emission for UL-MIMO	201
6.6.3C	Void	201
6.6.3D	Spurious emission for ProSe	201
6.6.3F	Spurious emission for category NB1	201
6.6A	Void	202
6.6B	Void	202
6.7	Transmit intermodulation	202
6.7.1	Minimum requirement	202
6.7.1A	Minimum requirement for CA	202
6.7.1B	Minimum requirement for UL-MIMO	203
6.7.1F	Minimum requirement for category NB1	203
6.8	Void	204
6.8.1	Void	204
6.8A	Void	204
6.8B	Time alignment error for UL-MIMO	204
6.8B.1	Minimum Requirements	204
7	Receiver characteristics	204
7.1	General	204
7.2	Diversity characteristics	205
7.3	Reference sensitivity power level	205
7.3.1	Minimum requirements (QPSK)	205
7.3.1A	Minimum requirements (QPSK) for CA	221
7.3.1B	Minimum requirements (QPSK) for UL-MIMO	251
7.3.1D	Minimum requirements (QPSK) for ProSe	251
7.3.1E	Minimum requirements (QPSK) for UE category 0 and M1	253
7.3.1F	Minimum requirements for UE category NB1	257
7.3.1F.1	Reference sensitivity for UE category NB1	257
7.3.1F.2	Void	257
7.3.2	Void	258
7.4	Maximum input level	258

7.4.1	Minimum requirements.....	258
7.4.1A	Minimum requirements for CA	258
7.4.1B	Minimum requirements for UL-MIMO	259
7.4.1D	Minimum requirements for ProSe	259
7.4.1F	Minimum requirements for category NB1	259
7.4A	Void.....	260
7.4A.1	Void	260
7.5	Adjacent Channel Selectivity (ACS).....	260
7.5.1	Minimum requirements.....	260
7.5.1A	Minimum requirements for CA	261
7.5.1B	Minimum requirements for UL-MIMO	264
7.5.1D	Minimum requirements for ProSe	264
7.5.1F	Minimum requirements for category NB1	265
7.6	Blocking characteristics	266
7.6.1	In-band blocking.....	266
7.6.1.1	Minimum requirements.....	266
7.6.1.1A	Minimum requirements for CA.....	267
7.6.1.1D	Minimum requirements for ProSe.....	270
7.6.1.1F	Minimum requirements for category NB1	271
7.6.2	Out-of-band blocking.....	272
7.6.2.1	Minimum requirements	272
7.6.2.1A	Minimum requirements for CA.....	273
7.6.2.1D	Minimum requirements for ProSe.....	277
7.6.2.1F	Minimum requirements for category NB1	277
7.6.3	Narrow band blocking	278
7.6.3.1	Minimum requirements.....	278
7.6.3.1A	Minimum requirements for CA.....	279
7.6.3.1D	Minimum requirements for ProSe.....	280
7.6A	Void.....	280
7.6B	Blocking characteristics for UL-MIMO.....	280
7.7	Spurious response.....	281
7.7.1	Minimum requirements.....	281
7.7.1A	Minimum requirements for CA	281
7.7.1B	Minimum requirements for UL-MIMO	282
7.7.1D	Minimum requirements for ProSe	283
7.7.1F	Minimum requirements for UE category NB1.....	283
7.8	Intermodulation characteristics	284
7.8.1	Wide band intermodulation.....	284
7.8.1.1	Minimum requirements.....	284
7.8.1A	Minimum requirements for CA	284
7.8.1B	Minimum requirements for UL-MIMO	287
7.8.1D	Minimum requirements for ProSe	287
7.8.1F	Minimum requirements for category NB1	288
7.8.2	Void	288
7.9	Spurious emissions	288
7.9.1	Minimum requirements.....	289
7.9.1A	Minimum requirements.....	289
7.10	Receiver image	289
7.10.1	Void	289
7.10.1A	Minimum requirements for CA	289
8	Performance requirement	290
8.1	General	290
8.1.1	Receiver antenna capability	290
8.1.1.1	Simultaneous unicast and MBMS operations.....	291
8.1.1.2	Dual-antenna receiver capability in idle mode.....	291
8.1.2	Applicability of requirements	291
8.1.2.1	Applicability of requirements for different channel bandwidths.....	291
8.1.2.2	Definition of CA capability.....	291
8.1.2.2A	Definition of dual connectivity capability.....	294
8.1.2.3	Applicability and test rules for different CA configurations and bandwidth combination sets.....	295

8.1.2.3A	Applicability and test rules for different dual connectivity configuration and bandwidth combination set	297
8.1.2.3B	Applicability and test rules for different TDD-FDD CA configurations and bandwidth combination sets.....	298
8.1.2.4	Test coverage for different number of component carriers	300
8.1.2.5	Applicability of performance requirements for Type B receiver	301
8.1.2.6	Applicability of performance requirements for 4Rx capable UEs	301
8.1.2.6.1	Applicability rule and antenna connection for single carrier tests with 2Rx	301
8.1.2.6.2	Applicability rule and antenna connection for CA and DC tests with 2Rx	302
8.1.2.6.3	Applicability rule and antenna connection for single carrier tests with 4Rx	303
8.1.2.6.4	Applicability rule for 256QAM tests	303
8.1.2.7	Applicability of Enhanced Downlink Control Channel Performance Requirements	303
8.1.2.8	Applicability of performance requirements for CDM-multiplexed DM RS with interfering simultaneous transmission (FRC) with multiple CSI-RS configurations	304
8.1.2.8A	Applicability of performance requirements for UE supporting coverage enhancement	304
8.1.3	UE category and UE DL category	304
8.2	Demodulation of PDSCH (Cell-Specific Reference Symbols)	305
8.2.1	FDD (Fixed Reference Channel)	305
8.2.1.1	Single-antenna port performance	305
8.2.1.1.1	Minimum Requirement	305
8.2.1.1.2	Void	310
8.2.1.1.3	Void	310
8.2.1.1.4	Minimum Requirement 1 PRB allocation in presence of MBSFN.....	310
8.2.1.2	Transmit diversity performance	310
8.2.1.2.1	Minimum Requirement 2 Tx Antenna Port.....	310
8.2.1.2.2	Minimum Requirement 4 Tx Antenna Port	311
8.2.1.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS).....	312
8.2.1.2.3A	Minimum Requirement 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	314
8.2.1.2.4	Enhanced Performance Requirement Type A - 2 Tx Antenna Ports with TM3 interference model	316
8.2.1.2.5	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM2 interference model	318
8.2.1.2.6	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM9 interference model	319
8.2.1.3	Open-loop spatial multiplexing performance.....	320
8.2.1.3.1	Minimum Requirement 2 Tx Antenna Port	320
8.2.1.3.1B	Enhanced Performance Requirement Type C -2Tx Antenna Ports	324
8.2.1.3.1C	Enhanced Performance Requirement Type C - 2 Tx Antenna Ports with TM1 interference	325
8.2.1.3.2	Minimum Requirement 4 Tx Antenna Port	326
8.2.1.3.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	326
8.2.1.3.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	330
8.2.1.4	Closed-loop spatial multiplexing performance	332
8.2.1.4.1	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Port.....	332
8.2.1.4.1A	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Port.....	333
8.2.1.4.1B	Enhanced Performance Requirement Type A - Single-Layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	333
8.2.1.4.1C	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured).....	335
8.2.1.4.1D	Enhanced Performance Requirement Type B - Single-layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	337
8.2.1.4.1E	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports with CRS assistance information	339
8.2.1.4.2	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	340
8.2.1.4.2A	Enhanced Performance Requirement Type C - Multi-layer Spatial Multiplexing 2Tx Antenna Ports.....	340
8.2.1.4.3	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port	341
8.2.1.4.3A	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port for dual connectivity	345

8.2.1.5	MU-MIMO.....	346
8.2.1.6	[Control channel performance: D-BCH and PCH]	346
8.2.1.7	Carrier aggregation with power imbalance	346
8.2.1.7.1	Minimum Requirement	347
8.2.1.8	Intra-band non-contiguous carrier aggregation with timing offset.....	347
8.2.1.8.1	Minimum Requirement	348
8.2.2	TDD (Fixed Reference Channel).....	348
8.2.2.1	Single-antenna port performance	349
8.2.2.1.1	Minimum Requirement	349
8.2.2.1.2	Void	353
8.2.2.1.3	Void	353
8.2.2.1.4	Minimum Requirement 1 PRB allocation in presence of MBSFN.....	353
8.2.2.2	Transmit diversity performance	354
8.2.2.2.1	Minimum Requirement 2 Tx Antenna Port	354
8.2.2.2.2	Minimum Requirement 4 Tx Antenna Port	354
8.2.2.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	355
8.2.2.2.3A	Minimum Requirement 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	357
8.2.2.2.4	Enhanced Performance Requirement Type A – 2 Tx Antenna Ports with TM3 interference model	359
8.2.2.2.5	Minimum Requirement 2 Tx Antenna Port (when <i>EIMTA-MainConfigServCell-r12</i> is configured)	361
8.2.2.2.6	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM2 interference model	361
8.2.2.2.7	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM9 interference model	363
8.2.2.3	Open-loop spatial multiplexing performance.....	364
8.2.2.3.1	Minimum Requirement 2 Tx Antenna Port	364
8.2.2.3.1A	Soft buffer management test.....	366
8.2.2.3.1B	Enhanced Performance Requirement Type C - 2Tx Antenna Ports	367
8.2.2.3.1C	Enhanced Performance Requirement Type C - 2 Tx Antenna Ports with TM1 interference	367
8.2.2.3.2	Minimum Requirement 4 Tx Antenna Port	368
8.2.2.3.3	Minimum Requirement 2Tx antenna port (demodulation subframe overlaps with aggressor cell ABS)	369
8.2.2.3.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	373
8.2.2.4	Closed-loop spatial multiplexing performance	375
8.2.2.4.1	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Port.....	375
8.2.2.4.1A	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Port.....	376
8.2.2.4.1B	Enhanced Performance Requirement Type A – Single-Layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	376
8.2.2.4.1C	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured).....	378
8.2.2.4.1D	Enhanced Performance Requirement Type B - Single-layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	380
8.2.2.4.1E	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports with CRS assistance information	382
8.2.2.4.2	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	383
8.2.2.4.2A	Enhanced Performance Requirement Type C Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	384
8.2.2.4.3	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port	385
8.2.2.4.3A	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port for dual connectivity	388
8.2.2.4.4	Void	390
8.2.2.5	MU-MIMO.....	390
8.2.2.6	[Control channel performance: D-BCH and PCH]	390
8.2.2.7	Carrier aggregation with power imbalance	390
8.2.2.7.1	Minimum Requirement	390
8.2.2.8	Intra-band contiguous carrier aggregation with minimum channel spacing.....	391
8.2.2.8.1	Minimum Requirement	391
8.2.3	TDD FDD CA (Fixed Reference Channel).....	392

8.2.3.1	Single-antenna port performance	393
8.2.3.1.1	Minimum Requirement for FDD PCell	393
8.2.3.1.2	Minimum Requirement for TDD PCell	396
8.2.3.2	Open-loop spatial multiplexing performance 2Tx Antenna port.....	398
8.2.3.2.1	Minimum Requirement for FDD PCell	398
8.2.3.2.1A	Soft buffer management test for FDD PCell	401
8.2.3.2.2	Minimum Requirement for TDD PCell	402
8.2.3.2.2A	Soft buffer management test for TDD PCell	405
8.2.3.3	Closed-loop spatial multiplexing performance 4Tx Antenna Port.....	406
8.2.3.3.1	Minimum Requirement for FDD PCell	406
8.2.3.3.2	Minimum Requirement for TDD PCell	409
8.2.3.4	Minimum Requirement for Closed-loop spatial multiplexing performance 4Tx Antenna Port for dual connectivity	412
8.2.4	LAA.....	414
8.2.4.1	Closed-loop spatial multiplexing performance 4Tx Antenna Port.....	414
8.2.4.1.1	FDD PCell (FDD single carrier).....	414
8.2.4.1.2	TDD PCell (TDD single carrier)	416
8.3	Demodulation of PDSCH (User-Specific Reference Symbols).....	419
8.3.1	FDD	419
8.3.1.1	Single-layer Spatial Multiplexing	420
8.3.1.1A	Enhanced Performance Requirement Type A – Single-layer Spatial Multiplexing with TM9 interference model.....	421
8.3.1.1B	Single-layer Spatial Multiplexing (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	423
8.3.1.1C	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM9 interference model.....	425
8.3.1.1D	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with CRS interference model.....	427
8.3.1.1E	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM3 interference model.....	428
8.3.1.1F	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM10 serving cell configuration and TM9 interference model	429
8.3.1.1G	Single-layer Spatial Multiplexing (CRS assistance information is configured).....	431
8.3.1.1H	Single-layer Spatial Multiplexing (With Enhanced DMRS table configured)	433
8.3.1.2	Dual-Layer Spatial Multiplexing	434
8.3.1.2A	Enhanced Performance Requirement Type C - Dual-Layer Spatial Multiplexing	436
8.3.1.3	Performance requirements for DCI format 2D and non Quasi Co-located Antenna Ports	437
8.3.1.3.1	Minimum requirement with Same Cell ID (with single NZP CSI-RS resource).....	437
8.3.1.3.2	Minimum requirements with Same Cell ID (with multiple NZP CSI-RS resources).....	439
8.3.1.3.3	Minimum requirement with Different Cell ID and Colliding CRS (with single NZP CSI-RS resource)	441
8.3.1.3.4	Minimum requirement with Different Cell ID and non-colliding CRS (with single NZP CSI-RS resource and CRS assistance information is configured).....	443
8.3.1.3.5	Minimum requirements with different Cell ID and non-colliding CRS (with multiple NZP CSI-RS resources and CRS assistance information is configured).....	445
8.3.2	TDD.....	447
8.3.2.1	Single-layer Spatial Multiplexing	448
8.3.2.1A	Single-layer Spatial Multiplexing (with multiple CSI-RS configurations)	450
8.3.2.1B	Enhanced Performance Requirement Type A – Single-layer Spatial Multiplexing with TM9 interference model.....	452
8.3.2.1C	Single-layer Spatial Multiplexing (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	454
8.3.2.1D	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM9 interference.....	456
8.3.2.1E	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with CRS interference model.....	458
8.3.2.1F	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM3 interference.....	460
8.3.2.1G	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM10 serving cell configuration and TM9 interference model	461
8.3.2.1H	Single-layer Spatial Multiplexing (CRS assistance information is configured).....	463
8.3.2.1I	Single-layer Spatial Multiplexing (With Enhanced DMRS table configured)	465

8.3.2.2	Dual-Layer Spatial Multiplexing	466
8.3.2.2A	Enhanced Performance Requirement Type C - Dual-Layer Spatial Multiplexing	467
8.3.2.3	Dual-Layer Spatial Multiplexing (with multiple CSI-RS configurations)	468
8.3.2.4	Performance requirements for DCI format 2D and non Quasi Co-located Antenna Ports	469
8.3.2.4.1	Minimum requirement with Same Cell ID (with single NZP CSI-RS resource).....	469
8.3.2.4.2	Minimum requirements with Same Cell ID (with multiple NZP CSI-RS resources).....	471
8.3.2.4.3	Minimum requirement with Different Cell ID and Colliding CRS (with single NZP CSI-RS resource)	473
8.3.2.4.4	Minimum requirement with Different Cell ID and non-Colliding CRS (with single NZP CSI-RS resource and CRS assistance information is configured).....	475
8.3.2.4.5	Minimum requirements with different Cell ID and non-colliding CRS (with multiple NZP CSI-RS resources and CRS assistance information is configured).....	477
8.3.3	LAA	479
8.3.3.1	Dual-Layer Spatial Multiplexing with DM-RS	479
8.3.3.1.1	FDD PCell (FDD single carrier).....	479
8.3.3.1.2	TDD Pcell (TDD single carrier)	482
8.4	Demodulation of PDCCH/PCFICH	485
8.4.1	FDD	485
8.4.1.1	Single-antenna port performance	486
8.4.1.2	Transmit diversity performance	486
8.4.1.2.1	Minimum Requirement 2 Tx Antenna Port	486
8.4.1.2.2	Minimum Requirement 4 Tx Antenna Port	486
8.4.1.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	487
8.4.1.2.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	491
8.4.1.2.5	Enhanced Downlink Control Channel Performance Requirement Type A - 2 Tx Antenna Port under Asynchronous Network	495
8.4.1.2.6	Enhanced Downlink Control Channel Performance Requirement Type A - 2 Tx Antenna Port with Non-Colliding CRS Dominant Interferer	496
8.4.1.2.7	Enhanced Downlink Control Channel Performance Requirement Type B - 2 Tx Antenna Port with Colliding CRS Dominant Interferer	497
8.4.1.2.8	Enhanced Downlink Control Channel Performance Requirement Type B - 2 Tx Antenna Port with Non-Colliding CRS Dominant Interferer	498
8.4.2	TDD	499
8.4.2.1	Single-antenna port performance	500
8.4.2.2	Transmit diversity performance	500
8.4.2.2.1	Minimum Requirement 2 Tx Antenna Port	500
8.4.2.2.2	Minimum Requirement 4 Tx Antenna Port	501
8.4.2.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	501
8.4.2.2.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	505
8.4.2.2.5	Enhanced Downlink Control Channel Performance Requirement Type A - 2 Tx Antenna Port with Colliding CRS Dominant Interferer.....	509
8.4.2.2.6	Enhanced Downlink Control Channel Performance Requirement Type A - 2 Tx Antenna Port with Non-Colliding CRS Dominant Interferer	510
8.4.2.2.7	Enhanced Downlink Control Channel Performance Requirement Type B - 2 Tx Antenna Port with Colliding CRS Dominant Interferer.....	511
8.4.2.2.8	Enhanced Downlink Control Channel Performance Requirement Type B - 2 Tx Antenna Port with Non-Colliding CRS Dominant Interferer	512
8.4.3	LAA	513
8.4.3.1	Transmit diversity performance	513
8.4.3.1.1	FDD Pcell (FDD single carrier).....	513
8.4.3.1.2	TDD Pcell (TDD single carrier)	514
8.5	Demodulation of PHICH.....	515
8.5.1	FDD	516
8.5.1.1	Single-antenna port performance	516
8.5.1.2	Transmit diversity performance	516
8.5.1.2.1	Minimum Requirement 2 Tx Antenna Port	516
8.5.1.2.2	Minimum Requirement 4 Tx Antenna Port	517
8.5.1.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	517