

ETSI TS 136 101 V14.14.0 (2020-02)



LTE;
**Evolved Universal Terrestrial Radio Access (E-UTRA);
User Equipment (UE) radio transmission and reception
(3GPP TS 36.101 version 14.14.0 Release 14)**

iTeh STANDARDS PREVIEW
Full standard: https://standards.iteh.ai/catalog/3gpp/36/36.101/v14.14.0-2020-02
450b-a638-b3dc1d1dc8b6/etsi-ts136101v14.14.0-2020-02



Reference

RTS/TSGR-0436101vEE0

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and
of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal notice

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal notice	2
Modal verbs terminology.....	2
Foreword.....	29
1 Scope	30
2 References	30
3 Definitions, symbols and abbreviations	31
3.1 Definitions	31
3.2 Symbols	32
3.3 Abbreviations	35
4 General	36
4.1 Relationship between minimum requirements and test requirements	36
4.2 Applicability of minimum requirements	37
4.3 Void.....	37
4.3A Applicability of minimum requirements (CA, UL-MIMO, ProSe, Dual Connectivity, UE category 0, UE category M1, UE category M2, UE category 1bis, UE category NB1 and NB2, V2X Communication, MBMS UE)	37
4.4 RF requirements in later releases	38
5 Operating bands and channel arrangement.....	39
5.1 General	39
5.2 Void.....	39
5.3 Void.....	39
5.4 Void.....	39
5.5 Operating bands.....	39
5.5A Operating bands for CA	41
5.5B Operating bands for UL-MIMO	50
5.5C Operating bands for Dual Connectivity.....	50
5.5D Operating bands for ProSe.....	52
5.5E Operating bands for UE category 0,UE category M1 and M2 and UE category 1bis	52
5.5F Operating bands for category NB1 and NB2.....	53
5.5G Operating bands for V2X Communication.....	53
5.6 Channel bandwidth.....	53
5.6.1 Channel bandwidths per operating band.....	54
5.6A Channel bandwidth for CA.....	56
5.6A.1 Channel bandwidths per operating band for CA.....	58
5.6B Channel bandwidth for UL-MIMO	107
5.6B.1 Void	107
5.6C Channel bandwidth for Dual Connectivity	107
5.6C.1 Void	107
5.6D Channel bandwidth for ProSe.....	107
5.6D.1 Channel bandwidths per operating band for ProSe	107
5.6F Channel bandwidth for category NB1 and NB2.....	108
5.6G Channel bandwidth for V2X Communication.....	109
5.6G.1 Channel bandwidths per operating band for V2X Communication	109
5.7 Channel arrangement.....	110
5.7.1 Channel spacing	110
5.7.1A Channel spacing for CA	111
5.7.1F Channel spacing for category NB1 and NB2	111
5.7.2 Channel raster	111
5.7.2A Channel raster for CA	111
5.7.2F Channel raster for category NB1 and NB2	111
5.7.3 Carrier frequency and EARFCN.....	111
5.7.3F Carrier frequency and EARFCN for category NB1 and NB2	113

5.7.4	TX-RX frequency separation	113
5.7.4A	TX-RX frequency separation for CA	114
5.7.4E	TX-RX frequency separation for category M1 and M2	114
5.7.4F	TX-RX frequency separation for category NB1 and NB2	114
6	Transmitter characteristics	115
6.1	General	115
6.2	Transmit power	115
6.2.1	Void	115
6.2.2	UE maximum output power	115
6.2.2A	UE maximum output power for CA	117
6.2.2B	UE maximum output power for UL-MIMO	119
6.2.2C	Void	121
6.2.2D	UE maximum output power for ProSe	121
6.2.2E	UE maximum output power for Category M1 and M2 UE	121
6.2.2F	UE maximum output power for category NB1 and NB2	122
6.2.2G	UE maximum output power for V2X Communication	123
6.2.3	UE maximum output power for modulation / channel bandwidth	124
6.2.3A	UE Maximum Output power for modulation / channel bandwidth for CA	125
6.2.3B	UE maximum output power for modulation / channel bandwidth for UL-MIMO	128
6.2.3D	UE maximum output power for modulation / channel bandwidth for ProSe	128
6.2.3E	UE maximum output power for modulation / channel bandwidth for category M1 and M2	129
6.2.3F	UE maximum output power for modulation / channel bandwidth for category NB1 and NB2	130
6.2.3G	UE maximum output power for modulation / channel bandwidth for V2X Communication	131
6.2.3G.1	MPR for Power class 3 V2X UE	131
6.2.3G.2	MPR for Power class 2 V2X UE	132
6.2.4	UE maximum output power with additional requirements	133
6.2.4A	UE maximum output power with additional requirements for CA	146
6.2.4A.1	A-MPR for CA_NS_01 for CA_1C	147
6.2.4A.2	A-MPR for CA_NS_02 for CA_1C	148
6.2.4A.3	A-MPR for CA_NS_03 for CA_1C	149
6.2.4A.4	A-MPR for CA_NS_04	149
6.2.4A.5	A-MPR for CA_NS_05 for CA_38C	150
6.2.4A.6	A-MPR for CA_NS_06	151
6.2.4A.7	A-MPR for CA_NS_07	152
6.2.4A.8	A-MPR for CA_NS_08	153
6.2.4B	UE maximum output power with additional requirements for UL-MIMO	154
6.2.4D	UE maximum output power with additional requirements for ProSe	155
6.2.4E	UE maximum output power with additional requirements for category M1 and M2 UE	155
6.2.4F	UE maximum output power with additional requirements for category NB1 and NB2 UE	157
6.2.4G	UE maximum output power with additional requirements for V2X Communication	158
6.2.5	Configured transmitted power	160
6.2.5A	Configured transmitted power for CA	194
6.2.5B	Configured transmitted power for UL-MIMO	196
6.2.5C	Configured transmitted power for Dual Connectivity	197
6.2.5D	Configured transmitted power for ProSe	198
6.2.5F	Configured transmitted Power for category NB1 and NB2	200
6.2.5G	Configured transmitted power for V2X Communication	201
6.3	Output power dynamics	205
6.3.1	(Void)	205
6.3.2	Minimum output power	205
6.3.2.1	Minimum requirement	205
6.3.2A	UE Minimum output power for CA	205
6.3.2A.1	Minimum requirement for CA	205
6.3.2B	UE Minimum output power for UL-MIMO	205
6.3.2B.1	Minimum requirement	206
6.3.2C	Void	206
6.3.2D	UE Minimum output power for ProSe	206
6.3.2F	UE Minimum output power for category NB1 and NB2	206
6.3.2G	UE Minimum output power for V2X Communication	206
6.3.3	Transmit OFF power	207
6.3.3.1	Minimum requirement	207

6.3.3A	UE Transmit OFF power for CA	207
6.3.3A.1	Minimum requirement for CA	207
6.3.3B	UE Transmit OFF power for UL-MIMO	207
6.3.3B.1	Minimum requirement	208
6.3.3D	Transmit OFF power for ProSe.....	208
6.3.3F	Transmit OFF power for category NB1 and NB2.....	208
6.3.3G	Transmit OFF power for V2X Communication.....	208
6.3.4	ON/OFF time mask.....	209
6.3.4.1	General ON/OFF time mask	209
6.3.4.2	PRACH and SRS time mask	210
6.3.4.2.1	PRACH time mask	210
6.3.4.2.2	SRS time mask	210
6.3.4.3	Slot / Sub frame boundary time mask	211
6.3.4.4	PUCCH / PUSCH / SRS time mask.....	212
6.3.4A	ON/OFF time mask for CA	214
6.3.4B	ON/OFF time mask for UL-MIMO	214
6.3.4D	ON/OFF time mask for ProSe.....	214
6.3.4D.1	General time mask for ProSe	215
6.3.4D.2	PSSS/SSSS time mask	215
6.3.4D.3	PSSS / SSSS / PSBCH time mask.....	216
6.3.4D.4	PSSCH / SRS time mask.....	217
6.3.4F	ON/OFF time mask for category NB1 and NB2.....	217
6.3.4F.1	General ON/OFF time mask	217
6.3.4F.2	NPRACH time mask	217
6.3.4G	ON/OFF time mask for V2X Communication.....	218
6.3.4G.1	PSSS / SSSS / PSBCH time mask.....	218
6.3.5	Power Control.....	219
6.3.5.1	Absolute power tolerance.....	219
6.3.5.1.1	Minimum requirements	219
6.3.5.2	Relative Power tolerance.....	219
6.3.5.2.1	Minimum requirements	219
6.3.5.3	Aggregate power control tolerance	220
6.3.5.3.1	Minimum requirement.....	221
6.3.5A	Power control for CA.....	221
6.3.5A.1	Absolute power tolerance.....	221
6.3.5A.1.1	Minimum requirements	221
6.3.5A.2	Relative power tolerance.....	221
6.3.5A.2.1	Minimum requirements	221
6.3.5A.3	Aggregate power control tolerance	222
6.3.5A.3.1	Minimum requirements	222
6.3.5B	Power control for UL-MIMO	222
6.3.5D	Power Control for ProSe	223
6.3.5D.1	Absolute power tolerance.....	223
6.3.5E	Power control for category M1 and M2.....	223
6.3.5E.1	Absolute power tolerance.....	223
6.3.5E.2	Relative Power tolerance.....	223
6.3.5E.3	Aggregate power control tolerance	223
6.3.5E.3.1	Minimum requirement.....	223
6.3.5F	Power Control for category NB1 and NB2.....	224
6.3.5F.1	Absolute power tolerance.....	224
6.3.5F.2	Relative power tolerance	225
6.3.5F.3	Aggregate power control tolerance for category NB1 and NB2	225
6.3.5F.3.1	Minimum requirement.....	225
6.3.5G	Power Control for V2X Communication	225
6.3.5G.1	Absolute power tolerance.....	226
6.4	Void.....	226
6.5	Transmit signal quality	226
6.5.1	Frequency error.....	226
6.5.1A	Frequency error for CA	226
6.5.1B	Frequency error for UL-MIMO	226
6.5.1D	Frequency error for ProSe.....	226
6.5.1E	Frequency error for UE category M1 and M2	227

6.5.1F	Frequency error for UE category NB1 and NB2	227
6.5.1G	Frequency error for V2X Communication.....	227
6.5.2	Transmit modulation quality.....	227
6.5.2.1	Error Vector Magnitude	228
6.5.2.1.1	Minimum requirement.....	228
6.5.2.2	Carrier leakage	228
6.5.2.2.1	Minimum requirements	228
6.5.2.3	In-band emissions	229
6.5.2.3.1	Minimum requirements	229
6.5.2.4	EVM equalizer spectrum flatness	230
6.5.2.4.1	Minimum requirements	230
6.5.2A	Transmit modulation quality for CA.....	231
6.5.2A.1	Error Vector Magnitude	231
6.5.2A.2	Carrier leakage for CA.....	232
6.5.2A.2.1	Minimum requirements.....	232
6.5.2A.3	In-band emissions	232
6.5.2A.3.1	Minimum requirement for CA.....	232
6.5.2B	Transmit modulation quality for UL-MIMO	235
6.5.2B.1	Error Vector Magnitude	235
6.5.2B.2	Carrier leakage	235
6.5.2B.3	In-band emissions	235
6.5.2B.4	EVM equalizer spectrum flatness for UL-MIMO	235
6.5.2D	Transmit modulation quality for ProSe.....	235
6.5.2D.1	Error Vector Magnitude	235
6.5.2D.2	Carrier leakage	236
6.5.2D.3	In-band emissions	236
6.5.2D.4	EVM equalizer spectrum flatness for ProSe	236
6.5.2E	Transmit modulation quality for category M1 and M2.....	236
6.5.2E.1	Error Vector Magnitude	236
The Error Vector Magnitude is defined in section 6.5.2.1.	236
6.5.2E.2	Carrier leakage	236
6.5.2E.2.1	Minimum requirements.....	236
6.5.2E.3	In-band emissions	236
6.5.2E.3.1	Minimum requirements	236
6.5.2F	Transmit modulation quality for Category NB1 and NB2.....	237
6.5.2F.1	Error Vector Magnitude	237
6.5.2F.2	Carrier leakage	237
6.5.2F.3	In-band emissions	238
6.5.2G	Transmit modulation quality for V2X Communication.....	238
6.5.2G.1	Error Vector Magnitude	239
6.5.2G.2	Carrier leakage	239
6.5.2G.3	In-band emissions	239
6.5.2G.4	EVM equalizer spectrum flatness	239
6.6	Output RF spectrum emissions.....	239
6.6.1	Occupied bandwidth	240
6.6.1.1	Additional minimum requirement for E-UTRA (network signalled value "NS_29").....	240
6.6.1A	Occupied bandwidth for CA	240
6.6.1B	Occupied bandwidth for UL-MIMO.....	241
6.6.1F	Occupied bandwidth for category NB1 and NB2	241
6.6.1G	Occupied bandwidth for V2X Communication	241
6.6.2	Out of band emission	241
6.6.2.1	Spectrum emission mask.....	241
6.6.2.1.1	Minimum requirement.....	241
6.6.2.1A	Spectrum emission mask for CA.....	242
6.6.2.2	Additional spectrum emission mask	244
6.6.2.2.1	Minimum requirement (network signalled value "NS_03", "NS_11", "NS_20", and "NS_21").....	244
6.6.2.2.2	Minimum requirement (network signalled value "NS_04").....	244
6.6.2.2.3	Minimum requirement (network signalled value "NS_06" or "NS_07")	245
6.6.2.2.4	Minimum requirement (network signalled value "NS_33" or "NS_34")	245
6.6.2.2.5	Minimum requirement (network signalled value "NS_27").....	246
6.6.2.2.6	Minimum requirement (network signalled value "NS_28").....	246
6.6.2.2A	Additional Spectrum Emission Mask for CA.....	247

6.6.2.2A.1	Minimum requirement (network signalled value "CA_NS_04").....	247
6.6.2.3	Adjacent Channel Leakage Ratio	248
6.6.2.3.1	Minimum requirement E-UTRA	248
6.6.2.3.1a	Additional minimum requirement for E-UTRA (network signalled value "NS_29")	249
6.6.2.3.1A	Void.....	249
6.6.2.3.1Aa	Void.....	249
6.6.2.3.2	Minimum requirements UTRA	249
6.6.2.3.2A	Minimum requirement UTRA for CA	250
6.6.2.3.3A	Minimum requirements for CA E-UTRA.....	251
6.6.2.4	Void.....	253
6.6.2.4.1	Void.....	253
6.6.2A	Void	253
6.6.2B	Out of band emission for UL-MIMO.....	253
6.6.2C	Void	253
6.6.2D	Out of band emission for ProSe	253
6.6.2F	Out of band emission for category NB1 and NB2	253
6.6.2F.1	Spectrum emission mask.....	253
6.6.2F.2.1	Minimum requirement (network signalled value "NS_02")	254
6.6.2F.2.2	Minimum requirement (network signalled value "NS_03")	254
6.6.2F.3	Adjacent Channel Leakage Ratio for category NB1 and NB2	254
6.6.2G	Out of band emission for V2X Communication	255
6.6.3	Spurious emissions	255
6.6.3.1	Minimum requirements	256
6.6.3.1A	Minimum requirements for CA.....	256
6.6.3.2	Spurious emission band UE co-existence	257
6.6.3.2A	Spurious emission band UE co-existence for CA	263
6.6.3.3	Additional spurious emissions	274
6.6.3.3.1	Minimum requirement (network signalled value "NS_05").....	274
6.6.3.3.2	Minimum requirement (network signalled value "NS_07").....	274
6.6.3.3.3	Minimum requirement (network signalled value "NS_08").....	275
6.6.3.3.4	Minimum requirement (network signalled value "NS_09").....	275
6.6.3.3.5	Minimum requirement (network signalled value "NS_12").....	275
6.6.3.3.6	Minimum requirement (network signalled value "NS_13").....	276
6.6.3.3.7	Minimum requirement (network signalled value "NS_14").....	276
6.6.3.3.8	Minimum requirement (network signalled value "NS_15").....	276
6.6.3.3.9	Minimum requirement (network signalled value "NS_16").....	276
6.6.3.3.10	Minimum requirement (network signalled value "NS_17").....	277
6.6.3.3.11	Minimum requirement (network signalled value "NS_18").....	277
6.6.3.3.12	Minimum requirement (network signalled value "NS_19").....	277
6.6.3.3.13	Minimum requirement (network signalled value "NS_11").....	277
6.6.3.3.14	Minimum requirement (network signalled value "NS_20").....	278
6.6.3.3.15	Minimum requirement (network signalled value "NS_21").....	278
6.6.3.3.16	Minimum requirement (network signalled value "NS_22").....	278
6.6.3.3.17	Minimum requirement (network signalled value "NS_23").....	279
6.6.3.3.18	Void.....	279
6.6.3.3.19	Minimum requirement (network signalled value "NS_04").....	279
6.6.3.3.20	Minimum requirement (network signalled value "NS_24").....	280
6.6.3.3.21	Minimum requirement (network signalled value "NS_25").....	280
6.6.3.3.22	Minimum requirement (network signalled value "NS_26").....	280
6.6.3.3.23	Minimum requirement (network signalled value "NS_27").....	281
6.6.3.3.24	Minimum requirement (network signalled value "NS_28").....	281
6.6.3.3.25	Minimum requirement (network signalled value "NS_29").....	281
6.6.3.3.26	Minimum requirement (network signalled value "NS_30").....	282
6.6.3.3.27	Minimum requirement (network signalled value "NS_31").....	283
6.6.3.3.28	Minimum requirement (network signalled value "NS_36").....	284
6.6.3.3A	Additional spurious emissions for CA	284
6.6.3.3A.1	Minimum requirement for CA_1C (network signalled value "CA_NS_01").....	284
6.6.3.3A.2	Minimum requirement for CA_1C (network signalled value "CA_NS_02").....	284
6.6.3.3A.3	Minimum requirement for CA_1C (network signalled value "CA_NS_03").....	285
6.6.3.3A.4	Minimum requirement for CA_38C (network signalled value "CA_NS_05").....	285
6.6.3.3A.5	Minimum requirement for CA_7C (network signalled value "CA_NS_06").....	285

6.6.3.3A.6	Minimum requirement for CA_39C and CA_39C-41A (network signalled value "CA_NS_07").....	286
6.6.3.3A.7	Minimum requirement for CA_42C (network signalled value "CA_NS_08").....	286
6.6.3.3A.8	Minimum requirement for CA_41C (network signalled value "CA_NS_04").....	287
6.6.3A	Void	287
6.6.3B	Spurious emission for UL-MIMO	287
6.6.3C	Void	287
6.6.3D	Spurious emission for ProSe	287
6.6.3F	Spurious emission for category NB1 and NB2	287
6.6.3G	Spurious emission for V2X Communication	287
6.6A	Void.....	289
6.6B	Void.....	289
6.7	Transmit intermodulation	289
6.7.1	Minimum requirement	289
6.7.1A	Minimum requirement for CA	290
6.7.1B	Minimum requirement for UL-MIMO	290
6.7.1F	Minimum requirement for category NB1 and NB2	290
6.7.1G	Minimum requirement for V2X Communication	291
6.8	Void.....	291
6.8A	Void.....	291
6.8B	Time alignment error for UL-MIMO	291
6.8B.1	Minimum Requirements	291
7	Receiver characteristics	291
7.1	General	291
7.2	Diversity characteristics	292
7.3	Reference sensitivity power level.....	292
7.3.1	Minimum requirements (QPSK).....	293
7.3.1A	Minimum requirements (QPSK) for CA.....	328
7.3.1B	Minimum requirements (QPSK) for UL-MIMO	393
7.3.1D	Minimum requirements (QPSK) for ProSe.....	393
7.3.1E	Minimum requirements (QPSK) for UE category 0, M1, M2 and 1bis	395
7.3.1F	Minimum requirements for UE category NB1 and NB2	403
7.3.1F.1	Reference sensitivity for UE category NB1 and NB2	403
7.3.1F.2	Void.....	404
7.3.1G	Minimum requirements (QPSK) for V2X	404
7.3.2	Void	406
7.4	Maximum input level	406
7.4.1	Minimum requirements.....	406
7.4.1A	Minimum requirements for CA	406
7.4.1B	Minimum requirements for UL-MIMO	407
7.4.1D	Minimum requirements for ProSe	407
7.4.1F	Minimum requirements for category NB1 and NB2.....	407
7.4.1G	Minimum requirements for V2X	408
7.4A	Void.....	408
7.4A.1	Void	408
7.5	Adjacent Channel Selectivity (ACS)	408
7.5.1	Minimum requirements	408
7.5.1A	Minimum requirements for CA	409
7.5.1B	Minimum requirements for UL-MIMO	413
7.5.1D	Minimum requirements for ProSe	413
7.5.1F	Minimum requirements for category NB1 and NB2	414
7.5.1G	Minimum requirements for V2X	415
7.6	Blocking characteristics	417
7.6.1	In-band blocking	417
7.6.1.1	Minimum requirements	417
7.6.1.1A	Minimum requirements for CA.....	418
7.6.1.1D	Minimum requirements for ProSe	422
7.6.1.1F	Minimum requirements for category NB1 and NB2	423
7.6.1.1G	Minimum requirements for V2X	424
7.6.2	Out-of-band blocking.....	425
7.6.2.1	Minimum requirements	425

7.6.2.1A	Minimum requirements for CA	427
7.6.2.1D	Minimum requirements for ProSe	430
7.6.2.1F	Minimum requirements for category NB1 and NB2	431
7.6.2.1G	Minimum requirements for V2X	432
7.6.3	Narrow band blocking	433
7.6.3.1	Minimum requirements	433
7.6.3.1A	Minimum requirements for CA	434
7.6.3.1D	Minimum requirements for ProSe	435
7.6A	Void	436
7.6B	Blocking characteristics for UL-MIMO	436
7.7	Spurious response	436
7.7.1	Minimum requirements	436
7.7.1A	Minimum requirements for CA	437
7.7.1B	Minimum requirements for UL-MIMO	438
7.7.1D	Minimum requirements for ProSe	438
7.7.1F	Minimum requirements for UE category NB1 and NB2	439
7.7.1G	Minimum requirements for V2X	439
7.8	Intermodulation characteristics	440
7.8.1	Wide band intermodulation	440
7.8.1.1	Minimum requirements	440
7.8.1A	Minimum requirements for CA	441
7.8.1B	Minimum requirements for UL-MIMO	444
7.8.1D	Minimum requirements for ProSe	444
7.8.1F	Minimum requirements for category NB1 and NB2	445
7.8.1G	Minimum requirements	445
7.8.2	Void	446
7.9	Spurious emissions	446
7.9.1	Minimum requirements	447
7.9.1A	Minimum requirements	447
7.10	Receiver image	448
7.10.1	Void	448
7.10.1A	Minimum requirements for CA	448
7.10.1G	Minimum requirements for V2X Communication	448
8	Performance requirement	449
8.1	General	449
8.1.1	Receiver antenna capability	449
8.1.1.1	Simultaneous unicast and MBMS operations	450
8.1.1.2	Dual-antenna receiver capability in idle mode	450
8.1.2	Applicability of requirements	450
8.1.2.1	Applicability of requirements for different channel bandwidths	450
8.1.2.2	Definition of CA capability	450
8.1.2.2A	Definition of dual connectivity capability	454
8.1.2.3	Applicability and test rules for different CA configurations and bandwidth combination sets	454
8.1.2.3A	Applicability and test rules for different dual connectivity configuration and bandwidth combination set	456
8.1.2.3B	Applicability and test rules for different TDD-FDD CA configurations and bandwidth combination sets	457
8.1.2.3C	Applicability and test rules for SDR tests for 4Rx capable UEs	459
8.1.2.3D	Applicability and test rules for different CA with LAA SCell(s) configurations and bandwidth combination sets	459
8.1.2.4	Test coverage for different number of component carriers	460
8.1.2.5	Applicability of performance requirements for Type B receiver	461
8.1.2.6	Applicability of performance requirements for 4Rx capable UEs	461
8.1.2.6.1	Applicability rule and antenna connection for single carrier tests with 2Rx	462
8.1.2.6.2	Applicability rule and antenna connection for CA and DC tests with 2Rx	463
8.1.2.6.3	Applicability rule and antenna connection for single carrier tests with 4Rx	463
8.1.2.6.4	Applicability rule for 256QAM tests	464
8.1.2.6.5	Applicability rule and antenna connection for CA and DC tests with 4Rx	464
8.1.2.6.6	Applicability rule for Type C with 4Rx	467
8.1.2.7	Applicability of Enhanced Downlink Control Channel Performance Requirements	467

8.1.2.8	Applicability of performance requirements for CDM-multiplexed DM RS with interfering simultaneous transmission (FRC) with multiple CSI-RS configurations	469
8.1.2.8A	Applicability of performance requirements for UE supporting coverage enhancement	469
8.1.2.9	Applicability of SDR requirements for CA and LAA	470
8.1.2.10	Applicability of performance requirements for Multi-user Superposed Transmission	470
8.1.2.11	Applicability CRS interference mitigation receivers performance requirements	471
8.1.3	UE category and UE DL category	471
8.2	Demodulation of PDSCH (Cell-Specific Reference Symbols)	471
8.2.1	FDD (Fixed Reference Channel)	471
8.2.1.1	Single-antenna port performance	472
8.2.1.1.1	Minimum Requirement	472
8.2.1.1.2	Void	477
8.2.1.1.3	Void	477
8.2.1.1.4	Minimum Requirement 1 PRB allocation in presence of MBSFN	477
8.2.1.1.4A	Minimum Requirement 1 PRB allocation in presence of FeMBMS Unicast-mixed Cell under CA	478
8.2.1.2	Transmit diversity performance	478
8.2.1.2.1	Minimum Requirement 2 Tx Antenna Port	478
8.2.1.2.2	Minimum Requirement 4 Tx Antenna Port	479
8.2.1.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	480
8.2.1.2.3A	Minimum Requirement 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	482
8.2.1.2.4	Enhanced Performance Requirement Type A - 2 Tx Antenna Ports with TM3 interference model	484
8.2.1.2.5	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM2 interference model	486
8.2.1.2.6	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM9 interference model	487
8.2.1.2.7	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	488
8.2.1.3	Open-loop spatial multiplexing performance	488
8.2.1.3.1	Minimum Requirement 2 Tx Antenna Port	488
8.2.1.3.1A	Soft buffer management test	491
8.2.1.3.1B	Enhanced Performance Requirement Type C - 2Tx Antenna Ports	493
8.2.1.3.1C	Enhanced Performance Requirement Type C - 2 Tx Antenna Ports with TM1 interference	493
8.2.1.3.2	Minimum Requirement 4 Tx Antenna Port	494
8.2.1.3.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	495
8.2.1.3.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	499
8.2.1.3.5	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	501
8.2.1.4	Closed-loop spatial multiplexing performance	502
8.2.1.4.1	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Port	502
8.2.1.4.1A	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Port	502
8.2.1.4.1B	Enhanced Performance Requirement Type A - Single-Layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	503
8.2.1.4.1C	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	505
8.2.1.4.1D	Enhanced Performance Requirement Type B - Single-layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	507
8.2.1.4.1E	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports with CRS assistance information	509
8.2.1.4.1F	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Ports with CRS assistance information	510
8.2.1.4.2	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	511
8.2.1.4.2A	Enhanced Performance Requirement Type C – Multi-layer Spatial Multiplexing 2Tx Antenna Ports	512
8.2.1.4.3	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port	512
8.2.1.4.3A	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port for dual connectivity	516
8.2.1.4.4	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port (Superposed transmission)	517

8.2.1.5	MU-MIMO.....	518
8.2.1.6	[Control channel performance: D-BCH and PCH]	518
8.2.1.7	Carrier aggregation with power imbalance	518
8.2.1.7.1	Minimum Requirement	518
8.2.1.8	Intra-band non-contiguous carrier aggregation with timing offset.....	519
8.2.1.8.1	Minimum Requirement	519
8.2.1.9	HST-SFN performance	520
8.2.1.9.1	Minimum Requirement	520
8.2.2	TDD (Fixed Reference Channel).....	521
8.2.2.1	Single-antenna port performance	521
8.2.2.1.1	Minimum Requirement	521
8.2.2.1.2	Void	525
8.2.2.1.3	Void	525
8.2.2.1.4	Minimum Requirement 1 PRB allocation in presence of MBSFN.....	525
8.2.2.2	Transmit diversity performance	526
8.2.2.2.1	Minimum Requirement 2 Tx Antenna Port	526
8.2.2.2.2	Minimum Requirement 4 Tx Antenna Port	527
8.2.2.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	527
8.2.2.2.3A	Minimum Requirement 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	529
8.2.2.2.4	Enhanced Performance Requirement Type A – 2 Tx Antenna Ports with TM3 interference model	531
8.2.2.2.5	Minimum Requirement 2 Tx Antenna Port (when <i>EIMTA-MainConfigServCell-r12</i> is configured)	533
8.2.2.2.6	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM2 interference model	533
8.2.2.2.7	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM9 interference model	535
8.2.2.2.8	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	536
8.2.2.3	Open-loop spatial multiplexing performance	537
8.2.2.3.1	Minimum Requirement 2 Tx Antenna Port	537
8.2.2.3.1A	Soft buffer management test.....	539
8.2.2.3.1B	Enhanced Performance Requirement Type C - 2Tx Antenna Ports.....	540
8.2.2.3.1C	Enhanced Performance Requirement Type C - 2 Tx Antenna Ports with TM1 interference	540
8.2.2.3.2	Minimum Requirement 4 Tx Antenna Port	541
8.2.2.3.3	Minimum Requirement 2Tx antenna port (demodulation subframe overlaps with aggressor cell ABS)	542
8.2.2.3.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	546
8.2.2.3.5	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	548
8.2.2.4	Closed-loop spatial multiplexing performance	549
8.2.2.4.1	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Port.....	549
8.2.2.4.1A	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Port.....	549
8.2.2.4.1B	Enhanced Performance Requirement Type A – Single-Layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	550
8.2.2.4.1C	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured).....	552
8.2.2.4.1D	Enhanced Performance Requirement Type B - Single-layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	554
8.2.2.4.1E	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports with CRS assistance information	556
8.2.2.4.1F	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Ports with CRS assistance information	557
8.2.2.4.2	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	559
8.2.2.4.2A	Enhanced Performance Requirement Type C Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	559
8.2.2.4.3	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port	560
8.2.2.4.3A	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port for dual connectivity	563
8.2.2.4.4	Void	565

8.2.2.4.5	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port (Superposed transmission)	565
8.2.2.5	MU-MIMO.....	566
8.2.2.6	[Control channel performance: D-BCH and PCH]	566
8.2.2.7	Carrier aggregation with power imbalance	566
8.2.2.7.1	Minimum Requirement	566
8.2.2.8	Intra-band contiguous carrier aggregation with minimum channel spacing.....	567
8.2.2.8.1	Minimum Requirement	567
8.2.2.9	HST-SFN performance	568
8.2.2.9.1	Minimum Requirement	568
8.2.3	TDD FDD CA (Fixed Reference Channel).....	568
8.2.3.1	Single-antenna port performance	569
8.2.3.1.1	Minimum Requirement for FDD PCell	569
8.2.3.1.2	Minimum Requirement for TDD PCell	573
8.2.3.2	Open-loop spatial multiplexing performance 2Tx Antenna port.....	575
8.2.3.2.1	Minimum Requirement for FDD PCell	575
8.2.3.2.1A	Soft buffer management test for FDD PCell	578
8.2.3.2.2	Minimum Requirement for TDD PCell	579
8.2.3.2.2A	Soft buffer management test for TDD PCell	583
8.2.3.3	Closed-loop spatial multiplexing performance 4Tx Antenna Port	584
8.2.3.3.1	Minimum Requirement for FDD PCell	584
8.2.3.3.2	Minimum Requirement for TDD PCell	587
8.2.3.4	Minimum Requirement for Closed-loop spatial multiplexing performance 4Tx Antenna Port for dual connectivity	590
8.2.4	LAA	592
8.2.4.1	Closed-loop spatial multiplexing performance 4Tx Antenna Port.....	592
8.2.4.1.1	FDD PCell (FDD single carrier).....	592
8.2.4.1.2	TDD PCell (TDD single carrier).....	595
8.3	Demodulation of PDSCH (User-Specific Reference Symbols).....	599
8.3.1	FDD	599
8.3.1.1	Single-layer Spatial Multiplexing.....	599
8.3.1.1A	Enhanced Performance Requirement Type A – Single-layer Spatial Multiplexing with TM9 interference model.....	601
8.3.1.1B	Single-layer Spatial Multiplexing (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	603
8.3.1.1C	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM9 interference model.....	605
8.3.1.1D	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with CRS interference model.....	607
8.3.1.1E	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM3 interference model.....	608
8.3.1.1F	Enhanced Performance Requirement Type B – Single-layer Spatial Multiplexing with TM10 serving cell configuration and TM9 interference model	609
8.3.1.1G	Single-layer Spatial Multiplexing (CRS assistance information is configured).....	611
8.3.1.1H	Single-layer Spatial Multiplexing (With Enhanced DMRS table configured)	613
8.3.1.1I	Single-layer Spatial Multiplexing (with assistance information for simultaneous transmission interfering PDSCH).....	614
8.3.1.2	Dual-Layer Spatial Multiplexing	616
8.3.1.2A	Enhanced Performance Requirement Type C - Dual-Layer Spatial Multiplexing	617
8.3.1.3	Performance requirements for DCI format 2D and non Quasi Co-located Antenna Ports	618
8.3.1.3.1	Minimum requirement with Same Cell ID (with single NZP CSI-RS resource).....	618
8.3.1.3.2	Minimum requirements with Same Cell ID (with multiple NZP CSI-RS resources).....	620
8.3.1.3.3	Minimum requirement with Different Cell ID and Colliding CRS (with single NZP CSI-RS resource)	622
8.3.1.3.4	Minimum requirement with Different Cell ID and non-colliding CRS (with single NZP CSI-RS resource and CRS assistance information is configured).....	624
8.3.1.3.5	Minimum requirements with different Cell ID and non-colliding CRS (with multiple NZP CSI-RS resources and CRS assistance information is configured).....	626
8.3.1.4	Performance Requirements for semiOpenLoop transmission	628
8.3.2	TDD	630
8.3.2.1	Single-layer Spatial Multiplexing	630
8.3.2.1A	Single-layer Spatial Multiplexing (with multiple CSI-RS configurations)	632