



LTE;
Evolved Universal Terrestrial Radio Access (E-UTRA);
User Equipment (UE) radio transmission and reception
(3GPP TS 36.101 version 15.9.0 Release 15)



ReferenceRTS/TSGR-0436101vF90

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal notice

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Foreword.....	31
1 Scope	32
2 References	32
3 Definitions, symbols and abbreviations	32
3.1 Definitions	32
3.2 Symbols	34
3.3 Abbreviations	37
4 General	38
4.1 Relationship between minimum requirements and test requirements	38
4.2 Applicability of minimum requirements	39
4.3 Void	39
4.3A Applicability of minimum requirements (CA, UL-MIMO, ProSe, Dual Connectivity, UE category 0, UE category M1, UE category M2, UE category 1bis, UE category NB1 and NB2, V2X Communication, MBMS UE)	39
4.4 RF requirements in later releases	41
5 Operating bands and channel arrangement.....	41
5.1 General	41
5.2 Void	41
5.3 Void	41
5.4 Void	41
5.5 Operating bands.....	41
5.5A Operating bands for CA	43
5.5B Operating bands for UL-MIMO	56
5.5C Operating bands for Dual Connectivity	56
5.5D Operating bands for ProSe.....	58
5.5E Operating bands for UE category 0, UE category M1 and M2 and UE category 1bis	59
5.5F Operating bands for category NB1 and NB2.....	59
5.5G Operating bands for V2X Communication	59
5.6 Channel bandwidth.....	60
5.6.1 Channel bandwidths per operating band	61
5.6A Channel bandwidth for CA.....	63
5.6A.1 Channel bandwidths per operating band for CA	65
5.6B Channel bandwidth for UL-MIMO	149
5.6B.1 Void	150
5.6C Channel bandwidth for Dual Connectivity	150
5.6C.1 Void	150
5.6D Channel bandwidth for ProSe.....	150
5.6D.1 Channel bandwidths per operating band for ProSe.....	150
5.6F Channel bandwidth for category NB1 and NB2.....	151
5.6G Channel bandwidth for V2X Communication	152
5.6G.1 Channel bandwidths per operating band for V2X Communication	152
5.7 Channel arrangement.....	154
5.7.1 Channel spacing.....	154
5.7.1A Channel spacing for CA.....	154
5.7.1F Channel spacing for category NB1 and NB2.....	155
5.7.2 Channel raster	155
5.7.2A Channel raster for CA	155
5.7.2F Channel raster for category NB1 and NB2	155
5.7.3 Carrier frequency and EARFCN.....	155
5.7.3F Carrier frequency and EARFCN for category NB1 and NB2.....	157
5.7.4 TX–RX frequency separation	157
5.7.4A TX–RX frequency separation for CA	158
5.7.4E TX–RX frequency separation for category M1 and M2	158
5.7.4F TX–RX frequency separation for category NB1 and NB2	158

6	Transmitter characteristics	159
6.1	General	159
6.2	Transmit power	159
6.2.1	Void	159
6.2.2	UE maximum output power	159
6.2.2A	UE maximum output power for CA	161
6.2.2B	UE maximum output power for UL-MIMO	165
6.2.2C	Void	167
6.2.2D	UE maximum output power for ProSe	167
6.2.2E	UE maximum output power for Category M1 and M2 UE	167
6.2.2F	UE maximum output power for category NB1 and NB2	168
6.2.2G	UE maximum output power for V2X Communication	169
6.2.3	UE maximum output power for modulation / channel bandwidth	171
6.2.3A	UE Maximum Output power for modulation / channel bandwidth for CA	172
6.2.3B	UE maximum output power for modulation / channel bandwidth for UL-MIMO	177
6.2.3D	UE maximum output power for modulation / channel bandwidth for ProSe	177
6.2.3E	UE maximum output power for modulation / channel bandwidth for category M1 and M2	178
6.2.3F	UE maximum output power for modulation / channel bandwidth for category NB1 and NB2	180
6.2.3G	UE maximum output power for modulation / channel bandwidth for V2X Communication	180
6.2.3G.1	MPR for Power class 3 V2X UE	180
6.2.3G.2	MPR for Power class 2 V2X UE	182
6.2.4	UE maximum output power with additional requirements	182
6.2.4A	UE maximum output power with additional requirements for CA	200
6.2.4A.1	A-MPR for CA_NS_01 for CA_1C	202
6.2.4A.2	A-MPR for CA_NS_02 for CA_1C	202
6.2.4A.3	A-MPR for CA_NS_03 for CA_1C	203
6.2.4A.4	A-MPR for CA_NS_04	204
6.2.4A.5	A-MPR for CA_NS_05 for CA_38C	206
6.2.4A.6	A-MPR for CA_NS_06	207
6.2.4A.7	A-MPR for CA_NS_07	207
6.2.4A.8	A-MPR for CA_NS_08	208
6.2.4A.9	Void	209
6.2.4B	UE maximum output power with additional requirements for UL-MIMO	209
6.2.4D	UE maximum output power with additional requirements for ProSe	210
6.2.4E	UE maximum output power with additional requirements for category M1 and M2 UE	210
6.2.4F	UE maximum output power with additional requirements for category NB1 and NB2 UE	219
6.2.4G	UE maximum output power with additional requirements for V2X Communication	220
6.2.5	Configured transmitted power	222
6.2.5A	Configured transmitted power for CA	247
6.2.5B	Configured transmitted power for UL-MIMO	251
6.2.5C	Configured transmitted power for Dual Connectivity	252
6.2.5D	Configured transmitted power for ProSe	253
6.2.5F	Configured transmitted Power for category NB1 and NB2	255
6.2.5G	Configured transmitted power for V2X Communication	256
6.3	Output power dynamics	260
6.3.1	(Void)	260
6.3.2	Minimum output power	260
6.3.2.1	Minimum requirement	260
6.3.2A	UE Minimum output power for CA	260
6.3.2A.1	Minimum requirement for CA	260
6.3.2B	UE Minimum output power for UL-MIMO	260
6.3.2B.1	Minimum requirement	261
6.3.2C	Void	261
6.3.2D	UE Minimum output power for ProSe	261
6.3.2F	UE Minimum output power for category NB1 and NB2	261
6.3.2G	UE Minimum output power for V2X Communication	261
6.3.3	Transmit OFF power	262
6.3.3.1	Minimum requirement	262
6.3.3A	UE Transmit OFF power for CA	262
6.3.3A.1	Minimum requirement for CA	262
6.3.3B	UE Transmit OFF power for UL-MIMO	263
6.3.3B.1	Minimum requirement	263

6.3.3D	Transmit OFF power for ProSe.....	263
6.3.3F	Transmit OFF power for category NB1 and NB2.....	263
6.3.3G	Transmit OFF power for V2X Communication.....	264
6.3.4	ON/OFF time mask.....	264
6.3.4.1	General ON/OFF time mask	264
6.3.4.2	PRACH and SRS time mask	265
6.3.4.2.1	PRACH time mask	265
6.3.4.2.2	SRS time mask	266
6.3.4.3	Slot / Sub frame boundary time mask for subframe TTI.....	267
6.3.4.4	PUCCH / PUSCH / SRS time mask for subframe TTI	269
6.3.4.5	Symbol / Subslot boundary time mask for subslot TTI.....	271
6.3.4.6	Subslot PUCCH / subslot PUSCH / SRS time mask for subslot TTI.....	273
6.3.4.7	Symbol / Slot boundary time mask for slot TTI.....	276
6.3.4.8	Slot PUCCH / slot PUSCH / SRS time mask for slot TTI	276
6.3.4.9	Consecutive subslot and slot TTI or consecutive subslot and subframe TTI time mask.....	277
6.3.4.10	Consecutive subframe and subslot TTI or consecutive slot and subslot TTI time mask.....	277
6.3.4.11	Consecutive TTI and slot TTI or consecutive slot TTI and TTI time mask.....	278
6.3.4A	ON/OFF time mask for CA	278
6.3.4B	ON/OFF time mask for UL-MIMO	278
6.3.4D	ON/OFF time mask for ProSe.....	279
6.3.4D.1	General time mask for ProSe	279
6.3.4D.2	PSSS/SSSS time mask	279
6.3.4D.3	PSSS / SSSS / PSBCH time mask.....	280
6.3.4D.4	PSSCH / SRS time mask.....	281
6.3.4F	ON/OFF time mask for category NB1 and NB2.....	281
6.3.4F.1	General ON/OFF time mask	281
6.3.4F.2	NPRACH time mask	281
6.3.4G	ON/OFF time mask for V2X Communication	282
6.3.4G.1	PSSS / SSSS / PSBCH time mask.....	282
6.3.5	Power Control	283
6.3.5.1	Absolute power tolerance.....	283
6.3.5.1.1	Minimum requirements	283
6.3.5.2	Relative Power tolerance.....	284
6.3.5.2.1	Minimum requirements	284
6.3.5.3	Aggregate power control tolerance.....	285
6.3.5.3.1	Minimum requirement.....	285
6.3.5A	Power control for CA.....	285
6.3.5A.1	Absolute power tolerance.....	285
6.3.5A.1.1	Minimum requirements	285
6.3.5A.2	Relative power tolerance.....	286
6.3.5A.2.1	Minimum requirements	286
6.3.5A.3	Aggregate power control tolerance	286
6.3.5A.3.1	Minimum requirements	286
6.3.5B	Power control for UL-MIMO	287
6.3.5D	Power Control for ProSe.....	287
6.3.5D.1	Absolute power tolerance.....	287
6.3.5E	Power control for category M1 and M2.....	287
6.3.5E.1	Absolute power tolerance.....	287
6.3.5E.2	Relative Power tolerance.....	287
6.3.5E.3	Aggregate power control tolerance	288
6.3.5E.3.1	Minimum requirement.....	288
6.3.5F	Power Control for category NB1 and NB2.....	288
6.3.5F.1	Absolute power tolerance.....	289
6.3.5F.2	Relative power tolerance.....	289
6.3.5F.3	Aggregate power control tolerance for category NB1 and NB2	290
6.3.5F.3.1	Minimum requirement.....	290
6.3.5G	Power Control for V2X Communication	290
6.3.5G.1	Absolute power tolerance.....	290
6.4	Void.....	291
6.5	Transmit signal quality	291
6.5.1	Frequency error.....	291
6.5.1A	Frequency error for CA.....	291

6.5.1B	Frequency error for UL-MIMO	291
6.5.1D	Frequency error for ProSe.....	291
6.5.1E	Frequency error for UE category M1 and M2	291
6.5.1F	Frequency error for UE category NB1 and NB2	291
6.5.1G	Frequency error for V2X Communication.....	292
6.5.2	Transmit modulation quality.....	292
6.5.2.1	Error Vector Magnitude	292
6.5.2.1.1	Minimum requirement.....	293
6.5.2.2	Carrier leakage	293
6.5.2.2.1	Minimum requirements	293
6.5.2.3	In-band emissions	294
6.5.2.3.1	Minimum requirements	294
6.5.2.4	EVM equalizer spectrum flatness	295
6.5.2.4.1	Minimum requirements	295
6.5.2A	Transmit modulation quality for CA.....	296
6.5.2A.1	Error Vector Magnitude	297
6.5.2A.2	Carrier leakage for CA	297
6.5.2A.2.1	Minimum requirements	297
6.5.2A.3	In-band emissions	297
6.5.2A.3.1	Minimum requirement for CA.....	297
6.5.2B	Transmit modulation quality for UL-MIMO	300
6.5.2B.1	Error Vector Magnitude	300
6.5.2B.2	Carrier leakage	300
6.5.2B.3	In-band emissions	300
6.5.2B.4	EVM equalizer spectrum flatness for UL-MIMO	300
6.5.2D	Transmit modulation quality for ProSe.....	300
6.5.2D.1	Error Vector Magnitude	300
6.5.2D.2	Carrier leakage	301
6.5.2D.3	In-band emissions	301
6.5.2D.4	EVM equalizer spectrum flatness for ProSe	301
6.5.2E	Transmit modulation quality for category M1 and M2	301
6.5.2E.1	Error Vector Magnitude	301
The Error Vector Magnitude is defined in section 6.5.2.1.		301
6.5.2E.2	Carrier leakage	301
6.5.2E.2.1	Minimum requirements	301
6.5.2E.3	In-band emissions	301
6.5.2E.3.1	Minimum requirements	301
6.5.2F	Transmit modulation quality for Category NB1 and NB2	303
6.5.2F.1	Error Vector Magnitude.....	303
6.5.2F.2	Carrier leakage	303
6.5.2F.3	In-band emissions	303
6.5.2G	Transmit modulation quality for V2X Communication.....	304
6.5.2G.1	Error Vector Magnitude	304
6.5.2G.2	Carrier leakage	305
6.5.2G.3	In-band emissions	305
6.5.2G.4	EVM equalizer spectrum flatness	305
6.6	Output RF spectrum emissions.....	305
6.6.1	Occupied bandwidth	305
6.6.1.1	Additional minimum requirement for E-UTRA (network signalled value "NS_29").....	306
6.6.1A	Occupied bandwidth for CA	306
6.6.1B	Occupied bandwidth for UL-MIMO.....	306
6.6.1F	Occupied bandwidth for category NB1 and NB2	307
6.6.1G	Occupied bandwidth for V2X Communication	307
6.6.2	Out of band emission.....	307
6.6.2.1	Spectrum emission mask.....	307
6.6.2.1.1	Minimum requirement.....	307
6.6.2.1A	Spectrum emission mask for CA.....	308
6.6.2.2	Additional spectrum emission mask	309
6.6.2.2.1	Minimum requirement (network signalled value "NS_03", "NS_11", "NS_20", and "NS_21")..	309
6.6.2.2.2	Minimum requirement (network signalled value "NS_04")	310
6.6.2.2.3	Minimum requirement (network signalled value "NS_06" or "NS_07")	310
6.6.2.2.4	Minimum requirement (network signalled value "NS_33" or "NS_34")	311

6.6.2.2.5	Minimum requirement (network signalled value "NS_27" and "NS_43")	311
6.6.2.2.6	Minimum requirement (network signalled value "NS_28")	312
6.6.2.2.7	Minimum requirement (network signalled value "NS_35")	312
6.6.2.2A	Additional Spectrum Emission Mask for CA	313
6.6.2.2A.1	Minimum requirement (network signalled value "CA_NS_04")	313
6.6.2.2A.2	Minimum requirement CA_66B (network signalled value "CA_NS_09")	313
6.6.2.2A.3	Minimum requirement CA_66C (network signalled value "CA_NS_09")	314
6.6.2.3	Adjacent Channel Leakage Ratio	314
6.6.2.3.1	Minimum requirement E-UTRA	315
6.6.2.3.1a	Additional minimum requirement for E-UTRA (network signalled value "NS_29")	316
6.6.2.3.1A	Void	316
6.6.2.3.1Aa	Void	316
6.6.2.3.2	Minimum requirements UTRA	316
6.6.2.3.2A	Minimum requirement UTRA for CA	317
6.6.2.3.3A	Minimum requirements for CA E-UTRA	319
6.6.2.4	Void	320
6.6.2.4.1	Void	320
6.6.2A	Void	320
6.6.2B	Out of band emission for UL-MIMO	320
6.6.2C	Void	320
6.6.2D	Out of band emission for ProSe	321
6.6.2F	Out of band emission for category NB1 and NB2	321
6.6.2F.1	Spectrum emission mask	321
6.6.2F.2	Additional Spectrum Emission Mask for Category NB1 and NB2	321
6.6.2F.2.1	Minimum requirement (network signalled value "NS_02")	321
6.6.2F.2.2	Minimum requirement (network signalled value "NS_03")	322
6.6.2F.3	Adjacent Channel Leakage Ratio for category NB1 and NB2	322
6.6.2G	Out of band emission for V2X Communication	322
6.6.3	Spurious emissions	323
6.6.3.1	Minimum requirements	323
6.6.3.1A	Minimum requirements for CA	324
6.6.3.2	Spurious emission band UE co-existence	325
6.6.3.2A	Spurious emission band UE co-existence for CA	332
6.6.3.3	Additional spurious emissions	343
6.6.3.3.1	Minimum requirement (network signalled value "NS_05")	343
6.6.3.3.2	Minimum requirement (network signalled value "NS_07")	344
6.6.3.3.3	Minimum requirement (network signalled value "NS_08")	344
6.6.3.3.4	Minimum requirement (network signalled value "NS_09")	344
6.6.3.3.5	Minimum requirement (network signalled value "NS_12")	344
6.6.3.3.6	Minimum requirement (network signalled value "NS_13")	345
6.6.3.3.7	Minimum requirement (network signalled value "NS_14")	345
6.6.3.3.8	Minimum requirement (network signalled value "NS_15")	345
6.6.3.3.9	Minimum requirement (network signalled value "NS_16")	346
6.6.3.3.10	Minimum requirement (network signalled value "NS_17")	346
6.6.3.3.11	Minimum requirement (network signalled value "NS_18")	346
6.6.3.3.12	Minimum requirement (network signalled value "NS_19")	346
6.6.3.3.13	Minimum requirement (network signalled value "NS_11")	347
6.6.3.3.14	Minimum requirement (network signalled value "NS_20")	347
6.6.3.3.15	Minimum requirement (network signalled value "NS_21")	347
6.6.3.3.16	Minimum requirement (network signalled value "NS_22")	348
6.6.3.3.17	Minimum requirement (network signalled value "NS_23")	348
6.6.3.3.18	Void	349
6.6.3.3.19	Minimum requirement (network signalled value "NS_04")	349
6.6.3.3.20	Minimum requirement (network signalled value "NS_24")	349
6.6.3.3.21	Minimum requirement (network signalled value "NS_25")	350
6.6.3.3.22	Minimum requirement (network signalled value "NS_26")	350
6.6.3.3.23	Minimum requirement (network signalled value "NS_27" and "NS_43")	350
6.6.3.3.24	Minimum requirement (network signalled value "NS_28")	350
6.6.3.3.25	Minimum requirement (network signalled value "NS_29")	351
6.6.3.3.26	Minimum requirement (network signalled value "NS_30")	351
6.6.3.3.27	Minimum requirement (network signalled value "NS_31")	352
6.6.3.3.28	Minimum requirement (network signalled value "NS_36")	353

6.6.3.3.29	Minimum requirement (network signalled value "NS_38").....	353
6.6.3.3.30	Minimum requirement (network signalled value "NS_39").....	353
6.6.3.3.31	Minimum requirement (network signalled value "NS_40" and "NS_41")	354
6.6.3.3.32	Minimum requirement (network signalled value "NS_42").....	354
6.6.3.3.33	Minimum requirement (network signalled value "NS_44").....	354
6.6.3.3A	Additional spurious emissions for CA	354
6.6.3.3A.1	Minimum requirement for CA_1C (network signalled value "CA_NS_01").....	355
6.6.3.3A.2	Minimum requirement for CA_1C (network signalled value "CA_NS_02").....	355
6.6.3.3A.3	Minimum requirement for CA_1C (network signalled value "CA_NS_03").....	355
6.6.3.3A.4	Minimum requirement for CA_38C (network signalled value "CA_NS_05").....	355
6.6.3.3A.5	Minimum requirement for CA_7C (network signalled value "CA_NS_06").....	356
6.6.3.3A.6	Minimum requirement for CA_39C and CA_39C-41A (network signalled value "CA_NS_07").....	356
6.6.3.3A.7	Minimum requirement for CA_42C (network signalled value "CA_NS_08").....	356
6.6.3.3A.8	Minimum requirement for CA_41C (network signalled value "CA_NS_04").....	357
6.6.3.3A.9	Void.....	357
6.6.3A	Void.....	357
6.6.3B	Spurious emission for UL-MIMO	357
6.6.3C	Void.....	357
6.6.3D	Spurious emission for ProSe.....	357
6.6.3F	Spurious emission for category NB1 and NB2.....	358
6.6.3G	Spurious emission for V2X Communication	358
6.6A	Void.....	361
6.6B	Void.....	361
6.7	Transmit intermodulation	361
6.7.1	Minimum requirement	361
6.7.1A	Minimum requirement for CA.....	362
6.7.1B	Minimum requirement for UL-MIMO.....	362
6.7.1F	Minimum requirement for category NB1 and NB2.....	362
6.7.1G	Minimum requirement for V2X Communication	363
6.8	Void.....	363
6.8A	Void.....	363
6.8B	Time alignment error for UL-MIMO	363
6.8B.1	Minimum Requirements	363
6.8C	Void.....	364
6.8D	Void.....	364
6.8E	Void.....	364
6.8F	Void.....	364
6.8G	Time alignment error.....	364
7	Receiver characteristics.....	364
7.1	General	364
7.2	Diversity characteristics	365
7.3	Reference sensitivity power level.....	365
7.3.1	Minimum requirements (QPSK).....	365
7.3.1A	Minimum requirements (QPSK) for CA.....	394
7.3.1B	Minimum requirements (QPSK) for UL-MIMO	464
7.3.1D	Minimum requirements (QPSK) for ProSe.....	464
7.3.1E	Minimum requirements (QPSK) for UE category 0, M1, M2 and 1bis.....	466
7.3.1F	Minimum requirements for UE category NB1 and NB2	474
7.3.1F.1	Reference sensitivity for UE category NB1 and NB2.....	474
7.3.1F.2	Void.....	475
7.3.1G	Minimum requirements (QPSK) for V2X	475
7.3.2	Void	477
7.4	Maximum input level	477
7.4.1	Minimum requirements.....	478
7.4.1A	Minimum requirements for CA	478
7.4.1B	Minimum requirements for UL-MIMO	479
7.4.1D	Minimum requirements for ProSe	479
7.4.1F	Minimum requirements for category NB1 and NB2.....	480
7.4.1G	Minimum requirements for V2X	480
7.4A	Void.....	481

7.4A.1	Void	481
7.5	Adjacent Channel Selectivity (ACS)	481
7.5.1	Minimum requirements	481
7.5.1A	Minimum requirements for CA	482
7.5.1B	Minimum requirements for UL-MIMO	486
7.5.1D	Minimum requirements for ProSe	486
7.5.1F	Minimum requirements for category NB1 and NB2	487
7.5.1G	Minimum requirements for V2X	488
7.6	Blocking characteristics	490
7.6.1	In-band blocking	490
7.6.1.1	Minimum requirements	490
7.6.1.1A	Minimum requirements for CA	492
7.6.1.1D	Minimum requirements for ProSe	495
7.6.1.1F	Minimum requirements for category NB1 and NB2	496
7.6.1.1G	Minimum requirements for V2X	496
7.6.2	Out-of-band blocking	498
7.6.2.1	Minimum requirements	498
7.6.2.1A	Minimum requirements for CA	499
7.6.2.1D	Minimum requirements for ProSe	503
7.6.2.1F	Minimum requirements for category NB1 and NB2	503
7.6.2.1G	Minimum requirements for V2X	504
7.6.3	Narrow band blocking	505
7.6.3.1	Minimum requirements	505
7.6.3.1A	Minimum requirements for CA	506
7.6.3.1D	Minimum requirements for ProSe	507
7.6A	Void	508
7.6B	Blocking characteristics for UL-MIMO	508
7.7	Spurious response	508
7.7.1	Minimum requirements	508
7.7.1A	Minimum requirements for CA	509
7.7.1B	Minimum requirements for UL-MIMO	510
7.7.1D	Minimum requirements for ProSe	510
7.7.1F	Minimum requirements for UE category NB1 and NB2	511
7.7.1G	Minimum requirements for V2X	511
7.8	Intermodulation characteristics	512
7.8.1	Wide band intermodulation	512
7.8.1.1	Minimum requirements	512
7.8.1A	Minimum requirements for CA	513
7.8.1B	Minimum requirements for UL-MIMO	516
7.8.1D	Minimum requirements for ProSe	516
7.8.1F	Minimum requirements for category NB1 and NB2	517
7.8.1G	Minimum requirements	517
7.8.2	Void	518
7.9	Spurious emissions	518
7.9.1	Minimum requirements	519
7.9.1A	Minimum requirements	519
7.10	Receiver image	520
7.10.1	Void	520
7.10.1A	Minimum requirements for CA	520
7.10.1G	Minimum requirements for V2X Communication	520
8	Performance requirement	521
8.1	General	521
8.1.1	Receiver antenna capability	521
8.1.1.1	Simultaneous unicast and MBMS operations	522
8.1.1.2	Dual-antenna receiver capability in idle mode	522
8.1.2	Applicability of requirements	522
8.1.2.1	Applicability of requirements for different channel bandwidths	522
8.1.2.2	Definition of CA capability	522
8.1.2.2A	Definition of dual connectivity capability	527
8.1.2.3	Applicability and test rules for different CA configurations and bandwidth combination sets	528

8.1.2.3A	Applicability and test rules for different dual connectivity configuration and bandwidth combination set	530
8.1.2.3B	Applicability and test rules for different TDD-FDD CA configurations and bandwidth combination sets	531
8.1.2.3C	Applicability and test rules for SDR tests for 4Rx capable UEs	533
8.1.2.3D	Applicability and test rules for different CA with LAA SCell(s) configurations and bandwidth combination sets	533
8.1.2.3E	Applicability and test rules for SDR tests for 8Rx capable UEs	534
8.1.2.4	Test coverage for different number of component carriers	535
8.1.2.5	Applicability of performance requirements for Type B receiver	536
8.1.2.6	Applicability of performance requirements for 4Rx capable UEs	536
8.1.2.6.1	Applicability rule and antenna connection for single carrier tests with 2Rx	536
8.1.2.6.2	Applicability rule and antenna connection for CA and DC tests with 2Rx	538
8.1.2.6.3	Applicability rule and antenna connection for single carrier tests with 4Rx	538
8.1.2.6.4	Applicability rule for 256QAM tests	539
8.1.2.6.5	Applicability rule and antenna connection for CA and DC tests with 4Rx	539
8.1.2.6.6	Applicability rule for Type C with 4Rx	542
8.1.2.6.7	Applicability rule for 1024QAM tests	542
8.1.2.7	Applicability of Enhanced Downlink Control Channel Performance Requirements	542
8.1.2.8	Applicability of performance requirements for CDM-multiplexed DM RS with interfering simultaneous transmission (FRC) with multiple CSI-RS configurations	544
8.1.2.8A	Applicability of performance requirements for UE supporting coverage enhancement	544
8.1.2.9	Applicability of SDR requirements for CA and LAA	545
8.1.2.10	Applicability of performance requirements for Multi-user Superposed Transmission	546
8.1.2.11	Applicability CRS interference mitigation receivers performance requirements	546
8.1.2.12	Applicability of performance requirements for 8Rx capable UEs	547
8.1.2.12.1	Applicability rule and antenna connection for single carrier PDSCH tests	547
8.1.2.12.2	Applicability rule and antenna connection for control channel tests	553
8.1.2.12.3	Applicability rule and antenna connection for CA and DC tests	553
8.1.3	UE category and UE DL category	554
8.2	Demodulation of PDSCH (Cell-Specific Reference Symbols)	554
8.2.1	FDD (Fixed Reference Channel)	554
8.2.1.1	Single-antenna port performance	555
8.2.1.1.1	Minimum Requirement	555
8.2.1.1.2	Void	560
8.2.1.1.3	Void	560
8.2.1.1.4	Minimum Requirement 1 PRB allocation in presence of MBSFN	560
8.2.1.1.4A	Minimum Requirement 1 PRB allocation in presence of FeMBMS Unicast-mixed Cell under CA	561
8.2.1.2	Transmit diversity performance	562
8.2.1.2.1	Minimum Requirement 2 Tx Antenna Port	562
8.2.1.2.2	Minimum Requirement 4 Tx Antenna Port	562
8.2.1.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	563
8.2.1.2.3A	Minimum Requirement 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	565
8.2.1.2.4	Enhanced Performance Requirement Type A - 2 Tx Antenna Ports with TM3 interference model	567
8.2.1.2.5	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM2 interference model	569
8.2.1.2.6	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM9 interference model	570
8.2.1.2.7	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	571
8.2.1.3	Open-loop spatial multiplexing performance	571
8.2.1.3.1	Minimum Requirement 2 Tx Antenna Port	571
8.2.1.3.1A	Soft buffer management test	575
8.2.1.3.1B	Enhanced Performance Requirement Type C - 2Tx Antenna Ports	576
8.2.1.3.1C	Enhanced Performance Requirement Type C - 2 Tx Antenna Ports with TM1 interference	577
8.2.1.3.2	Minimum Requirement 4 Tx Antenna Port	578
8.2.1.3.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	578

8.2.1.3.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	582
8.2.1.3.5	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	584
8.2.1.3.6	Minimum Requirement 2 Tx Antenna Port (network-based CRS interference mitigation).....	585
8.2.1.4	Closed-loop spatial multiplexing performance	586
8.2.1.4.1	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Port	586
8.2.1.4.1A	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Port	587
8.2.1.4.1B	Enhanced Performance Requirement Type A - Single-Layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	587
8.2.1.4.1C	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured).....	589
8.2.1.4.1D	Enhanced Performance Requirement Type B - Single-layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	591
8.2.1.4.1E	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports with CRS assistance information	593
8.2.1.4.1F	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Ports with CRS assistance information	594
8.2.1.4.2	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	595
8.2.1.4.2A	Enhanced Performance Requirement Type C – Multi-layer Spatial Multiplexing 2Tx Antenna Ports.....	596
8.2.1.4.3	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port	596
8.2.1.4.3A	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port for dual connectivity	600
8.2.1.4.4	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port (Superposed transmission)	602
8.2.1.5	MU-MIMO.....	603
8.2.1.6	[Control channel performance: D-BCH and PCH]	603
8.2.1.7	Carrier aggregation with power imbalance	603
8.2.1.7.1	Minimum Requirement	603
8.2.1.8	Intra-band non-contiguous carrier aggregation with timing offset.....	604
8.2.1.8.1	Minimum Requirement	604
8.2.1.9	HST-SFN performance	605
8.2.1.9.1	Minimum Requirement	605
8.2.2	TDD (Fixed Reference Channel)	606
8.2.2.1	Single-antenna port performance	606
8.2.2.1.1	Minimum Requirement	606
8.2.2.1.2	Void	611
8.2.2.1.3	Void	611
8.2.2.1.4	Minimum Requirement 1 PRB allocation in presence of MBSFN.....	611
8.2.2.2	Transmit diversity performance	611
8.2.2.2.1	Minimum Requirement 2 Tx Antenna Port	611
8.2.2.2.2	Minimum Requirement 4 Tx Antenna Port	612
8.2.2.2.3	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS)	613
8.2.2.2.3A	Minimum Requirement 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	614
8.2.2.2.4	Enhanced Performance Requirement Type A – 2 Tx Antenna Ports with TM3 interference model	616
8.2.2.2.5	Minimum Requirement 2 Tx Antenna Port (when <i>EIMTA-MainConfigServCell-r12</i> is configured)	618
8.2.2.2.6	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM2 interference model	618
8.2.2.2.7	Enhanced Performance Requirement Type B - 2 Tx Antenna Ports with TM9 interference model	620
8.2.2.2.8	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	621
8.2.2.3	Open-loop spatial multiplexing performance.....	622
8.2.2.3.1	Minimum Requirement 2 Tx Antenna Port	622
8.2.2.3.1A	Soft buffer management test.....	625
8.2.2.3.1B	Enhanced Performance Requirement Type C - 2Tx Antenna Ports	625
8.2.2.3.1C	Enhanced Performance Requirement Type C - 2 Tx Antenna Ports with TM1 interference	626
8.2.2.3.2	Minimum Requirement 4 Tx Antenna Port	627

8.2.2.3.3	Minimum Requirement 2Tx antenna port (demodulation subframe overlaps with aggressor cell ABS)	628
8.2.2.3.4	Minimum Requirement 2 Tx Antenna Port (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	632
8.2.2.3.5	Minimum Requirement 2 Tx Antenna Port (Superposed transmission)	634
8.2.2.3.6	Minimum Requirement 2 Tx Antenna Port (network-based CRS interference mitigation)	635
8.2.2.4	Closed-loop spatial multiplexing performance	636
8.2.2.4.1	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Port	636
8.2.2.4.1A	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Port	637
8.2.2.4.1B	Enhanced Performance Requirement Type A – Single-Layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	637
8.2.2.4.1C	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	639
8.2.2.4.1D	Enhanced Performance Requirement Type B - Single-layer Spatial Multiplexing 2 Tx Antenna Port with TM4 interference model	641
8.2.2.4.1E	Minimum Requirement Single-Layer Spatial Multiplexing 2 Tx Antenna Ports with CRS assistance information	643
8.2.2.4.1F	Minimum Requirement Single-Layer Spatial Multiplexing 4 Tx Antenna Ports with CRS assistance information	644
8.2.2.4.2	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	646
8.2.2.4.2A	Enhanced Performance Requirement Type C Multi-Layer Spatial Multiplexing 2 Tx Antenna Port	646
8.2.2.4.3	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port	647
8.2.2.4.3A	Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port for dual connectivity	651
8.2.2.4.4	Void	652
8.2.2.4.5	Minimum Requirement Multi-Layer Spatial Multiplexing 2 Tx Antenna Port (Superposed transmission)	652
8.2.2.5	MU-MIMO	653
8.2.2.6	[Control channel performance: D-BCH and PCH]	653
8.2.2.7	Carrier aggregation with power imbalance	653
8.2.2.7.1	Minimum Requirement	653
8.2.2.8	Intra-band contiguous carrier aggregation with minimum channel spacing	654
8.2.2.8.1	Minimum Requirement	654
8.2.2.9	HST-SFN performance	655
8.2.2.9.1	Minimum Requirement	655
8.2.3	TDD FDD CA (Fixed Reference Channel)	656
8.2.3.1	Single-antenna port performance	657
8.2.3.1.1	Minimum Requirement for FDD PCell	657
8.2.3.1.2	Minimum Requirement for TDD PCell	661
8.2.3.2	Open-loop spatial multiplexing performance 2Tx Antenna port	665
8.2.3.2.1	Minimum Requirement for FDD PCell	665
8.2.3.2.1A	Soft buffer management test for FDD PCell	668
8.2.3.2.2	Minimum Requirement for TDD PCell	669
8.2.3.2.2A	Soft buffer management test for TDD PCell	673
8.2.3.3	Closed-loop spatial multiplexing performance 4Tx Antenna Port	674
8.2.3.3.1	Minimum Requirement for FDD PCell	674
8.2.3.3.2	Minimum Requirement for TDD PCell	678
8.2.3.4	Minimum Requirement for Closed-loop spatial multiplexing performance 4Tx Antenna Port for dual connectivity	682
8.2.4	LAA	683
8.2.4.1	Closed-loop spatial multiplexing performance 4Tx Antenna Port	683
8.2.4.1.1	FDD PCell (FDD single carrier)	683
8.2.4.1.2	TDD PCell (TDD single carrier)	687
8.3	Demodulation of PDSCH (User-Specific Reference Symbols)	691
8.3.1	FDD	691
8.3.1.1	Single-layer Spatial Multiplexing	692
8.3.1.1A	Enhanced Performance Requirement Type A – Single-layer Spatial Multiplexing with TM9 interference model	694
8.3.1.1B	Single-layer Spatial Multiplexing (demodulation subframe overlaps with aggressor cell ABS and CRS assistance information are configured)	696