

# ETSI TS 138 141-1 V15.4.0 (2020-01)



**5G;  
NR;**

**Base Station (BS) conformance testing Part 1: Conducted  
conformance testing  
(3GPP TS 38.141-1 version 15.4.0 Release 15)**



---

**Reference**RTS/TSGR-0438141-1v140

---

**Keywords**5G

---

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

---

The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

---

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.

All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

**GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

---

# Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

---

# Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

Intellectual Property Rights .....	2
Legal Notice .....	2
Modal verbs terminology.....	2
Foreword.....	12
1 Scope .....	13
2 References .....	13
3 Definitions, symbols and abbreviations .....	15
3.1 Definitions .....	15
3.2 Symbols.....	17
3.3 Abbreviations .....	18
4 General conducted test conditions and declarations.....	20
4.1 Measurement uncertainties and test requirements .....	20
4.1.1 General.....	20
4.1.2 Acceptable uncertainty of Test System.....	20
4.1.2.1 General .....	20
4.1.2.2 Measurement of transmitter .....	21
4.1.2.3 Measurement of receiver .....	22
4.1.2.4 Measurement of performance requirements.....	25
4.1.3 Interpretation of measurement results .....	25
4.2 Conducted requirement reference points .....	25
4.2.1 <i>BS type I-C</i> .....	25
4.2.2 <i>BS type I-H</i> .....	26
4.3 Base station classes .....	27
4.4 Regional requirements.....	27
4.5 BS configurations .....	28
4.5.1 <i>BS type I-C</i> .....	28
4.5.1.1 Transmit configurations .....	28
4.5.1.1.1 General .....	28
4.5.1.1.2 Transmission with multiple transmitter antenna connectors.....	28
4.5.1.2 Receive configurations.....	29
4.5.1.2.1 General .....	29
4.5.1.2.2 Reception with multiple receiver antenna connectors, receiver diversity.....	29
4.5.1.3 Duplexers .....	29
4.5.1.4 Power supply options .....	30
4.5.1.5 Ancillary RF amplifiers.....	30
4.5.2 <i>BS type I-H</i> .....	31
4.5.2.1 Transmit configurations .....	31
4.5.2.2 Receive configurations.....	31
4.5.2.3 Power supply options .....	32
4.5.3 BS with integrated Iuant BS modem .....	32
4.6 Manufacturer declarations .....	32
4.7 Test configurations .....	36
4.7.1 General.....	36
4.7.2 Test signal used to build Test Configurations.....	36
4.7.3 NRTC1: Contiguous spectrum operation.....	36
4.7.3.1 NRTC1 generation .....	36
4.7.3.2 NRTC1 power allocation .....	36
4.7.4 NRTC2: Contiguous CA occupied bandwidth.....	36
4.7.4.1 NRTC2 generation .....	37
4.7.4.2 NRTC2 power allocation .....	37
4.7.5 NRTC3: Non-contiguous spectrum operation .....	37
4.7.5.1 NRTC3 generation .....	37
4.7.5.2 NRTC3 power allocation .....	38
4.7.6 NRTC4: Multi-band test configuration for full carrier allocation.....	38

4.7.6.1	NRTC4 generation .....	38
4.7.6.2	NRTC4 power allocation .....	38
4.7.7	NRTC5: Multi-band test configuration with high PSD per carrier .....	38
4.7.7.1	NRTC5 generation .....	39
4.7.7.2	NRTC5 power allocation .....	39
4.8	Applicability of requirements .....	39
4.8.1	General .....	39
4.8.2	Requirement set applicability .....	39
4.8.3	Applicability of test configurations for single-band operation .....	40
4.8.4	Applicability of test configurations for multi-band operation .....	41
4.9	RF channels and test models .....	42
4.9.1	RF channels .....	42
4.9.2	Test models .....	43
4.9.2.1	General .....	43
4.9.2.2	FR1 test models .....	43
4.9.2.2.1	FR1 test model 1.1 (NR-FR1-TM1.1) .....	45
4.9.2.2.2	FR1 test model 1.2 (NR-FR1-TM1.2) .....	45
4.9.2.2.3	FR1 test model 2 (NR-FR1-TM2) .....	46
4.9.2.2.4	FR1 test model 2a (NR-FR1-TM2a) .....	46
4.9.2.2.5	FR1 test model 3.1 (NR-FR1-TM3.1) .....	47
4.9.2.2.6	FR1 test model 3.1a (NR-FR1-TM3.1a) .....	47
4.9.2.2.7	FR1 test model 3.2 (NR-FR1-TM3.2) .....	47
4.9.2.2.8	FR1 test model 3.3 (NR-FR1-TM3.3) .....	48
4.9.2.3	Data content of Physical channels and Signals for NR-FR1-TM .....	49
4.9.2.3.1	PDCCH .....	49
4.9.2.3.2	PDSCH .....	49
4.10	Requirements for contiguous and non-contiguous spectrum .....	50
4.11	Requirements for BS capable of multi-band operation .....	51
4.12	Format and interpretation of tests .....	52
5	Operating bands and channel arrangement .....	53
6	Conducted transmitter characteristics .....	54
6.1	General .....	54
6.1.1	BS type 1-C .....	54
6.1.2	BS type 1-H .....	54
6.2	Base station output power .....	54
6.2.1	Definition and applicability .....	54
6.2.2	Minimum requirement .....	55
6.2.3	Test purpose .....	55
6.2.4	Method of test .....	55
6.2.4.1	Initial conditions .....	55
6.2.4.2	Procedure .....	55
6.2.5	Test requirement .....	56
6.3	Output power dynamics .....	56
6.3.1	General .....	56
6.3.2	RE power control dynamic range .....	56
6.3.2.1	Definition and applicability .....	56
6.3.2.2	Minimum requirement .....	56
6.3.2.3	Test purpose .....	56
6.3.3	Total power dynamic range .....	57
6.3.3.1	Definition and applicability .....	57
6.3.3.2	Minimum requirement .....	57
6.3.3.3	Test purpose .....	57
6.3.3.4	Method of test .....	57
6.3.3.4.1	Initial conditions .....	57
6.3.3.4.2	Procedure .....	57
6.3.3.5	Test requirements .....	58
6.4	Transmit ON/OFF power .....	58
6.4.1	Transmitter OFF power .....	58
6.4.1.1	Definition and applicability .....	58
6.4.1.2	Minimum requirement .....	58

6.4.1.3	Test purpose .....	59
6.4.1.4	Method of test .....	59
6.4.1.5	Test requirements .....	59
6.4.2	Transmitter transient period .....	59
6.4.2.1	Definition and applicability .....	59
6.4.2.2	Minimum requirement .....	59
6.4.2.3	Test purpose .....	59
6.4.2.4	Method of test .....	60
6.4.2.4.1	Initial conditions .....	60
6.4.2.4.2	Procedure .....	60
6.4.2.5	Test requirements .....	60
6.5	Transmitted signal quality .....	61
6.5.1	General .....	61
6.5.2	Frequency error .....	61
6.5.2.1	Definition and applicability .....	61
6.5.2.2	Minimum Requirement .....	61
6.5.2.3	Test purpose .....	61
6.5.2.4	Method of test .....	61
6.5.2.5	Test Requirements .....	61
6.5.3	Modulation quality .....	61
6.5.3.1	Definition and applicability .....	61
6.5.3.2	Minimum Requirement .....	62
6.5.3.3	Test purpose .....	62
6.5.3.4	Method of test .....	62
6.5.3.4.1	Initial conditions .....	62
6.5.3.4.2	Procedure .....	62
6.5.3.5	Test requirements .....	63
6.5.4	Time alignment error .....	64
6.5.4.1	Definition and applicability .....	64
6.5.4.2	Minimum requirement .....	64
6.5.4.3	Test purpose .....	65
6.5.4.4	Method of test .....	65
6.5.4.4.1	Initial conditions .....	65
6.5.4.4.2	Procedure .....	65
6.5.4.5	Test requirement .....	66
6.6	Unwanted emissions .....	66
6.6.1	General .....	66
6.6.2	Occupied bandwidth .....	66
6.6.2.1	Definition and applicability .....	66
6.6.2.2	Minimum Requirements .....	67
6.6.2.3	Test purpose .....	67
6.6.2.4	Method of test .....	67
6.6.2.4.1	Initial conditions .....	67
6.6.2.4.2	Procedure .....	67
6.6.2.5	Test requirements .....	68
6.6.3	Adjacent Channel Leakage Power Ratio (ACLR) .....	68
6.6.3.1	Definition and applicability .....	68
6.6.3.2	Minimum requirement .....	68
6.6.3.3	Test purpose .....	69
6.6.3.4	Method of test .....	69
6.6.3.4.1	Initial conditions .....	69
6.6.3.4.2	Procedure .....	69
6.6.3.5	Test requirements .....	70
6.6.3.5.1	General requirements .....	70
6.6.3.5.2	Limits and <i>basic limits</i> .....	70
6.6.3.5.3	<i>BS type 1-C</i> .....	72
6.6.3.5.4	<i>BS type 1-H</i> .....	73
6.6.4	Operating band unwanted emissions .....	73
6.6.4.1	Definition and applicability .....	73
6.6.4.2	Minimum requirement .....	74
6.6.4.3	Test purpose .....	75
6.6.4.4	Method of test .....	75

6.6.4.4.1	Initial conditions .....	75
6.6.4.4.2	Procedure .....	75
6.6.4.5	Test requirements .....	76
6.6.4.5.1	General requirements .....	76
6.6.4.5.2	Basic limits for Wide Area BS (Category A) .....	76
6.6.4.5.3	Basic limits for Wide Area BS (Category B) .....	77
6.6.4.5.3.1	Category B requirements (Option 1) .....	77
6.6.4.5.3.2	Category B requirements (Option 2) .....	78
6.6.4.5.4	Basic limits for Medium Range BS (Category A and B) .....	79
6.6.4.5.5	Basic limits for Local Area BS (Category A and B) .....	81
6.6.4.5.6	Basic limits for additional requirements .....	82
6.6.4.5.6.1	Limits in FCC Title 47 .....	82
6.6.4.5.6.2	Protection of DTT .....	82
6.6.4.5.6.3	(void) .....	82
6.6.4.5.7	<i>BS type 1-C</i> .....	82
6.6.4.5.8	<i>BS type 1-H</i> .....	82
6.6.5	Transmitter spurious emissions .....	83
6.6.5.1	Definition and applicability .....	83
6.6.5.2	Minimum requirement .....	83
6.6.5.3	Test purpose .....	83
6.6.5.4	Method of test .....	83
6.6.5.4.1	Initial conditions .....	83
6.6.5.4.2	Procedure .....	84
6.6.5.5	Test requirements .....	85
6.6.5.5.1	Basic limits .....	85
6.6.5.5.1.1	Tx spurious emissions .....	85
6.6.5.5.1.2	Protection of the BS receiver of own or different BS .....	85
6.6.5.5.1.3	Additional spurious emissions requirements .....	86
6.6.5.5.1.4	Co-location with other base stations .....	93
6.6.5.5.2	(void) .....	98
6.6.5.5.3	<i>BS type 1-C</i> .....	98
6.6.5.5.4	<i>BS type 1-H</i> .....	98
6.7	Transmitter intermodulation .....	98
6.7.1	Definition and applicability .....	98
6.7.2	Minimum requirement .....	98
6.7.3	Test purpose .....	99
6.7.4	Method of test .....	99
6.7.4.1	Initial conditions .....	99
6.7.4.2	Procedure .....	99
6.7.5	Test requirements .....	100
6.7.5.1	<i>BS type 1-C</i> .....	100
6.7.5.1.1	Co-location minimum requirements .....	100
6.7.5.1.2	Additional requirements .....	101
6.7.5.2	<i>BS type 1-H</i> .....	101
6.7.5.2.1	Co-location minimum requirements .....	101
6.7.5.2.2	Intra-system minimum requirements .....	102
6.7.5.2.3	Additional requirements .....	102
7	Conducted receiver characteristics .....	103
7.1	General .....	103
7.2	Reference sensitivity level .....	103
7.2.1	Definition and applicability .....	103
7.2.2	Minimum requirement .....	103
7.2.3	Test purpose .....	103
7.2.4	Method of test .....	104
7.2.4.1	Initial conditions .....	104
7.2.4.2	Procedure .....	104
7.2.5	Test requirements .....	104
7.3	Dynamic range .....	106
7.3.1	Definition and applicability .....	106
7.3.2	Minimum requirement .....	106
7.3.3	Test purpose .....	106

7.3.4	Method of test .....	106
7.3.4.1	Initial conditions .....	106
7.3.4.2	Procedure .....	106
7.3.5	Test requirements.....	107
7.4	In-band selectivity and blocking .....	110
7.4.1	Adjacent Channel Selectivity (ACS) .....	110
7.4.1.1	Definition and applicability.....	110
7.4.1.2	Minimum requirement .....	110
7.4.1.3	Test purpose .....	111
7.4.1.4	Method of test .....	111
7.4.1.4.1	Initial conditions.....	111
7.4.1.4.2	Procedure.....	111
7.4.1.5	Test requirements.....	111
7.4.2	In-band blocking.....	112
7.4.2.1	Definition and applicability.....	112
7.4.2.2	Minimum requirement .....	112
7.4.2.3	Test purpose .....	113
7.4.2.4	Method of test .....	113
7.4.2.4.1	Initial conditions.....	113
7.4.2.4.2	Procedure for general blocking.....	113
7.4.2.4.3	Procedure for narrowband blocking .....	113
7.4.2.5	Test requirements.....	114
7.5	Out-of-band blocking .....	116
7.5.1	Definition and applicability .....	116
7.5.2	Minimum requirement .....	116
7.5.3	Test purpose.....	116
7.5.4	Method of test .....	117
7.5.4.1	Initial conditions .....	117
7.5.4.2	Procedure .....	117
7.5.5	Test requirements.....	117
7.5.5.1	General requirements .....	117
7.5.5.2	Co-location requirements .....	118
7.6	Receiver spurious emissions.....	119
7.6.1	Definition and applicability .....	119
7.6.2	Minimum requirement .....	119
7.6.3	Test purpose.....	119
7.6.4	Method of test .....	119
7.6.4.1	Initial conditions .....	119
7.6.4.2	Procedure .....	119
7.6.5	Test requirements.....	120
7.6.5.1	Basic limits.....	120
7.6.5.2	BS type 1-C.....	120
7.6.5.3	BS type 1-H.....	121
7.7	Receiver intermodulation .....	121
7.7.1	Definition and applicability .....	121
7.7.2	Minimum requirement .....	121
7.7.3	Test purpose.....	121
7.7.4	Method of test .....	121
7.7.4.1	Initial conditions .....	121
7.7.4.2	Procedure .....	122
7.7.5	Test requirements.....	122
7.8	In-channel selectivity .....	126
7.8.1	Definition and applicability .....	126
7.8.2	Minimum requirement .....	126
7.8.3	Test purpose.....	126
7.8.4	Method of test .....	126
7.8.4.1	Initial conditions .....	126
7.8.4.2	Procedure .....	126
7.8.5	Test requirements.....	126
8	Conducted performance characteristics.....	130
8.1	General .....	130



8.1.1	Scope and definitions.....	130
8.1.2	Applicability rule .....	130
8.1.2.0	General .....	130
8.1.2.1	Applicability of PUSCH performance requirements.....	130
8.1.2.1.1	Applicability of requirements for different subcarrier spacings .....	130
8.1.2.1.2	Applicability of requirements for different channel bandwidths .....	130
8.1.2.1.3	Applicability of requirements for different configurations.....	131
8.1.2.2	Applicability of PUCCH performance requirements .....	131
8.1.2.2.1	Applicability of requirements for different formats.....	131
8.1.2.2.2	Applicability of requirements for different subcarrier spacings .....	131
8.1.2.2.3	Applicability of requirements for different channel bandwidths .....	131
8.1.2.2.4	Applicability of requirements for different configurations.....	131
8.1.2.2.5	Applicability of requirements for multi-slot PUCCH.....	132
8.1.2.3	Applicability of PRACH performance requirements .....	132
8.1.2.3.1	Applicability of requirements for different formats.....	132
8.1.2.3.2	Applicability of requirements for different subcarrier spacings .....	132
8.1.2.3.3	Applicability of requirements for different channel bandwidths .....	132
8.2	Performance requirements for PUSCH .....	132
8.2.1	Performance requirements for PUSCH with transform precoding disabled .....	132
8.2.1.1	Definition and applicability.....	132
8.2.1.2	Minimum Requirement .....	132
8.2.1.3	Test Purpose .....	132
8.2.1.4	Method of test .....	132
8.2.1.4.1	Initial Conditions .....	132
8.2.1.4.2	Procedure.....	133
8.2.1.5	Test Requirement .....	133
8.2.2	Performance requirements for PUSCH with transform precoding enabled .....	140
8.2.2.1	Definition and applicability.....	140
8.2.2.2	Minimum Requirement .....	140
8.2.2.3	Test Purpose .....	141
8.2.2.4	Method of test .....	141
8.2.2.4.1	Initial Conditions .....	141
8.2.2.4.2	Procedure.....	141
8.2.2.5	Test Requirement .....	142
8.2.3	Performance requirements for UCI multiplexed on PUSCH .....	143
8.2.3.1	Definition and applicability.....	143
8.2.3.2	Minimum Requirements.....	143
8.2.3.3	Test purpose .....	143
8.2.3.4	Method of test .....	143
8.2.3.4.1	Initial conditions .....	143
8.2.3.4.2	Procedure.....	144
8.2.3.5	Test Requirement .....	145
8.3	Performance requirements for PUCCH.....	146
8.3.1	Performance requirements for PUCCH format 0.....	146
8.3.1.1	Definition and applicability.....	146
8.3.1.2	Minimum Requirement .....	146
8.3.1.3	Test purpose .....	146
8.3.1.4	Method of test .....	146
8.3.1.4.1	Initial conditions .....	146
8.3.1.4.2	Procedure.....	147
8.3.1.5	Test Requirement .....	147
8.3.2	Performance requirements for PUCCH format 1 .....	148
8.3.2.1	NACK to ACK detection .....	148
8.3.2.1.1	Definition and applicability .....	148
8.3.2.1.2	Minimum Requirement .....	148
8.3.2.1.3	Test purpose .....	148
8.3.2.1.4	Method of test.....	149
8.3.2.1.4.1	Initial Conditions .....	149
8.3.2.1.4.2	Procedure .....	149
8.3.2.1.5	Test Requirement.....	149
8.3.2.2	ACK missed detection.....	150
8.3.2.2.1	Definition and applicability .....	150

8.3.2.2.2	Minimum Requirement .....	150
8.3.2.2.3	Test purpose .....	150
8.3.2.2.4	Method of test.....	151
8.3.2.2.4.1	Initial Conditions .....	151
8.3.2.2.4.2	Procedure .....	151
8.3.2.2.5	Test Requirement.....	152
8.3.3	Performance requirements for PUCCH format 2.....	152
8.3.3.1	ACK missed detection.....	152
8.3.3.1.1	Definition and applicability .....	152
8.3.3.1.2	Minimum requirements .....	152
8.3.3.1.3	Test purpose .....	153
8.3.3.1.4	Method of test.....	153
8.3.3.1.4.1	Initial Condition .....	153
8.3.3.1.4.2	Procedure .....	153
8.3.3.1.5	Test requirements .....	154
8.3.3.2	UCI BLER performance requirements.....	154
8.3.3.2.1	Definition and applicability .....	154
8.3.3.2.2	Minimum Requirement .....	154
8.3.3.2.3	Test purpose .....	154
8.3.3.2.4	Method of test.....	154
8.3.3.2.4.1	Initial Condition .....	154
8.3.3.2.4.2	Procedure .....	154
8.3.3.2.5	Test requirements .....	155
8.3.4	Performance requirements for PUCCH format 3.....	156
8.3.4.1	Definition and applicability.....	156
8.3.4.2	Minimum requirement .....	156
8.3.4.3	Test purpose .....	156
8.3.4.4	Method of test .....	156
8.3.4.4.1	Initial conditions.....	156
8.3.4.4.2	Procedure.....	156
8.3.4.5	Test requirement .....	157
8.3.5	Performance requirements for PUCCH format 4.....	159
8.3.5.1	Definition and applicability.....	159
8.3.5.2	Minimum requirement .....	159
8.3.5.3	Test purpose .....	159
8.3.5.4	Method of test .....	159
8.3.5.4.1	Initial conditions.....	159
8.3.5.4.2	Procedure.....	159
8.3.5.5	Test requirement .....	160
8.3.6	Performance requirements for multi-slot PUCCH.....	161
8.3.6.1	Performance requirements for multi-slot PUCCH format 1.....	161
8.3.6.1.1	NACK to ACK detection.....	161
8.3.6.1.1.1	Definition and applicability .....	161
8.3.6.1.1.2	Minimum Requirement.....	161
8.3.6.1.1.3	Test purpose.....	161
8.3.6.1.1.4	Method of test .....	161
8.3.6.1.1.4.1	Initial conditions.....	161
8.3.6.1.1.4.2	Procedure.....	161
8.3.6.1.1.5	Test Requirement .....	162
8.3.6.1.2	ACK missed detection.....	163
8.3.6.1.2.1	Definition and applicability .....	163
8.3.6.1.2.2	Minimum Requirement.....	163
8.3.6.1.2.3	Test purpose.....	163
8.3.6.1.2.4	Method of test .....	163
8.3.6.1.2.4.1	Initial conditions.....	163
8.3.6.1.2.4.2	Procedure.....	163
8.3.6.1.2.5	Test Requirement .....	164
8.4	Performance requirements for PRACH.....	164
8.4.1	PRACH false alarm probability and missed detection.....	164
8.4.1.1	Definition and applicability.....	164
8.4.1.2	Minimum requirement .....	165
8.4.1.3	Test purpose .....	165

8.4.1.4	Method of test .....	165
8.4.1.4.1	Initial conditions .....	165
8.4.1.4.2	Procedure.....	165
8.4.1.5	Test requirement .....	166
<b>Annex A (normative): Reference measurement channels .....</b>		<b>168</b>
A.1	Fixed Reference Channels for reference sensitivity level, ACS, in-band blocking, out-of-band blocking, receiver intermodulation and in-channel selectivity (QPSK, R=1/3).....	168
A.2	Fixed Reference Channels for dynamic range (16QAM, R=2/3).....	168
A.3	Fixed Reference Channels for performance requirements (QPSK, R=193/1024) .....	169
A.4	Fixed Reference Channels for performance requirements (16QAM, R=658/1024) .....	171
A.5	Fixed Reference Channels for performance requirements (64QAM, R=567/1024) .....	172
A.6	PRACH test preambles.....	173
<b>Annex B (normative): Environmental requirements for the BS equipment .....</b>		<b>174</b>
B.1	General .....	174
B.2	Normal test environment.....	174
B.3	Extreme test environment.....	174
B.3.1	Extreme temperature .....	174
B.4	Vibration.....	175
B.5	Power supply .....	175
B.6	Measurement of test environments.....	175
<b>Annex C (informative): Test tolerances and derivation of test requirements.....</b>		<b>176</b>
C.1	Measurement of transmitter.....	176
C.2	Measurement of receiver .....	178
C.3	Measurement of performance requirements.....	178
<b>Annex D (informative): Measurement system set-up.....</b>		<b>179</b>
D.1	<i>BS type 1-C</i> transmitter.....	179
D.1.1	Base station output power, output power dynamics, transmitter ON/OFF power, frequency error, EVM, unwanted emissions for <i>BS type 1-C</i> .....	179
D.1.2	Transmitter intermodulation for <i>BS type 1-C</i> .....	179
D.1.3	Time alignment error for <i>BS type 1-C</i> .....	180
D.2	<i>BS type 1-C</i> receiver .....	180
D.2.1	Reference sensitivity level for <i>BS type 1-C</i> .....	180
D.2.2	Dynamic range for <i>BS type 1-C</i> .....	181
D.2.3	In-channel selectivity for <i>BS type 1-C</i> .....	181
D.2.4	Adjacent Channel Selectivity (ACS) and narrowband blocking for <i>BS type 1-C</i> .....	182
D.2.5	Blocking characteristics for <i>BS type 1-C</i> .....	182
D.2.6	Receiver spurious emission for <i>BS type 1-C</i> .....	183
D.2.7	Intermodulation characteristics for <i>BS type 1-C</i> .....	183
D.3	<i>BS type 1-H</i> transmitter .....	184
D.3.1	Base station output power, output power dynamics, transmitter ON/OFF power, frequency error, EVM, unwanted emissions for <i>BS type 1-H</i> .....	184
D.3.2	Transmitter intermodulation for <i>BS type 1-H</i> .....	185
D.3.3	Transmitter spurious emissions for <i>BS type 1-H</i> .....	185
D.3.4	Time alignment error for <i>BS type 1-H</i> .....	187
D.4	<i>BS type 1-H</i> receiver .....	187
D.4.1	Reference sensitivity level for <i>BS type 1-H</i> .....	187

D.4.2	Receiver dynamic range for BS type 1-H.....	188
D.4.3	Receiver adjacent channel selectivity and narrowband blocking for BS type 1-H.....	188
D.4.4	Receiver spurious emissions.....	188
D.4.5	Receiver In-channel selectivity for BS type 1-H.....	190
D.4.6	Receiver intermodulation for BS type 1-H.....	191
D.5	<i>BS type 1-C</i> performance requirements.....	191
D.5.1	Performance requirements for PUSCH, single user PUCCH, PRACH on single antenna port in multipath fading conditions.....	191
D.5.2	Performance requirements for PUSCH transmission on two antenna ports in multipath fading conditions ..	192
D.5.3	Performance requirements for PRACH in static conditions.....	192
D.6	BS type 1-H performance requirements.....	193
D.6.1	Performance requirements for PUSCH, single user PUCCH, PRACH on single antenna port in multipath fading conditions.....	193
D.6.2	Performance requirements for PUSCH transmission on two antenna ports in multipath fading conditions ..	194
D.6.3	Performance requirements for PRACH in static conditions.....	194
<b>Annex E (normative):</b>	<b>Characteristics of interfering signals .....</b>	<b>195</b>
<b>Annex F (normative):</b>	<b>Void .....</b>	<b>196</b>
<b>Annex G (normative):</b>	<b>Propagation conditions.....</b>	<b>197</b>
G.1	Static propagation condition.....	197
G.2	Multi-path fading propagation conditions.....	197
G.2.1	Delay profiles.....	197
G.2.1.1	Delay profiles for FR1.....	198
G.2.2	Combinations of channel model parameters.....	199
G.2.3	MIMO channel correlation matrices.....	200
G.2.3.1	MIMO correlation matrices using Uniform Linear Array.....	200
G.2.3.1.1	Definition of MIMO correlation matrices.....	200
G.2.3.1.2	MIMO correlation matrices at high, medium and low level.....	201
G.2.3.2	Multi-antenna channel models using cross polarized antennas.....	203
G.2.3.2.1	Definition of MIMO correlation matrices using cross polarized antennas.....	204
G.2.3.2.2	Spatial correlation matrices at UE and gNB sides.....	204
G.2.3.2.2.1	Spatial correlation matrices at UE side.....	204
G.2.3.2.2.2	Spatial correlation matrices at gNB side.....	204
G.2.3.2.3	MIMO correlation matrices using cross polarized antennas.....	205
<b>Annex H (normative):</b>	<b>In-channel TX tests.....</b>	<b>206</b>
H.1	General.....	206
H.2	Basic principles.....	206
H.2.1	Output signal of the TX under test.....	206
H.2.2	Ideal signal.....	206
H.2.3	Measurement results.....	207
H.2.4	Measurement points.....	207
H.3	Pre-FFT minimization process.....	208
H.4	Timing of the FFT window.....	208
H.5	Resource element TX power.....	209
H.6	Post-FFT equalisation.....	210
H.7	EVM.....	211
H.7.0	General.....	211
H.7.1	Averaged EVM (FDD).....	212
H.7.2	Averaged EVM (TDD).....	212
<b>Annex I (informative):</b>	<b>Change history .....</b>	<b>214</b>
History.....		222

---

# Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

**PREVIEW**  
iTech STANDARD  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/6146421a-18c2-46dc-b723-8cb8ac084cb1/etsi-ts-138-141-1-v15.4.0-2020-01>