

ETSI TS 138 104 V15.8.0 (2020-01)



**5G;
NR;**
**Base Station (BS) radio transmission and reception
(3GPP TS 38.104 version 15.8.0 Release 15)**

Standard PREVIEW
(Standard: 3GPP TS 38.104 V15.8.0-2020-01)
Full standard: https://standards.iteh.ai/catalog/standards/sist/9ee8dd10-1dcd-481-b502-c2b94291b886/etsi-ts-138-104-v15-8-0-2020-01



ReferenceRTS/TSGR-0438104vf80

Keywords5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	11
1 Scope	12
2 References	12
3 Definitions, symbols and abbreviations	13
3.1 Definitions	13
3.2 Symbols.....	17
3.3 Abbreviations	19
4 General	21
4.1 Relationship with other core specifications.....	21
4.2 Relationship between minimum requirements and test requirements	21
4.3 Conducted and radiated requirement reference points	21
4.3.1 <i>BS type 1-C</i>	21
4.3.2 <i>BS type 1-H</i>	22
4.3.3 <i>BS type 1-O</i> and <i>BS type 2-O</i>	23
4.4 Base station classes	23
4.5 Regional requirements.....	24
4.6 Applicability of requirements.....	24
4.7 Requirements for contiguous and <i>non-contiguous spectrum</i>	25
4.8 Requirements for BS capable of multi-band operation	25
4.9 OTA co-location with other base stations	27
5 <i>Operating bands</i> and channel arrangement	28
5.1 General	28
5.2 <i>Operating bands</i>	28
5.3 <i>BS channel bandwidth</i>	29
5.3.1 General.....	29
5.3.2 <i>Transmission bandwidth configuration</i>	30
5.3.3 Minimum guardband and <i>transmission bandwidth configuration</i>	30
5.3.4 RB alignment.....	32
5.3.5 <i>BS channel bandwidth per operating band</i>	32
5.3A <i>BS channel bandwidth for CA</i>	36
5.3A.1 <i>Transmission bandwidth configuration for CA</i>	36
5.3A.2 Minimum guardband and <i>transmission bandwidth configuration for CA</i>	36
5.4 Channel arrangement.....	37
5.4.1 Channel spacing.....	37
5.4.1.1 Channel spacing for adjacent NR carriers	37
5.4.1.2 Channel spacing for CA	38
5.4.2 Channel raster	39
5.4.2.1 NR-ARFCN and channel raster.....	39
5.4.2.2 Channel raster to resource element mapping.....	39
5.4.2.3 Channel raster entries for each <i>operating band</i>	39
5.4.3 Synchronization raster	41
5.4.3.1 Synchronization raster and numbering.....	41
5.4.3.2 Synchronization raster to synchronization block resource element mapping.....	41
5.4.3.3 Synchronization raster entries for each <i>operating band</i>	41
6 Conducted transmitter characteristics	43
6.1 General	43
6.2 Base station output power	43
6.2.1 General.....	43
6.2.2 Minimum requirement for <i>BS type 1-C</i>	44

6.2.3	Minimum requirement for <i>BS type 1-H</i>	44
6.2.4	Additional requirements (regional).....	44
6.3	Output power dynamics.....	44
6.3.1	General.....	44
6.3.2	RE power control dynamic range	44
6.3.2.1	General	44
6.3.2.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	44
6.3.3	Total power dynamic range	45
6.3.3.1	General	45
6.3.3.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	45
6.4	Transmit ON/OFF power	46
6.4.1	Transmitter OFF power	46
6.4.1.1	General	46
6.4.1.2	Minimum requirement for <i>BS type 1-C</i>	46
6.4.1.3	Minimum requirement for <i>BS type 1-H</i>	46
6.4.2	<i>Transmitter transient period</i>	46
6.4.2.1	General	46
6.4.2.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	47
6.4.2.3	Void.....	47
6.5	Transmitted signal quality	47
6.5.1	Frequency error.....	47
6.5.1.1	General	47
6.5.1.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	48
6.5.2	Modulation quality.....	48
6.5.2.1	General	48
6.5.2.2	Minimum Requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	48
6.5.2.3	EVM frame structure for measurement.....	48
6.5.3	Time alignment error	48
6.5.3.1	General	48
6.5.3.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	49
6.6	Unwanted emissions.....	49
6.6.1	General.....	49
6.6.2	Occupied bandwidth	50
6.6.2.1	General	50
6.6.2.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	50
6.6.3	Adjacent Channel Leakage Power Ratio	50
6.6.3.1	General	50
6.6.3.2	Limits and <i>Basic limits</i>	50
6.6.3.3	Minimum requirement for <i>BS type 1-C</i>	53
6.6.3.4	Minimum requirement for <i>BS type 1-H</i>	53
6.6.4	Operating band unwanted emissions	54
6.6.4.1	General	54
6.6.4.2	<i>Basic limits</i>	56
6.6.4.2.1	<i>Basic limits</i> for Wide Area BS (Category A)	56
6.6.4.2.2	<i>Basic limits</i> for Wide Area BS (Category B).....	56
6.6.4.2.2.1	Category B requirements (Option 1).....	56
6.6.4.2.2.2	Category B requirements (Option 2).....	58
6.6.4.2.3	<i>Basic limits</i> for Medium Range BS (Category A and B).....	58
6.6.4.2.4	<i>Basic limits</i> for Local Area BS (Category A and B).....	59
6.6.4.2.5	<i>Basic limits</i> for additional requirements	59
6.6.4.2.5.1	Limits in FCC Title 47.....	59
6.6.4.2.5.2	Protection of DTT.....	59
6.6.4.3	Minimum requirements for <i>BS type 1-C</i>	60
6.6.4.4	Minimum requirements for <i>BS type 1-H</i>	60
6.6.5	Transmitter spurious emissions.....	60
6.6.5.1	General	60
6.6.5.2	<i>Basic limits</i>	61
6.6.5.2.1	General transmitter spurious emissions requirements	61
6.6.5.2.2	Protection of the BS receiver of own or different BS.....	61
6.6.5.2.3	Additional spurious emissions requirements	62
6.6.5.2.4	Co-location with other base stations.....	69
6.6.5.3	Minimum requirements for <i>BS type 1-C</i>	74

6.6.5.4	Minimum requirements for <i>BS type 1-H</i>	74
6.7	Transmitter intermodulation	74
6.7.1	General	74
6.7.2	Minimum requirements for <i>BS type 1-C</i>	74
6.7.2.1	Co-location minimum requirements	74
6.7.2.2	Additional requirements	75
6.7.3	Minimum requirements for <i>BS type 1-H</i>	75
6.7.3.1	Co-location minimum requirements	75
6.7.3.2	Intra-system minimum requirements	76
6.7.3.3	Additional requirements	76
7	Conducted receiver characteristics	77
7.1	General	77
7.2	Reference sensitivity level	77
7.2.1	General	77
7.2.2	Minimum requirements for <i>BS type 1-C</i> and <i>BS type 1-H</i>	77
7.3	Dynamic range	79
7.3.1	General	79
7.3.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	79
7.4	In-band selectivity and blocking	81
7.4.1	Adjacent Channel Selectivity (ACS)	81
7.4.1.1	General	81
7.4.1.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	81
7.4.1.3	Void	83
7.4.1.4	Void	83
7.4.2	In-band blocking	83
7.4.2.1	General	83
7.4.2.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	83
7.4.2.3	Void	85
7.4.2.4	Void	85
7.5	Out-of-band blocking	85
7.5.1	General	85
7.5.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	85
7.5.3	Co-location minimum requirements for <i>BS type 1-C</i> and <i>BS type 1-H</i>	86
7.5.4	Void	87
7.6	Receiver spurious emissions	87
7.6.1	General	87
7.6.2	<i>Basic limits</i>	87
7.6.3	Minimum requirement for <i>BS type 1-C</i>	88
7.6.4	Minimum requirement for <i>BS type 1-H</i>	88
7.7	Receiver intermodulation	88
7.7.1	General	88
7.7.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	88
7.8	In-channel selectivity	93
7.8.1	General	93
7.8.2	Minimum requirement for <i>BS type 1-C</i> and <i>BS type 1-H</i>	93
8	Conducted performance requirements	96
8.1	General	96
8.1.1	Scope and definitions	96
8.1.2	Void	96
8.2	Performance requirements for PUSCH	96
8.2.1	Requirements for PUSCH with transform precoding disabled	96
8.2.1.1	General	96
8.2.1.2	Minimum requirements	97
8.2.2	Requirements for PUSCH with transform precoding enabled	104
8.2.2.1	General	104
8.2.2.2	Minimum requirements	105
8.2.3	Requirements for UCI multiplexed on PUSCH	106
8.2.3.1	General	106
8.2.3.2	Minimum requirements	107
8.3	Performance requirements for PUCCH	108

8.3.1	DTX to ACK probability	108
8.3.1.1	General	108
8.3.1.2	Minimum requirement	108
8.3.2	Performance requirements for PUCCH format 0	108
8.3.2.1	General	108
8.3.2.2	Minimum requirements	109
8.3.3	Performance requirements for PUCCH format 1	109
8.3.3.1	NACK to ACK requirements	109
8.3.3.1.1	General	109
8.3.3.1.2	Minimum requirements	110
8.3.3.2	ACK missed detection requirements	111
8.3.3.2.1	General	111
8.3.3.2.2	Minimum requirements	111
8.3.4	Performance requirements for PUCCH format 2	112
8.3.4.1	ACK missed detection requirements	112
8.3.4.1.1	General	112
8.3.4.1.2	Minimum requirements	112
8.3.4.2	UCI BLER performance requirements	113
8.3.4.2.1	General	113
8.3.4.2.2	Minimum requirements	113
8.3.5	Performance requirements for PUCCH format 3	113
8.3.5.1	General	113
8.3.5.2	Minimum requirements	114
8.3.6	Performance requirements for PUCCH format 4	115
8.3.6.1	General	115
8.3.6.2	Minimum requirement	116
8.3.7	Performance requirements for multi-slot PUCCH	116
8.3.7.1	General	116
8.3.7.2	Performance requirements for multi-slot PUCCH format 1	116
8.3.7.2.1	NACK to ACK requirements	116
8.3.7.2.1.1	General	116
8.3.7.2.1.2	Minimum requirements	117
8.3.7.2.2	ACK missed detection requirements	117
8.3.7.2.2.1	General	117
8.3.7.2.2.2	Minimum requirements	117
8.4	Performance requirements for PRACH	118
8.4.1	PRACH False alarm probability	118
8.4.1.1	General	118
8.4.1.2	Minimum requirement	118
8.4.2	PRACH detection requirements	118
8.4.2.1	General	118
8.4.2.2	Minimum requirements	118
9	Radiated transmitter characteristics	120
9.1	General	120
9.2	Radiated transmit power	120
9.2.1	General	120
9.2.2	Minimum requirement for <i>BS type 1-H</i> and <i>BS type 1-O</i>	120
9.2.3	Minimum requirement for <i>BS type 2-O</i>	121
9.3	OTA base station output power	121
9.3.1	General	121
9.3.2	Minimum requirement for <i>BS type 1-O</i>	121
9.3.3	Minimum requirement for <i>BS type 2-O</i>	122
9.3.4	Additional requirements (regional)	122
9.4	OTA output power dynamics	122
9.4.1	General	122
9.4.2	OTA RE power control dynamic range	122
9.4.2.1	General	122
9.4.2.2	Minimum requirement for <i>BS type 1-O</i>	122
9.4.3	OTA total power dynamic range	122
9.4.3.1	General	122
9.4.3.2	Minimum requirement for <i>BS type 1-O</i>	122

9.4.3.3	Minimum requirement for <i>BS type 2-O</i>	123
9.5	OTA transmit ON/OFF power.....	123
9.5.1	General.....	123
9.5.2	OTA transmitter OFF power.....	123
9.5.2.1	General.....	123
9.5.2.2	Minimum requirement for <i>BS type 1-O</i>	123
9.5.2.3	Minimum requirement for <i>BS type 2-O</i>	123
9.5.3	OTA transient period.....	123
9.5.3.1	General.....	123
9.5.3.2	Minimum requirement for <i>BS type 1-O</i>	124
9.5.3.3	Minimum requirement for <i>BS type 2-O</i>	124
9.6	OTA transmitted signal quality.....	124
9.6.1	OTA frequency error.....	124
9.6.1.1	General.....	124
9.6.1.2	Minimum requirement for <i>BS type 1-O</i>	124
9.6.1.3	Minimum requirement for <i>BS type 2-O</i>	124
9.6.2	OTA modulation quality.....	125
9.6.2.1	General.....	125
9.6.2.2	Minimum Requirement for <i>BS type 1-O</i>	125
9.6.2.3	Minimum Requirement for <i>BS type 2-O</i>	125
9.6.2.3.1	EVM frame structure for measurement.....	125
9.6.3	OTA time alignment error.....	125
9.6.3.1	General.....	125
9.6.3.2	Minimum requirement for <i>BS type 1-O</i>	125
9.6.3.3	Minimum requirement for <i>BS type 2-O</i>	126
9.7	OTA unwanted emissions.....	126
9.7.1	General.....	126
9.7.2	OTA occupied bandwidth.....	127
9.7.2.1	General.....	127
9.7.2.2	Minimum requirement for <i>BS type 1-O</i> and <i>BS type 2-O</i>	127
9.7.3	OTA Adjacent Channel Leakage Power Ratio (ACLR).....	127
9.7.3.1	General.....	127
9.7.3.2	Minimum requirement for <i>BS type 1-O</i>	127
9.7.3.3	Minimum requirement for <i>BS type 2-O</i>	127
9.7.4	OTA operating band unwanted emissions.....	129
9.7.4.1	General.....	129
9.7.4.2	Minimum requirement for <i>BS type 1-O</i>	129
9.7.4.2.1	Additional requirements.....	130
9.7.4.2.1.1	Protection of DTT.....	130
9.7.4.2.1.2	Limits in FCC Title 47.....	130
9.7.4.3	Minimum requirement for <i>BS type 2-O</i>	130
9.7.4.3.1	General.....	130
9.7.4.3.2	OTA operating band unwanted emission limits (Category A).....	131
9.7.4.3.3	OTA operating band unwanted emission limits (Category B).....	132
9.7.5	OTA transmitter spurious emissions.....	132
9.7.5.1	General.....	132
9.7.5.2	Minimum requirement for <i>BS type 1-O</i>	132
9.7.5.2.1	General.....	132
9.7.5.2.2	General OTA transmitter spurious emissions requirements.....	133
9.7.5.2.3	Protection of the BS receiver of own or different BS.....	133
9.7.5.2.4	Additional spurious emissions requirements.....	133
9.7.5.2.5	Co-location with other base stations.....	133
9.7.5.3	Minimum requirement for <i>BS type 2-O</i>	133
9.7.5.3.1	General.....	133
9.7.5.3.2	General OTA transmitter spurious emissions requirements.....	134
9.7.5.3.2.1	General.....	134
9.7.5.3.2.2	OTA transmitter spurious emissions (Category A).....	134
9.7.5.3.2.3	OTA transmitter spurious emissions (Category B).....	134
9.7.5.3.3	Additional OTA transmitter spurious emissions requirements.....	135
9.8	OTA transmitter intermodulation.....	135
9.8.1	General.....	135
9.8.2	Minimum requirement for <i>BS type 1-O</i>	135

10	Radiated receiver characteristics	137
10.1	General	137
10.2	OTA sensitivity	138
10.2.1	<i>BS type 1-H</i> and <i>BS type 1-O</i>	138
10.2.1.1	General	138
10.2.1.2	Minimum requirement	138
10.2.2	<i>BS type 2-O</i>	138
10.3	OTA reference sensitivity level	139
10.3.1	General	139
10.3.2	Minimum requirement for <i>BS type 1-O</i>	139
10.3.3	Minimum requirement for <i>BS type 2-O</i>	140
10.4	OTA dynamic range	141
10.4.1	General	141
10.4.2	Minimum requirement for <i>BS type 1-O</i>	141
10.5	OTA in-band selectivity and blocking	150
10.5.1	OTA adjacent channel selectivity	150
10.5.1.1	General	150
10.5.1.2	Minimum requirement for <i>BS type 1-O</i>	150
10.5.1.3	Minimum requirement for <i>BS type 2-O</i>	151
10.5.2	OTA in-band blocking	152
10.5.2.1	General	152
10.5.2.2	Minimum requirement for <i>BS type 1-O</i>	152
10.5.2.3	Minimum requirement for <i>BS type 2-O</i>	155
10.6	OTA out-of-band blocking	155
10.6.1	General	155
10.6.2	Minimum requirement for <i>BS type 1-O</i>	155
10.6.2.1	General minimum requirement	155
10.6.2.2	Co-location minimum requirement	156
10.6.3	Minimum requirement for <i>BS type 2-O</i>	157
10.6.3.1	General minimum requirement	157
10.7	OTA receiver spurious emissions	157
10.7.1	General	157
10.7.2	Minimum requirement for <i>BS type 1-O</i>	157
10.7.3	Minimum requirement for <i>BS type 2-O</i>	158
10.8	OTA receiver intermodulation	159
10.8.1	General	159
10.8.2	Minimum requirement for <i>BS type 1-O</i>	159
10.8.3	Minimum requirement for <i>BS type 2-O</i>	163
10.9	OTA in-channel selectivity	164
10.9.1	General	164
10.9.2	Minimum requirement for <i>BS type 1-O</i>	164
10.9.3	Minimum requirement for <i>BS type 2-O</i>	167
11	Radiated performance requirements	169
11.1	General	169
11.1.1	Scope and definitions	169
11.1.2	OTA demodulation branches	169
11.1.3	Void	170
11.2	Performance requirements for PUSCH	170
11.2.1	Requirements for <i>BS type 1-O</i>	170
11.2.1.1	Requirements for PUSCH with transform precoding disabled	170
11.2.1.2	Requirements for PUSCH with transform precoding enabled	170
11.2.1.3	Requirements for UCI multiplexed on PUSCH	170
11.2.2	Requirements for <i>BS type 2-O</i>	170
11.2.2.1	Requirements for PUSCH with transform precoding disabled	170
11.2.2.1.1	General	170
11.2.2.1.2	Minimum requirements	171
11.2.2.2	Requirements for PUSCH with transform precoding enabled	173
11.2.2.2.1	General	173
11.2.2.2.2	Minimum requirements	173
11.2.2.3	Requirements for UCI multiplexed on PUSCH	174
11.2.2.3.1	General	174

11.2.2.3.2	Minimum requirements	175
11.3	Performance requirements for PUCCH	176
11.3.1	Requirements for <i>BS type 1-O</i>	176
11.3.1.1	DTX to ACK probability	176
11.3.1.2	Performance requirements for PUCCH format 0	177
11.3.1.3	Performance requirements for PUCCH format 1	177
11.3.1.4	Performance requirements for PUCCH format 2	177
11.3.1.5	Performance requirements for PUCCH format 3	177
11.3.1.6	Performance requirements for PUCCH format 4	177
11.3.2	Requirements for <i>BS type 2-O</i>	177
11.3.2.1	DTX to ACK probability	177
11.3.2.2	Performance requirements for PUCCH format 0	177
11.3.2.2.1	General	177
11.3.2.2.2	Minimum requirements	177
11.3.2.3	Performance requirements for PUCCH format 1	178
11.3.2.3.1	NACK to ACK requirements	178
11.3.2.3.1.1	General.....	178
11.3.2.3.1.2	Minimum requirements.....	179
11.3.2.3.2	ACK missed detection requirements	179
11.3.2.3.2.1	General.....	179
11.3.2.3.2.2	Minimum requirements.....	179
11.3.2.4	Performance requirements for PUCCH format 2	180
11.3.2.4.1	ACK missed detection requirements	180
11.3.2.4.1.1	General.....	180
11.3.2.4.1.2	Minimum requirements.....	180
11.3.2.4.2	UCI BLER performance requirements.....	180
11.3.2.4.2.1	General.....	180
11.3.2.4.2.2	Minimum requirements.....	181
11.3.2.5	Performance requirements for PUCCH format 3	181
11.3.2.5.1	General	181
11.3.2.5.2	Minimum requirements	182
11.3.2.6	Performance requirements for PUCCH format 4	182
11.3.2.6.1	General	182
11.3.2.6.2	Minimum requirements	183
11.4	Performance requirements for PRACH.....	183
11.4.1	Requirements for <i>BS type 1-O</i>	183
11.4.1.1	PRACH False alarm probability.....	183
11.4.1.2	PRACH detection requirements.....	183
11.4.2	Requirements for <i>BS type 2-O</i>	184
11.4.2.1	PRACH False alarm probability	184
11.4.2.1.1	General	184
11.4.2.1.2	Minimum requirement.....	184
11.4.2.2	PRACH detection requirements.....	184
11.4.2.2.1	General	184
11.4.2.2.2	Minimum requirements	184
Annex A (normative): Reference measurement channels		186
A.1	Fixed Reference Channels for reference sensitivity level, ACS, in-band blocking, out-of-band blocking, receiver intermodulation and in-channel selectivity (QPSK, R=1/3).....	186
A.2	Fixed Reference Channels for dynamic range (16QAM, R=2/3).....	187
A.3	Fixed Reference Channels for performance requirements (QPSK, R=193/1024)	187
A.4	Fixed Reference Channels for performance requirements (16QAM, R=658/1024)	192
A.5	Fixed Reference Channels for performance requirements (64QAM, R=567/1024)	196
A.6	PRACH Test preambles	198
Annex B (normative): Error Vector Magnitude (FR1)		199
B.1	Reference point for measurement.....	199

B.2	Basic unit of measurement	199
B.3	Modified signal under test	200
B.4	Estimation of frequency offset	200
B.5	Estimation of time offset	200
B.5.1	General	200
B.5.2	Window length	201
B.6	Estimation of TX chain amplitude and frequency response parameters	202
B.7	Averaged EVM	203
Annex C (normative): Error Vector Magnitude (FR2)		205
C.1	Reference point for measurement	205
C.2	Basic unit of measurement	205
C.3	Modified signal under test	206
C.4	Estimation of frequency offset	206
C.5	Estimation of time offset	206
C.5.1	General	206
C.5.2	Window length	207
C.6	Estimation of TX chain amplitude and frequency response parameters	207
C.7	Averaged EVM	209
Annex D (normative): Characteristics of the interfering signals		211
Annex E: Void		212
Annex F (normative): Relationship between EIRP based regulatory requirements and 3GPP requirements		213
F.1	General	213
F.2	Relationship between EIRP based regulatory requirements and conducted requirements	213
F.3	Relationship between EIRP based regulatory requirements and OTA requirements	214
Annex G (Normative): Propagation conditions		215
G.1	Static propagation condition	215
G.2	Multi-path fading propagation conditions	215
G.2.1	Delay profiles	215
G.2.1.1	Delay profiles for FR1	216
G.2.1.2	Delay profiles for FR2	217
G.2.2	Combinations of channel model parameters	218
G.2.3	MIMO Channel Correlation Matrices	219
G.2.3.1	MIMO Correlation Matrices using Uniform Linear Array (ULA)	219
G.2.3.1.1	Definition of MIMO Correlation Matrices	219
G.2.3.1.2	MIMO Correlation Matrices at High, Medium and Low Level	223
G.2.3.2	Multi-Antenna channel models using cross polarized antennas	225
G.2.3.2.1	Definition of MIMO Correlation Matrices using cross polarized antennas	226
G.2.3.2.2	Spatial Correlation Matrices at UE and gNB sides	226
G.2.3.2.2.1	Spatial Correlation Matrices at UE side	226
G.2.3.2.2.2	Spatial Correlation Matrices at gNB side	227
G.2.3.2.3	MIMO Correlation Matrices using cross polarized antennas	227
Annex H (informative): Change history		228
History		236

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

PREVIEW
STANDARD
ETSI
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/9ee8dd10-1dcd-481-b502-c2b94291b886/etsi-ts-138-104-v15.8.0-2020-01>

1 Scope

The present document establishes the minimum RF characteristics and minimum performance requirements of NR Base Station (BS).

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] ITU-R Recommendation SM.329: "Unwanted emissions in the spurious domain".
- [3] Recommendation ITU-R SM.328: "Spectra and bandwidth of emissions".
- [4] 3GPP TR 25.942: "RF system scenarios".
- [5] 3GPP TS 38.141-1: "NR; Base Station (BS) conformance testing; Part 1: Conducted conformance testing".
- [6] 3GPP TS 38.141-2: "NR; Base Station (BS) conformance testing; Part 2: Radiated conformance testing".
- [7] Recommendation ITU-R M.1545: "Measurement uncertainty as it applies to test limits for the terrestrial component of International Mobile Telecommunications-2000".
- [8] "Title 47 of the Code of Federal Regulations (CFR)", Federal Communications Commission.
- [9] 3GPP TS 38.211: "NR; Physical channels and modulation".
- [10] 3GPP TS 38.213: "NR; Physical layer procedures for control".
- [11] 3GPP TS 38.331: "NR; Radio Resource Control (RRC); Protocol specification".
- [12] ECC/DEC/(17)06: "The harmonised use of the frequency bands 1427-1452 MHz and 1492-1518 MHz for Mobile/Fixed Communications Networks Supplemental Downlink (MFCN SDL)".
- [13] 3GPP TS 36.104: "Evolved Universal Terrestrial Radio Access (E-UTRA); Base Station (BS) radio transmission and reception".
- [14] 3GPP TS 37.105: "Active Antenna System (AAS) Base Station (BS) transmission and reception".
- [15] 3GPP TS 38.212: "NR; Multiplexing and channel coding".
- [16] 3GPP TR 38.901: "Study on channel model for frequencies from 0.5 to 100 GHz".
- [17] 3GPP TS 38.101-1: "NR; User Equipment (UE) radio transmission and reception; Part 1: Range 1 Standalone".
- [18] 3GPP TS 38.101-2: "NR; User Equipment (UE) radio transmission and reception; Part 2: Range 2 Standalone".
- [19] ERC Recommendation 74-01, "Unwanted emissions in the spurious domain".