

ETSI TS 138 133 V15.8.0 (2020-02)



TECHNICAL SPECIFICATION

**5G;
NR;**

**Requirements for support of radio resource management
(3GPP TS 38.133 version 15.8.0 Release 15)**

STANDARD PREVIEW
(standards.iteh.ai)
Full standards lists/sist/bfi/7963-782e-4038-9d6b-e7983600240/etsi-ts-138-133-v15.8.0-2020-02
<https://standards.iteh.ai/catalog/standards/sist/bfi/7963-782e-4038-9d6b-e7983600240/etsi-ts-138-133-v15.8.0-2020-02>



Reference

RTS/TSGR-0438133vf80

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal notice

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

| | |
|---|----|
| Intellectual Property Rights | 2 |
| Legal notice | 2 |
| Modal verbs terminology..... | 2 |
| Foreword..... | 17 |
| 1 Scope | 18 |
| 2 References | 18 |
| 3 Definitions, symbols and abbreviations | 19 |
| 3.1 Definitions | 19 |
| 3.2 Symbols..... | 20 |
| 3.3 Abbreviations | 20 |
| 3.4 Test tolerances | 22 |
| 3.5 Frequency bands grouping | 22 |
| 3.5.1 Introduction..... | 22 |
| 3.5.2 NR operating bands in FR1 | 22 |
| 3.5.3 NR operating bands in FR2 | 23 |
| 3.6 Applicability of requirements in this specification version | 23 |
| 3.6.1 RRC connected state requirements in DRX..... | 23 |
| 3.6.2 Number of serving carriers | 24 |
| 3.6.2.1 Number of serving carriers for SA | 24 |
| 3.6.2.2 Number of serving carriers for EN-DC | 24 |
| 3.6.2.3 Number of serving carriers for NE-DC | 24 |
| 3.6.2.4 Number of serving carriers for NR-DC | 24 |
| 3.6.3 Applicability for intra-band FR2 | 25 |
| 3.6.4 Applicability for FR2 UE power classes..... | 25 |
| 3.6.5 Applicability for SDL bands | 25 |
| 3.6.6 Applicability of requirements for NGEN-DC operation..... | 25 |
| 4 SA: RRC_IDLE state mobility | 25 |
| 4.1 Cell Selection | 25 |
| 4.2 Cell Re-selection | 25 |
| 4.2.1 Introduction..... | 25 |
| 4.2.2 Requirements | 26 |
| 4.2.2.1 UE measurement capability | 26 |
| 4.2.2.5 Measurements of inter-RAT E-UTRAN cells..... | 29 |
| 4.2.2.6 Maximum interruption in paging reception..... | 30 |
| 4.2.2.7 General requirements | 30 |
| 6 RRC_CONNECTED state mobility | 32 |
| 6.1 Handover | 32 |
| 6.1.1 NR Handover | 32 |
| 6.1.1.1 Introduction..... | 32 |
| 6.1.1.2 NR FR1 - NR FR1 Handover | 32 |
| 6.1.1.2.1 Handover delay..... | 32 |
| 6.1.1.2.2 Interruption time..... | 32 |
| 6.1.1.3 NR FR2- NR FR1 Handover..... | 33 |
| 6.1.1.3.1 Handover delay..... | 33 |
| 6.1.1.3.2 Interruption time..... | 33 |
| 6.1.1.4 NR FR2- NR FR2 Handover..... | 34 |
| 6.1.1.4.1 Handover delay..... | 34 |
| 6.1.1.4.2 Interruption time..... | 34 |
| 6.1.1.5 NR FR1- NR FR2 Handover..... | 35 |
| 6.1.1.5.1 Handover delay..... | 35 |
| 6.1.1.5.2 Interruption time..... | 35 |
| 6.1.2 NR Handover to other RATs | 36 |
| 6.1.2.1 NR – E-UTRAN Handover..... | 36 |

| | | |
|-----------|---|----|
| 6.1.2.1.1 | Introduction | 36 |
| 6.1.2.1.2 | Handover delay..... | 36 |
| 6.1.2.1.3 | Interruption time..... | 36 |
| 6.2 | RRC Connection Mobility Control..... | 37 |
| 6.2.1 | SA: RRC Re-establishment | 37 |
| 6.2.1.1 | Introduction..... | 37 |
| 6.2.1.2 | Requirements | 37 |
| 6.2.1.2.1 | UE Re-establishment delay requirement | 37 |
| 6.2.2 | Random access..... | 38 |
| 6.2.2.1 | Introduction..... | 38 |
| 6.2.2.2 | Requirements | 38 |
| 6.2.2.2.1 | Contention based random access..... | 39 |
| 6.2.2.2.2 | Non-Contention based random access..... | 40 |
| 6.2.2.2.3 | UE behaviour when configured with supplementary UL | 41 |
| 6.2.3 | SA: RRC Connection Release with Redirection..... | 41 |
| 6.2.3.1 | Introduction..... | 41 |
| 6.2.3.2 | Requirements | 41 |
| 6.2.3.2.1 | RRC connection release with redirection to NR..... | 41 |
| 6.2.3.2.2 | RRC connection release with redirection to E-UTRAN..... | 42 |
| 7 | Timing..... | 42 |
| 7.1 | UE transmit timing | 42 |
| 7.1.1 | Introduction..... | 42 |
| 7.1.2 | Requirements | 42 |
| 7.1.2.1 | Gradual timing adjustment..... | 43 |
| 7.1.2.2 | One shot timing adjustment | 44 |
| 7.2 | UE timer accuracy | 44 |
| 7.2.1 | Introduction..... | 44 |
| 7.2.2 | Requirements | 45 |
| 7.3 | Timing advance..... | 45 |
| 7.3.1 | Introduction..... | 45 |
| 7.3.2 | Requirements | 45 |
| 7.3.2.1 | Timing Advance adjustment delay..... | 45 |
| 7.3.2.2 | Timing Advance adjustment accuracy..... | 45 |
| 7.4 | Cell phase synchronization accuracy..... | 45 |
| 7.4.1 | Definition..... | 45 |
| 7.4.2 | Minimum requirements..... | 45 |
| 7.5 | Maximum Transmission Timing Difference | 46 |
| 7.5.1 | Introduction..... | 46 |
| 7.5.2 | Minimum Requirements for inter-band EN-DC | 46 |
| 7.5.2.1 | Minimum Requirements for inter-band synchronous EN-DC | 46 |
| 7.5.3 | Minimum Requirements for intra-band EN-DC | 47 |
| 7.5.4 | Minimum Requirements for NR Carrier Aggregation | 47 |
| 7.5.5 | Minimum Requirements for inter-band NE-DC | 47 |
| 7.5.5.1 | Minimum Requirements for inter-band synchronous NE-DC | 48 |
| 7.5.6 | Minimum Requirements for inter-band NR DC | 48 |
| 7.6 | Maximum Receive Timing Difference..... | 48 |
| 7.6.1 | Introduction..... | 48 |
| 7.6.2 | Minimum Requirements for inter-band EN-DC | 49 |
| 7.6.2.1 | Minimum Requirements for inter-band synchronous EN-DC | 49 |
| 7.6.3 | Minimum Requirements for intra-band EN-DC | 49 |
| 7.6.4 | Minimum Requirements for NR Carrier Aggregation | 50 |
| 7.6.5 | Minimum Requirements for inter-band NE-DC | 50 |
| 7.6.5.1 | Minimum Requirements for inter-band synchronous NE-DC | 51 |
| 7.6.6 | Minimum Requirements for inter-band NR DC | 51 |
| 7.7 | <i>deriveSSB-IndexFromCell</i> tolerance | 51 |
| 7.7.1 | Minimum requirements..... | 51 |
| 7.8 | Void..... | 52 |
| 8 | Signalling characteristics..... | 52 |
| 8.1 | Radio Link Monitoring..... | 52 |
| 8.2 | Interruption..... | 61 |

| | | |
|-----------|---|-----|
| 8.2.1.2 | Requirements | 61 |
| 8.2.1.2.1 | Interruptions at transitions between active and non-active during DRX | 61 |
| 8.2.1.2.3 | Interruptions at SCell addition/release..... | 62 |
| 8.2.1.2.6 | Interruptions at UL carrier RRC reconfiguration | 64 |
| 8.2.1.2.7 | Interruptions due to Active BWP switching Requirement | 65 |
| 8.2.2.2.1 | Interruptions at SCell addition/release..... | 66 |
| 8.2.2.2.2 | Interruptions at SCell activation/deactivation..... | 67 |
| 8.2.2.2.3 | Interruptions during measurements on deactivated SCC..... | 68 |
| 8.2.2.2.5 | Interruptions due to Active BWP switching Requirement | 68 |
| 8.2.3 | NE-DC Interruptions..... | 70 |
| 8.2.3.1 | Introduction..... | 70 |
| 8.2.3.2 | Requirements | 71 |
| 8.2.3.2.1 | Interruptions at transitions between active and non-active during DRX | 71 |
| 8.2.3.2.3 | Interruptions at PSCell/SCell addition/release | 71 |
| 8.2.3.2.6 | Interruptions at UL carrier RRC reconfiguration | 74 |
| 8.2.3.2.7 | Interruptions due to Active BWP switching Requirement | 74 |
| 8.2.4 | NR-DC: Interruptions | 74 |
| 8.2.4.1 | Introduction..... | 74 |
| 8.2.4.2 | Requirements | 75 |
| 8.2.4.2.1 | Interruptions at PSCell/SCell addition/release | 75 |
| 8.2.4.2.2 | Interruptions at SCell activation/deactivation..... | 76 |
| 8.2.4.2.3 | Interruptions during measurements on SCC..... | 77 |
| 8.2.4.2.5 | Interruptions due to Active BWP switching Requirement | 77 |
| 8.2.4.2.6 | Interruptions at transitions between active and non-active during DRX | 78 |
| 8.2.4.2.7 | Interruptions at transitions from non-DRX to DRX | 78 |
| 8.3.3 | SCell Deactivation Delay Requirement for Activated SCell | 81 |
| 8.4 | UE UL carrier RRC reconfiguration delay..... | 81 |
| 8.4.1 | Introduction..... | 81 |
| 8.4.2 | UE UL carrier configuration delay requirement..... | 82 |
| 8.4.3 | UE UL carrier deconfiguration delay requirement..... | 82 |
| 8.6 | Active BWP switch delay..... | 94 |
| 8.6.1 | Introduction..... | 94 |
| 8.6.2 | DCI and timer based BWP switch delay..... | 94 |
| 8.6.3 | RRC based BWP switch delay..... | 95 |
| 8.7 | Void..... | 96 |
| 8.8 | NE-DC: E-UTRAN PSCell Addition and Release Delay | 96 |
| 8.8.1 | Introduction..... | 96 |
| 8.8.2 | E-UTRAN PSCell Addition Delay Requirement..... | 96 |
| 8.8.3 | E-UTRAN PSCell Release Delay Requirement | 96 |
| 8.10.6 | Active TCI state list update delay | 100 |
| 8.11 | PSCell Change..... | 100 |
| 9 | Measurement Procedure | 100 |
| 9.1 | General measurement requirement..... | 100 |
| 9.1.1 | Introduction..... | 100 |
| 9.1.2 | Measurement gap..... | 100 |
| 9.1.2.1 | EN-DC: Measurement Gap Sharing..... | 108 |
| 9.1.2.1a | SA: Measurement Gap Sharing..... | 108 |
| 9.1.2.1b | NE-DC: Measurement Gap Sharing..... | 109 |
| 9.1.2.1c | NR-DC: Measurement Gap Sharing | 110 |
| 9.1.3 | UE Measurement capability..... | 111 |
| 9.1.3.1 | EN-DC: Monitoring of multiple layers using gaps | 111 |
| 9.1.3.1b | NE-DC: Monitoring of multiple layers using gaps | 112 |
| 9.1.3.2 | EN-DC: Maximum allowed layers for multiple monitoring | 112 |
| 9.1.3.2a | SA: Maximum allowed layers for multiple monitoring | 113 |
| 9.1.3.2b | NE-DC: Maximum allowed layers for multiple monitoring | 113 |
| 9.1.4 | Capabilities for Support of Event Triggering and Reporting Criteria..... | 114 |
| 9.1.4.1 | Introduction..... | 114 |
| 9.1.4.2 | Requirements | 115 |
| 9.1.5 | Carrier-specific scaling factor..... | 116 |
| 9.1.5.1 | Monitoring of multiple layers outside gaps..... | 116 |

| | | |
|---|--|------------|
| 9.1.5.1.1 | EN-DC mode: carrier-specific scaling factor for SSB-based measurements performed outside gaps..... | 117 |
| 9.1.5.1.2 | SA mode: carrier-specific scaling factor for SSB-based measurements performed outside gaps..... | 117 |
| 9.1.5.1.3 | NR-DC mode: carrier-specific scaling factor for SSB-based measurements performed outside gaps..... | 118 |
| 9.1.5.1.4 | NE-DC mode: carrier-specific scaling factor for SSB-based measurements performed outside gaps..... | 118 |
| 9.1.5.2 | Monitoring of multiple layers within gaps..... | 118 |
| 9.1.5.2.1 | EN-DC mode: carrier-specific scaling factor for SSB-based measurements performed within gaps..... | 119 |
| 9.1.5.2.2 | SA mode: carrier-specific scaling factor for SSB-based measurements performed within gaps..... | 120 |
| 9.1.5.2.3 | NE-DC: carrier-specific scaling factor for SSB-based measurements performed within gaps..... | 121 |
| 9.1.5.2.4 | NR-DC: carrier-specific scaling factor for SSB-based measurements performed within gaps..... | 122 |
| 9.1.6 | Minimum requirement at transitions..... | 124 |
| 9.2 | NR intra-frequency measurements..... | 124 |
| 9.2.1 | Introduction..... | 124 |
| 9.2.2 | Requirements applicability..... | 124 |
| 9.2.3 | Number of cells and number of SSB..... | 125 |
| 9.2.4 | Measurement Reporting Requirements..... | 125 |
| 9.2.5 | Intrafrequency measurements without measurement gaps..... | 126 |
| 9.2.5.3.1 | Scheduling availability of UE performing measurements in TDD bands on FR1..... | 129 |
| 9.2.5.4 | SFTD Measurements between PCell and PSCell..... | 131 |
| 9.2.5.4.1 | Introduction..... | 131 |
| 9.2.5.4.2 | SFTD Measurement delay..... | 131 |
| 9.2.5.4.3 | SFTD Measurement Reporting Delay..... | 132 |
| 9.2.6 | Intrafrequency measurements with measurement gaps..... | 132 |
| 9.4 | Inter-RAT measurements..... | 139 |
| 9.4.1 | Introduction..... | 139 |
| 9.4.2 | NR – E-UTRAN FDD measurements..... | 140 |
| 9.4.3 | NR – E-UTRAN TDD measurements..... | 143 |
| 9.4.4 | Inter-RAT RSTD measurements..... | 145 |
| 9.4.5 | Inter-RAT E-CID measurements..... | 153 |
| 10.2 | E-UTRAN measurements..... | 194 |
| 10.2.1 | Introduction..... | 194 |
| 10.2.2 | E-UTRAN RSRP measurements..... | 194 |
| 10.2.3 | E-UTRAN RSRQ measurements..... | 195 |
| 10.2.4 | E-UTRAN RSTD measurements..... | 195 |
| 10.2.5 | E-UTRAN RS-SINR measurements..... | 195 |
| 11 | Void..... | 195 |
| Annex A (normative): Test Cases..... | | 196 |
| A.1 | Purpose of annex..... | 196 |
| A.2 | Requirement classification for statistical testing..... | 196 |
| A.2.1 | Types of requirements in TS 38.133..... | 196 |
| A.2.1.1 | Time and delay requirements on UE higher layer actions..... | 196 |
| A.2.1.2 | Measurements of power levels, relative powers and time..... | 197 |
| A.2.1.3 | Implementation requirements..... | 197 |
| A.2.1.4 | Physical layer timing requirements..... | 197 |
| A.3 | RRM test configurations..... | 198 |
| A.3.1 | Reference measurement channels..... | 198 |
| A.3.1.1 | PDSCH..... | 198 |
| A.3.1.1.1 | FDD..... | 198 |
| A.3.1.1.2 | TDD..... | 199 |
| A.3.1.2 | CORESET for RMSI scheduling..... | 202 |
| A.3.1.2.1 | FDD..... | 202 |
| A.3.1.2.2 | TDD..... | 203 |
| A.3.1.3 | CORESET for RMC scheduling..... | 206 |
| A.3.1.3.1 | FDD..... | 206 |

| | | |
|------------|--|-----|
| A.3.1.3.2 | TDD | 207 |
| A.3.1.4 | TDD UL/DL configuration | 209 |
| A.3.2 | OFDMA channel noise generator (OCNG)..... | 210 |
| A.3.2.1 | Generic OFDMA Channel Noise Generator (OCNG)..... | 210 |
| A.3.2.1.1 | OCNG pattern 1: Generic OCNG pattern for all unused REs..... | 211 |
| A.3.2.1.2 | OCNG pattern 2: Generic OCNG pattern for all unused REs for 2AoA setup | 211 |
| A.3.2.1.3 | OCNG pattern 3: Generic OCNG pattern for unused REs in the same bandwidth as PDSCH RMC..... | 212 |
| A.3.2.2 | Void | 212 |
| A.3.3 | Reference DRX configurations | 212 |
| A.3.3.1 | DRX Configuration 1: DRX cycle = 40 ms and TAT = 500 ms..... | 212 |
| A.3.3.2 | DRX Configuration 2: DRX cycle = 640 ms and TAT = 500 ms..... | 213 |
| A.3.3.3 | DRX Configuration 3: DRX cycle = 40 ms and TAT = Infinity | 213 |
| A.3.3.4 | DRX Configuration 4: DRX cycle = 160 ms and TAT = Infinity | 213 |
| A.3.3.7 | DRX Configuration 7: DRX cycle = 640 ms and TAT = Infinity | 214 |
| A.3.3.8 | DRX Configuration 8: DRX cycle = 320 ms and TAT = Infinity | 215 |
| A.3.3.9 | DRX Configuration 9: DRX cycle = 40 ms and TAT = 500 ms..... | 215 |
| A.3.3.10 | DRX Configuration 10: DRX cycle = 640 ms..... | 215 |
| A.3.3.11 | DRX Configuration 11: DRX cycle = 20 ms and TAT = Infinity | 216 |
| A.3.4 | Test Cases with Different Channel Bandwidths..... | 216 |
| A.3.4.1 | Test Cases with Different E-UTRA Channel Bandwidths..... | 216 |
| A.3.4.1.1 | Introduction..... | 216 |
| A.3.4.1.2 | Principle of testing | 216 |
| A.3.5 | Test Cases for Synchronous and Asynchronous DC Operations..... | 216 |
| A.3.5.1 | EN-DC Test Cases for Synchronous and Asynchronous EN-DC Operations | 216 |
| A.3.5.1.1 | Introduction..... | 216 |
| A.3.5.1.2 | Principle of Testing | 216 |
| A.3.6 | Antenna configurations | 217 |
| A.3.6.2 | Antenna configurations for FR2 | 219 |
| A.3.7 | EN-DC test setup..... | 219 |
| A.3.7.1 | Introduction..... | 219 |
| A.3.7.2 | E-UTRAN Serving Cell Parameters..... | 219 |
| A.3.7.2.1 | E-UTRAN Serving Cell Parameters for Tests with NR Cell(s) in FR1 | 219 |
| A.3.7.2.2 | E-UTRAN Serving Cell Parameters for Tests with NR Cell(s) in FR2 | 221 |
| A.3.7A | NR FR1-FR2 test setup | 222 |
| A.3.8 | PRACH configurations..... | 222 |
| A.3.8.1 | Introduction..... | 222 |
| A.3.8.2 | PRACH configurations in FR1..... | 222 |
| A.3.8.2.1 | FR1 PRACH configuration 1 | 222 |
| A.3.8.2.2 | FR1 PRACH configuration 2 | 223 |
| A.3.8.2.3 | FR1 PRACH configuration 3 | 224 |
| A.3.8.2.4 | FR1 PRACH configuration 4 | 225 |
| A.3.8.3 | PRACH configurations in FR2..... | 226 |
| A.3.8.3.1 | FR2 PRACH configuration 1 | 226 |
| A.3.8.3.2 | FR2 PRACH configuration 2 | 227 |
| A.3.8.3.3 | FR2 PRACH configuration 3 | 228 |
| A.3.8.3.4 | FR2 PRACH configuration 4 | 229 |
| A.3.9 | BWP configurations | 230 |
| A.3.9.1 | Introduction..... | 230 |
| A.3.9.2 | Downlink BWP configurations..... | 231 |
| A.3.9.2.1 | Initial BWP | 231 |
| A.3.9.2.2 | Dedicated BWP..... | 231 |
| A.3.9.3 | Uplink BWP configurations..... | 231 |
| A.3.9.3.1 | Initial BWP | 231 |
| A.3.9.3.2 | Dedicated BWP..... | 232 |
| A.3.10 | SSB Configurations..... | 232 |
| A.3.10.1 | SSB Configurations for FR1 | 232 |
| A.3.10.1.1 | SSB pattern 1 in FR1: SSB allocation for SSB SCS=15 kHz in 10 MHz..... | 232 |
| A.3.10.1.5 | SSB pattern 5 in FR1: SSB allocation for SSB SCS=15 kHz starting from odd SFN in 10 MHz | 235 |
| A.3.11 | SMTC Configurations | 239 |
| A.3.11.1 | SMTC pattern 1: SMTC period = 20 ms with SMTC duration = 1 ms..... | 239 |
| A.3.11.2 | SMTC pattern 2: SMTC period = 20 ms with SMTC duration = 5 ms..... | 240 |

| | | |
|-------------|---|-----|
| A.3.11.3 | SMTC pattern 3: SMTC period = 160 ms with SMTC duration = 1 ms..... | 240 |
| A.3.11.4 | SMTC pattern 4: SMTC period = 20 ms with SMTC duration = 1 ms..... | 240 |
| A.3.11.5 | SMTC pattern 5: SMTC period = 20 ms with SMTC duration = 5 ms..... | 240 |
| A.3.12 | Test Cases with Different CC Configurations..... | 240 |
| A.3.12.1 | EN-DC Test Cases with Different EN-DC Configurations..... | 240 |
| A.3.12.1.1 | Introduction..... | 240 |
| A.3.12.1.2 | Principle of testing..... | 241 |
| A.3.12.2 | Carrier Aggregation Test Cases with Different CA Configurations..... | 241 |
| A.3.12.2.1 | Introduction..... | 241 |
| A.3.12.2.2 | Principle of testing..... | 241 |
| A.3.13 | Test Cases in SA and EN-DC Operations..... | 241 |
| A.3.13.1 | Introduction..... | 241 |
| A.3.13.2 | Principle of Testing..... | 241 |
| A.3.14 | CSI-RS configurations..... | 242 |
| A.3.14.1 | FDD..... | 242 |
| A.3.14.2 | TDD..... | 243 |
| A.3.15 | Angle of Arrival (AoA) for FR2 RRM test cases..... | 246 |
| A.3.15.1 | Setup 1: Single AoA in Rx beam peak direction..... | 246 |
| A.3.15.2 | Setup 2: Single AoA in non Rx beam peak direction..... | 246 |
| A.3.15.2.1 | Setup 2a: Single AoA in non Rx beam peak direction without change in direction..... | 246 |
| A.3.15.2.2 | Setup 2b: Single AoA in non Rx beam peak direction with change in direction..... | 246 |
| A.3.15.3 | Setup 3: 2 AoAs..... | 246 |
| A.3.15.4 | Setup 4: 2 AoAs, 1 AoA in Rx beam peak direction, 1 in non Rx beam peak..... | 247 |
| A.3.15.4.1 | Setup 4a: 2 AoAs, 1 AoA in Rx beam peak direction, 1 in non Rx beam peak without change in direction..... | 247 |
| A.3.15.4.2 | Setup 4b: 2 AoAs, 1 AoA in Rx beam peak direction, 1 in non Rx beam peak with change in direction..... | 247 |
| A.3.16 | TCI State Configuration..... | 247 |
| A.3.16.1 | Introduction..... | 247 |
| A.3.16.2 | TCI states..... | 247 |
| A.3.17 | Configurations of CSI-RS for tracking..... | 248 |
| A.3.17.1 | Configuration of CSI-RS for tracking for FR1..... | 248 |
| A.3.17.1.1 | FDD..... | 248 |
| A.3.17.1.2 | TDD..... | 249 |
| A.3.17.2 | Configuration of CSI-RS for tracking for FR2..... | 250 |
| A.3.17.2.1 | TDD..... | 250 |
| A.3.18 | Additional definitions related to OTA testing for FR2 RRM test cases..... | 250 |
| A.3.18.1 | Introduction..... | 250 |
| A.3.18.2 | PRACH Power Measurement..... | 251 |
| A.4 | EN-DC tests with all NR cells in FR1..... | 251 |
| A.4.1 | Void..... | 251 |
| A.4.2 | Void..... | 251 |
| A.4.3 | RRC_CONNECTED state mobility..... | 251 |
| A.4.3.1 | Void..... | 251 |
| A.4.3.2 | RRC Connection Mobility Control..... | 251 |
| A.4.3.2.1 | Void..... | 251 |
| A.4.3.2.3 | Void..... | 257 |
| A.4.4 | Timing..... | 257 |
| A.4.4.1 | UE transmit timing..... | 257 |
| A.4.4.1.1 | NR UE Transmit Timing Test for FR1..... | 257 |
| A.4.4.1.1.1 | Test Purpose and environment..... | 257 |
| A.4.4.1.1.2 | Test requirements..... | 260 |
| A.4.4.2 | UE timer accuracy..... | 261 |
| A.4.4.3 | Timing advance..... | 261 |
| A.4.4.3.1 | EN-DC FR1 timing advance adjustment accuracy..... | 261 |
| A.4.4.3.1.1 | Test Purpose and Environment..... | 261 |
| A.4.4.3.1.2 | Test Parameters..... | 261 |
| A.4.4.3.1.3 | Test Requirements..... | 264 |
| A.4.5 | Signaling characteristics..... | 264 |
| A.4.5.1 | Radio link Monitoring..... | 264 |
| A.4.5.4 | UE UL carrier RRC reconfiguration Delay..... | 316 |

| | | |
|-------------|---|-----|
| A.4.5.4.1 | UE UL carrier RRC reconfiguration Delay..... | 316 |
| A.4.5.4.1.1 | Test Purpose and Environment..... | 316 |
| A.4.5.4.1.2 | Test Requirements..... | 321 |
| A.4.5.5 | Beam Failure Detection and Link recovery procedures..... | 322 |
| A.4.5.5.2.2 | Test Requirements..... | 329 |
| A.4.5.7 | PSCell addition and release delay..... | 349 |
| A.4.5.7.1 | Addition and Release Delay of known NR PSCell..... | 349 |
| A.4.5.7.1.1 | Test purpose and environment..... | 349 |
| A.4.5.7.1.2 | Test Requirements..... | 353 |
| A.4.6 | Measurement procedure..... | 353 |
| A.4.6.1 | Intra-frequency Measurements..... | 353 |
| A.4.6.1.1 | EN-DC event triggered reporting tests without gap under non-DRX..... | 353 |
| A.4.6.1.1.1 | Test purpose and Environment..... | 353 |
| A.4.6.1.1.2 | Test parameters..... | 353 |
| A.4.6.1.1.3 | Test Requirements..... | 355 |
| A.4.6.1.2 | EN-DC event triggered reporting tests without gap under DRX..... | 355 |
| A.4.6.1.2.1 | Test purpose and Environment..... | 355 |
| A.4.6.1.2.2 | Test parameters..... | 356 |
| A.4.6.1.2.2 | Test Requirements..... | 358 |
| A.4.6.1.3 | EN-DC event triggered reporting tests with per-UE gaps under non-DRX..... | 358 |
| A.4.6.1.3.1 | Test purpose and Environment..... | 358 |
| A.4.6.1.3.2 | Test parameters..... | 358 |
| A.4.6.1.3.3 | Test Requirements..... | 360 |
| A.4.6.1.4 | EN-DC event triggered reporting tests with per-UE gaps under DRX..... | 361 |
| A.4.6.1.4.1 | Test purpose and Environment..... | 361 |
| A.4.6.1.4.2 | Test parameters..... | 361 |
| A.4.6.1.4.3 | Test Requirements..... | 363 |
| A.4.6.1.5 | EN-DC event triggered reporting tests without gap under non-DRX with SSB index reading..... | 363 |
| A.4.6.1.5.1 | Test purpose and Environment..... | 363 |
| A.4.6.1.5.2 | Test parameters..... | 363 |
| A.4.6.1.5.3 | Test Requirements..... | 365 |
| A.4.6.1.6 | EN-DC event triggered reporting tests with SSB index reading with per-UE gaps..... | 366 |
| A.4.6.1.6.1 | Test purpose and Environment..... | 366 |
| A.4.6.1.6.2 | Test parameters..... | 366 |
| A.4.6.1.6.3 | Test Requirements..... | 368 |
| A.4.6.2 | Inter-frequency Measurements..... | 369 |
| A.4.6.2.1 | EN-DC event triggered reporting tests for FR1 cell without SSB time index detection when DRX is not used..... | 369 |
| A.4.6.2.1.1 | Test Purpose and Environment..... | 369 |
| A.4.6.2.1.2 | Test Requirements..... | 372 |
| A.4.6.2.2 | EN-DC event triggered reporting tests for FR1 cell without SSB time index detection when DRX is used..... | 372 |
| A.4.6.2.2.1 | Test Purpose and Environment..... | 372 |
| A.4.6.2.2.2 | Test Requirements..... | 375 |
| A.4.6.2.3 | Void..... | 376 |
| A.4.6.2.4 | Void..... | 376 |
| A.4.6.2.5 | EN-DC event triggered reporting tests for FR1 cell with SSB time index detection when DRX is not used..... | 376 |
| A.4.6.2.5.1 | Test Purpose and Environment..... | 376 |
| A.4.6.2.5.2 | Test Requirements..... | 379 |
| A.4.6.2.6 | EN-DC event triggered reporting tests for FR1 cell with SSB time index detection when DRX is used..... | 379 |
| A.4.6.2.6.1 | Test Purpose and Environment..... | 379 |
| A.4.6.2.6.2 | Test Requirements..... | 383 |
| A.4.6.2.7 | Void..... | 383 |
| A.4.6.2.8 | Void..... | 383 |
| A.4.6.3 | L1-RSRP measurement for beam reporting..... | 383 |
| A.4.6.3.1 | SSB based L1-RSRP measurement when DRX is not used..... | 383 |
| A.4.6.3.1.1 | Test Purpose and Environment..... | 383 |
| A.4.6.3.1.2 | Test parameters..... | 383 |
| A.4.6.3.1.3 | Test Requirements..... | 386 |
| A.4.6.3.2 | SSB based L1-RSRP measurement when DRX is used..... | 386 |

| | | |
|-------------|---|-----|
| A.4.6.3.2.1 | Test Purpose and Environment..... | 386 |
| A.4.6.3.2.2 | Test parameters..... | 386 |
| A.4.6.3.2.3 | Test Requirements..... | 388 |
| A.4.6.3.3 | CSI-RS based L1-RSRP measurement when DRX is not used..... | 388 |
| A.4.6.3.3.1 | Test Purpose and Environment..... | 388 |
| A.4.6.3.3.2 | Test parameters..... | 389 |
| A.4.6.3.3.3 | Test Requirements..... | 391 |
| A.4.6.3.4 | CSI-RS based L1-RSRP measurement when DRX is used..... | 391 |
| A.4.6.3.4.1 | Test Purpose and Environment..... | 391 |
| A.4.6.3.4.2 | Test parameters..... | 391 |
| A.4.6.3.4.3 | Test Requirements..... | 394 |
| A.4.7 | Measurement Performance requirements..... | 394 |
| A.4.7.1 | SS-RSRP..... | 394 |
| A.4.7.1.1 | EN-DC Intra-frequency measurement accuracy with FR1 serving cell and FR1 target cell..... | 394 |
| A.4.7.1.1.1 | Test Purpose and Environment..... | 394 |
| A.4.7.1.1.2 | Test parameters..... | 394 |
| A.4.7.1.1.3 | Test Requirements..... | 397 |
| A.4.7.1.3 | Void..... | 401 |
| A.4.7.2 | SS-RSRQ..... | 401 |
| A.4.7.2.1 | EN-DC Intra-frequency measurement accuracy with FR1 serving cell and FR1 target cell..... | 401 |
| A.4.7.2.1.1 | Test Purpose and Environment..... | 401 |
| A.4.7.2.1.2 | Test Parameters..... | 401 |
| A.4.7.2.1.3 | Test Requirements..... | 404 |
| A.4.7.3 | SS-SINR..... | 404 |
| A.4.7.3.1 | EN-DC Intra-frequency measurement accuracy with FR1 serving cell and FR1 target cell..... | 404 |
| A.4.7.3.1.1 | Test Purpose and Environment..... | 404 |
| A.4.7.3.1.2 | Test Parameters..... | 404 |
| A.4.7.3.1.3 | Test Requirements..... | 407 |
| A.4.7.3.2 | EN-DC Inter-frequency measurement accuracy with FR1 serving cell and FR1 target cell..... | 407 |
| A.4.7.3.2.1 | Test Purpose and Environment..... | 407 |
| A.4.7.3.2.2 | Test Parameters..... | 407 |
| A.4.7.3.2.3 | Test Requirements..... | 410 |
| A.4.7.4 | L1-RSRP measurement for beam reporting..... | 411 |
| A.4.7.4.1 | SSB based L1-RSRP measurement..... | 411 |
| A.4.7.4.1.1 | Test Purpose and Environment..... | 411 |
| A.4.7.4.1.2 | Test parameters..... | 411 |
| A.4.7.4.1.3 | Test Requirements..... | 414 |
| A.4.7.4.2 | CSI-RS based L1-RSRP measurement on resource set with repetition off..... | 414 |
| A.4.7.4.2.1 | Test Purpose and Environment..... | 414 |
| A.4.7.4.2.2 | Test parameters..... | 414 |
| A.4.7.4.2.3 | Test Requirements..... | 417 |
| A.4.7.5 | SFTD accuracy..... | 417 |
| A.4.7.5.1 | SFTD accuracy..... | 417 |
| A.4.7.5.1.1 | Test Purpose and Environment..... | 417 |
| A.4.7.5.1.2 | Test Parameters..... | 417 |
| A.4.7.5.1.3 | Test Requirements..... | 420 |
| A.4.7.5.2 | Void..... | 420 |
| A.4.7.5.3 | Void..... | 420 |
| A.4.8 | Void..... | 420 |
| A.5 | EN-DC tests with one or more NR cells in FR2..... | 421 |
| A.5.1 | Void..... | 421 |
| A.5.2 | Void..... | 421 |
| A.5.3 | RRC_CONNECTED state mobility..... | 421 |
| A.5.3.1 | Void..... | 421 |
| A.5.3.2 | RRC Connection Mobility Control..... | 421 |
| A.5.3.2.1 | Void..... | 421 |
| A.5.3.2.2 | Random Access..... | 421 |
| A.5.3.2.2.1 | Contention based random access test in FR2 for PSCell/SCell in EN-DC..... | 421 |
| A.5.3.2.2.2 | Non-contention based random access test in FR2 for PSCell/SCell in EN-DC..... | 425 |
| A.5.3.2.3 | Void..... | 429 |
| A.5.4 | Timing..... | 429 |

| | | |
|---------------|--|-----|
| A.5.4.1 | UE transmit timing | 429 |
| A.5.4.1.1 | NR UE Transmit Timing Test for FR2 | 429 |
| A.5.4.1.1.1 | Test Purpose and environment | 429 |
| A.5.4.1.1.2 | Test requirements | 431 |
| A.5.4.2 | UE timer accuracy | 432 |
| A.5.4.3 | Timing advance | 432 |
| A.5.4.3.1 | EN-DC FR2 timing advance adjustment accuracy | 432 |
| A.5.4.3.1.1 | Test Purpose and Environment | 432 |
| A.5.4.3.1.2 | Test Parameters | 432 |
| A.5.4.3.1.3 | Test Requirements | 435 |
| A.5.5 | Signaling characteristics | 435 |
| A.5.5.1 | Radio link Monitoring | 435 |
| A.5.5.1.1 | Radio Link Monitoring Out-of-sync Test for FR2 PSCell configured with SSB-based RLM RS in non-DRX mode | 435 |
| A.5.5.1.1.1 | Test Purpose and Environment | 435 |
| A.5.5.1.1.2 | Test Requirements | 438 |
| A.5.5.1.2 | Radio Link Monitoring In-sync Test for FR2 PSCell configured with SSB-based RLM RS in non-DRX mode | 438 |
| A.5.5.1.2.1 | Test Purpose and Environment | 438 |
| A.5.5.1.2.2 | Test Requirements | 441 |
| A.5.5.1.3 | Radio Link Monitoring Out-of-sync Test for FR2 PSCell configured with SSB-based RLM RS in DRX mode | 441 |
| A.5.5.1.3.1 | Test Purpose and Environment | 441 |
| A.5.5.1.3.2 | Test Requirements | 445 |
| A.5.5.1.4 | Radio Link Monitoring In-sync Test for FR2 PSCell configured with SSB-based RLM RS in DRX mode | 445 |
| A.5.5.1.4.1 | Test Purpose and Environment | 445 |
| A.5.5.1.4.2 | Test Requirements | 448 |
| A.5.5.1.9 | EN-DC Radio Link Monitoring UE Scheduling Restrictions on FR2 | 463 |
| A.5.5.1.9.1 | Test Purpose and Environment | 463 |
| A.5.5.1.9.2 | Test Requirements | 465 |
| A.5.5.2 | Interruption | 465 |
| A.5.5.2.1 | E-UTRAN – NR FR2 interruptions at transitions between active and non-active during DRX in synchronous EN-DC | 465 |
| A.5.5.2.1.1 | Test Purpose and Environment | 465 |
| A.5.5.2.1.2 | Test Requirements | 467 |
| A.5.5.2.2 | E-UTRAN – NR FR2 interruptions at transitions between active and non-active during DRX in asynchronous EN-DC | 467 |
| A.5.5.2.2.1 | Test Purpose and Environment | 467 |
| A.5.5.2.2.2 | Test Requirements | 470 |
| A.5.5.2.3 | E-UTRAN – NR FR2 interruptions during measurements on deactivated NR SCC in synchronous EN-DC | 470 |
| A.5.5.2.3.1 | Test Purpose and Environment | 470 |
| A.5.5.2.3.2 | Test Requirements | 473 |
| A.5.5.2.4 | E-UTRAN – NR FR2 interruptions during measurements on deactivated NR SCC in asynchronous EN-DC | 474 |
| A.5.5.2.4.1 | Test Purpose and Environment | 474 |
| A.5.5.2.4.2 | Test Requirements | 477 |
| A.5.5.2.5 | E-UTRAN – NR FR2 interruptions during measurements on deactivated E-UTRAN SCC in synchronous EN-DC | 478 |
| A.5.5.2.5.1 | Test Purpose and Environment | 478 |
| A.5.5.2.5.2 | Test Requirements | 480 |
| A.5.5.2.6 | E-UTRAN – NR FR2 interruptions during measurements on deactivated E-UTRAN SCC in asynchronous EN-DC | 481 |
| A.5.5.2.6.1 | Test Purpose and Environment | 481 |
| A.5.5.2.6.2 | Test Requirements | 483 |
| A.5.5.4 | Void | 491 |
| A.5.5.5 | Beam Failure Detection and Link recovery procedures | 491 |
| A.5.5.6 | Active BWP switch | 510 |
| A.5.5.6.1 | DCI-based and Timer-based Active BWP Switch | 510 |
| A.5.5.6.1.1 | E-UTRAN – NR PSCell FR2 DL active BWP switch with non-DRX in synchronous EN-DC | 510 |
| A.5.5.6.1.1.1 | Test Purpose and Environment | 510 |

| | | |
|---------------|--|-----|
| A.5.5.6.1.1.2 | Test Requirements | 514 |
| A.5.5.6.1.2 | E-UTRAN – NR PSCell FR2 DL active BWP switch with FR2 SCell in non-DRX in synchronous EN-DC..... | 515 |
| A.5.5.6.2 | RRC-based Active BWP Switch..... | 519 |
| A.5.5.7 | PSCell addition and release delay..... | 522 |
| A.5.5.7.1 | Addition and Release Delay of NR PSCell..... | 522 |
| A.5.5.7.1.1 | Test purpose and environment..... | 522 |
| A.5.5.7.1.2 | Test Requirements..... | 525 |
| A.5.5.8 | Active TCI state switch delay..... | 526 |
| A.5.5.8.1 | MAC-CE based active TCI state switch..... | 526 |
| A.5.5.8.1.1 | E-UTRAN – NR PSCell FR2 active TCI state switch for a known TCI state..... | 526 |
| A.5.5.8.1.1.1 | Test Purpose and Environment | 526 |
| A.5.5.8.1.1.2 | Test Requirements | 528 |
| A.5.5.8.2 | RRC based active TCI state switch..... | 528 |
| A.5.5.8.2.1 | E-UTRAN – NR PSCell FR2 active TCI state switch for a known TCI state..... | 528 |
| A.5.5.8.2.1.1 | Test Purpose and Environment | 528 |
| A.5.5.8.2.1.2 | Test Requirements | 531 |
| A.5.6 | Measurement procedure | 531 |
| A.5.6.1 | Intra-frequency Measurements | 531 |
| A.5.6.1.1 | EN-DC event triggered reporting test without gap under non-DRX..... | 531 |
| A.5.6.1.1.1 | Test purpose and Environment..... | 531 |
| A.5.6.1.1.2 | Test Requirements..... | 533 |
| A.5.6.1.2 | EN-DC event triggered reporting test without gap under DRX..... | 533 |
| A.5.6.1.2.1 | Test purpose and Environment..... | 533 |
| A.5.6.1.2.2 | Test Requirements..... | 535 |
| A.5.6.1.3 | EN-DC event triggered reporting test with per-UE gaps under non-DRX..... | 536 |
| A.5.6.1.3.1 | Test purpose and Environment..... | 536 |
| A.5.6.1.3.2 | Test Requirements..... | 538 |
| A.5.6.1.4 | EN-DC event triggered reporting test with per-UE gaps under DRX..... | 539 |
| A.5.6.1.4.1 | Test purpose and Environment..... | 539 |
| A.5.6.1.4.2 | Test Requirements..... | 541 |
| A.5.6.2 | Inter-frequency Measurements..... | 542 |
| A.5.6.2.1 | EN-DC event triggered reporting tests for FR2 cell without SSB time index detection when DRX is not used | 542 |
| A.5.6.2.1.1 | Test Purpose and Environment..... | 542 |
| A.5.6.2.1.2 | Test Requirements..... | 545 |
| A.5.6.2.2 | EN-DC event triggered reporting tests for FR2 cell without SSB time index detection when DRX is used..... | 545 |
| A.5.6.2.2.1 | Test Purpose and Environment..... | 545 |
| A.5.6.2.2.2 | Test Requirements..... | 548 |
| A.5.6.2.3 | EN-DC event triggered reporting tests for FR2 cell with SSB time index detection when DRX is not used | 548 |
| A.5.6.2.3.1 | Test Purpose and Environment..... | 548 |
| A.5.6.2.3.2 | Test Requirements..... | 551 |
| A.5.6.2.4 | EN-DC event triggered reporting tests for FR2 cell with SSB time index detection when DRX is used | 551 |
| A.5.6.2.4.1 | Test Purpose and Environment..... | 551 |
| A.5.6.2.4.2 | Test Requirements..... | 555 |
| A.5.6.2.5 | EN-DC event triggered reporting tests for FR2 cell without SSB time index detection when DRX is not used | 555 |
| A.5.6.2.5.1 | Test Purpose and Environment..... | 555 |
| A.5.6.2.5.2 | Test Requirements..... | 559 |
| A.5.6.2.6 | EN-DC event triggered reporting tests for FR2 cell without SSB time index detection when DRX is used..... | 560 |
| A.5.6.2.6.1 | Test Purpose and Environment..... | 560 |
| A.5.6.2.6.2 | Test Requirements..... | 563 |
| A.5.6.2.7 | EN-DC event triggered reporting tests for FR2 cell with SSB time index detection when DRX is not used | 564 |
| A.5.6.2.7.1 | Test Purpose and Environment..... | 564 |
| A.5.6.2.7.2 | Test Requirements..... | 567 |
| A.5.6.2.8 | EN-DC event triggered reporting tests for FR2 cell with SSB time index detection when DRX is used | 568 |