



**Universal Mobile Telecommunications System (UMTS);
LTE;
5G;
UICC-terminal interface;
Universal Subscriber Identity Module (USIM)
application test specification
(3GPP TS 31.121 version 15.6.1 Release 15)**



ReferenceRTS/TSGC-0631121vf61

Keywords5G,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	22
Introduction	22
1 Scope	23
2 References	23
3 Definitions, symbols, abbreviations and coding.....	25
3.1 Definitions	25
3.2 Symbols.....	26
3.3 Abbreviations	26
3.4 Coding Conventions.....	28
3.5 Generic procedures for E-UTRAN/UTRAN/GERAN/IMS/NB-IoT/5G-NR.....	28
3.6 Applicability.....	29
3.6.1 Applicability of the present document	29
3.6.2 Applicability to terminal equipment	29
3.6.3 Applicability of the individual tests	29
3.7 Table of optional features.....	30
3.8 Applicability table	34
4 Default Values.....	66
4.1 Definition of default values for USIM-Terminal interface testing (Default UICC)	66
4.1.1 Values of the EF's (Default UICC).....	66
4.1.1.1 EF _{IMSI} (IMSI)	66
4.1.1.2 EF _{AD} (Administrative Data)	66
4.1.1.3 EF _{LOCI} (Location Information)	66
4.1.1.4 EF _{Keys} (Cipherring and Integrity Keys)	67
4.1.1.5 EF _{KeysPS} (Cipherring and Integrity Keys for Packet Switched domain).....	67
4.1.1.6 EF _{ACC} (Access Control Class).....	67
4.1.1.7 EF _{FPLMN} (Forbidden PLMNs).....	67
4.1.1.8 EF _{UST} (USIM Service Table).....	67
4.1.1.9 EF _{EST} (Enable Service Table).....	68
4.1.1.10 EF _{ADN} (Abbreviated Dialling Number).....	68
4.1.1.11 EF _{PLMNWACT} (User Controlled PLMN Selector with Access Technology)	68
4.1.1.12 EF _{OPLMNWACT} (Operator Controlled PLMN Selector with Access Technology).....	69
4.1.1.13 Void.....	69
4.1.1.14 PIN	69
4.1.1.15 PIN2	70
4.1.1.16 Unblock PIN	70
4.1.1.17 Unblock PIN2	70
4.1.1.18 Other Values of the USIM	70
4.1.1.19 EF _{PSLOCI} (Packet Switch Location Information).....	70
4.1.1.20 Universal PIN.....	70
4.1.1.21 Unblock Universal PIN.....	71
4.2 Definition of FDN UICC.....	71
4.2.1 Values of the EF's (FDN UICC).....	71
4.2.1.1 EF _{UST} (USIM Service Table)	71
4.2.1.2 EF _{EST} (Enable Service Table).....	71
4.2.1.3 EF _{FDN} (Fixed Dialling Numbers)	71
4.2.1.4 EF _{ECC} (Emergency Call Codes).....	72
4.2.1.5 Other Values of the USIM	72
4.3 Void.....	73
4.4 Definition of E-UTRAN/EPC UICC	73
4.4.1 EF _{UST} (USIM Service Table)	73

4.4.2	EF _{EPSLOCI} (EPS Information).....	73
4.4.3	EF _{PLMNwACT} (User Controlled PLMN Selector with Access Technology).....	73
4.4.4	EF _{OPLMNwACT} (Operator Controlled PLMN Selector with Access Technology).....	74
4.4.5	EF _{ACSGL} (Allowed CSG Lists).....	75
4.4.6	EF _{CSTGT} (CSG Type).....	75
4.4.7	EF _{HNB} (Home (e)NodeB Name).....	77
4.4.8	EF _{EPSNSC} (EPS NAS Security Context).....	78
4.5	Definition of E-UTRAN/EPC ISIM-UICC.....	79
4.5.1	Applications on the E-UTRAN/EPC ISIM-UICC.....	79
4.5.2	Default USIM values on E-UTRAN/EPC ISIM-UICC.....	79
4.5.3	Default ISIM values on E-UTRAN/EPC ISIM-UICC.....	79
4.5.3.1	EF _{AD} (Administrative Data).....	79
4.5.3.2	EF _{IST} (ISIM Service Table).....	79
4.5.3.3	EF _{IMPI} (IMS private user identity).....	79
4.5.3.4	EF _{DOMAIN} (Home Network Domain Name).....	80
4.5.3.5	EF _{IMPU} (IMS public user identity).....	80
4.5.3.6	EF _{P-CSCF} (P-CSCF ADDRESS).....	81
4.5.3.7	EF _{SMS} (Short Message Service).....	81
4.5.3.8	EF _{SMSR} (Short message status reports).....	81
4.5.3.9	EF _{SMSp} (Short message service parameters).....	82
4.5.3.10	EF _{SMSs} (SMS Status).....	82
4.5.4	Default values at DF_TELECOM.....	82
4.5.4.1	EF _{PSISMSC} (Public Service Identity of the SM-SC).....	82
4.6	Definition of ACSGL/OCSGL E-UTRAN/EPC UICC.....	83
4.6.1	EF _{UST} (USIM Service Table).....	83
4.6.2	EF _{AD} (Administrative Data).....	83
4.6.3	EF _{OCSGL} (Operator CSG Lists).....	83
4.6.4	EF _{OCSGT} (Operator CSG Type).....	84
4.6.5	EF _{OHNB} (Operator Home (e)NodeB Name).....	85
4.7.1	Values of the EFs.....	87
4.7.1.1	EF _{UST} (USIM Service Table).....	87
4.7.1.2	EF _{NASCONFIG} (Non Access Stratum Configuration).....	87
4.9.1	EF _{UST} (USIM Service Table).....	94
4.9.2	EF _{IMSI} (IMSI).....	95
4.9.3	EF _{SGS3GPPLOCI} (5GS 3GPP location information).....	95
4.9.4	EF _{SUCI_Calc_Info} (Subscription Concealed Identifier Calculation Information EF).....	95
4.9.5	EF _{Routing_Indicator} (Routing Indicator EF).....	96
5	Subscription related tests.....	96
5.1	IMSI / TMSI handling.....	96
5.1.1	UE identification by short IMSI.....	96
5.1.1.1	Definition and applicability.....	96
5.1.1.2	Conformance requirement.....	97
5.1.1.3	Test purpose.....	97
5.1.1.4	Method of test.....	97
5.1.1.4.1	Initial conditions.....	97
5.1.1.4.2	Procedure.....	97
5.1.1.5	Acceptance criteria.....	98
5.1.2	UE identification by short IMSI using a 2 digit MNC.....	98
5.1.2.1	Definition and applicability.....	98
5.1.2.2	Conformance requirement.....	98
5.1.2.3	Test purpose.....	98
5.1.2.4	Method of test.....	98
5.1.2.4.1	Initial conditions.....	98
5.1.2.4.2	Procedure.....	99
5.1.2.5	Acceptance criteria.....	99
5.1.3	UE identification by "short" TMSI.....	99
5.1.3.1	Definition and applicability.....	99
5.1.3.2	Conformance requirement.....	100
5.1.3.3	Test purpose.....	100
5.1.3.4	Method of test.....	100
5.1.3.4.1	Initial conditions.....	100

5.1.3.4.2	Procedure.....	100
5.1.3.5	Acceptance criteria.....	101
5.1.4	UE identification by "long" TMSI.....	101
5.1.4.1	Definition and applicability.....	101
5.1.4.2	Conformance requirement.....	101
5.1.4.3	Test purpose.....	101
5.1.4.4	Method of test.....	101
5.1.4.4.1	Initial conditions.....	101
5.1.4.4.2	Procedure.....	102
5.1.4.5	Acceptance criteria.....	102
5.1.5	UE identification by long IMSI, TMSI updating and key set identifier assignment.....	102
5.1.5.1	Definition and applicability.....	102
5.1.5.2	Conformance requirement.....	103
5.1.5.3	Test purpose.....	103
5.1.5.4	Method of test.....	103
5.1.5.4.1	Initial conditions.....	103
5.1.5.4.2	Procedure.....	104
5.1.5.5	Acceptance criteria.....	105
5.1.6	UE identification by short IMSI when accessing E-UTRAN/EPC.....	105
5.1.6.1	Definition and applicability.....	105
5.1.6.2	Conformance requirement.....	105
5.1.6.3	Test purpose.....	106
5.1.6.4	Method of test.....	106
5.1.6.4.1	Initial conditions.....	106
5.1.6.4.2	Procedure.....	106
5.1.6.5	Acceptance criteria.....	106
5.1.7	UE identification by short IMSI using a 2 digit MNC when accessing E-UTRAN/EPC.....	107
5.1.7.1	Definition and applicability.....	107
5.1.7.2	Conformance requirement.....	107
5.1.7.3	Test purpose.....	107
5.1.7.4	Method of test.....	107
5.1.7.4.1	Initial conditions.....	107
5.1.7.4.2	Procedure.....	108
5.1.7.5	Acceptance criteria.....	108
5.1.8	UE identification after changed IMSI with service "EMM Information" not available.....	108
5.1.8.2	Conformance requirement.....	108
5.1.8.3	Test purpose.....	109
5.1.8.4	Method of test.....	109
5.1.8.4.1	Initial conditions.....	109
5.1.8.4.2	Procedure.....	109
5.1.8.5	Acceptance criteria.....	109
5.1.9	UE identification by GUTI when using USIM with service "EMM Information" not available.....	110
5.1.9.2	Conformance requirement.....	110
5.1.9.3	Test purpose.....	110
5.1.9.4	Method of test.....	110
5.1.9.4.1	Initial conditions.....	110
5.1.9.4.2	Procedure.....	110
5.1.9.5	Acceptance criteria.....	111
5.1.10	UE identification by GUTI when using USIM with service "EMM Information" available.....	111
5.1.10.1	Definition and applicability.....	111
5.1.10.2	Conformance requirement.....	111
5.1.10.3	Test purpose.....	112
5.1.10.4	Method of test.....	112
5.1.10.4.1	Initial conditions.....	112
5.1.10.4.2	Procedure.....	112
5.1.10.5	Acceptance criteria.....	112
5.2	Access Control handling.....	113
5.2.1	Access Control information handling.....	113
5.2.1.1	Definition and applicability.....	113
5.2.1.2	Conformance requirement.....	113
5.2.1.3	Test purpose.....	114
5.2.1.4	Method of test.....	114

5.2.1.4.1	Initial conditions	114
5.2.1.4.2	Coding details	114
5.2.1.4.3	Procedure	115
5.2.1.5	Acceptance criteria	115
5.2.2	Access Control information handling for E-UTRAN/EPC	127
5.2.2.1	Definition and applicability	127
5.2.2.2	Conformance requirement	127
5.2.2.3	Test purpose	127
5.2.2.4	Method of test	128
5.2.2.4.1	Initial conditions	128
5.2.2.4.2	Coding details	128
5.2.2.4.3	Procedure	128
5.2.2.5	Acceptance criteria	128
5.3	Handling subscription identifier privacy for 5G	153
5.3.1	SUCI calculation by ME using null scheme	153
5.3.1.1	Definition and applicability	153
5.3.1.2	Conformance requirement	153
5.3.1.3	Test purpose	154
5.3.1.4	Method of test	154
5.3.1.4.1	Initial conditions	154
5.3.1.4.2	Procedure	155
5.3.1.5	Acceptance criteria	155
5.3.2	SUCI calculation by ME using Profile B	156
5.3.2.1	Definition and applicability	156
5.3.2.2	Conformance requirement	156
5.3.2.3	Test purpose	156
5.3.2.4	Method of test	156
5.3.2.4.1	Initial conditions	156
5.3.2.4.2	Procedure	157
5.3.2.5	Acceptance criteria	157
5.3.3	UE identification by SUCI during initial registration – SUCI calculation by USIM	157
5.3.3.1	Definition and applicability	157
5.3.3.2	Conformance requirement	157
5.3.3.3	Test purpose	157
5.3.3.4	Method of test	158
5.3.3.4.1	Initial conditions	158
5.3.3.4.2	Procedure	159
5.3.3.5	Acceptance criteria	159
5.3.4	UE identification by SUCI in response to IDENTITY REQUEST message	159
5.3.4.1	Definition and applicability	159
5.3.4.2	Conformance requirement	159
5.3.4.3	Test purpose	160
5.3.4.4	Method of test	160
5.3.4.4.1	Initial conditions	160
5.3.4.4.2	Procedure	161
5.3.4.5	Acceptance criteria	161
5.3.5	UE identification by SUCI in response to IDENTITY REQUEST message with T3519 timer expiry	161
5.3.5.1	Definition and applicability	161
5.3.5.2	Conformance requirement	162
5.3.5.3	Test purpose	162
5.3.5.4	Method of test	162
5.3.5.4.1	Initial conditions	162
5.3.5.4.2	Procedure	163
5.3.5.5	Acceptance criteria	164
5.3.6	UE identification by SUCI in response to IDENTITY REQUEST message and AUTHENTICATION REJECT	164
5.3.6.1	Definition and applicability	164
5.3.6.2	Conformance requirement	164
5.3.6.3	Test purpose	164
5.3.6.4	Method of test	165
5.3.6.4.1	Initial conditions	165
5.3.6.4.2	Procedure	165

5.3.6.5	Acceptance criteria.....	166
5.3.7	SUCI calculation by the ME using null scheme – missing parameters for subscription identifier privacy support by the USIM.....	166
5.3.7.1	Definition and applicability.....	166
5.3.7.2	Conformance requirement.....	166
5.3.7.3	Test purpose	166
5.3.7.4	Method of test	166
5.3.7.4.1	Initial conditions.....	166
5.3.7.4.2	Procedure.....	167
5.3.7.5	Acceptance criteria.....	167
5.3.8	UE identification by 5G-GUTI – Last Registered TAI stored on USIM	167
5.3.8.1	Definition and applicability.....	167
5.3.8.2	Conformance requirement.....	167
5.3.8.3	Test purpose	168
5.3.8.4	Method of test	168
5.3.8.4.1	Initial conditions.....	168
5.3.8.4.2	Procedure.....	168
5.3.8.5	Acceptance criteria.....	168
5.3.9	UE identification by 5G-GUTI – Last Registered TAI stored by ME	169
5.3.9.1	Definition and applicability.....	169
5.3.9.3	Test purpose	169
5.3.9.4	Method of test	169
5.3.9.4.1	Initial conditions.....	169
5.3.9.4.2	Procedure.....	169
5.3.9.5	Acceptance criteria.....	170
5.3.10	UE identification after SUPI is changed	170
5.3.10.1	Definition and applicability.....	170
5.3.10.2	Conformance requirement.....	170
5.3.10.3	Test purpose	171
5.3.10.4	Method of test	171
5.3.10.4.1	Initial conditions.....	171
5.3.10.4.2	Procedure.....	171
5.3.10.5	Acceptance criteria.....	171
5.3.11	SUCI calculation by ME using Profile A	171
5.3.11.1	Definition and applicability.....	171
5.3.11.2	Conformance requirement.....	172
5.3.11.3	Test purpose	172
5.3.11.4	Method of test	172
5.3.11.4.1	Initial conditions.....	172
5.3.11.4.2	Procedure.....	173
5.3.11.5	Acceptance criteria.....	173
5.4	Unified Access Control information handling for 5G-NR	173
5.4.1	Unified Access Control – Access identity 0, no access identities indicated by USIM	173
5.4.1.1	Definition and applicability.....	173
5.4.1.2	Conformance requirement.....	174
5.4.1.3	Test purpose	174
5.4.1.4	Method of test	174
5.4.1.4.1	Initial conditions.....	174
5.4.1.4.2	Procedure.....	176
5.4.1.4.3	Acceptance criteria.....	176
5.4.2	Unified Access Control – Access Identity 1 – MPS indicated by USIM.....	177
5.4.2.1	Definition and applicability.....	177
5.4.2.2	Conformance requirement.....	177
5.4.2.3	Test purpose	178
5.4.2.4	Method of test	178
5.4.2.4.1	Initial conditions.....	178
5.4.2.4.2	Procedure.....	179
5.4.2.4.3	Acceptance criteria.....	180
5.4.3	FFS.....	181
5.4.4	FFS.....	181
5.4.5	Unified Access Control – Access Identity 2 – MCS indicated by USIM	181
5.4.5.1	Definition and applicability.....	181

5.4.5.2	Conformance requirement.....	182
5.4.5.3	Test purpose	182
5.4.5.4	Method of test	183
5.4.5.4.1	Initial conditions	183
5.4.5.4.2	Procedure.....	184
5.4.5.4.3	Acceptance criteria	184
5.4.6	FFS.....	186
5.4.7	FFS.....	186
5.4.8	Unified Access Control – Access Identities 11 and 15 indicated by USIM.....	186
5.4.8.1	Definition and applicability.....	186
5.4.8.2	Conformance requirement.....	186
5.4.8.3	Test purpose	187
5.4.8.4	Method of test	187
5.4.8.4.1	Initial conditions	187
5.4.8.4.2	Procedure.....	188
5.4.8.4.3	Acceptance criteria	188
5.4.9	Unified Access Control – Access Identities 12, 13 and 14 indicated by USIM.....	190
5.4.9.1	Definition and applicability.....	190
5.4.9.2	Conformance requirement.....	190
5.4.9.3	Test purpose	191
5.4.9.4	Method of test	191
5.4.9.4.1	Initial conditions	191
5.4.9.4.2	Procedure.....	192
5.4.9.4.3	Acceptance criteria	193
5.4.10	FFS.....	195
5.4.11	FFS.....	195
6	Security related Tests	195
6.1	PIN handling	195
6.1.1	Entry of PIN.....	195
6.1.1.1	Definition and applicability.....	195
6.1.1.2	Conformance requirement.....	195
6.1.1.3	Test purpose	195
6.1.1.4	Method of test	195
6.1.1.4.1	Initial conditions	195
6.1.1.4.2	Procedure.....	195
6.1.1.5	Acceptance criteria.....	196
6.1.2	Change of PIN	196
6.1.2.1	Definition and applicability.....	196
6.1.2.2	Conformance requirement.....	196
6.1.2.3	Test purpose	196
6.1.2.4	Method of test	196
6.1.2.4.1	Initial conditions.....	196
6.1.2.4.2	Procedure.....	196
6.1.2.5	Acceptance criteria.....	196
6.1.3	Unblock PIN	197
6.1.3.1	Definition and applicability.....	197
6.1.3.2	Conformance requirement.....	197
6.1.3.3	Test purpose	197
6.1.3.4	Method of test	197
6.1.3.4.1	Initial conditions	197
6.1.3.4.2	Procedure.....	197
6.1.3.5	Acceptance criteria.....	198
6.1.4	Entry of PIN2.....	198
6.1.4.1	Definition and applicability.....	198
6.1.4.2	Conformance requirement.....	198
6.1.4.3	Test purpose	198
6.1.4.4	Method of test	199
6.1.4.4.1	Initial conditions	199
6.1.4.4.2	Procedure.....	199
6.1.4.5	Acceptance criteria.....	199
6.1.5	Change of PIN2	199

6.1.5.1	Definition and applicability.....	199
6.1.5.2	Conformance requirement.....	199
6.1.5.3	Test purpose	199
6.1.5.4	Method of test	199
6.1.5.4.1	Initial conditions.....	199
6.1.5.4.2	Procedure.....	200
6.1.5.5	Acceptance criteria.....	200
6.1.6	Unblock PIN2	200
6.1.6.1	Definition and applicability.....	200
6.1.6.2	Conformance requirement.....	200
6.1.6.3	Test purpose	200
6.1.6.4	Method of test	200
6.1.6.4.1	Initial conditions.....	200
6.1.6.4.2	Procedure.....	201
6.1.6.5	Acceptance criterias	201
6.1.7	Replacement of PIN.....	202
6.1.7.1	Definition and applicability.....	202
6.1.7.2	Conformance requirement.....	202
6.1.7.3	Test purpose	202
6.1.7.4	Method of test	202
6.1.7.4.1	Initial conditions.....	202
6.1.7.4.2	Procedure.....	202
6.1.7.5	Acceptance criteria.....	202
6.1.8	Change of Universal PIN.....	203
6.1.8.1	Definition and applicability.....	203
6.1.8.2	Conformance requirement.....	203
6.1.8.3	Test purpose	203
6.1.8.4	Method of test	203
6.1.8.4.1	Initial conditions.....	203
6.1.8.4.2	Procedure.....	203
6.1.8.5	Acceptance criteria.....	204
6.1.9	Unblock Universal PIN.....	204
6.1.9.1	Definition and applicability.....	204
6.1.9.2	Conformance requirement.....	204
6.1.9.3	Test purpose	204
6.1.9.4	Method of test	204
6.1.9.4.1	Initial conditions.....	204
6.1.9.4.2	Procedure.....	204
6.1.9.5	Acceptance criteria.....	205
6.1.10	Entry of PIN on multi-verification capable UICCs.....	205
6.1.10.1	Definition and applicability.....	205
6.1.10.2	Conformance requirement.....	205
6.1.10.3	Test purpose	205
6.1.10.4	Method of test	205
6.1.10.4.1	Initial conditions.....	205
6.1.10.4.2	Procedure.....	206
6.1.10.5	Acceptance criteria.....	206
6.1.11	Change of PIN on multi-verification capable UICCs	206
6.1.11.1	Definition and applicability.....	206
6.1.11.2	Conformance requirement.....	206
6.1.11.3	Test purpose	207
6.1.11.4	Method of test	207
6.1.11.4.1	Initial conditions.....	207
6.1.11.4.2	Procedure.....	207
6.1.11.5	Acceptance criteria.....	208
6.1.12	Unblock PIN on multi-verification capable UICCs	208
6.1.12.1	Definition and applicability.....	208
6.1.12.2	Conformance requirement.....	208
6.1.12.3	Test purpose	208
6.1.12.4	Method of test	208
6.1.12.4.1	Initial conditions.....	208
6.1.12.4.2	Procedure.....	209

6.1.12.5	Acceptance criteria.....	210
6.1.13	Entry of PIN2 on multi-verification capable UICCs.....	210
6.1.13.1	Definition and applicability.....	210
6.1.13.2	Conformance requirement.....	210
6.1.13.3	Test purpose	210
6.1.13.4	Method of test	210
6.1.13.4.1	Initial conditions	210
6.1.13.4.2	Procedure.....	211
6.1.13.5	Acceptance criteria.....	211
6.1.14	Change of PIN2 on multi-verification capable UICCs	212
6.1.14.1	Definition and applicability.....	212
6.1.14.2	Conformance requirement.....	212
6.1.14.3	Test purpose	212
6.1.14.4	Method of test	212
6.1.14.4.1	Initial conditions	212
6.1.14.4.2	Procedure.....	213
6.1.14.5	Acceptance criteria.....	213
6.1.15	Unblock PIN2 on multi-verification capable UICCs	213
6.1.15.1	Definition and applicability.....	213
6.1.15.2	Conformance requirement.....	213
6.1.15.3	Test purpose	214
6.1.15.4	Method of test	214
6.1.15.4.1	Initial conditions	214
6.1.15.4.2	Procedure.....	215
6.1.15.5	Acceptance criterias	215
6.1.16	Replacement of PIN with key reference "07".....	216
6.1.16.1	Definition and applicability.....	216
6.1.16.2	Conformance requirement.....	216
6.1.16.3	Test purpose	216
6.1.16.4	Method of test	216
6.1.16.4.1	Initial conditions	216
6.1.16.4.2	Procedure.....	217
6.1.16.5	Acceptance criteria.....	217
6.2	Fixed Dialling Numbers (FDN) handling.....	218
6.2.1	Terminal and USIM with FDN enabled, EF _{ADN} readable and updateable	218
6.2.1.1	Definition and applicability.....	218
6.2.1.2	Conformance requirement.....	218
6.2.1.3	Test purpose	218
6.2.1.4	Method of test	219
6.2.1.4.1	Initial conditions	219
6.2.1.4.2	Procedure.....	219
6.2.1.5	Acceptance criteria.....	219
6.2.2	Terminal and USIM with FDN disabled.....	220
6.2.2.1	Definition and applicability.....	220
6.2.2.2	Conformance requirement.....	220
6.2.2.3	Test purpose	220
6.2.2.4	Method of test	220
6.2.2.4.1	Initial conditions	220
6.2.2.4.2	Procedure.....	221
6.2.2.5	Acceptance criteria.....	221
6.2.3	Enabling, disabling and updating of FDN	221
6.2.3.1	Definition and applicability.....	221
6.2.3.2	Conformance requirement.....	221
6.2.3.3	Test purpose	221
6.2.3.4	Method of test	222
6.2.3.4.1	Initial conditions	222
6.2.3.4.2	Procedure.....	222
6.2.3.5	Acceptance criteria.....	222
6.2.4	Terminal and USIM with FDN enabled, EF _{ADN} readable and updateable (Rel-4 and onwards)	222
6.2.4.1	Definition and applicability.....	222
6.2.4.2	Conformance requirement.....	222
6.2.4.3	Test purpose	223

6.2.4.4	Method of test	223
6.2.4.4.1	Initial conditions	223
6.2.4.4.2	Procedure	223
6.2.4.5	Acceptance criteria	224
6.3	Void	224
6.4	Advice of charge (AoC) handling	224
6.4.1	AoC not supported by USIM	224
6.4.1.1	Definition and applicability	224
6.4.1.2	Conformance requirement	224
6.4.1.3	Test purpose	225
6.4.1.4	Method of test	225
6.4.1.4.1	Initial conditions	225
6.4.1.4.2	Procedure	225
6.4.1.5	Acceptance criteria	226
6.4.2	Maximum frequency of ACM updating	226
6.4.2.1	Definition and applicability	226
6.4.2.2	Conformance requirement	226
6.4.2.3	Test purpose	226
6.4.2.4	Method of test	226
6.4.2.4.1	Initial conditions	226
6.4.2.4.2	Procedure	227
6.4.2.5	Acceptance criteria	229
6.4.3	Call terminated when ACM greater than ACMmax	229
6.4.3.1	Definition and applicability	229
6.4.3.2	Conformance requirement	229
6.4.3.3	Test purpose	229
6.4.3.4	Method of test	230
6.4.3.4.1	Initial conditions	230
6.4.3.4.2	Procedure	230
6.4.3.5	Acceptance criteria	232
6.4.4	Response codes of increase command of ACM	232
6.4.4.1	Definition and applicability	232
6.4.4.2	Conformance requirement	233
6.4.4.3	Test purpose	233
6.4.4.4	Method of test	233
6.4.4.4.1	Initial conditions	233
6.4.4.4.2	Procedure	234
6.4.4.5	Acceptance criteria	236
7	PLMN related tests	237
7.1	FPLMN handling	237
7.1.1	Adding FPLMN to the Forbidden PLMN list	237
7.1.1.1	Definition and applicability	237
7.1.1.2	Conformance requirement	237
7.1.1.3	Test purpose	239
7.1.1.4	Method of test	239
7.1.1.4.1	Initial conditions	239
7.1.1.4.2	Procedure	240
7.1.1.5	Acceptance criteria	243
7.1.2	UE updating forbidden PLMNs	245
7.1.2.1	Definition and applicability	245
7.1.2.2	Conformance requirement	246
7.1.2.3	Test purpose	246
7.1.2.4	Method of test	246
7.1.2.4.1	Initial conditions	246
7.1.2.4.2	Procedure	247
7.1.2.5	Acceptance criteria	248
7.1.3	UE deleting forbidden PLMNs	248
7.1.3.1	Definition and applicability	248
7.1.3.2	Conformance requirement	249
7.1.3.3	Test purpose	249
7.1.3.4	Method of test	250

7.1.3.4.1	Initial conditions	250
7.1.3.4.2	Procedure	250
7.1.3.5	Acceptance criteria	251
7.1.4	Adding FPLMN to the forbidden PLMN list when accessing E-UTRAN	252
7.1.4.1	Definition and applicability	252
7.1.4.2	Conformance requirement	253
7.1.4.3	Test purpose	253
7.1.4.4	Method of test	253
7.1.4.4.1	Initial conditions	253
7.1.4.4.2	Procedure	254
7.1.4.5	Acceptance criteria	255
7.1.5	UE updating forbidden PLMNs when accessing E-UTRAN	255
7.1.5.1	Definition and applicability	255
7.1.5.2	Conformance requirement	255
7.1.5.3	Test purpose	256
7.1.5.4	Method of test	256
7.1.5.4.1	Initial conditions	256
7.1.5.4.2	Procedure	256
7.1.5.5	Acceptance criteria	256
7.1.6	UE deleting forbidden PLMNs when accessing E-UTRAN	257
7.1.6.1	Definition and applicability	257
7.1.6.2	Conformance requirement	257
7.1.6.3	Test purpose	257
7.1.6.4	Method of test	258
7.1.6.4.1	Initial conditions	258
7.1.6.4.2	Procedure	258
7.1.6.5	Acceptance criteria	258
7.1.7	Updating the Forbidden PLMN list after receiving non-integrity protected reject message – UTRAN ..	259
7.1.7.1	Definition and applicability	259
7.1.7.2	Conformance requirement	259
7.1.7.3	Test purpose	260
7.1.7.4	Method of test	260
7.1.7.4.1	Initial conditions	260
7.1.7.4.2	Procedure	260
7.1.7.5	Acceptance criteria	261
7.1.8	Updating the Forbidden PLMN list after receiving non-integrity protected reject message – E- UTRAN	261
7.1.8.1	Definition and applicability	261
7.1.8.2	Conformance requirement	261
7.1.8.3	Test purpose	262
7.1.8.4	Method of test	262
7.1.8.4.1	Initial conditions	262
7.1.8.4.2	Procedure	263
7.1.8.5	Acceptance criteria	263
7.2	User controlled PLMN selector handling	264
7.2.1	UE updating the User controlled PLMN selector list	264
7.2.1.1	Definition and applicability	264
7.2.1.2	Conformance requirement	264
7.2.1.3	Test purpose	264
7.2.1.4	Method of test	264
7.2.1.4.1	Initial conditions	264
7.2.1.4.2	Procedure	264
7.2.1.5	Acceptance criteria	264
7.2.2	UE recognising the priority order of the User controlled PLMN selector list with the same access technology	265
7.2.2.1	Definition and applicability	265
7.2.2.2	Conformance requirement	265
7.2.2.3	Test purpose	265
7.2.2.4	Method of test	265
7.2.2.4.1	Initial conditions	265
7.2.2.4.2	Procedure	266
7.2.2.5	Acceptance criteria	268