

# ETSI EN 302 217-1 V3.3.1 (2021-10)



**Fixed Radio Systems;  
Characteristics and requirements for  
point-to-point equipment and antennas;  
Part 1: Overview, common characteristics and  
requirements not related to access to radio spectrum**

ETSI EN 302 217-1 V3.3.1 (2021-10)  
ETSI, 65 rue de Mantes, 92161 Issy-les-Moulineaux Cedex 13, France  
7ecc9766e556/etsi-en-302-217-1-v3-3-1-2021-10

---

**Reference**

REN/ATTM-0449

---

**Keywords**antenna, DFRS, DRRS, FWA, point-to-point, radio,  
transmission**ETSI**650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° w061004871

---

**Important notice**

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

---

**Notice of disclaimer & limitation of liability**

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.  
All rights reserved.

# Contents

Intellectual Property Rights .....	7
Foreword.....	7
Modal verbs terminology.....	8
1 Scope .....	9
2 References .....	9
2.1 Normative references .....	9
2.2 Informative references.....	11
3 Definition of terms, symbols and abbreviations.....	14
3.1 Terms.....	14
3.2 Symbols.....	20
3.3 Abbreviations .....	20
4 Structure and applicability of the ETSI EN 302 217 series.....	23
4.1 Generality .....	23
4.2 Cross references to previously relevant ENs and TSs .....	24
4.3 Summary of system options provided .....	24
4.4 User's guide .....	28
5 General characteristics .....	30
5.1 Frequency bands and channel arrangements .....	30
5.2 Special compatibility requirements between systems .....	30
5.3 Transmission capacity and spectral efficiency .....	30
5.4 Performance and availability requirements .....	30
5.5 Environmental profiles .....	31
5.5.0 Introduction.....	31
5.5.1 Environmental profile under Directive 2014/53/EU.....	31
5.5.2 ETSI standardized environmental profiles .....	31
5.5.2.0 Generality.....	31
5.5.2.1 Equipment intended for telecommunications applications installed in weather-protected locations (indoor locations) .....	32
5.5.2.2 Equipment intended for telecommunications applications installed in not-weather-protected locations (outdoor locations).....	32
5.5.3 Test environment profiles .....	32
5.6 Power supply .....	32
5.6.0 Introduction.....	32
5.6.1 Power supply profile under Directive 2014/53/EU.....	32
5.6.2 ETSI power supply profile.....	32
5.7 System block diagram .....	32
6 Baseband interfaces and parameters.....	33
6.0 Introduction .....	33
6.1 Ethernet interfaces .....	33
6.2 Plesiochronous interfaces .....	33
6.3 Synchronous digital hierarchy interfaces .....	34
6.4 Other baseband data interfaces.....	34
7 Main requirements.....	34
7.0 Introduction .....	34
7.1 General requirements .....	34
7.1.1 System identification .....	34
7.1.2 System nominal loading.....	35
7.1.3 Environmental profile .....	35
7.2 Transmitter characteristics.....	35
7.2.1 Transmitter power and power tolerance.....	35
7.2.1.1 Transmitter maximum power and EIRP.....	35
7.2.1.2 Transmitter combined output power and EIRP limits.....	35

7.2.1.3	Transmitter output power environmental variation .....	35
7.2.2	Transmitter power and frequency control .....	36
7.2.2.1	Transmitter Power and Frequency Control (ATPC, RTPC and RFC) .....	36
7.2.2.1.1	Automatic Transmit Power Control (ATPC) .....	36
7.2.2.1.2	Remote Transmit Power Control (RTPC) .....	37
7.2.2.1.3	Transmitter Remote Frequency Control (RFC) .....	37
7.2.3	Transmitter Radio Frequency spectrum mask .....	37
7.2.4	Transmitter discrete CW components exceeding the spectrum mask limit .....	37
7.2.4.1	Transmitter discrete CW components at the symbol rate .....	37
7.2.4.2	Transmitter other discrete CW components exceeding the spectrum mask limit .....	37
7.2.5	Transmitter unwanted emissions in the spurious domain .....	37
7.2.6	Transmitter dynamic change of modulation order .....	37
7.2.7	Transmitter radio frequency tolerance .....	37
7.2.8	Transmitter emission limitations outside the allocated band .....	38
7.3	Receiver characteristics .....	38
7.3.1	Unwanted emissions in the spurious domain .....	38
7.3.2	Receiver BER as a function of Receiver Signal Level (RSL) .....	38
7.3.3	Receiver selectivity .....	38
7.3.3.1	Introduction .....	38
7.3.3.2	Receiver co-channel, first and second adjacent channel interference sensitivity .....	38
7.3.3.3	Blocking (CW spurious interference sensitivity) .....	38
7.4	Antenna directional characteristics .....	38
8	Complementary requirements .....	39
8.0	Introduction .....	39
8.1	Branching/feeder requirements .....	39
8.1.1	Waveguide flanges (or other connectors) .....	39
8.1.2	Return loss of feeder/antenna systems at equipment antenna port (C/C reference point) .....	40
8.2	Intermodulation products .....	41
8.3	Transmitter characteristics .....	41
8.3.1	Unwanted emissions - internal .....	41
8.3.2	Transmitter Radio Frequency (RF) spectrum mask when mixed manufacturer compatibility is required .....	41
8.4	Receiver characteristics .....	42
8.4.1	Receiver maximum input level and input level range .....	42
8.4.2	Unwanted emissions - internal .....	43
8.4.3	Image rejection .....	43
8.4.4	Innermost channel selectivity .....	44
8.5	System performance without diversity .....	44
8.5.1	Equipment Residual BER (RBER) .....	44
8.5.2	Distortion sensitivity .....	46
8.5.2.1	Introduction .....	46
8.5.2.2	Requirement .....	46
8.5.2.3	Assessment .....	48
8.5.3	Interference sensitivity for CCDP with XPIC operation .....	48
8.5.3.1	General .....	48
8.5.3.2	Co-channel "internal" interference sensitivity in flat fading conditions .....	48
8.6	System characteristics with diversity .....	49
8.6.0	Introduction .....	49
8.6.1	Differential delay compensation .....	49
8.6.2	BER performance .....	49
<b>Annex A (normative):</b>	<b>Transmitter Radio Frequency spectrum masks and receiver selectivity when mixed manufacturer compatibility is required .....</b>	<b>50</b>
A.0	Introduction .....	50
A.1	Transmitter Radio Frequency masks assessment .....	51
A.2	Normal channels - Emission mask floor .....	51
A.2.1	RBER impact .....	51
A.2.2	Local TX to RX compatibility .....	51
A.2.2.1	Spectrum mask .....	51

A.2.2.2	Receiver selectivity.....	52
A.3	Innermost channels for channel arrangements from about 4 GHz to about 8,5 GHz with channel separation of 28 MHz to 30 MHz.....	52
A.3.0	Introduction.....	52
A.3.1	Innermost channels spectrum masks.....	52
A.3.2	Receiver innermost channel selectivity.....	54
A.4	Innermost channels for channel arrangements from about 4 GHz to 11 GHz with channel separation of 40 MHz.....	55
A.4.0	Introduction.....	55
A.4.1	Innermost channels spectrum masks.....	55
A.4.2	Receiver innermost channels selectivity.....	56
A.5	Innermost channels for 18 GHz channel arrangements with channel separation of 55 MHz.....	57
A.5.0	Introduction.....	57
A.5.1	Innermost channels spectrum masks.....	57
A.5.2	Receiver innermost channels selectivity.....	58
<b>Annex B (normative):</b>	<b>Definition of equivalent data rates for packet data, PDH/SDH and other signals on the traffic interface.....</b>	<b>60</b>
<b>Annex C (informative):</b>	<b>Information on <i>Multi-channel</i> and <i>Channels-aggregation</i> differences and operation.....</b>	<b>61</b>
C.1	Multi-channel and Channels-aggregation (two channel case).....	61
C.2	Channels-aggregation (more than two channels case).....	62
<b>Annex D (informative):</b>	<b>Additional information on relevant characteristics and operation.....</b>	<b>65</b>
D.1	Residual Bit Error Ratio (RBER) and Residual Frame Error Ratio (RFER).....	65
D.2	Measurement test set for XPI characteristics.....	66
D.3	Differential delay compensation range.....	67
D.4	FER/BER equivalence and FER performance measurement equipment settings (example).....	68
D.4.1	FER/BER equivalence.....	68
D.4.2	FER equipment settings and measurement techniques (example).....	69
D.5	Impact of power control (ATPC and/or RTPC), mixed-mode and bandwidth adaptive operation on spectrum mask and link design requirements.....	69
D.5.0	Introduction.....	69
D.5.1	ATPC and RTPC.....	69
D.5.1.1	ATPC.....	69
D.5.1.2	ATPC and RTPC implementation background.....	70
D.5.2	Mixed-mode and bandwidth adaptive operation impact.....	72
D.5.2.1	Mixed-mode basic concepts.....	72
D.5.2.2	Bandwidth adaptive.....	73
D.5.2.2.1	Basic concepts.....	73
D.5.2.2.2	Bandwidth (channel) occupancy.....	73
D.5.3	Impact on frequency co ordination.....	73
D.5.4	Impact of operating conditions on the access to radio spectrum through European Harmonised Standard.....	73
D.6	Typical interference sensitivity behaviour for frequency planning purpose.....	74
D.7	Band and Carrier Aggregation (BCA) operation.....	74
<b>Annex E (informative):</b>	<b>Mechanical characteristics.....</b>	<b>76</b>
<b>Annex F (informative):</b>	<b>Mitigation techniques referred in CEPT/ERC/DEC(00)07 (18 GHz band).....</b>	<b>77</b>
<b>Annex G (informative):</b>	<b>Bibliography.....</b>	<b>78</b>

<b>Annex H (informative):</b>	<b>Change history .....</b>	<b>79</b>
History .....		80

## **iTeh STANDARD PREVIEW (standards.iteh.ai)**

ETSI EN 302 217-1 V3.3.1 (2021-10)

<https://standards.iteh.ai/catalog/standards/sist/9175e0e8-2228-46e5-8b6f-7ecc9766e556/etsi-en-302-217-1-v3-3-1-2021-10>

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

ITEH STANDARD PREVIEW  
(standards.iteh.ai)

## Foreword

ETSI EN 302 217-1 V3.3.1 (2021-10)

This European Standard (EN) has been produced by ETSI Technical Committee Access, Terminals, Transmission and Multiplexing (ATTM).

<https://standards.iteh.ai/catalog/standards/siv/1790000-2220-4000-8000/7ecc9766e556/etsi-en-302-217-1-v3-3-1-2021-10>

The present document is part 1 of a multi-part deliverable covering the Fixed Radio Systems; Characteristics and requirements for point-to-point equipment and antennas, as identified below (see note):

**Part 1: "Overview, common characteristics and requirements not related to access to radio spectrum";**

Part 2: "Digital systems operating in frequency bands from 1 GHz to 86 GHz; Harmonised Standard for access to radio spectrum";

Part 4: "Antennas".

NOTE: In previous regulatory regime under Directive 1999/5/EC more parts (harmonised and non-harmonised standards) were published. Since Directive 2014/53/EU [i.1] repealed Directive 1999/5/EC the following parts have been replaced while the content has been moved to other parts of the series.

Those parts are:

Part 2-1: Technical content moved to present document (Part 1);

Part 2-2: Technical content reproduced in Part 2 (\*);

(\*) Part 2-2- was also published in the OJEU under Directive 2014/53/EU [i.1], presumption of conformity ceased on 31-12-2018;

Part 3: Technical content moved to Part 2 (including a complete new set of receiver parameters);

Part 4-1: Technical content reproduced in Part 4;

Part 4-2: Technical content reproduced in Part 4.

National transposition dates	
Date of adoption of this EN:	30 August 2021
Date of latest announcement of this EN (doa):	30 November 2021
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 May 2022
Date of withdrawal of any conflicting National Standard (dow):	31 May 2022

---

## Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are **NOT** allowed in ETSI deliverables except when used in direct citation.

## iTeh STANDARD PREVIEW (standards.iteh.ai)

[ETSI EN 302 217-1 V3.3.1 \(2021-10\)](#)

<https://standards.iteh.ai/catalog/standards/sist/9175e0e8-2228-46e5-8b6f-7ecc9766e556/etsi-en-302-217-1-v3-3-1-2021-10>



# 1 Scope

The present document applies to Digital Fixed Radio Systems (DFRS) in point-to-point operation with integral and external antennas in the frequency range of 1 GHz to 86 GHz corresponding to the appropriate frequency bands 1,4 GHz to 86 GHz as described in ETSI EN 302 217-2 [16], annex B to annex J.

The present document summarizes:

- all characteristics, principles and, of utmost importance, terms and definitions that are common to all P-P equipment and antennas and its consultation is necessary when using all other parts of ETSI EN 302 217 series;
- all system-dependent requirements for Point-to-Point (P-P) equipment. These requirements are introduced in two different clauses sub-sets:
  - **Main requirements** are requirements that are also related to the "essential requirements" under article 3.2 of Directive 2014/53/EU [i.1] and further detailed in the Harmonised Standard ETSI EN 302 217-2 [16].
  - **Complementary requirements** are requirements that are not related to essential requirements under article 3.2 of Directive 2014/53/EU [i.1]. Nevertheless they have been commonly agreed for proper system operation and deployment when specific deployment conditions or compatibility requirements are present. Compliance to all or some of these requirements is left to manufacturer decision.

Health and safety requirements and EMC conditions and requirements are not considered in the ETSI EN 302 217 series.

## iTeh STANDARD PREVIEW

# 2 References (standards.iteh.ai)

## 2.1 Normative references

ETSI EN 302 217-1 V3.3.1 (2021-10)

<https://standards.iteh.ai/catalog/standards/sist/9175e0e8-2228-46e5-8b6f-7ecc9766e556/etsi-en-302-217-1-v3-3-1-2021-10>

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] CEPT/ERC/DEC(00)07: "The shared use of the band 17.7 - 19.7 GHz by the fixed service and Earth stations of the fixed-satellite service (space-to-Earth)". ERC Decision, approved 19 October 2000, amended 04 March 2016.
- [2] ETSI EN 300 019-1-0: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-0: Classification of environmental conditions; Introduction".
- [3] ETSI EN 300 019-2-0: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 2-0: Specification of environmental tests; Introduction".
- [4] ETSI EN 300 019-1-1: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-1: Classification of environmental conditions; Storage".

- [5] ETSI EN 300 019-2-1: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 2-1: Specification of environmental tests; Storage".
- [6] ETSI EN 300 019-1-2: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-2: Classification of environmental conditions; Transportation".
- [7] ETSI EN 300 019-2-2: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 2-2: Specification of environmental tests; Transportation".
- [8] ETSI EN 300 019-1-3: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-3: Classification of environmental conditions; Stationary use at weather protected locations".
- [9] ETSI EN 300 019-2-3: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 2-3: Specification of environmental tests; Stationary use at weather protected locations".
- [10] ETSI EN 300 019-1-4: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 1-4: Classification of environmental conditions; Stationary use at non-weather protected locations".
- [11] ETSI EN 300 019-2-4: "Environmental Engineering (EE); Environmental conditions and environmental tests for telecommunications equipment; Part 2-4: Specification of environmental tests; Stationary use at non-weather protected locations".
- [12] ETSI EN 300 132-2: "Environmental Engineering (EE); Power supply interface at the input of Information and Communication Technology (ICT) equipment; Part 2: -48 V Direct Current (DC)".
- [13] ETSI EN 300 132-3: "Environmental Engineering (EE); Power supply interface at the input of Information and Communication Technology (ICT) equipment; Part 3: Up to 400 V Direct Current (DC)".
- [14] ETSI EN 301 126-1: "Fixed Radio Systems; Conformance testing; Part 1: Point-to-Point equipment - Definitions, general requirements and test procedures".
- [15] ETSI EN 302 099: "Environmental Engineering (EE); Powering of equipment in access network".
- [16] ETSI EN 302 217-2 (V3.3.1): "Fixed Radio Systems; Characteristics and requirements for point-to-point equipment and antennas; Part 2: Digital systems operating in frequency bands from 1 GHz to 86 GHz; Harmonised Standard for access to radio spectrum".
- [17] ETSI EN 302 217-4 (V2.1.1): "Fixed Radio Systems; Characteristics and requirements for point-to-point equipment and antennas; Part 4: Antennas".
- [18] EN 60835-2-4: "Methods of measurement for equipment used in digital microwave radio transmission systems - Part 2: Measurements on terrestrial radio-relay systems - Section 4: Transmitter/receiver including modulator/demodulator", produced by CENELEC.
- [19] EN 60835-2-8: "Methods of measurement for equipment used in digital microwave radio transmission systems - Part 2: Measurements on terrestrial radio-relay systems - Section 8: Adaptive equalizer", produced by CENELEC.
- [20] IEEE 802.3-2018™: "IEEE Standard for Ethernet".
- [21] Recommendation ITU-R F.746: "Radio-frequency arrangements for fixed service systems".
- [22] Recommendation ITU-R F.1668: "Error performance objectives for real digital fixed wireless links used in 27 500 km hypothetical reference paths and connections".
- [23] Recommendation ITU-R F.1703: "Availability objectives for real digital fixed wireless links used in 27 500 km hypothetical reference paths and connections".

- [24] Recommendation ITU-R P.530: "Propagation data and prediction methods required for the design of terrestrial line-of-sight systems".
- [25] Recommendation ITU-T G.703: "Physical/electrical characteristics of hierarchical digital interfaces".
- [26] Recommendation ITU-T G.704: "Synchronous frame structures used at 1544, 6312, 2048, 8448 and 44 736 kbit/s hierarchical levels".
- [27] Recommendation ITU-T G.707: "Network node interface for the synchronous digital hierarchy (SDH)".
- [28] Recommendation ITU-T G.708: "Sub STM-0 network node interface for the synchronous digital hierarchy (SDH)".
- [29] Recommendation ITU-T G.826: "End-to-end error performance parameters and objectives for international, constant bit-rate digital paths and connections".
- [30] Recommendation ITU-T G.828: "Error performance parameters and objectives for international, constant bit-rate synchronous digital paths".
- [31] Recommendation ITU-T G.829: "Error performance events for SDH multiplex and regenerator sections".
- [32] Recommendation ITU-T G.957: "Optical interfaces for equipment and systems relating to the synchronous digital hierarchy".
- [33] Recommendation ITU-T I.356: "B-ISDN ATM layer cell transfer performance".
- [34] Recommendation ITU-T I.357: "B-ISDN semi-permanent connection availability".
- [35] Recommendation ITU-T O.151: "Error performance measuring equipment operating at the primary rate and above".
- [36] Recommendation ITU-T O.181: "Equipment to assess error performance on STM-N interfaces".  
<https://standards.iteh.ai/catalog/standards/sist/9175e0e8-2228-46e5-8b6f-7ec0766e7556/etsi-en-302-217-1-v3-3-1-2021-10>
- [37] Recommendation ITU-T O.191: "Equipment to measure the cell transfer performance of ATM connections".
- [38] Recommendation ITU-T V.11: "Electrical characteristics for balanced double-current interchange circuits operating at data signalling rates up to 10 Mbit/s".
- [39] Recommendation ITU-T V.24: "List of definitions for interchange circuits between data terminal equipment (DTE) and data circuit-terminating equipment (DCE)".
- [40] Recommendation ITU-T V.28: "Electrical characteristics for unbalanced double-current interchange circuits".
- [41] Recommendation ITU-T Y.1540: "Internet protocol data communication service - IP packet transfer and availability performance parameters".

## 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Directive 2014/53/EU of the European Parliament and of the Council of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making available on the market of radio equipment and repealing Directive 1999/5/EC.
- [i.2] ETSI TR 101 035: "Transmission and Multiplexing (TM); Synchronous Digital Hierarchy (SDH) aspects regarding Digital Radio Relay Systems (DRRS)".
- [i.3] ETSI TR 102 243-1: "Fixed Radio Systems; Representative values for transmitter power and antenna gain to support inter- and intra-compatibility and sharing analysis; Part 1: Digital point-to-point systems".
- [i.4] CEPT/ERC/REC 12-03: "Harmonised radio frequency channel arrangements for digital terrestrial fixed systems operating in the band 17.7 GHz to 19.7 GHz".
- [i.5] CEPT/ECC/REC(02)06: "Preferred channel arrangements for digital Fixed Service Systems operating in the frequency range 7125-8500 MHz".
- [i.6] CEPT/ECC/Report 80: "Enhancing harmonisation and introducing flexibility in the spectrum regulatory framework".
- [i.7] CEPT/ECC/Report 198: "Adaptive modulation and ATPC operations in fixed point-to-point systems - Guideline on coordination procedures".
- [i.8] CEPT/ERC/REC 14-01: "Radio-frequency channel arrangements for high capacity analogue and digital radio-relay systems operating in the band 5925 MHz to 6425 MHz".
- [i.9] CEPT/ERC/REC 14-02: "Radio-frequency channel arrangements for high, medium and low capacity digital fixed service systems operating in the band 6425 to 7125 MHz".
- [i.10] ETSI GR mWT 015: "Frequency Bands and Carrier Aggregation Systems; Band and Carrier Aggregation".
- [i.11] ETSI EN 300 119 (all parts): "Environmental Engineering (EE); European telecommunication standard for equipment practice".
- [i.12] ETSI TR 101 036-1: "Fixed Radio Systems; Generic wordings for standards on DFRS (Digital Fixed Radio Systems) characteristics; Part 1: General aspects and point-to-point equipment parameters".
- [i.13] ETSI TR 101 506 (V2.1.1): "Fixed Radio Systems; Generic definitions, terminology and applicability of essential requirements covering article 3.2 of Directive 2014/53/EU to Fixed Radio Systems".
- [i.14] ETSI TR 101 854: "Fixed Radio Systems; Point-to-point equipment; Derivation of receiver interference parameters useful for planning fixed service point-to-point systems operating different equipment classes and/or capacities".
- [i.15] ETSI TR 103 103: "Fixed Radio Systems; Point-to-point systems; ATPC, RTPC, Adaptive Modulation (mixed-mode) and Bandwidth Adaptive functionalities; Technical background and impact on deployment, link design and coordination".
- [i.16] EN 122150: "Sectional Specification: Radio frequency coaxial connectors - Series EIA flange", produced by CENELEC.
- [i.17] EN 60153-2: "Hollow metallic waveguides. Part 2: Relevant specifications for ordinary rectangular waveguides", produced by CENELEC.
- [i.18] EN 60154-2: "Flanges for waveguides. Part 2: Relevant specifications for flanges for ordinary rectangular waveguides", produced by CENELEC.
- [i.19] IEC 60169-1: "Radio-frequency connectors. Part 1: General requirements and measuring methods".
- [i.20] IEC 60339 (all parts): "General purpose rigid coaxial transmission lines and their associated flange connectors".

- [i.21] Recommendation ITU-R F.383: "Radio-frequency channel arrangements for high capacity fixed wireless systems operating in the lower 6 GHz (5 925 to 6 425 MHz) band".
- [i.22] Recommendation ITU-R F.384: "Radio -frequency channel arrangements for medium- and high-capacity digital fixed wireless systems operating in the 6 425-7 125 MHz band".
- [i.23] Recommendation ITU-R F.385: "Radio-frequency channel arrangements for fixed wireless systems operating in the 7 110-7 900 MHz band".
- [i.24] Recommendation ITU-R F.595: "Radio-frequency channel arrangements for fixed wireless systems operating in the 17.7-19.7 GHz frequency band".
- [i.25] Recommendation ITU-R F.750: "Architectures and functional aspects of radio-relay systems for synchronous digital hierarchy (SDH)-based network".
- [i.26] Recommendation ITU-R F.752: "Diversity techniques for point-to-point fixed wireless systems".
- [i.27] Recommendation ITU-R F.1093: "Effects of multipath propagation on the design and operation of line-of-sight digital fixed wireless systems".
- [i.28] Recommendation ITU-R F.1101: "Characteristics of digital fixed wireless systems below about 17 GHz".
- [i.29] Recommendation ITU-R F.1102: "Characteristics of fixed wireless systems operating in frequency bands above about 17 GHz".
- [i.30] Recommendation ITU-R F.1191: "Bandwidths and unwanted emissions of digital fixed service systems".
- [i.31] Recommendation ITU-T G.783: "Characteristics of synchronous digital hierarchy (SDH) equipment functional blocks".
- [i.32] Recommendation ITU-T G.784: "Management aspects of the synchronous digital hierarchy (SDH) transport network element".
- [i.33] Recommendation ITU-T I.414: "Overview of Recommendations on layer 1 for ISDN and B-ISDN customer accesses".
- [i.34] ITU Radio Regulations, Edition of 2020.
- [i.35] J. Redd: "Calculating Statistical Confidence Levels for Error-Probability Estimates". Lightwave Magazine, pp. 110-114, April 2000.

NOTE: Available at <http://www.lightwaveonline.com/>.

- [i.36] Lundgren, C.W.; Rummler, W.D.: "Digital Radio Outage Due to Selective Fading - Observation vs Prediction from Laboratory Simulation". BSTJ 58-5 May-June 1979 pp 1073-1100.

NOTE: Available at <https://archive.org/details/bstj58-5-1073>.

- [i.37] ETSI EN 302 217-1 (V2.1.1): "Fixed Radio Systems; Characteristics and requirements for point-to-point equipment and antennas; Part 1: Overview and system-independent common characteristics".

NOTE: Superseded version still containing the information referred in clause 4.2.

## 3 Definition of terms, symbols and abbreviations

### 3.1 Terms

For the purposes of the present document and of the other ETSI EN 302 217 series parts (i.e. ETSI EN 302 217-2 [16] and ETSI EN 302 217-4 [17]), the terms given in Directive 2014/53/EU [i.1] and the following apply:

**aggregated channel:** one of the channels used in "*channels-aggregation*" equipment

NOTE: There is no relationship with the "aggregation" terminology used in some ITU-R and ECC recommendations on radio frequency channel arrangements; there, the "aggregation" of contiguous channels is used to determine wider channels positions.

**allocated radio frequency band:** Derived from the definition of "allocation (of a frequency band)" (ITU Radio Regulations [i.34], article 1.16): "entry in the Table of Frequency Allocations of a given frequency band for the purpose of its use by one or more terrestrial or space radiocommunication services or the radio astronomy service under specific conditions. This term is also applicable to the frequency band concerned".

NOTE: From the regulatory point of view three different applications might be envisaged and used in the whole allocated band or in its dedicated segments:

- **Frequency band where frequency co-ordination is applied:** in these bands, in the licensing process, regulatory bodies enforce co-ordination rules to ensure that all links work on an "acceptable interference" bases.
- **Frequency band where frequency co-ordination is not applied:** in these bands, irrespective of any licensing process or with no licensing at all, the deployment is freely made by the user on a "first on-first served" bases without any warrantee of "acceptable interference" from the regulatory body.
- **Frequency band where self-coordination is applied:** in these bands an approach similar to the "light licensing", described in CEPT/ECC/Report 80 [i.6], is used. Such regimes do not mean "licence exempt" use, but rather using a simplified set of conventional licensing mechanisms and attributes within the scope decided by the administration. This planning is delegated to the licensee.

**antenna:** part of the transmitting or receiving system that is designed to radiate and/or receive electromagnetic waves

**Automatic Transmit Power Control (ATPC):** function implemented to offer a dynamic power control that delivers maximum power only during deep fading; in this way for most of the time the interference is reduced and the transmitter operates in a higher linearity mode

NOTE: When this function is used, the transmit power is dynamically changed with respect to the propagation conditions. In principle, when ATPC is implemented, three different levels of power may be identified:

- **maximum available power** (delivered, when licensing conditions permits it, only in conditions of deep fading);
- **maximum nominal power** (useable on a permanent basis when ATPC is disabled); it should be noted that this power is "nominal for the equipment" and is not to be confused with the "nominal level set link by link" by the frequency co-ordinating body. This is achieved through the use of the RTPC function or passive RF attenuators;
- **minimum power** (delivered in unfaded conditions).

Maximum nominal and maximum available power levels may be coincident or, in case of multi-state modulation formats, the maximum available power may be used to overdrive the transmitter (loosing linearity but gaining fade margin when the fade conditions have already impaired the expected RBER). Performance predictions are usually made with the maximum "available power".

More detailed information on ATPC operation can be found in ETSI TR 103 103 [i.15].

**Band and Carrier Aggregation (BCA) systems:** combination of channels operating typically in different, well separated (e.g. 6 GHz plus 18 GHz or 38 GHz plus 80 GHz) bands carrying an overall packet payload capacity over the same link with different availability for the relevant portions of payload

NOTE: BCA concept is generic and is not specifically related to *channels-aggregation* or *multi-channel* concepts and it can be extended also to the case; even if in most cases *channels-aggregation* equipment and/or *multi-channel* systems are combined in BCA operation.

**bandwidth adaptive systems:** system, the capacity of which may be dynamically changed by means of bandwidth reduction during adverse propagation conditions

**block assignment:** application of block of spectrum assigned to one or more stations of an operator under a single exclusive licence

**channels-aggregation:** equipment where two ( $N = 2$ ) or more ( $N > 2$ ) radio channels (*aggregated channels*) are transmitted/received by the same radio equipment; each channel can be configured to operate within the whole *tuning range*

NOTE 1: The use of channels-aggregation system is intended, in general, to provide high capacity, through the aggregation of wide channels (e.g. 28/56/112/224 MHz).

NOTE 2: Under this category different applications are possible, to which the following more detailed definitions apply:

- 1) **channels-aggregation (single-band):** (applicable to equipment band-coverage) where the two *aggregated-channels* operate on the same overlapping or contiguous bands (see also clause O.1 of ETSI EN 302 217-2 [16]);
- 2) **channels-aggregation (dual-band):** (applicable to equipment band-coverage) where the two (or more) *aggregated-channels* operate on non-contiguous bands (see note 3);
- 3) **channels-aggregation/multi-port:** (applicable to equipment physical layout) equipment where the payload capacity is transmitted by the same radio equipment through more than 1 different antenna ports over:
  - 3a) same link and direction on two (or more) different (in frequency and/or in polarization) assigned radio frequency channels (see annex C) in the same or different frequency bands;
  - 3b) two (or more) different links and directions on the assigned radio frequency channels (see annex C) in the same or different frequency bands (see notes 4 and 5);
- 4) **channels-aggregation/single-port:** (applicable to equipment physical layout) equipment where the payload capacity is transmitted from the same radio equipment and unique antenna port over two (or more) different assigned frequency channels (see annex C) in the same or contiguous frequency bands (see notes 4 and 5);
- 5) **single-channel-port:** (applicable to port characteristic) an antenna port capable of emitting only one channel;
- 6) **multiple-channels-port:** (applicable to port characteristic) an antenna port capable of emitting two channels.

NOTE 3: This case can also constitute a "*Band and Carrier Aggregation systems*" (BCA).

NOTE 4: Note that the "*single-port*" layout implies only one "*multiple-channels-port*" and a "*multi-port*" layout, for  $N = 2$ , implies two "*single-channel-ports*". Note also that in previous version of the present document, when only  $N = 2$  was considered, the definition of "*dual-port*" was used instead of the more generic "*multi-port*" broadly valid for any  $N > 1$ .

NOTE 5: When more than two channels are aggregated, the equipment may have a combination of *single-channel-port* and *multiple-channels-ports* for operations depending on the desired combination of the channels on the antenna system, see examples in annex C.

**Channel Separation (CS):** distance between adjacent channels in a radio frequency channels arrangement; it represents one of the major parameters for the identification of the radio equipment use and relevant requirements