



**SLOVENSKI STANDARD**  
**SIST EN 300 175-3 V2.9.1:2022**

**01-maj-2022**

---

**Digitalne izboljšane brezvrvične telekomunikacije (DECT) - Skupni vmesnik (CI) - 3.  
del: Plast krmiljenja dostopa do prenosnega medija (MAC)**

Digital Enhanced Cordless Telecommunications (DECT) - Common Interface (CI) - Part  
3: Medium Access Control (MAC) layer

**iTeh STANDARD**  
**PREVIEW**  
**(standards.iteh.ai)**

**Ta slovenski standard je istoveten z: ETSI EN 300 175-3 V2.9.1 (2022-03)**

[SIST EN 300 175-3 V2.9.1:2022](https://standards.iteh.ai/catalog/standards/sist/2c7800f5-a5f7-4b96-870e-4911dff05ba4/sist-en-300-175-3-v2-9-1-2022)

[https://standards.iteh.ai/catalog/standards/sist/2c7800f5-  
a5f7-4b96-870e-4911dff05ba4/sist-en-300-175-3-v2-9-  
1-2022](https://standards.iteh.ai/catalog/standards/sist/2c7800f5-a5f7-4b96-870e-4911dff05ba4/sist-en-300-175-3-v2-9-1-2022)

**ICS:**

33.070.30	Digitalne izboljšane brezvrvične telekomunikacije (DECT)	Digital Enhanced Cordless Telecommunications (DECT)
-----------	--	--

**SIST EN 300 175-3 V2.9.1:2022**

**en**

**iTeh STANDARD  
PREVIEW  
(standards.iteh.ai)**

SIST EN 300 175-3 V2.9.1:2022

<https://standards.iteh.ai/catalog/standards/sist/2e7800f5-a5f7-4b96-870e-4911dff05ba4/sist-en-300-175-3-v2-9-1-2022>

# ETSI EN 300 175-3 V2.9.1 (2022-03)



**Digital Enhanced Cordless Telecommunications (DECT);  
Common Interface (CI);  
Part 3: Medium Access Control (MAC) layer**

[SIST EN 300 175-3 V2.9.1:2022](https://standards.iteh.ai/catalog/standards/sist/2e7800f5-a5f7-4b96-870e-4911dff05ba4/sist-en-300-175-3-v2-9-1-2022)

<https://standards.iteh.ai/catalog/standards/sist/2e7800f5-a5f7-4b96-870e-4911dff05ba4/sist-en-300-175-3-v2-9-1-2022>

---

**Reference**

REN/DECT-00353

---

**Keywords**DECT, IMT-2000, MAC, mobility, radio, TDD,  
TDMA**ETSI**650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° w061004871

---

**Important notice**

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our

Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

---

**Notice of disclaimer & limitation of liability**

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2022.

All rights reserved.

# Contents

Intellectual Property Rights .....	17
Foreword.....	17
Modal verbs terminology.....	17
1 Scope .....	18
2 References .....	18
2.1 Normative references .....	18
2.2 Informative references.....	19
3 Definition of terms, symbols and abbreviations.....	20
3.1 Terms.....	20
3.2 Symbols.....	20
3.3 Abbreviations .....	21
4 Description of the MAC layer .....	23
4.1 MAC layer reference model .....	23
4.1.1 General.....	23
4.1.2 Cluster Control Function (CCF) .....	24
4.1.3 Cell Site Functions (CSF).....	24
4.1.4 Relationship to physical layer elements.....	24
4.2 Frame and multiframe structures .....	25
4.2.1 General.....	25
4.2.2 Frame structure .....	25
4.2.3 Multiframe structure .....	26
4.3 State definitions.....	27
4.3.1 PP states .....	27
4.3.2 RFP states .....	28
5 Overview of MAC layer services.....	29
5.1 General .....	29
5.1.0 Service groupings .....	29
5.1.1 Broadcast Message Control (BMC) .....	29
5.1.2 Connectionless Message Control (CMC) .....	29
5.1.3 Multi-Bearer Control .....	29
5.2 Service descriptions.....	29
5.2.1 Common functions.....	29
5.2.2 BMC service .....	30
5.2.3 CMC service .....	30
5.2.4 MBC services.....	30
5.3 Logical channels.....	31
5.3.0 Overview .....	31
5.3.1 MBC connection endpoints (MC-SAP logical channels) .....	31
5.3.1.1 The higher layer C-plane channels, C .....	31
5.3.1.2 The higher layer U-Plane channels, I .....	32
5.3.1.3 The higher layer U-Plane control channels, G <sub>F</sub> and G <sub>FA</sub> .....	32
5.3.1.4 The higher layer U-Plane channel in E+U type slots, I <sub>PF</sub> .....	32
5.3.2 CMC endpoints (MB-SAP logical channels).....	33
5.3.2.1 The connectionless C-Plane channels, CL .....	33
5.3.2.2 The connectionless U-Plane channels, SI <sub>N</sub> and SI <sub>P</sub> .....	33
5.3.2.3 The connectionless U-Plane channel in E+U type slots, SI <sub>PF</sub> .....	33
5.3.3 BMC endpoint (MA-SAP logical channel).....	34
5.3.3.1 The slow broadcast channel, B <sub>S</sub> .....	34
5.3.3.2 The ULE broadcast channel, B <sub>U</sub> .....	34
5.3.4 Internal MAC control channels.....	34
5.3.4.1 The system information channel, Q .....	34
5.3.4.2 Identities channel, N.....	34
5.3.4.3 The MAC control channel, M .....	34

5.3.4.4	MAC paging channel, P .....	35
5.3.4.5	The Compound System Information Channel, Q <sub>C</sub> .....	35
5.3.4.6	The Split Identities Channel, N <sub>S</sub> .....	35
5.3.4.7	The ULE MAC Control Channel, M <sub>U</sub> .....	35
5.3.4.8	The ULE Paging Channel, P <sub>U</sub> .....	35
5.4	SAP definitions .....	36
5.4.0	General .....	36
5.4.1	MA SAP .....	36
5.4.2	MB SAP .....	36
5.4.3	MC SAP .....	36
5.4.4	ME SAP .....	37
5.4.5	Order of transmission .....	37
5.5	Bearer .....	37
5.5.0	General .....	37
5.5.1	Bearer types .....	38
5.5.2	Bearer operation .....	38
5.6	Connection oriented services .....	38
5.6.0	General .....	38
5.6.1	Connection types .....	39
5.6.1.0	General .....	39
5.6.1.1	Basic connections .....	39
5.6.1.2	Advanced connections .....	39
5.6.1.2.0	General .....	39
5.6.1.2.1	Rules for ECN selection in advanced connections .....	40
5.6.1.2.2	Expedited operations in advanced connections .....	40
5.6.1.3	Connection identifiers .....	40
5.6.1.4	Complementary connections .....	40
5.6.2	Symmetric and asymmetric connections .....	41
5.6.2.0	General .....	41
5.6.2.1	Symmetric connections .....	41
5.6.2.2	Asymmetric connections .....	47
5.7	Broadcast and connectionless services .....	57
5.7.0	General .....	57
5.7.1	The broadcast services .....	57
5.7.1.0	General .....	57
5.7.1.1	The continuous broadcast service .....	57
5.7.1.2	The non-continuous broadcast service .....	58
5.7.2	The connectionless services .....	58
5.7.2.0	General .....	58
5.7.2.1	Connectionless downlink services .....	58
5.7.2.1.0	General .....	58
5.7.2.1.1	Coding of TA and BA bits in connectionless downlink services .....	59
5.7.2.2	Connectionless uplink services .....	59
5.8	ULE Broadcast services .....	60
5.8.0	General .....	60
5.8.1	The continuous ULE broadcast service .....	60
6	Multiplexing .....	60
6.0	General .....	60
6.1	CCF multiplexing functions .....	60
6.2	CSF multiplexing functions .....	61
6.2.0	General .....	61
6.2.1	Bit Mappings (MAP) .....	66
6.2.1.0	General .....	66
6.2.1.1	D-field mapping (D-MAP) .....	66
6.2.1.1.0	General .....	66
6.2.1.1.1	D-field mapping for the double slot structure (physical packet P80) .....	67
6.2.1.1.2	D-field mapping for the full slot structure (physical packet P32) .....	67
6.2.1.1.3	D-field mapping for the short slot structure (physical packet P00) .....	68
6.2.1.1.4	D-field mapping for the variable slot structure (physical packet P00j) .....	69
6.2.1.2	A-field Mapping (A-MAP) .....	70
6.2.1.3	B-field Mapping (B-MAP) .....	71

6.2.1.3.0	General .....	71
6.2.1.3.1	Unprotected format.....	71
6.2.1.3.2	Encoded protected format.....	73
6.2.1.3.3	Multisubfield protected format.....	73
6.2.1.3.4	Singlesubfield protected format switches.....	76
6.2.1.3.5	Constant-size subfield protected format .....	77
6.2.2	Time multiplexers.....	80
6.2.2.0	General .....	80
6.2.2.1	Tail MULTipleXer (T-MUX).....	80
6.2.2.1.0	General .....	80
6.2.2.1.1	T-MUX algorithm for RFP transmissions.....	81
6.2.2.1.2	T-MUX algorithm for PT transmissions.....	82
6.2.2.2	B-field control multiplexer (E/U-MUX).....	83
6.2.2.3	B-field mode multiplexer E-type and E+U-type modes.....	85
6.2.2.3.1	E-type and E+U-type modes for slots with more than one subfield .....	85
6.2.2.3.2	Half slot (j=80) modes for 2-level modulation .....	99
6.2.2.4	Priority scheme in E or E+U mode .....	100
6.2.3	MAC Encryption .....	101
6.2.4	Scrambling.....	101
6.2.5	Error control.....	103
6.2.5.0	General .....	103
6.2.5.1	R-CRC overview.....	103
6.2.5.2	R-CRC generation and checking.....	104
6.2.5.3	X-CRC overview.....	104
6.2.5.4	X-CRC generation and checking.....	105
6.2.5.5	B-CRC generation and checking.....	107
6.2.6	Broadcast controller.....	107
7	Medium access layer messages .....	107
7.0	General .....	107
7.1	Header field.....	108
7.1.1	Overview/formatting.....	108
7.1.2	Tail identification, TA, bits $a_0$ to $a_2$ .....	108
7.1.3	The "Q1/BCK" bit, bit $a_3$ .....	109
7.1.4	B-field identification, BA, bits $a_4$ to $a_6$ .....	109
7.1.5	The "Q2" bit, bit $a_7$ .....	110
7.1.6	Combined coding of the bits $a_3$ to $a_7$ .....	110
7.2	Messages in the tail field.....	111
7.2.1	Overview .....	111
7.2.2	Identities information ( $N_T$ ).....	111
7.2.3	System information and multiframe marker ( $Q_T$ ).....	111
7.2.3.1	General .....	111
7.2.3.2	Static system information.....	112
7.2.3.2.1	General, $Q_H = 0, 1$ (hex).....	112
7.2.3.2.2	$Q_H$ and Normal-Reverse (NR).....	113
7.2.3.2.3	Slot Number (SN).....	113
7.2.3.2.4	Start Position (SP).....	113
7.2.3.2.5	ESCAPE bit (ESC).....	114
7.2.3.2.6	Number of transceivers.....	114
7.2.3.2.7	Extended RF carrier information available ( $M_c$ ).....	114
7.2.3.2.8	RF carriers available (RF-cars).....	114
7.2.3.2.9	Spare bits (SPR) .....	115
7.2.3.2.10	Carrier number.....	115
7.2.3.2.11	Extended static system information available (Ext-System-Info) and spare bit.....	115
7.2.3.2.12	Primary receiver Scan Carrier Number (PSCN).....	116
7.2.3.3	Extended RF carrier information part 1 .....	116
7.2.3.3.1	General, $Q_H = 2$ (hex).....	116
7.2.3.3.2	Further RF carrier extensions .....	117
7.2.3.3.3	Number of RF carriers.....	117
7.2.3.4	Fixed part capabilities .....	117
7.2.3.4.1	General, $Q_H = 3$ (hex).....	117
7.2.3.4.2	Standard capabilities.....	117

7.2.3.5	Extended fixed part capabilities .....	118
7.2.3.5.1	General, $Q_H = 4$ (hex) .....	118
7.2.3.5.2	Extended Physical and MAC layer capabilities .....	119
7.2.3.5.3	Extended higher layer capabilities .....	120
7.2.3.6	Secondary access rights identities .....	120
7.2.3.6.1	General, $Q_H = 5$ (hex) .....	120
7.2.3.6.2	SARI message .....	120
7.2.3.7	Multiframe number .....	120
7.2.3.7.1	General, $Q_H = 6$ (hex) .....	120
7.2.3.7.2	Multiframe number .....	121
7.2.3.8	Escape .....	121
7.2.3.8.1	General, $Q_H = 7$ (hex) .....	121
7.2.3.8.2	Escape information .....	121
7.2.3.9	Extended RF carrier information part 2 .....	121
7.2.3.9.1	General, $Q_H = 9$ (hex) .....	121
7.2.3.10	Transmit information .....	122
7.2.3.10.1	General, $Q_H = B$ (hex) .....	122
7.2.3.11	Extended fixed part capabilities (part 2) .....	122
7.2.3.11.1	General, $Q_H = C$ (hex) .....	122
7.2.3.11.2	Extended Physical and MAC layer capabilities (part 2) .....	123
7.2.3.11.3	Extended higher layer capabilities (part 2) .....	123
7.2.3.12	Extended static system information .....	124
7.2.3.12.1	General, $Q_H = D$ (hex) .....	124
7.2.3.12.2	Spare bits (Spare) .....	124
7.2.3.12.3	RFP slot scheme info .....	124
7.2.3.13	Extended fixed part capabilities (part 3) .....	125
7.2.3.13.1	General, $Q_H = E$ (hex) .....	125
7.2.3.13.2	Extended Physical and MAC layer capabilities (part 3) .....	125
7.2.3.13.3	Extended higher layer capabilities (part 3) .....	126
7.2.4	Paging Tail ( $P_T$ ) .....	126
7.2.4.1	General format .....	126
7.2.4.1.1	$P_T$ format for full and long page messages .....	126
7.2.4.1.2	$P_T$ format for short page messages .....	126
7.2.4.1.3	$P_T$ format for zero length page messages .....	126
7.2.4.1.4	$P_T$ format for MAC Resume and Control page message .....	127
7.2.4.2	$P_T$ header format .....	127
7.2.4.2.1	General format .....	127
7.2.4.2.2	Bit $a_8$ is the extend flag .....	128
7.2.4.2.3	$B_S$ SDU length indication .....	128
7.2.4.3	MAC layer information for PT .....	128
7.2.4.3.1	Information type .....	128
7.2.4.3.2	Fill bits / Blind long slot ( $j=640$ / $j=672$ ) information .....	128
7.2.4.3.3	Blind full slot information .....	129
7.2.4.3.4	Bearer description .....	129
7.2.4.3.5	Escape .....	130
7.2.4.3.6	Dummy or connectionless downlink bearer marker .....	130
7.2.4.3.7	Bearer handover/replacement and no-emission mode information .....	130
7.2.4.3.8	RFP status and modulation types .....	131
7.2.4.3.9	Active carriers .....	133
7.2.4.3.10	RFP power level .....	133
7.2.4.3.11	Blind double slot/RFP-FP interface resource information .....	134
7.2.4.3.12	Extended modulation types .....	134
7.2.5	MAC control ( $M_T$ ) .....	135
7.2.5.1	General format and contents .....	135
7.2.5.2	Basic connection control .....	135
7.2.5.2.1	General .....	135
7.2.5.2.2	Format for most messages .....	135
7.2.5.2.3	WAIT .....	136
7.2.5.2.4	ATTRIBUTES_T_{Req;Cfm} .....	136
7.2.5.3	Advanced connection control .....	136
7.2.5.3.1	General .....	136
7.2.5.3.2	ACCESS_REQUEST .....	137



7.2.5.3.3	BEARER_HANDOVER_REQUEST .....	137
7.2.5.3.4	CONNECTION_HANDOVER_REQUEST .....	137
7.2.5.3.5	UNCONFIRMED_ACCESS_REQUEST .....	137
7.2.5.3.6	BEARER_CONFIRM .....	138
7.2.5.3.7	WAIT .....	138
7.2.5.3.8	ATTRIBUTES_T_{Req;Cfm} .....	138
7.2.5.3.9	BANDWIDTH_T_{Req;Cfm} .....	144
7.2.5.3.10	Channel_list .....	144
7.2.5.3.11	Unconfirmed_dummy .....	146
7.2.5.3.12	Unconfirmed_handover .....	146
7.2.5.3.13	RELEASE .....	146
7.2.5.4	MAC layer test messages .....	147
7.2.5.4.0	General .....	147
7.2.5.4.1	Basic format .....	147
7.2.5.4.2	FORCE_TRANSMIT .....	147
7.2.5.4.3	LOOPBACK_DATA .....	148
7.2.5.4.4	DEFEAT_ANTENNA_DIVERSITY .....	148
7.2.5.4.5	ESCAPE .....	149
7.2.5.4.6	NETWORK_TEST .....	149
7.2.5.4.7	CLEAR_TEST_MODES .....	149
7.2.5.4.8	CHANGE_MODULATION_SCHEME .....	150
7.2.5.5	Quality control .....	150
7.2.5.5.0	General .....	150
7.2.5.5.1	Prolonged preamble diversity .....	152
7.2.5.6	Broadcast and connectionless services .....	152
7.2.5.7	Encryption control .....	153
7.2.5.8	B-field setup, first PT transmission .....	154
7.2.5.9	Escape .....	155
7.2.5.10	TARI message .....	155
7.2.5.11	REP connection control .....	155
7.2.5.11.1	General .....	155
7.2.5.11.2	Format for most messages .....	155
7.2.5.11.3	REP CHANNEL MAP REQUEST .....	156
7.2.5.11.4	REP CHANNEL MAP CONFIRM .....	156
7.2.5.12	Advanced connection control part 2 .....	156
7.2.5.12.1	General .....	156
7.2.5.12.2	Short description of the advanced connection control part 2 messages .....	156
7.2.5.12.3	Format for most advanced connection control part 2 messages .....	157
7.2.5.12.4	Format for "ready for release with G <sub>FA</sub> " and "expedited release with G <sub>FA</sub> " messages .....	157
7.2.5.12.5	Reason codes in "ready for release with G <sub>FA</sub> " and "expedited release with G <sub>FA</sub> " messages .....	159
7.2.5.12.6	Format for "Null or GFACHannel transmission" message .....	160
7.3	Messages in the B-field .....	161
7.3.1	Overview .....	161
7.3.2	Advanced connection control .....	162
7.3.2.1	General format .....	162
7.3.2.2	BEARER_REQUEST .....	163
7.3.2.3	BEARER_CONFIRM .....	164
7.3.2.4	WAIT .....	164
7.3.2.5	ATTRIBUTES_B_{Req;Cfm} .....	165
7.3.2.6	BANDWIDTH_B_{Req;Cfm} .....	167
7.3.2.7	CHANNEL_LIST .....	168
7.3.2.8	UNCONFIRMED_DUMMY .....	170
7.3.2.9	UNCONFIRMED_HANDOVER .....	170
7.3.2.10	RELEASE .....	170
7.3.3	Null or I <sub>PF</sub> segmentation info .....	172
7.3.3.0	General .....	172
7.3.3.1	Spare or I <sub>PF</sub> segmentation info .....	173
7.3.3.2	Extended NCF bits .....	173
7.3.4	Quality control .....	174
7.3.4.1	General format .....	174
7.3.4.2	Bearer and connection control .....	174
7.3.4.3	RESET .....	175

7.3.4.4	Bearer quality in an asymmetric connection .....	176
7.3.5	Extended system information .....	176
7.3.5.1	General format .....	176
7.3.5.2	TARI messages .....	177
7.3.5.3	"no-emission" mode sync information or ULE Dummy Bearer subfield 2.....	177
7.3.5.3.0	General .....	177
7.3.5.3.1	"no-emission" mode sync information for dummy bearer.....	177
7.3.5.3.2	ULE Dummy Bearer subfield 2.....	178
7.3.5.4	ULE Dummy Bearer subfield 3 .....	178
7.3.5.5	ULE Dummy Bearer subfield 0 .....	178
7.3.5.6	ULE Dummy Bearer subfield 1 .....	179
7.3.6	G <sub>F</sub> channel data packet.....	179
7.3.7	Escape .....	179
8	Medium access layer primitives .....	180
8.0	General .....	180
8.1	Connection oriented service primitives .....	180
8.1.0	General.....	180
8.1.1	Connection setup: MAC_CON {req;ind;cfm} .....	180
8.1.2	Connection modification: MAC_MOD {req;ind;cfm} .....	182
8.1.3	CO data transmit ready: MAC_CO_DTR {ind} .....	183
8.1.4	CO data transfer: MAC_CO_DATA {req;ind} .....	183
8.1.5	Restart DLC: MAC_RES_DLC {ind} .....	183
8.1.6	Connection release: MAC_DIS {req;ind} .....	184
8.1.7	MAC bandwidth: MAC_BW {ind;res} .....	184
8.1.8	Encryption.....	184
8.1.8.1	Load encryption key: MAC_ENC_KEY {req}.....	184
8.1.8.2	Enable/disable encryption: MAC_ENC_EKS {req;ind;cfm} .....	185
8.1.9	C-plane switching procedure .....	185
8.1.9.1	C-plane switching procedure: MAC_Cs_Cf {req, cfm, ind, res} .....	185
8.1.9.2	C-plane switching procedure: MAC_CsCf_END {ind} .....	185
8.2	Connectionless and broadcast service primitives .....	186
8.2.1	Paging: MAC_PAGE {req;ind}.....	186
8.2.2	Downlink connectionless: MAC_DOWN_CON {req;ind} .....	186
8.2.3	Uplink connectionless: MAC_UP_CON {req;ind;cfm} .....	187
8.2.4	"no-emission" mode .....	187
8.3	Management primitives .....	187
8.3.0	General.....	187
8.3.1	Connection control.....	187
8.3.1.1	Connection setup: MAC_ME_CON {ind}.....	187
8.3.1.2	Connection setup allowed: MAC_ME_CON_ALL {req} .....	187
8.3.1.3	Bearer release: MAC_ME_REL {req} .....	188
8.3.1.4	MBC release report: MAC_ME_REL_REP {ind} .....	188
8.3.2	System information and identities .....	188
8.3.2.1	FP information preloading: MAC_ME_RFP_PRELOAD {req} .....	188
8.3.2.2	PT information preloading: MAC_ME_PT_PRELOAD {req} .....	188
8.3.2.3	System information output: MAC_ME_INFO {ind;res} .....	188
8.3.2.4	Extended system info: MAC_ME_EXT.{req;ind;res;cfm} .....	188
8.3.3	Channel map: MAC_ME_CHANMAP {ind;res}.....	189
8.3.4	Status reports: MAC_ME_STATUS {req;ind;res;cfm} .....	189
8.3.5	Error reports: MAC_ME_ERROR {ind;res} .....	189
8.4	Flow control .....	189
8.4.1	MA SAP flow control.....	189
8.4.2	MB SAP flow control .....	189
8.4.3	MC SAP flow control .....	189
9	Broadcast and connectionless procedures .....	192
9.1	Downlink broadcast and connectionless procedures .....	192
9.1.0	General.....	192
9.1.1	Downlink broadcast procedure .....	192
9.1.1.1	Broadcast information.....	192
9.1.1.2	Channel selection for downlink broadcast services.....	192

9.1.1.3	Downlink broadcast procedure description.....	194
9.1.2	Downlink connectionless procedure.....	194
9.1.2.1	Channel selection at the RFP.....	194
9.1.2.2	Downlink connectionless procedure description.....	194
9.1.3	Paging broadcast procedure.....	195
9.1.3.0	General.....	195
9.1.3.1	RFP paging broadcasts.....	195
9.1.3.2	PP paging procedures.....	197
9.1.3.2.1	PP paging detection.....	197
9.1.3.2.2	PP paging processing.....	197
9.1.4	Downlink connectionless procedures for ULE.....	198
9.1.4.0	General.....	198
9.1.4.1	Transmission over the ULE dummy bearer.....	198
9.1.4.2	Transmission over the additional C/L bearers.....	198
9.1.4.2.0	General.....	198
9.1.4.2.1	MAC signalling.....	198
9.1.4.3	Announcement via the B <sub>U</sub> paging channel.....	199
9.1.4.4	Routing and instance separation.....	199
9.1.4.5	Additional attributes.....	199
9.1.4.6	Encryption.....	199
9.1.4.7	Destination and addressing: unicast and multicast.....	200
9.1.4.7.0	General.....	200
9.1.4.7.1	C/L downlink unicast service.....	200
9.1.4.7.2	C/L downlink multicast service.....	200
9.1.4.7.3	Identities in C/L downlink multicast service.....	200
9.1.4.8	Scrambling.....	200
9.1.4.9	Time references for the multicast transmission.....	201
9.1.4.9.1	Time reference for transmission over the dummy bearer.....	201
9.1.4.9.2	Time reference for transmission over additional C/L bearers.....	201
9.2	Uplink connectionless procedures.....	201
9.2.1	General.....	201
9.2.2	Bearer selection for the connectionless uplink.....	201
9.2.3	Procedure for the connectionless uplink.....	202
9.2.3.1	Predicates.....	202
9.2.3.2	PT D-field construction.....	202
9.2.3.3	PT transmission sequence.....	202
9.2.3.4	FT procedure.....	203
9.3	Non-continuous broadcast procedure.....	203
9.3.0	General.....	203
9.3.1	Request for specific Q channel information.....	203
9.3.1.0	General.....	203
9.3.1.1	A-field procedure.....	203
9.3.1.2	B-field procedure.....	204
9.3.2	Request for a new dummy bearer.....	204
9.4	"No-emission" mode procedures.....	204
9.4.0	General.....	204
9.4.1	Initiation of the "no-emission" mode.....	205
9.4.1.1	Successful activation (countdown to zero).....	205
9.4.1.2	Multiframe countdown stopped by FT.....	205
9.4.1.3	Multiframe countdown stopped by PT.....	206
9.4.1.4	PT does not receive multiframe countdown "zero".....	207
9.4.2	Behaviour during power-down-mode.....	207
9.4.3	Waking up, FT initiated.....	207
9.4.4	Waking up, PT initiated.....	211
9.5	Ultra Low Energy (ULE) Mode Procedures.....	212
9.5.0	General.....	212
9.5.1	Initiation of the ULE Mode.....	212
9.5.1.0	General.....	212
9.5.1.1	ULE Dummy Bearer Subfield 0.....	213
9.5.1.2	ULE Dummy Bearer Subfield 1.....	214
9.5.1.3	ULE Dummy Bearer Subfield 2.....	216
9.5.1.3.0	General.....	216

9.5.1.3.1	M <sub>U</sub> Channel Info 1 coding .....	217
9.5.1.3.2	M <sub>U</sub> Channel Info 2 coding .....	218
9.5.1.4	ULE Dummy Bearer Subfield 3 .....	219
9.5.1.5	Elements of the ULE paging system .....	220
9.6	U-NEMo mode procedures .....	221
9.6.1	General .....	221
9.6.2	Initiation of the U-NEMo mode .....	221
9.6.3	Behaviour during U-NEMo mode .....	221
9.6.4	Waking up, PT initiated .....	221
9.6.5	Raising a dummy bearer .....	223
9.6.5.1	General .....	223
9.6.5.2	Scanning, blind slot map, blind slot count .....	224
9.6.5.3	Identity Free ULE dummy .....	224
9.6.5.4	NEMo++ dummy .....	224
9.6.6	Waking up, FT initiated .....	225
9.6.6.1	Waking up for ULE without waking from no-emissions mode .....	225
9.6.6.2	Waking up for ULE and waking from no-emissions mode .....	225
10	Connection oriented service procedures .....	225
10.1	Overview .....	225
10.2	C/O connection setup .....	226
10.2.0	Introduction .....	226
10.2.1	General .....	226
10.2.2	Initiation of a basic and a normal connection setup .....	226
10.2.3	Initiation of a fast connection setup .....	227
10.2.4	Connection setup procedure description .....	227
10.2.4.1	Creation of MBCs .....	227
10.2.4.2	Establishment of a single bearer duplex connection of a known service type .....	229
10.2.4.3	Establishment of multi-bearer connections and connections needing service negotiation .....	230
10.2.4.3.0	General .....	230
10.2.4.3.1	Symmetric connection .....	232
10.2.4.3.2	Asymmetric uplink connection .....	232
10.2.4.3.3	Asymmetric downlink connection .....	232
10.2.4.3.4	Connection established .....	233
10.2.5	Expedited connections .....	233
10.3	C/O connection modification .....	233
10.3.1	Advanced connection: bandwidth modification .....	233
10.3.1.0	General .....	233
10.3.1.1	Suspend and resume .....	235
10.3.1.1.0	General .....	235
10.3.1.1.1	Expedited suspend and resume .....	235
10.3.1.2	MAC resume paging .....	235
10.3.1.3	ULE resume paging .....	236
10.3.2	Advanced connection: service type or slot type modification .....	236
10.3.2.0	General .....	236
10.3.2.1	Procedure for service type modification .....	236
10.3.2.2	Procedures for slot type modification .....	237
10.3.2.2.1	Procedure for slot type modification full to double .....	237
10.3.2.2.2	Procedure for slot type modification double to full .....	238
10.3.2.2.3	Procedures for slot type modification to/from long .....	238
10.3.2.2.4	Procedure for slot type modification in multibearer connections .....	239
10.3.2.3	Procedure for ECN number modification in an advanced connection .....	239
10.3.3	Connection type modification .....	239
10.3.3.0	General .....	239
10.3.3.1	Procedure for connection type modification basic to advanced .....	240
10.3.3.1.1	General procedure .....	240
10.3.3.1.2	Procedure for connection type modification basic to advanced plus slot type modification full to double .....	240
10.3.3.1.3	Procedure for connection type modification basic to advanced plus slot type modification full to long .....	241
10.3.3.2	Procedure for connection type modification advanced to basic .....	241
10.3.4	Modulation type modification .....	242

10.3.4.0	General .....	242
10.3.4.1	Adaptive code rate .....	243
10.3.5	Additional rules for Attributes_T message exchange .....	243
10.4	C/O connection release .....	244
10.4.1	General .....	244
10.4.1.0	Release causes .....	244
10.4.1.1	C/O connection release in packet mode connections .....	245
10.4.2	Procedure description .....	245
10.5	C/O bearer setup .....	245
10.5.1	Single bearer setup procedures .....	245
10.5.1.0	General .....	245
10.5.1.1	Basic bearer setup procedure .....	245
10.5.1.2	A-field advanced single bearer setup procedure .....	248
10.5.1.2.0	General .....	248
10.5.1.2.1	PT initiated .....	248
10.5.1.2.2	FT initiated .....	251
10.5.1.3	B-field single bearer setup procedure .....	252
10.5.1.3.0	General .....	252
10.5.1.3.1	PT initiated .....	252
10.5.1.3.2	FT initiated .....	254
10.5.1.4	Double simplex setup procedure .....	255
10.5.1.4.1	Terminology and Predicates .....	255
10.5.1.4.2	General description .....	255
10.5.1.4.3	Channel selection procedure for circuit mode connections .....	256
10.5.1.4.4	Channel selection procedure for packet mode connections .....	257
10.5.1.4.5	Indirect setup procedure .....	258
10.5.1.4.6	Direct setup procedure .....	258
10.5.1.4.7	Handling of encrypted connections .....	262
10.5.1.5	Additional duplex bearer setup procedure .....	263
10.5.1.5.1	General and predicates .....	263
10.5.1.5.2	General and predicates .....	264
10.5.1.6	Repeater Part (REP) procedures .....	264
10.5.1.6.1	Complementary connection bearer setup .....	264
10.5.1.6.2	Double duplex bearer setup procedure: Mapping procedure .....	265
10.5.1.7	Usage of TA special code "111" and M <sub>T</sub> message "B-field setup, first PT transmission" .....	266
10.5.1.7.0	General .....	266
10.5.1.7.1	Default rules for TA code "111" .....	267
10.5.1.7.2	Default rules for M <sub>T</sub> message "B-field setup, first transmission" .....	267
10.5.1.8	Expedited bearer setup procedures .....	268
10.5.1.8.1	General .....	268
10.5.1.8.2	Procedure for Single-burst setup and release .....	268
10.5.1.8.3	Procedure for Multi burst setup .....	270
10.5.1.8.4	Announcement "Ready for Release" .....	271
10.5.1.8.5	Indirect FT initiated expedited bearer setup procedure .....	272
10.5.1.8.6	Insertion of U-plane in "Expedited access request" messages .....	272
10.5.1.8.7	Connected state (TBC) in expedited bearer setup .....	273
10.5.1.8.8	Encryption synchronization in expedited bearer setup .....	273
10.5.1.8.9	Use of short slots in expedited connections .....	273
10.5.2	Channel list procedures .....	274
10.5.2.1	General .....	274
10.5.2.2	Description of the channel list messages .....	275
10.5.2.3	Usage of the channel list messages .....	275
10.6	C/O bearer handover .....	277
10.6.1	General .....	277
10.6.2	Duplex bearer handover procedure .....	278
10.6.2.1	PT initiated procedure .....	278
10.6.2.2	FT initiated procedure .....	278
10.6.3	Double simplex bearer handover .....	279
10.6.3.1	Procedure .....	279
10.6.3.2	Usage of quality control messages in bearer handover procedures .....	280
10.6.4	Bearer replacement .....	280
10.6.4.1	General bearer replacement .....	280

10.6.4.2	Frequency replacement .....	281
10.7	C/O bearer release .....	282
10.7.1	General.....	282
10.7.2	Bearer release procedure description .....	283
10.7.2.1	Unacknowledged release procedure.....	283
10.7.2.1.0	General .....	283
10.7.2.1.1	Crossed bearer release procedure .....	283
10.7.2.2	Acknowledged release procedure.....	284
10.7.2.3	Fast release procedure.....	284
10.7.2.4	REP relayed bearer release.....	285
10.7.3	Expedited bearer release procedures.....	285
10.7.3.0	General .....	285
10.7.3.1	General Expedited Release procedure.....	285
10.7.3.1.0	Usage .....	285
10.7.3.1.1	Procedure description .....	285
10.7.3.1.2	Exceptional cases and error handling .....	286
10.7.3.2	Special cases of expedited release procedures .....	286
10.7.3.2.1	Single-message expedited release procedure.....	286
10.7.3.2.2	Abnormal expedited release procedure.....	287
10.8	C/O data transfer .....	287
10.8.1	Higher layer associated signalling (C).....	287
10.8.1.0	General .....	287
10.8.1.1	C <sub>S</sub> channel data .....	287
10.8.1.1.0	General .....	287
10.8.1.1.1	Transmission principle .....	288
10.8.1.1.2	Numbering principle.....	288
10.8.1.2	C <sub>F</sub> channel data .....	288
10.8.1.2.0	General .....	288
10.8.1.2.1	Transmission principle .....	289
10.8.1.2.2	Numbering principle.....	289
10.8.1.3	Q1 and Q2 bit settings for all services except Ip_error_correct.....	289
10.8.1.3.0	Coding of the bits .....	289
10.8.1.3.1	Q1 and Q2 bit settings for MAC service Ip .....	289
10.8.1.3.2	Q1 and Q2 bit settings for MAC service Ip_error_detect .....	290
10.8.1.3.3	Q2 bit settings.....	290
10.8.1.3.4	Q1 bit settings.....	291
10.8.1.3.5	Q1 and Q2 settings when B-field is in B-mux modes.....	292
10.8.1.3.6	Q1 and Q2 settings when B-field is in "no-B-field" mode .....	293
10.8.1.3.7	Q1, Q2 and BCK settings when there are transitions in the coding rules or when the rules applicable to both directions are not the same.....	294
10.8.1.3.8	Q1 and Q2 settings when B-field mode is unknown .....	294
10.8.2	MOD-2 protected I channel operation (I <sub>p</sub> ).....	294
10.8.2.1	General .....	294
10.8.2.1.0	Introduction to MOD-2 protected I channel operation (I <sub>p</sub> ).....	294
10.8.2.1.1	Use of selective reception.....	295
10.8.2.2	Limiting the lifetime of packets .....	295
10.8.2.2.0	General .....	295
10.8.2.2.1	Lifetime setting and management.....	295
10.8.2.3	A-field shall always be correct.....	297
10.8.2.4	Use of the acknowledge bits.....	297
10.8.2.4.0	General .....	297
10.8.2.4.1	Q2 and BCK bit setting for Ip_error_correction services .....	297
10.8.2.4.2	BCK bit setting.....	298
10.8.2.5	Data jump procedures .....	298
10.8.2.5.0	General .....	298
10.8.2.5.1	New MOD-2 numbering in case of Bearer replacement .....	298
10.8.2.5.2	Unilateral jump.....	298
10.8.2.5.3	MAC Ip bearer reset.....	300
10.8.2.6	Bearer handover and bearer replacement procedures.....	300
10.8.2.6.1	General .....	300
10.8.2.6.2	Bearer handover in a MOD-2 protected I channel.....	300
10.8.2.6.3	Bearer replacement in a MOD-2 protected I channel .....	301

10.8.2.7	Exchange of data from/to higher layers .....	301
10.8.2.7.0	General .....	301
10.8.2.7.1	Operation if I <sub>PF</sub> channel is supported.....	302
10.8.3	Higher layer unprotected information (I <sub>N</sub> ) and MAC_error_detection services (I <sub>P</sub> ).....	302
10.8.3.1	I <sub>N</sub> _minimum_delay service (I <sub>NA</sub> ) .....	302
10.8.3.2	I <sub>N</sub> _normal_delay service (I <sub>NB</sub> ).....	303
10.8.3.2.1	General operation .....	303
10.8.3.2.2	Operation with restriction in the handover space .....	303
10.8.3.3	I <sub>P</sub> _error_detection service .....	304
10.8.3.3.0	General .....	304
10.8.3.3.1	Operation if I <sub>PF</sub> channel is supported.....	304
10.8.3.4	I <sub>P</sub> _encoded_protected service (I <sub>PX</sub> ) .....	304
10.8.4	Higher layer U-plane channel (I <sub>PF</sub> ) in E+U type mux.....	304
10.8.4.1	Purpose of the I <sub>PF</sub> channel .....	304
10.8.4.2	Activation of the E+U type mux mode .....	305
10.8.4.3	I <sub>PF</sub> procedures.....	305
10.8.4.3.0	General .....	305
10.8.4.3.1	I <sub>PF</sub> basic procedures .....	305
10.8.4.3.2	I <sub>PF</sub> advanced procedures .....	306
10.8.4.3.3	Special case: slots not multiple of 64 bits.....	306
10.8.4.4	I <sub>PF</sub> Mod-2 protected operation.....	307
10.8.4.5	I <sub>PF</sub> _error_detect operation .....	307
10.8.4.6	I <sub>PF</sub> _operation with I <sub>N</sub> service .....	307
10.8.4.7	Backcompatibility rule .....	308
10.9	C/O procedures for FT connections with CRFP.....	308
10.9.0	General.....	308
10.9.1	Dual C/O bearer setup.....	308
10.9.2	C/O connection release of connection with CRFP.....	308
10.9.3	C/O connection suspend and resume .....	308
11	Medium access layer management procedures .....	309
11.1	Broadcasting.....	309
11.1.1	RFP transmission .....	309
11.1.2	PP reception.....	309
11.2	Extended system information.....	309
11.2.1	PP requests .....	309
11.2.2	RFP response .....	309
11.3	PP states and state transitions .....	309
11.3.0	General.....	309
11.3.1	Actions in Idle_Unlocked and Active_Unlocked states.....	310
11.3.2	Entry into the Idle_Locked state .....	310
11.3.3	Actions in the Idle_Locked state.....	310
11.3.3.0	General .....	310
11.3.3.1	Page detection in Idle_Locked state.....	310
11.3.3.2	Setup detection in Idle_Locked state.....	311
11.3.4	Idle_Locked and Active_Locked state transitions .....	312
11.4	Physical channel selection.....	312
11.4.0	General.....	312
11.4.1	The channel selection lists .....	312
11.4.2	Physical channel and RFP selection at the PP .....	314
11.4.3	Physical channel selection at the RFP.....	316
11.4.4	Hand over criteria due to in-connection base identification .....	317
11.4.5	Handover criteria due to interference.....	317
11.4.6	Exception in channel selection rules for Ultra Low Energy devices .....	318
11.5	In-connection quality control .....	318
11.5.1	RFPI handshake .....	318
11.5.2	Frequency control .....	318
11.5.2.1	RFP measurement of frequency error .....	318
11.5.2.2	PT frequency correction .....	318
11.6	Maximum allowed system load at RFPs .....	319
11.7	PMID and FMID definitions .....	319
11.7.1	FMID definition.....	319