

ETSI EN 300 175-4 V2.9.1 (2022-03)



**Digital Enhanced Cordless Telecommunications (DECT);
Common Interface (CI);
Part 4: Data Link Control (DLC) layer**

[ETSI EN 300 175-4 V2.9.1 \(2022-03\)](https://standards.iteh.ai/catalog/standards/sist/f09040b9-3d86-40ae-8f55-d24e2d600c84/etsi-en-300-175-4-v2-9-1-2022-03)

<https://standards.iteh.ai/catalog/standards/sist/f09040b9-3d86-40ae-8f55-d24e2d600c84/etsi-en-300-175-4-v2-9-1-2022-03>

ReferenceREN/DECT-00354

KeywordsDECT, DLC, IMT-2000, mobility, radio, TDD,
TDMA

ETSI650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our

Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2022.
All rights reserved.

Contents

Intellectual Property Rights	13
Foreword.....	13
Modal verbs terminology.....	13
1 Scope	14
2 References	14
2.1 Normative references	14
2.2 Informative references.....	15
3 Definition of terms, symbols and abbreviations.....	16
3.1 Terms.....	16
3.2 Symbols.....	16
3.3 Abbreviations	17
4 Data Link Control (DLC) layer overview	19
4.1 General	19
4.2 C-plane services	20
4.3 U-plane services	21
4.4 Lower Layer Management Entity (LLME)	24
4.5 Instantiation in DLC U-plane	24
5 C-plane service characteristics.....	24
5.1 Data link service (LAPC+Lc).....	24
5.1.1 General.....	24
5.1.2 LAPC types of operation	25
5.1.3 Establishment of information transfer modes	25
5.1.3.1 Data Link Identifier (DLI)	25
5.1.3.2 LAPC states.....	26
5.2 Broadcast service (Lb).....	26
6 Frame structures for C-plane services.....	27
6.1 Data link service frame structure.....	27
6.1.0 Frame format type FA.....	27
6.1.1 General frame structure	27
6.1.2 Lc frame delimiting and transparency	28
6.1.3 Transmission order	28
6.1.4 Routing to logical channels.....	28
6.1.4.0 General	28
6.1.4.1 C _F /CL _F logical channel.....	29
6.1.4.2 C _S /CL _S logical channel.....	29
6.1.5 Invalid frames	29
6.2 Broadcast service frame structure.....	30
6.2.1 Standard frame structure	30
6.2.2 Extended frame structure	30
7 Elements of procedures and formats of fields for C-plane peer-to-peer communication.....	31
7.1 General	31
7.2 Address field formats	31
7.3 Address field parameters	31
7.3.1 REServed bit (RES)	31
7.3.2 Command Response (C/R) bit	31
7.3.3 SAPI field	31
7.3.4 New Link Flag (NLF) bit.....	32
7.3.5 LLN-field.....	32
7.3.6 Data Link Identifiers (DLI).....	32
7.4 Control field formats	33
7.5 Control field parameters	33
7.5.1 Poll/Final (P/F) bit	33

7.5.2	Multiple frame operation variables and sequence numbers	33
7.5.2.1	Modulus	33
7.5.2.2	Send state Variable V(S)	34
7.5.2.3	Acknowledge state Variable V(A)	34
7.5.2.4	Send sequence Number N(S)	34
7.5.2.5	Receive state Variable V(R)	34
7.5.2.6	Receive sequence Number N(R)	34
7.5.3	Unacknowledged operation variables and sequence numbers	34
7.5.4	Supervisory and Unnumbered function bits S and U	34
7.6	Length indicator field format	34
7.7	Length indicator field parameters	35
7.7.1	Length indicator field extension bit (N)	35
7.7.2	More data bit (M)	35
7.7.3	Length parameter (L _I)	35
7.7.4	Extended length parameter (L _{JJ})	36
7.7.5	Reserved bit (RES)	36
7.8	Fill field format	36
7.9	Checksum field format	36
7.10	Checksum field parameters	37
7.11	Commands and responses	38
7.11.0	General	38
7.11.1	Information (I) command	38
7.11.2	Receive Ready (RR) command/response	38
7.11.3	Receive Not Ready (RNR) command/response	39
7.11.4	REJect (REJ) command/response	39
7.11.5	Set Asynchronous Balanced Mode (SABM) command	39
7.11.6	Disconnect Mode (DM) response	39
7.11.7	Unnumbered Information (UI) command	39
7.11.8	DISConnect (DISC) command	40
7.11.9	Unnumbered ACK (UA) response	40
8	Primitives	40
8.1	Primitive types	40
8.2	Primitives to the MAC layer (lower layer)	40
8.3	Primitives to the NWK layer (higher layer)	41
8.3.0	General	41
8.3.1	Parameter definitions	41
8.3.2	S-SAP primitives	42
8.3.2.0	List of primitives	42
8.3.2.1	DL_ESTABLISH primitive	42
8.3.2.2	DL_RELEASE primitive	43
8.3.2.3	DL_DATA primitive	43
8.3.2.4	DL_UNIT_DATA primitive	43
8.3.2.5	DL_SUSPEND primitive	43
8.3.2.6	DL_RESUME primitive	44
8.3.2.7	DL_ENC_KEY primitive	44
8.3.2.8	DL_ENCRYPT primitive	44
8.3.2.9	DL_SERVICE_MOD primitive	45
8.3.3	B-SAP primitives	45
8.3.3.0	List of primitives	45
8.3.3.1	DL_BROADCAST primitive	45
8.3.3.2	DL_EXPEDITED primitive	45
8.4	Primitives to the interworking unit	46
8.4.0	General	46
8.4.1	Parameter definitions	46
8.4.2	LU _X -SAP primitives	46
8.4.2.0	List of primitives	46
8.4.2.1	DL_U_DATA primitive	46
8.4.2.2	DL_U_UNIT_DATA primitive	47
8.4.2.3	DL_U_ERROR primitive	47
9	C-plane peer-to-peer procedures	47

9.1	General	47
9.2	Point-to-point acknowledged operation.....	48
9.2.1	Procedure for the use of the P/F bit	48
9.2.1.1	Class A acknowledged information transfer	48
9.2.1.2	Class B acknowledged information transfer	48
9.2.2	Use of LLN	48
9.2.2.1	Class A operation	48
9.2.2.2	Class B operation	48
9.2.3	Link establishment and information transfer in class A operation.....	49
9.2.3.1	Establishing class A operation	49
9.2.3.2	Class A acknowledged information transfer	49
9.2.3.3	Transmission of class A I-frames	50
9.2.3.4	Reception of class A I-frames	50
9.2.3.5	Receiving acknowledgements	50
9.2.3.6	Waiting for acknowledgement	51
9.2.3.7	Release of class A operation	51
9.2.3.8	Re-establishment of class A operation	51
9.2.4	Establishing class B multiple frame operation.....	52
9.2.4.1	Overview	52
9.2.4.2	Class B multiple frame establishment procedures.....	52
9.2.4.3	Class B LLN assignment procedures	53
9.2.4.3.0	General	53
9.2.4.3.1	PT establishment	54
9.2.4.3.2	FT establishment	54
9.2.5	Link maintenance and information transfer in class B multiple frame operation	54
9.2.5.0	General	54
9.2.5.1	Transmitting I-frames.....	55
9.2.5.2	Receiving I-frames	55
9.2.5.2.0	General	55
9.2.5.2.1	P bit set to 1	55
9.2.5.2.2	P bit set to 0	55
9.2.5.3	Sending and receiving acknowledgements.....	56
9.2.5.3.1	Sending acknowledgements	56
9.2.5.3.2	Receiving acknowledgements	56
9.2.5.4	Receiving REJ-frames.....	56
9.2.5.5	Receiving RNR-frames	57
9.2.5.6	LAPC own receiver busy condition	58
9.2.5.7	Waiting acknowledgement.....	59
9.2.5.8	Appropriate supervisory frame.....	59
9.2.6	Release of class B multiple frame operation.....	59
9.2.7	Link suspension and resumption.....	60
9.2.7.1	Link suspension.....	60
9.2.7.1.0	General	60
9.2.7.1.1	Class B acknowledged suspend	60
9.2.7.1.2	Unacknowledged suspend	61
9.2.7.2	Class B link resumption	62
9.2.7.3	Connection handover	63
9.2.7.3.0	General	63
9.2.7.3.1	Class A connection handover	65
9.2.7.3.2	Class B connection handover	65
9.2.7.3.3	Expiry of connection handover timer	66
9.2.8	Re-establishment of class B multi-frame operation	66
9.2.8.1	Criteria for re-establishment.....	66
9.2.8.2	Procedure	66
9.2.9	Exception handling	67
9.2.9.1	General	67
9.2.9.2	Class B exception condition reporting and recovery.....	67
9.2.9.2.0	General	67
9.2.9.2.1	N(S) sequence error.....	67
9.2.9.2.2	N(R) sequence error	68
9.2.9.2.3	Timer recovery condition	68
9.2.9.2.4	Collision of identical transmitted and received commands	68

9.3	Unacknowledged operation	68
9.3.1	Use of LLN for unacknowledged information transfer	68
9.3.2	Class U link establishment	68
9.3.3	Unacknowledged information transfer	68
9.3.3.1	Transmission of unacknowledged information	68
9.3.3.2	Reception of unacknowledged information	68
9.3.4	Unacknowledged release	69
9.4	Broadcast operation	69
9.4.1	Normal operation	69
9.4.1.1	Procedure in the Fixed radio Termination (FT)	69
9.4.1.2	Procedure in the Portable radio Termination (PT)	69
9.4.2	Expedited operation	69
9.4.2.1	Procedure in the Fixed radio Termination (FT)	69
9.4.2.2	Procedure in the Portable radio Termination (PT)	70
9.5	MAC layer interfaces	70
9.5.1	MC-SAP	70
9.5.1.1	C-plane overview	70
9.5.1.2	C-plane service data procedures	70
9.5.1.3	U-plane service data	71
9.5.2	MB-SAP	71
9.5.2.0	General	71
9.5.2.1	C-plane service data procedures	71
9.5.2.2	U-plane service data	72
9.5.3	MA-SAP	72
9.5.3.1	Overview	72
9.5.3.2	Service data procedures	72
10	Management procedures	72
10.1	Lower Layer Management Entity (LLME)	72
10.2	MAC connection management	73
10.2.0	General	73
10.2.1	MAC connection set-up	73
10.2.2	MAC connection release	73
10.2.3	MAC connection modification	74
10.2.4	MAC connection identifiers	74
10.2.4.1	Overview	74
10.2.4.2	Advanced MAC Connection Identifiers (AMCI)	75
10.2.4.3	Basic MAC Connection Identifiers (BMCI)	75
10.2.4.4	MAC Connection Endpoint Identifier (MCEI)	75
10.2.5	Selection of logical channel (C _S or C _F)	75
10.3	DLC C-plane (LAPC) management	76
10.3.0	General	76
10.3.1	Provision of link signature	76
10.3.2	Routing of connection oriented links	77
10.3.3	Routing of connectionless links	77
10.4	DLC U-plane (LUX) management	77
10.4.0	General	77
10.4.1	U-plane establishment	77
10.4.2	U-plane release	78
10.4.3	U-plane suspend and resume	78
10.5	Connection handover management	78
10.6	Cipherring management	79
10.6.1	Cipherring management in cases where the NWK layer executes the cipherring related MM procedure	79
10.6.1.0	General	79
10.6.1.1	Providing a key to the MAC layer	79
10.6.1.2	Starting and stopping the cipherring	79
10.6.1.3	Connection handover	79
10.6.2	Cipherring management in cases where the NWK layer does not execute the cipherring related MM procedure	80
10.7	Broadband data link management	80
11	U-plane service characteristics	80

11.1	General	80
11.2	LU1 TRansparent UnProtected service (TRUP)	81
11.3	LU2 Frame RELay service (FREL).....	82
11.3.1	General.....	82
11.3.2	Checksum operation	83
11.3.3	Segmentation and transmission class	83
11.3.4	Data transmission.....	84
11.3.4.1	Send side procedure	84
11.3.4.2	Receive side procedure	84
11.4	LU3 Frame SWITching service (FSWI).....	84
11.5	LU4 Forward Error Correction (FEC) service.....	85
11.6	LU5 Basic RATE adaption service (BRAT).....	85
11.6.1	Overview	85
11.6.2	Protected service operation.....	86
11.6.2.1	General	86
11.6.2.2	Data buffering and initial rate adaptation.....	87
11.6.2.3	Multi-channel set multiplexing	88
11.6.2.4	Segmentation of Multiplexed Data Units (MDU).....	89
11.6.2.5	Frame sequencing and addition of control and fill octets.....	90
11.6.2.6	Frame transmission	91
11.6.3	Unprotected service operation	91
11.6.3.1	General	91
11.6.3.2	Data buffering and initial rate adaption.....	92
11.6.3.3	Multi-channel set multiplexing	92
11.6.3.4	Segmentation of MDUs.....	93
11.6.3.5	Frame transmission	93
11.7	LU6 Secondary RATE adaption (SRAT) service	94
11.7.1	General.....	94
11.8	LU16 ESCape Service (ESC).....	95
11.8.1	General.....	95
11.9	LU7 64 kbit/s data bearer service	95
11.9.1	General.....	95
11.9.2	Physical layer service.....	95
11.9.3	MAC layer service	96
11.9.4	DLC layer service	96
11.9.4.1	Architectural model.....	96
11.9.4.1.0	General	96
11.9.4.1.1	Transmit (Tx) frame buffering	96
11.9.4.1.2	Receive (Rx) frame buffering	96
11.9.4.2	Automatic-Repeat-Request (ARQ) and Forward Error Control (FEC).....	97
11.9.4.2.0	General	97
11.9.4.2.1	Control field	98
11.9.4.2.2	Information field.....	100
11.9.4.2.3	ARQ checksum.....	100
11.9.4.3	Procedures for normal operation	101
11.9.4.3.0	General	101
11.9.4.3.1	Establishment and synchronization procedures	101
11.9.4.3.2	Active phase	103
11.9.4.3.3	Release.....	104
11.9.4.4	Exceptional procedures	104
11.9.4.4.0	General	104
11.9.4.4.1	Invalid frame condition	104
11.9.4.4.2	Establishment	105
11.9.4.4.3	Transmitting frames.....	105
11.9.4.4.4	Receiving frames	105
11.9.4.4.5	Sending acknowledgements	105
11.9.4.4.6	Forwarding of received data	105
11.9.4.4.7	N(R) sequence error	105
11.9.4.4.8	N(O) sequence error	105
11.9.4.4.9	N(S) sequence error.....	106
11.9.4.4.10	Format error.....	106
11.9.4.4.11	Abnormal release.....	106

11.9.4.4.12	Implicit reset.....	106
11.9.5	Network layer service.....	107
11.9.5.1	LCE service.....	107
11.9.5.2	CC service.....	107
11.10	LU8 service.....	107
11.10.0	General.....	107
11.10.1	Physical layer service.....	107
11.10.2	MAC layer service.....	107
11.10.3	DLC layer service.....	107
11.11	LU9 - Unprotected Rate Adaption for V series Equipment (RAVE) Service.....	108
11.11.1	Overview.....	108
11.11.1.0	General.....	108
11.11.1.1	FU9 frame structure.....	108
11.11.1.1.1	General frame structure.....	108
11.11.1.1.2	FU9 buffering procedures.....	109
11.11.1.1.3	Connection handover.....	109
11.11.1.1.4	Transmission order.....	109
11.11.2	Alignment signal management.....	109
11.11.2.1	General.....	109
11.11.2.2	Procedures.....	110
11.11.3	V.24 Signalling.....	111
11.11.3.1	General.....	111
11.11.3.2	Transmitter procedures.....	111
11.11.3.3	Receiver procedures.....	111
11.11.4	Rate Coding.....	111
11.11.4.1	General.....	111
11.11.4.2	Transmitter procedures.....	112
11.11.4.3	Receiver procedures.....	113
11.11.5	DECT Independent Clocking (DIC).....	113
11.11.5.1	General.....	113
11.11.5.2	Measurement of phase differences.....	113
11.11.5.3	Compensation control rules.....	114
11.11.5.3.1	General.....	114
11.11.5.3.2	Optimizing error resilience.....	114
11.11.6	Information field.....	115
11.11.6.1	General.....	115
11.11.6.2	User data rates.....	115
11.11.6.3	Information field filling rule.....	116
11.11.7	Primitives.....	116
11.12	LU10 Enhanced Frame RELay (EFREL) service.....	117
11.12.1	General.....	117
11.12.2	Segmentation and transmission class.....	118
11.12.3	Data transmission.....	118
11.12.3.1	Send side procedures.....	118
11.12.3.1.0	General.....	118
11.12.3.1.1	"Early transmission" option.....	119
11.12.3.2	Receive side procedure.....	119
11.12.3.2.0	General.....	119
11.12.3.2.1	Standard SDU delivery mode.....	119
11.12.3.2.2	In-sequence SDU delivery mode.....	120
11.12.3.2.3	PDU-in-sequence delivery mode.....	120
11.12.3.2.4	PDU-as-received delivery mode.....	120
11.12.4	SDU boundaries definition.....	120
11.12.4.0	General.....	120
11.12.4.1	Infinite SDU mode.....	121
11.12.5	Use over C/L downlink channels.....	121
11.12.5.0	General.....	121
11.12.5.1	Use over C/L downlink channels: unicast mode.....	121
11.12.5.2	Use over C/L downlink channels: multicast mode.....	121
11.12.5.2.0	General.....	121
11.12.5.2.1	DLC acknowledgement in multicast mode.....	121
11.13	LU11 service.....	122

11.13.0	General.....	122
11.13.1	Physical layer service.....	122
11.13.2	MAC layer service.....	122
11.13.3	DLC layer service.....	122
11.14	LU12 UNprotected Framed service (UNF).....	122
11.14.1	General.....	122
11.14.2	DLC layer service.....	122
11.14.2.0	General.....	122
11.14.2.1	Segmentation.....	123
11.14.2.2	Data transmission.....	124
11.14.2.2.1	Send side procedure.....	124
11.14.2.2.2	Receive side procedure.....	124
11.15	LU13 Enhanced Frame RELay service with CRC (EFREL-CRC).....	125
11.15.1	General.....	125
11.15.2	SDU CRC generation.....	125
11.15.3	Use over C/L downlink channels.....	125
11.15.3.0	General.....	125
11.15.3.1	Use over C/L downlink channels: unicast mode.....	126
11.15.3.2	Use over C/L downlink channels: multicast mode.....	126
11.15.3.2.0	General.....	126
11.15.3.2.1	DLC acknowledgement in multicast mode.....	126
11.16	LU14 Enhanced Frame RELay service with CCM (EFREL-CCM).....	126
11.16.1	General.....	126
11.16.2	LU14 SDU structure.....	126
11.16.2.0	General.....	126
11.16.2.1	SDU sizes.....	127
11.16.2.2	Security model.....	127
11.16.2.3	SDU processing.....	127
11.16.2.4	Limitations.....	128
11.16.2.5	CCM sequence numbers.....	128
11.16.2.6	CCM control procedures.....	128
11.16.3	Use over C/L downlink channels.....	128
11.16.3.0	General.....	128
11.16.3.1	Use over C/L downlink channels: unicast mode.....	128
11.16.3.2	Use over C/L downlink channels: multicast mode.....	129
11.16.3.2.0	General.....	129
11.16.3.2.1	DLC acknowledgement in multicast mode.....	129
12	Frame structures for U-plane services.....	129
12.1	General.....	129
12.2	FU1 frame structure.....	130
12.2.1	General frame structure.....	130
12.2.2	FU1 buffering procedures.....	131
12.2.3	Minimum delay (speech) operation.....	132
12.2.4	Connection handover.....	132
12.2.5	Transmission order.....	132
12.3	FU2 frame structure.....	132
12.3.1	General frame structure.....	132
12.3.2	FU2 buffering procedures.....	133
12.3.3	Connection handover.....	133
12.3.4	Transmission order.....	133
12.4	FU3 frame structure.....	133
12.4.1	General frame structure.....	133
12.4.2	FU3 buffering procedures.....	134
12.4.3	Connection handover.....	135
12.4.4	Transmission order.....	135
12.5	FU4 frame structure.....	135
12.5.1	General frame structure.....	135
12.5.2	FU4 buffering procedures.....	136
12.5.3	Connection handover.....	136
12.5.4	Transmission order.....	136
12.6	FU5 frame structure.....	136

12.6.1	General frame structure	136
12.6.2	FU5 buffering procedures	137
12.6.3	Connection handover	138
12.6.4	Transmission order	138
12.7	FU6 frame structure.....	138
12.7.1	General frame structure	138
12.7.2	FU6 buffering procedures	139
12.7.3	Connection handover	139
12.7.4	Transmission order	139
12.8	FU7 frame structure.....	139
12.9	FU8 frame structure.....	139
12.10	FU9 frame structure.....	139
12.11	FU10 frame structure.....	140
12.11.1	General frame structure	140
12.11.1.0	General	140
12.11.1.1	Specific for MAC service I_{PK}	142
12.11.2	Transmission of FU10c and FU10d frames	143
12.11.2.0	General	143
12.11.2.1	Insertion of the FU10c frame in an FU10a frame of the opposite link.....	143
12.11.2.2	Transmission of the F10c frame using the G_F channel.....	143
12.11.2.3	Insertion of the FU10d frame in an FU10a frame of the opposite link	144
12.11.2.4	Transmission of the FU10d frame using the G_{FA} channel.....	144
12.11.3	FU10 buffering procedures	144
12.11.4	Connection handover	144
12.11.5	Transmission order	144
12.12	FU12 frame structure.....	145
12.12.1	General frame structure	145
12.12.2	FU12 buffering procedures	145
12.12.3	Connection handover	146
12.12.4	Transmission order	146
13	Elements of procedures and formats of fields for U-plane peer-to-peer communication	146
13.1	General	146
13.2	Address elements.....	146
13.2.1	Address field format	146
13.2.2	Address field parameters	147
13.3	Length indicator elements	147
13.3.1	Length indicator field format	147
13.3.1.1	Length indicator field format for all services except LU10	147
13.3.1.2	Length indicator field format for service LU10	147
13.3.2	Length indicator field parameters	148
13.3.2.1	Length indicator field parameters for all services except LU10.....	148
13.3.2.2	Length indicator field parameters for LU10 service	149
13.3.2.2.0	General	149
13.3.2.2.1	Meaning of the more (M) bit	151
13.4	Sequence number elements	152
13.4.1	Send sequence number format	152
13.4.2	Send sequence number parameters	152
13.4.3	Receive sequence number format	152
13.4.4	Receive sequence number parameters	153
13.5	Fill elements - Fill field format	153
14	U-plane peer-to-peer procedures	153
14.1	General	153
14.2	Frame transmission principles.....	153
14.2.1	Sequence numbering.....	153
14.2.2	Acknowledgements.....	154
14.2.2.1	Sending acknowledgements	154
14.2.2.2	Receiving acknowledgements	154
14.2.3	Transmission classes	154
14.2.3.0	General	154
14.2.3.1	Class 0: No LU_X retransmission or sequencing.....	154

14.2.3.2	Class 1: no LU _X retransmission.....	155
14.2.3.2.0	General	155
14.2.3.2.1	Class 1: use over C/L downlink channels.....	155
14.2.3.3	Class 2: variable throughput, limited delay LU _X retransmission.....	155
14.2.3.4	Class 3: fixed throughput LU _X retransmission	156
14.2.4	Operation parameter negotiation.....	156
14.3	Frame transmission procedures	156
14.3.1	General.....	156
14.3.2	Class 0 procedures	156
14.3.2.0	General	156
14.3.2.1	Sending side procedure	157
14.3.2.2	Receiving side procedure	157
14.3.3	Class 1 procedures	157
14.3.3.0	General	157
14.3.3.1	Sending side procedure	157
14.3.3.2	Receiving side procedure	158
14.3.4	Class 2 procedures	158
14.3.4.0	General	158
14.3.4.1	Sending side procedure	158
14.3.4.1.0	General	158
14.3.4.1.1	Synchronization message sending side procedure (LU10).....	160
14.3.4.1.2	Tx side end-of-activity rule	160
14.3.4.1.3	Abnormal SDU termination/abort signal (LU10 only).....	161
14.3.4.1.4	Retransmission procedure.....	162
14.3.4.2	Receiving side procedure	162
14.3.4.2.0	General	162
14.3.4.2.1	Acknowledgement procedure	162
14.3.4.2.2	Rx side end-of-activity rule	164
14.3.4.2.3	Retransmission request procedure	164
14.3.4.2.4	SDU delivery procedure	165
14.3.4.2.5	Synchronization message receiver side procedure (LU10).....	165
14.3.4.2.6	Reception of an abnormal SDU termination/abort signal (LU10).....	166
14.3.5	Class 3 procedures	166
14.3.5.0	General	166
14.3.5.1	Sending side procedure	166
14.3.5.2	Receiving side procedure	167
Annex A (normative): System parameters.....		169
A.1	LAPC timer values	169
A.2	U-plane timer values	170
A.3	Constants	170
A.3.1	Retransmission counter (N250).....	170
A.3.2	Maximum number of CHO attempts (N251)	170
Annex B (normative): Checksum algorithms.....		171
B.1	Arithmetic conventions	171
B.2	Coding algorithm.....	171
B.3	Decoding algorithm.....	171
B.4	Some examples.....	172
Annex C (informative): MAC connection states.....		173
Annex D (normative): Mapping of agreed channel rates to MCS sizes		174
D.0	General	174
D.1	Protected class operation	174
D.2	Unprotected class operation	175

Annex E (normative):	LU12 applications	176
E.1	G.729.1 over 32 kbit/s channel.....	176
E.1.0	General	176
E.1.1	G.729.1 payload format.....	176
E.1.1.0	General.....	176
E.1.1.1	G.729.1 payload header coding	177
E.1.2	Operations	179
E.1.2.1	Encoder bit rate.....	179
E.1.2.2	Protection against random errors	179
Annex F (informative):	Bibliography.....	180
Annex G (informative):	Change history	181
History		182

iTeh STANDARD PREVIEW (standards.iteh.ai)

[ETSI EN 300 175-4 V2.9.1 \(2022-03\)](https://standards.iteh.ai/catalog/standards/sist/f09040b9-3d86-40ae-8f55-d24e2d600c84/etsi-en-300-175-4-v2-9-1-2022-03)
<https://standards.iteh.ai/catalog/standards/sist/f09040b9-3d86-40ae-8f55-d24e2d600c84/etsi-en-300-175-4-v2-9-1-2022-03>

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

(standards.iteh.ai)

This European Standard (EN) has been produced by ETSI Technical Committee Digital Enhanced Cordless Telecommunications (DECT).

The present document is part 4 of a multi-part deliverable ([1] to [8]). Full details of the entire series can be found in part 1 [1].

Further details of the DECT system may be found in ETSI TR 101 178 [i.1] and ETSI ETR 043 [i.2].

National transposition dates

Date of adoption of this EN:	23 March 2022
Date of latest announcement of this EN (doa):	30 June 2022
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 December 2022
Date of withdrawal of any conflicting National Standard (dow):	31 December 2023

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document is one of the parts of the specification of the Digital Enhanced Cordless Telecommunications (DECT) Common Interface (CI).

The present document specifies the Data Link Control (DLC) layer. The DLC layer is part 4 of the DECT CI standard and layer 2b of the DECT protocol stack.




Figure 1.1

Two planes of operation are specified for this DLC (sub)layer. These planes are called the Control plane (C-plane) and the User plane (U-plane).

The C-plane is mostly concerned with the DECT signalling aspects. It provides a reliable point-to-point service that uses a link access protocol to offer error protected transmission of Network (NWK) layer messages. The C-plane also provides a separate point-to-multipoint (broadcast) service (Lb).

The U-plane is only concerned with end-to-end user information. This plane contains most of the application dependent procedures of DECT. Several alternative services (both circuit-mode and packet-mode) are defined as a family of independent entities. Each service provides one or more point-to-point U-plane data links, where the detailed characteristics of those links are determined by the particular needs of each service. The defined services cover a wide range of performance, from "unprotected with low delay" for speech applications to "highly protected with variable delay", for local area network applications.

NOTE: The performance of the DLC services need not be tight to any particular application. For example the "unprotected with low delay" service could also be used for data applications, e.g. if some data protection is provided outside the DECT protocol.

The present document uses the layered model principles and terminology as described in Recommendations ITU-T X.200 [14] and X.210 [15].

The present document includes New Generation DECT, a further development of the DECT standard introducing wideband speech, improved data services, new slot types and other technical enhancements.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 300 175-1: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 1: Overview".
- [2] ETSI EN 300 175-2: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 2: Physical Layer (PHL)".
- [3] ETSI EN 300 175-3: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 3: Medium Access Control (MAC) layer".
- [4] Void.
- [5] ETSI EN 300 175-5: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 5: Network (NWK) layer".
- [6] ETSI EN 300 175-6: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 6: Identities and addressing".
- [7] ETSI EN 300 175-7: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 7: Security features".
- [8] ETSI EN 300 175-8: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 8: Speech and audio coding and transmission".
- [9] ETSI TS 144 006: "Digital cellular telecommunications system (Phase 2+) (GSM); Mobile Station - Base Station System (MS - BSS) interface; Data Link (DL) layer specification (3GPP TS 44.006)".
- [10] Recommendation ITU-T Q.920: "ISDN user-network interface data link layer - General aspects".
- [11] Recommendation ITU-T Q.921: "ISDN user-network interface - Data link layer specification".
- [12] Recommendation ITU-T V.42: "Error-correcting procedures for DCEs using asynchronous-to-synchronous conversion".
- [13] Recommendation ITU-T V.110: "Support by an ISDN of data terminal equipments with V-Series type interfaces".
- [14] Recommendation ITU-T X.200: "Information technology - Open Systems Interconnection - Basic Reference Model: The basic model".
- [15] Recommendation ITU-T X.210: "Information technology - Open Systems Interconnection - Basic Reference Model: Conventions for the definition of OSI services".
- [16] ISO/IEC 8073: "Information technology -- Open Systems Interconnection -- Protocol for providing the connection-mode transport service".
- [17] ETSI EN 301 649: "Digital Enhanced Cordless Telecommunications (DECT); DECT Packet Radio Service (DPRS)".
- [18] National Institute of Standards and Technology (NIST) FIPS Publication 197 (2001): "Advanced Encryption Standard (AES)".
- [19] IETF RFC 3610: "Counter with CBC-MAC (CCM)".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.