



SLOVENSKI STANDARD
oSIST prEN 300 175-5 V2.8.5:2022
01-marec-2022

**Digitalne izboljšane brezvrvične telekomunikacije (DECT) - Skupni vmesnik (CI) - 5.
del: Omrežna plast (NWK)**

Digital Enhanced Cordless Telecommunications (DECT) - Common Interface (CI) - Part
5: Network (NWK) layer

**iTeh STANDARD
PREVIEW
(standards.itech.ai)**

Ta slovenski standard je istoveten z: ETSI EN 300 175-5 V2.8.5 (2021-12)

[oSIST prEN 300 175-5 V2.8.5:2022](https://standards.itech.ai/catalog/standards/sist/3a6d9f7-1b5d-4474-8c87-9c03adeeb9ba/osist-pren-300-175-5-v2-8-5-2022)

<https://standards.itech.ai/catalog/standards/sist/3a6d9f7-1b5d-4474-8c87-9c03adeeb9ba/osist-pren-300-175-5-v2-8-5-2022>

ICS:

33.070.30	Digitalne izboljšane brezvrvične telekomunikacije (DECT)	Digital Enhanced Cordless Telecommunications (DECT)
35.100.30	Omrežni sloj	Network layer

oSIST prEN 300 175-5 V2.8.5:2022 **en**

**iTeh STANDARD
PREVIEW
(standards.iteh.ai)**

[oSIST prEN 300 175-5 V2.8.5:2022](https://standards.iteh.ai/catalog/standards/sist/3a6df9f7-1b5d-4474-8c87-9c03adeeb9ba/osist-pren-300-175-5-v2-8-5-2022)

<https://standards.iteh.ai/catalog/standards/sist/3a6df9f7-1b5d-4474-8c87-9c03adeeb9ba/osist-pren-300-175-5-v2-8-5-2022>

Draft ETSI EN 300 175-5 V2.8.5 (2021-12)



**Digital Enhanced Cordless Telecommunications (DECT);
Common Interface (CI);
Part 5: Network (NWK) layer**

[oSIST prEN 300 175-5 V2.8.5:2022](https://standards.iteh.ai/catalog/standards/sist/3a6df9f7-1b5d-4474-8c87-9c03adeeb9ba/osist-pren-300-175-5-v2-8-5-2022)
<https://standards.iteh.ai/catalog/standards/sist/3a6df9f7-1b5d-4474-8c87-9c03adeeb9ba/osist-pren-300-175-5-v2-8-5-2022>

Reference

REN/DECT-00355

Keywords

DECT, IMT-2000, mobility, radio, TDD, TDMA

ETSI650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871**Important notice**

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>[https://standards.iteh.ai/catalog/standards/sist/3a6d1917-](https://standards.iteh.ai/catalog/standards/sist/3a6d1917-1b5d-44)[1b5d-44](https://standards.iteh.ai/catalog/standards/sist/3a6d1917-1b5d-44) **Notice of disclaimer & limitation of liability**

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.
All rights reserved.

Contents

Intellectual Property Rights	16
Foreword.....	16
Modal verbs terminology.....	16
1 Scope	17
2 References	17
2.1 Normative references	17
2.2 Informative references.....	22
3 Definition of terms, symbols and abbreviations.....	23
3.1 Terms.....	23
3.2 Symbols.....	23
3.3 Abbreviations	24
4 Overview of the NWK layer	28
5 Overview of procedures	29
5.1 General	29
5.2 Overview of Call Control (CC).....	30
5.2.1 General.....	30
5.2.2 Call establishment.....	30
5.2.2.1 Call setup	30
5.2.2.2 Service negotiation.....	31
5.2.3 Call connect	31
5.2.4 Call information.....	31
5.2.5 Service change	31
5.2.6 Call release.....	32
5.3 Overview of Supplementary Services (SS)	32
5.3.1 General.....	32
5.3.2 Keypad protocol.....	33
5.3.3 Feature key management protocol.....	33
5.3.4 Functional protocol.....	33
5.4 Overview of Connection Oriented Message Service (COMS).....	33
5.4.1 General.....	33
5.4.2 COMS establishment	34
5.4.3 Service negotiation	34
5.4.4 COMS connect.....	34
5.4.5 COMS data transfer	34
5.4.6 COMS suspend and resume	34
5.4.7 COMS release	35
5.5 Overview of ConnectionLess Message Service (CLMS)	35
5.5.0 General.....	35
5.5.1 Fixed length message service.....	35
5.5.2 Variable length message service.....	35
5.6 Overview of Mobility Management (MM)	35
5.6.1 General.....	35
5.6.2 Identity procedures	36
5.6.3 Authentication procedures	36
5.6.4 Location procedures.....	37
5.6.5 Access rights procedures	37
5.6.6 Key allocation procedure	37
5.6.7 Parameter retrieval procedure	38
5.6.8 Cipherring related procedure.....	38
5.6.9 External protocol information procedure.....	38
5.7 Overview of Link Control Entity (LCE)	38
5.7.1 General.....	38
5.7.2 Data Link Endpoint Identifier (DLEI)	38
5.7.3 Data link establishment.....	39

5.7.4	Data link re-establishment	39
5.7.5	Data link release	39
5.7.6	Data link suspend and resume.....	40
5.7.7	Queuing of messages	40
5.7.8	Request paging.....	40
6	Message functional definitions.....	40
6.1	Overview of message structures	40
6.1.1	Messages.....	40
6.1.2	Information elements	41
6.2	Message summaries.....	42
6.2.1	Summary of CC messages	42
6.2.2	Summary of CISS messages	42
6.2.3	Summary of COMS messages	43
6.2.4	Summary of CLMS messages.....	43
6.2.5	Summary of MM messages	44
6.2.6	Summary of LCE messages	44
6.3	S-FORMAT message functional contents.....	45
6.3.1	S-FORMAT message overview.....	45
6.3.2	CC-messages.....	45
6.3.2.1	{CC-SETUP}	45
6.3.2.2	{CC-INFO}	47
6.3.2.3	{CC-SETUP-ACK}	48
6.3.2.4	{CC-CALL-PROC}	49
6.3.2.5	{CC-ALERTING}	50
6.3.2.6	{CC-CONNECT}	51
6.3.2.7	{CC-CONNECT-ACK}	52
6.3.2.8	{CC-RELEASE}	52
6.3.2.9	{CC-RELEASE-COM}	53
6.3.2.10	{CC-SERVICE-CHANGE}	54
6.3.2.11	{CC-SERVICE-ACCEPT}	55
6.3.2.12	{CC-SERVICE-REJECT}	55
6.3.2.13	{CC-NOTIFY}	56
6.3.2.14	{IWU-INFO}	57
6.3.3	SS-messages (call related and call independent).....	58
6.3.3.1	{FACILITY}	58
6.3.3.2	{HOLD}	59
6.3.3.3	{HOLD-ACK}	59
6.3.3.4	{HOLD-REJECT}	60
6.3.3.5	{RETRIEVE}	60
6.3.3.6	{RETRIEVE-ACK}	61
6.3.3.7	{RETRIEVE-REJECT}	61
6.3.3.8	{CISS-REGISTER}	62
6.3.3.9	{CISS-RELEASE-COM}	63
6.3.4	COMS-messages.....	63
6.3.4.1	{COMS-SETUP}	63
6.3.4.2	{COMS-INFO}	64
6.3.4.3	{COMS-ACK}	64
6.3.4.4	{COMS-CONNECT}	65
6.3.4.5	{COMS-RELEASE}	65
6.3.4.6	{COMS-RELEASE-COM}	66
6.3.4.7	{COMS-NOTIFY}	66
6.3.5	CLMS-message.....	67
6.3.5.1	{CLMS-VARIABLE}	67
6.3.6	MM-messages.....	68
6.3.6.1	{ACCESS-RIGHTS-ACCEPT}	68
6.3.6.2	{ACCESS-RIGHTS-REJECT}	68
6.3.6.3	{ACCESS-RIGHTS-REQUEST}	69
6.3.6.4	{ACCESS-RIGHTS-TERMINATE-ACCEPT}	69
6.3.6.5	{ACCESS-RIGHTS-TERMINATE-REJECT}	70
6.3.6.6	{ACCESS-RIGHTS-TERMINATE-REQUEST}	70
6.3.6.7	{AUTHENTICATION-REJECT}	71

6.3.6.8	{ AUTHENTICATION-REPLY }	71
6.3.6.9	{ AUTHENTICATION-REQUEST }	72
6.3.6.10	{ CIPHER-REJECT }	73
6.3.6.11	{ CIPHER-REQUEST }	73
6.3.6.12	{ CIPHER-SUGGEST }	74
6.3.6.13	{ DETACH }	74
6.3.6.14	{ IDENTITY-REPLY }	75
6.3.6.15	{ IDENTITY-REQUEST }	75
6.3.6.16	{ KEY-ALLOCATE }	76
6.3.6.17	{ LOCATE-ACCEPT }	77
6.3.6.18	{ LOCATE-REJECT }	77
6.3.6.19	{ LOCATE-REQUEST }	78
6.3.6.20	{ MM-INFO-ACCEPT }	79
6.3.6.21	{ MM-INFO-REJECT }	79
6.3.6.22	{ MM-INFO-REQUEST }	80
6.3.6.23	{ MM-INFO-SUGGEST }	80
6.3.6.24	{ TEMPORARY-IDENTITY-ASSIGN }	81
6.3.6.25	{ TEMPORARY-IDENTITY-ASSIGN-ACK }	82
6.3.6.26	{ TEMPORARY-IDENTITY-ASSIGN-REJ }	82
6.3.6.27	{ MM-IWU }	83
6.3.6.28	{ MM-NOTIFY }	83
6.3.7	LCE-messages	84
6.3.7.1	{ LCE-PAGE-RESPONSE }	84
6.3.7.2	{ LCE-PAGE-REJECT }	84
6.4	B-FORMAT message functional contents	85
6.4.1	B-FORMAT message overview	85
6.4.2	{ LCE-REQUEST-PAGE }	85
6.4.3	{ CLMS-FIXED }	86
7	S-FORMAT message structures	86
7.1	Overview	86
7.2	Protocol Discrimination (PD) element	87
7.3	Transaction Identifier (TI) element	87
7.4	Message type element	88
7.4.0	General	88
7.4.1	Messages for CC	89
7.4.2	Messages for SS	89
7.4.3	Messages for COMS	89
7.4.4	Messages for CLMS	90
7.4.5	Messages for MM	90
7.4.6	Messages for LCE	90
7.5	Other information elements	91
7.5.1	Coding rules	91
7.5.2	Extensions of codesets	93
7.5.3	Locking shift procedure	93
7.5.4	Non-locking shift procedure	94
7.5.5	Display and keypad elements	94
7.5.6	Repeated elements	94
7.6	Fixed length information elements	95
7.6.1	Summary	95
7.6.2	Sending complete, delimiter request and use TPUI	95
7.6.3	Repeat indicator	96
7.6.4	Basic service	96
7.6.5	Single display	97
7.6.6	Single keypad	97
7.6.7	Release reason	97
7.6.8	Signal	99
7.6.9	Timer restart	100
7.6.10	Test hook control	100
7.7	Variable length information elements	100
7.7.1	Summary	100
7.7.2	Allocation type	102

7.7.3	Alphanumeric	102
7.7.4	Auth type	104
7.7.5	Call attributes.....	106
7.7.6	Call identity	111
7.7.7	Called party number.....	111
7.7.8	Called party subaddress	112
7.7.9	Calling party number	113
7.7.10	Cipher info	114
7.7.11	Connection attributes	115
7.7.12	Connection identity.....	123
7.7.13	Duration	124
7.7.14	End-to-end compatibility	124
7.7.15	Facility	127
7.7.16	Feature activate.....	128
7.7.17	Feature indicate.....	130
7.7.18	Fixed identity	132
7.7.19	Identity type	133
7.7.20	Info type	134
7.7.21	InterWorking Unit (IWU) attributes	135
7.7.22	IWU packet	139
7.7.23	IWU to IWU	141
7.7.24	Key.....	143
7.7.25	Location area	143
7.7.26	Multi-display.....	144
7.7.27	Multi-keypad.....	145
7.7.28	NetWoRK (NWK) assigned identity.....	145
7.7.29	Network parameter	146
7.7.30	Portable identity	148
7.7.31	Progress indicator	151
7.7.32	RAND	152
7.7.33	Rate parameters	153
7.7.34	Reject reason.....	154
7.7.35	RES	155
7.7.36	RS	155
7.7.37	Segmented info	156
7.7.38	Service change info	156
7.7.39	Service class.....	158
7.7.40	Setup capability	158
7.7.41	Terminal capability	160
7.7.42	Transit delay	166
7.7.43	Window size	167
7.7.44	ZAP field	168
7.7.45	Escape to proprietary	168
7.7.46	Model identifier	169
7.7.47	MMS Generic Header.....	170
7.7.48	MMS Object Header.....	170
7.7.49	MMS Extended header	170
7.7.50	Time-Date	170
7.7.51	Ext h/o indicator	172
7.7.52	Called party Name	173
7.7.53	Calling party Name.....	174
7.7.54	Codec List.....	174
7.7.55	Events notification	176
7.7.55.1	General structure	176
7.7.55.2	Event types	177
7.7.56	Call information.....	181
7.7.57	List change details	185
7.7.58	ULE MAC Configuration Info.....	187
8	B-FORMAT message structures	187
8.1	General	187
8.2	LCE request paging messages	188

iTeh STANDARD
PREVIEW
(standards.iteh.ai)

[oSIST prEN 300 175-5 V2.8.5:2022](https://standards.iteh.ai/catalog/standards/sist/3a6df917-4474-8c87-9c03adeeb9ba/osist-pren-300-175-5-v2-8-5-2022)

[https://standards.iteh.ai/catalog/standards/sist/3a6df917-](https://standards.iteh.ai/catalog/standards/sist/3a6df917-4474-8c87-9c03adeeb9ba/osist-pren-300-175-5-v2-8-5-2022)

[4474-8c87-9c03adeeb9ba/osist-pren-300-175-5-](https://standards.iteh.ai/catalog/standards/sist/3a6df917-4474-8c87-9c03adeeb9ba/osist-pren-300-175-5-v2-8-5-2022)

[v2-8-5-2022](https://standards.iteh.ai/catalog/standards/sist/3a6df917-4474-8c87-9c03adeeb9ba/osist-pren-300-175-5-v2-8-5-2022)

8.2.0	General.....	188
8.2.1	Short format message.....	188
8.2.2	Full format message.....	189
8.2.3	Long format message.....	191
8.2.4	Message elements.....	191
8.2.4.1	LCE paging header.....	191
8.2.4.2	Info fields (Full format).....	192
8.2.4.3	Default setup behaviour.....	193
8.2.4.4	Address elements in collective or group ringing.....	194
8.3	CLMS-FIXED messages.....	195
8.3.1	General message structure.....	195
8.3.2	Message elements.....	195
8.3.3	Standard message structures.....	197
8.3.3.1	General.....	197
8.3.3.2	Messages using 4-bit characters.....	197
8.3.3.3	Messages using 8-bit characters.....	197
9	Call Control (CC) procedures.....	198
9.1	General.....	198
9.2	Call Control (CC) states.....	201
9.2.1	States at PT.....	201
9.2.1.0	General.....	201
9.2.1.1	State T-00: "NULL".....	201
9.2.1.2	State T-19: "RELEASE PENDING".....	201
9.2.1.3	State T-10: "ACTIVE".....	201
9.2.1.4	State T-01: "CALL INITIATED".....	201
9.2.1.5	State T-02: "OVERLAP SENDING".....	201
9.2.1.6	State T-03: "CALL PROCEEDING".....	201
9.2.1.7	State T-04: "CALL DELIVERED".....	201
9.2.1.8	State T-06: "CALL PRESENT".....	201
9.2.1.9	State T-07: "CALL RECEIVED".....	201
9.2.1.10	State T-08: "CONNECT PENDING".....	201
9.2.2	States at FT.....	202
9.2.2.0	General.....	202
9.2.2.1	State F-00: "NULL".....	202
9.2.2.2	State F-19: "RELEASE PENDING".....	202
9.2.2.3	State F-10: "ACTIVE".....	202
9.2.2.4	State F-01: "CALL-INITIATED".....	202
9.2.2.5	State F-02: "OVERLAP SENDING".....	202
9.2.2.6	State F-03: "CALL PROCEEDING".....	202
9.2.2.7	State F-04: "CALL DELIVERED".....	202
9.2.2.8	State F-06: "CALL PRESENT".....	202
9.2.2.9	State F-07: "CALL RECEIVED".....	202
9.2.3	Optional states (PT and FT).....	203
9.2.3.0	General.....	203
9.2.3.1	States T-22 and F-22: "OVERLAP RECEIVING".....	203
9.2.3.2	States T-23 and F-23: "INCOMING CALL PROCEEDING".....	203
9.3	Call establishment procedures.....	203
9.3.1	PT initiated call establishment (outgoing call).....	203
9.3.1.0	General.....	203
9.3.1.1	Call request.....	203
9.3.1.2	Call accept or reject.....	204
9.3.1.3	Selection of lower layer resources.....	204
9.3.1.4	Connection of U-plane.....	205
9.3.1.5	Overlap sending.....	205
9.3.1.6	Call proceeding.....	206
9.3.1.7	Call confirmation.....	206
9.3.1.8	Call connection.....	207
9.3.1.9	Expiry of timer <CC.04>.....	207
9.3.2	FT initiated call establishment (incoming call).....	207
9.3.2.0	General.....	207
9.3.2.1	Call request.....	207

9.3.2.2	Call accept or reject.....	208
9.3.2.3	Selection of lower layer resources	208
9.3.2.4	Connection of U-plane	209
9.3.2.5	Overlap receiving	209
9.3.2.6	Call proceeding	209
9.3.2.7	Call confirmation	209
9.3.2.8	Call connection	210
9.3.2.9	Sending of <<TERMINAL-CAPABILITY>>.....	210
9.3.2.10	Expiry of timer <CC.04>	210
9.4	Call information procedures	210
9.5	Call release procedures.....	211
9.5.1	Normal call release	211
9.5.2	Abnormal call release	211
9.5.2.1	Definitions.....	211
9.5.2.2	Abnormal release general description (PT or FT).....	212
9.5.2.3	Abnormal release in case of call setup collisions.....	213
9.5.3	Release collisions.....	216
9.6	Service change procedures	216
9.6.1	General.....	216
9.6.2	Change of Bandwidth parameters (including changes in connection type)	217
9.6.3	Service rerouting.....	217
9.6.4	NWK layer service suspension and resumption.....	217
9.6.5	Modulation scheme change.....	218
9.7	NWK layer Packet mode procedures.....	218
9.7.1	General.....	218
9.7.2	PT initiated access	219
9.7.3	FT initiated access	219
9.7.4	NWK layer suspend and resume.....	219
9.7.4.1	General	219
9.7.4.2	C-plane NWK layer suspend and resume	220
9.7.4.3	U-plane NWK layer suspend and resume	220
9.8	Emergency call procedure	220
9.9	Segmentation of information in CC procedures	221
10	Supplementary Services procedures.....	222
10.1	General	222
10.2	Keypad protocol	223
10.3	Feature key management protocol.....	223
10.4	Functional protocol.....	224
10.4.0	General.....	224
10.4.1	Separate messages approach	224
10.4.1.0	General	224
10.4.1.1	Hold procedures	224
10.4.1.2	Retrieve procedures.....	224
10.4.1.3	Auxiliary states for hold and retrieve	225
10.4.2	Common information element approach.....	225
10.4.2.0	General	225
10.4.2.1	Call Related Supplementary Services (CRSS) procedures.....	225
10.4.2.2	Call Independent Supplementary Services (CISS) procedures	225
10.4.2.2.0	General	225
10.4.2.2.1	Transport of CISS.....	226
10.4.2.3	Connectionless Supplementary Service (CLSS) procedure	226
10.5	Co-existence of multiple protocols.....	227
10.6	Application protocols	227
10.6.1	DECT standard functional supplementary services	227
10.6.2	DECT specific supplementary services	228
10.6.2.0	General	228
10.6.2.1	Queue management.....	228
10.6.2.2	Indication of subscriber number.....	228
10.6.2.3	Control of echo control functions.....	229
10.6.2.4	Cost information	229

11	Connection Oriented Message Service (COMS).....	230
11.1	General	230
11.2	COMS states.....	230
11.2.1	States at PT	230
11.2.1.1	State TS-0: "NULL"	230
11.2.1.2	State TS-1: "CONNECT PENDING"	230
11.2.1.3	State TS-2: "RELEASE PENDING"	230
11.2.1.4	State TS-3: "ACTIVE"	230
11.2.2	States at FT	230
11.2.2.1	State FS-0: "NULL"	230
11.2.2.2	State FS-1: "CONNECT PENDING"	230
11.2.2.3	State FS-2: "RELEASE PENDING"	230
11.2.2.4	State FS-3: "ACTIVE"	231
11.3	COMS establishment procedures	231
11.3.1	PT initiated COMS establishment	231
11.3.1.1	COMS request.....	231
11.3.1.2	COMS connection.....	231
11.3.2	FT initiated COMS establishment	232
11.3.2.1	COMS request.....	232
11.3.2.2	COMS connection.....	232
11.4	COMS data transfer procedures	232
11.4.1	Procedure at the sending side.....	232
11.4.2	Procedure at the receiving side	233
11.5	COMS NWK layer suspend and resume procedures.....	234
11.6	COMS release procedures	234
11.6.1	Normal COMS release.....	234
11.6.2	Release collisions.....	234
12	ConnectionLess Message Service (CLMS).....	235
12.1	General	235
12.2	CLMS states	235
12.3	CLMS message transmission procedures	235
12.3.1	Fixed length messages	235
12.3.1.0	General	235
12.3.1.1	Procedure in the Fixed radio Termination (FT)	235
12.3.1.2	Procedure in the Portable radio Termination (PT)	236
12.3.2	Variable length messages.....	236
12.3.2.0	General	236
12.3.2.1	Procedure at the sending side	236
12.3.2.2	Procedure at the receiving side.....	236
12.3.2.3	Restrictions for portable side initiated messages.....	237
13	Mobility Management (MM) procedures.....	237
13.1	General	237
13.2	Identity procedures	238
13.2.0	General.....	238
13.2.1	Procedure for identification of PT	238
13.2.2	Procedure for temporary identity assignment	239
13.3	Authentication procedures.....	240
13.3.0	General.....	240
13.3.1	Authentication of a PT	240
13.3.2	Authentication of the user.....	242
13.3.3	Authentication of a FT	243
13.4	Location procedures	244
13.4.0	General.....	244
13.4.1	Location registration	244
13.4.2	Detach	246
13.4.3	Location update	246
13.5	Access rights procedure.....	247
13.5.1	Obtaining the access rights	247
13.5.2	Termination of access rights	248
13.5.3	Modification of access rights	249

13.6	Key allocation procedure.....	250
13.7	Parameter retrieval procedure.....	251
13.8	Ciphering related procedure	253
13.9	External protocol information procedure	256
13.9.0	General.....	256
13.9.1	Procedure for external protocol information initiated by the FT	256
13.9.2	Procedure for external protocol information initiated by the PT	256
13.9.3	Segmentation of information in MM procedures.....	256
14	Link Control Entity (LCE) procedures.....	258
14.1	General	258
14.2	Connection oriented link control procedures.....	259
14.2.1	Link establishment.....	259
14.2.2	Direct PT initiated link establishment.....	259
14.2.3	Indirect (paged) FT initiated link establishment	260
14.2.4	Direct FT initiated link establishment.....	261
14.2.5	Link maintenance.....	262
14.2.6	Link suspend and resume.....	262
14.2.6.0	General	262
14.2.6.1	Link suspend	262
14.2.6.2	Link resume.....	263
14.2.7	Link release.....	263
14.2.7.0	General	263
14.2.7.1	NLR notification without "partial release" as release reason	263
14.2.7.2	NLR notification with "partial release" as release reason	264
14.3	Connectionless link control procedures.....	264
14.3.1	Message routing.....	264
14.3.2	Broadcast announce procedure	265
14.3.3	LCE paging codes for connectionless service.....	265
14.4	Procedure for collective and group ringing	265
14.5	LCE paging procedures for DPRS	266
14.5.1	DPRS initial setup paging.....	266
14.5.1.0	General	266
14.5.1.1	Assumptions for Short paging format or for Full format with IPUI.....	266
14.5.1.2	Coding for Full paging format with TPUI.....	267
14.5.2	DPRS Resume paging.....	267
14.5.2.0	General	267
14.5.2.1	Assumptions for Short paging format or for Full format with IPUI.....	267
14.5.2.2	Coding for Full paging format with TPUI.....	267
14.5.2.3	LCE Resume Procedure description.....	268
14.5.3	Special cases	268
14.5.3.1	Rule for DPRS Class 1 devices	268
14.5.3.2	Rule for backcompatibility with former A/B 1 devices	268
15	Management procedures.....	269
15.1	Lower Layer Management Entity (LLME)	269
15.2	Service mapping and negotiation	269
15.2.1	General.....	269
15.2.2	Prioritized list negotiation.....	270
15.2.3	Exchanged attribute negotiation	270
15.2.4	Operating parameter negotiation.....	270
15.2.5	Peer attribute negotiation	271
15.3	Service modification procedures	271
15.4	Resource management.....	271
15.5	Management of MM procedures	271
15.6	Call ciphering management.....	273
15.7	External Handover.....	273
15.7.0	General.....	273
15.7.1	Handover candidate procedures	274
15.7.1.1	General	274
15.7.1.2	Handover candidate indication.....	274
15.7.1.3	Handover candidate retrieval	274

15.7.1.4	Target FP selection.....	275
15.7.2	Handover reference procedure.....	275
15.7.2.1	General.....	275
15.7.2.2	Handover reference indication.....	275
15.7.2.3	Handover reference retrieval.....	276
15.7.3	External handover suggested by FP.....	276
15.7.4	NWK layer set up procedure.....	276
15.7.4.0	General.....	276
15.7.4.1	Handover request.....	276
15.7.4.2	Handover confirm.....	277
15.7.4.3	Handover accept.....	277
15.7.4.4	Handover reject.....	277
15.7.4.5	Release of old connection.....	277
15.7.4.6	Handover Fall Back.....	277
15.7.5	U-plane handling.....	278
15.7.6	Ciphering procedure.....	278
15.7.7	Interaction with location registration.....	279
15.8	Test management procedures.....	279
15.8.0	General.....	279
15.8.1	Test call back procedure.....	279
15.8.2	Test hook control procedures.....	280
15.8.3	Upper tester procedure.....	280
15.9	Application assistance procedures.....	281
15.9.1	DECT Identity Resolution (Retrieval) Procedure.....	281
15.9.1.0	General.....	281
15.9.1.1	FT (or HyP) initiated Connectionless Identity Resolution procedure.....	281
15.9.1.2	PT initiated Connectionless Identity Resolution procedure.....	281
15.9.1.3	Connection oriented Identity Resolution procedure.....	282
15.9.2	Application Address Resolution (Retrieval) Procedure.....	282
15.9.3	Application Parameter Allocation Procedure.....	282
15.9.3.0	General.....	282
15.9.3.1	FT initiated application parameter allocation procedure.....	282
15.9.3.2	PT initiated application parameter allocation procedure.....	282
15.9.4	Application parameter information procedure.....	283
15.9.4.0	General.....	283
15.9.4.1	FT initiated connection oriented Application parameter information procedure.....	283
15.9.4.2	PT initiated connection oriented Application parameter information procedure.....	283
15.9.4.3	FT initiated connectionless Application parameter information procedure.....	283
15.9.4.4	PT initiated connectionless Application parameter information procedure.....	284
15.9.5	Application Parameter Indication procedure.....	284
16	Primitives.....	285
16.1	Primitive types.....	285
16.2	Primitives to lower layer (DLC layer).....	285
16.3	Primitives to IWU.....	285
16.3.0	General.....	285
16.3.1	Parameter definitions.....	285
16.3.2	MNCC primitives.....	286
16.3.2.0	List of primitives.....	286
16.3.2.1	MNCC_SETUP primitive.....	287
16.3.2.2	MNCC_SETUP_ACK primitive.....	287
16.3.2.3	MNCC_REJECT primitive.....	288
16.3.2.4	MNCC_CALL_PROC primitive.....	288
16.3.2.5	MNCC_ALERT primitive.....	289
16.3.2.6	MNCC_CONNECT primitive.....	289
16.3.2.7	MNCC_RELEASE primitive.....	290
16.3.2.8	MNCC_FACILITY primitive.....	290
16.3.2.9	MNCC_INFO primitive.....	291
16.3.2.10	MNCC_MODIFY primitive.....	291
16.3.2.11	MNCC_HOLD primitive.....	291
16.3.2.12	MNCC_RETRIEVE primitive.....	292
16.3.2.13	MNCC_IWU_INFO primitive.....	292

16.3.3	MNSS primitives	292
16.3.3.0	List of primitives	292
16.3.3.1	MNSS_SETUP primitive	292
16.3.3.2	MNSS_FACILITY primitive	293
16.3.3.3	MNSS_RELEASE primitive	293
16.3.4	MNCO primitives	293
16.3.4.0	List of primitives	293
16.3.4.1	MNCO_SETUP primitive	294
16.3.4.2	MNCO_CONNECT primitive	294
16.3.4.3	MNCO_INFO primitive	294
16.3.4.4	MNCO_ACK primitive	294
16.3.4.5	MNCO_RELEASE primitive	295
16.3.4.6	MNCO_REJECT primitive	295
16.3.5	MNCL primitives	295
16.3.5.0	List of primitives	295
16.3.5.1	MNCL_UNITDATA primitive	295
16.3.6	MM primitives	296
16.3.6.0	List of primitives	296
16.3.6.1	MM_IDENTITY primitive	296
16.3.6.2	MM_IDENTITY_ASSIGN primitive	296
16.3.6.3	MM_AUTHENTICATE primitive	297
16.3.6.4	MM_LOCATE primitive	297
16.3.6.5	MM_DETACH primitive	297
16.3.6.6	MM_ACCESS_RIGHTS primitive	298
16.3.6.7	MM_ACCESS_RIGHTS_TERMINATE primitive	298
16.3.6.8	MM_KEY_ALLOCATE primitive	298
16.3.6.9	MM_INFO primitive	299
16.3.6.10	MM_CIPHER primitive	299
16.3.6.11	MM_IWU primitive	299
17	Handling of error and exception conditions	300
17.0	General	300
17.1	Protocol discrimination error	300
17.2	Message too short	300
17.3	Transaction identifier error	300
17.3.1	Illegal and unsupported transaction identifier value	300
17.3.2	Transaction identifier procedural errors and exception conditions	300
17.3.2.1	Unknown active CC call	300
17.3.2.2	Unknown active CISS call	301
17.3.2.3	Unknown active COMS call	301
17.3.2.4	Unknown active CLMS call	301
17.3.2.5	Unknown active MM transaction	301
17.3.2.6	Unknown active LCE transaction	301
17.3.3	Call Resource Contention	301
17.4	Message type or message sequence errors	302
17.4.1	CC message error	302
17.4.2	CISS message error	302
17.4.3	COMS or CLMS message error	302
17.4.4	MM message error	302
17.4.5	LCE message error	302
17.5	General information element errors	302
17.5.0	General	302
17.5.1	Information element out of sequence	302
17.5.2	Duplicated information elements	303
17.6	Mandatory information element errors	303
17.6.1	Mandatory information element missing in CC messages	303
17.6.2	Mandatory information element content error in CC messages	303
17.6.3	Mandatory information element error in COMS or CLMS messages	303
17.6.4	Mandatory information element error in MM messages	304
17.6.5	Mandatory information element error in LCE messages	304
17.7	Non-mandatory information element errors	304
17.7.0	General	304

17.7.1	Unrecognized information element.....	304
17.7.2	Non-mandatory information element content error	304
17.8	Data link reset.....	305
17.9	Data link failure.....	305
Annex A (normative): System parameters.....		306
A.1	CC timers.....	306
A.2	SS timers	307
A.3	COMS timers.....	307
A.4	CLMS timer.....	308
A.5	MM timers.....	308
A.6	LCE timers	311
A.7	NWK layer constants.....	311
A.8	Restart.....	312
Annex B (normative): CC state transition tables.....		313
B.1	CC state transitions at PT side.....	313
B.1.1	CC state table at PT side.....	313
B.1.2	CC transition procedures at PT side.....	314
B.2	CC state transitions at FT side.....	316
B.2.1	CC state table at FT side.....	316
B.2.2	CC transition procedures at FT side.....	316
Annex C (informative): DLC states as viewed by the LCE.....		319
Annex D (normative): DECT standard character sets		320
D.1	General	320
D.2	DECT standard 8-bit characters	320
D.2.1	General	320
D.2.2	Control codes.....	321
D.2.3	Standard IA5 codes	322
D.2.4	extended codes and escape to alternative character sets.....	322
D.3	DECT standard 4-bit characters	322
Annex E (normative): Default coding of information elements.....		323
E.1	Default coding of <<IWU-ATTRIBUTES>> and <CALL-ATTRIBUTES>> information elements for basic speech.....	323
E.2	Default coding of <<IWU-ATTRIBUTES>>, <<CALL-ATTRIBUTES>> and <<CONNECTION-ATTRIBUTES>> information elements for wideband speech	323
E.2.0	General	323
E.2.1	Default setup attributes for basic service wideband speech	324
Annex F (normative): Broadcast attributes coding		325
F.1	Higher layer capabilities.....	325
F.2	Extended higher layer capabilities	326
F.3	Extended higher layer capabilities (part 2).....	326
F.4	Extended higher layer capabilities (part 3).....	328
Annex G (normative): Use of <<IWU-PACKET>> and <<IWU-TO-IWU>> information elements		329