

ETSI TS 123 501 V15.9.0 (2020-03)



5G; System architecture for the 5G System (5GS) (3GPP TS 23.501 version 15.9.0 Release 15)

*ITeH STANDARD PREVIEW
(standards.it) Full standard: 3GPP TS 23.501-15.9.0 V15.9.0 (2020-03)
<https://standards.iteh.ai/catalog/standards/3gpp/ts/23-501-15.9.0>
4323-b6f1-d3998f70119f/etsi-ts-123-501-15.9.0*



ReferenceRTS/TSGS-0223501vf90

Keywords5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	12
1 Scope	13
2 References	13
3 Definitions and abbreviations.....	16
3.1 Definitions	16
3.2 Abbreviations	18
4 Architecture model and concepts	20
4.1 General concepts	20
4.2 Architecture reference model	21
4.2.1 General.....	21
4.2.2 Network Functions and entities	21
4.2.3 Non-roaming reference architecture	22
4.2.4 Roaming reference architectures.....	25
4.2.5 Data Storage architectures	27
4.2.6 Service-based interfaces	29
4.2.7 Reference points	29
4.2.8 Support of non-3GPP access.....	31
4.2.8.1 General Concepts to Support Non-3GPP Access	31
4.2.8.2 Architecture Reference Model for Non-3GPP Accesses.....	32
4.2.8.2.1 Non-roaming Architecture for Non-3GPP Accesses	32
4.2.8.2.2 LBO Roaming Architecture for Non-3GPP Accesses, N3IWF in same PLMN as 3GPP access.....	32
4.2.8.2.3 Home-routed Roaming Architecture for Non-3GPP Accesses, N3IWF in same PLMN as 3GPP access	33
4.2.8.2.4 LBO Roaming Architecture for Non-3GPP Accesses, N3IWF in different PLMN from 3GPP access.....	34
4.2.8.2.5 Home-routed Roaming Architecture for Non-3GPP Accesses, N3IWF in different PLMN from 3GPP access.....	35
4.2.8.3 Non-3GPP Access Reference Points	36
4.2.9 Network Analytics architecture	36
4.3 Interworking with EPC.....	37
4.3.1 Non-roaming architecture	37
4.3.2 Roaming architecture.....	38
4.3.3 Interworking between 5GC via non-3GPP access and E-UTRAN connected to EPC.....	39
4.3.3.1 Non-roaming architecture	39
4.3.3.2 Roaming architecture	40
4.3.4 Interworking between ePDG connected to EPC and 5GS	42
4.3.4.1 Non-roaming architecture	42
4.3.4.2 Roaming architectures.....	43
4.4 Specific services	45
4.4.1 Public Warning System	45
4.4.2 SMS over NAS	45
4.4.2.1 Architecture to support SMS over NAS.....	45
4.4.2.2 Reference point to support SMS over NAS	47
4.4.2.3 Service based interface to support SMS over NAS	47
4.4.3 IMS support	47
4.4.4 Location services	48
4.4.4.1 Architecture to support Location Services	48
4.4.4.2 Reference point to support Location Services.....	48
4.4.4.3 Service Based Interfaces to support Location Services.....	49
4.4.5 Application Triggering Services	49

5	High level features.....	49
5.1	General	49
5.2	Network Access Control	49
5.2.1	General.....	49
5.2.2	Network selection	49
5.2.3	Identification and authentication.....	50
5.2.4	Authorisation	50
5.2.5	Access control and barring	50
5.2.6	Policy control.....	51
5.2.7	Lawful Interception.....	51
5.3	Registration and Connection Management.....	51
5.3.1	General.....	51
5.3.2	Registration Management	51
5.3.2.1	General	51
5.3.2.2	5GS Registration Management states.....	51
5.3.2.2.1	General	51
5.3.2.2.2	RM-DEREGISTERED state.....	51
5.3.2.2.3	RM-REGISTERED state	52
5.3.2.2.4	5GS Registration Management State models	52
5.3.2.3	Registration Area management	53
5.3.2.4	Support of a UE registered over both 3GPP and Non-3GPP access	53
5.3.3	Connection Management	55
5.3.3.1	General	55
5.3.3.2	5GS Connection Management states.....	55
5.3.3.2.1	General	55
5.3.3.2.2	CM-IDLE state	55
5.3.3.2.3	CM-CONNECTED state	56
5.3.3.2.4	5GS Connection Management State models	56
5.3.3.2.5	CM-CONNECTED with RRC Inactive state	57
5.3.3.3	NAS signalling connection management	59
5.3.3.3.1	General	59
5.3.3.3.2	NAS signalling connection establishment	59
5.3.3.3.3	NAS signalling connection Release.....	59
5.3.3.4	Support of a UE connected over both 3GPP and Non-3GPP access	59
5.3.4	UE Mobility	60
5.3.4.1	Mobility Restrictions.....	60
5.3.4.1.1	General	60
5.3.4.1.2	Management of Service Area Restrictions	61
5.3.4.2	Mobility Pattern	62
5.3.4.3	Radio Resource Management functions.....	62
5.3.4.4	UE mobility event notification.....	63
5.4	3GPP access specific aspects.....	64
5.4.1	UE reachability in CM-IDLE.....	64
5.4.1.1	General	64
5.4.1.2	UE reachability allowing mobile terminated data while the UE is CM-IDLE.....	65
5.4.1.3	Mobile Initiated Connection Only (MICO) mode.....	65
5.4.2	UE reachability in CM-CONNECTED.....	66
5.4.3	Paging strategy handling.....	66
5.4.3.1	General	66
5.4.3.2	Paging Policy Differentiation.....	66
5.4.3.3	Paging Priority	67
5.4.4	UE Radio Capability handling.....	67
5.4.4.1	UE radio capability information storage in the AMF.....	67
5.4.4.2	Void.....	68
5.4.4.2a	UE Radio Capability Match Request	68
5.4.4.3	Paging assistance information.....	68
5.4.4a	UE MM Core Network Capability handling.....	69
5.4.4b	UE 5GSM Core Network Capability handling	69
5.4.5	DRX (Discontinuous Reception) framework.....	69
5.4.6	Core Network assistance information for RAN optimization	70
5.4.6.1	General	70
5.4.6.2	Core Network assisted RAN parameters tuning.....	70

5.4.6.3	Core Network assisted RAN paging information.....	70
5.4.7	NG-RAN location reporting	71
5.5	Non-3GPP access specific aspects	71
5.5.1	Registration Management	71
5.5.2	Connection Management	72
5.5.3	UE Reachability	72
5.5.3.1	UE reachability in CM-IDLE	72
5.5.3.2	UE reachability in CM-CONNECTED	73
5.6	Session Management	73
5.6.1	Overview	73
5.6.2	Interaction between AMF and SMF	75
5.6.3	Roaming.....	76
5.6.4	Single PDU Session with multiple PDU Session Anchors	77
5.6.4.1	General	77
5.6.4.2	Usage of an UL Classifier for a PDU Session.....	77
5.6.4.3	Usage of IPv6 multi-homing for a PDU Session.....	78
5.6.5	Support for Local Area Data Network.....	80
5.6.6	Secondary authentication/authorization by a DN-AAA server during the establishment of a PDU Session	82
5.6.7	Application Function influence on traffic routing	83
5.6.8	Selective activation and deactivation of UP connection of existing PDU Session	88
5.6.9	Session and Service Continuity	89
5.6.9.1	General	89
5.6.9.2	SSC mode.....	89
5.6.9.2.1	SSC Mode 1.....	89
5.6.9.2.2	SSC Mode 2.....	89
5.6.9.2.3	SSC Mode 3.....	89
5.6.9.3	SSC mode selection.....	90
5.6.10	Specific aspects of different PDU Session types	90
5.6.10.1	Support of IP PDU Session type	90
5.6.10.2	Support of Ethernet PDU Session type	91
5.6.10.3	Support of Unstructured PDU Session type	92
5.6.11	UE presence in Area of Interest reporting usage by SMF.....	93
5.6.12	Use of Network Instance.....	94
5.6.13	Always-on PDU session	94
5.6.14	Support of Framed Routing	95
5.7	QoS model.....	95
5.7.1	General Overview	95
5.7.1.1	QoS Flow	95
5.7.1.2	QoS Profile.....	96
5.7.1.3	Control of QoS Flows	96
5.7.1.4	QoS Rules	97
5.7.1.5	QoS Flow mapping	97
5.7.1.6	DL traffic.....	99
5.7.1.7	UL Traffic	99
5.7.1.8	AMBR/MFBR enforcement and rate limitation.....	100
5.7.1.9	Precedence Value	100
5.7.2	5G QoS Parameters.....	100
5.7.2.1	5QI	100
5.7.2.2	ARP.....	101
5.7.2.3	RQA	101
5.7.2.4	Notification control	101
5.7.2.5	Flow Bit Rates.....	102
5.7.2.6	Aggregate Bit Rates	102
5.7.2.7	Default values	103
5.7.2.8	Maximum Packet Loss Rate.....	103
5.7.3	5G QoS characteristics.....	103
5.7.3.1	General	103
5.7.3.2	Resource Type.....	104
5.7.3.3	Priority Level	104
5.7.3.4	Packet Delay Budget	104
5.7.3.5	Packet Error Rate	105

5.7.3.6	Averaging Window	105
5.7.3.7	Maximum Data Burst Volume	105
5.7.4	Standardized 5QI to QoS characteristics mapping.....	106
5.7.5	Reflective QoS.....	109
5.7.5.1	General	109
5.7.5.2	UE Derived QoS Rule	110
5.7.5.3	Reflective QoS Control	111
5.7.6	Packet Filter Set	112
5.7.6.1	General	112
5.7.6.2	IP Packet Filter Set.....	112
5.7.6.3	Ethernet Packet Filter Set.....	112
5.8	User Plane Management.....	113
5.8.1	General.....	113
5.8.2	Functional Description.....	113
5.8.2.1	General	113
5.8.2.2	UE IP Address Management	113
5.8.2.2.1	General	113
5.8.2.2.2	Routing rules configuration	115
5.8.2.2.3	The procedure of Stateless IPv6 Address Autoconfiguration	115
5.8.2.3	Management of CN Tunnel Info	116
5.8.2.3.1	General	116
5.8.2.3.2	Management of CN Tunnel Info in the SMF.....	116
5.8.2.3.3	Management of CN Tunnel Info in the UPF	116
5.8.2.4	Traffic Detection	116
5.8.2.4.1	General	116
5.8.2.4.2	Traffic Detection Information	116
5.8.2.5	Control of User Plane Forwarding	117
5.8.2.6	Charging and Usage Monitoring Handling	118
5.8.2.6.1	General	118
5.8.2.6.2	Activation of Usage Reporting in UPF.....	118
5.8.2.6.3	Reporting of Usage Information towards SMF	119
5.8.2.7	PDU Session and QoS Flow Policing	119
5.8.2.8	PCC Related Functions.....	120
5.8.2.8.1	Activation/Deactivation of predefined PCC rules	120
5.8.2.8.2	Enforcement of Dynamic PCC Rules.....	120
5.8.2.8.3	Redirection	121
5.8.2.8.4	Support of PFD Management.....	121
5.8.2.9	Functionality of Sending of "End marker"	121
5.8.2.9.0	Introduction	121
5.8.2.9.1	UPF Constructing the "End marker" Packets	122
5.8.2.9.2	SMF Constructing the "End marker" Packets.....	122
5.8.2.10	UP Tunnel Management	122
5.8.2.11	Parameters for N4 session management.....	123
5.8.2.11.1	General	123
5.8.2.11.2	N4 Session Context	123
5.8.2.11.3	Packet Detection Rule	123
5.8.2.11.4	QoS Enforcement Rule.....	124
5.8.2.11.5	Usage Reporting Rule.....	127
5.8.2.11.6	Forwarding Action Rule	129
5.8.2.11.7	Usage Report generated by UPF	132
5.8.2.12	Reporting of the UE MAC addresses used in a PDU Session.....	132
5.8.3	Explicit Buffer Management.....	133
5.8.3.1	General	133
5.8.3.2	Buffering at UPF	133
5.8.3.3	Buffering at SMF	133
5.8.4	SMF Pause of Charging	133
5.9	Identifiers	134
5.9.1	General.....	134
5.9.2	Subscription Permanent Identifier	134
5.9.2a	Subscription Concealed Identifier.....	134
5.9.3	Permanent Equipment Identifier	134
5.9.4	5G Globally Unique Temporary Identifier	134

5.9.5	AMF Name	135
5.9.6	Data Network Name (DNN)	135
5.9.7	Internal-Group Identifier	136
5.9.8	Generic Public Subscription Identifier	136
5.9.9	AMF UE NGAP ID	136
5.10	Security aspects	136
5.10.1	General	136
5.10.2	Security Model for non-3GPP access	137
5.10.2.1	Signalling Security	137
5.10.3	PDU Session User Plane Security	137
5.11	Support for Dual Connectivity, Multi-Connectivity	138
5.11.1	Support for Dual Connectivity	138
5.12	Charging	139
5.12.1	General	139
5.12.2	Usage Data Reporting for Secondary RAT	139
5.12.3	Secondary RAT Periodic Usage Data Reporting Procedure	140
5.13	Support for Edge Computing	140
5.14	Policy Control	140
5.15	Network slicing	141
5.15.1	General	141
5.15.2	Identification and selection of a Network Slice: the S-NSSAI and the NSSAI	141
5.15.2.1	General	141
5.15.2.2	Standardised SST values	142
5.15.3	Subscription aspects	143
5.15.4	UE NSSAI configuration and NSSAI storage aspects	143
5.15.4.1	General	143
5.15.4.1.1	UE Network Slice configuration	143
5.15.4.1.2	Mapping of S-NSSAIs values in the Allowed NSSAI and in the Requested NSSAI to the S-NSSAIs values used in the HPLMN	145
5.15.4.2	Update of UE Network Slice configuration	145
5.15.5	Detailed Operation Overview	146
5.15.5.1	General	146
5.15.5.2	Selection of a Serving AMF supporting the Network Slices	146
5.15.5.2.1	Registration to a set of Network Slices	146
5.15.5.2.2	Modification of the Set of Network Slice(s) for a UE	149
5.15.5.2.3	AMF Re-allocation due to Network Slice(s) Support	151
5.15.5.3	Establishing a PDU Session in a Network Slice	151
5.15.6	Network Slicing Support for Roaming	152
5.15.7	Network slicing and Interworking with EPS	153
5.15.7.1	General	153
5.15.7.2	Idle mode aspects	153
5.15.7.3	Connected mode aspects	154
5.15.8	Configuration of Network Slice availability in a PLMN	154
5.16	Support for specific services	155
5.16.1	Public Warning System	155
5.16.2	SMS over NAS	155
5.16.2.1	General	155
5.16.2.2	SMS over NAS transport	156
5.16.3	IMS support	156
5.16.3.1	General	156
5.16.3.2	IMS voice over PS Session Supported Indication over 3GPP access	156
5.16.3.2a	IMS voice over PS Session Supported Indication over non-3GPP access	157
5.16.3.3	Homogeneous support for IMS voice over PS Session supported indication	157
5.16.3.4	P-CSCF address delivery	157
5.16.3.5	Domain selection for UE originating sessions / calls	157
5.16.3.6	Terminating domain selection for IMS voice	158
5.16.3.7	UE's usage setting	158
5.16.3.8	Domain and Access Selection for UE originating SMS	159
5.16.3.8.1	UE originating SMS for IMS Capable UEs supporting SMS over IP	159
5.16.3.8.2	Access Selection for SMS over NAS	159
5.16.3.9	SMF support for P-CSCF restoration procedure	159
5.16.3.10	IMS Voice Service via EPS Fallback or RAT fallback in 5GS	159

5.16.4	Emergency Services.....	160
5.16.4.1	Introduction.....	160
5.16.4.2	Architecture Reference Model for Emergency Services.....	162
5.16.4.3	Mobility Restrictions and Access Restrictions for Emergency Services.....	162
5.16.4.4	Reachability Management.....	162
5.16.4.5	SMF and UPF selection function for Emergency Services.....	163
5.16.4.6	QoS for Emergency Services.....	163
5.16.4.7	PCC for Emergency Services.....	163
5.16.4.8	IP Address Allocation.....	163
5.16.4.9	Handling of PDU Sessions for Emergency Services.....	163
5.16.4.9a	Handling of PDU Sessions for normal services for Emergency Registered UEs.....	163
5.16.4.10	Support of eCall Only Mode.....	164
5.16.4.11	Emergency Services Fallback.....	164
5.16.5	Multimedia Priority Services.....	165
5.16.6	Mission Critical Services.....	166
5.17	Interworking and Migration.....	167
5.17.1	Support for Migration from EPC to 5GC.....	167
5.17.1.1	General.....	167
5.17.1.2	User Plane management to support interworking with EPS.....	168
5.17.2	Interworking with EPC.....	168
5.17.2.1	General.....	168
5.17.2.2	Interworking Procedures with N26 interface.....	171
5.17.2.2.1	General.....	171
5.17.2.2.2	Mobility for UEs in single-registration mode.....	171
5.17.2.3	Interworking Procedures without N26 interface.....	172
5.17.2.3.1	General.....	172
5.17.2.3.2	Mobility for UEs in single-registration mode.....	173
5.17.2.3.3	Mobility for UEs in dual-registration mode.....	174
5.17.2.3.4	Redirection for UEs in connected state.....	175
5.17.2.4	Mobility between 5GS and GERAN/UTRAN.....	175
5.17.3	Interworking with EPC in presence of Non-3GPP PDU Sessions.....	175
5.17.4	Network sharing support and interworking between EPS and 5GS.....	176
5.17.5	Configuration Transfer Procedure between NG-RAN and E-UTRAN.....	176
5.17.5.1	Architecture Principles for Configuration Transfer between NG-RAN and E-UTRAN.....	176
5.17.5.2	Addressing, routing and relaying.....	177
5.17.5.2.1	Addressing.....	177
5.17.5.2.2	Routing.....	177
5.17.5.2.3	Relaying.....	177
5.18	Network Sharing.....	177
5.18.1	General concepts.....	177
5.18.2	Broadcast system information for network sharing.....	178
5.18.2a	PLMN list handling for network sharing.....	178
5.18.3	Network selection by the UE.....	178
5.18.4	Network selection by the network.....	179
5.18.5	Network Sharing and Network Slicing.....	179
5.19	Control Plane Load Control, Congestion and Overload Control.....	179
5.19.1	General.....	179
5.19.2	TNLA Load Balancing and TNLA Load Re-Balancing.....	179
5.19.3	AMF Load Balancing.....	180
5.19.4	AMF Load Re-Balancing.....	180
5.19.5	AMF Control Of Overload.....	181
5.19.5.1	General.....	181
5.19.5.2	AMF Overload Control.....	181
5.19.6	SMF Overload Control.....	182
5.19.7	NAS level congestion control.....	182
5.19.7.1	General.....	182
5.19.7.2	General NAS level congestion control.....	182
5.19.7.3	DNN based congestion control.....	183
5.19.7.4	S-NSSAI based congestion control.....	185
5.19.7.5	Group specific NAS level congestion control.....	186
5.20	External Exposure of Network Capability.....	186
5.21	Architectural support for virtualized deployments.....	187

5.21.0	General.....	187
5.21.1	Architectural support for N2.....	187
5.21.1.1	TNL associations.....	187
5.21.1.2	NGAP UE-TNLA-binding.....	187
5.21.1.3	N2 TNL association selection.....	188
5.21.2	AMF Management.....	188
5.21.2.1	AMF Addition/Update.....	188
5.21.2.2	AMF planned removal procedure.....	188
5.21.2.2.1	AMF planned removal procedure with UDSF deployed.....	188
5.21.2.2.2	AMF planned removal procedure without UDSF.....	190
5.21.2.3	Procedure for AMF Auto-recovery.....	192
5.22	System Enablers for priority mechanism.....	193
5.22.1	General.....	193
5.22.2	Subscription-related Priority Mechanisms.....	193
5.22.3	Invocation-related Priority Mechanisms.....	194
5.22.4	QoS Mechanisms applied to established QoS Flows.....	195
5.23	Supporting for Asynchronous Type Communication.....	196
5.24	3GPP PS Data Off.....	196
5.25	Support of OAM Features.....	197
5.25.1	Support of Tracing: Signalling Based Activation/Deactivation of Tracing.....	197
5.26	Configuration Transfer Procedure.....	197
5.26.1	Architecture Principles for Configuration Transfer.....	197
5.26.2	Addressing, routing and relaying.....	198
5.26.2.1	Addressing.....	198
5.26.2.2	Routing.....	198
5.26.2.3	Relaying.....	198
6	Network Functions.....	199
6.1	General.....	199
6.2	Network Function Functional description.....	199
6.2.1	AMF.....	199
6.2.2	SMF.....	200
6.2.3	UPF.....	201
6.2.4	PCF.....	201
6.2.5	NEF.....	201
6.2.5.1	Support for CAPIF.....	202
6.2.6	NRF.....	202
6.2.7	UDM.....	203
6.2.8	AUSF.....	204
6.2.9	N3IWF.....	204
6.2.10	AF.....	205
6.2.11	UDR.....	205
6.2.12	UDSF.....	205
6.2.13	SMSF.....	205
6.2.14	NSSF.....	206
6.2.15	5G-EIR.....	206
6.2.16	LMF.....	206
6.2.17	SEPP.....	206
6.2.18	Network Data Analytics Function (NWDAF).....	206
6.3	Principles for Network Function and Network Function Service discovery and selection.....	207
6.3.1	General.....	207
6.3.2	SMF discovery and selection.....	208
6.3.3	User Plane Function Selection.....	209
6.3.3.1	Overview.....	209
6.3.3.2	SMF Provisioning of available UPF(s).....	209
6.3.3.3	Selection of an UPF for a particular PDU Session.....	209
6.3.4	AUSF discovery and selection.....	210
6.3.5	AMF discovery and selection.....	211
6.3.6	N3IWF selection.....	212
6.3.6.1	General.....	212
6.3.6.2	Stand-alone N3IWF selection.....	213
6.3.6.3	Combined N3IWF/ePDG Selection.....	213

6.3.6.4	PLMN Selection for emergency services	214
6.3.7	PCF discovery and selection	215
6.3.7.0	General principles	215
6.3.7.1	PCF discovery and selection for a UE or a PDU Session	215
6.3.7.2	Providing policy requirements that apply to multiple UE and hence to multiple PCF.....	216
6.3.7.3	Binding an AF request targeting a UE address to the relevant PCF.....	216
6.3.8	UDM discovery and selection.....	216
6.3.9	UDR discovery and selection.....	217
6.3.10	SMSF discovery and selection.....	217
6.3.11	CHF discovery and selection	218
7	Network Function Services and descriptions	218
7.1	Network Function Service Framework.....	218
7.1.1	General.....	218
7.1.2	NF Service Consumer - NF Service Producer interactions.....	218
7.1.3	Network Function Service discovery	220
7.1.4	Network Function Service Authorization	220
7.1.5	Network Function and Network Function Service registration and de-registration.....	220
7.2	Network Function Services	221
7.2.1	General.....	221
7.2.2	AMF Services	222
7.2.3	SMF Services.....	222
7.2.4	PCF Services.....	223
7.2.5	UDM Services	223
7.2.6	NRF Services.....	224
7.2.7	AUSF Services.....	224
7.2.8	NEF Services	225
7.2.9	SMSF Services.....	225
7.2.10	UDR Services	225
7.2.11	5G-EIR Services	226
7.2.12	NWDAF Services	226
7.2.13	UDSF Services.....	226
7.2.14	NSSF Services	226
7.2.15	BSF Services.....	227
7.2.16	LMF Services.....	227
7.2.17	CHF Services	227
7.3	Exposure.....	227
8	Control and User Plane Protocol Stacks.....	228
8.1	General	228
8.2	Control Plane Protocol Stacks.....	228
8.2.1	Control Plane Protocol Stacks between the 5G-AN and the 5G Core: N2	228
8.2.1.1	General	228
8.2.1.2	AN - AMF.....	229
8.2.1.3	AN - SMF	229
8.2.2	Control Plane Protocol Stacks between the UE and the 5GC	229
8.2.2.1	General	229
8.2.2.2	UE - AMF	231
8.2.2.3	UE - SMF	231
8.2.3	Control Plane Protocol Stacks between the network functions in 5GC	232
8.2.3.1	The Control Plane Protocol Stack for the service based interface.....	232
8.2.3.2	The Control Plane protocol stack for the N4 interface between SMF and UPF.....	232
8.2.4	Control Plane for untrusted non 3GPP Access	233
8.3	User Plane Protocol Stacks.....	233
8.3.1	User Plane Protocol Stack for a PDU Session	233
8.3.2	User Plane for untrusted non 3GPP Access.....	235
Annex A (informative):	Relationship between Service-Based Interfaces and Reference Points...236	
Annex B (normative):	Mapping between temporary identities	238
Annex C (informative):	Guidelines and Principles for Compute-Storage Separation.....	239

Annex D (informative): **Change history**240
History250

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/e0a1c542-0ae8-4323-b6f1-d3998f70119f/etsi-ts-123-501-v15.9.0-2020-03>

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/e0a1c542-0aeb-4323-b6f1-d3998f70119f/etsi-ts-123-501-v15.9.0-2020-03>