

---

---

**Petroleum and natural gas industries —  
Specific requirements for offshore  
structures —**

**Part 7:  
Stationkeeping systems for floating  
offshore structures and mobile offshore  
units**

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

*Industries du pétrole et du gaz naturel — Exigences spécifiques  
relatives aux structures en mer —*

*Partie 7: Systèmes de maintien en position des structures en mer  
flottantes et des unités mobiles en mer*



## iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO 19901-7:2013

<https://standards.iteh.ai/catalog/standards/sist/6936eb85-24ce-4140-8687-1d5803621578/iso-19901-7-2013>



### **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

Page

Foreword .....	v
Introduction.....	vii
1 Scope .....	1
2 Normative references .....	2
3 Terms and definitions .....	2
4 Symbols and abbreviated terms .....	7
4.1 Symbols.....	7
4.2 Abbreviated terms .....	8
5 Overall considerations .....	9
5.1 Functional requirements.....	9
5.2 Safety requirements .....	9
5.3 Planning requirements.....	10
5.4 Inspection and maintenance requirements .....	10
5.5 Analytical tools .....	10
6 Design requirements .....	10
6.1 Exposure levels .....	10
6.2 Limit states .....	11
6.3 Defining design situations .....	11
6.4 Design situations.....	12
7 Actions.....	14
7.1 General .....	14
7.2 Site-specific data requirements .....	14
7.3 Environmental actions on mooring lines .....	15
7.4 Indirect actions .....	16
8 Mooring analysis .....	18
8.1 Basic considerations .....	18
8.2 Floating structure offset .....	19
8.3 Floating structure response .....	20
8.4 Mooring line response .....	25
8.5 Line tension .....	26
8.6 Line length and geometry constraints .....	26
8.7 Anchor forces .....	27
8.8 Typical mooring configuration analysis and assessment .....	27
8.9 Thruster-assisted moorings .....	28
8.10 Transient analysis of floating structure motions .....	29
9 Fatigue analysis.....	30
9.1 Basic considerations .....	30
9.2 Fatigue resistance .....	30
9.3 Fatigue analysis procedure .....	32
10 Design criteria.....	37
10.1 Floating structure offset .....	37
10.2 Line tension limit .....	38
10.3 Grounded line length .....	38
10.4 Anchoring systems .....	38
10.5 Fatigue safety factor .....	41
10.6 Corrosion and wear .....	41
10.7 Clearances .....	42

10.8	Supporting structures .....	42
11	Mooring hardware .....	42
11.1	Mooring line components .....	42
11.2	Winching equipment .....	43
11.3	Monitoring equipment .....	43
12	In-service inspection, monitoring and maintenance .....	44
12.1	General .....	44
12.2	Mobile moorings .....	44
12.3	Permanent moorings .....	44
13	Dynamic positioning system .....	46
13.1	Basic considerations .....	46
13.2	Design and analysis .....	47
13.3	Design, test and maintenance .....	48
13.4	Operating personnel .....	48
13.5	Determination of stationkeeping capability .....	48
14	Synthetic fibre rope mooring .....	48
14.1	Basic considerations .....	48
14.2	Fibre rope mooring analysis .....	49
14.3	Fatigue analysis .....	50
14.4	Creep analysis .....	50
14.5	Design criteria .....	50
14.6	Model testing .....	51
Annex A (informative)	Additional information and guidance .....	52
Annex B (informative)	Regional information .....	169
Bibliography .....		176

<https://standards.iteh.ai/catalog/standards/sist/6936eb85-24ce-4140-8687-1d5803621578/iso-19901-7-2013>  
 ISO 19901-7:2013

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 19901-7 was prepared by Technical Committee ISO/TC 67, *Materials, equipment and offshore structures for petroleum, petrochemical and natural gas industries*, Subcommittee SC 7, *Offshore structures*.

This second edition cancels and replaces the first edition (ISO 19901-7:2005), which has been technically revised.

This second edition of ISO 19901-7 includes several major additions and changes, primarily to Annex A (informative). The largest change is the addition of detailed informative text incorporated directly from API RP 2SK on all types of anchor design. In the first edition of this International Standard, this material was previously addressed only by reference to API RP 2SK. Informative material has also been added from API RP 2SK regarding the analysis and mitigation of vortex-induced motions of large cylindrical hulls. Consequently, the normative text has been modified to remove reference to API RP 2SK and to cross-reference portions of the expanded informative annex.

The other significant change is the updating of guidance on polyester rope mooring design to conform to the provisions of the recent amendment to API RP 2SM. The changes include new definitions of stiffness, recognition of effective filter barriers, removal of the prohibition against the rope touching the sea floor, and more detail on minimum tension requirements, among others. Additionally, minor corrections were made to the text in 7.4.4 (Wind actions) and 8.3.4 (Riser considerations), and the terminology "most probable maximum" has been standardized throughout. Finally, the Norwegian clause of Annex B has been updated at the request of Norway, and a new Canadian clause has been added.

ISO 19901 consists of the following parts, under the general title *Petroleum and natural gas industries — Specific requirements for offshore structures*:

- *Part 1: Metocean design and operating considerations*
- *Part 2: Seismic design procedures and criteria*
- *Part 3: Topsides structure*
- *Part 4: Geotechnical and foundation design considerations*
- *Part 5: Weight control during engineering and construction*
- *Part 6: Marine operations*
- *Part 7: Stationkeeping systems for floating offshore structures and mobile offshore units*

The following parts are under preparation:

- *Part 8: Marine soil investigations*

ISO 19901 is one of a series of International Standards for offshore structures. The full series consists of the following International Standards:

- ISO 19900, *Petroleum and natural gas industries — General requirements for offshore structures*
- ISO 19901 (all parts), *Petroleum and natural gas industries — Specific requirements for offshore structures*
- ISO 19902, *Petroleum and natural gas industries — Fixed steel offshore structures*
- ISO 19903, *Petroleum and natural gas industries — Fixed concrete offshore structures*
- ISO 19904-1, *Petroleum and natural gas industries — Floating offshore structures — Part 1: Monohulls, semi-submersibles and spars*
- ISO 19905-1, *Petroleum and natural gas industries — Site-specific assessment of mobile offshore units — Part 1: Jack-ups*
- ISO/TR 19905-2, *Petroleum and natural gas industries — Site-specific assessment of mobile offshore units — Part 2: Jack-ups commentary and detailed sample calculation*
- ISO 19905-3, *Petroleum and natural gas industries — Site-specific assessment of mobile offshore units — Part 3: Floating units*<sup>1)</sup>
- ISO 19906, *Petroleum and natural gas industries — Arctic offshore structures*

ISO 19901-7:2013  
<https://standards.iteh.ai/catalog/standards/sist/6936eb85-24ce-4140-8687-1d5803621578/iso-19901-7-2013>

---

1) Under preparation.

## Introduction

The series of International Standards applicable to types of offshore structure, ISO 19900 to ISO 19906, constitutes a common basis covering those aspects that address design requirements and assessments of all offshore structures used by the petroleum, petrochemical and natural gas industries worldwide. Through their application, the intention is to achieve reliability levels appropriate for manned and unmanned offshore structures, whatever type of structure and nature or combination of materials used.

It is important to recognize that structural integrity is an overall concept comprising models for describing actions, structural analyses, design rules, safety elements, workmanship, quality control procedures and national requirements, all of which are mutually dependent. The modification of one aspect of design in isolation can disturb the balance of reliability inherent in the overall concept or structural system. The implications involved in modifications therefore need to be considered in relation to the overall reliability of all offshore structural systems.

The series of International Standards applicable to types of offshore structure is intended to provide wide latitude in the choice of structural configurations, materials and techniques without hindering innovation. Sound engineering judgement is therefore necessary in the use of these International Standards.

This part of ISO 19901 was developed in response to the worldwide offshore industry's demand for a coherent and consistent definition of methodologies to analyse, design and evaluate stationkeeping systems used for floating production and/or storage platforms of various types (e.g. semi-submersibles, spar platforms, ship-shaped structures) and to assess site-specific applications of mobile offshore units (such as mobile offshore drilling units, pipelay units, construction units).

Stationkeeping is a generic term covering systems for keeping a floating structure, which is under the constant influence of external actions, on a pre-defined location and/or heading with limited excursions. Stationkeeping systems resist external actions by means of any combination of the following:

- mooring systems (e.g. spread moorings or single point moorings);
- dynamic positioning systems (generally consisting of thrusters).

The external actions generally consist of wind, wave, current and ice actions on the floating structure, mooring and/or risers.

Some background to, and guidance on, the use of this part of ISO 19901 is provided in informative Annex A. The clause numbering in Annex A is the same as in the normative text to facilitate cross-referencing.

Regional information, where available, is provided in informative Annex B.

## **iTeh STANDARD PREVIEW** **(standards.iteh.ai)**

ISO 19901-7:2013

<https://standards.iteh.ai/catalog/standards/sist/6936eb85-24ce-4140-8687-1d5803621578/iso-19901-7-2013>



# Petroleum and natural gas industries — Specific requirements for offshore structures —

## Part 7: Stationkeeping systems for floating offshore structures and mobile offshore units

### 1 Scope

This part of ISO 19901 specifies methodologies for

- a) the design, analysis and evaluation of stationkeeping systems for floating structures used by the oil and gas industries to support
  - 1) production,
  - 2) storage,
  - 3) drilling, well intervention and production,
  - 4) production and storage,
  - 5) drilling, well intervention, production and storage, and
- b) the assessment of stationkeeping systems for site-specific applications of mobile offshore units (e.g. mobile offshore drilling units, construction units, and pipelay units).

Most stationkeeping systems used with the class of floating structures covered by a) are termed “permanent mooring systems”, for which this part of ISO 19901 is applicable to all aspects of the life cycle and includes requirements relating to the manufacture of mooring components, as well as considerations for in-service inspections. Most stationkeeping systems used with mobile offshore units, the class covered by b), are termed “mobile mooring systems”. Throughout this part of ISO 19901, the term “floating structure”, sometimes shortened to “structure”, is used as a generic term to indicate any member of the two classes, a) and b).

This part of ISO 19901 is applicable to the following types of stationkeeping systems, which are either covered directly in this part of ISO 19901 or through reference to other guidelines:

- spread moorings (catenary, taut-line and semi-taut-line moorings);
- single point moorings, anchored by spread mooring arrangements;
- dynamic positioning systems;
- thruster-assisted moorings.

Descriptions of the characteristics and of typical components of these systems are given in Annex A.

The requirements of this part of ISO 19901 mainly address spread mooring systems and single point mooring systems with mooring lines composed of steel chain and wire rope. This part of ISO 19901 also provides

guidance on the application of the methodology to synthetic fibre rope mooring systems, and includes additional requirements related to the unique properties of synthetic fibre ropes.

This part of ISO 19901 is applicable to single anchor leg moorings (SALMs) and other single point mooring systems (e.g. tower soft yoke systems) only to the extent to which the requirements are relevant.

This part of ISO 19901 is not applicable to the vertical moorings of tension leg platforms (TLPs).

The methodology described in this part of ISO 19901 identifies a set of coherent analysis tools that, combined with an understanding of the site-specific metocean conditions, the characteristics of the floating structure under consideration, and other factors, can be used to determine the adequacy of the stationkeeping system to meet the functional requirements of this part of ISO 19901.

NOTE For moorings deployed in ice-prone environments, additional requirements are given in ISO 19906.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 19900, *Petroleum and natural gas industries — General requirements for offshore structures*

ISO 19901-1, *Petroleum and natural gas industries — Specific requirements for offshore structures — Part 1: Metocean design and operating considerations*

ISO 19904-1, *Petroleum and natural gas industries — Floating offshore structures — Part 1: Monohulls, semi-submersibles and spars*

[ISO 19901-7:2013](https://standards.iteh.ai/catalog/standards/sist/6936eb85-24ce-4140-8687-1d5803621578/iso-19901-7-2013)

<https://standards.iteh.ai/catalog/standards/sist/6936eb85-24ce-4140-8687-1d5803621578/iso-19901-7-2013>

## 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

**3.1**  
**action**  
external load applied to the structure (direct action) or an imposed deformation or acceleration (indirect action)

EXAMPLE An imposed deformation can be caused by fabrication tolerances, settlement, temperature change or moisture variation.

NOTE An earthquake typically generates imposed accelerations.

[ISO 19900:2002]

**3.2**  
**action effect**  
effect of actions on structural components

[ISO 19900:2002]

EXAMPLE Internal forces, moments, stresses, strains, rigid body motions or elastic deformations.

**3.3**  
**catenary mooring**  
mooring system where the restoring action is provided by the distributed weight of mooring lines

[ISO 19900:2002]

**3.4****characteristic value**

value assigned to a basic variable, an action or a resistance from which the design value can be found by the application of a partial factor

NOTE 1 The value usually has a prescribed probability of not being violated which, in the case of an action, will normally relate to a reference period.

NOTE 2 Adapted from ISO 19900:2002, definition 2.7.

**3.5****design criteria**

quantitative formulations that describe the conditions to be fulfilled for each limit state

[ISO 19900:2002]

**3.6****design service life**

assumed period for which a structure or a structural component is to be used for its intended purpose with anticipated maintenance, but without substantial repair being necessary

NOTE Adapted from ISO 19900:2002, definition 2.12.

**3.7****design situation**

set of physical conditions during a certain reference period for which the design will demonstrate that relevant limit states are not exceeded

NOTE Adapted from ISO 19900:2002, definition 2.13.

**3.8****dynamic action**

action that induces acceleration of a structure or a structural component of a magnitude sufficient to require specific consideration

**3.9****dynamic positioning****DP**

stationkeeping technique consisting primarily of a system of automatically controlled on-board thrusters, which generate appropriate thrust vectors to counter the mean and slowly varying induced actions

**3.10****expected value**

first-order statistical moment of the probability density function for the considered variable that, in the case of a time-dependent parameter, can be associated with a specific reference period

**3.11****fit-for-purpose****fitness-for-purpose**

meeting the intent of an International Standard although not meeting specific provisions of that International Standard in local areas, such that failure in these areas will not cause unacceptable risk to life-safety or the environment

[ISO 19900:2002]

**3.12**

**floating structure**

structure where the full weight is supported by buoyancy

[ISO 19900:2002]

NOTE The full weight includes lightship weight, mooring system pre-tension, riser pre-tension, operating weight, etc.

**3.13**

**limit state**

state beyond which the structure no longer fulfils the relevant design criteria

[ISO 19900:2002]

**3.14**

**maintenance**

set of activities performed during the operating life of a structure to ensure it is fit-for-purpose

**3.15**

**minimum breaking strength**

**MBS**

RCS certified strength of a chain, wire rope, fibre rope or accessories

**3.16**

**mobile mooring system**

mooring system, generally retrievable, intended for deployment at a specific location for a short-term operation, such as those for mobile offshore units (MOUs)

**3.17**

**mobile offshore drilling unit**

**MODU**

structure capable of engaging in drilling and well intervention operations for exploration or exploitation of subsea petroleum resources

**3.18**

**mobile offshore unit**

**MOU**

structure intended to be frequently relocated to perform a particular function

[ISO 19900:2002]

EXAMPLE Pipelaying vessel or barge, offshore construction structure, accommodation structure (floatel), service structure, or mobile offshore drilling units.

**3.19**

**mooring component**

general class of component used in the mooring of floating structures

EXAMPLE Chain, steel wire rope, synthetic fibre rope, clump weight, buoy, winch/windlass, fairlead or anchor.

**3.20**

**owner**

representative of the company or companies which own a development, who can be the operator on behalf of co-licensees

**3.21**

**permanent mooring system**

mooring system normally used to moor floating structures deployed for long-term operations, such as those for a floating production system (FPS)

**3.22****proximity**

closeness in distance

NOTE 1 Mooring systems are considered to be in proximity to a surface installation (or facility) if any part of the other installation lies within a contour described by the set of offsets coinciding with each line reaching 100 % MBS in the intact or redundancy check condition, whichever is larger.

NOTE 2 Mooring systems are considered to be in proximity to a sea floor installation (or facility) if any part of the other installation lies within a polygon formed by the anchor locations.

**3.23****RCS****recognized classification society**

member of the international association of classification societies (IACS), with recognized and relevant competence and experience in floating structures, and with established rules and procedures for classification/certification of installations used in petroleum-related activities

**3.24****resistance**

capacity of a structure, a component or a cross-section of a component to withstand action effects without exceeding a limit state

NOTE This definition is at variance with that specified in ISO 19900:2002.

**3.25****return period**

average period between occurrences of an event or of a particular value being exceeded

NOTE The offshore industry commonly uses a return period measured in years for environmental events. The return period is equal to the reciprocal of the annual probability of exceedance of the event.

[ISO 19901-1:2005] <https://standards.iteh.ai/catalog/standards/sist/6936eb85-24ce-4140-8687-1d5803621578/iso-19901-7-2013>

**3.26****riser**

piping connecting the process facilities or drilling equipment on the floating structure with the subsea facilities or pipelines, or reservoir

NOTE 1 Possible functions include drilling and well intervention, production, injection, subsea systems control and export of produced fluids.

NOTE 2 Adapted from ISO 19900:2002, definition 2.29.

**3.27****semi-submersible**

floating structure normally consisting of a deck structure with a number of widely spaced, large cross-section, supporting columns connected to submerged pontoons

NOTE Pontoon/column geometry is usually chosen to minimize global motions in a broad range of wave frequencies.

**3.28****serviceability**

ability of a structure or structural component to perform adequately for normal functional use

**3.29****significant value**

statistical measure of a zero-mean random variable equal to twice the standard deviation of the variable

**3.30**

**single point mooring**

mooring system that allows the floating structure to which it is connected to vary its heading (weathervane)

EXAMPLE One example of a single point mooring is a turret mooring system where a number of mooring lines are attached to a turret, which includes bearings to allow the structure to rotate.

**3.31**

**ship-shaped structure**

monohull floating structure having a geometry similar to that of ocean-going ships

**3.32**

**spar platform**

deep-draught, small water-plane area floating structure

**3.33**

**spread mooring**

mooring system consisting of multiple mooring lines terminated at different locations on a floating structure, and extending outwards, providing an almost constant structure heading

**3.34**

**stationkeeping system**

system capable of limiting the excursions of a floating structure within prescribed limits

**3.35**

**structural component**

physically distinguishable part of a structure

[ISO 19900:2002]

**3.36**

**structure**

organized combination of connected components designed to withstand actions and provide adequate rigidity

[ISO 19900:2002]

**3.37**

**taut-line mooring**

mooring system where the restoring action is provided by elastic deformation of mooring lines

[ISO 19900:2002]

**3.38**

**thruster-assisted mooring**

stationkeeping system consisting of mooring lines and thrusters

**3.39**

**verification**

examination made to confirm that an activity, product, or service is in accordance with specified requirements

**3.40**

**weathervaning**

process by which a floating structure passively varies its heading in response to time-varying environmental actions

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

ISO 19901-7:2013

[https://standards.iteh.ai/catalog/standards/sist/6936eb85-24ce-4140-8687-](https://standards.iteh.ai/catalog/standards/sist/6936eb85-24ce-4140-8687-1d5803621578/iso-19901-7-2013)

[1d5803621578/iso-19901-7-2013](https://standards.iteh.ai/catalog/standards/sist/6936eb85-24ce-4140-8687-1d5803621578/iso-19901-7-2013)

## 4 Symbols and abbreviated terms

### 4.1 Symbols

$C$	coefficient (non-dimensional unless otherwise specified)
$D$	annual fatigue damage, in years <sup>-1</sup>
$d$	diameter of the mooring line or component, in metres (m)
$F$	direct action, in newtons (N), or a direct action per unit length, in newtons per metre, (N/m)
$f$	frequency, in hertz (Hz)
$K$	fatigue constant (non-dimensional unless otherwise specified)
$k$	axial stiffness, in newtons per metre (N/m)
$L$	design service life, in years
$l$	length, in metres (m)
$M$	mass, in kilograms (kg)
$m$	inverse slope of T-N or S-N fatigue curves
$N$	total number of (permissible) cycles
$n$	number of cycles per annum, in year <sup>-1</sup>
$P$	probability of occurrence
$S$	offset or motion, in metres (m)
$S_R$	stress range, in megapascals (MPa)
$s$	standard deviation
$T$	tension force, in newtons (N); or non-dimensional tension ratio
$t$	time, period or duration, in seconds (s)
$v$	velocity, in metres per second (m/s)
$W$	submerged weight, in newtons (N), or weight per unit length, in newtons per metre (N/m)
$\Gamma$	gamma function
$\gamma$	design safety factor
$\delta$	bandwidth parameter for the wave frequency
$\varepsilon$	annual creep elongation, percent per year
$\sigma$	ratio of the standard deviation of the tension variations around the mean tension to a reference breaking strength
$\rho$	density, in kilograms per cubic metre (kg/m <sup>3</sup> )