

ETSI TS 132 423 V15.2.0 (2020-03)



**Digital cellular telecommunications system (Phase 2+) (GSM);
Universal Mobile Telecommunications System (UMTS);**

LTE;

**Telecommunication management;
Subscriber and equipment trace;
Trace data definition and management
(3GPP TS 32.423 version 15.2.0 Release 15)**



ReferenceRTS/TSGS-0532423vf20

KeywordsGSM,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

| | |
|--|-----------|
| Intellectual Property Rights | 2 |
| Legal Notice | 2 |
| Modal verbs terminology..... | 2 |
| Foreword..... | 5 |
| Introduction | 5 |
| 1 Scope | 6 |
| 2 References | 6 |
| 3 Definitions, symbols and abbreviations | 8 |
| 3.1 Definitions | 8 |
| 3.2 Symbols..... | 8 |
| 3.3 Abbreviations | 8 |
| 4 Trace record contents | 9 |
| 4.1 General | 9 |
| 4.2 MSC Server Trace Record Content | 10 |
| 4.3 MGW Trace Record Content..... | 17 |
| 4.4 SGSN Trace Record Content..... | 18 |
| 4.5 GGSN Trace Record Content..... | 27 |
| 4.6 UTRAN Trace Record Content | 31 |
| 4.7 S-CSCF Trace Record Content | 38 |
| 4.8 P-CSCF Trace Record Content | 38 |
| 4.9 HSS Trace Record Content | 39 |
| 4.10 BM-SC Trace Record Content | 43 |
| 4.11 PGW Trace Record Content | 44 |
| 4.12 MME Trace Record Content | 49 |
| 4.13 E-UTRAN Trace Record Content | 58 |
| 4.14 SGW Trace Record Content..... | 64 |
| 4.15 EIR Trace Record Content | 69 |
| 4.16 LTE MDT Trace Record Content..... | 70 |
| 4.16.1 Trace Record for Immediate MDT measurements..... | 70 |
| 4.16.2 Trace Record for UE location information | 73 |
| 4.17 UMTS MDT Trace Record Content..... | 73 |
| 4.17.1 Trace Record for Immediate MDT measurements..... | 73 |
| 4.17.2 Trace Record for UE location information | 75 |
| 4.18 AMF Trace Record Content | 75 |
| 4.19 SMF Trace Record Content..... | 77 |
| 4.20 PCF Trace Record Content..... | 77 |
| 4.21 AUSF Trace Record Content..... | 78 |
| 4.22 NEF Trace Record Content | 78 |
| 4.23 NRF Trace Record Content | 79 |
| 4.24 NSSF Trace Record Content | 79 |
| 4.25 UDM Trace Record Content | 80 |
| 4.26 UPF Trace Record Content | 81 |
| 4.27 SMSF Trace Record Content..... | 81 |
| 4.28 AF Trace Record Content..... | 81 |
| 4.29 Void..... | 82 |
| 4.30 gNB-CU-CP Trace Record Content | 82 |
| 4.31 gNB-CU-UP Trace Record Content | 83 |
| 4.32 gNB-DU Trace Record Content | 83 |
| 4.33 ng-eNB Trace Record Content | 84 |
| Annex A (normative): Trace Report File Format | 85 |
| A.0 Introduction | 85 |

| | | |
|-------------------------------|--|------------|
| A.1 | Parameter description and mapping table..... | 86 |
| A.2 | XML file format definition..... | 89 |
| A.2.1 | XML trace/MDT file diagram..... | 89 |
| A.2.2 | Trace data file XML schema..... | 90 |
| Annex B (normative): | Trace Report File Conventions and Transfer Procedure..... | 93 |
| B.0 | Introduction..... | 93 |
| B.1 | File naming convention..... | 93 |
| B.2 | File transfer..... | 94 |
| Annex C (informative): | Trace Functional Architecture: Reporting..... | 95 |
| C.1 | Figure of Trace Reporting..... | 95 |
| Annex D (informative): | Examples of trace files..... | 97 |
| D.1 | Examples of trace XML file..... | 97 |
| D.1.1 | Example of XML trace file with the maximum level of details..... | 97 |
| D.1.2 | Example of XML trace file with the minimum level of details..... | 98 |
| D.1.3 | Example of XML trace file for IMSI information from the MME..... | 98 |
| D.1.4 | Example of MDT XML file..... | 99 |
| Annex E (informative): | Void..... | 100 |
| Annex F (informative): | Change history..... | 101 |
| History..... | | 104 |

iTeh STANDARD PREVIEW
 (standards.iteh.ai)
 Full standard:
<https://standards.iteh.ai/catalog/standards/sist/61d423998-1da6-421d-9a49-1216db76829b/etsi-ts-132-423-v15-2-0-2020-03>

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management, as identified below:

TS 32.421: "Subscriber and equipment trace; Trace concepts and requirements";

TS 32.422: "Subscriber and equipment trace; Trace control and configuration management";

TS 32.423: "Subscriber and equipment trace; Trace data definition and management";

Subscriber and MS Trace provide very detailed information at call level on one or more specific mobile(s). This data is an additional source of information to Performance Measurements and allows going further in monitoring and optimisation operations.

Contrary to Performance Measurements, which are a permanent source of information, Trace is activated on user demand for a limited period of time for specific analysis purpose

Trace plays a major role in activities such as determination of the root cause of a malfunctioning mobile, advanced troubleshooting, optimisation of resource usage and quality, RF coverage control and capacity improvement, dropped call analysis, Core Network and TRAN end to end procedure validation.

The capability to log data on any interface at call level for a specific user (e.g. IMSI or SUPI) or mobile type (e.g. IMEI or IMEISV) allows getting information which cannot be deduced from Performance Measurements such as perception of end-user QoS during his call (e.g. requested QoS vs. provided QoS), correlation between protocol messages and RF measurements, or interoperability with specific mobile vendors.

Moreover, Performance Measurements provide values aggregated on an observation period, Subscriber and Equipment Trace give instantaneous values for a specific event (e.g. call, location update, etc.).

If Performance Measurements are mandatory for daily operations, future network planning and primary trouble shooting, Subscriber and MS Trace is the easy way to go deeper into investigation and network optimisation.

In order to produce this data, Subscriber and MS trace are carried out in the NEs, which comprise the network. The data can then be transferred to an external system (e.g. an Operations System (OS) in TMN terminology, for further evaluation).

1 Scope

The present document describes Trace data definition and management. It covers the trace records content, their format and transfer across UMTS networks, EPS networks or 5GS networks. GSM Trace is outside of the scope of this specification..

The present document also describes the data definition for Minimization of Drive Tests (MDT) across UMTS networks or EPS networks.

The objectives of the present document are:

- To provide the descriptions for a standard set of Trace and MDT data;
- To define the common format of trace and MDT records; and
- To define a method for the reporting of Trace and MDT results across the management interfaces.

Clause 4 details the various Trace records content, Annex A provides Trace and MDT report file format, Annex B provides the trace report file conventions and transfer procedure, Annex C provides the trace reporting functional architecture and Annex D provides some trace and MDT files examples. Trace and MDT concepts and requirements are covered in TS 32.421 [2] while Trace control and configuration management are described in 3GPP TS 32.422 [3].

The definition of Trace and MDT data is intended to result in comparability of Trace and MDT data produced in a multi-vendor wireless UMTS and/or EPS network.

The following is beyond the scope of the present document, and therefore the present document does not describe:

- Any notification mechanisms or IRPs for trace. Only file transfer mechanism is specified for trace data transfer;
- Any data compression mechanisms for trace data transfer;
- Any Trace capability limitations (e.g. maximum number of simultaneous traced mobiles for a given NE).

2 References

The following documents contain provisions, which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
- [2] 3GPP TS 32.421: "Telecommunication management; Subscriber and equipment trace: Trace concepts and requirements."
- [3] 3GPP TS 32.422: "Telecommunication management; Subscriber and equipment trace: Trace control and configuration management".
- [4] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [5] W3C Recommendation "Extensible Markup Language (XML) 1.0" (Second Edition, 6 October 2000) <http://www.w3.org/TR/2000/REC-xml-20001006>
- [6] W3C Recommendation "Namespaces in XML" (14 January 1999) <http://www.w3.org/TR/1999/REC-xml-names-19990114>

- [7] W3C Recommendation "XML Schema Part 0: Primer" (2 May 2001)
<http://www.w3.org/TR/2001/REC-xmlschema-0-20010502>
- [8] W3C Recommendation "XML Schema Part 1: Structures" (2 May 2001)
<http://www.w3.org/TR/2001/REC-xmlschema-1-20010502>
- [9] W3C Recommendation "XML Schema Part 2: Datatypes" (2 May 2001)
<http://www.w3.org/TR/2001/REC-xmlschema-2-20010502>
- [10] International Standard ISO 8601: 1988 (E) "Representations of dates and times" (1988-06-15)
<http://www.iso.ch/markete/8601.pdf>
- [11] 3GPP TS 32.300: "Telecommunication management; Configuration Management (CM); Name convention for Managed Objects".
- [12] 3GPP TS 32.622: "Telecommunication management; Configuration Management (CM); Generic network resources Integration Reference Point (IRP): Network Resource Model (NRM)".
- [13] 3GPP TS 29.274: "3GPP Evolved Packet System (EPS); Evolved General Packet Radio Service (GPRS) Tunnelling Protocol for Control plane (GTPv2-C); Stage 3".
- [14] 3GPP TS 29.212: "Policy and Charging Control (PCC); Reference points".
- [15] 3GPP TS 29.273: "Evolved Packet System (EPS); 3GPP EPS AAA interfaces".
- [16] 3GPP TS 36.413: "Evolved Universal Terrestrial Radio Access Network (E-UTRAN); S1 Application Protocol (S1AP)".
- [17] 3GPP TS 36.423 "Evolved Universal Terrestrial Radio Access Network (E-UTRAN); X2 Application Protocol (X2AP)".
- [18] 3GPP TS 23.501: "System Architecture for the 5G System; Stage 2".
- [19] 3GPP TS 23.502: "Procedures for the 5G System; Stage 2"
- [20] 3GPP TS 38.300: "NR and NG-RAN Overall Description; Stage 2".
- [21] 3GPP TS 38.331: "NR; Radio Resource Control (RRC); Protocol specification".
- [22] 3GPP TS 38.401: "NG-RAN; Architecture Description".
- [23] 3GPP TS 38.413: "NG-RAN; NG Application Protocol (NGAP)".
- [24] 3GPP TS 38.423: "NG-RAN; Xn Application Protocol (XnAP)".
- [25] 3GPP TS 38.463: "NG-RAN; E1 Application Protocol (E1AP)".
- [26] 3GPP TS 38.473: "NG-RAN; F1 Application Protocol (F1AP)".
- [27] 3GPP TS 24.501: "Non-Access-Stratum (NAS) protocol for 5G System (5GS); Stage 3".
- [28] 3GPP TS 36.331: "Evolved Universal Terrestrial Radio Access (E-UTRA); Radio Resource Control (RRC); Protocol specification".
- [29] 3GPP TS 23.107: "Quality of Service (QoS) concept and architecture".
- [30] 3GPP TS 25.331: "Radio Resource Control (RRC); Protocol specification".
- [31] 3GPP TS 36.314: "Evolved Universal Terrestrial Radio Access (E-UTRA); Layer 2 - Measurements".
- [32] 3GPP TS 37.320: "Universal Terrestrial Radio Access (UTRA) and Evolved Universal Terrestrial Radio Access (E-UTRA); Radio measurement collection for Minimization of Drive Tests (MDT); Overall description; Stage 2".
- [33] 3GPP TS 36.213: "Evolved Universal Terrestrial Radio Access (E-UTRA); Physical layer procedures".

- [34] 3GPP TS 36.133: "Evolved Universal Terrestrial Radio Access (E-UTRA); Requirements for support of radio resource management".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TS 32.421 [2], 3GPP TS 32.422 [3], TS 23.501 [18], TS 38.300 [20], TS 38.401 [22], TS 37.320 [32] and the following apply.









Minimum Level of detail: Allows for retrieval of a decoded subset of the IEs contained in the signalling interface messages.

Medium Level of detail: Allows for retrieval of the decoded subset of the IEs contained in the signalling interface messages in the Minimum Level plus a selected set of decoded radio measurement IEs.

Maximum Level of detail: Allows for retrieval of signalling interface messages within the Trace Scope in encoded format.

3.2 Symbols

For the purposes of the present document, the following symbols apply:

| | |
|---|--|
|  | : Element named xxx The maximum number of occurrence is 1 |
|  | : Element named xxx The maximum number of occurrence is unbounded |
|  | : Global element |
|  | The XML element has a value part |
|  | : Required element |
|  | : Optional element |
|  | : Sequence |
|  | : Choice |

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [4], TS 32.101 [1], TS 23.501 [18], TS 38.300 [20] and TS 38.401 [22] and TS 37.320 [32] apply.

NSA Non Stand Alone

4 Trace record contents

4.1 General

The trace reference, trace type and operation system identification are all provided on trace activation.

Each record may contain an MSC Server, MGW, SGSN, GGSN, S-CSCF, P-CSCF, UTRAN, HSS, MME, Serving GW, E-UTRAN, AUSF, AMF, NEF, NRF, NSSF, PCF, SMF, SMSF, UDM, UPF, AF and , ng-eNB, gNB-CU-CP, gNB-CU-UP and gNB-DU event record. A key is included in the table indicating whether or not the field is mandatory.

The following table shows the template for trace record description for minimum and medium trace depth:

| Interface name | Protocol name | IE name | Message name(s) | Trace depth | | Notes |
|----------------|---------------|---------|-----------------|-------------|-----|-------|
| | | | | Min | Med | |
| | | | | | | |

Interface name: Contains the name of the interface, where the IE is available.

Protocol name: Contains the protocol name on the interface, where the IE is available.

IE name: The name of the Information Element, which should be decoded.

Message name(s): The name of the message(s), where the IE is included.

Trace depth: Shows in which trace depth the IE should be recorded. It also classifies whether the IE is mandatory in the trace record or not (M, O or X: meaning described in the previous table)

| | | |
|-----------|-----------------------|---|
| M | Mandatory | This field must be in the trace record if it is available, i.e. if the message appears during the trace recording session and the IE is present in the message. |
| O | Optional | This field is optional and its support is a matter for agreement between equipment manufacturer and network operator. |
| X | Not applicable | This field is not required in this instance. |
| CM | Conditional Mandatory | This field must be in the trace record if it is available and the condition is met. |

NOTE: Any kind of comments related to the IE can be made here. Also this is the placeholder for referencing the relevant 3GPP specifications, which define the IE.

4.2 MSC Server Trace Record Content

The following table shows the trace record content for MSC Server.

The trace record is the same for management based activation and for signalling based activation.

For MSC Server, the Minimum level of detail shall be supported.

*iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/61d23998-1da6-421d-9a49-1216db76829b/etsi-ts-132-423-v15.2.0-2020-03>*

| Interface name | Prot. name | IE name | Message name(s) | Trace depth | | Notes |
|----------------|------------|------------------------------|--|-------------|-----|------------------------|
| | | | | Min | Med | |
| lu, A | CC | Facility | ALERTING CALL PROCEEDING CONNECT DISCONNECT FACILITY RELEASE RELEASE COMPLETE SETUP | M | M | TS 24.008 TS 24.080 |
| | | Bearer capability | CALL CONFIRMED CALL PROCEEDING EMERGENCY SETUP MODIFY MODIFY COMPLETE MODIFY REJECT SETUP | M | M | TS 24.008 |
| | | Cause | CALL CONFIRMED CONGESTION CONTROL DISCONNECT HOLD REJECT MODIFY REJECT RELEASE RELEASE COMPLETE RETRIEVE REJECT START DTMF REJECT STATUS | M | M | TS 24.008 |
| | | Connected number | CONNECT | M | M | TS 24.008 |
| | | Calling party BCD number | SETUP | M | M | TS 24.008 |
| | | Called party BCD number | SETUP | M | M | TS 24.008 |
| | | Redirecting party BCD number | SETUP | M | M | TS 24.008 |
| lu, A | MM | Reject cause | AUTHENTICATION FAILURE CM SERVICE REJECT ABORT LOCATION UPDATING REJECT MM STATUS | M | M | TS 24.008 |
| | | Location area identification | CM RE-ESTABLISHMENT REQUEST LOCATION UPDATING ACCEPT LOCATION UPDATING REQUEST TMSI REALLOCATION COMMAND | M | M | TS 24.008 |
| | | Mobile identity | CM RE-ESTABLISHMENT REQUEST CM SERVICE REQUEST IDENTITY REQUEST IDENTITY RESPONSE IMSI DETACH INDICATION LOCATION UPDATING ACCEPT LOCATION UPDATING REQUEST TMSI REALLOCATION COMMAND | M | M | TS 24.008 |
| | | CM service type | CM SERVICE REQUEST | M | M | TS 24.008 |
| | | Location updating type | LOCATION UPDATING REQUEST | M | M | TS 24.008 |
| | | Facility | FACILITY REGISTER RELEASE COMPLETE | M | M | TS 24.008 |

| | | | | | | |
|----------------------------------|---|-------------------------------|---|--------------|--|-----------|
| | | Cause | RELEASE COMPLETE | M | M | TS 24.008 |
| lu, A | SMS | TP-Originating-Address | SMS-DELIVER | M | M | TS 23.040 |
| | | TP-Service-Centre- Time-Stamp | SMS-DELIVER SMS-SUBMIT-REPORT SMS-STATUS-REPORT | M | M | TS 23.040 |
| | | TP-Failure-Cause | SMS-DELIVER-REPORT SMS-SUBMIT-REPORT | M | M | TS 23.040 |
| | | TP-Destination-Address | SMS-SUBMIT SMS-COMMAND | M | M | TS 23.040 |
| | | TP-Recipient-Address | SMS-STATUS-REPORT | M | M | TS 23.040 |
| | | A | BSSMAP | Channel Type | ASSIGNMENT REQUEST HANDOVER REQUEST | M |
| Circuit | ASSIGNMENT REQUEST | | | M | M | TS 48.008 |
| Cell Identifier (Serving) | ASSIGNMENT COMPLETE HANDOVER REQUEST HANDOVER COMMAND HANDOVER PERFORMED PERFORM LOCATION REQUEST | | | M | M | TS 48.008 |
| Chosen Channel | ASSIGNMENT COMPLETE HANDOVER REQUEST ACKNOWLEDGE HANDOVER PERFORMED | | | M | M | TS 48.008 |
| Speech version (chosen) | ASSIGNMENT COMPLETE HANDOVER REQUEST HANDOVER REQUIRED HANDOVER REQUEST ACKNOWLEDGE HANDOVER PERFORMED | | | M | M | TS 48.008 |
| Cause | ASSIGNMENT FAILURE HANDOVER REQUEST HANDOVER REQUIRED HANDOVER FAILURE CLEAR REQUEST CLEAR COMMAND HANDOVER PERFORMED HANDOVER REQUIRED REJECT | | | M | M | TS 48.008 |
| RR Cause | ASSIGNMENT FAILURE HANDOVER COMPLETE HANDOVER FAILURE | | | M | M | TS 48.008 |
| Cell Identifier (target) | HANDOVER REQUEST | | | M | M | TS 48.008 |
| Current Channel type 1 | HANDOVER REQUEST HANDOVER REQUIRED | | | M | M | TS 48.008 |
| Cell Identifier List (Preferred) | HANDOVER REQUIRED PAGING | | | M | M | TS 48.008 |
| IMSI | PAGING COMMON ID | | | M | M | TS 48.008 |
| Location Type | PERFORM LOCATION REQUEST | | | M | M | TS 48.008 |
| Location Estimate | PERFORM LOCATION RESPONSE | | | M | M | TS 48.008 |
| LCS Cause | PERFORM LOCATION RESPONSE PERFORM LOCATION ABORT | | | M | M | TS 48.008 |