

ETSI TS 138 101-1 V15.9.0 (2020-04)



TECHNICAL SPECIFICATION

**5G;  
NR;**

**User Equipment (UE) radio transmission and reception;  
Part 1: Range 1 Standalone  
(3GPP TS 38.101-1 version 15.9.0 Release 15)**

PREVIEW  
https://standards.iteh.ai/standards/sist/3631b429-32a5-4888-9010-450a49db4200/38-101-1-v15.9.0-2020-04



---

**Reference**RTS/TSGR-0438101-1v90

---

**Keywords**5G

---

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

---

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

---

**Copyright Notification**

---

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.

All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

**3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

**GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

---

# Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

---

# Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

Intellectual Property Rights .....	2
Legal Notice .....	2
Modal verbs terminology.....	2
Foreword.....	11
1 Scope .....	12
2 References .....	12
3 Definitions, symbols and abbreviations .....	12
3.1 Definitions .....	12
3.2 Symbols.....	13
3.3 Abbreviations .....	15
4 General .....	16
4.1 Relationship between minimum requirements and test requirements .....	16
4.2 Applicability of minimum requirements .....	16
4.3 Specification suffix information.....	16
5 Operating bands and channel arrangement.....	17
5.1 General .....	17
5.2 Operating bands.....	17
5.2A Operating bands for CA .....	18
5.2A.1 Intra-band CA .....	18
5.2A.2 Inter-band CA .....	19
5.2B Void.....	19
5.2C Operating band combination for SUL .....	19
5.3 UE channel bandwidth .....	20
5.3.1 General.....	20
5.3.2 Maximum transmission bandwidth configuration .....	20
5.3.3 Minimum guardband and transmission bandwidth configuration.....	21
5.3.4 RB alignment .....	22
5.3.5 UE channel bandwidth per operating band .....	22
5.3.6 Asymmetric channel bandwidths .....	24
5.3A UE channel bandwidth for CA .....	24
5.3A.1 General.....	24
5.3A.2 Maximum transmission bandwidth configuration for CA .....	24
5.3A.3 Minimum guardband and transmission bandwidth configuration for CA .....	25
5.3A.4 Void .....	26
5.3A.5 UE channel bandwidth per operating band for CA.....	26
5.4 Channel arrangement.....	27
5.4.1 Channel spacing.....	27
5.4.1.1 Channel spacing for adjacent NR carriers .....	27
5.4.2 Channel raster .....	27
5.4.2.1 NR-ARFCN and channel raster.....	27
5.4.2.2 Channel raster to resource element mapping.....	28
5.4.2.3 Channel raster entries for each operating band .....	28
5.4.3 Synchronization raster .....	29
5.4.3.1 Synchronization raster and numbering.....	29
5.4.3.2 Synchronization raster to synchronization block resource element mapping.....	30
5.4.3.3 Synchronization raster entries for each operating band.....	30
5.4.4 TX–RX frequency separation .....	31
5.4A Channel arrangement for CA.....	32
5.4A.1 Channel spacing for CA.....	32
5.4A.2 Channel raster for CA.....	32
5.4A.3 Synchronization raster for CA .....	32
5.4A.4 Tx-Rx frequency separation for CA.....	32
5.5 Void.....	33

5.5A	Configurations for CA.....	33
5.5A.1	Configurations for intra-band contiguous CA.....	33
5.5A.2	Void.....	34
5.5A.3	Configurations for inter-band CA.....	34
5.5B	Void.....	37
5.5C	Configurations for SUL.....	37
6	Transmitter characteristics .....	38
6.1	General .....	38
6.2	Transmitter power .....	38
6.2.1	UE maximum output power.....	38
6.2.2	UE maximum output power reduction.....	39
6.2.3	UE additional maximum output power reduction.....	41
6.2.3.1	General.....	41
6.2.3.2	A-MPR for NS_04.....	44
6.2.3.3	A-MPR for NS_10.....	45
6.2.3.4	A-MPR for NS_05 and NS_05U.....	46
6.2.3.5	A-MPR for NS_40.....	49
6.2.3.6	A-MPR for NS_43 and NS_43U.....	49
6.2.3.7	A-MPR for NS_03 and NS_03U.....	50
6.2.3.8	A-MPR for NS_37.....	50
6.2.3.9	A-MPR for NS_38.....	51
6.2.3.10	A-MPR for NS_39.....	51
6.2.3.11	A-MPR for NS_41.....	52
6.2.3.12	A-MPR for NS_42.....	53
6.2.3.13	A-MPR for NS_18.....	53
6.2.4	Configured transmitted power.....	54
6.2A	Transmitter power for CA.....	56
6.2A.1	UE maximum output power for CA.....	56
6.2A.1.1	Void.....	56
6.2A.1.2	Void.....	56
6.2A.1.3	UE maximum output power for Inter-band CA.....	56
6.2A.2	UE maximum output power reduction for CA.....	57
6.2A.2.1	Void.....	57
6.2A.2.2	Void.....	57
6.2A.2.3	UE maximum output power reduction for Inter-band CA.....	57
6.2A.3	UE additional maximum output power reduction for CA.....	57
6.2A.3.1.1	Void.....	57
6.2A.3.1.2	Void.....	57
6.2A.3.1.3	UE additional maximum output power reduction for Inter-band CA.....	57
6.2A.4	Configured output power for CA.....	57
6.2A.4.1	Configured transmitted power level.....	57
6.2A.4.1.1	Void.....	57
6.2A.4.1.2	Void.....	57
6.2A.4.1.3	Configured transmitted power for Inter-band CA.....	57
6.2A.4.2	$\Delta T_{IB,c}$ for CA.....	59
6.2A.4.2.1	Void.....	59
6.2A.4.2.2	Void.....	59
6.2A.4.2.3	$\Delta T_{IB,c}$ for Inter-band CA.....	59
6.2B	Void.....	60
6.2C	Transmitter power for SUL.....	60
6.2C.1	Configured transmitted power for SUL.....	60
6.2C.2	$\Delta T_{IB,c}$ .....	60
6.2D	Transmitter power for UL MIMO.....	61
6.2D.1	UE maximum output power for UL MIMO.....	61
6.2D.2	UE maximum output power reduction for UL MIMO.....	61
6.2D.3	UE additional maximum output power reduction for UL MIMO.....	62
6.2D.4	Configured transmitted power for UL MIMO.....	62
6.3	Output power dynamics.....	62
6.3.1	Minimum output power.....	62
6.3.2	Transmit OFF power.....	63
6.3.3	Transmit ON/OFF time mask.....	63

6.3.3.1	General .....	63
6.3.3.2	General ON/OFF time mask .....	64
6.3.3.3	Transmit power time mask for slot and short or long subslot boundaries.....	64
6.3.3.4	PRACH time mask.....	64
6.3.3.5	Void.....	65
6.3.3.6	SRS time mask.....	65
6.3.3.7	PUSCH-PUCCH and PUSCH-SRS time masks .....	67
6.3.3.8	Transmit power time mask for consecutive slot or long subslot transmission and short subslot transmission boundaries .....	68
6.3.3.9	Transmit power time mask for consecutive short subslot transmissions boundaries .....	68
6.3.4	Power control.....	69
6.3.4.1	General .....	69
6.3.4.2	Absolute power tolerance.....	69
6.3.4.3	Relative power tolerance.....	69
6.3.4.4	Aggregate power tolerance.....	70
6.3A	Output power dynamics for CA .....	70
6.3A.1	Minimum output power for CA .....	70
6.3A.1.1	Void.....	70
6.3A.1.2	Void.....	70
6.3A.1.3	Minimum output power for inter-band CA .....	70
6.3A.2	Transmit OFF power for CA.....	71
6.3A.2.1	Void.....	71
6.3A.2.2	Void.....	71
6.3A.2.3	Transmit OFF power for inter-band CA.....	71
6.3A.3	Transmit ON/OFF time mask for CA .....	71
6.3A.3.1	Void.....	71
6.3A.3.2	Void.....	71
6.3A.3.3	Transmit ON/OFF time mask for inter-band CA .....	71
6.3A.4	Power control for CA.....	71
6.3A.4.1	Void.....	71
6.3A.4.2	Void.....	71
6.3A.4.3	Power control for inter-band CA.....	71
6.3D	Output power dynamics for UL MIMO .....	71
6.3D.1	Minimum output power for UL MIMO .....	71
6.3D.2	Transmit OFF power for UL MIMO.....	71
6.3D.3	Transmit ON/OFF time mask for UL MIMO .....	72
6.3D.4	Power control for UL MIMO.....	72
6.4	Transmit signal quality .....	72
6.4.1	Frequency error.....	72
6.4.2	Transmit modulation quality.....	72
6.4.2.1	Error Vector Magnitude .....	72
6.4.2.2	Carrier leakage .....	73
6.4.2.3	In-band emissions .....	73
6.4.2.4	EVM equalizer spectrum flatness .....	74
6.4.2.4.1	Requirements for Pi/2 BPSK modulation.....	75
6.4A	Transmit signal quality for CA.....	76
6.4A.1	Frequency error for CA.....	76
6.4A.1.1	Void.....	76
6.4A.1.2	Void.....	76
6.4A.1.3	Frequency error for inter-band CA.....	76
6.4A.2	Transmit modulation quality for CA.....	77
6.4A.2.1	Void.....	77
6.4A.2.2	Void.....	77
6.4A.2.3	Transmit modulation quality for inter-band CA.....	77
6.4D	Transmit signal quality for UL MIMO.....	77
6.4D.1	Frequency error for UL MIMO.....	77
6.4D.2	Transmit modulation quality for UL MIMO.....	77
6.4D.2.1	Error Vector Magnitude .....	77
6.4D.2.2	Carrier leakage .....	77
6.4D.2.3	In-band emissions .....	78
6.4D.2.4	EVM equalizer spectrum flatness for UL MIMO .....	78
6.4D.3	Time alignment error for UL MIMO .....	78

6.4D.4	Requirements for coherent UL MIMO .....	78
6.5	Output RF spectrum emissions.....	79
6.5.1	Occupied bandwidth .....	79
6.5.2	Out of band emission .....	79
6.5.2.1	General .....	79
6.5.2.2	Spectrum emission mask .....	79
6.5.2.3	Additional spectrum emission mask .....	80
6.5.2.3.1	Requirements for network signalling value "NS_35" .....	80
6.5.2.3.2	Requirements for network signalling value "NS_04" .....	81
6.5.2.3.3	Requirements for network signalling value "NS_03" .....	81
6.5.2.3.4	Requirements for network signalling value "NS_06" .....	82
6.5.2.3.5	Void .....	83
6.5.2.3.6	Void .....	83
6.5.2.3.7	Void .....	83
6.5.2.4	Adjacent channel leakage ratio .....	83
6.5.2.4.1	NR ACLR .....	83
6.5.2.4.2	UTRA ACLR .....	83
6.5.3	Spurious emissions .....	84
6.5.3.1	General spurious emissions .....	84
6.5.3.2	Spurious emissions for UE co-existence .....	85
6.5.3.3	Additional spurious emissions .....	90
6.5.3.3.1	Requirement for network signalling value "NS_04" .....	90
6.5.3.3.2	Requirement for network signalling value "NS_17" .....	90
6.5.3.3.3	Requirement for network signalling value "NS_18" .....	90
6.5.3.3.4	Requirement for network signalling value "NS_05" .....	90
6.5.3.3.5	Requirement for network signalling value "NS_43" .....	91
6.5.3.3.6	Requirement for network signalling value "NS_37" .....	91
6.5.3.3.7	Requirement for network signalling value "NS_38" .....	91
6.5.3.3.8	Requirement for network signalling value "NS_39" .....	91
6.5.3.3.9	Requirement for network signalling value "NS_40" .....	92
6.5.3.3.10	Requirement for network signalling value "NS_41" .....	92
6.5.3.3.11	Requirement for network signalling value "NS_42" .....	92
6.5.3.3.12	Void .....	93
6.5.3.3.13	Void .....	93
6.5.3.3.14	Void .....	93
6.5.3.3.15	Void .....	93
6.5.3.3.16	Requirement for network signalling value "NS_50" .....	93
6.5.4	Transmit intermodulation .....	93
6.5A	Output RF spectrum emissions for CA.....	93
6.5A.1	Occupied bandwidth for CA .....	94
6.5A.1.1	Void .....	94
6.5A.1.2	Void .....	94
6.5A.1.3	Occupied bandwidth for Inter-band CA .....	94
6.5A.2	Out of band emission for CA .....	94
6.5A.2.1	General .....	94
6.5A.2.2	Spectrum emission mask .....	94
6.5A.2.2.1	Void .....	94
6.5A.2.2.2	Void .....	94
6.5A.2.2.3	Spectrum emission mask for Inter-band CA .....	94
6.5A.2.3	Additional spectrum emission mask .....	95
6.5A.2.3.1	Void .....	95
6.5A.2.3.2	Void .....	95
6.5A.2.3.3	Additional spectrum emission mask for Inter-band CA .....	95
6.5A.2.4	Adjacent channel leakage ratio .....	95
6.5A.2.4.1	NR ACLR .....	95
6.5A.2.4.1.1	Void .....	95
6.5A.2.4.1.2	Void .....	95
6.5A.2.4.1.3	NR ACLR for Inter-band CA .....	95
6.5A.2.4.2	UTRA ACLR .....	95
6.5A.2.4.2.1	Void .....	95
6.5A.2.4.2.2	Void .....	95
6.5A.2.4.2.3	UTRA ACLR for Inter-band CA .....	95

6.5A.3	Spurious emission for CA.....	95
6.5A.3.1	General spurious emissions.....	95
6.5A.3.2	Spurious emissions for UE co-existence.....	96
6.5A.3.2.1	Void.....	96
6.5A.3.2.2	Void.....	96
6.5A.3.2.3	Spurious emissions for UE co-existence for Inter-band CA.....	96
6.5A.4	Transmit intermodulation for CA.....	97
6.5A.4.1	Void.....	97
6.5A.4.2	Void.....	97
6.5A.4.3	Transmit intermodulation for Inter-band CA.....	97
6.5D	Output RF spectrum emissions for UL MIMO.....	97
6.5D.1	Occupied bandwidth for UL MIMO.....	97
6.5D.2	Out of band emission for UL MIMO.....	97
6.5D.3	Spurious emission for UL MIMO.....	97
6.5D.4	Transmit intermodulation for UL MIMO.....	97
7	Receiver characteristics.....	98
7.1	General.....	98
7.2	Diversity characteristics.....	98
7.3	Reference sensitivity.....	98
7.3.1	General.....	98
7.3.2	Reference sensitivity power level.....	98
7.3.3	$\Delta R_{IB,c}$ .....	104
7.3A	Reference sensitivity for CA.....	104
7.3A.1	General.....	104
7.3A.2	Reference sensitivity power level for CA.....	104
7.3A.2.1	Reference sensitivity power level for Intra-band contiguous CA.....	104
7.3A.2.2	Void.....	104
7.3A.2.3	Reference sensitivity power level for Inter-band CA.....	104
7.3A.2.4	Reference sensitivity power level for SDL bands.....	105
7.3A.3	$\Delta R_{IB,c}$ for CA.....	107
7.3A.3.1	General.....	107
7.3A.3.2	$\Delta R_{IB,c}$ for Inter-band CA.....	107
7.3A.3.2.1	$\Delta R_{IB,c}$ for two bands.....	107
7.3A.3.2.2	Void.....	107
7.3A.4	Reference sensitivity exceptions due to UL harmonic interference for CA.....	107
7.3A.5	Reference sensitivity exceptions due to intermodulation interference due to 2UL CA.....	110
7.3A.6	Reference sensitivity exceptions due to cross band isolation for CA.....	110
7.3B	Void.....	111
7.3C	Reference sensitivity for SUL.....	111
7.3C.1	General.....	111
7.3C.2	Reference sensitivity power level for SUL.....	111
7.3C.3	$\Delta R_{IB,c}$ for SUL.....	113
7.3C.3.1	General.....	113
7.3C.3.2	SUL band combination.....	113
7.3C.3.2.1	$\Delta R_{IB,c}$ for two bands.....	113
7.3D	Reference sensitivity for UL MIMO.....	113
7.4	Maximum input level.....	113
7.4A	Maximum input level for CA.....	114
7.4A.1	Maximum input level for Intra-band contiguous CA.....	114
7.4A.2	Void.....	114
7.4A.3	Maximum input level for Inter-band CA.....	114
7.4D	Maximum input level for UL MIMO.....	115
7.5A	Adjacent channel selectivity for CA.....	119
7.5A.1	Adjacent channel selectivity for Intra-band contiguous CA.....	119
7.5A.2	Void.....	121
7.5A.3	Adjacent channel selectivity Inter-band CA.....	121
7.5D	Adjacent channel selectivity for UL MIMO.....	121
7.6	Blocking characteristics.....	121
7.6.1	General.....	121
7.6.2	In-band blocking.....	121
7.6.3	Out-of-band blocking.....	123



7.6.4	Narrow band blocking .....	126
7.6A	Blocking characteristics for CA .....	127
7.6A.1	General.....	127
7.6A.2	In-band blocking for CA.....	127
7.6A.2.1	In-band blocking for Intra-band contiguous CA .....	127
7.6A.2.2	Void.....	128
7.6A.2.3	In-band blocking for Inter-band CA.....	128
7.6A.3	Out-of-band blocking for CA.....	128
7.6A.3.1	Out-of-band blocking for Intra-band contiguous CA .....	128
7.6A.3.2	Void.....	129
7.6A.3.3	Out-of-band blocking for Inter-band CA .....	129
7.6A.4	Narrow band blocking for CA .....	130
7.6A.4.1	Narrow band blocking for Intra-band contiguous CA.....	130
7.6A.4.2	Void.....	131
7.6A.4.3	Narrow band blocking for Inter-band CA .....	131
7.6C	Blocking characteristics for SUL .....	131
7.6C.1	General.....	131
7.6C.2	In-band blocking for SUL.....	131
7.6C.3	Out-of-band blocking for SUL.....	131
7.6C.4	Narrow band blocking for SUL .....	132
7.6D	Blocking characteristics for UL MIMO .....	132
7.7	Spurious response.....	132
7.7A	Spurious response for CA.....	134
7.7A.1	Spurious response for Intra-band contiguous CA .....	134
7.7A.2	Void .....	134
7.7A.3	Spurious response for Inter-band CA.....	134
7.7D	Spurious response for UL MIMO.....	134
7.8	Intermodulation characteristics .....	134
7.8.1	General.....	134
7.8.2	Wide band Intermodulation .....	135
7.8A	Intermodulation characteristics for CA .....	137
7.8A.1	General.....	137
7.8A.2	Wide band intermodulation for CA .....	137
7.8A.2.1	Wide band intermodulation for Intra-band contiguous CA .....	137
7.8A.2.2	Void.....	138
7.8A.2.3	Wide band intermodulation for Inter-band CA .....	138
7.8D	Intermodulation characteristics for UL MIMO .....	138
7.9	Spurious emissions .....	138
7.9A	Spurious emissions for CA.....	139
7.9A.1	Void .....	139
7.9A.2	Void .....	139
7.9A.3	Spurious emissions for Inter-band CA.....	139
<b>Annex A (normative): Measurement channels.....</b>		<b>140</b>
A.1	General .....	140
A.2	UL reference measurement channels .....	140
A.2.1	General .....	140
A.2.2	Reference measurement channels for FDD .....	141
A.2.2.1	DFT-s-OFDM Pi/2-BPSK .....	141
A.2.2.2	DFT-s-OFDM QPSK.....	144
A.2.2.3	DFT-s-OFDM 16QAM.....	147
A.2.2.4	DFT-s-OFDM 64QAM.....	150
A.2.2.5	DFT-s-OFDM 256QAM.....	153
A.2.2.6	CP-OFDM QPSK .....	156
A.2.2.7	CP-OFDM 16QAM .....	159
A.2.2.8	CP-OFDM 64QAM .....	162
A.2.2.9	CP-OFDM 256QAM .....	165
A.2.3	Reference measurement channels for TDD.....	168
A.2.3.1	DFT-s-OFDM Pi/2-BPSK .....	168
A.2.3.2	DFT-s-OFDM QPSK.....	171
A.2.3.3	DFT-s-OFDM 16QAM.....	174

A.2.3.4	DFT-s-OFDM 64QAM.....	177
A.2.3.5	DFT-s-OFDM 256QAM.....	180
A.2.3.6	CP-OFDM QPSK .....	183
A.2.3.7	CP-OFDM 16QAM .....	186
A.2.3.8	CP-OFDM 64QAM .....	189
A.2.3.9	CP-OFDM 256QAM .....	192
A.3	DL reference measurement channels .....	195
A.3.1	General .....	195
A.3.2	DL reference measurement channels for FDD .....	196
A.3.2.1	General.....	196
A.3.2.2	FRC for receiver requirements for QPSK.....	196
A.3.2.3	FRC for maximum input level for 64QAM .....	199
A.3.2.4	FRC for maximum input level for 256 QAM .....	202
A.3.3	DL reference measurement channels for TDD.....	205
A.3.3.1	General.....	205
A.3.3.2	FRC for receiver requirements for QPSK.....	206
A.3.3.3	FRC for maximum input level for 64QAM .....	209
A.3.3.4	FRC for maximum input level for 256 QAM .....	212
A.4	CSI reference measurement channels.....	215
A.5	OFDMA Channel Noise Generator (OCNG) .....	215
A.5.1	OCNG Patterns for FDD .....	215
A.5.1.1	OCNG FDD pattern 1: Generic OCNG FDD Pattern for all unused RES.....	215
A.5.2	OCNG Patterns for TDD .....	215
A.5.2.1	OCNG TDD pattern 1: Generic OCNG TDD Pattern for all unused RES .....	215
A.6	Void.....	216
<b>Annex B (informative):</b>	<b>Void .....</b>	<b>217</b>
<b>Annex C (informative):</b>	<b>Downlink physical channels.....</b>	<b>218</b>
C.1	General .....	218
C.2	Setup.....	218
C.3	Connection .....	218
C.3.1	Measurement of Receiver Characteristics .....	218
<b>Annex D (normative):</b>	<b>Characteristics of the interfering signal .....</b>	<b>220</b>
D.1	General .....	220
D.2	Interference signals.....	220
<b>Annex E (normative):</b>	<b>Environmental conditions .....</b>	<b>222</b>
E.1	General .....	222
E.2	Environmental .....	222
E.2.1	Temperature .....	222
E.2.2	Voltage .....	222
E.2.3	Vibration.....	223
<b>Annex F (normative):</b>	<b>Transmit modulation.....</b>	<b>224</b>
F.0	General .....	224
F.1	Measurement Point.....	224
F.2	Basic Error Vector Magnitude measurement .....	224
F.3	Basic in-band emissions measurement.....	225
F.4	Modified signal under test.....	225
F.5	Window length.....	227

F.5.1 Timing offset .....227

F.5.2 Window length .....227

F.5.3 Window length for normal CP .....227

F.5.4 Window length for Extended CP .....229

F.5.5 Window length for PRACH .....229

F.6 Averaged EVM .....230

F.7 Spectrum Flatness .....231

**Annex G (informative): Void .....232**

**Annex H (informative): Void .....232**

**Annex I (informative): Void .....232**

**Annex J (informative): Void .....232**

**Annex K (informative): Void .....232**

**Annex L (informative): Change history .....233**

History .....244

**iTeh STANDARD PREVIEW**  
 (standards.iteh.ai)  
 Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/3631b429-32a5-4888-9000-450a49db4200/etsi-ts-138-101-1-v15.9.0-2020-04>

---

# Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)  
Full standard:  
<https://standards.iteh.ai/catalog/standards/sist/3631b429-32a5-4888-9000-450a49db4200/etsi-ts-138-101-1-v15.9.0-2020-04>

---

# 1 Scope

The present document establishes the minimum RF requirements for NR User Equipment (UE) operating on frequency Range 1.

---

## 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.

For a specific reference, subsequent revisions do not apply.

For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document in the same Release as the present document.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 38.101-2: "NR; User Equipment (UE) radio transmission and reception; Part 2: Range 2 Standalone".
- [3] 3GPP TS 38.101-3: "NR; User Equipment (UE) radio transmission and reception; Part 3: Range 1 and Range 2 Interworking operation with other radios".
- [4] 3GPP TS 38.521-1: "NR; User Equipment (UE) conformance specification; Radio transmission and reception; Part 1: Range 1 Standalone".
- [5] Recommendation ITU-R M.1545: "Measurement uncertainty as it applies to test limits for the terrestrial component of International Mobile Telecommunications-2000".
- [6] 3GPP TS 38.211: "NR; Physical channels and modulation".
- [7] 3GPP TS 38.331: "Radio Resource Control (RRC) protocol specification".
- [8] 3GPP TS 38.213: "NR; Physical layer procedures for control".
- [9] ITU-R Recommendation SM.329-10, "Unwanted emissions in the spurious domain".
- [10] 3GPP TS 38.214: "NR; Physical layer procedures for data".

---

## 3 Definitions, symbols and abbreviations

### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

**Aggregated Channel Bandwidth:** The RF bandwidth in which a UE transmits and receives multiple contiguously aggregated carriers.

**Carrier aggregation:** Aggregation of two or more component carriers in order to support wider transmission bandwidths.

**Carrier aggregation band:** A set of one or more operating bands across which multiple carriers are aggregated with a specific set of technical requirements.