

ETSI TS 138 141-1 V15.5.0 (2020-04)



**5G;
NR;**

Base Station (BS) conformance testing Part 1: Conducted conformance testing

(3GPP TS 38.141-1 version 15.5.0 Release 15)

5G; NR; conformance testing Part conformance testing 8.141-1 version 15.5.0 Re



Reference

RTS/TSGR-0438141-1vf50

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and

of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and
of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	12
1 Scope	13
2 References	13
3 Definitions, symbols and abbreviations	15
3.1 Definitions	15
3.2 Symbols	17
3.3 Abbreviations	18
4 General conducted test conditions and declarations.....	20
4.1 Measurement uncertainties and test requirements	20
4.1.1 General.....	20
4.1.2 Acceptable uncertainty of Test System.....	20
4.1.2.1 General	20
4.1.2.2 Measurement of transmitter	21
4.1.2.3 Measurement of receiver	22
4.1.2.4 Measurement of performance requirements	25
4.1.3 Interpretation of measurement results.....	25
4.2 Conducted requirement reference points	25
4.2.1 BS type 1-C	25
4.2.2 BS type 1-H	26
4.3 Base station classes	27
4.4 Regional requirements.....	27
4.5 BS configurations	28
4.5.1 BS type 1-C	28
4.5.1.1 Transmit configurations	28
4.5.1.1.1 General	28
4.5.1.1.2 Transmission with multiple transmitter antenna connectors	28
4.5.1.2 Receive configurations	29
4.5.1.2.1 General	29
4.5.1.2.2 Reception with multiple receiver antenna connectors, receiver diversity	29
4.5.1.3 Duplexers	29
4.5.1.4 Power supply options	30
4.5.1.5 Ancillary RF amplifiers	30
4.5.2 BS type 1-H	31
4.5.2.1 Transmit configurations	31
4.5.2.2 Receive configurations	31
4.5.2.3 Power supply options	32
4.5.3 BS with integrated Iuau BS modem	32
4.6 Manufacturer declarations	32
4.7 Test configurations	36
4.7.1 General.....	36
4.7.2 Test signal used to build Test Configurations	36
4.7.3 NRTC1: Contiguous spectrum operation	36
4.7.3.1 NRTC1 generation	36
4.7.3.2 NRTC1 power allocation	36
4.7.4 NRTC2: Contiguous CA occupied bandwidth	36
4.7.4.1 NRTC2 generation	37
4.7.4.2 NRTC2 power allocation	37
4.7.5 NRTC3: Non-contiguous spectrum operation	37
4.7.5.1 NRTC3 generation	37
4.7.5.2 NRTC3 power allocation	38
4.7.6 NRTC4: Multi-band test configuration for full carrier allocation	38

4.7.6.1	NRTC4 generation	38
4.7.6.2	NRTC4 power allocation	38
4.7.7	NRTC5: Multi-band test configuration with high PSD per carrier	38
4.7.7.1	NRTC5 generation	39
4.7.7.2	NRTC5 power allocation	39
4.8	Applicability of requirements	39
4.8.1	General	39
4.8.2	Requirement set applicability	39
4.8.3	Applicability of test configurations for single-band operation	40
4.8.4	Applicability of test configurations for multi-band operation	41
4.9	RF channels and test models	42
4.9.1	RF channels	42
4.9.2	Test models	43
4.9.2.1	General	43
4.9.2.2	FR1 test models	43
4.9.2.2.1	FR1 test model 1.1 (NR-FR1-TM1.1)	45
4.9.2.2.2	FR1 test model 1.2 (NR-FR1-TM1.2)	45
4.9.2.2.3	FR1 test model 2 (NR-FR1-TM2)	46
4.9.2.2.4	FR1 test model 2a (NR-FR1-TM2a)	46
4.9.2.2.5	FR1 test model 3.1 (NR-FR1-TM3.1)	47
4.9.2.2.6	FR1 test model 3.1a (NR-FR1-TM3.1a)	47
4.9.2.2.7	FR1 test model 3.2 (NR-FR1-TM3.2)	47
4.9.2.2.8	FR1 test model 3.3 (NR-FR1-TM3.3)	48
4.9.2.3	Data content of Physical channels and Signals for NR-FR1-TM	49
4.9.2.3.1	PDCCH	49
4.9.2.3.2	PDSCH	49
4.10	Requirements for contiguous and non-contiguous spectrum	50
4.11	Requirements for BS capable of multi-band operation	51
4.12	Format and interpretation of tests	52
5	Operating bands and channel arrangement	53
6	Conducted transmitter characteristics	54
6.1	General	54
6.1.1	BS type 1-C	54
6.1.2	BS type 1-H	54
6.2	Base station output power	54
6.2.1	Definition and applicability	54
6.2.2	Minimum requirement	55
6.2.3	Test purpose	55
6.2.4	Method of test	55
6.2.4.1	Initial conditions	55
6.2.4.2	Procedure	55
6.2.5	Test requirement	56
6.3	Output power dynamics	56
6.3.1	General	56
6.3.2	RE power control dynamic range	56
6.3.2.1	Definition and applicability	56
6.3.2.2	Minimum requirement	56
6.3.2.3	Test purpose	56
6.3.3	Total power dynamic range	57
6.3.3.1	Definition and applicability	57
6.3.3.2	Minimum requirement	57
6.3.3.3	Test purpose	57
6.3.3.4	Method of test	57
6.3.3.4.1	Initial conditions	57
6.3.3.4.2	Procedure	57
6.3.3.5	Test requirements	58
6.4	Transmit ON/OFF power	58
6.4.1	Transmitter OFF power	58
6.4.1.1	Definition and applicability	58
6.4.1.2	Minimum requirement	58

6.4.1.3	Test purpose	59
6.4.1.4	Method of test	59
6.4.1.5	Test requirements	59
6.4.2	Transmitter transient period	59
6.4.2.1	Definition and applicability	59
6.4.2.2	Minimum requirement	59
6.4.2.3	Test purpose	59
6.4.2.4	Method of test	60
6.4.2.4.1	Initial conditions	60
6.4.2.4.2	Procedure	60
6.4.2.5	Test requirements	60
6.5	Transmitted signal quality	61
6.5.1	General	61
6.5.2	Frequency error	61
6.5.2.1	Definition and applicability	61
6.5.2.2	Minimum Requirement	61
6.5.2.3	Test purpose	61
6.5.2.4	Method of test	61
6.5.2.5	Test Requirements	61
6.5.3	Modulation quality	61
6.5.3.1	Definition and applicability	61
6.5.3.2	Minimum Requirement	62
6.5.3.3	Test purpose	62
6.5.3.4	Method of test	62
6.5.3.4.1	Initial conditions	62
6.5.3.4.2	Procedure	62
6.5.3.5	Test requirements	63
6.5.4	Time alignment error	64
6.5.4.1	Definition and applicability	64
6.5.4.2	Minimum requirement	64
6.5.4.3	Test purpose	65
6.5.4.4	Method of test	65
6.5.4.4.1	Initial conditions	65
6.5.4.4.2	Procedure	65
6.5.4.5	Test requirement	66
6.6	Unwanted emissions	66
6.6.1	General	66
6.6.2	Occupied bandwidth	66
6.6.2.1	Definition and applicability	66
6.6.2.2	Minimum Requirements	67
6.6.2.3	Test purpose	67
6.6.2.4	Method of test	67
6.6.2.4.1	Initial conditions	67
6.6.2.4.2	Procedure	67
6.6.2.5	Test requirements	68
6.6.3	Adjacent Channel Leakage Power Ratio (ACLR)	68
6.6.3.1	Definition and applicability	68
6.6.3.2	Minimum requirement	68
6.6.3.3	Test purpose	69
6.6.3.4	Method of test	69
6.6.3.4.1	Initial conditions	69
6.6.3.4.2	Procedure	69
6.6.3.5	Test requirements	70
6.6.3.5.1	General requirements	70
6.6.3.5.2	Limits and <i>basic limits</i>	70
6.6.3.5.3	<i>BS type I-C</i>	72
6.6.3.5.4	<i>BS type I-H</i>	73
6.6.4	Operating band unwanted emissions	73
6.6.4.1	Definition and applicability	73
6.6.4.2	Minimum requirement	74
6.6.4.3	Test purpose	75
6.6.4.4	Method of test	75

6.6.4.4.1	Initial conditions	75
6.6.4.4.2	Procedure	75
6.6.4.5	Test requirements	76
6.6.4.5.1	General requirements	76
6.6.4.5.2	Basic limits for Wide Area BS (Category A)	76
6.6.4.5.3	Basic limits for Wide Area BS (Category B)	77
6.6.4.5.3.1	Category B requirements (Option 1)	77
6.6.4.5.3.2	Category B requirements (Option 2)	78
6.6.4.5.4	Basic limits for Medium Range BS (Category A and B)	79
6.6.4.5.5	Basic limits for Local Area BS (Category A and B)	81
6.6.4.5.6	Basic limits for additional requirements	82
6.6.4.5.6.1	Limits in FCC Title 47	82
6.6.4.5.6.2	Protection of DTT	82
6.6.4.5.6.3	(void)	82
6.6.4.5.7	<i>BS type 1-C</i>	82
6.6.4.5.8	<i>BS type 1-H</i>	82
6.6.5	Transmitter spurious emissions	83
6.6.5.1	Definition and applicability	83
6.6.5.2	Minimum requirement	83
6.6.5.3	Test purpose	83
6.6.5.4	Method of test	83
6.6.5.4.1	Initial conditions	83
6.6.5.4.2	Procedure	84
6.6.5.5	Test requirements	85
6.6.5.5.1	Basic limits	85
6.6.5.5.1.1	Tx spurious emissions	85
6.6.5.5.1.2	Protection of the BS receiver of own or different BS	85
6.6.5.5.1.3	Additional spurious emissions requirements	86
6.6.5.5.1.4	Co-location with other base stations	93
6.6.5.5.2	(void)	98
6.6.5.5.3	<i>BS type 1-C</i>	98
6.6.5.5.4	<i>BS type 1-H</i>	98
6.7	Transmitter intermodulation	98
6.7.1	Definition and applicability	98
6.7.2	Minimum requirement	98
6.7.3	Test purpose	99
6.7.4	Method of test	99
6.7.4.1	Initial conditions	99
6.7.4.2	Procedure	99
6.7.5	Test requirements	100
6.7.5.1	<i>BS type 1-C</i>	100
6.7.5.1.1	Co-location minimum requirements	100
6.7.5.1.2	Additional requirements	101
6.7.5.2	<i>BS type 1-H</i>	101
6.7.5.2.1	Co-location minimum requirements	101
6.7.5.2.2	Intra-system minimum requirements	102
6.7.5.2.3	Additional requirements	102
7	Conducted receiver characteristics	103
7.1	General	103
7.2	Reference sensitivity level	103
7.2.1	Definition and applicability	103
7.2.2	Minimum requirement	103
7.2.3	Test purpose	103
7.2.4	Method of test	104
7.2.4.1	Initial conditions	104
7.2.4.2	Procedure	104
7.2.5	Test requirements	104
7.3	Dynamic range	106
7.3.1	Definition and applicability	106
7.3.2	Minimum requirement	106
7.3.3	Test purpose	106

7.3.4	Method of test	106
7.3.4.1	Initial conditions	106
7.3.4.2	Procedure	106
7.3.5	Test requirements.....	107
7.4	In-band selectivity and blocking	110
7.4.1	Adjacent Channel Selectivity (ACS)	110
7.4.1.1	Definition and applicability.....	110
7.4.1.2	Minimum requirement	110
7.4.1.3	Test purpose	111
7.4.1.4	Method of test	111
7.4.1.4.1	Initial conditions.....	111
7.4.1.4.2	Procedure	111
7.4.1.5	Test requirements	111
7.4.2	In-band blocking	112
7.4.2.1	Definition and applicability.....	112
7.4.2.2	Minimum requirement	112
7.4.2.3	Test purpose	113
7.4.2.4	Method of test	113
7.4.2.4.1	Initial conditions.....	113
7.4.2.4.2	Procedure for general blocking.....	113
7.4.2.4.3	Procedure for narrowband blocking	113
7.4.2.5	Test requirements	114
7.5	Out-of-band blocking	116
7.5.1	Definition and applicability	116
7.5.2	Minimum requirement	116
7.5.3	Test purpose.....	116
7.5.4	Method of test	117
7.5.4.1	Initial conditions	117
7.5.4.2	Procedure	117
7.5.5	Test requirements.....	117
7.5.5.1	General requirements	117
7.5.5.2	Co-location requirements	118
7.6	Receiver spurious emissions.....	119
7.6.1	Definition and applicability	119
7.6.2	Minimum requirement	119
7.6.3	Test purpose.....	119
7.6.4	Method of test	119
7.6.4.1	Initial conditions	119
7.6.4.2	Procedure	119
7.6.5	Test requirements.....	120
7.6.5.1	Basic limits.....	120
7.6.5.2	BS type 1-C	120
7.6.5.3	BS type 1-H.....	121
7.7	Receiver intermodulation	121
7.7.1	Definition and applicability	121
7.7.2	Minimum requirement	121
7.7.3	Test purpose.....	121
7.7.4	Method of test	121
7.7.4.1	Initial conditions	121
7.7.4.2	Procedure	122
7.7.5	Test requirements.....	122
7.8	In-channel selectivity	126
7.8.1	Definition and applicability	126
7.8.2	Minimum requirement	126
7.8.3	Test purpose.....	126
7.8.4	Method of test	126
7.8.4.1	Initial conditions	126
7.8.4.2	Procedure	126
7.8.5	Test requirements.....	126
8	Conducted performance characteristics.....	130
8.1	General	130

8.1.1	Scope and definitions.....	130
8.1.2	Applicability rule	130
8.1.2.0	General	130
8.1.2.1	Applicability of PUSCH performance requirements.....	130
8.1.2.1.1	Applicability of requirements for different subcarrier spacings	130
8.1.2.1.2	Applicability of requirements for different channel bandwidths	130
8.1.2.1.3	Applicability of requirements for different configurations.....	131
8.1.2.2	Applicability of PUCCH performance requirements	131
8.1.2.2.1	Applicability of requirements for different formats.....	131
8.1.2.2.2	Applicability of requirements for different subcarrier spacings	131
8.1.2.2.3	Applicability of requirements for different channel bandwidths	131
8.1.2.2.4	Applicability of requirements for different configurations.....	131
8.1.2.2.5	Applicability of requirements for multi-slot PUCCH.....	132
8.1.2.3	Applicability of PRACH performance requirements	132
8.1.2.3.1	Applicability of requirements for different formats.....	132
8.1.2.3.2	Applicability of requirements for different subcarrier spacings	132
8.1.2.3.3	Applicability of requirements for different channel bandwidths	132
8.2	Performance requirements for PUSCH	132
8.2.1	Performance requirements for PUSCH with transform precoding disabled	132
8.2.1.1	Definition and applicability.....	132
8.2.1.2	Minimum Requirement	132
8.2.1.3	Test Purpose	132
8.2.1.4	Method of test	132
8.2.1.4.1	Initial Conditions	132
8.2.1.4.2	Procedure	133
8.2.1.5	Test Requirement	133
8.2.2	Performance requirements for PUSCH with transform precoding enabled	140
8.2.2.1	Definition and applicability.....	140
8.2.2.2	Minimum Requirement	140
8.2.2.3	Test Purpose	141
8.2.2.4	Method of test	141
8.2.2.4.1	Initial Conditions	141
8.2.2.4.2	Procedure	141
8.2.2.5	Test Requirement	142
8.2.3	Performance requirements for UCI multiplexed on PUSCH	143
8.2.3.1	Definition and applicability.....	143
8.2.3.2	Minimum Requirements	143
8.2.3.3	Test purpose	143
8.2.3.4	Method of test	143
8.2.3.4.1	Initial conditions	143
8.2.3.4.2	Procedure	144
8.2.3.5	Test Requirement	145
8.3	Performance requirements for PUCCH	146
8.3.1	Performance requirements for PUCCH format 0.....	146
8.3.1.1	Definition and applicability.....	146
8.3.1.2	Minimum Requirement	146
8.3.1.3	Test purpose	146
8.3.1.4	Method of test	146
8.3.1.4.1	Initial conditions	146
8.3.1.4.2	Procedure	147
8.3.1.5	Test Requirement	147
8.3.2	Performance requirements for PUCCH format 1	148
8.3.2.1	NACK to ACK detection	148
8.3.2.1.1	Definition and applicability	148
8.3.2.1.2	Minimum Requirement	148
8.3.2.1.3	Test purpose	148
8.3.2.1.4	Method of test	149
8.3.2.1.4.1	Initial Conditions	149
8.3.2.1.4.2	Procedure	149
8.3.2.1.5	Test Requirement.....	149
8.3.2.2	ACK missed detection.....	150
8.3.2.2.1	Definition and applicability	150

8.3.2.2.2	Minimum Requirement	150
8.3.2.2.3	Test purpose	150
8.3.2.2.4	Method of test.....	151
8.3.2.2.4.1	Initial Conditions	151
8.3.2.2.4.2	Procedure	151
8.3.2.2.5	Test Requirement.....	152
8.3.3	Performance requirements for PUCCH format 2.....	152
8.3.3.1	ACK missed detection.....	152
8.3.3.1.1	Definition and applicability.....	152
8.3.3.1.2	Minimum requirements	152
8.3.3.1.3	Test purpose	153
8.3.3.1.4	Method of test.....	153
8.3.3.1.4.1	Initial Condition	153
8.3.3.1.4.2	Procedure	153
8.3.3.1.5	Test requirements	154
8.3.3.2	UCI BLER performance requirements.....	154
8.3.3.2.1	Definition and applicability.....	154
8.3.3.2.2	Minimum Requirement	154
8.3.3.2.3	Test purpose	154
8.3.3.2.4	Method of test.....	154
8.3.3.2.4.1	Initial Condition	154
8.3.3.2.4.2	Procedure	154
8.3.3.2.5	Test requirements	155
8.3.4	Performance requirements for PUCCH format 3.....	156
8.3.4.1	Definition and applicability.....	156
8.3.4.2	Minimum requirement	156
8.3.4.3	Test purpose	156
8.3.4.4	Method of test	156
8.3.4.4.1	Initial conditions	156
8.3.4.4.2	Procedure	156
8.3.4.5	Test requirement	157
8.3.5	Performance requirements for PUCCH format 4.....	159
8.3.5.1	Definition and applicability.....	159
8.3.5.2	Minimum requirement	159
8.3.5.3	Test purpose	159
8.3.5.4	Method of test	159
8.3.5.4.1	Initial conditions	159
8.3.5.4.2	Procedure	159
8.3.5.5	Test requirement	160
8.3.6	Performance requirements for multi-slot PUCCH.....	161
8.3.6.1	Performance requirements for multi-slot PUCCH format 1.....	161
8.3.6.1.1	NACK to ACK detection.....	161
8.3.6.1.1.1	Definition and applicability	161
8.3.6.1.1.2	Minimum Requirement	161
8.3.6.1.1.3	Test purpose	161
8.3.6.1.1.4	Method of test	161
8.3.6.1.1.4.1	Initial conditions	161
8.3.6.1.1.4.2	Procedure	161
8.3.6.1.1.5	Test Requirement	162
8.3.6.1.2	ACK missed detection.....	163
8.3.6.1.2.1	Definition and applicability	163
8.3.6.1.2.2	Minimum Requirement	163
8.3.6.1.2.3	Test purpose	163
8.3.6.1.2.4	Method of test	163
8.3.6.1.2.4.1	Initial conditions	163
8.3.6.1.2.4.2	Procedure	163
8.3.6.1.2.5	Test Requirement	164
8.4	Performance requirements for PRACH	164
8.4.1	PRACH false alarm probability and missed detection.....	164
8.4.1.1	Definition and applicability.....	164
8.4.1.2	Minimum requirement	165
8.4.1.3	Test purpose	165

8.4.1.4	Method of test	165
8.4.1.4.1	Initial conditions	165
8.4.1.4.2	Procedure	165
8.4.1.5	Test requirement	166

Annex A (normative): Reference measurement channels168

A.1	Fixed Reference Channels for reference sensitivity level, ACS, in-band blocking, out-of-band blocking, receiver intermodulation and in-channel selectivity (QPSK, R=1/3).....	168
A.2	Fixed Reference Channels for dynamic range (16QAM, R=2/3).....	168
A.3	Fixed Reference Channels for performance requirements (QPSK, R=193/1024)	169
A.4	Fixed Reference Channels for performance requirements (16QAM, R=658/1024)	171
A.5	Fixed Reference Channels for performance requirements (64QAM, R=567/1024)	172
A.6	PRACH test preambles.....	173

Annex B (normative): Environmental requirements for the BS equipment174

B.1	General	174
B.2	Normal test environment.....	174
B.3	Extreme test environment.....	174
B.3.1	Extreme temperature	174
B.4	Vibration.....	175
B.5	Power supply	175
B.6	Measurement of test environments.....	175

Annex C (informative): Test tolerances and derivation of test requirements.....176

C.1	Measurement of transmitter.....	176
C.2	Measurement of receiver.....	178
C.3	Measurement of performance requirements.....	178

Annex D (informative): Measurement system set-up179

D.1	BS type 1-C transmitter.....	179
D.1.1	Base station output power, output power dynamics, transmitter ON/OFF power, frequency error, EVM, unwanted emissions for BS type 1-C	179
D.1.2	Transmitter intermodulation for BS type 1-C.....	179
D.1.3	Time alignment error for BS type 1-C	180
D.2	BS type 1-C receiver	180
D.2.1	Reference sensitivity level for BS type 1-C	180
D.2.2	Dynamic range for BS type 1-C	181
D.2.3	In-channel selectivity for BS type 1-C	181
D.2.4	Adjacent Channel Selectivity (ACS) and narrowband blocking for BS type 1-C	182
D.2.5	Blocking characteristics for BS type 1-C	182
D.2.6	Receiver spurious emission for BS type 1-C.....	183
D.2.7	Intermodulation characteristics for BS type 1-C	183
D.3	BS type 1-H transmitter	184
D.3.1	Base station output power, output power dynamics, transmitter ON/OFF power, frequency error, EVM, unwanted emissions for BS type 1-H	184
D.3.2	Transmitter intermodulation for BS type 1-H	185
D.3.3	Transmitter spurious emissions for BS type 1-H.....	185
D.3.4	Time alignment error for BS type 1-H	187
D.4	BS type 1-H receiver	187
D.4.1	Reference sensitivity level for BS type 1-H	187

D.4.2	Receiver dynamic range for BS type 1-H.....	188
D.4.3	Receiver adjacent channel selectivity and narrowband blocking for BS type 1-H.....	188
D.4.4	Receiver spurious emissions.....	188
D.4.5	Receiver In-channel selectivity for BS type 1-H.....	190
D.4.6	Receiver intermodulation for BS type 1-H.....	191
D.5	<i>BS type 1-C</i> performance requirements	191
D.5.1	Performance requirements for PUSCH, single user PUCCH, PRACH on single antenna port in multipath fading conditions	191
D.5.2	Performance requirements for PUSCH transmission on two antenna ports in multipath fading conditions ..	192
D.5.3	Performance requirements for PRACH in static conditions	192
D.6	BS type 1-H performance requirements	193
D.6.1	Performance requirements for PUSCH, single user PUCCH, PRACH on single antenna port in multipath fading conditions	193
D.6.2	Performance requirements for PUSCH transmission on two antenna ports in multipath fading conditions ..	194
D.6.3	Performance requirements for PRACH in static conditions	194
Annex E (normative):	Characteristics of interfering signals	195
Annex F (normative):	Void	196
Annex G (normative):	Propagation conditions.....	197
G.1	Static propagation condition.....	197
G.2	Multi-path fading propagation conditions	197
G.2.1	Delay profiles	197
G.2.1.1	Delay profiles for FR1	198
G.2.2	Combinations of channel model parameters	199
G.2.3	MIMO channel correlation matrices.....	200
G.2.3.1	MIMO correlation matrices using Uniform Linear Array.....	200
G.2.3.1.1	Definition of MIMO correlation matrices	200
G.2.3.1.2	MIMO correlation matrices at high, medium and low level	201
G.2.3.2	Multi-antenna channel models using cross polarized antennas.....	203
G.2.3.2.1	Definition of MIMO correlation matrices using cross polarized antennas	204
G.2.3.2.2	Spatial correlation matrices at UE and gNB sides.....	204
G.2.3.2.2.1	Spatial correlation matrices at UE side.....	204
G.2.3.2.2.2	Spatial correlation matrices at gNB side	204
G.2.3.2.3	MIMO correlation matrices using cross polarized antennas	205
Annex H (normative):	In-channel TX tests.....	206
H.1	General	206
H.2	Basic principles	206
H.2.1	Output signal of the TX under test	206
H.2.2	Ideal signal	206
H.2.3	Measurement results.....	207
H.2.4	Measurement points	207
H.3	Pre-FFT minimization process	208
H.4	Timing of the FFT window	208
H.5	Resource element TX power	209
H.6	Post-FFT equalisation.....	210
H.7	EVM	211
H.7.0	General.....	211
H.7.1	Averaged EVM (FDD)	212
H.7.2	Averaged EVM (TDD).....	212
Annex I (informative):	Change history	214
History	222	

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

iTeh STANDARD PREVIEW
(standards.iteh.ai)
Full standard:
<https://standards.iteh.ai/catalog/standards/sist/08610222-3f10/4972-a469-bd5c3f8b1d09/etsi-ts-138-141-1-v15.5.0-2020-04>