

ETSI TS 138 141-2 V15.5.0 (2020-04)



TECHNICAL SPECIFICATION

**5G;
NR;**

**Base Station (BS) conformance testing
Part 2: Radiated conformance testing
(3GPP TS 38.141-2 version 15.5.0 Release 15)**

STANDARD PREVIEW
https://standards.itec.ai/en/standards/sist/7ad83d09-1a03-4e80-b87-f13ee0064734/3gpp-ts-38-141-2-v15-5-0-2020-04



Reference

RTS/TSGR-0438141-2v15

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	14
1 Scope	15
2 References	15
3 Definitions, symbols and abbreviations	17
3.1 Definitions	17
3.2 Symbols.....	20
3.3 Abbreviations	22
4 General radiated test conditions and declarations	24
4.1 Measurement uncertainties and test requirements	24
4.1.1 General.....	24
4.1.2 Acceptable uncertainty of OTA Test System	26
4.1.2.1 General	26
4.1.2.2 Measurement of transmitter	27
4.1.2.3 Measurement of receiver	30
4.1.2.4 Measurement of performance requirement	31
4.1.3 Interpretation of measurement results	32
4.2 Radiated requirement reference points	33
4.3 Base station classes	34
4.4 Regional requirements.....	34
4.5 BS configurations	35
4.5.1 Transmit configurations	35
4.5.2 Receive configurations	36
4.5.3 Power supply options.....	37
4.5.4 BS with integrated Iuant BS modem	37
4.6 Manufacturer's declarations.....	37
4.7 Test configurations	46
4.7.1 General.....	46
4.7.2 Test signal configurations	46
4.7.2.1 Test signal used to build Test Configurations	46
4.7.2.2 NRTC1: Contiguous spectrum operation	46
4.7.2.2.1 NRTC1 generation.....	46
4.7.2.2.2 NRTC1 power allocation.....	47
4.7.2.3 NRTC2: Contiguous CA occupied bandwidth	47
4.7.2.3.1 NRTC2 generation.....	47
4.7.2.3.2 NRTC2 power allocation.....	47
4.7.2.4 NRTC3: Non-contiguous spectrum operation.....	48
4.7.2.4.1 NRTC3 generation.....	48
4.7.2.4.2 NRTC3 power allocation.....	48
4.7.2.5 NRTC4: Multi-band test configuration for full carrier allocation	48
4.7.2.5.1 NRTC4 generation.....	48
4.7.2.5.2 NRTC4 power allocation.....	49
4.7.2.6 NRTC5: Multi-band test configuration with high PSD per carrier	49
4.7.2.6.1 NRTC5 generation.....	49
4.7.2.6.2 NRTC5 power allocation.....	50
4.8.1 Requirement set applicability	50
4.8.2 Applicability of test configurations for <i>single-band RIB</i>	50
4.8.3 Applicability of test configurations for <i>multi-band RIB</i>	51
4.9 RF channels and test models	52
4.9.1 RF channels	52
4.9.2 Test models	53
4.9.2.1 General	53

4.9.2.2	NR FR2 test models	53
4.9.2.2.1	NR FR2 test model 1.1 (NR-FR2-TM1.1).....	55
4.9.2.2.2	NR FR2 test model 2 (NR-FR2-TM2).....	55
4.9.2.2.3	NR FR2 test model 3.1 (NR-FR2-TM3.1).....	56
4.9.2.3	Data content of physical channels and signals for NR-FR2-TM.....	56
4.9.2.3.1	PDCCH.....	56
4.9.2.3.2	PDSCH	57
4.10	Requirements for contiguous and non-contiguous spectrum.....	58
4.11	Requirements for BS capable of multi-band operation	58
4.12	Co-location requirements	58
4.12.1	General.....	58
4.12.2	Co-location test antenna.....	59
4.12.2.1	General	59
4.12.2.2	Co-location test antenna characteristics	59
4.12.2.3	Co-location test antenna alignment	59
4.13	Format and interpretation of tests.....	60
4.14	Reference coordinate system.....	61
5	Operating bands and channel arrangement.....	63
6	Radiated transmitter characteristics.....	64
6.1	General	64
6.2	Radiated transmit power.....	64
6.2.1	Definition and applicability	64
6.2.2	Minimum requirement	64
6.2.3	Test purpose.....	65
6.2.4	Method of test.....	65
6.2.4.1	Initial conditions	65
6.2.4.2	Procedure	65
6.2.5	Test requirement	66
6.3	OTA base station output power.....	66
6.3.1	Definition and applicability	66
6.3.2	Minimum requirement	66
6.3.3	Test purpose.....	66
6.3.4	Method of test.....	67
6.3.4.1	Initial conditions	67
6.3.4.2	Procedure	67
6.3.5	Test requirement	67
6.3.5.1	BS type 1-O	67
6.3.5.2	BS type 2-O	68
6.4	OTA output power dynamics	68
6.4.1	General.....	68
6.4.2	OTA RE power control dynamic range	68
6.4.2.1	Definition and applicability.....	68
6.4.2.2	Minimum requirement	68
6.4.2.3	Method of test	68
6.4.3	OTA total power dynamic range.....	68
6.4.3.1	Definition and applicability.....	68
6.4.3.2	Minimum requirement	69
6.4.3.3	Test purpose	69
6.4.3.4	Method of test	69
6.4.3.4.1	Initial conditions	69
6.4.3.4.2	Procedure.....	69
6.4.3.5	Test requirement	70
6.4.3.5.1	BS type 1-O.....	70
6.4.3.5.2	BS type 2-O.....	70
6.5	OTA transmit ON/OFF power.....	71
6.5.1	OTA transmitter OFF power.....	71
6.5.1.1	Definition and applicability.....	71
6.5.1.2	Minimum requirement	71
6.5.1.3	Test purpose	71
6.5.1.4	Method of test	71

6.5.1.5	Test requirements	71
6.5.2	OTA transmitter transient period	71
6.5.2.1	Definition and applicability	71
6.5.2.2	Minimum requirement	72
6.5.2.3	Test purpose	72
6.5.2.4	Method of test	72
6.5.2.4.1	Initial conditions	72
6.5.2.4.2	Procedure	73
6.5.2.4.2.1	General procedure	73
6.5.2.4.2.2	BS type 1-O	73
6.5.2.4.2.3	BS type 2-O	73
6.5.2.5	Test requirements	74
6.5.2.5.1	BS type 1-O	74
6.5.2.5.2	BS type 2-O	74
6.6	OTA transmitted signal quality	74
6.6.1	General	74
6.6.2	OTA frequency error	74
6.6.2.1	Definition and applicability	74
6.6.2.2	Minimum Requirement	74
6.6.2.3	Test purpose	74
6.6.2.4	Method of test	74
6.6.2.4.1	Initial conditions	75
6.6.2.5	Test Requirements	75
6.6.3	OTA modulation quality	75
6.6.3.1	Definition and applicability	75
6.6.3.2	Minimum Requirement	75
6.6.3.3	Test purpose	75
6.6.3.4	Method of test	75
6.6.3.4.1	Initial conditions	75
6.6.3.4.2	Procedure	76
6.6.3.5	Test requirements	77
6.6.3.5.1	BS type 1-O	77
6.6.3.5.2	BS type 2-O	78
6.6.4	OTA time alignment error	79
6.6.4.1	Definition and applicability	79
6.6.4.2	Minimum requirement	79
6.6.4.3	Test purpose	79
6.6.4.4	Method of test	79
6.6.4.4.1	Initial conditions	79
6.6.4.4.2	Procedure	80
6.6.4.5	Test Requirement	80
6.6.4.5.1	BS type 1-O	80
6.6.4.5.2	BS type 2-O	81
6.7	OTA unwanted emissions	81
6.7.1	General	81
6.7.2	OTA occupied bandwidth	81
6.7.2.1	Definition and applicability	81
6.7.2.2	Minimum requirement	82
6.7.2.3	Test purpose	82
6.7.2.4	Method of test	82
6.7.2.4.1	Initial conditions	82
6.7.2.4.2	Procedure	82
6.7.2.5	Test requirement	83
6.7.2.5.1	BS type 1-O	83
6.7.2.5.2	BS type 2-O	83
6.7.3	OTA Adjacent Channel Leakage Power Ratio (ACLR)	84
6.7.3.1	Definition and applicability	84
6.7.3.2	Minimum requirement	84
6.7.3.3	Test purpose	84
6.7.3.4	Method of test	84
6.7.3.4.1	Initial conditions	84
6.7.3.4.2	Procedure	84

6.7.3.5	Test requirements	85
6.7.3.5.1	<i>BS type 1-O</i>	85
6.7.3.5.2	<i>BS type 2-O</i>	88
6.7.4	OTA operating band unwanted emissions	91
6.7.4.1	Definition and applicability	91
6.7.4.2	Minimum requirement	91
6.7.4.3	Test purpose	91
6.7.4.4	Method of test	91
6.7.4.4.1	Initial conditions	91
6.7.4.4.2	Procedure	91
6.7.4.5	Test requirements	92
6.7.4.5.1	<i>BS type 1-O</i>	92
6.7.4.5.1.1	Wide Area BS (Category A)	93
6.7.4.5.1.2	Wide Area BS Category B (Option 1)	95
6.7.4.5.1.3	Wide Area BS Category B (Option 2)	97
6.7.4.5.1.4	Medium Range BS (Category A and Category B)	97
6.7.4.5.1.5	Local Area BS (Category A and Category B)	100
6.7.4.5.1.6	Additional requirements	102
6.7.4.5.1.6.1	Limits in FCC Title 47	102
6.7.4.5.1.6.2	Protection of DTT	102
6.7.4.5.2	<i>BS type 2-O</i>	103
6.7.4.5.2.1	General	103
6.7.4.5.2.2	OTA operating band unwanted emission limits (Category A)	103
6.7.4.5.2.3	OTA operating band unwanted emission limits (Category B)	104
6.7.5	OTA transmitter spurious emissions	104
6.7.5.1	General	104
6.7.5.2	General OTA transmitter spurious emissions requirements	105
6.7.5.2.1	Definition and applicability	105
6.7.5.2.2	Minimum requirement	105
6.7.5.2.3	Test purpose	105
6.7.5.2.4	Method of test	105
6.7.5.2.4.1	Initial conditions	105
6.7.5.2.4.2	Procedure	106
6.7.5.2.5	Test requirement	107
6.7.5.2.5.1	Test requirement for <i>BS type 1-O</i>	107
6.7.5.2.5.2	Test requirement for <i>BS type 2-O</i>	107
6.7.5.2.5.2.1	General	107
6.7.5.2.5.2.2	OTA transmitter spurious emissions (Category A)	108
6.7.5.2.5.2.3	OTA transmitter spurious emissions (Category B)	108
6.7.5.3	Protection of the BS receiver of own or different BS	108
6.7.5.3.1	Definition and applicability	108
6.7.5.3.2	Minimum requirements	109
6.7.5.3.3	Test purpose	109
6.7.5.3.4	Method of test	109
6.7.5.3.4.1	Initial conditions	109
6.7.5.3.4.2	Procedure	109
6.7.5.3.5	Test requirements	110
6.7.5.3.5.1	Test requirement for <i>BS type 1-O</i>	110
6.7.5.4	Additional spurious emissions requirements	110
6.7.5.4.1	Definition and applicability	110
6.7.5.4.2	Minimum Requirement	110
6.7.5.4.3	Test purpose	111
6.7.5.4.4	Method of test	111
6.7.5.4.4.1	Initial conditions	111
6.7.5.4.4.2	Procedure	111
6.7.5.4.5	Test requirement	112
6.7.5.4.5.1	Test requirement for <i>BS type 1-O</i>	112
6.7.5.5	Co-location requirements	117
6.7.5.5.1	Definition and applicability	117
6.7.5.5.2	Minimum requirements	117
6.7.5.5.3	Test purpose	117
6.7.5.5.4	Method of test	117

6.7.5.5.4.1	Initial conditions	117
6.7.5.5.4.2	Procedure	118
6.7.5.5.5	Test requirements	118
6.7.5.5.5.1	Test requirement for <i>BS type 1-O</i>	118
6.8	OTA transmitter intermodulation	123
6.8.1	Definition and applicability	123
6.8.2	Minimum requirement	124
6.8.3	Test purpose.....	124
6.8.4	Method of test	124
6.8.4.1	Initial conditions	124
6.8.4.2	Procedure	124
6.8.5	Test requirements.....	126
6.8.5.1	Requirement for <i>BS type 1-O</i>	126
7	Radiated receiver characteristics	127
7.1	General	127
7.2	OTA sensitivity	127
7.2.1	Definition and applicability	127
7.2.2	Minimum requirement	128
7.2.3	Test Purpose.....	128
7.2.4	Method of test	128
7.2.4.1	Initial conditions	128
7.2.4.2	Procedure	129
7.2.5	Test requirements.....	129
7.2.5.1	General	129
7.2.5.2	Test requirements for <i>BS type 1-H</i> and <i>BS type 1-O</i>	129
7.2.5.3	Test requirements for <i>BS type 2-O</i>	130
7.3	OTA reference sensitivity level.....	130
7.3.1	Definition and applicability	130
7.3.2	Minimum requirement	130
7.3.3	Test Purpose.....	130
7.3.4	Method of test	130
7.3.4.1	Initial conditions	130
7.3.4.2	Procedure	131
7.3.5	Test requirements.....	131
7.3.5.1	General	131
7.3.5.2	Test requirements for <i>BS type 1-O</i>	131
7.3.5.3	Test requirements for <i>BS type 2-O</i>	133
7.4	OTA dynamic range	134
7.4.1	Definition and applicability	134
7.4.2	Minimum requirement	134
7.4.3	Test purpose.....	134
7.4.4	Method of test	134
7.4.4.1	Initial conditions	134
7.4.4.2	Procedure	134
7.4.5	Test requirement	135
7.4.5.1	General	135
7.4.5.2	Test requirements for <i>BS type 1-O</i>	135
7.5	OTA in-band selectivity and blocking.....	144
7.5.1	OTA adjacent channel selectivity	144
7.5.1.1	Definition and applicability.....	144
7.5.1.2	Minimum requirement	144
7.5.1.3	Test purpose	144
7.5.1.4	Method of test	144
7.5.1.4.1	Initial conditions	144
7.5.1.4.2	Procedure.....	144
7.5.1.5	Test requirement	145
7.5.1.5.1	General	145
7.5.1.5.2	Test requirements for <i>BS type 1-O</i>	145
7.5.1.5.3	Test requirements for <i>BS type 2-O</i>	146
7.5.2	OTA in-band blocking	147
7.5.2.1	Definition and applicability.....	147

7.5.2.2	Minimum requirement	147
7.5.2.3	Test purpose	147
7.5.2.4	Method of test	147
7.5.2.4.1	Initial conditions	147
7.5.2.4.2	Procedure	148
7.5.2.5	Test requirement	148
7.5.2.5.1	General	148
7.5.2.5.2	Test requirements for <i>BS type 1-O</i>	149
7.5.2.5.3	Test requirements for <i>BS type 2-O</i>	152
7.6	OTA out-of-band blocking	153
7.6.1	Definition and applicability	153
7.6.2	Minimum requirement	153
7.6.3	Test purpose	153
7.6.4	Method of test	153
7.6.4.1	Initial conditions	153
7.6.4.2	Procedure	154
7.6.4.2.1	<i>BS type 1-O</i> procedure for out-of-band blocking	154
7.6.4.2.2	<i>BS type 1-O</i> procedure for co-location blocking	154
7.6.4.2.3	<i>BS type 2-O</i> procedure for out-of-band blocking	155
7.6.5	Test requirements	156
7.6.5.1	Requirement for <i>BS type 1-O</i>	156
7.6.5.1.1	General	156
7.6.5.1.2	Co-location requirement	156
7.6.5.2	Requirement for <i>BS type 2-O</i>	157
7.6.5.2.1	General requirement	157
7.7	OTA receiver spurious emissions	157
7.7.1	Definition and applicability	157
7.7.2	Minimum requirement	158
7.7.3	Test purpose	158
7.7.4	Method of test	158
7.7.4.1	Initial conditions	158
7.7.4.2	Procedure	159
7.7.5	Test requirement	159
7.7.5.1	Test requirement for <i>BS type 1-O</i>	159
7.7.5.2	Test requirement for <i>BS type 2-O</i>	160
7.8	OTA receiver intermodulation	161
7.8.1	Definition and applicability	161
7.8.2	Minimum requirement	161
7.8.3	Test purpose	161
7.8.4	Method of test	161
7.8.4.1	Initial conditions	161
7.8.4.2	Procedure	161
7.8.5	Test requirement	162
7.8.5.1	<i>BS type 1-O</i>	162
7.8.5.2	<i>BS type 2-O</i>	166
7.9	OTA in-channel selectivity	166
7.9.1	Definition and applicability	166
7.9.2	Minimum requirement	166
7.9.3	Test purpose	167
7.9.4	Method of test	167
7.9.4.1	Initial conditions	167
7.9.4.2	Procedure	167
7.9.5	Test requirement	168
7.9.5.1	<i>BS type 1-O</i>	168
7.9.5.2	<i>BS type 2-O</i>	170
8	Radiated performance requirements	171
8.1	General	171
8.1.0	Scope and definitions	171
8.1.1	OTA demodulation branches	171
8.1.2	Applicability rule	172
8.1.2.0	General	172

8.1.2.1	Applicability of PUSCH performance requirements.....	172
8.1.2.1.1	Applicability of requirements for different subcarrier spacings	172
8.1.2.1.2	Applicability of requirements for different channel bandwidths	172
8.1.2.1.3	Applicability of requirements for different configurations.....	172
8.1.2.2	Applicability of PUCCH performance requirements	173
8.1.2.2.1	Applicability of requirements for different formats.....	173
8.1.2.2.2	Applicability of requirements for different subcarrier spacings	173
8.1.2.2.3	Applicability of requirements for different channel bandwidths	173
8.1.2.2.4	Applicability of requirements for different configurations.....	173
8.1.2.2.5	Applicability of requirements for multi-slot PUCCH.....	173
8.1.2.3	Applicability of PRACH performance requirements	173
8.1.2.3.1	Applicability of requirements for different formats.....	173
8.1.2.3.2	Applicability of requirements for different subcarrier spacings	173
8.1.2.3.3	Applicability of requirements for different channel bandwidths	173
8.2	OTA performance requirements for PUSCH	174
8.2.1	Performance requirements for PUSCH with transform precoding disabled	174
8.2.1.1	Definition and applicability.....	174
8.2.1.2	Minimum Requirement	174
8.2.1.3	Test purpose	174
8.2.1.4	Method of test	174
8.2.1.4.1	Initial conditions	174
8.2.1.4.2	Procedure.....	174
8.2.1.5	Test Requirement	176
8.2.1.5.1	Test requirement for <i>BS type 1-O</i>	176
8.2.1.5.2	Test requirement for <i>BS type 2-O</i>	179
8.2.2	Performance requirements for PUSCH with transform precoding enabled	182
8.2.2.1	Definition and applicability.....	182
8.2.2.2	Minimum Requirement	182
8.2.2.3	Test Purpose	182
8.2.2.4	Method of test	182
8.2.2.4.1	Initial Conditions	182
8.2.2.4.2	Procedure.....	182
8.2.2.5	Test Requirement	184
8.2.2.5.1	Test requirement for <i>BS type 1-O</i>	184
8.2.2.5.2	Test requirement for <i>BS type 2-O</i>	184
8.2.3	Performance requirements for UCI multiplexed on PUSCH	185
8.2.3.1	Definition and applicability.....	185
8.2.3.2	Minimum Requirement	185
8.2.3.3	Test purpose	186
8.2.3.4	Method of test	186
8.2.3.4.1	Initial conditions	186
8.2.3.4.2	Procedure.....	186
8.2.3.5	Test Requirement	188
8.2.3.5.1	Test requirement for <i>BS type 1-O</i>	188
8.2.3.5.2	Test requirement for <i>BS type 2-O</i>	189
8.3	OTA performance requirements for PUCCH	190
8.3.1	Performance requirements for PUCCH format 0.....	190
8.3.1.1	Definition and applicability.....	190
8.3.1.2	Minimum Requirement	190
8.3.1.3	Test purpose	191
8.3.1.4	Method of test	191
8.3.1.4.1	Initial conditions	191
8.3.1.4.2	Procedure.....	191
8.3.1.5	Test Requirement	192
8.3.1.5.1	Test requirement for <i>BS type 1-O</i>	192
8.3.1.5.2	Test requirement for <i>BS type 2-O</i>	193
8.3.2	Performance requirements for PUCCH format 1	193
8.3.2.1	NACK to ACK detection	193
8.3.2.1.1	Definition and applicability	193
8.3.2.1.2	Minimum Requirement	193
8.3.2.1.3	Test purpose	193
8.3.2.1.4	Method of test.....	194

8.3.2.1.4.1	Initial Conditions	194
8.3.2.1.4.2	Procedure	194
8.3.2.1.5	Test Requirement.....	195
8.3.2.1.5.1	Test Requirement for <i>BS type 1-O</i>	195
8.3.2.1.5.2	Test Requirement for <i>BS type 2-O</i>	195
8.3.2.2	ACK missed detection.....	196
8.3.2.2.1	Definition and applicability	196
8.3.2.2.2	Minimum Requirement	196
8.3.2.2.3	Test purpose	196
8.3.2.2.4	Method of test.....	196
8.3.2.2.4.1	Initial Conditions	196
8.3.2.2.4.2	Procedure	197
8.3.2.2.5	Test Requirement.....	198
8.3.2.1.5.1	Test Requirement for <i>BS type 1-O</i>	198
8.3.2.2.5.2	Test Requirement for <i>BS type 2-O</i>	199
8.3.3	Performance requirements for PUCCH format 2.....	199
8.3.3.1	ACK missed detection performance requirements	199
8.3.3.1.1	Definition and applicability	199
8.3.3.1.2	Minimum Requirement	199
8.3.3.1.3	Test Purpose	199
8.3.3.1.4	Method of test.....	200
8.3.3.1.4.1	Initial conditions	200
8.3.3.1.4.2	Procedure	200
8.3.3.1.5	Test requirement	201
8.3.3.1.5.2	Requirements for <i>BS type 2-O</i>	202
8.3.3.2	UCI BLER performance requirements.....	202
8.3.3.2.1	Definition and applicability	202
8.3.3.2.2	Minimum Requirement	202
8.3.3.2.3	Test Purpose	202
8.3.3.2.4	Method of test.....	202
8.3.3.2.4.1	Initial conditions	202
8.3.3.2.4.2	Procedure	202
8.3.3.2.5	Test requirement	204
8.3.3.2.5.1	Requirements for <i>BS type 1-O</i>	204
8.3.3.2.5.2	Requirements for <i>BS type 2-O</i>	204
8.3.4	Performance requirements for PUCCH format 3.....	204
8.3.4.1	Definition and applicability.....	204
8.3.4.2	Minimum requirement	205
8.3.4.3	Test purpose	205
8.3.4.4	Method of test	205
8.3.4.4.1	Initial conditions	205
8.3.4.4.2	Procedure.....	205
8.3.4.5	Test requirement	206
8.3.4.5.1	Test requirement for <i>BS type 1-O</i>	206
8.3.4.5.2	Test requirement for <i>BS type 2-O</i>	207
8.3.5	Performance requirements for PUCCH format 4.....	208
8.3.5.1	Definition and applicability.....	208
8.3.5.2	Minimum requirement	208
8.3.5.3	Test purpose	208
8.3.5.4	Method of test	208
8.3.5.4.1	Initial conditions	208
8.3.5.4.2	Procedure.....	208
8.3.5.5	Test requirement	210
8.3.5.5.1	Test requirement for <i>BS type 1-O</i>	210
8.3.5.5.2	Test requirement for <i>BS type 2-O</i>	210
8.3.6	Performance requirements for multi-slot PUCCH format	211
8.3.6.1	Performance requirements for multi-slot PUCCH format 1.....	211
8.3.6.1.1	NACK to ACK detection.....	211
8.3.6.1.1.1	Definition and applicability	211
8.3.6.1.1.3	Test purpose.....	211
8.3.6.1.1.4	Method of test	211
8.3.6.1.1.4.1	Initial conditions.....	211

8.3.6.1.1.4.2	Procedure.....	211
8.3.6.1.1.5	Test Requirement.....	212
8.3.6.1.1.5.1	Test Requirement for <i>BS type 1-O</i>	212
8.3.6.1.1.5.2	Void.....	213
8.3.6.1.2	ACK missed detection.....	213
8.3.6.1.2.1	Definition and applicability.....	213
8.3.6.1.2.2	Minimum Requirement.....	213
8.3.6.1.2.3	Test purpose.....	213
8.3.6.1.2.4	Method of test.....	213
8.3.6.1.2.4.1	Initial Conditions.....	213
8.3.6.1.2.4.2	Procedure.....	213
8.3.6.1.2.5	Test Requirement.....	214
8.3.6.1.2.5.1	Test Requirement for <i>BS type 1-O</i>	214
8.3.6.1.2.5.2	Void.....	215
8.4	OTA performance requirements for PRACH.....	215
8.4.1	PRACH false alarm probability and missed detection.....	215
8.4.1.1	Definition and applicability.....	215
8.4.1.2	Minimum requirement.....	215
8.4.1.3	Test purpose.....	215
8.4.1.4	Method of test.....	216
8.4.1.4.1	Initial conditions.....	216
8.4.1.4.2	Procedure.....	216
8.4.1.5	Test requirement.....	217
8.4.1.5.1	Test requirement for <i>BS type 1-O</i>	217
8.4.1.5.2	Test requirement for <i>BS type 2-O</i>	218
Annex A (normative): Reference measurement channels.....		220
A.1	Fixed Reference Channels for OTA sensitivity, OTA reference sensitivity level, OTA ACS, OTA in-band blocking, OTA out-of-band blocking, OTA receiver intermodulation and OTA in-channel selectivity (QPSK, R=1/3).....	220
A.2	Fixed Reference Channels for OTA dynamic range (16QAM, R=2/3).....	221
A.3	Fixed Reference Channels for performance requirements (QPSK, R=193/1024).....	221
A.4	Fixed Reference Channels for performance requirements (16QAM, R=658/1024).....	226
A.5	Fixed Reference Channels for performance requirements (64QAM, R=567/1024).....	229
A.6	PRACH Test preambles.....	231
Annex B (normative): Environmental requirements for the BS equipment.....		232
B.1	General.....	232
B.2	Normal test environment.....	232
B.3	Extreme test environment.....	232
B.3.1	Extreme temperature.....	232
B.4	Vibration.....	233
B.5	Power supply.....	233
B.6	Measurement of test environments.....	233
B.7	OTA extreme test methods.....	234
B.7.1	Direct far field method.....	234
B.7.2	Relative method.....	234
Annex C (informative): Test tolerances and derivation of test requirements.....		236
C.1	Measurement of transmitter.....	237
C.2	Measurement of receiver.....	240
C.3	Measurement of performance requirements.....	242

Annex D (normative):	Calibration.....	243
Annex E (informative):	OTA measurement system set-up.....	244
E.1	Transmitter	244
E.1.1	Radiated transmit power, OTA output power dynamics, OTA transmitted signal quality, OTA occupied bandwidth, and OTA transmit ON/OFF power (<i>BS type 2-O</i>)	244
E.1.2	OTA base station output power, OTA ACLR, OTA operating band unwanted emissions	245
E.1.3	OTA spurious emissions	245
E.1.4	OTA co-location emissions, OTA transmit ON/OFF power (<i>BS type 1-O</i>)	246
E.1.5	OTA transmitter intermodulation	247
E.2	Receiver.....	248
E.2.1	OTA sensitivity and OTA reference sensitivity level.....	248
E.2.2	OTA dynamic range	248
E.2.3	OTA adjacent channel selectivity, general OTA blocking, and OTA narrowband blocking	249
E.2.4	OTA blocking.....	250
E.2.4.1	General OTA out-of-band blocking.....	250
E.2.4.2	OTA co-location blocking	251
E.2.5	OTA receiver spurious emissions.....	251
E.2.6	OTA receiver intermodulation	252
E.2.7	OTA in-channel selectivity.....	252
E.3	Performance requirements.....	253
Annex F (normative):	Void	254
Annex G (informative):	Transmitter spatial emissions declaration.....	255
G.1	General	255
G.2	Declarations.....	255
Annex H (normative):	Characteristics of the interfering signals.....	257
Annex I (normative):	TRP measurement procedures	258
I.1	General	258
I.2	Spherical equal angle grid	258
I.2.1	General	258
I.2.2	Reference angular step criteria.....	258
I.3	Spherical equal area grid	260
I.4	Spherical Fibonacci grid.....	261
I.5	Orthogonal cut grid	261
I.5.1	General	261
I.5.2	Operating band unwanted emissions	262
I.5.3	Spurious unwanted emissions.....	262
I.6	Wave vector space grid	263
I.7	Void.....	263
I.8	Void.....	263
I.9	Full sphere with sparse sampling	263
I.10	Beam-based directions	264
I.11	Peak method	264
I.12	Equal sector with peak average	264
I.13	Pre-scan	265
Annex J (normative):	Propagation conditions.....	266